

UNCLASSIFIED

| |
|--|
| |
| |
| |
| AD NUMBER |
| AD160636 |
| NEW LIMITATION CHANGE |
| TO Approved for public release, distribution unlimited |
| FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; JUL 1958. Other requests shall be referred to Picatinny Arsenal, Dover, NJ. |
| AUTHORITY |
| PA ltr, 6 Feb 1969 |

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD 160636

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA

Best Available Copy



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

UNITED STATES ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

Mr. Heznedari/mr./3757

IN REPLY
REFER TO:
SMUPA-VA6

7 July 1965

SUBJECT: Request for Report(s)

TO: Defense Documentation Center
Cameron Station
Alexandria, Virginia 22314
Attn: Mr. R. Zimmer

REFERENCE: (copy destroyed) Phone conversation with Mr. H. Voos and Mr. P. Zimmer,
30 June 1965.

In response to referenced correspondence:

___ Not yet published.

___ Available to government agencies and their contractors from:

Defense Documentation Center
Cameron Station
Alexandria, Virginia 22314

AD No. _____

___ Available to the public from:

U. S. Department of Commerce
Clearinghouse for Federal Scientific &
Technical Information
Sills Building
5285 Port Royal Road
Springfield, Virginia 22151

AD No. _____
PB No. _____
No. _____

___ Requested item(s) available at this Arsenal. However, it is required that your request be directed through your cognizant military contracting office, citing the contract under which the item(s) will be used, and with certification of "need-to-know".

XXX Other: Inclosed Technical Report 2510 is forwarded for your files.
The AD number is 160 636.

To be refilled
FOR THE COMMANDER:

1 Incl
1. PATR 2510, cy 20

Michael A Costello
MICHAEL A. COSTELLO
Chief, Technical Information Branch



PICATINNY ARSENAL
TECHNICAL REPORT NO. 2510

DICTIONARY OF EXPLOSIVES, AMMUNITION AND WEAPONS

(GERMAN SECTION)

BASIL T. FEDOROFF

HENRY A. AARONSON

GEORGE D. CLIFT

EARL F. REESE

DOVER, NEW JERSEY

1958

BEST AVAILABLE COPY



TABLE OF CONTENTS

| | PAGES |
|---|-----------|
| Foreword | I - IV |
| List of German Explosives, Ammunition and Weapons | 1 - 264 |
| Vocabulary of German Ordnance, etc. | 265 - 308 |
| List of German Abbreviations of Ordnance and Related Terms | 309 - 345 |

**GERMAN EXPLOSIVES, PROPELLANTS, AMMUNITION
AND RELATED ITEMS**

Foreword

In both WWI and WWII the Germans suffered great shortages of TNT, NG, etc. and had to resort to substitute explosives (called Ersatzsprengstoffe) which in many cases were inferior and more expensive than those used by the Allies. This same may be said about the propellants.

The development of German military explosives and propellants may be subdivided into the following:

A. Period Before WWI. Black powder was used as a propellant and as an explosive up to the eighties when it was replaced for a short period by brown powder and finally in the nineties by smokeless propellants invented by Duttchenhofer. A single-base tubular propellant was adopted in 1897, under the name of R1'97 (Röhrenpulver 1897) and a double-base tubular propellant (Nitroglycerinpulver) called R1'07 was adopted in 1907. In addition to these the Germans made a flake propellant (Blattchenpulver) and a disk or cube propellant (Wurfelpulver). As a filler for projectiles the black powder was replaced in 1888 for a short period by picric acid (P.A.) and then in 1902 by TNT.

B. Period of WWI. Due to the shortage of NG the Germans were forced either to use single-base propellants or to substitute the NG in double-base propellants by some other HE, such as TNT or DNT. During the latter part of WWI, when a shortage of cotton developed due to the Allied blockade, the Germans resorted to the use of wood pulp in the form of Crepe paper for nitration to NG, and also to the use of compositions not containing any NG or NG (See Ammonpulver).

As high-explosives for filling projectiles the Germans used in addition to TNT, DNB, TNANs and mixtures of these with Am nitrate. In the later part of the war, when these aromatic nitrocompounds became scarce they began using HNDPhA, TNN, HNDPh, TNN, HNDPh sulfide and their mixtures with Am nitrate, Pb nitrate and K chlorate. Commercial blasting explosives, such as Donarit and Westphalit, and other more sensitive explosives were used for projectiles which were subjected to little or no setback, such as trench mortar shells, grenades and bombs. The Germans also started to incorporate Al powder in underwater explosives. All of these substitutes were fairly powerful and superior to the mixtures which they were forced to use during the later part of WWI.

C. Period Before WWII. Beginning in the middle 1900's the Germans foresaw a war and began the development of explosives which could be used to replace those prepared by the nitration of aromatic hydrocarbons (derived from coal tar), of which it was patent there would be a shortage. The most important of these explosives were Hexogen (Cyclonite or RDX) and Pentrit (Pentaerythritoltetranitrate or PETN). Both of these explosives were derived from aliphatic compounds of which no shortage was expected during a war. In addition, these explosives were much more powerful than TNT, P.A., or even tetryl, but they were too sensitive to be used alone as bursting charges in shells. This difficulty was overcome, however, by coating the particles of these explosive with about 10% of Montan wax applied in the molten condition. Such explosive mixtures could be safely pre-loaded into projectiles, such as 20mm to 88mm shells or loaded into boosters for various shell. These mixtures could not be cast because the m.p.'s of RDX and PETN are too

high to permit them to be melted with low pressure steam. When it was desired to load shells by casting, the Germans mixed RDX or PETN with about equal parts of low-melting explosives such as DNB or TNT.

In addition to these superior explosives the Germans began the development of some rather inferior explosives before WWII. These were called Ersatzsprengstoffe (qv) (Substitute explosives).

As to propellants, about 5 years before WWII, the Germans started to develop double-base propellants which contained DEGDN (in lieu of NG) with or without NGu. These were superior to NG powders because being "cooler" they caused much less erosion of the gun barrels. The development of these propellants was done under the direction of General Uto Gallwitz (See Propellants).

D. Period of WWII. At the beginning of the war the Germans did not experience a shortage of aromatic nitrocompounds and were able to use the following explosives for loading shells: TNT, DNB, P.A., tetryl, HNDPhA, some alone and others in admixtures with other explosives. For underwater explosives, the Germans incorporated also 15% of powdered Al in the high explosives, as had already been done by them in WWI (See also under Aluminized Explosives, under A).

Of the explosives mentioned above, all except DNB may be considered a good military explosives. DNB is not as good because it is less powerful and more toxic than TNT. It was used, however, to stretch the supply of TNT in amatol and ammonal-types of explosive mixtures. The comparatively low m.p. of DNB (ca 90°) permitted its use with loading mixtures containing Am nitrate, Al, etc. Such mixtures did not exude even at tropical temperatures.

As mentioned above, the Germans before WWII, developed two of the most powerful explosives, RDX and PETN. When these explosives became available on an industrial scale they started to replace the aromatic nitrocompounds as bursting charges for various projectiles, as boosters and as base charges for detonators. When Al powder was incorporated in mixtures of RDX and PETN with other substances the resulting explosives were the most powerful and brisant underwater explosives. It was by the use of these that the Germans sank many American and British ships.

The enormous demand for explosives and the shortage of raw materials created a situation, about 1943, which made it necessary to use substitutes inferior to TNT, thus lowering the efficiency of their ammunition. These mixtures are listed, and some of them described, under Ersatzsprengstoffe (qv).

The Germans used single-base propellants in small arms and in some smaller guns, while double-base propellants in which part or all the NG was replaced by DEGDN (or sometimes TEGDN), with or without NGu, were used in 37mm or larger caliber cannon. A propellant of tubular granulation was used for guns, while either flake or disk type was used in howitzers (See Propellants).

Following are some figures for the monthly production, in metric tons of the principal high explosives for the years 1943 and 1944.

| Explosive | As of June 1943 (Produced) | As of June 1944 (Produced) |
|-----------|----------------------------|----------------------------|
| TN | 2,000 | 21,000 |
| P.A. | 1,000 | 1,000 |
| DNB | 100 | 30 |
| Tetryl | 1,500 | 950 |
| HNDPhA | 100 | 1,000 |
| RDX | 1,000 | 1,400 |
| PETN | | |

References:

1) R. Escaler, Nitrogluzerin (1908)
 2) R. Escaler, Ammonsäure (1909)
 3) R. Escaler, Chloratsprengstoffe (1910)
 4) R. Escaler, Schwarzpulver und Sprengstoffe (1914)
 5) R. Escaler, Nitrosprengstoffe (1915)
 6) R. Escaler & A. Stettbacher, Nitrosprengstoffe (1917)
 6a) E. B. Barnett, Explosives, Van Nostrand, Braunschweig (1926)
 6b) H. Kast, Spreng- und Zündstoffe, Vieweg, Braunschweig (1926)
 7) A. Marshall, Explosives, Churchill, London, v1 (1917), v2 (1917), v3 (1932)
 8) K. J. Czerny, Lehrbuch der Ballistik, Springer, Berlin (1925), v2 (1926), v3 (1927)
 9) H. Brunschwig, Das rauchlose Pulver, W. de Gruyter, Dresden (1924)
 10) P. Naoum, Schiess- und Sprengstoffe, T. Steinkopff, Dresden (1923)
 11) P. Naoum, Nitroglycerin, Williams & Wilkins, Baltimore (1923)
 12) F. Ullmann Enzyklopädie der technischen Chemie, & Schwarzenberg, Berlin, v4 (1929)
 13) A. Stettbacher, Die Schiess- und Sprengstoffe, J.A.B. Barth, Leipzig (1933)
 14) C. Beyling & K. Drekopf, Sprengstoffe und Zündmittel, Springer, Berlin (1936)
 15) R. Feuchtinger, Praxis der Sprengtechnik, Wien und Leipzig (1937)
 16) T. L. Davis, The Chemistry of Powder and Explosives, J. Wiley, N Y (1943)
 17) A. Stettbacher, Protar 9, 33-45 (1945)
 18) J. J. Phillips, Picatinny Arsenal Tech Repts Nos 1282 (1944) and 1456 (1944)
 19) Anon, Collective Data on Foreign Explosives, PB Rept No 11 544 (1944)
 20) Anon, Physical and Chemical Investigations of T-Stoff Solution, Rept No 597 of the IG Farbenindustrie at Oppau, August 1944. (U.S. Office of Technical Services)
 19a) H. Kast-L. Metz, Chemische Untersuchung der Spreng- und Zündstoffe, Vieweg, Braunschweig (1944)
 20) L. Nutting and W. Schaurr, Hexogen (Germany), PB Rept No 16,665 (1945)
 21) L. Nutting, Nitrocellulose Manufacture at the Krümmel Plant of Dynamit A-G, PB Rept No 16,666 (1945)
 22) D. D. Steer and A. A. Swanson, Hexogen Manufacture at Fabrik Bobinzen, PB Rept No 4272 (1945)
 23) Nav Ord Rept No 43-45, German Powder Development from 1918 to 1942, PB Rept No 47,059 (1945) (Translation under the direction of Linus Pauling, of the book by U. Gallwitz, "Die Geschützladung", which means "Propelling Charge for Guns", Berlin (1944)
 24) C. H. Brooks et al, Hexan-trodiphenylamine Manufacture

Germany, PB Rept No 38,154 (1945)
 25) C. H. Brooks et al, US Naval Technical Mission in Europe, PB Rept No 39,480 (1945). (Schmid-Meissner Continuous Nitrators for Liquid Explosives Manufacture)
 26) A.N. Donin & J. J. Donovan, Captured Enemy Propellants. (SR 1, Div 3, Section II, Final Report Series P, No 10.2 (1945))
 27) A. Swanson, Manufacture of Phlegmatized PETN at Woltershausen, Germany, PB Rept No 320 (1945)
 28) O. W. Stickland et al, General Summary of Explosive Plants, PB Rept No 925 (1945)
 29) L. Nutting, Development and Manufacture of Hexogen in Germany, PB Rept No 16,669 (1945)
 30) O. W. Stickland et al, Survey of German Practice in Filling H.C., PB Rept No 1820 (1945)
 31) L. Sheldon, Propellants (Germany), PB Rept No 12,662 (1945)
 32) W. R. Tomlinson, Jr, Picatinny Arsenal Tech Rept No 1555 (1945)
 33) Anon, Aberdeen Proving Ground, Allied and Enemy Explosives, Aberdeen, Md (1946)
 34) G. C. Harp, Army Ordn 30, 155, 218-19 (1946)
 35) G. Kömer, Reports on Explosives (Germany), PBL Rept No 85,170 (1945)
 36) R. Ashcross et al, Investigation of German Commercial Explosives Industry, BIOS Final Rept 833, Item No 2, H.M.S.O., London. (1946) [PB Rept No 63,877 (1946)]
 37) R. A. Coole, Chemical Industries 58, 645-49, 759 (1946) (Axis Manufacture of Explosives)
 38) Anon, Manufacture of German Detonators and Detonating Compositions, PB Rept No 95,613 (1947) (Landsdowne House, Berkeley Square, W.1, London)
 39) L. E. Simon, German Research in World War II, J. Wiley, N Y (1947)
 40) H. Walter & B. Valter, German Development in High Explosives, FIAT Final Rept No 1035 (1947) [PB Rept No 78,271 (1947)]
 41) A. Ducrocq, Les Armes Secrètes Allemandes, Berger-Levrault, Paris (1947)
 42) A. Stettbacher, Spreng- und Schiessstoffe, Rascher Verlag, Zürich (1948)
 43) L. Médard, Mem Art: Fr 22, 595-611 (1943) (Velocities of Detonation and Trauzl Test Values for Explosives Containing Al)
 44) F. Ross, Jr, Guided Missiles, Rockets and Torpedoes, Lothrop, Lee, Shepard Co., N Y (1951), pp 14-66
 45) K. W. Gatland, Development of Guided Missiles, "Flight" Publication, London (1952)
 46) F. Weichelt, Handbuch der gewerblichen Sprengtechnik, C. Marhold, Halle/Saale (1955)
 47) Anon, German Explosive Ordnance, Department of the Army Technical Manual, TM 9-190-2 and TM 9-1905-3, Govt Printing Office, Washington, D.C. (1953)
 48) Journals a) Zeitschrift für das gesamte Schiess- und Sprengstoffwesen (abbreviated in this book as SS). b) Cellulosechemie, c) Nitrocellulose d) Protar (Switzerland), e) Sprengtechnik and f) Explosivstoffe
 49) Picatinny Arsenal Technical Reports by A. B. Schilling and others are listed under Ammunition
 50) BIOS (British Intelligence Objectives Sub-Committee) Final Reports (Numbers) 593, 644, 668, 683, 709, 716, 833, 889, 900, 1200, 1201, 1202, 1203, 1442, 1487, 1623, 1631, 1633, 1636, 1639, 1640, 1641, 1642, 1643, 1682, 1720, and 1842
 51) BIOS Miscellaneous Reports (Numbers) 2 and 24
 52) CIOS (Combined Intelligence Objectives Sub-Committee) Reports (Item Numbers) 21-3, 22-4, 22-6, 22-9, 22-10, 23-15, 24-3, 24-4, 24-10, 24-12, 24-21, 24-22, 25-7, 25-14, 25-16, 25-17, 25-20, 25-22, 25-32, 25-33, 25-34, 25-38, 25-39, 25-44, 25-52, 26-11, 26-12, 26-32, 26-34, 26-51, 26-68,

26-9, 26-10, 26-11, 26-12, 26-13, 26-14, 26-80, 27-13, 27-30, 27-38, 27-42, 27-71, 27-85, 27-100, 28-3, 28-24, 28-31, 28-39, 28-41, 28-43, 28-47, 28-51, 28-56, 28-61, 28-67, 28-69, 28-73, 28-60, 29-10, 29-12, 29-14, 29-17, 29-18, 29-20, 29-23, 29-24, 29-26, 29-28, 29-30, 29-39, 29-44, 29-45, 29-57, 29-61, 30-8, 30-55, 30-71, 30-84, 30-93, 30-115, 31-3, 31-9, 31-12, 31-13, 31-15, 31-20, 31-40, 31-40, 31-48, 31-53, 31-54, 31-55, 31-56, 31-57, 31-68, 31-77, 31-73, 32-8, 32-13, 32-27, 32-33, 32-35, 32-38, 32-61, 32-64, 32-66, 32-79, 32-108, 32-109, 32-114, 33-2, 33-7, 33-10, 33-11, 33-20, 33-41, 33-43, 33-44 and 33-60

53) Anon, Peere, Feuerwerkei. Geschoszzünder, Reichsdruckerei, Berlin (1938)

54) Krupp Wörterbuch Deutsch-Französisch-Englisch, I. Teil: Feld-, Gebirgs- und Flugabwehrgeschütz, Essen (1938)

55) Ditto, II Teil: Eisenbahnartillerie, Maschinenwaffe, Panzerkampfwagen, Ballistik, Sondergeräte, Essen (1942)

56) Anon, Geräteleiste vom 1.7.43, Reichsdruckerei, Berlin (1943)

57) Anon, Deutsche Abwurfmunition, Reichsdruckerei, Berlin (1943)

58) Anon, Illustrated Record of German Army Equipment 1939-1945, Lithographed book in 5 volumes issued by the British War Office, London (1947-1948)

Note: This book, being classified could not be used in compilation of this dictionary

59) G.M.Chinn, The Machine Gun, US Navy, Bureau of Ordnance, Washington, D.C., v 1 (1952) (Unclassified), v 3 (1953) (Confidential)

60) W.Domberger, V-2, Viking Press, N.Y. (1954)

61) W.H.B.Smith, Small Arms of the World, Military Service Publishing Co, Harrisburg, Penna (1955)

62) A.S.Locke, Guidance, Van Nostrand, N.Y. (1955) (V. 2 of the book "Principles of Guided Missiles", edited by Grayson Merrill) (See also under Warplans, Weapons and other items)

(c) Private communications from:

- a) Dr L. R. Littleton, Washington D C
- b) Dr A. Stettbacher, Zürich, Switzerland
- c) Dr M. M. Kostevitch, Buenos Aires, Argentina
- d) Wm. H. Rinckenbach, Allentown, Pennsylvania
- e) G. B. Jarratt and K. F. Kempf, Museum of Aberdeen Proving Ground, Maryland

Some information and technical assistance was obtained from the following personnel of Picatinny Arsenal, Dover New Jersey: R.Frye, C.G.Dunkle, D.D.Sager, L.H.Eriksen, J.B.Capeil, A.B.Schilling, H.H.Bullock, H.A.Fisch, M.Reznick, G.H.Rogers and Dr L.T.Smith.

Abbreviations for Ordnance Terms

American and British abbreviations are given under individual items, whereas German abbreviations are assembled in a separate section at the end of this dictionary.

Acknowledgements:

The authors wish to make grateful acknowledgement for the generous assistance given by a number of people at Picatinny Arsenal, Dover, New Jersey, and Aberdeen Proving Ground, Maryland. Special thanks are due to the Museum personnel of these two facilities and to members of the following groups at Picatinny Arsenal: Foreign Ammunition Unit, Chemical Research Section, Technical Publications Section, Technical Information Section, Printing Control Office Print Shop, Photographic Unit and Stenographic Unit.

The names of persons who helped materially by direct technical assistance, and those who by administrative assistance made it possible to complete the work will be listed when the "General Section" is published. The names of individual contributors to this "German Section" are noted in the references.

The authors also wish to acknowledge their appreciation to Dr Hans Walter, now at Picatinny Arsenal and with the German Wehrmacht during WW II, for reviewing the manuscript the furnishing some last minute additional information.

Due to the shortage of funds for this dictionary, every effort was made to keep the typing and printing costs as low as possible. For this reason the lower cost varotyping (outside contract) was used instead of the better but more expensive linotyping.

Abbreviations Used in References:

| | |
|--------------|--|
| A.E.F. | Allied Expeditionary Force |
| Anon | Anonymous |
| Barnett | Barnett Explosives, Van Nostrand, N.Y. (1919) |
| BIOS | British Intelligence Objectives Sub-Committee |
| Br | British |
| CIOS | Combined Intelligence Objectives Sub-committee |
| Colver | Colver, High Explosives, Van Nostrand, N.Y. (1918) |
| Davis | Davis Chemistry of Powder and Explosives, Wiley, N.Y. (1943) |
| D.C. | District of Columbia |
| DRP | Deutsches Reichs Patent (German Patent) |
| FIAT | Field Intelligence Agency, Technical |
| FM | Field Manual |
| Ger | German |
| Govt | Government |
| Gr Br | Great Britain |
| HMSO | His Majesty's Stationary Office |
| Marshall | Marshall Explosives, Churchill, London, v 1 & 2 (1917), v 3 (1932) |
| Md | Maryland |
| Mém Artil Fr | Mémorial de l'Artillerie Française |
| Mém poud | Mémorial des poudres |
| Nav Ord | Naval Ordnance |
| NDRC | National Defense Research Council |
| N.J. | New Jersey |
| N.Y. | New York |
| OSRD | Office of Scientific Research and Development |
| Pa | Pennsylvania |
| Pat or P | Patent |
| PB | Publication Board (of the U.S. Office of Technical Services) |
| Pic Arsn | Picatinny Arsenal, Dover, N.J. |
| Rept | Report |
| Sch | Zeitschrift für das gesamte Schiess- und Sprengstoffwesen |
| TM | Technical Manual |
| u | und (Ger for "and") |
| USP | United States Patent |
| v | volume |
| von | von |

Remarks

This compilation has been made with the object of providing a ready reference to the subject matter covered by means of an alphabetical arrangement. In general, only sufficient information is furnished for understanding of the principles, meaning of terms, process, mechanical layout etc. Numerous references to original sources are provided for those seeking more detailed information. Classified information has been carefully excluded. However, a few classified references have been given to permit further study by those with authorized access to such sources. No attempt has been made to include all data and information available to the Ordnance Corps. It should be noted that the use of the period with abbreviations, in the tables and at the end of sentences was, in general, omitted where this could be done without causing any difficulty to the reader. However, a period was used at the end of each dictionary item to indicate the conclusion of the item.

Some last minute changes and insertions were made by Dr Fedoroff and not edited. For faulty punctuation, poor English or irregular arrangements, he assumes the responsibility and hopes that the sense of the text is clear everywhere.

It is hoped that the General and Analytical sections of this project, "A Dictionary of Explosives, Ammunition and Weapons", will be linotyped and present a better appearance than was possible to date.

NOTE

The General and Analytical Sections referred to in the body of this Section have not yet been published. It is expected that preparation of the General and Analytical Sections will be started early in 1958 with a publication target date sometime in 1960. Data under each letter of the alphabet will constitute a separate report.

The General Section will cover American and British explosives, ordnance terms and a short resume of American and British ammunition and weapons.

The Foreign Section will include explosives, ammunition and weapons of countries other than US and British, i e, German (this section), French, Italian, Japanese, Belgian, Czech, Spanish, Swedish, Swiss, and Russian. Only the Russian Section has been published to date as Picatinny Arsenal Technical Report No. 2145, February 1955. The Russian Section is classified Confidential.

LIST OF GERMAN EXPLOSIVES, AMMUNITION
AND RELATED ITEMS

"121" (Filling Composition) and Filling Composition 121.

"A" Rockets - The Germans started to experiment with military rockets. The first model was the A-1 which weighed about 330 lbs. and was 57" long and 4 1/2 in diameter; it was unsuccessful. The next rocket, the A-2, which appeared in 1931, was an improved A-1 and when fired it reached an altitude of 6000 feet. In 1932, at Peenemünde, the A-3 was developed. This was the predecessor of the A-5, developed in December 1932 and now commonly known as the V-2. The A-3 rocket weighed 1,550 lbs. and was 25 ft long and 2 1/2 ft in diameter. The A-4 rocket is briefly described under V-2. The next A rockets that were developed at Peenemünde: the A-5, A-6, A-7, A-8, A-9 and A-10, were purely experimental. Among these, the A-9 and A-10 were intended for bombardment of the U.S.A. The A-9 was intended to be carried aloft by the A-1 during the first phase of the trans-Atlantic trip.

Reference: E. Ross, Jr., Guided Missiles, Rockets and Torpedoes, Lothrop & Co., N.Y. (1951), pp 22-34.

A-2 Same as V-2.

A-4 (Rocket). Same as V-2 (Rocket).

See also W. Dornberger, V-2, Viking, N.Y. (1954).

"A6" Fuseheads were low tension fuseheads developed at Troisdorf Fabrik as substitutes for the "G 3" fuseheads after it became difficult to obtain cerium - magnesium alloy (called Mischmetall), one of the essential ingredients of G 3.

The A6 fuseheads were made by dipping the tip of a bridge wire successively into the following compositions:

- First dip composition consisted of dry Pb picrate 90g and silicon (particle size 20 to 40 microns) 10g, suspended in about 75 ml of a 2% soln of NC in amyl or butyl acetate. After the coating was dry, the bead on the bridge wire was dipped into the
- Second dip composition which consisted of dry Pb picrate 50g, Pb chromate 35g and silicon (size 20 to 40 microns) 15g, suspended in about 75 ml of 3% soln of NC in amyl, or butyl acetate. The dried bead was dipped into the
- Third dip composition which was a lacquer consisting of a 15% soln of NC in 75/25 - butyl acetate/alcohol, to which was added 20% Sipalin AOM (methyl-cyclohexyl ester of adipic acid) calculated on the dry weight of the NC. Then the dried bead was dipped into the
- Fourth dip composition which consisted of NC lacquer as in (c) to which was added 0.8g of Sudan Brown (0.8g per 10 l of lacquer).

Further operations are the same as described under Fusehead Manufacture.

Reference: R. Ashcroft et al, B.I.O.S. Final Rept No 833, Item No 2 (1946), p A-3/35.

A-9/A-10. Long range guided missile designed to have a range of 5,000 km is briefly described in TM 9-1985-2 (1953), p 233.

Abbreviations for Ordnance Terms. See Ordnance Terms and Abbreviations in this section.

Abfallsäure or Abgangssäure. See Waste (or Spent) Acids.

Azonachit 2. Same as Filler No 57.

Absolute Method of Measurement Based on Impulse (Absolut Messverfahren auf Grund des Kraftstoßes). A. Schmidt devel-

oped a method which permitted calculation of the mechanical work produced by the detonation of an explosive. It is described briefly by A. Stettbacher, Spreng- und Schießstoffe, Zurich (1948), p 110.

Acetylen (Acetylene). See general section and the following references:

- 1) W. Reppel, Advances in Acetylene Chemistry, PB Rept 1112 (about 1946).
- 2) W. Reppel, Syntheses of Intermediates for Polyamides on Acetylene Basis, I I Rept 25,553 (about 1946).

Active Sheath (Active Mantelpatrone) A type of sheath containing NG or NGc (nitroglycol) together with inert ingredients was used by the Germans for some permissible explosives, such as Wetter-Wasapit, etc. One of the earlier active sheaths consisted of NG 15, rock salt 35 and Na bicarbonate 50% but this was later changed to NG (with or without nitroglycol) 12, rock salt 35 and Na bicarbonate 53%. The composition of some other active sheaths were:

| Sheath | NG | NGc | NaCl | Na bicarbonate | Kieselguhr |
|----------------|------|-----|------|----------------|------------|
| M ₁ | 10,0 | - | 35,0 | 55,0 | - |
| M ₃ | 12,0 | - | 68,0 | 20,0 | - |
| M ₄ | 11,0 | 1,0 | 87,0 | - | 1,0 |
| M ₅ | 10,6 | - | 88,0 | - | 2,0 |

The sheathing operation was carried out automatically at the Sythen plant of W.A.S.A.G. on a modified Niepmann cartridge machine, permitting cartridges weighing 70 grams to be sheathed with 55 grams of active sheathing material. Note: According to Stettbacher (Ref 3) a sheath (Mantelpatrone) 25 mm in diameter and 3.5 mm thick, consisting of Na bicarbonate 82 - 85 with NG 18 - 15%, reduces the temperature of the gases of detonation from 2000° (for an un-sheathed explosive) to 400° C.

Note: According to T. Urbanski, Przemysl Chemiczny 4, 487, (1948), the active layer (sheath) was made in the form of a tube slightly larger than the cartridge of the regular charge. The cartridge was then inserted into the tube. When the cartridge was exploded, the combustible protective layer (sheath) was dispersed and vaporized, thus forming a "cloud of salt" which prevented the ignition of fireclamp or coal dust which might be caused by the charge alone.


(See also "Sheathed Explosives" in the general section).

References:

- 1) O. W. Stickland, PB Rept No 925 (1945)
- 2) R. Ashcroft, PB Rept No 61,677 (1945), p A-1 8 and A-1/11
- 3) A. Stettbacher, Spreng- und Schießstoffe, Zurich (1948), p 92.

Aerial Burst Fuzes are devices designed to function a bomb while still in flight. Following German fuzes are briefly described in TM 9-1985-2 (1953), pp 132, 168, 171 174-8:

- 1) (41) Mechanical Clockwork Fuze was used in St. 2A Butterfl, bomb (pp 132-3)
- 2) (29) Mechanical Aerial Burst Fuze, used in the LC 10f single unit parachute flare, consisted of a bakelite housing containing a closing cap, withdrawal lug, safety spring, striker pellet guide, striker pellet, striker letent pin, firing spring, two ball detents, and a striker return spring. The withdrawal lug and the closing cap were retained by a cord which was attached to the flare parachute. As the flare descended the safety spring was extended until it was tensioned sufficiently to withdraw the striker-detent pin. The ball detents were then free to move inward, and the striker pellet was forced by the firing spring to carry the striker into the percussion cap. At the end of its travel, the striker pellet compressed the striker return spring. The flash from the cap ignited the delay element and, after the delay, the detonator initiated the main charge of the bomb (pp 168-9)




3) Pyrotechnic Aerial Burst Fuzes (49)AII and (49)BI were used in some rocket bombs, such as P.C. 500RS and P.C. 1000RS (p 169)

4) (59) Mechanical Aerial Burst Fuze was used in parachute flares and photoflash bombs (pp 171-175) 5) 59A and (59)A Electrical Aerial Burst Fuze: (EIZZ) used in some antipersonnel and incendiary containers, consisted of two igniter bridges connected directly to the two plungers without any intervening condensers or resistances. The bridges were thus fired as soon as the bomb or flare left the aircraft, initiating pyrotechnic delay trains which provided the aerial burst functioning. The shorter delay was fired from the A plunger and the longer delay from the B plunger. If both plungers were charged, the short delay functioned and if only B was charged, the longer delay functioned. The inner construction of both fuzes was the same, but the (59)A was twice as long as the 59A (p 172)

6) (59)B Electric Aerial Burst Fuze (EIZTZ) used in SC 250 bomb and in some parachute flares, differed from the previous fuze by having three igniters instead of the conventional two. The igniter under the A plunger was in such a position as to give a 12-second delay. The other two igniters were under the B plunger and gave 41 and 58 second delays respectively. If the short delay was required, both plungers were charged. If a longer delay was necessary, only the B plunger was charged (pp 172-3)

7) 69CII, 69I, and 69E Electrical Aerial Burst Fuzes (Pyrotechnic Delay) used in various bombs and containers, were cylindrical in shape and made of aluminum. On release from the plane, the igniter bridge fired igniting the loose black powder. This in turn ignited the pyrotechnic delay mixture (no composition was given). On expiration of burning of the delay mixture, flash composition and the black powder pellets were



ignited, etc (pp 174-5)

8) 79, (79) and (79)A Electrical Aerial Burst Fuzes (Pyrotechnic Delay) used in parachute flares and photoflash bombs, resembled in appearance and action the 59 fuzes (pp 174-5)

9) (89), (89)B, (89)C and (89)D Clockwork Aerial Burst Fuzes are described on pp 175-7

The following aerial burst fuzes are described in TM E9-1983 (1942), File Nos: 2342.9, 2342.91, 2342.92, 2342.93, 2342.94

(59) Mechanical Aerial Burst Fuze

(9) Electrical Aerial Burst Fuze (See below)




(49) Aerial burst (Special) Fuzes

(59)A Electrical Aerial Burst Short Time Fuze

(89) Clockwork Aerial Burst Short Time Fuze. One of these fuzes is described below

10) (9) and (9)A Electrical Aerial Burst (Short Time) Fuzes, used in some parachute flares and in EIC 50 photoflash bomb, were cylindrical in shape and contained a discharge tube, two condensers, a resistance, a

bridge and two charging plungers. The third, smaller plunger, was believed to be used for testing the glow discharge tube. Before capping the flare, the charge from the plunger passed through the charging condenser. The charge then slowly leaked through the resistance to the firing condenser. At the time of firing, the charge was built up on one plate of the firing condenser. When the charge, which was slowly leaked by and through the igniter bridge, reached the other plate of the discharge tube to the positive charge of the gas, the current surged through the tube and igniter bridge which then ignited the quick-match train which fired the burster charge of the flare or of the photostat bomb. The function of the glow discharge tube was similar to a condenser.



Agosid 2. One of the pre-WWI dynamites; NG 30.0, vegetable jelly 2.0, wood meal 1.0, Am nitrate 36.0, K chloride 31.0%, oxygen balance + 5.0%, Trauzl test 225 cc [Naoum, Nitroglycerin (1928), p 411].

Akardit (Acardite, or asym-Diphenylurea). Described in the general section. Acardite was used by the Germans in some smokeless propellants. When used in small quantities (say 0.8%) it was as a stabilizer, while in larger quantities (e.g. 8%), it was used as a moderator of the burning rate and as a flash reducer.

Note: According to PB Rept No 11,544, neither an asym nor a sym DPhU exercises any gelatinizing action on NC, especially if NC is of high nitrogen content.

During WWII, the Germans called asym-DPhU Akardit I, because they developed two other derivatives of urea: Akardit II, $(H_2C)HN.CO.N(C_6H_5)_2$, and Akardit III, $(H_2C_2)HN.CO.N(C_6H_5)_2$. As a stabilizer, Akardit II was better than Akardit III, and the latter was better than Akardit I. For gelatinization of NC Akardit III was better than Akardit II, and II was better than I [See PB Rept No 925 (1945) p 18].

Albit. See Gesteins-Albit.

Aldorfit (Aldorfite). A Favier-type explosive invented in Switzerland and also used in Germany. For example: Am nitrate 81, TNT 17 and rye flour 2%; velocity of detonation 1960 m/sec at d 1.17 for charges confined in 50mm diameter steel tubes.

References:

- 1) Marshall, I(1917), p 391
- 2) Barnett(1919), p195 (See also under Swiss Explosives).

Aliphatic Nitramines of WW II. Out of a great number of aliphatic nitramines examined in Germany during WW II from the point of view of utilizing them as explosives or as plasticizers for NC, Römer mentions that two of them: $(O_2N.O)CH_2N(NO_2)CH_2N(NO_2)CH_2N(NO_2)CH_2(ONO_2)$, m p 155° and $(O_2NO)CH_2N(NO_2)CH_2N(NO_2)CH_2N(NO_2)CH_2N(NO_2)CH_2(ONO_2)$, m p 211°, are of particular interest

because they seem to be more powerful than RDX, judged by the Trauzl lead block test. Both nitramines were obtained as by-products in the manufacture of RDX using either the E-Salz or the KA-Salz process. [G.Römer, PBL Rept No 85,160 (1946), p 16].

Note: According to Mr L.Silberman of Picatinny Arsenal, the above compounds are called:

- 1.7- Dinitroxy - 2, 4, 6 - trinitro - 2, 4, 6 - triaza heptane
- and 1.9 - Dinitroxy - 2, 4, 6, 8 - tetranitro - 2, 4, 6, 8 - tetrazanonane.

The description of these compounds is given in the general section.

Alkalsit (Alcalsite). A type of blasting explosive based on perchlorates, such as Alkalsit I: K chlorate 28, Am nitrate 25, K or Na nitrate 30, nitrobody (such as TNT) 11.5, wood or cereal meal 2.5, resin (such as colophony) 2.5, and hydrocarbon 0.5%.

References:

- 1) F. Ullmann, Enzyklopädie der technischen Chemie, Urban & Schwarzenberg, Berlin, v 4 (1929), p 788;
- 2) A. Pérez-Ara, Tratado de Explosivos, Cultural, La Habana (Cuba) (1945) p 218.

Alloy Steels, especially high temperature alloys, such as Röhler alloy, Cromadur, Remanit, Sicromal B, Thermanit and Termex are described in CIOS Rept File No 29-23 (1946)

Aluminium (Aluminum) is described in the general section. The German electrolytic method of manufacture of Al from bauxite is described in CIOS Rept File No 22-4 (1946)

Aluminized Explosives. *Aluminiumaluge Sprengstoffe.* The use of Al explosives was begun about 1900 (in Austria) and such explosives were known as Ammonals. One such explosive was tested in France in 1902 by the Commiss on les Substances Explosives. According to Lheure it contained: Al 3, Am nitrate 71, charcoal 24. Another aluminized explosive, called Fühler, contained: Al 14, Am nitrate 83 and charcoal 3%.

The role of Al in explosives was not very clear until recently when it was explained by A. Stettbacher of Switzerland (Ref 1) and H. Muraour of France (Ref 2). After it was found that Al is particularly effective when used in underwater explosives, the Germans replaced their underwater explosive of WW I TNT 60, HNDPhA (hexanitrodiphenylamine 10 cyclic) following mixture: TNT 55.7, HNDPhA 27.9 and Al grit (0.070 mesh) 16.4%. The same idea was followed in Sweden, where Al was used in their Bonit and Novit explosives. Great Britain and the U.S.A. also included Al in underwater explosives, such as Torpex and Tritonal (British UWE). The Italians and Japanese also used Al explosives. According to Stettbacher, another German underwater explosive contained: TNT 61.8, HNDPhA 23.0, Al 15.2%.

Among German aluminized explosives developed before or during WWII may be cited: S-6, S-6 modif, S-19, S-22, S-26, E-1, KMA and S-16. Their compositions are given under *Ersatzsprengstoffe* (See also Anagon, Berclavit B, and Nitrobaronit).

(For more information see *Aluminized Explosives* in the general section).

References:

- 1) A. Stettbacher, *Protar* 9, 33-45 (1913)
- 2) H. Muraour, *ibid*, 62-63 (1913)
- 3) L. Médard, *Ann Art Fr* 22, 598-611 (1918), *Aluminized Explosives*
- 4) A. Stettbacher, *Spreng- und Schiesstoffe*, Rascher, Zürich (1918), p 88-90.

Aluminum-Chloromethyl Mixture. See *Methyl Stoff*.

Aluminum Mine. See under Landminen and also on p 273 of TM 9-1985-2 (1973).

Amatol (*Füllpulver*, abbreviated Fp) (*Amatol*). The composition of most amatols was TNT and ammonium nitrate, but the designation was the reverse of the American amatols. For instance, German 40-60 Amatol or Fp 40-60, corresponded to the American 60-40 Amatol (Am nitrate 60, TNT 40). (See also Filler No 1, - No 14a and - No 88).

There were also German amatols which contained no TNT but some other explosive or explosives. These amatols (No 39, 40 and 41) are described below.

Amatol 39. A mixture developed by Römer (Ref 2) as a bursting charge for the V-1 rockets. It contained DNB 50, Am nitrate 35, RDX 15, and was claimed to be as powerful as Fp 60/40 (TNT 60, Am nitrate 40). Due to the toxicity of DNB, loading of the projectiles was conducted in a special building provided with good ventilation. As it was difficult to cast-load Amatol 39 uniformly (without formation of cavities) in large caliber projectiles, G. Römer (Ref 3) used the so-called "biscuit" loading method. In this method, a projectile was filled alternately with pieces (pellets) of so-called "biscuit mixture A" (Am nitrate 50, technical Ca nitrate 25, PETN 10 and RDX 15%) and molten Amatol 39 at a temperature of about 80°. The resulting mixture formed no cavities on cooling. Its density at room temperature was 1.58; velocity of detonation 5600 m/sec, Trauzl lead block expansion test 350cc for a 10 g sample and a crusher test value (Stauchprobe) (compression of a

lead block) 17.5 mm.

Notes: a) According to Ref 3, **Amatol 39** was developed in 1939 at the Krummel Fabrik of Dynamit A-G and was used for filling projectiles.

b) One of the Amatols 39 was used in underwater explosive charges.

Amatol 40. This explosive was sometimes used during WW II for filling the war head of V-1 Rockets. It contained DNAs 50, Am nitrate 35 and RDX 15%. It could be cast-loaded like TNT (Ref 3).

(Another composition, also known as **Amatol 40**, is given under *Ersatzsprengstoffe*).

Amatol 41. An explosive similar in composition to ammonites: Am nitrate 52, Ca nitrate (tech) 6, PH-Salz 30, RDX 10, montan wax 2%; density of fragments 40 m (TNT 10 m); used in bombs (Ref 3).

Note: According to Ref 1, Kant, as early as 1915, proposed the mixture of Am nitrate 40 and TNT 60% for cast-loading German projectiles. The same mixture was used later by the British under the name of 40/60 Amatol. According to Urbaniski (Ref 3) an Amatol of WW II contained TNT 50, RDX 5-10 and Am nitrate 45-60%.

Abbreviations: DNAs Dinitroanisole; DNB Dinitrobenzene; PETN Pentaerythritol tetranitrate; RDX Cyclonite; TNT Trinitrotoluene.

References:

- 1) A. Stettbacher, *Schiess- und Sprengstoffe*, Barth, Leipzig, (1913), p 308
- 2) G. Römer, *DBL Rept No 85, 160* (1944), pp 17 & 23
- 3) G. V. Stickland et al, *General Summary of Explosives Plants*, PB Rept No 925 (1945)
- 4) F. Urbaniski, *Przemysl Chemiczny* 4, 187 (1948).

Amberit (*Amiarite*). One of the sporting propellants: collodion cotton 50, guncotton 13, Ba or K nitrate 19, paraffin 6.0, moisture 1.5, gelatinizer 1.5% Brunswick, *Das rauchlose Pulver* (1926), p 134.

Amidpulver (*Amidpowder*) was a sulfurless black powder substitute invented in 1885 by Güns of Hamburg. It had the following composition: Am nitrate 38, K nitrate 40 and charcoal 22%. Its composition was modified several times until a powder which was flashless and almost smokeless was obtained. The improved composition: Am nitrate 37, K nitrate 41 and charcoal 19%, was used during WW I as a cannon propellant.

References:

- 1) Davis, (1913), p 49
- 2) Hebie, (1913), pp 20-21.

Ammonals (*Aluminium haltige Sprengstoffe*) are explosives based on Am nitrate, Al, and TNT or other organic substances. Ammonals have been used for many years, not only in Germany but in other countries, and for this reason are also described in the general section. Several ammonals were used in Germany for military purposes. They may be considered as substitute explosives (*Ersatzsprengstoffe*), for example:

Ammonal I. Am nitrate 54, TNT 30 and Al flakes 16%.

Ammonal II. Am nitrate 72, TNT 12 and Al flakes 16%.

Ammonal B. Am nitrate 93-93.5, charcoal 2-3 and Al 2.5-3.5%.

Ammonal. Am nitrate 91.3, TNT 0.3, Al 1.7 and pitch 6.7%.

This composition required a booster for initiation. (See also Fillers Nos 19, 13-113 and 110).

References:

- 1) Davis, (1913) p 368
- 2) PB Rept No 925, (1945)
- 3) DBL Rept 85, 160 (1946)
- 4) A. Stettbacher, *Spreng- und Schiesstoffe*, Rascher, Zürich (1918), p 88.

Ammonalhalt See *Wetter-Ammonalhalt*.

Ammoncarbonit (Ammoncarbonite) A type of permissible explosive which may be considered intermediate between carbonites and ammonium nitrate explosives. Table 1 gives the composition and properties of some of these explosives:

Table 1

| Composition (%) and some properties | Ammoncarbonit I (Ref 1) | Ammoncarbonit (Refs 1&3) | Ammoncarbonit II (Ref 2) |
|---------------------------------------|-------------------------|--------------------------|--------------------------|
| Ammonium nitrate | 80.4 | 82 | 50.0 |
| Potassium nitrate | 8 | 10 | - |
| Sodium nitrate | - | - | - |
| Nitroglycerin | 1 | 3.5 | 5.0 |
| Collodion cotton | 0.2 | 0.2 | - |
| Glycerin | - | - | 2.0 |
| Carbohydrates (such as starch, flour) | 1.5 | - | - |
| Coal dust | 6 | - | - |
| Alkali chloride | - | - | 2.0 |
| Wood meal | - | 9 | - |
| Oxygen Balance | - | - | 10% |
| Density | 1.11 | 1.06 | - |
| Velocity of Detonation | 3195 m/sec | 3350 m/sec | - |
| Trauzl Test | 35 cc | - | 210 cc |

References:

- 1) Marshall I, p 397, 2, p 193
- 2) P. Naoum, Nitroglycerin (1928), p 331-332, Ullmann, Enzyklopädie, v 1 (1929), p 780
- 3) Davis, (1933), p 352

Ammondynamit (Ammonidynamite) A type of straight dynamite containing a considerable amount of ammonium nitrate.

Am nitrate 30.0, NG 63.0, collodion cotton 2.0, wood meal 5.0%, oxygen balance + 1.5%, density 1.11, Trauzl test value 185 cc, Pb block crushing 21.0mm, velocity of detonation 7000 m. sec, heat of explosion (water vapor) 1300 kcal/kg, temperature of explosion 2770°C.

This type of explosive was not very popular in Germany but was used in France and the U.S.A. (P. Naoum, Nitroglycerin (1928), p 349).

Ammongelatine (Ammongelatın) A type of permissible dynamite, such as:

- a) **Ammongelatine 2:** DNT 7-8, Al 1.5-2.5, collodion cotton 0.5-0.7, dinitrochlorohydrin (DNCIII) 21-21, Am nitrate 61-65 and carbohydrates not more than 1.5% (Ref 1).

Note: The Am nitrate may be replaced by Na nitrate to the extent of 8.5% of the entire explosive and the DNCIII may be replaced by NG to the extent of 4% of the entire explosive.

- b) **Ammongelatine** An explosive permitted after WWI for use in Prussian mining: DNCIII (of which up to 5% of the total explosive may be replaced by NG) 28 to 33, collodion cotton 1 to 3, Am nitrate 45 to 50, alkali nitrate 10 to 15, a nitrocompound of toluene and/or naphthalene and/or diphenylamine 6 to 12, vegetable meal 0 to 2% (Ref 3).

- c) **Deutsche Ammongelatine** DNCIII, containing 15-20% of NG (such a mixture was called Nitrochlorin) 30, collodion cotton 5, mixture of DNT and TNT 10, Am nitrate 45, Na nitrate 10, wood meal 2; density 1.45, velocity of detonation 6900 m/sec, Trauzl test value 400 cc, vol of gases at NTP 771 l/kg, heat of explosion 1101 kcal/kg, temp of explosion 2570°C, specific

pressure 8108 atm, brisance by the Kast formula 82,000 (Refs 2 and 4).

Abbreviations: DNCII Dinitrochlorohydrin, NTP Normal temperature, $^{\circ}$ C and pressure 760 mm.

(Compare with Ammon-Australin).

References:

- 1) A. Marshall, Explosives, v 3 (1933), p 165
- 2) F. Naoum, Schiess- und Sprengstoffe (1927), p 113
- 3) P. Naoum, Nitroglycerin (1928), p 370
- 4) A. Stettbacher, Spreng- und Schiessstoffe (1918), p 86.

Ammoniak (Ammonia) is described in the general section. The German method of manufacture of synthetic ammonia is described in HOS Final Rept I (1946).

AMMONIT (Ammonite) A type of ammonium nitrate explosive which has been known for many years and which exists in many varieties. Most ammonites were used as commercial explosives, but some of them have found use in military applications, chiefly as substitutes (see Ersatzsprengstoffe) for explosives based on organic nitrocompounds, such as TNT, or nitric esters (such as NG).

Many types of ammonites were known in Germany before WWI. For instance, Naoum (Ref 1) describes seven types, Beyling and Drekopf (Ref 3) four types and Stettbacher (See table 2 on next page listing ammonites used during WW II for military purposes and see also under Commercial Explosives).

References:

- 1) P. Naoum, Schiess- und Sprengstoffe, Steinkopf, Dresden (1927), pp 119-127
- 2) A. Stettbacher, Schiess- und Sprengstoffe, Barth, Leipzig, (1933), p 216
- 3) C. Beyling & K. Drekopf, Schiessstoffe und Zundmittel, Springer, Berlin (1936), pp 94-95
- 4) G.W. Stickland et al., General Summary of Explosives Plants, PB Rept No 925 (1945), Appendix 7, p 77
- 5) G. Römer, Report on Explosives, PBL Rept No 85, 160 (1945), pp 22-4.

Ammonium Nitrate. See Ammonsalpeter

Ammonium Nitrate Explosives See Ammonsalpetersprengstoffe

Ammon-Nobelit (Ammon-Nobelite) A type of permissible explosive used after WWI, such as: a) Am nitrate 78.0, K nitrate 5.0, alkali chloride 8.0, meal 5.0, NG 4.0%, oxygen balance + 11.8%, Trauzl test value, 200cc. b) Am nitrate 61.0, Na nitrate 3.0, meal 7.5, glycerin 3.0, nitrotoluenes 1.0, alkali chloride 20.5, NG 4.0%; oxygen balance 0.0%. Trauzl test value 215 cc. Naoum, Nitroglycerin (1928), pp 434-5.

Ammonpulver (Ammonpowder) A propellant first manufactured in 1890 in Austria by incorporating Am nitrate 85 with charcoal 15% and compressing the mixture into large pellets to a density of about 1.1. It was used during WWI by the Austrians and Germans as a substitute for NC propellant and ballistite and was claimed to be very effective and practically smokeless, flashless, and erosionless. On the other hand, it was found to be difficult to ignite, gave rather irregular ballistics and had a tendency to disintegrate on storage due to allotropic change in the Am nitrate at 32 $^{\circ}$ (90 $^{\circ}$ F). In order to minimize irregular ballistics, only 1.3 to 1.2 of the propellant charge consisted of Ammonpulver, the rest being NC propellant. In order to protect the Am nitrate from atmospheric moisture the pellets were sometimes enclosed in a box made of thin sheets of double-base propellant (Ref 1) Note: According to Davis (Ref 3), Ammonpulver contained a small amount of an aromatic nitrocompound in addition to the above listed components.

The Ammonpulver described by Herbat (Ref 2) contained

Table 2

| Components and some properties | Designation of Ammonites | | | | | | | | | | | | |
|--------------------------------|--------------------------|------|------|-----|------|------|------|------|------|------|------|-----|-----|
| | No 1 | 13A | 13B | 13c | 13c | No 7 | H1 | H5 | No 1 | No 2 | No 3 | H-2 | H-8 |
| Am nitrate | 12,0 | 10,0 | 50,0 | - | 15,0 | 46,0 | 50,0 | 50,0 | 55,0 | 52,0 | 50,0 | - | - |
| Na nitrate | 0,8 | - | 8,0 | - | - | - | - | 5,0 | 5,0 | 8,0 | - | - | - |
| Ca nitrate, $6H_2O$ | - | 8,0 | 6,0 | - | 10,0 | 8,0 | 15,0 | 15,0 | 10,0 | 7,0 | 15,0 | - | - |
| Ni nitrate, $6H_2O$ | 8,0 | - | - | - | - | - | - | - | - | - | 10,0 | - | - |
| Guanidine nitrate | - | 8,0 | 10,0 | - | 15,0 | - | - | - | - | - | 10,0 | - | - |
| PETN | 9,8 | - | 2,0 | - | - | - | 10,0 | - | - | - | - | - | - |
| PB-Salz | - | - | 5,0 | - | - | 10,0 | - | 10,0 | 10,0 | - | - | - | - |
| RDX | 30,0 | 8,0 | 7,0 | - | - | - | 25,0 | 20,0 | 20,0 | 25,0 | 25,0 | - | - |
| Tetra-Salz | - | - | - | - | - | - | - | - | - | 8,0 | - | - | - |
| TNT | - | 30,0 | 10,0 | - | 30,0 | - | - | - | - | - | - | - | - |
| "Valamol" (emulsified loaded) | - | 0,3 | 0,3 | - | 0,5 | - | - | - | - | - | - | - | - |
| Density (cast) | - | 1,58 | 1,01 | - | - | - | - | - | 1,55 | 1,50 | - | - | - |
| Casting Temperature | - | 160 | 105 | - | - | - | - | - | 108 | 112 | - | - | - |
| Density of Fragments | 41m | - | 38m | - | - | - | - | - | 40m | 41m | - | - | - |
| Mining Effect | 21m ³ | - | - | - | - | - | - | - | - | - | - | - | - |
| References | 5 | 5 | 5 | - | - | 5 | 4 | 4 | 5 | 5 | 4 | - | - |

The composition given by Röpfer (Ref 5, p 22) totals 100

Ammonit 13C exploded in 1944 on a loading line and its manufacture was discontinued. It was reported that mixtures of TNT with guanidine nitrate were unstable

Most of these mixtures were suitable for loading bombs, grenades and shells.

Am nitrate 90 and charcoal 10%. The mixture was compressed in the form of perforated cylindrical pellets 5 to 5 cm long and 3 to 4 cm in diameter. The ignition temp of the compound was 160-165°, but if substances like iron rust, ZnO or CuO were present the temp was lowered to 80-120°

Note: According to CIGS 31-68, p 7, the composition of Ammonipulver used during WW II was as follows: Am nitrate 50, Na (12%) 22, DEGON 22, hydrocellulose 5 and centralite 1%

References:

- 1) Marshall, 3 (1932), pp 88-2) H. Herbst, Chem Ztg 59, 744-5 (1935)
- 3) Davis (1943), p 49.

Ammonsalpeter (Ammonium Nitrate) is described in the general section. Its manufacture in Germany at Bitterfeld South and Wolfen plants is described in BIOS Final Rept No 889 (1946).

Ammonsalpetersprengstoffe (AS) oder Sicherheitsprengstoffe
See Ammonium Nitrate Explosives in the general section.

The German References on this subject include:

- 1) R. Escales, Ammonsalpetersprengstoffe, Veit, Leipzig (1909)
- 2) P. Naoum, Schiess- und Sprengstoffe, Steinkopf, Dresden (1927), pp 114
- 3) P. Naoum, Nitroglycerin etc., Williams & Wilkins, Baltimore (1928), p 423
- 4) A. Stettbacher, Schiess- und Sprengstoffe, Barth, Leipzig (1933) p 295
- 5) C. Beyling & K. Dreikopf, Sprengstoffe und Zündmittel Springer, Berlin (1936), pp 93-96
- 6) A. Stettbacher, Spreng- und Schiessstoffe, Rascher, Zürich (1938) pp 86-88.

AMMUNITION (Munition). See under Bombs, Bullets, Cartridges, Fuzes, Grenades, Mines, Projectiles, Rockets and also in the following references:

- 1) Johnson, Jr and C.T. Haven, Ammunition, D. Morrow, N Y (1943)
- 2) Dept of the Army Tech Manuals, TM 9-1985-2 and TM 9-

1985-3 (1953)

- 3) G.M. Taliaferro, Picatinny Arsenal Technical Report, 982 (1939) (20 mm Rheinmetall CRA)
- 4) W.H. Ewart, *ibid*, 1053 (1940) (20 mm Solothurn CRA)
- 5) A.B. Schilling, *ibid*, 1168 (1942) (105 mm How CRA)
- 6) A.B. Schilling, *ibid*, 1228 (1943) (88 mm APC HE CRA)
- 7) A.B. Schilling, *ibid*, 1238 (1943) (50 mm APHE SC CRA)
- 8) R.M. Dennis, *ibid*, 1242 (1943) (20 mm APHV CRA)
- 9) R.M. Dennis, *ibid*, 1243 (1943) (47 mm APC CRA)
- 10) A. B. Schilling, *ibid*, 1245 (1943) (47 mm APHV CRA)
- 11) A.B. Schilling, *ibid*, 1247 (1943) (75 mm APC HE CRA)
- 12) R.M. Dennis, *ibid*, 1248 (1943) (20 mm Inc CRA)
- 13) A.B. Schilling, *ibid*, 1250 (1943) (50mm APHV Mk II CRA)
- 14) R.M. Dennis, *ibid*, 1253 (1943) (37 mm APHE CRA)
- 15) A.B. Schilling, *ibid*, 1256 (1943) (20 mm HE SV CRA)
- 16) A.B. Schilling, *ibid*, 1259 (1943) (47 mm HE CRA)
- 17) A.B. Schilling, *ibid*, 1263 (1943) (80 mm Sm CRA for Mor)
- 18) A.B. Schilling, *ibid*, 1267 (1943) (50 mm APHV SC CRA)
- 19) A.B. Schilling, *ibid*, 1270 (1943) (50 mm HE CRA for Mor)
- 20) R.M. Dennis, *ibid*, 1271 (1943) (37 mm APHV MB CRA)
- 21) R.M. Dennis, *ibid*, 1272 (1943) (47 mm AP MB CRA)
- 22) R.M. Dennis, *ibid*, 1273 (1943) (50 mm APHE MB CRA)
- 23) R.M. Dennis, *ibid*, 1274 (1943) (50 mm APHE LC CRA)
- 24) A.B. Schilling, *ibid*, 1275 (1943) (20 mm A? Inert Loaded CRA)
- 25) R.M. Dennis, *ibid*, 1276 (1943) (75 mm HE CRA)
- 26) A.B. Schilling, *ibid*, 1300 (1943) (88 mm HE CRA)
- 27) R.M. Dennis, *ibid*, 1305 (1943) (50 mm HE SC CRA)
- 28) R.M. Dennis, *ibid*, 1314 (1943) (37 mm HE CRA)
- 29) R.M. Dennis, *ibid*, 1318 (1944) (50 mm HE LC CRA)
- 30) R.M. Dennis, *ibid*, 1320 (1943) (37 mm APHE MB CRA)
- 31) R.M. Dennis, *ibid*, 1326 (1944) (42/28 mm APHV CRA)
- 32) A.B. Schilling, *ibid*, 1329 (1944) (28/20 mm APHV CRA of two design, single-piece body and two-piece body)
- 33) A.B. Schilling, *ibid*, 1334 (1943) (75 mm Chem CRA)
- 34) R.M. Dennis, *ibid*, 1340 (1944) (80 mm HE CRA for Mor)
- 35) R.M. Dennis, *ibid*, 1343 (1944) (75 mm HE CRA for Pak 40 gun)

- 36) A.B.Schilling, *ibid*, 1390 (1944) (28.20 mm HEHV CRA)
 37) A.B.Schilling, *ibid*, 1391 (1944) (88 mm HE LC CRA for Flak 41 gun)
 38) A.B.Schilling, *ibid*, 1392 (1944) (88 mm APC LC CRA for Flak 41 gun)
 39) A.B.Schilling, *ibid*, 1398 (1944) (37 mm HE HoC CRA)
 40) A.B.Schilling, *ibid*, 1421 (1944) (75 mm APC HE CRA)
 41) J.F.Wardlaw, *ibid*, 1422 (1944) (80 mm HE CRA for Mor) (Bouncing type shell)
 42) F.G.Haverlak, *ibid*, 1430 (1944) (20 mm HE-1 CRA for Muser gun)
 43) A.B.Schilling, *ibid*, 1454 (1944) (75 mm HE HoC CRA for How)
 44) A.B.Schilling, *ibid*, 1455 (1944) (75 mm HE CRA for How)
 45) A.B.Schilling, *ibid*, 1468 (1945) (50 mm HE LC CRA)
 46) F.G.Haverlak, *ibid*, 1478 (1944) (20 mm HE Inc CRA)
 47) F.G.Haverlak, *ibid*, 1481 (1944) (105 mm HE HoC SO CRA)
 48) F.G.Haverlak, *ibid*, 1487 (1944) (75 mm HE HoC CRA for recoilless gun)
 49) A.B.Schilling, *ibid*, 1488 (1945) (150 mm HE HoC CRA)
 50) J.P.Wardlaw, *ibid*, 1490 (1945) (75 mm HE HoC CRA for Pak 40 gun)
 51) F.G.Haverlak, *ibid*, 1498 (1945) (105 mm HE HoC Type C LO shell CRA)
 52) F.G.Haverlak, *ibid*, 1503 (1945) (75 mm HE HoC CRA for KwK40 gun)
 53) F.G.Haverlak, *ibid*, 1508 (1945) (100 mm APC HE CRA)
 54) F.G.Haverlak, *ibid*, 1516 (1945) (88 mm AFC HE CRA for KwK43 and Pak gun)
 55) A.B.Schilling, *ibid*, 1522 (1945) (150 mm HE CRA, separate loading)
 56) A.B.Schilling, *ibid*, 1529 (1945) (150 mm HE A/C CRA with BD fuze)
 57) F.G.Haverlak, *ibid*, 1540 (1945) (75 mm HE HoC CRA for short barrel tank gun, KwK 38)
 58) F.G.Haverlak, *ibid*, 1551 (1945) (150 mm How CRA)
 59) F.G.Haverlak, *ibid*, 1552 (1945) (210 mm HE CRA)
 60) A.B.Schilling, *ibid*, 1559 (1945) (88 mm HE, serrated shell for Flak 18 gun)
 61) F.G.Haverlak, *ibid*, 1575 (1945) (152 mm CP shell and cartridge case with propellant of Russian origin)
 62) A.B.Schilling, *ibid*, 1577 (1945) (240 mm HE shell with PD and BD fuzes; cartridge case and propellant)
 63) A.B.Schilling, *ibid*, 1578 (1945) (75/55 mm HE CRA for tapered bore Pak 41 gun)
 64) A.B.Schilling, *ibid*, 1579 (1945) (75/55 mm AP CRA for tapered bore Pak 41 gun)
 65) A.B.Schilling, *ibid*, 1582 (1945) (100 mm HE CRA for Mor)
 66) A.B.Schilling, *ibid*, 1604 and 1605 (1946) (105 mm rocket assisted HE shell)
 67) A.B.Schilling, *ibid*, 1606 (1946) (128 mm rocket assisted HE shell)
 68) A.B.Schilling, *ibid*, 1607, 1608 and 1609 (1946) (150 mm rocket assisted HE shell)
 69) A.B.Schilling, *ibid*, 1610 (1946) (150 mm rocket assisted AP shell)
 70) A.B.Schilling, *ibid*, 1903 (1954) (30 mm HE and Inc shell for the A/C Mk-108 cannon) (Confidential)
 71) Anon, *Enemy Bombs and Fuzes*, War Dept TM-E9-1983 (1942)
 72) Anon, *Enemy War Materials Inventory List, Ammunition*, Supreme Headquarters AEF (1945)
 73) Anon, *Recognition Handbook of German Ammunition*, Supreme Headquarters AEF (1945).
- Note: All Picatinny Arsenal reports except No 1903 are unclassified
- Abbreviations AA Antiaircraft; AC Aircraft; A/C Anti-concrete; AP Armor-piercing; A/P Anti-personnel; BD Bore

detonating; C Capped; Chem Chemical; CP Concrete-piercing
 CRA Complete round of ammunition; Flak German designation of Antiaircraft; HC High capacity; HE High explosive; HoC Hollow (shaped) charge; How Howitzer; HV Hyper velocity; Inc Incendiary; KwK German designation of Tank Gun; LC Long case; LO Long ogive; MB Monoblock; Mor Mortar; Pak German designation for Antitank; PD Point-detonating; SC Short case; SD Self-destroying; Sm Smoke; SO Short ogive; T Tracer.

"Amorce" (Toy Pistol Cap). Due to the shortage of fulminate caps during WW II, the Germans used amorces as igniters for some hand grenades. Amorces manufactured by Ferdinand Wicke, Wupertal-Barmen and by Blumberg & Co, Lintorf bei Düsseldorf contained: K chlorate 67.5 to 80.6, phosphorus 12.3 to 8.0, sulfur 8.9 to 5.7 and chalk 11.3 to 5.7%
 Reference: BIOS Final Rept 1313 (1947), pp 2-4.

Anagon. One of the early aluminized explosives: Al 5.5, Am nitrate 84.5, K nitrate 1.5, charcoal 8.0, Ba nitrate 0.5%; L. Médard, *Mém Artill Fr* 22, 596 (1948).

Ansonitkapseln (Ansonit Caps). Due to the shortage of brass during WW I, the Germans used zinc and zincated iron caps. They were filled with TNT as the base charge and compressed silver fulminate as the primary charge. The ensemble was called Ansonitkapsel. [P. Naoum, *Schiess- und Sprengstoffe*, Steinkopf, Dresden (1927), p 185].

Antiaircraft Wind Gun. See Wind Gun

Antibrake-up Fuze (Antirupture Fuze), such as AZ (24)A was a mechanical impact fuze with a safety arming period of 10 seconds provided by the clockwork gear train. There were two striker systems incorporated: an inertia striker system to operate on impact and an antirupture striker to function in case there was any distortion of bomb or fuze pocket on impact. The two striker systems were located at opposite ends of the fuze separated by a flash channel about 260 mm long. This fuze, as well as the AZ (24), are described in TM 9-1985-2 (1953), pp 135-9. They were used in bomb SC 2500 kg.

(See illustration on next page).

Antidisturbance Fuze (Electrical) was a device designed to function if disturbed after the bomb, dropped from a plane had come to rest. One type, the 50, consisted of a cylindrical case containing an electrical circuit (two condensers, two resistors, a super-sensitive ball-trembler switch and bridge wire of primer) and two charging plungers. The base of the cylindrical case was threaded to receive a gaine. Before dropping the bomb, an electrical charge from the plane was conducted through the charging plungers into the charging condenser. During the flight the charge slowly leaked through a high resistor into the firing condenser. If after the bomb had come to rest it was subsequently disturbed, the trembler switch caused the circuit to be closed. This ignited the primer, initiated the booster and detonated the HE charge of the bomb. This also took place when one or both charging plungers were depressed. In this case the current from the condenser by-passed the switch. [TM E9-1983-(1942), file No 2325.0].

Another antidisturbance fuze, the 50a or Y was much more complicated. Its description is given in TM 9-1985-2 (1953), pp 183-6.




(See illustration on next page).

Antilifting Igniter. See items I and L under Igniter

Antipathfinder Devices. See Pyrotechnic Antipathfinder Devices.

Antipodal Bomber. See Sänger-Bredt Missile.

Anti-Ricochet Plates. Circular shaped metallic devices attached to the noses of some aircraft bombs intended to prevent ricochet when striking at an angle of obliquity against very resistant targets (such as armor), or to prevent excessive penetration into less resistant targets (such as concrete or wood) when striking them at an angle close to normal. (See illustration on next page and also under Koptring) [TM 9-1985-2 (1953), p 3].



Antiwithdrawal Fuzes (Mechanical) were designed as protective devices to prevent withdrawal of regular time fuzes from bombs. Three types of such fuzes are described in TM 9-1985-2 (1953), pp 177 & 179-181: ZusZ 40, Types I, II and III. The type I fuze consisted of a cylindrical body with a central opening in the upper surface to receive the gaine of the time fuze which it protected, and a second gaine which was threaded into the base of a ZusZ 40. An attempt to withdraw the fuze would cause the steel ball (below the derent spring) to be displaced, thus allowing the striker to hit the detonator. The resulting flash was transmitted through a small channel to the booster and the bomb was exploded. To prevent the withdrawal of the ZusZ 40 when the time fuze was removed, spring-loaded knife edges were placed in the upper part of the device. (See illustration on next page).


"Anzio Annie" or "Leopold 280 mm Railroad Gun, Model 5. (See under Weapons).

Armored Cars are described in the following references:
 1) G.B. Jarrett, "Achtung Panzer", Great Oaks, RD 1, Aberdeen, Md (1948)
 2) D.F. von Senger u Etterlin, "Taschenbuch der Panzer", Lehmann, München (1954) (See also under Panzer).

Arif (Arife). A mining explosive reported to be manufl by VEB Sprengstoffwerke, Ginaschwitz. Its approximate composition is NG, pyroxylin, sawdust, TNT and inorganic salts.

Arrowhead (Needle Point) Projectile, such as 5 cm Pzgr/Patr 40 für 5 cm Pak, was a 50 mm AP proj which consisted of the following components: a pointed tungsten carbide core cemented to a steel body which had forward and rearward flanges, a plastic arrowhead shaped head covered with a sheet steel ballistic cap and a tracer assembly. The forward flange acted as the rotating band, while the rear flange acted as the bourrelet.

The Pzgr 40 was fired from a normal gun. On striking the armor, the ballistic cap, the head and the body with





tracer assembly were shattered thus leaving the tungsten carbide core to penetrate the armor.
 By employing the arrowhead design, the weight of proj was about half the conventional Pzgr (HEAP) shell. Due to this lightness, it was possible to develop very high velocities and high armor penetration at short ranges. The proj was, however, very inaccurate at long ranges and the penetration hole was small in comparison with the gun caliber (See also Tapered-Bore Gun Projectile).

There were also 37 mm (3.7 cm PzgrPatr 40), 4" mm (4.7 cm PzgrPatr 40) and 75 mm (7.5 cm PzgrPatr 41) arrowhead type AP projectiles.

- References:
 1) E. Engesburg, Ordnance Sergeant May 1944, pp 311-12
 2) Anon, Technical Manual TM 9-1985-3, pp 373, 376-7

**75 MM
 AP PRO JECTILE
 WITH TUNG STEN CAR-
 BIDE CORE (ARROWHEAD)**



ARROWHEAD PROJECTILE

Arrow Projectile (I-feilstabiles Geschoss) is a slender, very long, fin-stabilized subcaliber projectile fired from a smooth-bore gun at supersonic velocity. Its development which is described in Ref 1 may be considered as one of the outstanding German achievements of WW II. Some of these projectiles were used in the attack on the Maginot Line and were successful in penetrating concrete. Their subsequent use was confined to the Russian front.

ARROW PROJECTILE

References:

1) H. Kurzweg, Die grundsätzlichen aerodynamischen Untersuchungen zur Entwicklung Pfeilstabiler Geschosse. Schriften der Deutschen Akademie der Luftfahrtforschung, Nr 1059-43 (1943), pp 33-71

2) L.E. Simon, German Research During WW II. J. Wiley, N.Y. (1917), p 191

3) Dept of the Army Tech Manual, TM 9-1985-3 (1953), p 300.

Note: According to H.H. Bullock and G. Coghlan, the above projectile was also called a **Needle Shell**. A projectile available at the museum of Picatinny Arsenal was 105/60 mm caliber and about 700 mm long (Compare with Röchling Anticoncrete Projectile).

(See also Gessner Projectile).

Arsenals and Explosives and Ammunition Plants. See Warplants.

Artillerie (Artillery). A list of German cannons etc may be found under Weapons. (See also Taschenbuch für den Artilleristen published in 1937 by Rheinmetall-Borsig).

Artillery Ammunition (Complete Round). See under Grenade.

AS. Abbreviation for Ammonsalpetersprengstoffe. (Explosives based on ammonium nitrate) [Weichert (1953), pp 39, 375.]

AS-3. One of the German priming (igniting) compositions used during WW II in some electric fuses etc. It contained red lead 77, silicon 19, NC suspended in acetone 4%. [PB Rept No 95 613 (1947), Section V].

ASN. See under Unterwassersprengstoffe.

A-Staff (Liquid Oxygen) is described in the general section. It was used in some liquid propellants for guided missiles such as the A-4 (V-2), Taifun and Wasserfall.

Reference: Gollin, Rockets and Directed Missiles, CIOS File No 28-56 (1946), p 3.

Note: According to CIOS 33-13, p 20, the AS-3, which means Artillery School composition 3 (Artillerieschule 3), was an incendiary composition prepared by mixing 75 parts of red lead with 25 p of silicon made into a paste with NC jelly.

Assisted Take-Off (ATO) Units. See under Rocket.

Astralit (Astralite). A type of mining explosive similar in composition to Ammonit and Donarit.

Typical compositions are given in the following Table 3a.

Table 3a

| Composition (%) and some properties | Astralit 1 | Astralit 2 | Astralit 3 | Astralit 4 | Astralit ON |
|--|------------|------------|------------|------------|-------------|
| Ammonium nitrate | 84.5 | 80.0 | 79.0 | 68.3 | 80.0 |
| TNT + DNT | 7.0 | 12.0 | - | - | - |
| Vegetable meal | 1.0 | 3.0 | - | - | - |
| TNT + DNT + meal | - | - | 17.0 | 27.7 | 20.0 |
| Charcoal | 1.0 | 1.0 | - | - | - |
| Paraffin oil | 2.5 | - | - | - | - |
| Nitroglycerin | 4.0 | 4.0 | 4.0 | 4.0 | - |
| Oxygen Balance, % | - | - | +2.5 | - | +0.3 |
| Trauzl Test, cc | - | - | 390 | - | 375 |
| Pb Block Crushing, mm | - | - | 26.2 | - | 16.0 |
| Sensitiveness to Initiation (requires) | - | - | No 1 Cap | - | No 3 Cap |
| Propagation in 30 cm Cartridges | - | - | 12.0cm | - | 80cm |
| Velocity of Detonation m/sec | - | - | 5400 | - | 4900 |
| Density of Cartridge | - | - | 1.09 | - | 1.03 |
| Heat of Explosion, kcal/kg | - | - | 957 | - | 1006 |
| Temperature of Explosion, °C | - | - | 2170 | - | 2220 |

*See Propagation of Explosion in Cartridges, described in the general section.

References:

- 1) A. Marshall, Explosives, 1, (1917), p 397
- 2) P. Naoum, Nitroglycerin (1928), pp 423 & 426.

Ethylphenylurethan (Ethylphenylurethane) was used as an ingredient of some smokeless propellants as a stabilizer-gelatinizer. [PB Rept No 11,544 (1945)].

Auroj or Ingolin. See T-Stoff.

Ausbuchungsprobe (Expansion Test). See Trauzl Lead Block Test in the general section.

Ausschwitzungsprobe (Sweating Test). See Exudation Test in this and in the general sections.

Azeton (Acetone). See general section.

Azide (Azides) are described in the general section. (See also this section under Bleiazid).

Azoimid (Stickstoffwasserstoffsäure) (Hydrazoic Acid). See general section.

3-4 A vehicle 12' long, 6' wide and 4' high provided with a 6 cylinder engine (in the rear), a radio and a space for the driver. After loading the vehicle with some demolition charges, the driver took the car (max speed 30 mph) as close as possible to the target marked for destruction (such as a barbed wire, road block, pillbox, bridge, etc), dropped the demolition charges, set the time fuse and then rushed back. These vehicles were easy targets for the Allies' artillery.

Reference: *Amon, Field Artillery J*, 34, 505 (1944).

Bo (Bochem 349 Missile). See Natter Ba 349A and 349B.

Bolinit. One of the mining explosives: Am nitrate 85 and TNT 15%. *L. Colver, High Explosives (1918)*, p 219.

"Boiter" See "Hetzer" armored vehicle listed under Panzer.

Ballistische Beständigkeit (Ballistic Stability). See general section.

Ballistit or WPC/89 (Kurfelpulver/89) (Cube Powder of 1889) (Ballistite). Dark grey propellant consisting of equal parts of NG and collodion cotton together with 0.56 to 1% of DPA and vaselin. It was adopted in 1889 by the German Navy. Less erosive compositions were introduced in 1897 and 1906, under the designation of RPK/97 and RPK/06, where RP stands for Rohrpulver (tube powder). *Marshall, v1 (1917)*, p 303.

Bandisch Pulver was prep'd by compressing the Schultze Pulver into grains of high density. *L.Gody, Traité des Matières Explosives, Namur, (1907)*, p 469.

Bangalore Torpedo (In Rohr gefüllte Reihenladung). See general section.

Bär (Bear). One of the experimental tanks (See under Panzer).

Baratol. See general section.

Barytique (Poudre). Under this title, *Daniel, Dictionnaire (1902)*, p 57 gives a mixture of 8 parts of black powder with 2 parts of Ba nitrate. It was used in the 1860's in larger caliber guns.

Baumwolle (Cotton). See under Cellulose in the general section.

Behelfsmine (Improvised or Makeshift Mine). Several land mines used by the Germans during WW II were made from items not specially designed for mines. For instance Behelfsmine W-1, A/P was improvised from captured 50 mm mortar shell. Several improvised land mines are described on pp 279-83 of TM 9-1985-2 (1953).

Beilodung. See Booster Charge and under Ignition.

Bellit (Bellite). One of the Sprengel type explosives. It was also used in England and other countries (See in the general section).

Bent Barrel. See Krummerlauf.

Beobachtungsgeschosspatrone (Observation Round). Fixed round with a projectile which had a core of HE, a fuze in the central portion and a phosphorus filler in the base.

The purpose of this round was to indicate the exact location of a hit by means of a puff of smoke (produced on ignition of the phosphorus).

Reference: *A.J.Dere, Ordnance Sergeant, Dec 1943*, pp 357-61.

Berclavite B. According to L. Médard, *Mém Artil Fr 22, 596(1948)*, the Berclavite B is one of the older aluminized explosives: Am nitrate 79.5, DNT 5, NG 5, collodion cotton 0.5, Al 5 and cellulose 5%; power by the French lead block expansion test (modified Trauzl test) is 125, taking the value for picric acid as 100.

Berger-Mischung (Berger Mixture). A smoke-producing mixture composed of 2 parts of zinc dust and 3 pts of hexachloroethane. *US War Dept Tech Manual, TM 36-566 (1944)*, p 23.

Bergmann-Junk Stability Test. See general section under Stability Tests.

Besetz oder Verdämmung (Tamping or Stemming). See general section.

Beschussprobe (Shooting Test, called in the U.S.A. Rifle Bullet Test). It is similar to the US test described in the general section. The German test is conducted according to *Stettlacher, Spreng- und Schießstoffe (1948)*, p 121 by firing a standard infantry rifle from a distance of 25 meters.

Biazzi Continuous Process for the Production of Nitroglycerin and Nitroglycol as used at the Dynamit A-G, Schlebusch Fabrik is described by *Drs W.B.Littler & D.B.Clapp, BIOS Final Rept 1842 (1946)* (See also under general section).

Bichel Explosives. Several compositions were patented by C.E.Bichel at the end of the last century, among them: a) NG 100 parts mixed with 10 p of sulfureted turpentine, b) Na nitrate 90-100 p mixed with 5 p of nitrocumene and 10 p of sulfureted tar oil, c) Am nitrate 86 p mixed with 8 p of TNT and 6 p flour or starch.

Reference: *Daniel, Dictionnaire (1902)*, pp 67-8.

Big Bertha Gun. See general section.

Bikarbit (Bicarbite). A type of permissible explosive containing large amounts of sodium bicarbonate and small amounts of NG, patented by W A S A -G before WW II. These explosives, although they contained a large amount of NaHCO₃ and a small amount of NG, were very easy to initiate. Mixtures containing as much as 95% NaHCO₃ and as little as 5% NG could still be initiated by ordinary blasting caps.

The following are the composition and properties of one of the bicarbites: NG 15, NaHCO₃ 50 and NaCl 35%; temp of explosion 400°, veloc of deton 2500 m/sec, heat of explosion 162 kcal/kg, d 1.35, Trauzl test value 30 cm for a 10 g sample, specific pressure 610 atm x l/kg, ρ -insance value (Kast) $B = d \times (\text{sp press}) \times (\text{vel of det}) \times 10^{-10} = 2.06$, gap test value (Detonationsübertragungprobe oder Schlagweitprobe) 40 cm, required for initiation at least a No 2 blasting cap; volume of gases evolved on explosion of 1 kg is 258 l at 20° and 760 mm Hg (H₂O in vapor phase). Composition of gases: CO₂ 46.1, H₂O 43.2, N₂ 9.2, and O₂ 1.5%.

Note: When a more brilliant explosive is desired, the amount of NG is increased, the amounts of NaCl and NaHCO₃ are decreased and some fuel and oxidizer are incorporated.

The following mixture may serve as an example of such an explosive: NC (slightly gelatinized) 40, N_2O_4 40, NaCl 12.5, wood meal 4.7 and NaNO_2 13.6%; temperature of explosion 1100°, velo. of deton. 1000 m/sec. d 1.4, Trauzl test value 121 cc for a 1 lb. sample, gap test value 30 cm; could be initiated by a No 2 blasting cap.

The materials were comparatively expensive, but they proved to be very safe for use in gaseous or dusty coal mines.

Reference:

C. Leyling & K. Dreikopf, Sprengstoffe und Zündmittel, I. Springer, Berlin (1936) lithographed by Edwards Bros., Ann Arbor, Mich., pp 145-146.

Biscuit Mixture A. See under Amatol 32.

Black Powder. See Schwartzpulver.

Blasting Caps See Detonators.

Blasting Gelatin. See Sprenggelatine.

Blätchenpulver oder "B" Pulver (Leaf Powder or Flake Propellant). According to Strohacher, Spreng- und Schiesstoffe (1938), p 41 it was prep'd by colloidizing a mixture of 3 parts of picricotton (Schieswolle) of N content minimum 13.1% and 1 p of soluble NC (Kollodiumwolle) of N content 13.6%. After incorporating into mixture 0.5% of the stabilizer (DPhA) and 1% of flash-reducer (Na oxalate), the mass was flaked and dried. The resulting flakes (which were 0.3 mm thick and had a surface of 1.3 mm²) were surface-treated with centralite and finely pulverized graphite in order to make them progressive burning.

Blitzoxid (Lead Azide) (I. A). See general section under Azides. It was used in Germany in some priming and initiating compositions.

I. A. was prep'd in Germany during WW II from sodium azide and lead nitrate in the presence of dextrin, in the following manner:

a) Fifty liters of water containing 1.5 kg of sodium azide was added slowly to 60 l of an aqueous solution containing 5 kg of $\text{Pb}(\text{NO}_3)_2$ and 0.15 kg of dextrin, preheated to 60° and stirred by air. After adding the first 5 liters, there was a pause of 5 minutes. The remaining 45 l. was added during the next 45 minutes, and the stirring was continued for 15 minutes, while the mixture was cooled by means of cold water circulating through the jacket.

b) Following this, the reactor was tipped onto a filter and the I. A. retained on a filter cloth made of horse hair. Suction was applied.


c) After rinsing the I. A. with several portions of water, it was placed on sheets of paper attached to frames and dried to a moisture content below 0.1%. Drying was done by blowing air for 48 hrs at 45-50° through the chamber containing the frames.

d) After cooling to 20°, the contents of each sheet were transferred to a graphited cardboard dish. The desired amount of dried I. A. was added to the same dish, which was then sent to detonator manufacturing plant. (Yield was about 3.3 kg per batch).

In order to destroy any I. A. remaining in the mother liquor, about 5 liters of nitric acid (5° Be) and about 1/2 l of conc'd Na nitrite soln were added per batch of I. A.

Reference: PB Rept 95,613 (1947), Sections O & P.

Notes: According to L.M. Sheldon, "Manufacture of Initiating Explosives, etc", CIOS Rept 27-38 p 3, the manufacture of I. A. at the Wolftrushausen plant of Dynamit A-G was conducted in a large, well polished, stainless steel, round bottom, cylindrical vessel, jacketed for circulation of heating, or cooling water or brine. Agitation was conducted by one centrally located shaft having 4 blades as shown on the attached drawing. This agitator could be raised or lowered as required to provide the most effective position for securing the desired mixing. For discharging the contents of the reaction vessel the agitator shaft was raised clear of the kettle which was then tilted by a control wheel located on the supporting framework. Stock solutions, 9 to 10 % by weight of lead nitrate and 2.7 to 3.0% by wt of sodium azide were kept in large vessels placed higher than the reactor in order to secure the flow of liquids by gravity. The correct volume for each precipitation charge was obtained by the use of calibrated glass bottles.



Flow rates were controlled by manually operated stopcocks. Before proceeding with precipitation the alkalinity of the sodium azide solution was checked by titrating with normal sulfuric acid soln. To be acceptable for use, 50 ml of azide soln required 8 to 10 ml of acid to reach the phenolphthalein end point. If the soln was not sufficiently alkaline some dilute sodium hydroxide was added to the stock soln and the titration repeated. Ordinary tap water was used for making the stock solutions.

In carrying out an individual precipitation, the volume of solution required to give 4.5 kg of actual lead nitrate (500 l when using a 9% soln) was drawn from the supply tank and measured in a calibrated glass bottle from which it was transferred to the reactor. (This amount of lead nitrate is about 18% in excess of that theoretically required). After heating the soln to about 50° some dilute sodium hydroxide was added until the soln became neutral to methyl orange, as determined by a spot plate test. After neutralization, 150 g of potato dextrin (which had previously been dispersed in warm water) was added to the soln.

The correct volume of sodium azide soln to give 1.5 kg of actual material (500 l when using a 3% soln) was measured in a calibrated glass bottle from which it was discharged through an adjustable stopcock into the reactor, while constantly stirring the soln and maintaining it at 50°. The rate of flow was controlled so that the total quantity of Na azide soln was added at a fairly uniform rate over a period of about 1 hour.

After addition of the Na azide soln had been completed, the agitator was stopped, the lead azide allowed to settle and the mother liquor decanted by tilting the vessel. After giving one dilution wash directly in the reaction vessel, it was tilted and the precipitate transferred by means of a jet of water onto a large cloth filter supported on a natural drainage filter. After rinsing the lead azide with three displacement type washes, the cloth was folded over the azide and the ensemble placed in a plastic bucket which was carried to the storage area. The yield was about 3.3 kg of dextrinated lead azide.

A sample of each batch was sent to the laboratory where the crystals were examined microscopically and compared with acceptable standards. Then part of azide was dried and its loading density was determined.

For destruction of unwanted I. A., it was treated successively with a 15% nitric acid soln and an 8% Na nitrite soln.

Note: Crystalline structure of I. A. is described by G. Mefferkorn in the Zeitschrift für Naturforschung 3a, 364 (1948).

According to V. Schneider, Sprengtechnik No 10-11, pp 185-196 (1952) and Explosivstoffe No 1-2, pp 1-10 (1953), technical I. A. (purity 92-94%) used in German Sprengkapsel A and Sprengkapsel B becomes dead-pressed if the loading pressure exceeds about 900 kg/cm² (about 12,600 psi) depending on conditions. Perfectly dry I. A. can stand higher pressures without being dead-pressed, but I. A. con-

forming granules in order to de-airpress. Crystal size also affects the pressure at which lead-pressing occurs.

Bleiblockausbauchung (Trauzische Probe) Bleiblockprobe auch **Trauzi** oder **Bleizylinderprobe** nach Trauzl (Trauzl Test) (Block Test) See general section and the books of Stettbacher.

Bleiblockprobe Same as Bleiblockausbauchungsprobe, which means Lead Block Expansion Test.

Bleiblockstauchungsprobe (Lead Block Compression Test) **Stauchprobe** See Coucher Test in the general section.

Bleimonoxyd (Lead Monoxide), PbO . See general section.

Bleinitrat (Lead Nitrate) See general section.

Bleioxyd, rotes oder **Bleioxyduloxyd** (Red Lead Oxide), Pb_3O_4 . See general section.

Bleioxydul (Lead Suboxide), Pb_2O . See general section.

Bleiperoxyd (Lead Peroxide), PbO_2 . See general section under Peroxides. Was used during WW I as one of the ingredients of fusehead compositions such as in the Spalt Fuseheads of high tension; PbO_2 33, Al (crushed flake) 33.5, special Mg alloy 33.5; (PB Rept No 63,877 (1945), 11 AV 51 and AV 48).

Bleipikrat (Lead Picrate) (L. P.). See general section under Picrates; was used in Germany for the preparation of ignition mixtures in fusehead manufacture. The following method was used for the preparation of lead picrate by the action of lead nitrate on picric acid:

Place 8 l of lead nitrate solution (containing 180 g per liter) into a small stainless steel vessel (V2A steel), similar in construction to those used in lead azide manufacture and provided with a wooden stirrer. Add 15 l of ice water so that the temp in the vessel is about 6°. Feed in gradually (within 5 minutes) with stirring, 15 l of picric acid solution containing 10 g/l A per liter. Add 7-8 l of cold water and allow to settle for 3 hours. Decant the liquor, transfer the slurry to a calico filter cloth placed over a Nutsch or large porcelain vacuum filter with sloping sides. After allowing the slurry to settle until the surface of the L. P. is just distinguished through the mother liquor, start the vacuum pump and let it run for 3-4 hours. Lift the calico filter and transfer the L. P. to a stainless steel carrying pot containing 10 l of 90-95% ethane¹ benatured with 2% of methanol, together with 500 ml of 10% aqueous lead nitrate solution. After thoroughly mixing the ingredients (by means of a wooden spatula), transfer the slurry back to the calico filter cloth on the Nutsch, allow to settle for about 1/2 hour and then operate the vacuum pump for 1 to 2 hours.

Note: The extent of the drying on the filter should be governed by the fact that the paste has to be soft enough to smear in a fairly thin layer on paper for subsequent drying.

Place the calico filter cloth containing the L. P. in a papier-mâché bucket and transfer it to the drying house. By means of a wooden spatula, smear the moist L. P. upon a double sheet of paper 2' x 3', placed on the cloth of a drying frame. Dry the material for 4 hours, starting at room temp and raising it to 40° and finally to 60°.

Note: Caking usually results if the temperature is raised too rapidly.

Transfer the Lead Picrate into papier-mâché containers (yield of dried material should be about 2.2 kg with 1% content about 62%), provided with rubber stoppers. Screen the material, by placing 300 g at a time, together with a rubber stopper (about 1 1/2" diam and 2" high) into a cylindrical sieve 18" diam by 6" deep, provided with a silk sieve cloth, 600 meshes per sq cm. Store the sieved material in stoppered papier-mâché or rubber containers until ready to use.

Note: After finishing the precipitation of the L. P., the vessel should be cleaned before being used again by stirring with 4 l of 5° be nitric acid and 100 l of water.

References:

- 1) G. Ashcroft et al, investigation of German Commercial Explosives Industry, B I O S Final Report No 833, Item No 2, London, H M Stationary Office (1946); PB Rept No 63,877 (1946), 1 AV 27
- 2) Anon, PB Rept No 95,613 (1947), Section D.

Bleiplattenprobe. See Lead Plate Test in the general section.

Bleisalpeter (Lead Nitrate). See general section, under Nitrates.

Bleitritrosorcinat oder **Bleistyphnat** (Lead Trinitrosorcinat or Lead Styphnat) (L. St.) **Blei Salz des Trizinis**, **Trizinat** oder **Tricinat**. See general section under Styphnic Acid and also the references listed below. One of the methods of prepn used in Germany during WW I was as follows: Trinitrosorcinat (TNR), called Trizin, 72 kg was stirred into 120 l of water containing 12 g of MgO until the TNR dissolved. Then the solution was diluted with water until it contained 2.4 kg TNR for each 40 l of solution. The resulting mixture contained magnesium trinitrosorcinat.

To 40 l of the above mixture, preheated to 60° and stirred in a vessel, was added gradually (during 20 minutes) 12.5 l of an aq solution containing 4 kg of lead nitrate. This gave lead styphnat. After allowing the mixture to stand and cooling it to 20°, the mother liquor was decanted leaving the ppt of L. St. As some L. St. remained in the mother liquor, it had to be destroyed. This was done by adding some sodium carbonate to which transformed the L. St. into Na styphnat and precipitated the lead as $PbCO_3$. After removing the $PbCO_3$, the remaining liquid was acidified with waste acid and the resulting styphnic acid reduced to a non-explosive triamine by means of iron filings (Ref 2).

According to Stettbacher (Ref 3), L. St. may be prepd by mixing the boiling solns of trinitrosorcinol (previously neutralized with Na carbonate) and lead nitrate.

According to Naoum (Ref 1), L. St. has been used as an initiating explosive in Germany since about 1920 when the so-called Trizinatkapseln (qv) were put on the market by the Rheinisch-Westfälische Sprengstoffe A-G.

Several types of initiating compositions used by the Germans during WW II contained L. St.

(See also under Primary and Initiating Compositions).

- 1) P. Naoum, Schiess- und Sprengstoffe (1927), p 186
- 2) PB Rept 95,613 (1947), Section N
- 3) A. Stettbacher, Spreng- und Schiessstoffe (1948), p 98.

Note: L. M. Sheldon, Manufacture of Initiating Explosives, etc., C I O S Rept, File No 27-38 (1945), pp 9-11 describes the method of manufacture of L. St. at Wolftratshausen Plant, Dynamit A-G:

- a) 120 kg of TNR was dispersed in 350 l of water and

20 kg of MgO was added. The mixture was heated to 60° and held for a short period until a solution was formed, before use the solution was filtered through a muslin cloth and then diluted to 1.0 l and allowed to settle for 24 hours during which time the temperature dropped to $25-30^\circ$.

In carrying out the actual precipitation, 80.4 l of 0.1% soln was decanted from the storage vessel and transferred to the precipitating vessel where it was heated to 60° . Then, 22.70 l of lead nitrate soln (31.0% or 31% by weight) was added over a period of 20-30 minutes maintaining the temperature at 60° during the entire addition period. As soon as all of the L.N. soln had been added the contents of vessel were cooled to 25° as rapidly as possible and the agitation was stopped in order to allow the L.St. to settle. After removing the mother liquor by decantation two dilution washes were given to the precipitate directly in the vessel. Then the product was transferred by means a stream of water onto a cloth filter where it was thoroughly rinsed using the same technique as for extruded L.A. The yield of L.St. was about 8 kg.

According to C.S. Livingston et al, CIOS Rept No 24-3, the following method of manufacture of L.St. was used at Troisdorf Plant, Dynamit A-G:

Into a stainless steel kettle of about 14 (British) gallon capacity (about 53.1 liters), provided with an agitator, were introduced 40 l of water, 2.4 kg of stypnic acid and 0.4 kg of magnesium oxide. The formation of magnesium stypnate developed heat, and when the temperature reached about $55^\circ C$, a solution of 4 kg of lead nitrate in 12.5 l of water was run in. The yield was 3.6 kg of L.St.

In all the above methods of manufacture of L.St. the vessels were similar to those used for the manufacture of L.A.

For the destruction of L.St. in the mother liquor, an excess of sodium bicarbonate was added and, after mixing thoroughly, iron filings followed by sulfuric acid were added.

Bleitrixinor. Same as Bleitritinitrosorcinat.

Bleizylinderprobe nach Trauzl (Bleiblockaustauchungsprobe). See Trauzl Lead Block Test in the general section.

"Blitzpulver". According to Stettbacher, Spreng- und Schiessstoffe (1948), p 99 it is one of the names for Nitrodiazobenzeneperchlorate, $C_6H_4(NO_2)N_2 \cdot ClO_4$, which is described in the general section under Diazobenzeneperchlorate.

Bobbinit. See bobbinit in the general section.

Bohrpatrone 02 (BhrPatr 02) (literally Drill Cartridge of 1902). A demolition charge consisting of 75 g of TNT used at the time of war for military pioneer work. It replaced a similar charge made of picric acid and called Bohrpatrone 88. Colver, High Explosives (1918), p 23.

Bohrpatrone 28 (Drill Cartridge of 1928). A blasting cartridge, described under Demolition Charge. According to TM 9-4985-2 (1953), p 277 the charge was used also in anti-personnel land mines such as Stockmine.

Bomb Containers. See under Containers.

BOMBE (Bomb). Table 3b gives the designations of some German bombs and their English equivalents.

Table 3b


| | | |
|------------|-------------------------------|--|
| BLZ | Blitzlichtzylindrische | Cylindrical photoflash bomb |
| BT | Bomben Torpedo | Torpedo bomb |
| KC | Kampfstoffzylindrische | Chemical cylindrical bomb |
| NIC | Nebelzylindrische | Cylindrical smoke bomb |
| PC | Panzerdurchschlagzylindrische | Armor-piercing (AP) bomb |
| PD | Panzerdickwandige | Armor-piercing (AP) bomb, thick walled |
| SA | - | High capacity (HC) bomb (Bomb of maximum blast) |
| SB | Sprengbombe | High-explosive (Demolition bomb) of high capacity |
| SBe | Splitterbeton | Concrete fragmentation bomb |
| SC | Sprengzylindrische | High-explosive cylindrical (General purpose) bomb |
| SD (klein) | Sprengdickwandige (klein) | Anti-personnel (Small) bomb |
| SD | Sprengdickwandige | High-explosive thick walled (Semi-armor piercing fragmentation) bomb |
| SP | Splitter | Fragmentation (Anti-personnel) bomb |
| ZC | Zementzylindrische | Cement, cylindrical bomb. |

Note: The two principal German HE bombs were SC and SB. The SC, or general purpose bombs, had loading factors of 50-55% and because of their destructive quality were used primarily for general demolition. These bombs were usually of three piece steel construction, with the nose being welded to a spherical body and the sheet steel or alloy tail being attached to the bomb body by screws or rivets. The SC bombs were not streamlined. The SD bombs, being either AP or SAP, had a loading factor of about 35% and, because of their penetrative qualities, were used primarily against ships or fortifications. The bombs were streamlined and had thicker walls than the SC. They were usually drawn or forged in one piece. A tail extension with a dummy fuze head was sometimes attached to give the bomb a more streamlined appearance.


Other bombs SA, SB, SBe, etc may be characterized as follows: The SA and SB bombs were thin walled with

loading factors as high as 80%. They were designed to give maximum blast effect. The SBa bombs had thick concrete walls reinforced with steel and their loading factor was about 20%. They were filled with a low power explosive and were used for the same purpose as SD's. The PC bombs were AP and used primarily against ships and fortifications. They were slightly streamlined with a heavy nose (hardened cast steel) and heavy walls (cast steel) with the thickness decreasing toward the base of the bomb. Their loading factor was about 20%. The PD bombs were thinner, longer, had thicker walls than PC's and their loading factor was about 15%. They were more penetrating than PC's. The BT was designed along lines similar to a torpedo except for the after section where there were three large tail fins. The missile was put into production during the last two months of the war, but was never used operationally. The ZC bombs, such as ZC 10 kg and ZC 50 kg were practice

BOMBS



BOMBS



bombs constructed from concrete. The **BLZ**, **KC** and **NbC** bombs resembled in appearance the **SC** bomb but had different fillings. The **SP**, fragmentation, A.P. bombs are not described in TM 9-1985-2 (1953)

The following bombs are described in the U.S. Dept. of the Army Technical Manual TM 9-1985-2, German Explosive Ordnance, Washington, D.C. (1953) p 1 to 124.

1) SC 50 kg Bi was filled with 24.4 kg of cast TNT, amatol or trialen (p 6)

Note: TM 9-1985-2 (1953) does not give the German equivalent of Bi but simply says that the bomb had a one-piece cast steel body machined; all the fittings were welded in place.

2) SC 50 kg Grade I - Ja, L, and Stabo were filled with 21 to 25 kg of cast TNT, powdered amatol or cast trialen (p 6)

3) SC 50 kg Grade II - JB, JC, J and J,2 were filled with 21 to 25 kg of TNT, amatol or trialen (p 7)

4) SC 250 kg - Types 1, 2, and 3. J, L, L,2, B and K were filled with 287 lbs of amatol, TNT, TNT and wax or wood meal and Al powder and naphthalene and Am nitrate (p 8)

5) SC 500 kg Grade III (K, L,2 and J) were filled with 220 kg of amatol, TNT or trialen. Bombs recovered with trialen filling contained also up to 500 cylindrical paper-wrapped pellets composed of RDX/Al/wax (p 9).

6) SC 1000 kg "Hermann" (C, L, and L,2) were filled with about 600 kg of amatol, TNT/Al/wood meal or trialen (p 9)

7) SC 1200 kg was filled with 631 kg of trialen.

8) SC 1800 kg "Satan" was filled with amatol, TNT or trialen (p 11)

9) SC 2000 kg was filled with 975 kg amatol (p 12).

10) SC 2500 kg "MAX" was filled with trialen or a mixture of amatol with RDX and Al powder (p 13)

11) SB 400 kg Kugel K - "Kurt" Apparatus was filled with 300 kg high explosive. It was a "skip" bomb designed to operate like a skipping stone over a smooth water surface for use against ships, power plants, lock gates, etc. (pp 14-16)

12) SB 1000 kg was filled with 735 kg RDX/Al/wax biscuits in a Trialen 106 matrix (p 17)

13) SB 1000 kg Parachute was filled with biscuits consisting of Am nitrate 51, Ca nitrate 31 and RDX 16% in matrix of DNB 48, RDX 15, and Am nitrate 37% (p 17)

14) SB 2500 kg was filled with 2400 kg amatol or Trialen 105 (P18)

15) SD 50 (D50, D50J, and D50L) were filled with 16.4 kg TNT (p 19)

16) SD 250 kg (D250, D250JB, D250L, and D250DL) were filled with 79 kg TNT (p 20)

17) SD 500 kg, SD500A and SD500E were filled with about 200 kg amatol or TNT/wax (p 22)

18) SD 1700 kg was filled with 730 kg of TNT or amatol (p 23)

19) PC 500 kg, D 500 E, and D 500 L were filled with about 75 kg of TNT, TNT/wax or amatol (p 24)

20) PC 1000 kg, FSAU was filled with 160 kg TNT/wax (p 24)

21) PC 1400 kg, FRITZ was filled with 300 kg of TNT, wax or trialen (p 25)

22) PC 1600 kg was filled with 230 kg RDX/Al/TNT mixture (p 26)

23) PC 500 kg RS was filled with 14 kg TNT (p 28)

24) PC 1000 kg RS was filled with 54 kg TNT (p 29)

25) PC 1800 kg RS was filled with 360 kg of TNT and trialen. One specimen had 3 blocks of NGu in the nose and 10 blocks of RDX/Al/wax in two cardboard cylinders

in the body (p 36)

26) PD 500 kg was filled with 32 kg RDX Al/wax in the body, associated with a nose filling block of NGu (p 31)

27) 0.5 kg A/P Parachute bomb contained 1 oz of an explosive (p 32)

28) 1 kg SD 1 Mortar contained cast TNT (p 33)

29) 1 kg SD1 FRZ contained amatol or granular TNT. The FRZ was a French bomb used by the Germans (p 33)

30) 2 kg "Butterfly" SD 2A and SD 2B was filled with 7.5 oz of cast TNT surrounded by a layer of Titaneous composition (p 34)

31) SB 3 kg contained 4 lbs of an explosive (p 35)

32) SD 4 kg III, (hollow charge) A.F. and V-Bohle contained 12 oz of cast TNT or 40.50 - TNT, RDX (p 36)

33) SD 10A Types I, II and SD 10 FRZ contained TNT or amatol (p 38)

34) SD 10C contained about 0.75 kg of an explosive (p 39)

35) 12 kg SC 10 Concrete contained 0.9 kg TNT (p 40)

36) SD 15 Converted Projectile contained hollow (shaped) charge explosive (p 40)

37) SBe 50 kg Concrete in earlier specimens contained TNT, and in all later bombs a naphthalene explosive mixture of low brisance (p 42)

38) SBe 250 kg Concrete contained TNT pellets and a mixture of Am nitrate with small amounts of wood meal and Al powder (p 43)

39) SA 4000 kg contained biscuits of RDX Al/wax in a matrix of 97.50 Amatol (P13)

39a) BT (Bomben Torpedo), 200 kg, 400 kg, 700 kg, and 1400 kg (p 44)

40) 2 kg Aircraft Towed Paravane was filled with a HE (p 46)

41) 1 kg, 1.3 kg, 2 kg and 2.2 kg Incendiary contained thermite as the incendiary and a HE as the burster charge (pp 46-50)

42) 50 kg Incendiary (Sprengbrand C 50) contained thermite as the incendiary and TNT as the burster charge (p 50)

43) 250 kg Incendiary (FLAM) contained an oil incendiary mixture and TNT as the burster charge (p 52)

44) 500 kg Incendiary (FLAM) contained a mixture of 70.30 - petroleum/benzene as the incendiary and TNT as the burster charge (p 54)

45) 50 kg Incendiary (Brand C 50 A) contained about 30 lbs of a mixture consisting of benzene 80, phosphorus 4 and pure rubber 10% (p 54)

46) 50 kg Incendiary (Brand C 50 B) contained about 77 lbs of white phosphorus (p 55)

47) 250 kg Incendiary (Brand C 250 A) Types I and II, contained a mixture of petroleum 87.7, polystyrene 1.7 and phosphorus 0.5% (p 56)

48) 50 kg Smoke (NC 50) contained a light grey smoke producing substance smelling strongly of camphor (p 58)

49) 50 kg Smoke Marker (NC 50 NC D, SEE) contained an unidentified smoke producing composition (p 58)





50) 250 kg Smoke (NC 250 S) contained a mixture of sulfur trioxide 60 and chlorosulfonic acid 40% (p 58)

51) Practice Bombs: SD 1, SD 2, ZC 10 kg Concrete, ZC 50 kg Concrete, FC 1000 RS EX, and ZC 250 kg Concrete are described on pp 59-65 of TM 9-1985-2


52) Parachute Flares: LC 10 Single Candle, LC 50 Single Candle, LC 50 F Ausf C Four Candles, LC 50 Ausf B, LC 50 F Ausf G, Mark C 50 FA, Mark 50 Kask Target Indicating, Mark S Types 1 & 2 and some others are described on pp 65-79

53) Smoke Flares Orange were used as wind direction

GENERAL BOMBS



OF THE BOMBS



HE high explosive
 MK Wax, MNB Magnesium
 NGC Nitroglycerine
 PC Percussion
 PD Powder
 SA Sulfur
 SC Sulfur
 ZC Zinc

HV-226 of Bloom and Voss was described in
 V. A. Bloom, Les Armes Secretes Alle
 (Paris, 1947).

High Explosive Train (one of the German HE trains
 used in World War II) consisted of the following parts:
 1. Electric primer. A layer of lead wire with a bead, which
 was fused to a plate made of lead, tellurium, cadmium
 and sulfur, fused after applying. In order
 to prevent the fuse from igniting on ignition of the bead
 the bead was surrounded with lead.

Delay composition for the delay element varied, de-
 pending on the desired delay time.

2. Delay up to 1 second contained black powder.
 3. Delay up to 14 seconds consisted of $KClO_4$ 10,
 $Cu(NO_3)_2 \cdot 3H_2O$ 10, $Fe(NO_3)_3 \cdot 9H_2O$ 10.
 As this mixture was heated to ignite from the head of the igniter, the follow-
 ing composition facilitated this operation; red lead
 20, SnO_2 20, carbonium 20%. In order to intensify the
 effect of the delay, the following booster composition
 was used: $KClO_4$ 50, Pb ferrocyanide 38, resin 6%.

4. Delay up to 30 seconds contained: $K_2Cr_2O_7$ 78.0,
 K_2CrO_4 6.1, Na_2O_2S wax 0.1% and were used
 in conjunction with the ignition mixture and booster,
 as described under (b).

5. Relay Two kinds were used: black powder, or the follow-
 ing mixture: $KClO_4$ 25-30, Pb SCN_2 40-50, NC 20, sulfur
 18%.

6. Detonator contained lead azide, sensitized with lead
 stannate.

7. Sub-booster consisted of a layer of PETN over PEIN-
 wax mixture contained in a cup, called the "gain". The
 gain was surrounded by a pressed P.A. ring with the
 remainder of the fuze pocket filled with pressed P.A.

Auxiliary booster consisted of pressed TNT pellet,
 which was placed in a brass container. An auxiliary
 booster was inserted to amplify the detonation even
 if the fuze contained explosives for charging, bonds,
 etc. The following were the principal explosives used in
 the fuze: PETN, PEIN wax, Amolol, Amonal, Cyclitol,
 Hexogen, Hexolite.

Main fuze fuze explosives: Atenben Troving Ground,
 etc.

Booster, Booster Charge, Gain (Initiation, Building,
Self-Action, Antipersonnel). The German booster was
 a cylindrical container of brass containing a gain filled
 with PETN, wax or L.A., PEIN wax or RDX wax and
 containing inside the forward end, a detonator filled with
 PEIN, PETN and a priming layer of MF for boosters
 filled with L.A. or with L.A. L.S. layer in other cases.
 The purpose of this detonator was to pick up the shock
 wave due to the explosion of the fuze detonator, to amplify
 the effect of the shock wave, and, in turn, to detonate the
 main booster charge. The powdered L.A. filling wax in brass
 containers, the PEIN wax and RDX wax fillings were in
 compressed form, i.e., respectively, pale pink and pale
 blue or light green.

The fuze charges examined are listed in Table 4
 (Ref. 22), Table 4 of the fuze charges examined
 during World War II (General, Dover, New Jersey (Ref 23))

Table 4

| Composition | Uses |
|-----------------------------|--|
| 94 15-PEIN Wax | 47 mm HE shell, 75 mm AP shell, 128 mm HE shell, 150 mm HE shell, 80 mm mortar bomb, HoC magnetic grenade, A/T rifle grenade, HoC rifle grenade and 210 mm HE rocket |
| 89 15-PEIN Wax | 75 mm HE shell, A/T rifle grenade |
| 88 15-PEIN Wax | 80 mm Mortar bomb |
| 87 15-PEIN Wax | 75 mm HoC shell, 80 mm HE mortar shell, 88 mm HE and HoC shell and 105 mm HoC shell |
| 91 9-PEIN Wax | 110 PAK 41 bomb, land mine |
| 92 8-PEIN Wax | 50 mm HE shell, 88 mm AP shell, 105 mm How shell |
| 85 15-PEIN pressed TNT | 47 mm AP shell |
| 95 5-RDX Wax | 21 lb HoC demolition charge |
| 96 5 1/2-RDX Wax | 88 mm AP shell |
| Tetryl (pressed) | 76.2 mm HE shell |
| TNT (cast), PETN-Wax core | 75 mm AP shell |
| TNT (pressed to about 1.45) | 47 mm AP and HE shells, land mine |
| Picric acid (pressed) | 105 mm HE shell, 150 mm and 210 mm anti-concrete shells, hand grenades, Panzerwurm (A/T trench mortar shell) |
| 40 60-tetryl TNT (pressed) | 40 mm HE shell, A/T mine |
| Black powder | A P mine |

Abbreviations: AP Armor-piercing, A/P Antipersonnel, A/T Antitank, HoC Hollow (shaped) charge, HE High explosive, How Howitzer, L.A. Lead azide, L.S. Lead styphnate, MF Mercuric fulminate, Np Same as PETN, P.A. Picric acid, PAK Antitank, PETN Pentacrythritol tetranitrate, RDX Cyclonite (Hexogen).

The following types of boosters are described in Ref 1:
 a. **Booster A** (Zdg A) consisted of an Al cylinder 2.95" long and .83" in diameter, closed at one end and filled with a pressed RDX/wax-92/8% pellet, density 1.61 and weighing 577 grains. The pellet was tinted blue by the ad-

dition of a small quantity of dye. A cavity was formed at the forward end to receive the detonator which contained 0.5 grains of RDX under 0.3 grains of I. A. I. St-58.8, 41.2% in an enclosed Al tube. A disc of Al with a central hole, held the detonator tube firmly in its cavity. The ensemble, held by a leather washer and an Al ring, completed the closure by being folded over the lip of the body.

b) **Booster B (Zdlg B)** consisted of an Al cylinder 4.7" long and .83" in diameter, closed at one end and filled with three RDX wax pressed pellets which were enclosed in two separate Al containers. The lower container had two RDX wax-92.8% pellets, density 1.59, each weighing 232 grains. The container was sealed by pressing the lip over two Al discs. The upper container held a single pellet of RDX wax (weighing 324 grains) and the detonator unit contg 6.9 grains of RDX under 5 grains of I. A. I. St-68.6, 31.4%. The container was closed by a perforated Al disc. The two containers were slid into the booster cylinder, and the whole assembly was retained in the booster body by a leather washer and an Al security ring, as in the Zdlg A.

c) **Booster C/98Np (Zdlg C/98Np)** consisted of an Al container filled with a PETN wax pellet. There were two sizes; a small size, 1.0" long and .8" in diameter, designated "KzZdlg C/98" and a large size, 3" long and .8" in diameter, designated "GrZdlg C/98". The first was used in smoke shells and the second in HE shells.

There were also boosters: **Zdlg C/98** (picric acid charge), **grZdlg C/98Np** (large C/98 Np booster), **kzZdlg 34Np** (short PETN charge booster), **Zdlg 36** (PETN charge in bakelite container) and **Zdlg 40** (PETN in cardboard container)

- 1) E. Englesburg, Ordnance Sergeant, May 1944, pp 319-20;
- 2) W.R. Tomlinson, Jr, Picatinny Arsenal Technical Report 1555 (1945), pp 9-10.

Bounding Mine. Same Type Mortar as antipersonnel Land Mines, Schrapnellminen, such as S-Mi 35 and S-Mi 42, briefly described under Landminen.

Bounding Type Mortar Shell, 80 mm, HE. According to an examination conducted at Picatinny Arsenal (Ref 1), this shell was constructed as follows:

The contour of the shell was, in general, of conventional mortar design, but the shell itself was in two parts, the division being at the forward edge of the bourrelet. In the nose (3) of the shell was assembled the German Mortar Shell Fuze Wgr Z 38 and the expulsion charge assembly (19). This was followed by the igniter tube (18), the detonator-booster assembly (4) and the HE filler (bursting charge). The base of the shell was provided with 12 fins of conventional design, an ignition cartridge and propellant increments. The body and fuze of the shell was 8 9/16" long and weighed 6.75 lbs when assembled. The length of the complete round (including the fin assembly) was 13.1" and the weight was 7.82 lb (See illustration on next page).

The shell was fired from mortar in the conventional manner but the functioning of the shell was different, as can be seen from the short description given below.

The impact of the fuze, or a sudden slowing up of the shell, resulted in the firing of the fuze primer. The flash from the primer ignited the igniter charge in the top of the expulsion charge assembly (19) in the forward end of the shell, and caused the burning of the propellant within the capsule. This separated the shell body and nose by shearing the set screws (16) which caused the body portion to be thrown upward or to bounce along the ground. A slight delay was possibly obtained by the gases from the expulsion charge (19) passing through the hole in the igniter tube (18), then expanding in the cavity below. An additional delay was obtained by means of the delay-detonator (12), the different elements in the delay-detonator being ignited in the order of their arrangement. Explosion of the detonator

caused functioning of the booster pellet (11), which in turn caused the functioning of the bursting charge of the shell.

This type of shell was particularly convenient for use over soft terrain such as swamplands. Where the shell would normally be buried prior to detonation, this design caused the shell, after deflection to burst in the air.

The compositions of the explosive components, as taken from Ref 2, are given below:

A) Ignition cartridge primer: a) upper charge: Ca silicide 59.4, NG lead 24.7 and Ba nitrate 15.9%; weight 0.023 g, b) lower charge: Ba nitrate 47, Pb styphnate 33 and Ca silicide 20%; weight 0.034 g

B) Ignition cartridge propellant: NC (N content 13.4%) 58.3, NG 59.0, centralite 0.8, graphite 0.8, total volatiles 1.0 and unaccounted 0.7%; weight 10.0 g; squares about 0.008" thick with length of side 0.637"

C) Projectile fuze primer: K chlorate 51, Sb trisulfate 44 and Hg fulminate 5%; weight 0.022 g

D) Projectile expulsion charge assembly: a) igniter cup weighed 0.12 g and consisted of celluloid with N content 8.7%, b) igniter weighed 0.050 g and consisted of K perchlorate 50, Pb thiocyanate 45 and NC 5%, c) black powder pellet weighed 0.17 g and consisted of K nitrate 77.5, charcoal 12.7 and sulfur 9.8%, d) expulsion propellant capsule weighed 3.1 g and consisted of celluloid with N content 8.7%, e) expulsion propellant charge weighed 12.5 and consisted of NC (N content 13.9%) 93.9, centralite 2.0, graphite 1.0; total volatiles 1.2, diphenylamine 0.3 and unaccounted 1.0%; form: conis 0.0352" long and 0.0409 diameter

E) Delay-detonator-booster assembly: a) washer consisted of phenol-formaldehyde impregnated paper, b) delay-detonator consisted of 0.10 g upper charge: red lead 74.7, silicon 17.8 and binder, of which there was 5.1% of "A" stage phenol-formaldehyde condensation product and 2.4% of "B" stage product, c) lower charge consisted of 0.225 g of Pb chromate 50.2, K perchlorate 24.5, silicon 24.8 and binder 0.8%, d) disc separating delay from detonator consisted of 0.038 g NC 70 and NG 30%, e) detonator consisted of 0.35 g upper charge Pb azide 50, Pb styphnate 30 PETN 10% and 0.25 g PETN as lower charge

F) Bursting charge of the shell consisted of about 380 g of TNT or of 65/35 Amatol (Am nitrate 65, TNT 35%).

G) A disc (15) serving as a gas check and consisting of 4.2 g Mg oxychloride, was placed at the bottom of the bursting charge.

References:

- 1) J.P. Wardlaw, Pic Arsn Tech Rept 1422 (1944)
- 2) E.F. Reese et al, Pic Arsn Chem Lab Rept 102 912 (1944).



"B" Pulver. See Blättchenpulver.

Brandbombe. An incendiary bomb containing white phosphorus either alone or in mixtures with highly combustible materials. The following types are described in TM 9-1985-2 (1953), pp 54-7:


- a) Brand C50A contained approx 30 lb of a mixture consisting of phosphorus 4, benzene 86, and pure rubber 10% (p 54)
- b) Brand C50B contained white phosphorus (p 55)
- c) Brand 250A, Types I and II contained the following mixture: petroleum 87.7, polystyrene 11.7 and phosphorus 6.9% (p 55)

(See also under Flammbomben, Incendiary Bombs and Sprengbrandbomben.)


Brandkissen (Self-Igniting Cushion) consisted of a 2' x 2' rubber-impregnated cheese-cloth pillow case filled with capsules containing aluminum-chloromethyl mixture (Merhyl



**BOUNCING TYPE
MORTAR SHELL
(80 mm HE)**



PRIMER ASSEMBLY



FUZE ASSEMBLY

**DETONATOR - BOOSTER AND
IGNITION TUBE ASSEMBLY**

| LINE NO | NAME OF COMPONENT | POUNDS |
|---------|--|--------|
| 1 | ROUND COMPLETE ASSEMBLY | 7.82 |
| 2 | CARTRIDGE IGNITION | .06 |
| 3 | IGNITION ASSEMBLY | .83 |
| 4 | PRIMER | .12 |
| 5 | EXPULSION CHARGE ASSEMBLY | .64 |
| 6 | IGNITION TUBE | .15 |
| 7 | DETONATOR-BOOSTER HOLDER | .08 |
| 8 | DETONATOR-BOOSTER ASSEMBLY WITH PAPER FILLER | .23 |
| 9 | BOUNCING CHARGE | .28 |
| 10 | INCREMENT, PROPELLANT | .02 |
| 11 | SHELL AS FIRED | 7.74 |

TABLE OF WEIGHTS

Stoff). A number of such cushions was placed on the runway of a landing field. It was hoped that on landing, the pressure of the wheels of the enemy's plane on the cushions would crush some of the capsules. The liberated Al chloromethyl would then ignite on contact with the air and destroy the tires and possibly the plane. In practice the idea was unsuccessful as ignition was too slow and the high landing speed of the planes usually carried them safely beyond the ignited cushions.

Reference: CLOS Rept 25-18 (1945), p 25.

Brandstoffe und Brandbomben. See Incendiary Compositions and Incendiary Bombs.

Brank (von Brank) in 1891-1892 patented several compositions suitable for use as propellants in small arms, such as: a) K chlorate 59.52, K bichromate 34.53, carnauba wax 5.95%, b) K chlorate 86.96, resin 13.04%. Daniel, Dictionnaire (1902), p 790

Brennstoff und SV-Stoff. See SV-Stoff und Brennstoff.

Brennzünder (Friction Type Igniter). See under Igniter

Brenzkatechin. See Pyrocatechol in the general section. Was used by Germans as an ingredient of liquid propellants, usually in combination with Visol 6 (vinylethylether), aniline etc. Methods of analysis of such mixtures are given in I G Farbenind A-G Report, Arch' Nr 110/20 g, Methoden zur Untersuchung von Brenzkatechin-Brennstoffen in Visol 6, 20 March (1944).

Brisanz (Brisance). See in the general section.

Brisanzmesser (Apparatus for Measuring Brisance). See under Brisance Tests in the general section.

Brisanzplattenbeschuss (Literally Brisance Plate Shooting). The plate test for brisance was conducted by exploding a charge of an explosive on the surface of a metallic plate such as lead, steel, or aluminum. The extent of the damage produced was compared with that caused by the same weight of a standard explosive, such as TNT. The tests are briefly described in the general section and also in A. Stettbacher, Spreng- und Schiessstoffe, Zürich (1948) pp 110-111.

Brisanzwert (B) (Brisance Value) is calculated by the method developed by Kast, as described in the general section.

Briska Kapsel (Briska Detonator). According to Stettbacher (Ref 1), Briska Kapsel No 8 contained a primary charge 0.30g of 4/6 mixt L A/L St (compressed at 400-500 atm) and as base charge 0.85 g tetryl, compressed at 2000 atm. Médard (Ref 2) gives for Briska detonator: 0.32 g of L A/L St mixture and 0.70 g of tetryl. The detonator case was made of aluminum because copper and brass are attacked by L A.

References:

- 1) A. Stettbacher, Schiess- und Sprengstoffe, J.A. Barth, Leipzig (1933) p 348
- 2) L. Médard, Mém poud 33, 339 (1951).

Brückenzünder (Bridge-wire Cap or Electric Blasting Cap). Various systems of German electric caps using resistance bridge wire are described in Beyling-Drekopf, Sprengstoffe und Zündmittel, Springer, Berlin, (1936) pp 179-216.

Brummbär (Grizzly Bear). A self-propelled mount consisting of 150 mm howitzer or heavy infantry gun on PzKpfw IV

(See also under Panzer)

"B" Stobmine. See under Landminen and also on pp 276- of TM 9-1985-2 (1953).

B-Stoff (LB-Stoff). A mixture consisting of hydrazine hydrate 92 and water 8%. Sp gr 1.032 at 20°. When mixed with T-Stoff (hydrogen peroxide) and K cuprocyanide as a catalyst the liquid ignites spontaneously. Since the heat of combustion of hydrazine hydrate is very low a new mixture known as C-Stoff was proposed (CLOS 30-115, pp 8 & 10). (See also C-Stoff, M-Stoff and T-Stoff).

"Buck" (Zünder). Chemical, crush-actuated type igniter. It is briefly described under Igniter.

Bullet (Geschoss oder Kugel). See Small Arms Ammunition

Bumble Bee. See Hummel.

Bursting Charge (Sprengladung, Sprengstoffgehalt, Sprengsatz) Table 5, given on next two pages, lists German bursting charges described in Picatinny Arsenal Tech Rept 1555, pp 3-8.

"Busy Lizzie". See under High Pressure Pump.

1, 2, 4 - Butanetrioltrinitrate. See general section under Butanetriol. According to Stickland et al, PB Rept 925 (1945), p 15, the substance was tried by the Germans during WWII as an explosive plasticizer for NC to replace NG, but apparently it was not adopted. Its properties were reported as follows: stable, less volatile than NG, calorific value 1.40 cal/g with H₂O in liquid phase. It proved to be only a medium good gelatinizer for NC.

C-2. Same as Wasserfall (Waterfall Guided Missile) [TM 9-1985-2 (1953), pp 219-23]

"C6". A mixture developed in Germany during WWII as one of the substitutes for TNT: Man-Salz 50, NaNO₃ 35 and RDX 15%. Its density of fragments was 39 m(TNT 40 m). It was suitable for loading shells and bombs. G. Gomer, PBL Rept No 85,160 (1946) p 25.

Cahusit (Cahuesite). A type of blasting explosive such as: a) K nitrate 70, wood meal 10, charcoal 6 and sulfur 12% (Ref 1); b) K nitrate 64.0, lampblack 7.0, sulfur 12.0 and wood pulp 17.0% and iron sulfate added 1.5% (Ref 2). These explosives were manufactured by the Deutsche Cahusit Werke A-G, Gnaschwitz. (See also Wetterammoncahusit under Wettersprengstoffe)

References:

- 1) Ullmann, Enzyklopädie, v 4 (1929), p 780
- 2) Thorpe's Dictionary, v 4 (1940), p 463.

Calcinite (Calcinite). A type of mining explosive contg large amounts of technical calcium nitrate [Ca(NO₃)₂ · 4H₂O], such as:

Calcinite 1. NG 15-20, Ca nitrate 32-36, Am nitrate 32-34, wood meal 13-17, liquid hydrocarbon (with flash point not lower than 30°) 0-2% (Ref 2).

Calcinite 2. NG 15-20, Ca nitrate 60-70, Am nitrate 0-15, charcoal and/or vegetable meal 6-15, liquid hydrocarbon (with flash point not less than 30°) 0-8% (Ref 2)

Marshall (Ref 1) gives for a Calcinite: NG 20, Ca nitrate 66 and charcoal 14%. Stickland (Ref 3) gives for Calcinite 1 manufactured at the Krümmel Fabrik of D A-G the following composition: NGc (nitroglycol) 6.0, DNT 4.8, TNT 7.2, Ca nitrate (tech) 38.0, Am nitrate 35.5, wood meal 8.0, caput mortuum dye (Fe₂O₃) 0.5%.

References:

- 1) Marshall, Explosives, v 3 (1952), p 109
- 2) Beyling-Drekopf, Sprengstoffe (1936), p 99
- 3) Stickland, PB Rept 925 (1945), p 69.

Table 5
Bursting Charges

| Charge | Uses |
|---|---|
| TNT (pressed) | 37 mm HE shell with PETN as a detonator base charge, 40 mm HE shell with 40/60-tetryl/pressed TNT booster, 47 mm AP shell with 85/15-PETN/pressed TNT booster and 150 mm HoC (shaped charge) rocket |
| TNT (cast) | 37 mm HE shell with PETN/wax booster, 47 mm AP or HE shells with pressed TNT boosters and 50 mm HE shell with PETN/wax booster; 50 mm Trench Mortar shell with 92/8-PETN/wax booster, 75 mm AP and HE shells with PETN/wax boosters; 76.2 mm AP shell with PETN/wax booster; Used in captured 76.2 mm HE shell with tetryl booster } Russian guns 80 mm HE shell with PETN/wax or pressed TNT booster, 88 mm HE shell and 105 mm AP shell and 105 mm HE shell with pressed P A or PETN/wax boosters; 105 mm How shell with 92/8-PETN/wax booster, 150 mm HE shell with PETN/wax booster, 150 mm and 210 mm A/C shells with PETN/wax boosters, 170 mm and 203 mm HE shells with PETN/wax boosters, 210 mm A/C and HE shells with PETN/wax boosters and 240 mm and 280 mm HE shells with PETN/wax boosters ; 500 kg and 1000 kg AP bombs; 1 kg, 2 kg, 10 kg, 250 kg and 500 kg Frag bombs and 10 kg, 50 kg, 250 kg, 500 kg, 1000 kg and 1800 kg GP bombs; 50 kg HE Inc bomb, Butterfly bomb and 50 kg A/C bomb, 50 mm, 80 mm and 105 mm Mortar shells; 27.5 lb and 110 lb Demolition charges, Egg and Stick hand grenades, Panzerwurfmine, A/P and A/T mines, and A/T and HoC rifle grenades 500 kg Frag bomb |
| 85/15-TNT/wax TNT with 5-10% wax | 88 mm AP shell with 92/8-PETN/wax booster, 47 mm HE shell and 150 mm A/C shell with P A booster, 500 kg, 1000 kg and 1400 kg bombs |
| 90/10-TNT/Al Picric acid (pressed) EDDN (Ethylenediamine dinitrate) RDX (Hexogen) 88/12-PETN/wax | 250 kg GP bomb and 75 mm HE Inc shell 75 mm HE shell with PETN/wax booster 105 mm AP shell with RDX/wax booster 42 mm HE shell 20 mm AP and HE shells with PETN detonator base charges, 28/20 mm HE shell and A/T rifle grenade 37 mm AP shell |
| 82/18-PETN/wax 87/13-PETN/wax 85/15-PETN/wax 90/10-PETN/wax | 50 mm AP shell with PETN/wax booster 20 mm HE shell and 37 mm AP shell 27 mm and 37 mm HE shells with PETN detonator base charges and 40 mm HE shell with 40/60-tetryl/pressed TNT booster |
| 91.5/8.5-PETN/wax PETN/wax/Al 90/10-RDX/wax | 20 mm HE shell, 50 mm AP shell, 80 mm Chem Mortar shell 20 mm HE Inc shell 75 mm AP shell with 94/6-PETN/wax detonator base charge and 88 mm AP shell with RDX or 96.5/3.5-RDX/wax detonator base charge |
| 94/6-RDX/wax EDDN/RDX 33/3/64-RDX/wax/Zn 75/1/19/5-RDX/wax/powd Al/solid Al ring pellet 30/70-PETN/TNT (pressed) 30/70-PETN/TNT (cast) 62/35.5/2.5-RDX/TNT/wax (pressed) 57.5/40/2.5-RDX/TNT/wax 57/40/3-RDX/TNT/wax 51/48/1-RDX/TNT/wax 48.5/48.5/3-RDX/TNT/wax TNT/KCl/wax 76/4/20-RDX/wax/Al with NGu nose pad | 75 mm HoC shell with 90/10-PETN/wax booster 105 mm AP shell with RDX/wax booster 20 mm HE Inc shell with PETN detonator base charge 20 mm HE Inc shell with PETN detonator base charge 37 mm AP shell with PETN detonator base charge 37 mm AP shell 37 mm HoC shell with 90/10-PETN/wax booster 75 mm HoC shell with 89/11-PETN/wax booster 105 mm HoC shell with PETN/wax booster 75 mm HE shell 150 mm HoC shell with 90/10-PETN/wax booster 210 mm A/C shell with P A booster 1800 kg AP bomb |

Table 5 (cont)

| | |
|---|--|
| 10/60-Amatol | 75 mm HE shell with PETN/wax booster, 76.2 mm HE, 80 mm, 88 mm, 105 mm, 120 mm, 128 mm, 150 mm and 210 mm shells, 210 mm and 300 mm Rockets; Panzerfaust with 90/10-PETN/wax booster |
| 15/65-Amatol | 75 mm HE shell with 94/6-PETN/wax booster; 80 mm mortar shell and land mine |
| 65/35-Amatol | 200 mm Mortar shell with PETN/wax booster |
| 30/70-Amatol | 75 mm HE shell with 89/11-PETN/wax booster |
| 60/40-Amatol | 88 mm HE shell with 87/13-PETN/wax booster and 500 kg AP bomb; 1 kg, 2 kg, 50 kg and 500 kg Frag bombs, 50 kg, 250 kg, 1000 kg, 1700 kg, 1800 kg and 2000 kg GP bombs |
| 50/50-Amatol | 50 kg, 250 kg and 500 kg GP bombs; A/T mine, land mine, wood land mine and 80 mm Mortar shell |
| 45/55-Amatol | Land mine |
| 80/20-Amatol | Egg hand grenade, rifle grenade |
| Triolen (C5/50/15 RDX/TNT/Al) | 1400 kg and 1800 kg AP bombs; 250 kg, 500 kg, 1000 kg, 1200 kg, 1800 kg and 2500 kg GP bombs |
| 60/30/5/2.5-NH ₄ NO ₃ /C ₁₀ H ₁₀ wood meal Al | 50 kg A/C bomb, 250 kg GP bomb |
| 35/50/15-NH ₄ NO ₃ LNB/RDX | 70 kg, Frag. bomb and 250 kg GP bomb |
| 35/50/15-NH ₄ NO ₃ /DNB/RDX, with nose filling of 54/40/17-NH ₄ NO ₃ /C a nitrate/RDX and TNT top off | 500 kg, Frag. bomb, 50 kg GP bomb, 250 kg GP bomb and 1000 kg Parachute bomb |
| RDX/comp B | 1000 kg Bomb |
| 70/20/10-NH ₄ NO ₃ /TNT Al | PAK 44 bomb with 90/10-PETN wax booster |
| 50/50-RDX/TNT | 35.5 kg Demolition charge, Panzerwurfmine, Magnetic grenade and rifle grenade |
| 60/40-RDX/TNT | Panzerfaust with PETN/wax booster |
| 69/17/11/3-NC/NG/wax/Mg salts | Land mines |
| TNT/DNAniline | Rifle grenades |
| Hexanite/TNT/Al | Sea mines |

Abbreviations: AA Antiaircraft; A/C Anticoncrete; AP Armor-piercing; A/P antipersonnel; A/T Antitank; GP General purpose; HE High-explosive; HoC Hollow charge; How Howitzer; NGu Nitroguanidine; P A Picric acid; PETN Pentaerythritol tetranitrate; Inc Incendiary; Comp Composition; Frag Fragmentation.
Note: According to M. Giua et al, Dizionario di Chimica UT-ET Torino, v2 (1949), p. 166 some German hand grenades were filled with a mixture of black powder 83, K perchlorate 12 and Al (powder) 5%.

Calciumkarbonat (Calcium Carbonate). See general section.

Calciumnitrat (Calcium Nitrate). See general section, under Nitrates.

Calciumsilizid (Calcium Silicide). See general section.

Colorific Value of a propellant was determined by firing a charge of 1.2 g in a calorimeter bomb of 12 cc capacity, the charge being ignited by means of a hot wire and a piece of uncolloided gun-cotton. The values obtained by this method were higher than those obtained by calculation.
Reference: CIOS 31-68, p 8.

Cannon. See Kanone and under Weapons.

Carbonit (Carbonite). A type of permissible explosive which may be considered as a straight dynamite with the temperatures of explosion lowered by the excess of carbon it contains. As a class, carbonites merge through the ammon-carbonites with the ammonium nitrate class of explosives.

The first carbonite appeared in 1885 (Michel and Schmidt inventors) and since then the carbonites have been modified several times. The composition which passed the Woolwich Test in England contained, according to Marshall (Ref 1): NG 26, K and Ba nitrate 33, wood meal 40.5, sulfuretted

benzene 0.25, Ca and Na carbonate 0.25%.

The composition of four German carbonites used after WW I given in Table 6 were described by Naoum (Ref 2) and Davis (Ref 3).

[See Table 6 on next page.]

(See also Kohlen-Carbonit under Kohlen-Sprengstoffe and Extra-Carbonit).

References:

- 1) Marshall, I (1917) pp 375 & 492
- 2) Naoum, Nitroglycerin, Baltimore (1928), pp 401-2
- 3) Davis (1943), pp 352-353.

Cartridge (Patrone in fixed ammunition; Kartusche in semi-fixed ammunition); Cartridge Case (Patronehulsc; Kartuschhulsc). German cartridge cases for small arms ammunition were of conventional design and drawn either from sheet brass (Cu 72, Zn 28%) or from sheet steel, copper-plated on both sides (Ref 1, p 357). German artillery cartridge cases of pre-WW II were made of brass but since 1942 the majority of cases were made of sheet steel, copper-plated on both sides. Later in the war the so-called wrapped steel cartridges were produced. Cartridge cases were employed in all German artillery ammunition (fixed and semi-fixed) and there was no ammunition corresponding to the American "separate-loading". The case was chiefly employed to reinforce the breech block and to seal the gases generated by the propellant. Although in fixed ammunition the cartridge case served the purpose of protecting the propellant charge, in many of the semi-fixed rounds the propellant charge was

Table 6
Carbonites

| Composition (%) and properties | Carbonit | Carbonit I | Carbonit II | Carbonit Extra |
|--------------------------------|----------|------------|-------------|-----------------|
| NO ₂ | 25.0 | 25.0 | 30.0 | 35.0 |
| Collodion cotton | - | - | - | 0.3 |
| K nitrate | 30.5 | - | - | 25.5 |
| Na nitrate | - | 30.5 | 24.5 | - |
| Ba nitrate | 4.0 | - | - | 4 |
| Spent tan bark | 40.0 | - | - | - |
| Meal | - | 39.5 | 40.5 | 34.7 (tan meal) |
| K bichromate | - | 5.0 | 5.0 | - |
| Na carbonate | 0.5 | - | - | 0.5 |
| Density | - | - | 1.10 | 1.20 |
| Heat of Explosion, kcal/kg | 576 | 536 | 602 | - |
| Temperature of Explosion °C | 1874 | 1666 | 1639 | - |
| Velocity of Detonation, m/sec | 2443 | 3042 | 3850 | 4070 |
| Trauzl Test (10g sample) | 235 cc | 240 cc | 258 cc | - |

larger than the cartridge case and therefore the case did not give complete protection to the charge (Ref 2)

The following cartridges, both German and captured from conquered countries, are briefly described in Ref 3:

A. Fixed Artillery Ammunition include:

- 20 mm Mauser and Oerlikon; used on various 2 cm guns and some machine guns
- 30 mm; used in 3 cm Solothurn Aircraft Cannon
- 37 mm; used in 3.7 cm Pak, 3.7 cm Flak, 3.7 C/30 (Naval) and 3.7 cm Polish Pak guns
- 40 mm; used in 4.0 cm Flak 28
- 47 mm; used in 4.7 cm Czech and 4.7 mm Austrian Böhler guns
- 50 mm; used in 5 cm Pak and 5 cm KwK 38 guns
- 75 mm; used in various 7.5 cm guns
- 75.2 mm; used in captured Russian 7.62 cm guns
- 76.5 mm; used in 7.65 cm captured Austrian, Czech and Yugoslav guns
- 88 mm; used in 8.8 cm Flak 18, Flak 36, Flak 37 and Flak 41 as well as various 8.8 cm Pak guns
- 100 mm; used in 10 cm K 17, and K 18 guns and various 10 cm FH

B. Semifixed Ammunition includes:

- 75 mm; used in 7.5 cm FK and 7.5 cm FH
- 105 mm; used in 10 cm K 17, K 18 and various FH
- 122 mm; used in some 12.2 cm captured Russian guns
- 128 mm; used in 12.8 cm Flak 40 and Pak 44 guns
- 150 mm; used in 15 cm K 18, K 39, sFH 13, sFH 18 and other weapons
- 152 mm; used in 15.2 cm captured Russian guns
- 155 mm; used in 15.5 cm captured French and Polish guns
- 170 mm; used in 17cm KiMrs Laf
- 194 mm; used 19.4 cm French Railway Gun
- 203 mm; used in 20 cm K (E)
- 210 mm; used in 21 cm Mrs 18 and lgMrs 18
- 240 mm; used in 24 cm ThBrK(E) and Czech sK
- 280 mm; used in K5(E) and other guns
- 353 mm; used in 35.3 cm HMI

C. Small Arms Ammunition includes:

- 6.35 mm pistol cartridges
- 7.65 mm pistol cartridges

c) 7.92 mm rifle and machine gun cartridges

d) 9 mm machine gun cartridges

e) 13 mm Solothurn cartridge


f) 15 mm Mauser cartridge

Note: Some of the 13 mm and 15 mm ammunition have sometimes been considered as artillery ammunition


Designations: C Construction (Pattern); (E) Eisenbahn (Railroad); F Feld (Field); FH Feldhaubitze (Field Howitzer); FK Feldkanone (Field Cannon); Flak Antiaircraft; H Haubitze (Howitzer); K Kanone (Cannon); K(E) Kanone Eisenbahn (Railroad Gun); KiMrs Laf Kanone ins Mörser Lafette (Gun in Mortar Mounting); KK Kasemattenkanone (Casemate Gun); KwK Kampfwagenkanone (Tank Gun); l leicht (light); lg lang (long); lFH light Field Howitzer; lgMrs Long Mortar; M Mark or Model; Mörser (Mortar); Pak Antitank; s schwer (heavy); sK Heavy Gun; ThBrK(E) Theodor Bruno Kanone, Eisenbahn (Theodor Bruno Gun, Railroad).

(See also Ammunition, Bullet, Grenade, Small Arms Ammunition and Steel Ammunition).
(References are given on the next page).

**SEMI-FIXED
CARTRIDGE CASE**



FIXED CARTRIDGE CASE



References:

- 1) A. J. Dere, Ordnance Sergeant, Dec 1943, pp 357-61
- 2) E. Englesburg, Ordnance Sergeant, May 1944, pp 321-2
- 3) Anon, Technical Manual TM 9-1985-3 (1953), pp 540-44.

Cartridge Cap Compositions examined at Picatinny Arsenal and listed in the Pic Arsn Tech Rept 1555 (1945) p 30 are as follows:

- a) M F 52, K chlorate 23, Sb trisulfide 20, abrasive 5%
- b) M F 25, K Chlorate 37, Sb trisulfide 30, glass 8%.

Cartridge Case Percussion Primer (Low Explosive Train or Propellant Train) (Zündpatronensatz). The compositions in Table 7 were taken from Picatinny Arsenal Technical Report 1555, p 15.

Cartridge Cases, Steel (Patronenhülse Stahl). Due to the shortage of copper many types of German cartridge cases were made of steel. Brief descriptions of their methods of manufacture are given in the following CIOS Reports: 26-74, 27-36, 31-53 and 31-54.

Cascade Flame Bomb (Mark 50 Kaskade) is briefly described under Pyrotechnic Anti-Pathfinder Devices.

Cellulol (Celludin or Camphrosol). See Plastol

Centralit (Centralite) is a type of organic derivative of N,N'-diphenylurea developed beginning in 1906 at the Zentralstelle für wissenschaftlich-technische Untersuchungen zu Neubabelsberg. Following are compounds suitable for use as stabilizers:

- Controlit I (Mollit I) (Ethyl centralite) N,N'-Diethyl N,N'-diphenyl-urea.
Controlit II (Mollit II) (Methyl centralite) N,N'-Dimethyl-

N,N'-diphenyl-urea

Controlit III (Methylethyl centralite) N-Methyl-N'-ethyl-N,N'-diphenyl-urea.

All three centralites are described in the general section. The first two compounds were used in Germany and other countries primarily as stabilizers for propellants. When used in amounts exceeding the requirements for a stabilizer (such as above, about 1%), centralites act also as gelatinizers for NC and probably, at least in part, as flash reducers (See also under Propellants).

References:

- 1) A. Stettbacher, Schiess- und Sprengstoffe, Barth, Leipzig (1933), p 197
- 2) Kast-Metz, Chemische Untersuchung, Vieweg, Braunschweig (1944), p 165.

Table 7

Cartridge Case Percussion Primer Compositions.

| Composition % | Uses |
|---|---|
| 48/52-Ba nitrate/L St | 7.92/13 mm HE shell |
| 35/37.5/21.5/6.5-KClO ₃ / Sb ₂ S ₃ /M F /abrasive | 20 mm AP Inert Chge shell, 20 mm HE shell, 50 mm AP & AP HV shell, 88 mm HF and Mech time fuze shell |
| 43/24/24/9-KClO ₃ /Sb ₂ S ₃ / M F / abrasive | 37 mm AP and HE shells and 105 mm HE Howitzer shell |
| 30 24/35/11-M F /KClO ₃ / Sb ₂ S ₃ /glass | 37 mm HE shell |
| 28/31/26/15-KClO ₃ / Sb ₂ S ₃ /M F abrasive | 47 mm AP, AP HV and HE shells |
| 32/11-L St /NC lacquer | 50 mm AP, AP HV and HE shells and 75 mm AP and I shells |
| 28/34/32/6-M F /KClO ₃ / Sb ₂ S ₃ / glass | 50 mm HE shell |
| 22/40/38-M F /KClO ₃ /Sb ₂ S ₃ | 76.2 mm AP shell |
| Pb picrate/NC/charcoal/KNO ₃ | 150 mm and 210 mm Rockets (Wurfgranaten) |

Abbreviations: AP Armor piercing; HE High-explosive; HV Hyper-velocity; L A Lead azide; L St Lead styphnate; M F Mercuric fulminate; NC Nitrocellulose; Chge charge; Mech Mechanical. (See also Primers).

Zentralstelle für, etc. See Zentralstelle für wissenschaft-techn Untersuchungen.

Centrifugal Casting of Gun Barrels is described in CIOS Repts: 29-39 and 31-46.

Cheddite (Cheddite). Chlorate and perchlorate explosives invented in France but also used in Germany and other countries (see under French Explosives and in the general section).

Chemical Warfare (Chemischer Krieg, Gaskampf, Gaskrieg) and Chemical Warfare Agent (Chemischer Kampfstoff). Although the Germans did not use any of the poison gases or liquids during WW II, as they did during WW I, quite a number of such substances, and some of them extremely toxic, were prepared and were ready for use. The most dangerous among them were the Trilons (q.v.).

L.W. Bateman, in CIOS Rept 32-13 (1945), pp 20-2, describes several Chemical Warfare Weapons manufactured by the Maschinen-Fabrik Peterson, Oldenburg. Some of the weapons were filled with toxic mixtures based on DM (Adamsite), as for instance: DM 43.2, Am perchlorate 28.5 and urea resin syrup 28.3%. This mixture was initially liquid but became solid 2 hours after being prepared. Another mixture known as **A-Pulver** consisted of DM, NC and diphenylamine in various proportions. Several other mixtures, such as APM 30, APM 49 and Q 192 are mentioned by Bateman, but the compositions are not given.

Chemische Beständigkeitsproben (Chemical Stability Tests). Various tests used for explosives and propellants are described in the book of Kast-Metz, *Chemische Untersuchung der Spreng- und Zündstoffe*, Vieweg, Braunschweig (1944) and also in the general section.

Chemischer Zünder "Buck". See Chemical Igniter under Igniter

Chemisch-mechanischer Zünder. See Chemical-Mechanical Igniter under Igniter.

Chemisch-Technische Reichsanstalt (CTR), vormals Militärversuchsanstalt (Government Chemical-Technical Institution, formerly Office of Military Research). A scientific institution located in Berlin and devoted to problems of the Armed Forces (Wehrmacht). Its work included research on ammunition, explosives, liquid fuel, military equipment etc. The Reichsanstalt, before WW II, published the journal called *Jahresbericht der Chemisch-technischen Reichsanstalt*.

Reference: Dr H.W. Adam, Picatinny Arsenal; Private communication (1954).

Chlorate Explosives. See Chloratsprengstoffe.

Chloratit (Chloratite). A type of chlorate blasting explosive, such as listed in the Table 8

Table 8

| Components and some properties | Chloratit 1 | Chloratit 2 | Chloratit 3 |
|---|-------------|-------------|-------------|
| Na chlorate and/or K chlorate | 70-72 | 73-75 | 83-91 |
| Vegetable meal | 1-2 | 1-2 | 0-4 |
| TNT and DNT | 18-20 | 18-20 | - |
| Paraffin | 3-4 | 3-4 | - |
| Nitroglycerin | 3-4 | - | - |
| Liquid hydrocarbons (flash point not less than 30°) | - | - | 5-12 |
| Oxygen Balance | +3.0% | +1.9% | - |
| Lead Block Expansion | 290 cc | 280 cc | - |
| Lead Block Crushing | 20 mm | 19.5 mm | - |
| Sensitivity to Initiation (requires at least) | No 3 Cap | No 1 Cap | - |
| Gap Test (using 25 mm cartridges) | 8 cm | 8 cm | - |
| Velocity of Detonation | 5000 m/sec | 4300 m/sec | - |
| Density of Charge | 1.57 | 1.46 | - |
| Heat of Explosion | 1250 cal/g | 1280 cal/g | - |
| Temperature of Explosion | 3645° | 3700° | - |

Note: One of the chloratites 1 was called Gesteins-Koronit T 1, one of the chloratites 2 was called Gesteins-Koronit T 2 and one of the chloratites 3 was called Miedziankit.

References:
 1) P. Naoum, *Schiess- und Sprengstoffe* (1927), p 131
 2) Marshall, 3 (1932), p 112 3) A. Stettbacher (1934), p 314
 4) Beyling-Drekopf (1936), p 97 5) F. Weichelt, *Handbuch der gewerblichen Sprengtechnik*, C. Margold, Halle/Saale (1953), p 35.

Chloratsprengstoff (Chlorate Explosives). Mixtures based on chlorates, such as Chloratit, Gesteins-Albit, Gesteins-Koronit and Miedzi.

The chlorate explosives were invented in France and used under the name of Cheddites.

References:

- 1) R. Escalles, *Chloratsprengstoffe*, Veit, Leipzig (1910)
- 2) P. Naoum, *Schiess- und Sprengstoffe*, Steinkopf, Dresden (1927), pp 124-132
- 3) A. Stettbacher, *Schiess- und Sprengstoffe*, Barth, Leipzig (1933), pp 309-315
- 4) C. Beyling-K. Drekopf, *Sprengstoffe und Zündmittel*, Springer, Berlin (1936), p 96
- 5) A. Stettbacher, *Spreng- und Schiesstoffe*, Rascher, Zürich (1948), pp 90-1.

Chlorobromomethane. See Feuerlöschmittel CB.

Chrom-Ammonit (Chrome-ammonite). A type of coal mining explosive used before WW I: a) Am nitrate 70.0, K nitrate 10.0, TNT 12.5, vaseline, or paraffin 0.5, chrome-alum 7.0%; b) Am nitrate 63.25, K nitrate 17.5, collodion cotton 9.25, vaseline or paraffin 0.5, chrome-alum 9.5%. [See Thorpe's Dictionary, v 4 (1940), p 554].

Chrome Plating of Gun Barrels. Experiments on the plating of tubes up to 88 mm caliber were conducted during WW II by the firm of Heinrich Reining GmbH, Enger (Westfalen). The thickness of plating ranged between 0.012 and 0.035 mm. No information is available as to outcome of the experiments CIOS 32-64).

Closed Cycle Diesel. See under U-Boat Walter.

Closed Vessel Testing. According to CIOS 31-68, pp 12-16, closed vessels were used for the following purposes:

- a) The development of new propellants
- b) Studies of particular properties of propellants
- c) Obtaining data for ballistic calculations.

Tests designed for the first two purposes were carried out mainly at the Düneberg factory of Dynamit A-G, while those for the 3rd purpose were made at the Essen factory of Krupp. A certain amount of closed vessel testing of small arms propellants was done in the DWM (Deutsche Waffen- und Munitionsfabriken) research laboratory at Lübeck.

Cold Extrusion Process (Kaltspritzen) (literally cold-squirting) as used during WW II by the Germans in the manufacture of ammunition and weapons is briefly described in the following PB Report prepared in the period 1945-1948 by the Heintz Manufacturing Co, Philadelphia Pennsylvania: Nos 39371, 96704 and 96704s (See also Cold Extrusion in the general section).

Colored Smoke (Buntrauch). The bulk of the work on the development of dyes suitable for use in colored smokes was done by the IG Farbenindustrie. The pamphlet "IG-187r" of the Office of Technical Services gives a list of these dyes.

The following references describe some German colored smokes and smoke signals:

- 1) W.T. Annasovich & E.C. Stawick, "German Smoke Signals", PB Rept 49467 (1944)
- 2) H.J. Eppig, "Chemical Composition of German Pyrotechnic Smoke Signals", PB Rept 16728 (1945)
- 3) J. Kanegis, "Colored Smokes", PB Rept 102,500 (1951) (Included are several tables of colored smoke compositions and some references) (See also Colored Smokes in the general section).

Colored Smoke Ammunition. See under Signal Device and under Smoke Projectile.

Commercial (Industrial or Mining) Explosives (Gewerbliche Sprengstoffe oder Zivilsprengstoffe) Predating WW II.

The first application of explosives (black powder) in mining was made, according to Peyling and Drekopf, in 1627 when an Austrian, Caspar Weindl, blasted some ore at Oberliferstollen in Hungary. The next mine blasting was done in 1632 near Claustahl, and then in 1645 near Freiburg, Germany. The first blasting in England took place in 1670. From that time on the blasting of coal and ores spread to other countries. Black powders of various compositions were used exclusively until about 1835 when A. Nobel introduced NG dynamites (See under Swedish Explosives).

Among the commercial explosives used in Germany prior to WW II, the following may be listed: Ammonal, Ammonchlorat, Ammongelatine, Ammonit, Bikarbit, Calcinit, Cheddrit, Chloratit, Detonit, Donarit, Dynamit, Gelotit, Gesteins-Albit, Gesteins-Koronit, Gesteins-Persalit, Guhrdynamit, Leonit, Miedziankit, Wetterdetonit, Wetterlignosit, Wetternobelit, Wetterosalit, Wetterwasagit, Wetterwestfalit, Wetterzellit and others.

These explosives are described briefly in this (German) section of the book according to their alphabetical order. Some of the typical explosives used during WW II are given in Table 9 under Commercial Explosives of WW II.

It is interesting to note that some of the commercial explosives used before WW II were manufactured from surplus military explosives and propellants. Among these explosives were: Energit, Nitroglycerin Powders No 1 and No 2, Pikrit (or Silvit), Pyrolit No 1 and No 2 and Triwestfalit.

References:

- 1) P. Naoum, Nitroglycerin and Nitroglycerin Explosives (translated from the German by F.M. Symmes), Williams & Wilkins, Baltimore (1928)
- 2) A. Stettbacher, Schiess- und Sprengstoffe. J.A. Barth, Leipzig (1933)
- 3) C. Beyling & K. Drekopf, Sprengstoffe und Zündmittel, J. Springer, Berlin (1936)
- 4) A. Stettbacher, Spreng- und Schiessstoffe, Rascher, Zürich. (1948).

COMMERCIAL (INDUSTRIAL OR MINING) EXPLOSIVES (GEWERBLICHESPRENGSTOFFE) OF WW II. Among the German industrial (mining) explosives, the most important were dynamite-type explosives containing various amounts of a product obtained by nitrating a mixture of glycerin and glycol (usually 60/40). The nitration of glycerin and glycol is described briefly under Nitroglycerin.

There were generally two types of mining explosives: the gelatinized type (such as some donarites) and the powder type (such as calcinit and some donarites).

Following is a short description of their methods of manufacture:

A) Gelatin type explosives

Procedure

a) A weighed amount of collodion cotton (previously dried at 50-60° in a rack dryer to a moisture content of about 1% and then cooled) was introduced into a kneading pan which contained the required amount of liquid DNT, or other liquid nitrocompound, maintained at a temperature of 15-20°. The mass was stirred all the while with a long handled wooden spatula. The kneading pan was a flat vessel made of copper plate with an outer jacket of aluminum for warm water heating. This op-

eration was followed by addition of a weighed amount of NG-nitroglycol mixture, while continuing the hand stirring. The resulting gelatin was allowed to stand for 1 hour.

Note: For Am nitrate-type explosives, the plasticity was sometimes controlled by adding a solution of "gelose".

b) The pan was removed to another building where it was placed under the outlet funnel of a sieve through which the usual solid components of dynamites (such as Am or Na nitrates, TNT, wood meal, dye, etc.) were fed. These components were previously pulverized and dry blended in another building. While the addition of the solid ingredients took place, the mass in the pan was stirred by means of a planetary stirring mechanism, which could be lowered or raised as desired. Kneading time was usually about 20 minutes.

Note: Several types of mixers (blenders) were used, such as the Dreiswerke, Wetzig, McRoberts and a modified Werner-Pfleiderer.

c) The thoroughly kneaded mass of gelatin and of solid components was removed by a wooden hand spatula into wooden transport boxes to be carried to the cartridgeing plant.

Note: German permissible explosives were usually white in color, while the non-permissible were colored red by the addition of caput mortum (Fe₂O₃) in the mixing stage.

d) Cartridgeing was done either by fully automatic machines (such as the system of Niepmann & Co., Gevelsburg) or by semi-automatic machines (such as the system of Breusing). The Breusing machine (made entirely of brass) consisted of a conical casing through which passed a horizontal feeding screw. The gelatinized mass was introduced into the machine by hand through the filling funnel. A paper cartridge was placed at the narrow end of the conical casing. After a cartridge was filled, it was removed by hand and the open end crimped. The diameter of a cartridge was 22, 25 or 30 mm. After packing these cartridges into a box (36, 25 and 20 cartridges per box, respectively), the box was wrapped in paper and dipped in paraffin. For shipping, 10 boxes were packed in a case.

e) Permissible explosives were mechanically sheathed with an "active sheath" consisting of NG 12, NaCl 33, and NaHCO₃ 55%. Originally, the composition of the sheath was NG 15, NaCl 35, NaHCO₃ 50%. The sheath weighed 55 g and the cartridge itself 70 g.

b) **Powder type explosives:** To this type belong explosives which contained small amounts of NG; such as 4% no collodion cotton and were pulverulent. The mixing of the components was done in a tiltable type Werner-Pfleiderer blender which consisted of a brass trough provided with two horizontal brass stirring rollers running in opposite directions.

Procedure:

a) The weighed amounts of the solid components (such as Am, Ca or Na nitrates, TNT, wood meal, dye etc.) were mixed in a Werner-Pfleiderer blender and then the liquid DNT, NG, NGe etc., were added and the mass kneaded for 15 minutes.

b) The kneader was then tilted and the mixture discharged into wooden casks to be taken to the cartridgeing plant.

Note: In the case of explosives such as Calcinit 1, the mass could be immediately cartridgeed, but with Donarit 1, the mass had to be left overnight in storage before cartridgeing.

c) Cartridgeing was usually done by fully automatic

machins of the Niepmann type. Diameter of cartridges for Calcinit I was 28 mm, while for Donarit I it was 36 mm. The finished cartridges of Donarit I were dipped in paraffin and packed in boxes (25 per box). The cartridges of Calcinit I were not paraffined but were packed

directly in boxes (32 per box) and then the boxes were dipped in paraffin.

Table 9 gives some typical German Commercial Explosives manufactured before and during WW II.

Table 9

| Ingredients and some properties | Ammonit I (1932) | Donarit | Dynamit I | Gelatine -Donarit I (1936) | Wetter -Donarit A (1936) | Wetter -Nobelit A (1932) | Wetter -Nobelit B (1932) | Wetter -Wasagit | | Wetter -Westfalit A (Permissible) |
|--|------------------|---------|-----------|----------------------------|--------------------------|--------------------------|--------------------------|-----------------|------|-----------------------------------|
| | | | | | | | | A | B | |
| NG(Nitroglycerin) | 4.0 | 4.0 | 63.0 | - | 6.0 | 25.4 | 29.2 | 30.0 | 27.8 | 4.0 |
| NG ^o (Nitroglycol) | - | - | - | 22.0 | - | - | - | - | - | - |
| NC(Nitrocellulose) | - | - | 2.0 | 0.8 | - | 0.6 | 0.8 | 1.0 | 0.7 | - |
| TNT(Trinitrotoluene) | 6.0 | 12.0 | - | 5.0 | 2.0 | - | - | - | - | 0.5 |
| DNF(Dinitrotoluene)(liquid) | 6.0 | 2.0 | - | 6.0 | - | 2.0 | - | - | - | 0.5 |
| Am nitrate | 80.2 | 79.8 | - | 55.0 | 72.0 | 52.0 | 26.5 | 29.5 | 30.5 | 80.5 |
| Na nitrate | - | - | 26.7 | 10.0 | - | - | - | - | - | - |
| wood meal | 3.5 | 2.0 | 8.0 | 1.0 | 2.0 | 1.0 | 0.5 | - | 0.3 | 1.5 |
| Rock salt(NaCl) | - | - | - | - | 18.0 | 36.5 | 40.0 | 39.0 | 39.5 | 13.0 |
| Caput mortum (Fe ₂ O ₃) | 0.4 | 0.2 | 0.3 | 0.2 | - | - | - | - | - | - |
| Gelose (Carragan moss) | - | - | - | - | - | - | - | 0.5 | 0.7 | - |
| Talc | - | - | - | - | - | - | - | - | 0.5 | - |
| 50% Ca nitrate solution | - | - | - | - | - | 2.5 | 3.0 | - | - | - |
| Trauzl Test, cc | 370.0 | - | 385.0 | 380.0 | 220.0 | 205.0 | 185.0 | - | - | - |
| Lead Block | 17.5 | - | 24.0 | 20.0 | 10.5 | 16.5 | 14.5 | - | - | - |
| Compression, mm | - | - | - | - | - | - | - | - | - | - |
| Veloc of Deton, m/sec | 4800(at d=1.12) | - | 6350 | 6150 | 3000(at d=1.10) | 5750 | 5650 | - | - | - |
| Cartridge Density, g/cc | 1.07 | - | 1.53 | 1.53 | 1.06 | 1.66 | 1.69 | - | - | - |
| Gap Test, cm | 6.0 | - | 10.0 | 1.0 | 8.0 | 6.0 | - | - | - | - |
| Charge Limit, g | - | - | - | - | 600 | 700 | 700 | - | - | - |
| Oxygen Balance % | +0.06 | - | +3.0 | +3.68 | +10.4 | -4.08 | +6.15 | - | - | - |
| Heat of Explosion, kcal/kg | 996.0 | - | 1291 | 1029 | 516 | 642.0 | 568.0 | - | - | - |
| Gas Volume, l/kg | 904.0 | - | 603.0 | 806.0 | 772.0 | 536.0 | 500.0 | - | - | - |

Note: The composition of sheaths used with some of these explosives are given under Active Sheath.

References:

- 1) O.W.Stickland, General Summary of Explosives Plants, PB Rept 925 (1945), p 69
- 2) R.Ashcroft, et al, Investigation of German Commercial

Explosives, H I O S Final Rept 833, Item 2

- 3) R.Ashcroft, et al, Investigation of German Commercial Explosives, PB Rept 63,877 (1946), pp A 1/8 and A 1/11.

Complete Round of Artillery Ammunition. See under Granate

Composition A (Comp A) A mixture of RDX 90-97 and Montan wax 10-3%, similar in properties to Comp A used in the USA during WW I and described in the general section. German uses of Comp A were in boosters, sub-boosters and as a filler in some grenades and shaped charges. (See also Filler No 86, No 91 and No 92).

Reference: Allied and Enemy Explosives, Aberdeen Proving Ground, Md, (1946), p 122.




Composition B (Comp B) (Cyclotol) A mixture of RDX and TNT in various proportions similar to Comp B described in the general section. Some of the compositions contained small amounts of wax. Comp B was used by Germans during WW II for filling shaped charge shells, grenades, rockets, and some demolition charges. Pellets of Comp B embedded in TNT were used in 4000 kg bombs.

(See also Filler No 18 and Filler No 95).



Reference: Allied and Enemy Explosives (1946), p 24.

Composition C. A plastic explosive similar in properties


CONTAINERS





AB 42 Container



AB 210-1 Container



AB 500-1 Container



AB 1000-2 Container

to Group C described in the general section and the PIB, used by the British during WWI. The German version is described here as "Plastit".
Reference: Allied and Enemy Explosives (1916), p 127.

Concrete Ball Mine. See 278 of TM 9-1985-2 (1953) and also under Landmine.

Connecting (or Intermediate) Composition. See under Gasless Detonators (Electric).

Containers Carried by Planes. German containers may be subdivided into (1) those intended to carry their contents safely to earth and (2) those designed to scatter their contents before impact.

The first type served to deliver supplies to specific locations and generally consisted of a compartment to house the supplies and a parachute to bring the container safely to earth. No explosive opening devices were incorporated.

The second type could be subdivided into dropable and nondropable (retained in the aircraft) containers and also according to content into bomb container, flare container or combination bomb-flare container.

Dropable containers were fitted with fuzing and opening devices intended to release the missiles after a predetermined time of fall from the aircraft. Some of these were open devices which held a cluster of bombs or flares by means of securing bands, whereas others were closed containers in the shape of a bomb.

Nondropable containers were intended to be used repeatedly and they were constructed to carry and scatter a great number of small incendiary bombs. Their release mechanism permitted desired spacing of the bombs in flight. These containers could be jettisoned if necessary.

The following bomb and flare containers are described in TM 9-1985-2 (1953), pp 93-120:

- 1) BDF 10 Cluster Container carried five SC 10 or SD 16A bombs (pp 93-5)
- 2) AB 23 SD 2 Container carried 23 SD 2 bombs (pp 95-7)
- 3) AB 24T SD 2 Container carried 12 SD 2 bombs (pp 96-8)
- 4) AB 36 Container carried 36 1 kg or 24 2 kg bombs (p 98)
- 5) BSK 36 Three-Sided Container carried 36 1 kg or 12 2 kg bombs (p 98)
- 6) AB 42 Container carried 42 1 kg incendiaries (pp 99-100)
- 7) AB 70-1 or Mark 70S Container carried 3 Mark S flares (pp 100-1)
- 8) AB 70-3 Container carried 22 SD 2 bombs (pp 101-3)
- 9) AB 70D-1 Container carried 50 SD 1 bombs (p 104)
- 10) AB 250-1 Container carried 96 SD 2 bombs (pp 104-6)
- 11) AB 250-2 Container could carry 224 SD 1 bombs, or 144 SD 2 bombs, or 17 SD 10A bombs, (pp 106-7)
- 12) AB 250-3 Types I and II Container carried 108 SD 2 bombs (p 107)
- 13) AB 250 KZ Boden Container could carry 19 parachute flares and three SD 2 bombs (p 108)
- 14) Mk 250 LK Flare Container carried 41 single candle parachute flares (pp 108-9)
- 15) Mk 250 BK carried 25 modified red flares and three SD 2 bombs (pp 108-9)
- 16) BSR 360 Container carried 320 1 kg incendiary bombs (p 110)
- 17) BSB 700 carried 702 1 kg incendiary bombs (p 110)
- 18) BSB 1000 carried 570 1 kg incendiary bombs (p 110)
- 19) AB 500-1 Container could carry one of the following fillings: 37 SD 10A bombs, 392 SD 1 bombs, 184 1 kg incendiary bombs, 28 SD 10FRZ bombs or 116 2 kg incendiary bombs (pp 111-13)
- 20) AB 500-3A Cluster Adapter could carry 4 SD 50 kg or SK 70 kg French bombs, as well as 50 or 100 kg French bombs (pp 113-15)
- 21) AB 500-1B Container carried 28 SD 10FRZ bombs (p 115)
- 22) ABB 500 Container carried 133 1 kg incendiary bombs (p 116)
- 23) "Streubrand C 500" Container (lit Scatter Incendiary Bomb) carried 1200 green celluloid incendiary boxes immersed in water (p 117)
- 24) Mk 500 "Boden" Container carried 9 or 15 single

candle flares or 6 SD 2 bombs (p 117)

25) AB 1000-2 Container carried one of the following fillings: 629 1 kg bombs, 246 1 kg and 234 2 kg bombs, or 372 2 kg bombs (p 119) (See illustrations).

Continuous Methods of Manufacture of Explosives. See Kontinuierliche Verfahren.

Cordite Charge Casings. According to CIOS 31-68, p 8, propellant tubes in smaller guns (caliber below about 200 mm) ran the full length of the charge and there was only one section, while for larger guns the charge was in two sections, the *Hauptkartusche* (main charge) and the *Vorkartusche* (forward charge). Both these charges were in silk bags placed in the cartridge called *Kartusche* which was not rigidly attached to projectile. Any additional charges of propellant were called *Teilladungen* (increments).

For the largest of these guns the silk bag was found to be insufficient protection for the *Vorkartusche* and it was bound with a brass strip. Owing to a shortage of brass these strips were replaced in the later part of WW I, by a large cordite cylinder surrounding the charge. The casing was made by bending a sheet of cordite into a cylindrical shape and by joining the edges using a NC solvent. Each end of the cylinder was closed by a cap made of the same material.

Coronit (Coronite). An early blasting explosive used in stone quarries and ore mines: Na chlorate 72, NG 3, TNT with DNT 20, paraffin 4, vegetable meal 1%. Has been replaced by Percoronite (qv). [J. Bebie, Manual of Explosives etc, MacMillan N Y (1943), p 52].

"C" Process of Precision Casting of Metals. See Shell Mold Process.

Cracking of Sulfuric Acid. See Lurgi Spaltanlage.

Cresylit (Cresylite). Same as Trinitrocresol.

C-Staff (C-Staff) A liquid rocket fuel consisting of 50/50 mixture of hydrazine hydrate and methanol. The combination of this fuel with concentrated (80%) hydrogen peroxide (called T-Staff) was used in the rocket fighter plane Heinkel 173 at the end of WW I.

Reference: J.G. Tschinkel, Chem & Eng News 32, 2506-7 (1954) (Propellants for Rockets and Space Ships).

Note: According to CIOS Rept 30-115 (1945), pp 8-10 & 13, the C-Staff consisted of hydrazine hydrate 30, methanol 57 and total water 13%. Water was incorporated in order to reduce the combustion temperature in rocket chambers. To this mixture was added K cuprocyanide (0.6 g of Cu per liter of C-Staff) serving as catalyst. The mixture had a specific gravity 0.915 at 20°C. On mixing C-Staff with T-Staff, the liquid ignited spontaneously and the gaseous products served for driving the aircraft rocket units, the guided missiles and the ATO units.

The following plastic materials were reported to withstand the action of C-Staff very well: polyvinylchloride (without softener), polyamide and Buna S. Polyethylene was good, while polyvinylchloride with tricresylphosphate as softener was not suitable. (See also B-Staff, M-Staff and T-Staff).

CTR. See Chemisch-Technische Reichsanstalt.

Cyclonite. See Hexogen.

Cyclotol. See Composition B.

Dahmen Explosives were invented by J. von Dahmen of Austria and used in Austria, Belgium, Germany and probably England. In Germany they were manufactured by Castrop Sicherheits-Sprengstoff A-G at Castrop (Westfalen):

- a) Am nitrate 92.0, phenanthrene 5.5, K bichromate 2.5%
- b) Am nitrate 30, sawdust 35, K bichromate 5, NG 30%.

Reference: J. Daniel, Dictionnaire, Dunod, Paris, (1902), pp 791-2.

Dahment A (Dahmente A) One of the Favier type explosives: Am nitrate 90.8 K dichromate 2.2, naphthalene 6.5, curcuma 6.5, vel of deton 3680 m/sec at d 1.02 [Marshall, v 2 (1917), p 493]

Decomposition Number of Hydrogen Peroxide is the ratio of the concentration of peroxide after being heated at 65°C for 24 hours to the original concentration (CIOS 30-115, p 9).

Decoppering Agent (Entkupferungsmittel). According to Pic Arsn Tech Rept 1555 (1945), p 36 the following compositions were found in some German ammunition captured during WW I.

- Tin 60, lead 38, bismuth 1.8 and antimony 0.2%; used in some 37 mm HE shells
- Tin 61 and lead 39%; used in some 40 mm HE shells.

Note: According to E.Englesburg, The Ordnance Sergeant, May 1944 the usual German decoppering agent consisted of a lead wire wrapped around the propellant bag or placed on top of it. Upon deflagration of the charge the wire formed a brittle alloy with the copper of the rotating band, and this alloy was rubbed off by the inner surface of the gun barrel. When the next charge containing no decoppering agent was fired, the shell shattered the brittle alloy, thus clearing the gun tube.

Deep Bonding Process. See Tiefbinder Verfahren

Deflagration Temperature Test (Verpuffungs-Probe). See Ignition or Explosion Temperature Test.

Delay Compositions (Verzögerungsverbindungen). A brief description of such compositions is given in the general section.

Shortly before WWI, the Germans developed gasless delay compositions suitable for electric detonators. These mixtures consisted of powdered potassium permanganate (KMnO₄) and antimony (Sb). Following is a brief description of the method of preparation as conducted at the Troisdorf plant:

Procedure:

The dry crystalline K permanganate was ground in a special mill (called Kolloplex) to a particle size of about 0.006 mm. The antimony, received at the plant in a fairly finely divided state, was ground, without previous drying or other treatment, in a special mill (called Schwingmühle). The resulting powder was separated in an air elutriator into fine (grist size under 40 microns) and coarser fractions. The coarser fraction was placed on a vibrating sieve containing 16,900 meshes per cm² and the fraction retained on the sieve was used as coarse Sb. For the preparation of quick burning mixtures the fine Sb was used, while for slow mixtures the coarse material was more suitable. For instance a mixture of 36% fine Sb with 64% KMnO₄ loaded into No 10 delay element (qv) burned in 3.5 to 4.5 seconds, while the mixture of 36% coarse Sb and 64% KMnO₄ burned in 6.5 to 7.5 seconds. With a lower content of Sb and a higher content of KMnO₄ the burning time was longer. In order to obtain a composition with a desired delay, the coarse Sb was blended with the fine material.

Following is an example of the calculation for preparing a delay composition with a desired delay:

Suppose that it is necessary to prepare 80 kg of delay composition consisting of 36% Sb and 64% KMnO₄ which would burn for 4.85 sec in a No 10 delay element. The time of burning of coarse material is 7.50 sec and of the fine 3.50 sec.

If the "rectangle method" is used for computation (as is customary in Germany and some other countries of Europe) the calculation will be made by setting up the data shown below:

$$\begin{array}{r} 7.50 \\ 4.85 \\ 3.50 \end{array} \quad \begin{array}{r} 1.35 \\ \dots \\ 2.65 \end{array} \quad \begin{array}{l} \dots \text{Xkg (coarse Sb)} \\ \dots \\ (80-X) \text{kg (fine Sb)} \end{array}$$

In this configuration 1.35 is the difference between 4.85 and 3.50 and 2.65 is the difference between 7.50 and 4.85 seconds.

From the above, X may be calculated as follows:

$$X = \frac{1.35 \times (80-X)}{2.65} = \frac{1.35 \times 80 - 1.35X}{2.65} = \frac{108}{2.65} - \frac{1.35X}{2.65}$$

$$2.65X = 108 - 1.35X \text{ or } X = \frac{108}{4} = 27 \text{ kg (coarse)}$$

The amount of fine material is then (80-X), or (80-27)= 53 kg.

After thoroughly mixing 27 kg of coarse Sb with 53 kg of fine Sb, a small sample consisting of 36 parts of mixed Sb and 64 pts of KMnO₄ was prep'd and tested in a No 10 delay element. If instead of the desired time of 4.85, 5.15 sec was actually obtained, then this Sb mixture would need to be corrected by adding some fine Sb (3.50 sec). The amount of fine Sb to be added was calculated using the "rectangle" method as described above and a small sample of new, corrected, mixture was prepared. If the burning time in a No 10 delay element was exactly the desired 4.85 sec, the total batch consisting of 36% of "corrected" Sb and 64% of KMnO₄ was blended and pelleted. The pellets were ground and screened using sieves of 225 and 961 meshes per cm². The material which passed the 225 mesh sieve and was retained on the 961 mesh sieve was removed to storage while the material which was retained on the coarser sieve was reground and rescreened as above. The fine material (dust) which passed through the 961 mesh sieve was saved for adding to compositions considered to be too slow burning.

Before commencing to load a delay element (qv) with the above prep'd mixture, it was tested as follows:

- Moisture content. A weighed sample of a delay mixture (5-10g) was heated for 2 hours at 110°. If the loss of weight exceeded 0.2% the entire batch of delay composition was dried for several hours at 50° in a steam heated oven before it was loaded into delay elements
- Particle size of Sb. A weighed sample of a delay mixture was leached in a Gooch-type crucible with hot water to remove the KMnO₄ and the particle size of the dried weighed Sb powder was determined (Refs 2 and 3)

Note: The method for determination of particle size is not described in the references given below.

A different type of delay composition consisting of NC, red lead (Pb₃O₄) and silicon was used for the 200 mm HE mortar bomb. The composition in the sleeve was: NC 3.9, red lead 75.5 and silicon 20.6%, while in the pellet it was: NC 2.7, red lead 72.0 and silicon 25.3% (Ref 1)

References:

- W.R. Tomlinson Jr, Pic Arsn Tech Rept 1555 (1945), p30
- R. Ashcroft, B I O S Final Rept 833, H M Stationary Office, London (1946), Item 2, pp A3/7 to A3/12
- Anon, PB Rept 93,613 (1947) (Manufacture of German Detonators and Detonating Compositions).

Delay Element: (Verzögerungskörper). The elements used

during WWII consisted of metallic sleeves (of Al, Cu, brass, or coppered Fe) loaded with "gasless delay composition" (qv) consisting of powdered KMnO_4 , 64 and Sb 30%. The sleeves had an inside diameter 3.30 to 3.45 mm and an outside diameter of 6.45 \pm 0.02 mm. The length (L) of the sleeves when using brass was as follows:

| | | | | | | |
|--------------------------|------|------|------|------|------|------|
| Delay in sec L. in mm | 1 | 2 | 3 | 4 | 5 | 6 |
| | 5 | 5.5 | 8 | 10.5 | 13 | 15.5 |
| Delay in sec L. in mm | 7 | 8 | 9 | 10 | 11 | 12 |
| | 18.5 | 21.2 | 24.2 | 27 | 29.5 | 32 |

Loading of the sleeves was done by means of a 70 ton hydraulic press at pressures of 250 kg/cm². Details of the method are given in Ref 2, section F.

The above delay elements were used in electric detonators, described briefly under Detonators (Electric).

References

- 1) R. Ashcroft, B.I.O.S. Final Rept No 833, HMSO, London (1946)
- 2) Anon, PB Rept No 95 613 (1947), Sections F & G.

Demolition Charge (Sprengladung oder Sprengkörper) The following charges were examined during WWII by U S Ordnance Dept establishments:

- a) Bohrpatrone 28 (Blasting cartridge pattern 1928). A cartridge 3.9" long and 1.2" diameter, consisting of 3 1/2 oz of TNT or P A wrapped in waxed paper
- b) Sprengpatrone 28. A cartridge 4.1" long and 1.4" diam., consisting of P A wrapped in varnished paper
- c) Sprengkörper 28 (Demolition block pattern 1928). A block 2 3/4 x 2 x 1 1/2" consisting of 7 oz of TNT or P A wrapped in waxed paper
- d) Sprengkörper 28 consisting of two blocks of TNT, total wt 7 oz placed in a bakelite container 3 x 1.8 x 2.2"
- e) Sprengbüchse 24 (Demolition block in container, pattern 1924). A block of TNT or P A weighing 2 lb 3 oz placed in a zinc container 7.9 x 2.9 x 2.2"
- f) Sprengbüchse 24. A block of 90/10 - PETN/Wax weighing 2 lb 3 oz
- g) Geballteladung 3 kg (Concentrated charge 3 kg). The demolition charge consisted of several blocks of TNT or P A with a total weight of 6.5 lb, placed in a zinc container (7.7 x 6.5 x 3") provided with carrying handle
- h) Geballteladung 10 kg. Same as above except that it contained 22 lb TNT. The size of zinc container was 10 3/8 x 7 5/8 x 5 3/4"
- i) 12.3 kg Demolition Charge. A triangular block of 27 lb RDX/TNT in a seamless steel container.
- j) Plastit. A block of plastic explosive RDX/Oil weighing 1 lb 1 1/2 oz
- k) 300 g Hohlladung (Hollow charge). A shaped charge of a HE, size 3 1/2" high and 2.8" diameter
- l) 400 g Hohlladung. A shaped charge consisting of 12 oz of PETN/Wax in an aluminum case 3.1" high and 2.8" in diam
- m) 12.5 kg Hohlladung. A shaped charge consisting of 28 lbs (with a container) of TNT in a sheet iron case 8.1" high and 11" diameter
- n) 13.5 kg Hohlladung. A shaped charge consisting of 21 lb 3 oz (without a container) of 50/50 - RDX/TNT in a mild steel container 9" high and 13 1/2" diameter
- o) 50 kg Hohlladung. A shaped charge consisting of

110 lb (with a container) of TNT in a sheet iron case 10.2" high and 20" diameter, provided with a carrying handle

p) 500 g Hlafthohlladung (Magnetic antitank hollow charge). A shaped charge of a HE weighing 1 lb 1 1/4 oz

r) 3 kg Hlafthohlladung. A shaped charge consisting of 1 lb 50/50 - RDX/TNT mixture in a metal container 7.7" high and 6.2" diameter

s) 3.6 kg Hlafthohlladung. A shaped charge consisting of 2 1/4 lb TNT in an aluminum container.

References:

- 1) Picatinny Arsenal Technical Rept No 1555 (1945), p 31
- 2) U S War Dept Technical Manual FM 5-25 (1945), GP 129-132
- 3) Dept of the Army Field Manual FM 5-25 (1954), pp 196-7.

Density of Fragments Test. See Fragments Density Test.

Derne Mining Association Testing Station. See under Galleries, Testing, in the general section.

Detonationsdruck (Blast Pressure). See general section.

Detonationsfähigkeit (Ability to Detonate or Sensitivity to Initiation). The value is usually expressed by the smallest numbered standard cap required to initiate the explosive under test. For instance, in Naoum's book Schiess- und Sprengstoffe, 1927 p 121, it is said that in order to initiate Ammonit 2, a No 3 cap is required, while for Ammonit 1 and 5, a No 1 cap suffices. This means that Ammonit 2 is less sensitive to initiation than are ammonites 1 and 5. The same test is used in Italy.

Detonationsgeschwindigkeit (Velocity of Detonation). See general section.

Detonationsübertragung; Schlagweite (Transmission of Detonation, Striking distance). Also called "Sympathetic Detonation". The test is similar to the Gap Test described in the general section. (See also Four Cartridge Test).

DETONATORS (Detonatoren); BLASTING CAPS (Sprengkapseln); Igniters (Zündern). A short description is given in the general section. A. Stettbacher, (Ref 1) defines detonators (Detonatoren) as reinforced blasting caps which are designed to initiate explosives which are difficult to detonate by means of ordinary blasting caps.

The following military detonators were examined at Picatinny Arsenal during WWII and described in Ref 4, p 30:

Detonator R contained 4 grains of 75/25-L A /L St mixture over 6.9 grains PETN.

Detonator T contained 3.9 grains of 42/58-L A /L St mixture over 10.8 grains of tetryl in an Al cap. Both detonators were used in HE hand grenades.

Some of the captured German detonators in fuzes (some times called gaines) examined at Picatinny Arsenal during WWII are listed in Table 11.

Following are the principal current commercial detonators and blasting caps:

Sprengkapsel A consists of an Al shell, 11 mm long, 4.36 mm in diam filled with a 6 mm layer of PETN weighing 0.11 g (base charge) and a 3 mm layer, weighing 0.16 g of 80/20-L A /L St mixture, called in Germany the "Mischsatz" (primer mixture). Both the primary and secondary charges were press-loaded at 860 kg/cm² (Ref 6)

**Table 11
Detonators**

| Designation | Composition (%) | | | Uses |
|----------------|--|---------------------|--------------------|---|
| | Upper charge | Intermediate charge | Lower charge | |
| Gain A | L. A 59, L. St 41% | RDX | RDX 92, wax 8% | Not indicated |
| Gain B | L. A 69, L. St 31% | RDX | RDX 92, wax 8% | " " " |
| Gain Model 40 | L. A / L. St | - | PETN 87, wax 13% | " " " |
| Detonator Gain | M F | - | Tetryl 49, TNT 51% | Land Mine |
| " | L. A 82, Sb ₂ S ₃ 7 and abrasive 11% | - | PETN | 37 mm HE and 50 mm HE shells |
| " | L. A with cover charge of black powder | - | PETN/TNT | 47 mm AP RN shell |
| " | L. A 14.4 and L. St 85.6% | - | PETN | 47 mm AP shell |
| " | L. A 55, L. St 45% | - | PETN | Some 50 mm, 75 mm, 80 mm, 88 mm and 105 mm shells |

Sprengkapsel B consists of an Al shell, 17 mm long, 7.98 mm in diam, filled with a 6 mm layer of PETN weighing 0.40 g (base charge) and a 4 mm layer, weighing 0.40 g of "Mischsatz" (primary charge) (Ref 6).

Note: In both above caps the L. A was of technical grade, containing 92-94% of PbN₆ and not more than 0.35% moisture.

Some of the current commercial caps are described in Ref 7. The so-called "Normal copper cap No 8" (Kupfer-Normalsprengkapsel No 8) consists of a Cu shell, 6.8 to 6.9 mm in diam, press-loaded at 480 kg/cm² with 0.7 g TNT (base charge), placed in two layers each weighing 0.35 g and with 0.55 g of M F as the primary charge. The same Ref 7 compares the properties of flat-bottomed caps with those of shaped charges. While the Trauzl test value and Kast crusher test values are practically unaffected by a change in the shape of the bottom, the lead plate test value is much higher for the shaped charge.

A. Izzo, (Ref 8) describes the following German detonators: **Detonator Brisko No 8** consists of a shell 40 mm long, 6.85 mm in diam, filled with 0.8 g Tetryl compressed at 2000 kg/cm² (base charge) and 0.3 g of L. A / L. St mixture (primary charge). **Detonator No 10** of D A -G, Troisdorf contained 1.25 g of Tetryl and 0.3 g of L. A / L. St mixture.

Abbreviations: L. A Lead azide; L. St Lead styphnate; M F Mercury fulminate; AP Armor-piercing; RN Round nose; HE High-explosive; PETN Pentaerythritol tetranitrate; RDX Cyclonite, or Hexogen; TNT Trinitrotoluene.

References:

- 1) A. Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933), pp 348-352
- 2) C. Beyling & K. Drekopf, Sprengstoffe und Zündmittel, Springer, Berlin (1936), p 151
- 3) PB Rept 11,544 (1945), part III, p 10
- 4) Picatinny Arsenal Tech Rept 1555 (1945), pp 30-31
- 5) A. Stettbacher, Spreng- und Schiessstoffe, Zürich (1948), p 105
- 6) W. Schneider, Sprengtechnik, No 10/11, p 186 (1952)
- 7) I. Kirsche, Sprengtechnik, No 12, pp 228-32 (1952)
- 8) Technical Report TM 9-1985-3 (1953), pp 547, 563, 566, 568, 569

9) A. Izzo, Manuale del Minatore Esplosivista, Hoepli, Milano (1953), p 77.
(See also BIOS Final Rept 644 and CIRS Rept 24-3).

Detonit (Detonite). A type of permissible explosive used before WWI. Some compositions are given in Table 12

Table 12

| Composition and some properties | Detonit 3 (powdered) | Detonit 5 | Detonit 6 (or 14A) | Detonit 14 |
|---------------------------------|----------------------|-----------|--------------------|------------|
| Am nitrate | 82.7 | 68.0 | 82.0 | 82.0 |
| K nitrate | - | - | - | 10.0 |
| NG (mixed with NC) | 4.0 | 4.0 | - | - |
| NG (straight) | - | - | 4.0 | 4.0 |
| Aromatic nitro-compound | 1.0 | - | - | - |
| Vegetable meal | 4.3 | 2.0 | - | 1.5 |
| Wood meal | - | - | 2.0 | - |
| Coal (powdered) | - | 4.0 | 0.5 | - |
| MNN | - | - | 1.0 | 2.5 |
| Alkali chloride | - | 22.0 | - | - |
| Na chloride | 8.0 | - | 10.5 | - |
| Oxygen Balance | +10.3% | -4.8% | +10.9% | +13.6% |
| Trauzl Test | 225cc | 220cc | 230cc | 235cc |

Abbreviations: MNN Mononitronaphthalene; NC Nitrocellulose; NG Nitroglycerin.

References:

- 1) Naoum, Schiess- und Sprengstoffe (1927), p 146
- 2) Naoum, Nitroglycerin (1928), pp 434-5
- 3) Beyling und Drekopf, Sprengstoffe und Zündmittel (1936), p 141.

Diathylenglykoldinitrat (Diethyleneglycol Dinitrate) See Diglykolnitrat.

Diamin oder EDC (Ethylenediamine Dinitrate) See general section. EDD was used by the Germans in Fillers No 20, No 83, No 84 and No 86 as well as in the following mixtures of unknown names:

a) EDD 45 and Am nitrate 55%

b) EDD 45, Am nitrate 53.5 and Al 1.5%

Note: Mixture of EDD and Am nitrate forms a eutectic which permits cast loading.

Reference: Allied and Enemy Explosives, Aberdeen Proving Ground, Mkl (1946), p 145.

Diazobenzolperchlorat (Diazobenzeneperchlorate). See general section.

Diazonitrobenzolperchlorat oder Nitrodiazobenzolperchlorat, known also as **Blitzpulver** is described in the general section under Diazobenzeneperchlorate.

Dichte (Density). See general section.

Dicyandimid (Dicyandiamide). Its manufacture in Germany is described in BIOS Final Report 1720 (1947). (See also in the general section).

Didi-Pulver. An abbreviation for Diglykoldinitratpulver (Diethyleneglycoldinitrate Propellant) [Stettbacher, Spreng- und Schiesstoffe (1948), p 44].

Diesel Igniters. See Fuel Oil Igniters.

Diethyleneglycoldinitrate. See Diglykoldinitrat.

Diethylnitramine, Hexanitro. See general section.

Diglykoldinitrat, Diglykolnitrat oder Didi (Diethyleneglycoldinitrate) (DEGDN or DEGN). Preparation and properties are given in the general section.

Following is a brief description of the German method of prepn as practiced at the Krümmel Fabrik of DA-G:

a) 420 kg of technical "Diglykol" (DEG), contg about 1% of ethyleneglycol and about 0.1% of water, was run slowly with stirring into 1218 kg of mixed acid consisting of 65% nitric acid and 35% sulfuric acid. The acid was cooled to below 25° by brine circulated in cooling coils. Total time of nitration was 22 minutes.

Note: A great excess of nitric acid was used in order to retard the decomposition of the otherwise extremely unstable spent acid. While the NG spent acid remained fairly stable for days, the DEGDN acid had to be worked up at once since it decomposed rapidly on standing.

b) After the reaction was complete, the mixture was cooled to 15° and transferred to a separator where it was allowed to stand for 7 minutes. The spent acid (nitric acid 8-9, sulfuric acid 64-66 and nitrated products 4-5%) separated at the bottom, while the oil collected as the upper layer.

c) The spent acid was then transferred to a "denitrator", while the oil, was run into the "primary washer" contg 300 liters of water stirred by air. The resulting acidic wash water contained an appreciable amount of nitric acid and was later denitrated.

d) The oil was run into the "main washer" to be treated (with vigorous air-stirring) first with 500 l of cold water, then with 150 l of 5% soda ash soln, preheated to 60° and finally with 500 l of cold water.

e) A sample of the oil thus purified was sent to the laboratory and if the KI test at 82° was not less than 20 min the material was considered to be satisfactory for use in the prepn of the so-called Rohpulvermasse (q v).

The yield of DEGDN was 710-715 kg or 170% of the DEG used; theoretically it should be 777 kg.

The purified DEGDN had the following properties: light yellowish oil, d 1.38 to 1.39, N content 14.1 to 14.2%, fr p below -10°, b p (decomp ca 162° and puffs off ca 200°), calorific value 1070 kcal/kg (vs 1715 for NG), water calculated as liquid, impact sensitivity with 2 kg weight 160 cm (vs 4 cm for NG), solubility in water ca 0.4% at room temperature, and volatility ca 4-5 times more volatile than NG.

DEGDN was used in the so-called "cool" propellants, such as "G" Pulver and "Gudol" Pulver.

References:
1) O.W. Strickland, PB Rept No 925 (1945), p 57
2) A. Stettbacher, Spreng- und Schiesstoffe (1948), pp 61-2 (See also CIOS Report 28-61).

Dimethylammonium Nitrate. See Di-Salz.

Dimethylethylenedinitramine (DMEDNA). Described in the general section. It was investigated by G. Römer, PBL Rept 85,160, p 14 as a component of some explosive compositions, such as:

- 1) DMEDNA 12, RDX 50, R-Salz 36, DPhA 1 and unaccounted 1%
- 2) DMEDNA 2.5, RDX 96.5 and DPhA 1.0%.

Dimethylnitramine (DMNA). Described in the general section. It was investigated by G. Römer, PBL Rept 85,160, p 13 as a possible addition to R-Salz in order to render it cas.able at temps of 100°, or lower. It was decided that incorporation of about 10% of DMNA was sufficient to give satisfactory results.

Dina. German abbreviation for Dinitronaphthalene.

Dinitranilin (Dinitroaniline) (DNA). Described in the general section under Aniline. The Germans used DNA during WWII as an addition to TNT. The resulting explosive was yellow in color, less powerful than TNT and much less sensitive to impact or friction. It produced larger projectile fragments than did TNT [Allied and Enemy Explosives, Aberdeen Proving Ground (1946), p 90].

Dinitranisol oder Disol (Dinitroanisole) (DNAs). See general section under Anisole; was used by the Germans in some explosive compositions, such as "Amatol No 40" (q v).

Dinitrobenzol (Dinitrobenzene) (DNB). See general section under Benzene. It was used by the Germans as an extender for TNT and as a desensitizer for some explosives, such as RDX. The addition of it to some high-melting explosives rendered them suitable for cast loading [Allied & Enemy Explosives, Aberdeen Proving Ground (1946), p 111].

Dinitrodiglykol. See Diglykoldinitrat.

Dinitrochlorhydrin (Dinitrochlorohydrin) (DNCH or DNCIH) is described in the general section under Chlorohydrin.

Dinitroglykol (Dinitroglycol). See general section, under Glycol.

Dinitronaphthalin, Dina, (Dinitronaphthalene) (DNN). See

general section under Naphthalene. It was manufactured during WWII, together with trinitronaphthalene, at Semtin Fabrik at Pardubice, Czechoslovakia, and used in some composite explosives.

References:

- 1) PB Rept No 1820 (1945)
- 2) Allied and Enemy Explosives, Aberdeen Proving Ground (1946), p 117.

(See also in the general section under Napthalene).

Dinitrophenol. See general section under Phenol.


Dinitrotoluol (Liquid) (Known in the USA as Drip oil). Was used by the Germans in some commercial explosives, such as Donarit.

"Dinort" Rods were devices secured to the nose of A/P (antipersonnel) bombs to produce a burst above the ground. This assured a greater number of effective fragments close to the surface of the ground. Fragments would be ineffective if the bomb had penetrated the soil prior to bursting. In the case of "shaped charge bombs" the Dinort rod acted as a stand-off device to improve the effectiveness of the charge (Ref 2)

There were two types of Dinort rods: a) drawn steel tubes (1.75" dia x 23.6" long or 2.75" dia x 14.8" long) and b) square wooden sticks (2.25 by 2.25" and 22.6" long) (Ref 1).

References:

- 1) Department of the Army Technical Manual TM 9-1985-2 (1953), p 4
- 2) J.H. Robinson, J.E. Capell and A.B. Schilling of Picatinny Arsenal; private communication (1955).



Dipentaerythritolhexanitrat. (Dipentaerythritolhexanitrate). See general section, and also W. Brün, S S 27, 73-76, 125-27, and 156-58 (1932).

Diphenylamin (Diphenylamine) (DPhA). See general section.

Diphenylurethan (Diphenylurethane). See general section; was used by the Germans during WWII as a stabilizer in some of their smokeless propellants [PB Rept 11,544 (1944)].

Directed Missiles. See Guided Missiles.

DI-SALZ. German abbreviation, for Dimethylammonium Nitrate, one of the Ersatzsprengstoffe (substitute explosives) prepared in Germany during WW II in order to combat the shortage of TNT and other high explosives. DI-Salt was prepd by the reaction of aqueous Dimethylamine with nitric acid (d 1.42). After vacuum distillation, a crystalline substance was obtained which decomposed explosively above 120°. The salt was found to be very unstable at temperatures above 100°. In the decomposition of DI-Salz, it was observed that free dimethylamine and nitric acid were produced first. This was followed by oxidation of the dimethylamine (by the nitric acid), which resulted in the progressive formation of nitrogen oxides as well as carbon oxides. The reaction accelerated autocatalytically into an explosion. When the salt was dissolved in water and then heated, strong hydrolysis took place.


No military application of this salt was reported.

References:

- 1) H. Walter et al, German Developments in High Explosives, PB Rept No 78,271 (1947)
- 2) F I A T Final Rept 1035 (1947), p 7.

Disintegrating Rotating Band Projectiles, such as 105 mm and 150 mm, were modifications of "sabot" projectiles. They contained at the shoulder a detachable guide band, which was almost completely trisected by cuts, spaced 120° apart. The band served as the bourrelet. The rotating band and its holder were located at the base of the shell, which was keyed to receive them. The holder itself was in three detachable segments held in position by the soft iron rotating band.


It is believed that after leaving the gun, the bourrelet and the driving band holder each split into three separate segments which were thrown off together with the pieces of metal which initially held them on the shell. The projectile which remained not only had a better aerodynamic shape than conventional projectiles but also was about 30% lighter.



References:

- 1) E. Engleburg, Ordnance Sergeant, May 1944, p 308
- 2) TM 9-1985-3 (1953), pp 369-71 (See Sabot Projectile).

Distance Piece (Kreuzrohr) (Cross Tube). When a propellant charge of semi-fixed artillery ammunition was smaller than a cartridge case, one or several tubular sticks of a double-base propellant were inserted into the propellant bag and tied tightly at its neck. The upper end of the sticks extended as far as the bottom surface of a closing cup (or the base of the projectile), while the lower ends held the bag against the primer. With this arrangement the propellant charge was not loose and, being held close to the primer flash hole, the propellant was readily ignited.



References:
1) E.Englesburg, The Ordnance Sergeant, May 1944, p 321
2) A.B.Schilling, Picatinny Arsenal; private communication (1955).

DMW-Pulver. Fast-burning NC propellant used in 7.65 mm standard cartridges for pistols and revolvers. It was in the form of small greenish cylinders 0.4 mm diam and 0.4 mm high, which were not graphited. [A.Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), p 45].

"Dobgerdt". A device used for launching the "Taifun" rocket [TM 9-1985-2 (1953), p 223].

Donarit (Donarite). A type of mining explosive manufd in Germany for many years. It is known that at least one of donarites was used during WW II (under the name of Filler No 56) for military purposes.

Table 13 gives the composition of some mining donarites

Table 13

| Composition (%) | Donarit 1 (Gelatin type) | Donarit 1 (Powdery type) | Donarit 2 (Powdery type) |
|-------------------------|-----------------------------|-----------------------------|-----------------------------|
| Nitroglycerin | - | - | 4.0 |
| Nitroglycol | 22.0 | - | - |
| Collod cotton | 1.0 | - | - |
| Am nitrate | 55.0 | 81.5 | 84.0 |
| Na nitrate | 10.0 | - | - |
| Aromatic nitrocompounds | - | - | 3.0 |
| Trinitrotoluene | 5.0 | 14.0 | - |
| Dinitrotoluene (liquid) | 6.0 | 2.0 | - |
| Wood meal | 0.8 | 2.0 | 9.0 |
| Dye(Capur mortum) | 0.2 | 0.5 | - |

Note: The first two compositions were manufactured during WW I at the Krümmel Fabrik, of D A -G (Ref 2). The composition of Donarit 2 is given in Ref 1. According to Weichelt (Ref 3) there are three current donarites in Germany having the approximate composition: Am nitrate 86, Sprengöl (nitroglycerin with nitroglycol) 4-6 and TNT with Al powder 8-10%.

The properties of these donarites are as follows:

Temperature of explosion, °C 2580 to 3345°C
Volume of gases of explosion at NTP 832 to 924 in l/kg
Cartridge density (including the paper) 0.87 to 0.98
Specific pressure, kg/cm² 9900 to 10270
Velocity of detonation, m/sec 3800 to 4850
Trauzl test value, cc 435 to 4850
Impact sensitivity with 2kg weight, 60 to 70 in cm

(See also under Commercial Explosives).

References:

- 1) C.Beyling K.Drekopf, Sprengstoffe und Zündmittel, Springer, Berlin (1936), p 94
- 2) O.W.Stickland, General Summary of Explosive Plants, PB Rept No 925 (1945), p 69
- 3) F.Weichelt, Handbuch der gewerblichen Sprengtechnik, C.Marhold, Halle/Saale (1953), pp 37-8 & 375.

Doppelzünder (Double Igniter) for acoustic mines, developed during WW II at Troisdorf Fabrik D A -G. These mines consisted of two delay detonators (crimped into a sleeve) and mounted co-axially with their bases pointing away from each other, and with their fuseheads connected in series for simultaneous firing. The fuseheads had one direct connecting wire between them, while the other connecting wire from each of them made contact with a metal ring on the outside of the assembly. This arrangement permitted the fuseheads to be fired by applying an appropriate voltage to these two rings.

Reference: W.Taylor et al, BIOS Final Rept 644 (1945), p 17.

"Dora". Same as Sevastopol Gun, called also Gustav Geschütz.

Dortmund Gallery. See under Versuchsstrecke.

Drehspiegelkamera (Rotating mirror camera) See general section.

Drillingspulver. Short tubular powder for howitzers (Haubitze) such as the 10 cm Haubitze [Brunswig, Das rauchlose, Pulver (1926), p 131].

Dualin (Dualine). Under this name, Schultze, in 1868, patented a mixture of wood nitrocellulose and NG. Under the same name, Dittmar later patented a mixture of 50 NG, 30 nitrated sawdust and 20% saltpeter [Naoúm, Nitroglycerin (1928), p 282].

Durchschlags- und Strahlungsproben (Penetration and Radiation Tests). These tests are similar to those described in the general section under Lead Plate Test and Steel Plate Test. The German test is also called Brisanzplattenbeschuss, which means Brisance Plate Shooting.

References:


- 1) A.Stettbacher, Schiess- und Sprengstoffe, Barth, Leipzig (1933), p 361
- 2) A.Stettbacher, Spreng- und Schiesstoffe, Raschig, Zürich (1948), p 110.

Dust Fuze, developed during WW II at the Rheinmetall-Borrig, laboratory, was based on the principle of charging a condenser electrostatically by means of a dust field. The fuze was located in the nose of a bomb or a shell. Prior to dropping the bomb, the plastic cap covering the slits on the head of the fuze were removed. As the bomb fell, the air stream entered the fuze via the slits in the outer generator cone. This action disturbed the talcum powder and created a dust cloud in and around the forward part of the fuze. When the dust particles came into violent

contact with each other and also with the outer and inner generator cones, an electrostatic charge was developed. The condenser, which was connected to both generating cones, drew off the electric charge and built it up sufficiently to ignite the detonator on impact. (The size of the electric charge was controlled by the quantity of dust within the fuze).

The electric circuit could be closed for firing by any of three switches: a nose contact switch or two trembler switches set at right angles to each other. An extremely low energy electric igniter was used with this type of switch so that even though a small part of the charge leaked from the condenser, the remaining charge would be sufficient to fire the fuze.

The fuze was used in some shells, such as the 37 mm and some smaller bombs, such as the SD 4 and SD 10. Reference: TM 9-1485-2 (1953), pp 190-2.



Duxit (Duxite). An explosive made in Germany before WWI and placed on the British Permitted List in 1914: NG 31-33, collodion cotton 0.75-1.5, NaNO₃ 27-29, wood meal 8-10, Am oxalate 28-31, moisture 0 to 2.5%; max charge 12 oz, ballistic pendulum swing 2.45" vs 3.27" for British standard Gelnite containing 60% NG [F. Barnett, Explosives, Van Nostrand, N Y (1919), p 136].

Dynamit (Dynamite). According to Stettbacher (Ref 2), dynamite may be subdivided into the following groups: a) Guhr'dynamit (Guhrdynamite), b) Sprenggelatine (Blasting Gelatin), c) Gelatine-dynamit, and d) Sicherheitsdynamit (Safety Dynamite)

According to Marshall (Ref 1) the following three dynamites given in Table 14 were authorized between WWI and WWII for use in German coal mines:

Table 14

| Components | Dynamit | | |
|---------------------------------------|------------|----------|----------|
| | 1 | 2 | 3 |
| Nitroglycerin | 61 to 63.5 | 34 to 39 | 16 to 22 |
| Collodion cotton | 1.5 to 3 | 0.5 to 3 | 0.5 to 2 |
| Nanitrate and/or Knitrate | 25 to 29 | - | - |
| Na nitrate and/or Amnitrate | - | 45 to 54 | 50 to 74 |
| Vegetable meal | 6 to 9 | 1 to 6 | 1 to 6 |
| Soda ash or chalk | 0 to 2 | - | - |
| Nitrotoluene and/or nitro-naphthalene | - | 6 to 10 | 2 to 12 |
| Na chloride | - | - | 0 to 12 |

Note: According to Weichelt (Ref 3) the properties of "Dynamit 1" are as follows: temp of explosion 3600°C, vol of gases at NTP 603 l/kg, cartridge density 1.45, specific pressure 9600 kg/cm², veloc of deton 6350m/sec, Trauzl test value 385cc, and impact sensitivity with 2 kg weight 10 cm.

Dynamit N (DN). A current dynamite suitable for use in the demolition of reinforced concrete and steel construction. Its composition and properties are given by Weichelt, as follows: RDX 70 and nitroglycol (gelatinized) 30%; temperature of explosion 4170°C, volume of gases at NTP 746 l/kg, cartridge density 1.54, veloc of detonation 8200 m/sec, specific pressure 12538 kg/cm².

See also Ammondynamit, Ammongelatine, Donarit Gelatine-Dynamit and Ersatzsprengstoffe.

References:

- 1) A. Marshall, Explosives, Churchill, London, v 3 (1932), p 109
- 2) A. Stettbacher, Spreng- und Schiesstoffe, Rascher, Zürich (1948), pp 82-90
- 3) F. Weichelt Handbuch der gewerblichen Sprengtechnik, C. Marhold, Halle/Saale (1953), pp 34-5, 375.

Dynammon . Dynammons are ammonium nitrate explosives used in Germany, Russia, Italy, etc :

- a) Am nitrate 90 and red charcoal 10%
- b) Am nitrate 95.5 and charcoal 4.5%.

Reference: A. Marshall, Explosives, London, v 2, (1917), p 493.

E-4 HEXA (Explosive). See under Ersatzsprengstoffe.

E (Series) Tanks such as E-100. See Experimental Tanks, under Panzer.

Earth-Displacement Test (Cratering Effect Test, or Mining Effect Test). In order to test the efficiency of bombs and land mines on explosion under ground, the Germans buried an item (such as a 250 kg bomb) and then exploded it. The volume of the resulting crater (in cubic meters) gave an approximate idea of the power of the explosive charge.

Reference: O.W. Stickland, PB Rept No 925 (1945), Appendix 7.

E C (Pulver). One of the sporting propellants: colloid cotton 28, guncotton 26, Ba and K nitrate 38, camphor 2.0, wood pulp 4.0, moisture 1.5 and gelatinizer 0.5% [Brunswig, Das rauchlose Pulver (1926), p 134].

EDD. One of the abbreviations for Ethylenediaminedinitrate, called also DIAMIN.

Effective Calculated Calorific Values of Propellants. If it is assumed that for a certain muzzle velocity and a given projectile, the product of the charge weight and calorific value of a propellant is constant, then by knowing the calorific value and weight of a propellant, it is possible to calculate the calorific value of a second propellant of a similar nature (if its charge weight had been previously determined experimentally). For instance, if for one propellant the values were 820 kcal and 4.3 kg and for a second propellant X kcal and 6.2 kg then:

$$X = \frac{820 \times 4.3}{6.2} = \frac{3526}{6.2} = 570 \text{ kcal/kg.}$$

This may be considered as the "effective calorific value" and it differs from the value determined in a calorific bomb, which is usually higher, e.g. 690-700 kcal/kg, for the example cited immediately above.

In calculating the life of a gun barrel, it was considered preferable to deal with the "effective calorific values" than with values obtained in a calorific bomb. (See also under Erosion of the Bore and under Energy Content of Propellant Charge)

Reference: "B Rept 925 (1945), pp 16 & 82.

Eindrahtzunder (One Wire Electric Igniter or Primer) is described in Beyling and Drekopf, Sprengstoffe und Zundmittel, Berlin, (1936), p 220.

Einfache Zunder (Simple Igniter or Primer) is described in Beyling and Drekopf, pp 172, 174, 177.

Einheitspulver. See Standard Propellant.

Ein-Mann Torpedo. See One-Man Torpedo

Eisenbahnverkehrsordnung, Vorschrift zur Prüfung von Sprengstoffen (Railroad Traffic Regulation, Instruction for Testing Explosives). Information on this subject may be found in:

- 1) Zeitschrift für das gesamte Schiess- und Sprengstoffwesen (abbreviated as S S V), vol 24 (1929), Supplement
- 2) Kast-Metz, Chemische Untersuchung der Spreng- und Zundstoffe (1941), pp 188, 225, 235 & 238.

Eismine 42 oder Flascheneismine. See under Landminen and also on pp 281-2 of TM 9-1985-2 (1953).

Ejecting Projectiles See under Krümmel Fabrik, Dynamit A-G Pressing of Explosives, etc.

Electric Fuze (Elektrischer Zunder). The development of electrical time and impact fuzes had been carried on in Germany since 1926 and the greater part of the work was done by the Rheinmetall-Borsig Co, under the direction of H. Rühlemann. The original object of the development was to produce for projectiles an electrical time fuze which could be set at the instant of firing. However, before this work was completed a successful electrical bomb fuze was

developed which was adopted in 1937 by the Luftwaffe. This was followed by several other types of electrical bomb fuzes. All these fuzes were cylindrical in shape and, with the exception of Type 5, used aluminum for the case.

The inner part of a typical fuze consisted of two sections:


- a) The upper section, called the switch block, was molded polystyrene which had been machined to take various plunger contacts, the trembler switches, and in some cases the long delay igniter bridge.
- b) The lower section contained the storage and firing condensers, the resistances and instantaneous and short delay igniters. All these items were held in place by a black bitumen calking substance. The condensers were constructed of metal foil strips separated by wax paper, all wound on one cardboard cylinder. The carbon resistances were usually located inside this cylinder. Some fuzes, as for instance EIZ (9), described in this section under Aerial Burst Fuzes, contained the glow discharge tube, also called the long delay cold cathode tube. The igniter block fitted into the bottom of the fuze and contained the black powder flash pellet, the cover with three perforations leading from the pellet to the igniter bridges, and the short delay train.


The electrical bomb fuzes were either impact or time types.

Following is a brief description of operation of a three circuit electrical impact fuze illustrated on next page:

As the bomb was placed in the plane, a charging head was clamped on the fuze head. The charging pins contacted the plungers and depressed them so that they could make electrical contact with the storage condensers. The two charging pins were connected to the sliding contacts located in the charging arm. These contacts closed when the bomb had fallen from 1 to 3 inches from the rack. This prevented charging of the fuze while the bomb was still in the aircraft. The two sliding contacts were connected to the positive terminal of the 240 volt battery. The B plunger circuit was connected directly while the A plunger circuit was connected through a selector switch which had two positions: open (MV) with delay, and closed (OV) without delay. The battery was tapped at 240 and 150 volts and the two leads were run to the voltage switch. This switch was set at 150 v for level bombing and at 240 v for dive bombing, but it could not be used to open the circuit. The voltage switch was connected to the master switch which was used to jettison the bombs. The master switch was connected to the charging head which contacted the fuze head and completed the electrical circuit through the fuze body to the storage condensers.

Prior to the release of the bomb, the master switch was closed completing the circuit from the batteries through to the fuze except for the sliding contacts in the charging head. When the bomb was dropped, the charging arm was extended, causing the sliding contacts to meet for about 1/3000 of a second, the ground return circuit being through the fuze body. If the selector switch was closed, both plungers received the current and the storage condensers, C-1 and C-3, were charged. The charge of C-1 leaked slowly through the resistance R-1 into the firing condenser C-2 (The time required for the current to pass from C-1 to C-2 and build up sufficiently to fire the igniter is called the arming time). At the same time the charge of C-3 leaked through R-2 into the firing condenser C-5 and also part of the current leaked through R-3 into the firing condenser C-4. On impact, the tremblers of switches S-1, S-2 and S-3, made contacts with their cups, causing the current to flow through the igniter bridges. These were thereby heated and fired the match compositions surrounding them. When all three igniter bridges fired simultaneously the instantaneous bridge fired the flash pellet and detonated the bomb through the normal explosive train. The short and long delay trains started to burn just at the instant of detonation.





If the selector switch was held open, then the charge went through plunger B to the storage condenser C-3 and nothing passed to the instantaneous circuit. The circuit through the resistance R-2 to the condenser C-5 became armed before the circuit through both resistances R-2 and R-3 to firing condenser C-4. If the bomb had been dropped from an altitude of less than 1170 ft, the latter circuit would not be armed before impact and the igniter bridge associated with the trembler switch S-2 would fire the long delay pellet which acting through the explosive train of the fuze would detonate the bomb. If the bomb was dropped from an altitude greater than 1170 ft, both circuits would be armed before impact, but because of the shorter

delay train used in conjunction with the trembler switch S-3, the short delay would initiate the final explosive train.

Electrical time fuzes (EIZZ) contained essentially the same basic parts as the electrical impact fuzes (EIAZ), except that the trembler switches were replaced by a vacuum tube which became conducting at a critical predetermined voltage. At the instant the bomb was started on its trajectory, an electric charge was put on the storage condenser, and another smaller charge was put on the firing condenser. The time setting of the fuze was adjusted by varying the amount of charge placed on the firing condenser. During flight, part of the charge on the storage condenser leaked through the resistor to the firing condenser. As the charge on the firing condenser increased, the voltage across the vacuum tube also increased. When the firing voltage of the tube had been reached, the firing condenser discharged through the tube and the igniter bridge thus firing the fuze.

Electrical bomb fuzes are described in Refs 1 and 3 and are listed in this work under Fuze. Some of these fuzes are described in this work under Aerial Burst Fuzes.

An electrical time fuze (EIZZ S/30) for use in projectiles is briefly described in Ref 4, pp 605-8. Prior to firing the projectile, the fuze was charged either by hand or by a machine by putting 300 to 500 volts across the shell and an insulated contact which put voltage on the annular storage condenser. The charging could also be done by allowing the "feeler wire" (connected to the electrical circuit of the fuze) to contact the "muzzle charging ring" as the projectile was leaving the gun. A brief description of a muzzle charging ring is given in Ref 4, p 606.

A device, described in Refs 2 p 422 and 4 p 623 as the electric fuze, ERZ 30, was used for igniting the black powder charge which set off the propellant of 15 cm and 21 cm rockets. This device is briefly described in this work under Rocket Propellant Igniter.

(See also under Electrical Igniter and under Igniter).

References:

- 1) Anon, War Dept Tech Manual TM E9-1983 (1942), Enemy Bombs and Fuzes, File Numbers 2321.5, 2321.8, 2324.92 & 2324.93
- 2) Anon, Ordnance Bomb Disposal Center, Aberdeen Proving Ground, Md (No date); German Artillery Projectiles and Fuzes p 422
- 3) Anon, Dept of the Army Tech Manual TM 9-1985-2 (1953), German Bombs, Fuzes, Rockets, etc, pp 125-132 and others
- 4) Anon, Dept of the Army Tech Manual TM 9-1985-3 (1953), German Projectiles and Fuzes, pp 605-7 and 623.

Electric Fuze Primer Composition. See Primary and Initiating Compositions.

Electric Igniter (Elektrischer Zünder). Among the numerous igniters used by the Germans in mines was one type, ESMIZ 40, which used an electric current for firing the charge of a mine. This fuze is briefly described in TM 9-1985-2 (1953), pp 300-1. (See also under Igniter).

Electric Igniters and Primers (Elektrische Zünder) Used for Commercial Explosives. These devices, described in Beyling-Drekopf, Sprengstoffe und Zündmittel (1936) may be subdivided into the following groups:

- a) Einfache Zünder (Simple igniter). It consisted of a capsule (Hülse), a priming composition (Zündsatz) and electric lead-in wires connected to a bridge wire (B & D, pp 177-222)
- b) Zusammengesetzte Zünder (Composite igniter or primer), such as Sprengzünder (detonating primer), consists of a simple electric igniter combined with a detonator, (B & D, pp 174 and 222-24)

1) Zünder mit fest eingesetzter Sprengkapsel consists of a simple primer into which a No 8 blasting cap (Sprengkapsel No 8) is firmly set. (See B & D, pp 174 and 225)

2) Unterwasserzünder (Underwater primer) is described in B & D, pp 225-26.

3) Zeitschwarzzeitzünder (Time Igniter with fuse), consists of a simple primer combined with at least a 20-cm piece of fuse (B & D pp 175 and 226-29)

4) Schnellzeitzünder (Instantaneous igniter or primer), described in B & D, pp 175 and 225

5) Unterwasser-Schnellzeitzünder (Underwater instantaneous igniter or primer), described in B & D, pp 175 and 225.

Abbreviation: B & D Beyling and Drekopf.

Electric Marchhead or Fusehead is the combination of bridge wire, igniter head and lead-in wires employed in electric blasting caps and detonators. (CIGS Rept 21-3, p 7 and also under Fusehead Manufacture).

Electric Proximity Fuze. See Proximity Fuze.

"Elefant" (Elephant). A tank destroyer known also as **Schwerer Panzer Jagd "Elefant"**; It was an improved version of "Ferdinand" (q.v.). See also under Panzer.

Elektronbombe (Electron-bomb). See general section).

Empfindlichkeit gegen Reibung (Sensitiveness to Friction). See general section.

Empfindlichkeit gegen mechanischen Einwirkungen (Sensitiveness to Mechanical Action). See general section.

Empfindlichkeit gegen Stoss (Sensitiveness to Shock or Impact). See general section.

Empfindlichkeit gegen Wärme (Sensitiveness to Heat), also called **Chemische Beständigkeit** (Chemical Stability) is described in the general section under Stability.

Energiegehalt des rauchlosen Pulvern. See Energy Content of a Propellant Charge.

Energit (Energite). According to Naoum (Ref 1), Energit was a commercial explosive manufd after WW I by Nobel's Dynamit A-G. The explosive was prepd by wet grinding various kinds of surplus double-base propellants in "Excelsior" mills between steel discs, to a particle size of 0.5 to 2 mm, followed by drying and packing in cartridges 25 to 30 mm diameter. This explosive was used to a great extent in potash mining.

According to Pepin Lehalleur (Ref 2), Energit and Triwestfalit were industrial explosives prepared by blending a smokeless propellant (left as surplus after WW I) previously wetted with about an equal quantity of a solvent such as furfural or acetone, with liquid aromatic nitro-compounds and oxidizing agents such as alkali nitrates or chlorates in a kneader. The strength of these explosives as determined by the Trauzl test was 330 to 350 cc; velocity of detonation 3000 to 5000 m/sec.

References:

1) P. Naoum, Nitroglycerin, etc, Baltimore (1928), p 449

2) J. Pepin Lehalleur, Poudrea, etc, Paris (1935), p 457.

See also Nitroglycerin-Nitrocellulose Explosives (Mining Lists 33, 35 and 36) as well as Triwestfalit SN j.

Energy Content of a Propellant Charge. According to IIG Rept 925 (1945), p 82, the energy content is equal to the charge weigh. of a propellant multiplied by its calorific value. For a given projectile and a given initial (muzzle) velocity, the energy content is constant and independent of the type of propellant used. For instance, if for a certain initial velocity of a projectile the charge weight of a propellant with a calorific value of 820 cal/g is 4.3 kg a propellant of 570 cal/g (such as a nitroguanidine propellant) would require a charge of 6.2 kg. (See Effective Calorific Values of Propellants).

Entflammungsprobe (Flash Test). The test as applied to smokeless propellants is described by H. Brunswig, Das rauchlose Pulver, (1926) p 304.

Entflammungspunkt oder Entflammungstemperatur (Flash Point, Kindling Temperature). The test is described in the general section.

Entkupferungsmittel. See Decoppering Agent.

Entlastungszünder (Antilifting Type Igniter with HE Charge). See under Igniter.

Entwässerung oder Trocknung (Dehydration, Drying). See general section.

Enzian Rakete (Enzian Rocket). One of the guided rockets developed and used by the Germans during WW II. It has been described by:

1) F. Ross, Jr, Guided Missiles, Rockets and Torpedoes, N Y (1946), p 43

2) A. Ducrocq, Les Armes Secrètes Allemandes, Paris (1947), p 99 3) TM 9-1985-2, pp 229-32.

(See also Great Enzian or E-4 Missile).

Entzündlichkeit (Inflammability). See general section.

Entzündungsgemisch (Ignition Mixture). See general section.

Entzündungsprobe (Ignition Test). See general section.

Entzündungspunkt (Ignition or Burning Point). See general section.

Entzündungstemperatur oder Verpuffungstemperatur (Ignition, Deflagration or Explosion Temperature). See general section.

Erdstuka (Earth Stuka). A rocket-assisted 1800 kg armor-piercing bomb (PC 1800 RS) used by Stuka bombers against land targets. This bomb is mentioned, but not described, in TM E 9-1983 (1942), File No 2324.92.

Erosionless Priming and Initiation (Erosionsfreie Zündung). Priming and initiating compositions containing mercuric fulminate and the chlorates (such as $KClO_3$) have been known to cause considerable erosion of gun barrels. In 1904, H. Ziegler of Switzerland, therefore, proposed that Ba salts such as the nitrate be substituted for the chlorate salts. These new compositions were known in the industry as "rostfreie Zündungen" (rust-free primers). As these substances were not entirely satisfactory, further search resulted about 1930 in the invention of compositions based entirely on organic compounds, such as Tetracene (Tetrazen). These substances, called "erosionfreien Sinoxysätzen", were manufactured before WW II by the Rheinisch-Westfälische Sprengstoffe A-G, in Numberg.

References:

- 1) P. Wot, S. S. 27, 397-99 (1932), Die korrosionsfreie Zündung
- 2) L. von Herz, ibid. 28, 37-42 (1933), Die erosionsfreie Zündung
- 3) A. Stettbacher, Spreng- und Schießstoffe, Kasper, Zurich (1948), pp 100-107.

Erosion of the Bore (Erosion der Gewehrlaute, Bohrausnutzung oder Bohrausbrennung): Erosion of guns is described briefly in the general section.

In this section a short account is given of recent German efforts to reduce the erosion of their guns.

Due to the fact that the armor of tanks and ships during WWI was made thicker and thicker and the speed of the planes greater and greater, the muzzle velocity of guns was increased to as much as 3300 ft/sec. In order to achieve such velocities it was necessary to use propellants of high ballistic potential, such as those containing NG. As these propellants were "hot" (calorific value about 950 kcal/kg) they caused excessive erosion thus lowering the life of a gun considerably.

For instance, the life of AA guns using a 950 kcal/kg propellant was only 1700 firings and for a 820 kcal/kg propellant about 3500 firings. Even before this number of firings was reached the gun became less effective because of the escape of gases between the walls of the barrel and the projectile. This escape of gases not only reduced the chamber pressure (thus causing reduction in muzzle velocity of the projectile with consequent reduction of range and penetration) but also caused excessive muzzle flash. As the decrease in efficiency of an older gun is usually compensated for by increasing the propellant charge, this lead to a still brighter flash. In order to reduce the flash in such increased charges, more and more potassium sulfate (or other flash reducing agent) had to be incorporated. As these agents are inert materials, they diminish the efficiency of the propellant.

Erosion is the greatest factor in the wearing of the rifling of a gun, the result of which is always unsatisfactory rotation of the shell (spin) with associated fuze failure. Particularly bad erosion was obtained with high velocity guns (such as those with a muzzle velocity of about 3300 ft/sec). For them the use of propellants having calorific value of 820, or 950 kcal/kg was absolutely prohibitive and it was necessary to use cooler propellants.

Due to the fact that during the last war Germany suffered considerable shortage of steel-hardening metals, such as Cr, Ni, Mn, Mo etc required for making modern gun barrels, and due to the shortage of labor and in some cases of ordinary steel, the replacement of eroded guns was quite a serious problem. Fortunately for the Germans, a series of "cool" propellants or low calorific value propellants were developed, such as the "G" Pulver by Gen Gallwitz and the Gudolpulver by Dynamit A-G. The use of these propellants prolonged the life of a barrel to as many as 17,000 firings. This high figure was more than the Germans ever expected to achieve. As was mentioned previously, the prewar NG propellant with a calorific value of 950 kcal/kg permitted a maximum of 1700 firings, when used in AA guns. When the Germans decreased the calorific value of some of their NG powders to about 820 kcal/kg, the number of firings was increased to about 3500. Therefore, it was calculated that each reduction of about 130 kcal/kg should double the life of a gun. When Gen Gallwitz prepared his cool "G" propellants, the calorific bomb determination

gave values of about 690 kcal/kg. As it had previously been found that a reduction of 130 kcal/kg doubled the life of a gun barrel, the Germans thought that the new propellants would permit about $2 \times 3500 = 7000$ firings. Instead of this value they unexpectedly obtained 15,000 or even 17,000 firings. If previous German assumptions were right, then the new propellants should possess calorific values of 550 to 570 kcal/kg and not 690 kcal/kg as the calorific bomb showed. The values 550-570 kcal/kg were considered as the "effective calculated calorific values". These values were used by the Germans in preference to the calorific bomb values, such as 690 kcal/kg.

References:

- 1) U to Gallwitz, Die Geschuzladung, Heereswaffenamt, Berlin (1943)
- 2) O.W. Stiefland, et al, General Summary of Explosive Plants, PB Rept 925 (1945).

Ersatzdynamit (Substitute Dynamite) is any dynamite in which a large proportion of NG is substituted by some other explosive in such a manner that the resulting composition is equal in strength to the original dynamite (P. Naüm, Schiess- und Sprengstoffe, Steinkopf, Dresden (1927), p 95).

Ersatz-Geschoss (Substitute Shell). Due to the shortage of steel and other metals, the Germans, during WWI, developed, among many other substitute ammunition items, a sort of HE Shrapnel shell which was made of a combination of concrete and steel scrap. These shells were used toward the end of the war. (L.E. Simon, German Research in WWI, Wiley, N.Y. (1947), p 190).

ERSATZSPRENGSTOFFE (Substitute Explosives). Due to the acute shortage in Germany of TNT and other aromatic nitrocompounds, several substitute explosive mixtures were developed and used during WWI. Many of the "Ersatz" explosives were developed at the Krümmel Plant of Dynamit A-G others at Christianstadt and other plants.

In the preparation of various melt-loading compositions, the following trends were noticeable:

- a) Substitution of RDX for part of the TNT in amatols.
- b) Substitution of DNB for TNT in amatols
- c) Substitution for TNT, by nitroaromatics such as dinitrodiphenylamine, hexanitrodiphenylamine, trinitroxylylene, dinitronaphthalene, etc
- d) The use of low melting hydrous inorganic nitrate compounds, such as Ca, K and Na nitrates, to permit the reduction or replacement of TNT
- e) The use of Al powder as an ingredient
- f) The use of miscellaneous organic ingredients such as urea, PE (pentaerythritol), guanidine nitrate, ethylenediaminedinitrate, methylaminenitrate, etc
- g) The use of sodium chloride (up to 60%) or of so-called "Scheidemehl" (powder consisting of a mixture of Ca and Mg silicates) in order to reduce the amount of TNT.

Most of the explosives containing these substances were much less powerful and brisant than TNT alone. Note: From German documents, it appears that the critical period with regard to the supply of explosives and ammunition was reached in August 1944. From that date, serious shortages occurred. It was in September 1944 that on account of the shortage of NH_4NO_3 , the High Command ordered the use of mixtures of 50/50 TNT/NaCl, or even 40/60 TNT/NaCl, for loading shells. However, previous to this, mixtures of 50/50 TNT/ NaNO_2 (Sodatol) and 45/40/15 TNT/

Table 15

| Components | Designation and % Composition | | | | | | | | | | | | | | | | | | | | |
|--|-------------------------------|-----|----|---------|------|------|------|-----|-----|-----------|------|------|-----------------|------|-----|-----------|------|------|----------------|---------------|----|
| | Amatol | | | Ammonit | | | | | | | HEXO | | HEXA | | | KMA Block | S-16 | S-19 | NaCl Explosive | TNX Explosive | |
| | 39 | 39a | 40 | 11-1 | 11-2 | 11-5 | 11-8 | 43c | S-6 | S-6 modif | S-19 | S-22 | S-22 (see note) | S-26 | E-4 | | | | | | |
| TNT | 50 | - | - | - | - | - | - | 30 | 40 | 30 | - | - | - | - | - | - | - | - | - | - | |
| Am nitrate | 40-45 | 35 | 40 | 50 | 50 | 50 | 50 | 15 | - | - | 55 | 45 | 45 | 55 | 44 | 40 | - | 32 | 73.3 | 40-50 | 80 |
| Na nitrate | - | - | - | - | - | 5 | - | - | - | - | 9 | 9 | 9 | 9 | 10 | - | - | 6-8 | 17.4 | - | - |
| K nitrate | - | - | - | - | - | - | 25 | - | - | - | 4.2 | 3 | 3 | 4.2 | - | - | - | 0-2 | - | - | - |
| $\text{Ca}(\text{NO}_3)_2 \cdot 4\text{H}_2\text{O}$ | - | - | - | 15 | 15 | 15 | - | 10 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| RDX | 5-10 | 15 | 10 | 25 | 25 | 20 | 15 | - | - | - | 15 | 14 | - | - | - | - | - | 10 | - | - | - |
| PH-Salz | - | - | - | - | - | 10 | - | - | - | - | - | 14 | 14 | - | - | - | - | 10 | - | - | - |
| Urea | - | - | - | - | - | - | - | - | - | - | 1.8 | - | - | 1.8 | 2 | - | - | - | 9.3 | - | - |
| Al powder | - | - | - | - | - | - | - | - | 10 | 15-25 | 15 | 15 | 15 | 15 | 30 | 10 | 40 | - | - | - | - |
| HNDPhA | - | - | - | - | - | - | - | - | 30 | 35-30 | - | - | 14 | 15 | 14 | 30 | - | - | - | - | - |
| DNN | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 20 | - | - | - | - | - |
| DNB | - | 50 | 50 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| PETN | - | - | - | 10 | - | - | 10 | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| GuN | - | - | - | - | 10 | - | - | 15 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| DNDPhA | - | - | - | - | - | - | - | - | 20 | 15-20 | - | - | - | - | - | - | - | - | - | - | - |
| Na chloride | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 60-50 | - |
| TNX | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 20 |

Note: Composition S-22 sometimes exploded during the loading of projectiles.

Abbreviations: Am Ammonium; DNB Dinitrobenzene; DNN Dinitronaphthalene; DNDPhA Dinitrodiphenylamine; GuN Guanidine nitrate; HNDPhA Hexanitrodiphenylamine; PETN Pentaerythritol tetranitrate; PH-Salz Ethylenediamine dinitrate; RDX Cyclonite, or hexogen; TNT Trinitrotoluene; TNX Trinitroxylene.

NaNO_3/Al had been used to a considerable extent.

Table 15 lists the principal "substitute explosives" used by the Germans during WW I.

To this table may be added the following:

a) An explosive composition prep'd by I.G.Farbenindustrie by nitrating a mixture of MNX, methylaniline and MNT. The nitrated product consisted of TNX 45, tetryl 50 and TNT 5%.

b) An explosive mixture of the Krümmel plant of D A-G contained TNT 45, Am nitrate 40 and Al powder 15%. It was suitable for cast-loading bombs, grenades and land mines.

c) An explosive mixture of the Christianstadt plant of D A-G was a slurry of 70% $\text{Ca}(\text{NO}_3)_2 \cdot 4\text{H}_2\text{O}$ and 30% TNT.

The following explosives, listed in the German section under their proper names, also belong to Ersatzsprengstoffe: Amatol, Ammol, Ammonit, DI-Salz, Filiers Nos 13, 13a, 13-113, 19, 20, 52, 56, 57 (or Abonachit), 60, 61, 64, 70, 84 and 88, Formit, HDD, MAN-Salz, Myrol, PH-Salz, Tetrasprengstoffe (TeNMe explosives), Tetramethylnitraminotetramethylmethane, TETRA-Salz, Trinitroethanol Perchlorate (see in the general section under Perchlorates) and TRI-Salz.

In addition to the explosives mentioned above, before and during WW I, the Germans developed and used several new explosives and explosive mixtures which cannot be called "substitutes" (Ersatzsprengstoffe) because they were more powerful than the previously used military explosives, such as TNT and P A. These new powerful explosives included PETN and RDX, as well as various mixtures containing these substances.

References:

1) O.W.Stickland et al, Survey of German Practice and Experience in Filling High Explosive Items, US Office of Technical Service, PB Rept No 1820 (1945), pp 11, 15, 16, 24, 29.

2) O.W.Stickland et al, General Summary of Explosive Plants, PB Rept No 925 (1947), Appendix 7.

"E"-Salz.Hexogen (RDX) prep'd from formaldehyde, ammonium nitrate and acetic anhydride; see under Hexogen in this section.

Eschbachzünder oder Verzögerungzünder Eschbach[Eschbach Primer or Igniter, Delayed Action Primer of Eschbach]. It was described in Ger P 379, 939 (1922) and in Beyling-Drekopf, (1936) pp 232-35.

Note: W.Taylor et al, BIOS Final Report 644 (1945), pp 3-16 describes these devices under the term of "Eschbach Gasless Delay Detonators" or "LT Electric Detonators".

Essigäther (Ethyl Acetate). See general section.

Essigsäure (Acetic Acid). See general section.

Etagenguss (Multiple-Pouring or Increment Loading). See general section under Loading of Ammunition.

Ethylacetanilide. See Mannol.

Ethylenediaminedinitrate (EDD). See Dianin.

Ethyleneglycoldinitrate or Nitroglycol. Same as Glykolnitrat.

"Eumuco" Shell Forging Press is a vertical type press which combines punching and drawing operations. It was designed and manufd by Eumuco A-G, Leverkusen-Schlebusch and used by the following plants; Krenprinz A-G, Immigrath, Gutehoffnungshütte A-G, Sterkrade, Kieserling & Albrecht A-G, Solingen and Hasenclever A-G, Düsseldorf.
Reference: HOS Final Rept 668 (1946).

Experimental Mine. See Versuchsstrecke.

Explosionsdruck (Pressure of Explosion). See general section.

Explosionskraft (Explosive Force or Power). See general section.

Explosionstemperatur oder Detonationstemperatur: (Temperature of Explosion or of Detonation). See general section.

Explosionswärme (Heat of Explosion) See general section.

Explosives Developed by H. Walter et al. Between 1942 and 1945, a team of chemists under the direction of Dr Hans Walter and which included Dr Benno Walter, developed several explosives by using methanol and ammonia as starting materials. The work was started in the Degussa Laboratories in Frankfurt on Main and was transferred to Tetschen, Czechoslovakia in 1944. The most important explosives developed by this group were MAN-Salz, Myrol and TETRA-Salz. Of these substances Walter considered Myrol as the most important, followed by the TETRA-salt and last by MAN-salt.

A few less important explosives as well as derivatives of the above three substances, and various mixtures containing them were also investigated, such as: DI-Salz, Armit, MAN-Salz plus NaNO_3 , MAN-Salz plus NH_4NO_3 , MAN-Salz perchlorate and TRI-Salz.

Reference: H. Walter et al, German Development in High Explosives, FIAT Final Rept No 1035, PB Rept No 78, 271 (1947).

Explosive Powered Vortices. A weapon designed by Zippermeyer to be used against airplanes duplicated in miniature the effects of tornadoes. In his experiments, Z. shot a projectile filled with powdered coal dust and a charge of finely grained rough-surfaced double base propellant from a mortar. When the projectile approached the vicinity of a plane the propellant was exploded by means of an initiator. The combination of the forward component of velocity of the coal particles (created by the movement of the projectile) and a lateral component of velocity (created by the explosion of the propellant) was supposed to create a sort of tornado. Such a tornado was expected to cause a plane's wing to snap off. High speed movies of this phenomenon indicated that a considerable vortex effect was achieved. The development work was not completed [L.E. Simon, German Research in WW II, Wiley N Y (1947), pp 183-4].

(See also item C under Krümmel Fabrik of Dynamit A-G).

Explosive Rivet. See Sprengniet.

Explosive Speedboats. Among the interesting inventions of WWII were small wooden boats containing large charges of explosives and designed to combat Allied shipping. When the detonating device was set, a bump against the frame-work was sufficient to set off the explosive charge. The boats always operated in packs and were accompanied by a command boat. When targets were picked, the pilot set the detonating device, locked the steering gear in

position and allowed the boat to drive at top speed against the target, while he jumped overboard to be picked up by the command boat [Army Ordnance, 29 pp 378-80 (1945)].

Extra-Carbonit (Extra-carbonite). N_2 55, colloid cotton 0.3, Ba nitrate 4, K nitrate 2.5, tan meal 4.7, Na carbonate 0.5%; veloc of deton 4070 m/sec at d 1.20.
[E. Barnett, Explosives, Van Nostrand, N Y (1919) p 194]

Exudation (or Sweating) Test (Ausschwitzungsprobe.) This test was conducted in Germany essentially as follows: A 20-g sample of TNT, melted and cast as a cylinder 18 mm in diameter, was placed with the bottom part on a sheet of special Schleicher & Schülle filter paper resting on an aluminum plate. As a reference standard a similar pellet of Grade A TNT (s p 80.4 to 80.6^o) was placed about 100 mm away. The ensemble was placed in an oven and left there for 6 hours at 72^o. The diameter of the circle produced by the exudate was measured and if it was not greater than 35 mm the TNT was considered as Grade A. Any diameter between 35 mm and 70 mm was considered as Grade B (s p about 79.5^o).

In addition to these two grades, the Germans manufactured Grade UK (umkrystallisiert - recrystallized) with a s p of 80.7^o to 80.8^o.

Note: It is interesting to note that sulfite (sellite) refined TNT required a s p of about 80.6^o in order to pass the German exudation test for Grade A, while TNT produced by a nitric acid refining process, developed by Dr Wille of Allendorf Plant of DA-G, passed the Grade A test with a s p of only 80.2^o. This may be explained as follows: In order to obtain a practically non-exudable TNT it is necessary to remove the bulk of the two principal impurities of crude TNT: DNT and the isomers (beta and gamma) of TNT. Of these impurities, the DNT being of low s p causes higher exudation and is the most undesirable. As these impurities adhere to the surface of crystals of alpha TNT, the simplest way to remove them is to rinse the crystals with a liquid which would either react with the impurities or dissolve them without attacking or dissolving appreciable amounts of alpha TNT. It has been claimed that while the nitric acid method removes both the DNT and the isomers of TNT, the sulfite (sellite) method removes only the isomers and leaves the DNT. The only way to remove the bulk of the DNT by the 2nd method is to use such a large amount of sellite that the DNT would be washed out mechanically together with the isomers. Such treatment would give a high s p (say 80.6^o), but it is uneconomical because a significant amount of alpha TNT is removed together with the impurities. If the TNT purified by sellite has a high s p (say above 80.2^o) and it still exudes, there is a possibility of the presence of some DNT in addition to isomers of alpha TNT, and other impurities. It is claimed by the inventors of the nitric acid purification process, that practically no danger of exudation exists with 80.2^o TNT purified by their method because the bulk (or nearly all) of the DNT has been removed and if the s p is still lower than that of pure TNT, it is due to the presence of impurities which are less liable to cause exudation.

Abbreviation: s p Setting point (freezing point).

References:

- 1) C.H. Brooks, Explosives, TNT Manufacture and Development Work in Germany, PB Rept No 22,930, US Office of Technical Services, Washington, D C (1945), p 15
- 2) O.W. Stickland et al, Survey of German Practice and Experience in Filling High Explosives, U S Office of Technical Services, Washington, D C, PB Rept No 1820, p 7.

Fallhammerprobe oder Fallhammerprüfung (Falling Hammer Test, Drop Test or Impact Test). See general section and also:


- 1) A. Stettbacher, Spreng- und Sprengstoffe, Leipzig, (1933) pp 371-77
- 2) A. Stettbacher, Spreng- und Schiessstoffe, Leipzig (1948) pp 118-126.

Faustpatrone (First Cartridge, Tank Cartridge). Hollow charge antitank rocket grenade fired from a tubular discharger. The smaller model, **Faustpatrone 1** was later called **Panzerfaust 30**, Klein and the larger model, **Faustpatrone 2**, was called **Panzerfaust 30** (Ref 1).

The grenade for the Faustpatrone consisted of a large war head (contg. HOC-HE) and a cylindrical body (tube) terminating in a tail to which were attached four spring steel stabilizing fins. The tube contained a base fuze and a booster. The projector was a simple metal tube in which was located a propellant charge contained in a waxed cardboard cylinder held in position by a set screw. On the opposite side of the set screw was an igniter situated below a flash hole. On the top of the tube was a firing mechanism with a release button, firing pin and spring and a safety catch. A folding sight, adjustable for a range of 33 yards, was used for aiming. The grenade was armed by unscrewing the tail and inserting the booster and fuze, open ends facing each other. The fins were wrapped around the tail and the cylindrical part of grenade was inserted into the launcher tube. The pressure of the fins against the inside of the tube served to hold the grenade in position.

According to instructions furnished with the weapon, the firing mechanism was cocked first, the ensemble was placed under the right arm (the left hand supporting the forward part) and the sight adjusted to a range of 33 yards. The weapon was then fired by depressing the release button, thus allowing the striker to go forward. When the weapon was discharged, the propelling charge drove the grenade towards the target, while a portion of the gases blasted down the rear of the projector tube thereby offsetting the recoil. The back blast of the gases resulted in a jet of flame 6 to 8 ft long at the rear, which made it extremely dangerous for anyone to stand behind the firer.

The tube was discarded after firing.



The original models (Faustpatrone 30 and 30 klein) were very much feared by the soldiers assigned to use them, but the improved forms (Panzerfaust 60 and Panzerfaust 100) were safe to handle. The model 60 weighed only 13 1/4 lb and could be fired standing, kneeling or prone. It had as much flexibility as an ordinary rifle.

The hollow charge of the war head was capable of penetrating 8" of homogeneous armor plate and within the firing range there was no practical variation in the penetrating power.

New models were provided with heavier projectors, carrying larger propelling charge, which allowed the range to be increased to 150 meters (Refs 4 & 5).

(See also 44.5 mm Recoilless Grenade Discharger, under Weapons).

Note: Smith (Ref 5) calls Faustpatrone the "German Recoilless Grenade Discharger".

References:

- 1) Anon, Enemy War Materials Inventory List, SHAEF Office of AC of S, G-4 (1945), p 159

2) Anon, Intelligence Bulletin, 3, No 7, p 9 (1945)

3) A. J. Dere, The Ordnance Sergeant, Oct 1945, pp 10-11

4) L. E. Simon, German Research in WW II, J. Wiley, N Y (1947), p 188

5) Anon, German Explosive Ordnance, TM 9-1985-2, (1953), pp 339-40

6) W. H. B. Smith, Small Arms of the World, Military Service Publishing Co, Harrisburg, Pa (1955), p 522

7) G. G. G. and H. H. Hullock, Museum of Picatinny Arsenal, Dover, N J private communication (1955).

"Ferdinand". A self-propelled mount consisting of 85 mm A/T gun on PzKpfw VI (P) (See under Panzer).

Note: its improved version was known as "Elefant".

Ferro-Alloys were extensively used in war plants and for the manufacture of ammunition and weapons. One of the largest manufacturers of such alloys was the Badische Wolframerz GmbH, Sellingen.

Reference: CIOS Report No 30-55 (1945).

Ferrosilizium (Ferrosilicide or Ferrosilicon). See general section.

Feuchtigkeitsprobe (Moisture Content Test). See general section.

Feuerlinie. One of the guided missiles, developed and used during WWII. (See under Guided Missiles).

Feuerlöschmittel CB (Fire Extinguisher CB). Chlorobromomethane, CH₂ClBr. It was claimed to have been more successful as a fire extinguisher than carbon tetrachloride because it was heavier and less toxic.

Reference: CIOS Rept 25-18 (1945), p 26.

Feuerwaffe (Firearm). See under Weapons.

Feuerwerkerei, Feuerwerkerei oder Feuerwerkskörper (Fireworks). See Pyrotechnics.

Fichtenharz oder Kolophonium (Spruce Resin, Rosin or Colophony). See general section.

FILLER OR BURSTING CHARGE (Füllung oder Füllpulver) (Fp oder FP). Following is a list of explosives used for filling projectiles. These explosives are designated as Filler No 1, Filler No 2 etc. Some of them have prefixes such as Fp O2 which means TNT, or Fp 50/50 which means 50/50 Amatol.

Filler No 1 (FpO2). TNT pressed in cardboard or metal containers; was used for loading shells, depth charges, land mines, or for the prepn of demolition charges

Filler No 2 (Grf 88). P A pressed in cardboard or metal containers; was used in shells, land mines, depth and demolition charges

Filler No 3 (Np). PETN pressed; was used as the detonator and as a filler for grenades and small shells such as 20 to 50 mm

Filler No 4 (Fp O2). TNT loose in paper containers; was used in grenades

Filler No 5. Granular P A; was used as a bursting charge in stick hand grenade 24

Filler No 6. TNT/Wax - 95/5 in blocks in cardboard containers

Filler No 7 (Fp O2). TNT pressed; was used for loading shells, auxiliary boosters, bombs (heavier than 50 lbs) and chemical ammunition

Filler No 8 (Fp O2). TNT, cast; was used for loading HE shells

Filler No 10. Fp O2 + Fp 5 + Fp 10, pressed; was used

in AP shells.

Filler 11. Fp O2 + Fp 10 + Fp 15 + Fp 20, pressed; was used in AP shells

Filler No 12. Fp O2 + Fp 5 + RDX/Wax - 90/10, pressed in cardboard containers; was used in AP shells

Note: In the above mixtures Fp O2 means pure TNT while Fp 5, Fp 10, and Fp 20 mean TNT plus 5, 10 or 20% wax respectively. In AP shells, the filler varied with the section of the shell. The higher wax-content TNT was in the nose where the shock of impact was more intense, whereas, the booster surround consisted of pure TNT

Filler No 13 (Fp 60/40). NH₄NO₃ 40 and TNT 60%; corresponds to American 40/60 Amatol. Its fragment density test gave 39 meters vs 40 m for TNT. It was cast loaded in GP, SAP and A/P bombs and shells.

Filler No 13a (Fp 50/50). Same as 50/50 American Amatol. Its fragment density was 35 m vs 40 m for TNT; it was cast loaded in GP bombs and land mines such as Tellermine

Filler No 13-113. NH₄NO₃ 70, TNT 20 and Al 10%; was used for filling GP bombs. Another mixture consisted of Am nitrate 74 and TNT 26%

Filler No 14 (Fp O2). TNT cast; was used for filling GP, SAP, AP and A/P bombs.

Note: In the pressed form Fp O2 was also used as an auxiliary booster in all HE bombs over 50 kg and as a burster in chemical ammunition

Filler No 15. TNT 90 and Al 10%; was used in the shells of mountain artillery

Filler No 16. TNT cast in an aluminum container + PETN/Wax - 90/10 as an exploder; used in some shells and as a core in submarine mines

Filler No 17. TNT/Al powder (90/10) cast + PETN/Wax - 90/10 as an exploder; uses not specified

Filler No 17A. Matrix of DNAs/Am nitrate/RDX - 54/32/14, with biscuit of Am nitrate/Ca nitrate/RDX/PETN/combined water - 46/21/20/9/4

Filler No 18 (Fp O2/H5-80/20). TNT 80, RDX 19 and Montan wax 1%; was used in some shells

Filler No 19. Am nitrate 35, TNT 55 and Al 10%; was used in some HE shells (mountain artillery)

Filler No 20. Am nitrate 53.5, EDD 45 and Al 1.5%; use unknown

Filler No 21. Am nitrate 60 and TNT 40% with a core of pressed TNT pellets

Filler No 22. TNT 35, Am nitrate 50 and DNN 15%; was used as an extender for TNT in some ammunition.

Filler No 24. Cast P A; was used as a bursting charge in some shells, as a standard burster and as a sub-booster in mines when M.F. was used as the initiator.

Filler No 27. Fp O2 + Fp 10 (pressed); was used in AP shells and SAP bombs

Filler No 28. TNT/Wax - 90/10 + PETN/Wax - 90/10, pressed in blocks in aluminum containers; used in some HE and AP shells

| Filler No 29. Fp 10 | Layers pressed in shell |
|----------------------|-------------------------|
| Fp O2 (crystallized) | " " " " |
| Fp 10/KCl-70/30 | " " " " |
| Fp 10/KCl-50/50 | " " " " |

Note: Ref 3, p 286 gives for Fp 29 the following composition: Fp 10 + TNT (crystallized) + TNT/wax/KCl-63/7/30 + TNT/wax/KCl-45/5/50 + KCl, pressed in blocks in cardboard containers.

Filler No 30. Fp O2 + Fp 5, pressed in shells.

Note: Same as under Filler No 12

Filler No 32. PETN/wax-90/10 Pressed in wax paper;
Filler No 33. PETN/wax-85/15 were used in A/T mines and as standard sub-boosters in all kinds of ammunition

Filler No 34. PETN/wax-70/30 was used as filler of special shells

Filler No 36. PETN/wax-60/40; was used as filler of special shells

Filler No 37. PETN/wax-50/50; used as above

Filler No 38. PETN/wax-35/65; used as above

Filler No 39. PETN 91.5, wax 8.5%; was used as sub-booster in bomb gains, in 80 mm CM shells and in some 50 mm and 37 mm shells

Filler No 40. PETN/wax-82/18; was used in 37 mm APRN and APMB shells

Filler No 41. PETN/wax-87/13; was used in 88 mm HE shell

Filler No 42. PETN/wax-92/8 + 2%; was used in A/T Mk1 50 mm LM, 105 mm HE How as a detonator surround in HE shells (50 and 75 mm) and in some 50 mm and 88 mm AP shells

Filler No 42. Pentol (pressed); was used in HE shells.

Filler No 43. Plastic explosive consisting of PETN and mineral oil; was used in some HE shells

Filler No 45. PETN/RDX-50/50, plus 30% wax; similar in properties to PETN/wax-70/30; was used in some special projectiles. Another mixture contained RDX 50, PETN 35, and wax 15%

Filler No 52. An amatol-type explosive containing DNB 50, NH₄NO₃ 35, and RDX 15%; yellow solid; could be cast; explosive properties similar to those of 50/50 amatol; toxic (due to the presence of DNB). Was used in 50 kg GP and SAP bombs. (Ref 1, p 133)

Filler No 52a. An amatol-type explosive containing tech Ca nitrate 30, NH₄NO₃ 55, RDX 15%; was less powerful and brisant than 50/50 Amatol but of about the same sensitivity. Was used as a biscuit filling in the nose of parachute and robot bombs, with a surround of Filler No 52a

Recognition Handbook (Ref 3, p 286) gives the following compositions for Fillers No 52 and 52A:

Filler No 52. Matrix DNB/Am nitrate/RDX - 47/38/15, with a biscuit of Am nitrate /Ca nitrate/RDX/PETN/ Combined water - 46/21/20/9/4

Filler No 52A. Matrix DNB/Am nitrate/RDX - 50/35/15, with a biscuit of Am nitrate/Ca nitrate/RDX/PETN/ Combined water - 46/21/20/9/4

Filler No 52A. Matrix DNB/Am nitrate/RDX - 53/30/17, with a biscuit of Am nitrate/Ca nitrate/RDX/PETN/ Combined water - 46/21/20/9/4

Filler No 56 or Donarit. Am nitrate 67-80, TNT 12-25, NG 3.8, collodion cotton 0.2 and vegetable meal 4%. It was a yellow, semi-plastic substance possessing nearly the same explosive properties as 80/20 amatol, except that it was slightly more sensitive to impact and rifle bullet tests. It was used for filling some hand grenades (Ref 1, p 90)

Note: Ref 3, p 287 gives the following composition for Filler No 56. Am nitrate 80, TNT 12, NG 4 and rye flour 4%

Filler No 57 or Abonachit 2. Am nitrate 64, K or Na nitrate 3, TNX 13, collodion cotton 1, and Na chlorate 19%; was used in some grenades

Note: Ref 3, p 287 gives the following composition for Filler No 57. Am nitrate/alkali nitrate/TNT/alkali chloride/collodion cotton/charcoal - 64/3/14/17/1/1. This composition was called Monochit

Filler No 7. RDX 8, tech Ca nitrate 5, Am nitrate 55, EDD 30 and wax 2%; white substance; used in some

ammunition (cast loaded). Its explosive properties were comparable to 50/50 Amatol (Ref 1, p 134)

Filler No 60. Pressed TNCB; was used as a shell filler

Filler No 61. Cast TNCB; was used as above

Filler No 64. Cast-loaded mixture of TNCB 60 and Am nitrate 40%; white to brownish color, m.p. 81-82°, partially sol in w, sol in alc and acetone; explosive properties were similar to 40/60 Amatol; hygroscopic and somewhat very toxic; was used as a shell filler (Ref 1, p 134)

Filler No 66. PETN/wax - 50/50

Filler No 70. Pressed TNB; was used in some primers

Filler No 83. EDD in mixtures with some HE, to permit cast loading

Filler No 84. EDD 55 and Am nitrate 45%, was used in some shells

Filler No 85. EDD/RDX/Wax - 46/18/36, pressed in blocks wrapped in wax paper and placed in an aluminum container

Filler No ? (Fp 30/70). TNT 30 and Am nitrate 70%; was used in some A/P bombs

Filler No ? (Fp 5/95). TNT 5 and Am nitrate 95%; use is not known

Filler No 88 (Fp 40/60). NH₄NO₃ 60 and TNT 40%; was used in some shells grenades and radio-guided bombs

Filler No 89. General name of cast mixtures based on RDX

Filler No 90. General name of pressed mixtures based on RDX

Filler No 91-H5. RDX 95 and Montan wax 5%; was used in sub-boosters and boosters

Filler No 92-H10. RDX 90 and Montan wax 10%; was used in boosters

Filler No ? (H 10.3). RDX 89.7 and Montan wax 10.3%; was used in 75 mm AP shells

Filler No ? (H 3). RDX 97 and Montan wax 3%; was used in boosters for tropical countries, to replace PETN/wax mixtures

Filler No 95 (H/Fp 02). RDX 60 and TNT 40%; was used in some shells (press-loaded)

Filler No 101 (Fp 15). TNT/wax-85/15%; was used in AP bombs. (Ref 2 gives for Filler 101. TNT 92 and Montan wax 8%)

Filler No 102. Am nitrate 60, TNT 40% and some wax; uses not indicated

Filler No 104. RDX; uses not indicated

Filler No 105 (Triolen 105). RDX 15, TNT 70, and Al (powder) 15%; was used cast-loaded in GP bombs and torpedoes. Another mixture contained TNT 74, naphthalene 14 and Al 12%

Filler No 106 (Triolen 106). RDX 25, TNT 50 and Al 25%; was used in some bombs

Filler No 107 (Triolen 107). RDX 20, TNT 50 and Al 30%; was used in underwater ammunition

Filler No 108 (?) (Triolital). RDX 20, TNT 60 and Al 20; was used in underwater ammunition

Filler No 109 (Triolen 109). RDX 70, Al 25 and Montan wax 5%; was used, compressed in pellets, as a biscuit filling; with NGu in the nose and as a surround for Filler No 106 (Triolen 106) in the 500 kg GP, 1800 kg AP bombs and in some pilotless aircraft missiles.

Note: NGu was used as protection for Filler No 109, which alone is even more sensitive than straight RDX.

Filler No 110. Am nitrate 90, Al 2.5, naphthalene 5 and wood meal 2.5%; light gray in color; required a secondary HE primer to detonate; was used, press-loaded in concrete and in A/P bombs

Filler No 111. Am nitrate 90, carbon 6 and mineral matter 4%; was used press-loaded in some bombs. Note: Ref 3, p 288 gives for Filler No 111 Am nitrate 96 and carbon 4%

Filler No 112. Am nitrate 80 and TNT 20%; was used in some bombs

Filler No 113. Am nitrate/TNT/Al powder - 70/20/10; uses not indicated.

Abbreviations: Al Aluminum; alc alcohol; Am Ammonium; AP Armor-piercing; A/P Antipersonnel; A/T Antitank; CM Chemical mortar; DNN Dinitronaphthalene; EDD Ethyldiamine dinitrate; GP General purpose; H Hexogen (RDX); HE High-explosive; HoC Hollow (shaped) charge; How Howitzer; L A Lead azide, L S Lead styphnate; MB Monoblock; M F Mercuric fulminate; Mk Mark; NGu Nitroguanidine; P A Picric acid; PETN Pentaerythritol tetrantrate; RN Round nose; RDX Cyclonite or Hexogen; SAP Semi armor-piercing; sol soluble; tech technical; TM Trench mortar; TNB Trinitrobenzene; TNCB Trinitrochlorobenzene; TNT Trinitrotoluene; TNX Trinitroxylyene; w water

References:

1) Allied and Enemy Explosives, Aberdeen Proving Ground, Maryland (1946), pp 75, 79, 82, 86, 88, 97, 112, 113, 118, 120, 122, 124, 129, 133, 134, 137, 139, 141, 142 and 147


2) US Department of the Army Technical Manual TM 9-1985-3 (1953), pp 536-7

3) Anon, Recognition Handbook for German Ammunition, Supreme Headquarters Allied Expeditionary Force (1945), pp 286-8.

Fillers Used in Anticoncrete and Armor-Piercing Shells.

In order to make the explosives such as TNT safe for use in armor-piercing and anticoncrete shells, sections of TNT close to the nose were made less sensitive to shock by incorporating some wax and K chloride.

A good example of this type of filling was the one in 210 mm Anticoncrete Shell (21 cm GrBe). Its filler consisted of ten pressed pellets placed in cardboard container and held in position by a cement lining. The forward three sections 6, 7 and 8 were intended to provide protective layers, practically insensitive to shock whereas the layers close to the base were nearly or just as sensitive as straight TNT. The enclosed list gives the compositions and weights of charges shown on the enclosed drawing.



- No 1 4 lb, 2 oz of TNT/Wax - 94/6
- No 1a 8 oz of Straight TNT
- No 2 4 lb, 3/4 oz of TNT/Wax - 90/10
- No 2a 1 lb, 5/8 oz of Straight TNT
- No 3 5 lb, 5/8 oz of TNT/Wax - 90/10
- No 4 5 lb, 4/8 oz of TNT/Wax - 91/9
- No 5 4 lb, 2 oz of TNT/Wax - 91/9
- No 6 6 oz of TNT/Wax/K chloride-60.5/5.4/34.1
- No 7 5 oz of TNT/Wax/K chloride-44.1/5.6/50.3
- No 8 6 oz of K chloride

Total weight of filler was 25 lb 8 1/2 oz
Reference: E.Englesburg, The Ordnance Sergeant, May 1944, p 320.

Firing or Igniter Composition 121. One of the mixtures used during WWI: silicon 25, Pb chromate 50, and K chlorate 25% [PB Rept 95,613 (1947), Section U].


Flammbombe. An incendiary bomb containing an oil mixture and a HE bursting charge. The following types are described in TM 9-1985-2 (1953), pp 52-54:

- a) Flam C 250 A (B or C) contained 50 kg of oil incendiary mixture and TNT bursting charge (p 52)
- b) Flam KC 250; same filling as above (p 53)
- c) Flam C 500 contained the incendiary oil consisting of 70% petroleum and 30% TNT, with TNT bursting charge (p 54).

(See also Incendiary Bombs, Brandbomben and Sprengbomben). (Illustrations are given under Bombe).

Flammability Test (Entzündlichkeitsprobe). A special apparatus called "Flammenpendel" and its application to testing of various explosives and pyrotechnic compositions was described by F. Lenze SS 27, 366-69 (1932).

Flammenauslöschendzusatz (Flame Extinguishing Addition or Flame Reductant). See Flash Reducing Compounds in the general section.



Flanschgeschoss (Flange Projectile), called also "Squeeze-bore", or "Littlejohn" was a subcaliber projectile provided with a flange and three hollow studs as shown on Figure and described in the TM 9-1985-3, p 360.


It was fired from a cylindrical rifled barrel to which a smooth-bored, tapered muzzle extension was attached. The principal advantage of the "flange" projectile in comparison to the other subcaliber projectiles was that it had no parts to be discarded, because the hollow stud and the flange were easily depressed when the projectile passed from the rifled section of the gun to the smaller caliber smooth bore extension.

(Compare with Arrowhead Projectile, Arrow or Needle Projectile, Disintegrating Band Projectile, Röchling Projectile, Sabot Projectile and Lapped Bore Projectile).

Flare (Leuchtkugel oder Fackel). A German flare usually consisted of a cylindrical container housing an illuminating element. Upon being ignited by a pull friction igniter or a time fuze the flare burned vigorously producing intense light and heat. The illuminating element consisted either of a single or a multiple candle unit which varied in intensity of illumination and color. Flares were made with or without parachutes.

A brief description of the following flares is given in TM 9-1985-2 (1953), pp 65-81:

- 1) LC 10 (Leuchtzylinder 10) consisted of an aluminum cylinder, a single candle in a cardboard liner, an "89" clockwork fuze and a parachute located in the tail end. The flare was dropped from a plane and at a predetermined time the fuze fired and ejected the candle and its parachute from the body. Simultaneously the candle was ignited (p 65)
- 2) FB 50, Single Candle Parachute Flare (p 66)
- 3) LC 50F Ausf C Parachute Flare consisted of an aluminum cylindrical body with dome-shaped nose attached by means of brass screws. On releasing the flare, the pyrotechnic delay (inside the fuze) was ignited. This fired the quickmatch, which in turn burned through the flash tube and ignited the black powder charge in the tail. The pressure of the gases developed by the deflagrating black powder, caused all four flare candles and the parachute to be expelled through the nose, after shearing the holding screws. Simultaneously, the candles were ignited through perforations in the ejector plate. The composition of the candle was Ba nitrate 75.8, Al 16.5 and S 7.7%. The burning time was slightly over 5 min and the candlepower 216,000 (p 68)
- 4) LC 50F Ausf E, Single Candle Parachute Flare (p 68-9)
- 5) LC 50F Ausf G, Single Candle Parachute Flare (pp 69-70)
- 6) Mark C 50 F/A Parachute Flare consisted of a cylindrical aluminum housing containing a parachute, fuze, quickmatch, single candle unit, flash tube, priming composition and ejection disk. When the flare was released, the aerial burst fuze started to function. The flash ignited the quickmatch and the flame was transmitted through the flash tube to the tail end to ignite the ejection disk of black powder. The pressure of the gases developed by the burning powder expelled the parachute and the candle through the nose. Simultaneously the primer composition and the candle were ignited (pp 70-1)
- 7) Mark 50 Koskade Target Indicating Flare consisted of a sheet metal cylindrical container 7.7" diam and 41.0" long containing 62 flares (in three layers separated by perforated cardboard partitions), an expelling charge of black powder, smokeless propellant ignition disks and an igniter (fuze) assembly. A heavy concrete nose was provided to make the missile fall with the nose downwards, when released from a plane. As the missile fell, the expelling charge was ignited thus ejecting the flares (candles). At the same time the propellant



ignition discs lit each candle. (Composition of candles is given under Pyrotechnics. See also BIOS Rept 1233 (1946), p 1.)

8) Single Candle Parachute Flare with Pull Igniter was similar in construction to the Mark C50F/A flare. The principal difference was that the candle was reversed and ignited by pull (friction) igniters instead of by a black powder charge. After the flare was released from the aircraft, the fuze (through the flash tube) ignited the ejection charge of black powder and the pressure of the gases ejected the parachute and the candle through the nose. At the same time the parachute pulled the cords of the igniters, which were provided with delay elements of $3\frac{1}{2}$ sec. The candle was then ignited and burned for 5 minutes (pp 73-5).

9) Single Candle Unit Parachute Flare (White) consisted of a cylindrical aluminum body which was attached to a parachute by means of a cable. Eight shroud lines terminated in a loop which was in turn attached to the pull cord of the igniter. On releasing the flare, the parachute exerted a pull on the igniter "31" firing cord thus releasing the striker spring. Then the striker hit the percussion cap igniting the black powder primer and the candle (pp 74-5).

10) Single Candle Parachute Flares: I (White) and II (Red) (pp 75-7)

11) Mark S Flares, Types 1 and 2 consisted of a cylindrical buoyancy chamber which contained two candles. To these were attached a fuze, a static cord and a pull igniter. The static cord functioned either the arming device of the fuze or the pull igniter. When the device was released (from a container) over the water it went under the surface and then came up. It floated with the head of the flare just clear of the water. When the 1st candle was about $\frac{1}{4}$ burned out, a piece of safety fuse running to the 2nd candle was ignited and, after a short delay, the 2nd candle started to burn. Each candle burned for about $2\frac{1}{4}$ min (p 77-8).

12) Smoke Flares: Orange 160 and Orange 80 were used as wind drift indicators (pp 79-80).

13) Smoke Signal Flare, used as navigation aids by pilots (p 80).

14) Smoke Signal Flare ARDR was used for the same purpose as above (p 80).

15) Distress Signal Torch consisted of a narrow sheet aluminum cylinder containing three pressed charges of flare compositions which burned respectively red, white and red. The compositions were ignited by a pull igniter (p 81).

16) Ground Flare, Bodenleuchte (P) F156 217 is briefly described in BIOS Final Report 1233 (1946), p 2 and the composition of the flare is given under Pyrotechnics.

In addition to flares dropped from planes, there were some flares fired from guns, e.g. the Flare Projectile for the 203 mm Railway Gun (20.3 cm Leuchtgranate) described in TM 9-1985-3 (1953), pp 519-20. The shell was conventional in design except that it had an additional bourrelet machined near the middle of the shell body. The weight of the shell was 226 $\frac{1}{4}$ lb, that of the flare candle unit and parachute assembly 47 lb, and of the expelling charge (black powder) $\frac{1}{4}$ lb. The flare and parachute were expelled through the base of the shell.

Flash Reduction in Propellants (Mündungsfeuertvermindung oder Mündungsfeuertdämpfung). In order to reduce the flash produced on combustion of propellants, the Germans for many years used the salts of potassium, such as K sulfate, K nitrate, or K oxalate. The investigation conducted before WWI has shown that of the inorganic compounds the best flash reducers are the alkali salts and that flashiness is improved on going up the series in the Periodic System. (Cs is better than Rb and Rb is better than K).

The inorganic flash reducers (such as K sulfate) were usually loaded in small bags separately from the propellant,

and placed between the projectile and the propellant. These anti-flash bags, called in German "Vorlage", consisted of two perforated discs of artificial silk or cotton cloth sewed together in the form of "doughnuts" and filled with coarsely pulverized K sulfate. (Ref 1, p 324).

Another flash reducer consisted of a large bag with oxalic acid and a small bag with potassium oxalate.

With the incorporation during WWI of nitroguanidine (NGu) in some propellants (see Gudolpulver), it was found that NGu alone gave sufficient flashlessness without incorporating any of the usual flash reducing agents. In propellants which did not contain NGu, flashlessness could be successfully achieved by using a small bag with NGu and a small bag with K nitrate.

It should be noted that the use of inert (non-explosive and non-combustible) flash reducers such as K sulfate, nitrate, or oxalate, oxalic acid etc, is always bound to decrease the ballistic potential of the propellant and their use in large amounts should be avoided. This does not apply to NGu because this compound is not inert but is an explosive. For this reason, much larger amounts of NGu may be used, either directly incorporated in a powder, or used in a separate bag.

The following German flash reductants were examined at Picatinny Arsenal (Ref 3) during WWI:

- Potassium chloride; was used in 76.2 mm AP weapons
- Potassium sulfate; was used in 7.92 Ball, 20 mm AP/IV, 20 mm Inc, 20 mm HE Mauser, 20 mm Solothurn, 37 mm APHV, 37 mm AP/IV, 37 mm APMB, 37 mm HE, 50 mm HE, 75 mm AP, 75 mm HE and 100 mm K18 weapons
- Sodium bicarbonate; was used in some 88 mm AP guns
- Sodium sulfate; was used in some 75 mm HE guns.

According to Ref 4 the following compounds were examined at the Düneberg Fabrik Dynamit A-G as possible flash reducers (Flammendämpfer):

Aminoguanidine bicarbonate, Am acetate, Am phosphate, Am sulfate, apatite, asbestos, Ba sulfate, boron nitride, cerium oxide, cryolite, dicyandiamide, dimethyl oxamide, dimethyl urea, disodium phosphate, mercurous nitrate, methylene urea, K bicarbonate, K chloride, K iodide, K metaphosphate, K perchlorate, K phosphate, K silico-fluoride, K urea oxalate, sodium ammonium sulfate, sulfur, zinc sulfate and Zr oxide.

It was claimed that methylene urea reduced the flash to a far greater extent than any of the organic compounds used. It was also stated that cerium salts were much more effective than any other metallic salts investigated (Ref 5). Abbreviations: AP Armor-piercing; HE High-explosive; HV Hyper velocity; MB Monoblock; Inc Incendiary.

References:

- Davis (1943), p 324
- O.W. Stickland et al., General Summary of Explosives Plants, PB Rept 925 (1945), Appendix B
- Picatinny Arsenal Tech Rept 1555 (1945), p 31
- A.A. Swanson & D.D. Sager, CIOS Rept 29/24 (1946), p 6
- CIOS 29-24 (1946), p 6.

Flash Reduction in Projectiles. When it was required by the German High Command to have an AA (Flak) projectile whose explosive flash is practically invisible in the night sky, the Krümmel Fabrik A-G satisfied the requirement in the following manner:

The high explosive filling was completely surrounded with a 5 - 6 mm thick layer (sheath) of chlorine atom containing material such as tetrachloro- or hexachloronaphthalene or Am chloride.

Reference: PB Rept 925 (1945), Appendix 7.

Flüchtigkeit (Volatility). The determination of volatility of explosives is described in the analytical section.

Fluorine and Fluorides. See general section. The methods of manufacture, as practiced at the IG Farbenindustrie plants at Leverkusen and Oppau, are briefly described in BIOS Final Rept 1595 (1951).

Flüssige Tri (Liquid TNT). See Drip Oil in the general section and Tropföl in the book by Stettbacher, Schiess- und Sprengstoffe (1933), p 240.

Flüssigeluftsprengrstoffe (Liquid Air Explosives, Oxyliquit). See general section.

Fog Screen (Smoke-Screen Agent). See Nebelschutz.

Föhn Gerät, Föhn RZ 73. See RZ 73 Föhn and also TNT 135-2 (1953), p 235.

Fördit (Foerdite). According to Naoum, Nitroglycerin, Baltimore (1928), pp 407, 411, Foerdites were permissible gelatin-dynamites manufd after WWI. Their composition is given in Table 16.

Table 16

| Components and properties | Designation | | |
|---------------------------|-------------|----------|----------|
| | Fördit ? | Fördit 1 | Fördit 4 |
| Am nitrate | 41.0 | 37.0 | 38.0 |
| NG (nitroglycerin) | 23.0 | 25.5 | 21.0 |
| Collod cotton | 1.0 | 1.5 | 1.0 |
| MNT (mononitrotoluene) | 3.5 | 5.0 | 5.0 |
| Glycerin | 8.7 | 3.0 | 3.0 |
| Cereal or potato flour | - | - | 12.0 |
| K chloride | 22.0 | 24.0 | 19.0 |
| Am oxalate | - | - | 1.0 |
| Bolus (china clay) | 0.1 | - | - |
| Dextrin | 0.7 | 4.0 | - |
| Oxygen Balance, % | - | - | -19.5 |
| Trauzl Test value, cc | - | - | 220 |

Formit (Formite). One of the Ersatzsprengstoffe developed during WWI by an explosive group under the direction of Dr Hans Walter. It was obtained by heating a mixture of 30% commercial formaldehyde and NH_4NO_3 (in the ratio 6 mols HCHO to 8 mols NH_4NO_3) under reflux for about 1 hour, followed by vacuum distillation to remove the water and unreacted formaldehyde. The residue was a faintly yellow composition which consisted of MAN-Salz 25 to 30, TRI-Salz 1 to 3 and Am nitrate 67 to 74%. Its calorific value was 900 kcal/kg and volume of gases produced on explosion 1050 l/kg (calculated at 0° and 760 mm Hg). When about 15% of RDX or PETN was incorporated, the velocity of detonation was increased appreciably and the brisance was increased to that of TNT, while the volume of gases evolved on explosion was higher than for TNT. This explosive could be cast-loaded (setting point about 90°) in projectiles but unfortunately it exuded at 60-70°. It was fairly stable to heat provided no iron impurities were present.

References:

- 1) H. Walter et al, German Developments in High Explosives, PB Rept No 78,271 (1947), p 4; 2) A. LeRoux, Mém Poud, 34, 132 (1952).

Four-Cartridge Test, designed to determine the ability of mining explosives to transmit detonation, called in German *Detonationsfähigkeit Probe*, was conducted as follows:

Four cartridges, 35 mm in diameter, were laid end to end on a bed of sand and one side of the train was detonated by a No 3 blasting cap. It was required that all four cartridges be detonated completely.
Reference: BIOS Final Rept 1266 (1947), p 2.

Fp (Füllpulver) Any explosive used for filling shells, bombs, etc.

Fp 60/40 (Füllpulver 60/40) Amatol containing TNT 60 and Am nitrate 40%.

Fp O2 (Füllpulver O2). Explosive, pattern 1902 (TNT).

Fp 88 (Füllpulver 88). Explosive, pattern 1888 (P A).

Fragment Density Test, Fragment Concentration Test or Density of Splinters Test (Splitterdichteprobe). A series of investigations were conducted during WWI by the German Ordnance Dept (Waffenamt), under the direction of Dr G. Römer in order to determine the relation between effective fragment (splinter) weight, fragment velocity, fragment number and fragment range (distance of travel) and the weight and type of the explosive material, as well as the type and thickness of steel used in ammunition. These tests were conducted with a view to designing the most effective ammunition. One of the tests used for this purpose was the fragment density test (density of fragment test), which was conducted in the following manner:

A shell containing an explosive to be tested was detonated while surrounded with wooden boards 2 cm thick. The number of fragments per square meter piercing the boards was counted and the average distance at which there would be one fragment per sq m was calculated from a specially constructed curve. In order to obtain reliable results it was necessary to detonate at least 10 shells.

Following are some values for the average distance to obtain one penetration per square meter using a 105 mm shell:

TNT 39-40 m, 40/60 - Amatol 38-39 m, 50/50 - Amatol 35 m, 60/40 - Amatol 34 m, 50/50 - TNT/NaCl 26 m and 40/60 - TNT/NaCl 23 m.

Note: As this method was expensive and time consuming, the Krümmel Factory of Dynamit A-G proposed loading an iron tube with an explosive to be tested and to detonate it on lead. No details of the last method were given.
References:

- 1) O.W. Stickland et al, General Summary of Explosive Plants, PB Rept No 925 (1945), Appendix 7 2) G. Römer, PBL Rept 85 160 (1946) and private communication Dec 12, 1953.

Friction Type Igniter (Brennzünder). See under Igniter.

Friedler of Halberstadt in 1893 patented an incendiary composition which burst into flame on contact with water. It consisted of metallic sodium or potassium incorporated in a mass of crude rubber. The mixture was loaded in thin walled projectiles which being lighter than water floated on its surface [Daniel, Dictionnaire (1902), p 310].

Fritsche Zündschnur (Fritsche's Fuse). A core consisting of a pressed mixture of K nitrate 63, alderwood charcoal, (Erlenholzkohle) 13, and pulverized sulfur 24% enclosed in a fabric tube. It was slow-burning. [A. Stettbacher, Spreng- und Schiessstoffe, Zürich (1948), p 107].

F-Stoff (Titanium Tetrachloride). See general section; was used as a smoke-producing agent.

Fuel Oil Igniters (Diesel Igniters) were sticks of wood 3" x 1/8" x 1/16" which were dipped, first in acetone-celluloid solution and then in the following pyrotechnic mixture: Al 38.6, Ba nitrate 26.3, K nitrate 23.0, S 5.0 and gum 5.9%. In order to make the match friction sensitive, one end of the stick was coated by dipping it into a mixture containing K chlorate 6.9, Fe oxide 11.9, powdered glass 6.0 and gum 12.2%.

On striking, these igniters burned fiercely. It is believed that they were used for igniting fuel oil in power houses.

Reference: T.M. Bennett, BIOS Final Rept, 1313 (1947), pp 5-6.

Füllpulver (Fp) oder Füllung (Filler or Filling Explosive) See Filler.

Füllstoffe (Filling Materials). Non-explosive materials, such as NaCl, chalk, etc., incorporated in dynamites and other explosive compositions either to change the characteristics of explosives (such as to make them less brisant) or to economize on the amount of NG, TNT, etc.

Dynamites containing Füllstoffe were called **Gestreckte Dynamite** (Stretched dynamites) [Naoúm, Schiess- und Sprengstoffe (1927), p 100].

Fulmenit (Fulminate). Fulminates were Favier-type explosives such as: a) Am nitrate 86.5, guncotton 4, TNT 5.5, paraffin oil 2.5 and charcoal 1.5% (Ref 1), b) Am nitrate 82.5, guncotton 4, TNT 11, charcoal 1.5 and paraffin oil 1% (Ref 2).

References:

1) Marshall, v 1 (1917), p 391 2) E. Barnett, Explosives, Van Nostrand, N Y (1919), p 113.

Fulminante Stoff (Fulminating Compound Under this name, Stettbacher, Spreng- und Schiesstoffe (1948), p 119, lists the following substances: Jodstickstoff, (Nitrogen iodide), Knallsilber von Bertollet (Fulminating silver of Bertollet), Nitrodiazobenzolperchlorat (Nitrodiazobenzeneperchlorate) and Knallsilber (Silver fulminate).

The initiating compounds, such as MF, LA, and L St, are listed in the same book as Zündstoffe.

Fulminatn. An explosive proposed by Fuchs of Silesia: NG 68, and wool shearings (clippings) 32% [L. Gody, Traité des Matières Explosives, Namur (1907), p 359].

Fulminatschnur (Fulminate Fuse) is a detonating fuse which has a core of mercuric fulminate desensitized with paraffin. Its velocity of detonation is 5300 m/sec. [A. Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), p 107].

Funkenchronograph (Spark Chronograph). See Chronographs in the general section.

Funkenzünder [Spark Igniter or Primer (Electric) Devices], such as Bornhardt's are described in Beyling-Drekopf (1936), p 216.

Furfural Alcohol was used to initiate the combustion of gasoline at the moment of its coming in contact with mixed nitric-sulfuric acid; called SV-Stoff in Germany (CIOS 30-115, p 11).

Fuse (Zündschnur oder Zeitzünder). See general section and also Beyling-Drekopf, Sprengstoffe und Zündmittel,

Berlin (1936), pp 161-66.

Fuse (Obsolete). Daniel, Dictionnaire des Matières Explosives (1902) described a fuse called "mèche allemande" (German fuse). It consisted of a strip of paper impregnated with sulfur and saltpeter, then dried and inserted in a paper tube containing a small amount of fine grain black powder. The ensemble was placed in a bore-hole on top of a cartridge of a blasting explosive. After igniting the strip of paper, the operator took cover.

Fuse, Safety (Sicherheitszündschnur). See under Fuses in the general section.

Fusehead is the combination of bridge wire, igniter bead (drop) and lead-in wires. It is a component of electric primers and detonators [BIOS Final Rept 833, Item 2, p A3/27].

Note: In CIOS Report 24-3, p 7 the same combination is called "Electric Match Head".

Fusehead "A6". Low-tension fusehead introduced during WWII as a substitute for fusehead "G3" after it became difficult to obtain the cerium-magnesium metals necessary for the preparation of Mischmetall (mixed metal) one of the essential ingredients of "G3".

The "A6" were prepd at Troisdorf Fabrik by dipping the tip of a bridge wire (called also fuse) successively into the following liquid compositions:

a) 1st dip which consisted of dry Pb picrate 90g and silicon (20 to 40 microns) 10g, all suspended in about 75 ml of a 2% solution of NC in amyl or butyl acetate. The coating was then dried

b) 2nd dip which consisted of dry Pb picrate 50g, Pb chromate 35g and silica (20 to 40 microns) 15g, all suspended in about 75 ml of 3% solution of NC in amyl or butyl acetate. The coating was again dried

c) 3rd dip which was a lacquer consisting of a 15% solution of NC in 75/25 butyl acetate/ethanol, to which was added (20% dry weight of NC) Sipolin AOM, which is the methylcyclohexyl ester of adipic acid

d) 4th dip was the same as the 3rd, but it contained 0.8g of Sudan Brown per each 100 of lacquer.

Note: Soldering of fuse wires to lead-in wires, preparation of the dry ingredients for fuseheads dips, preparation of NC lacquers and the process of dipping the fuseheads combs are described under Fusehead Manufacture.

Reference: BIOS Final Report 833, Item 2 (1946), p A3/35.

Fusehead Comb. A new type of fusehead suitable for mechanical production was developed during WWII at Troisdorf. It consisted of a strip of sheet steel from which the outline of a comb was stamped. The two legs of each fusehead were then bonded together with "Mipolam", the tips of the teeth suitably bent and the bridge wire soldered into position. After dipping the bridge wires into fusehead compositions, the back of the comb was sheared off [BIOS Final Report No 833, Item 2, London, (1946), p A3/38].

Fusehead "G3". Low tension fuseheads used in gasless delay detonators were prepared at Troisdorf Fabrik by dipping the tip of the "bridge wire" (fuse) successively in the following liquid compositions:

a) 1st dip which consisted of 77g dry lead picrate 18.5g cerium-magnesium mixture (Mischmetall) and 4.5g alderwood charcoal, all suspended in about 75 ml of a 2% soln of NC in amyl, or butyl acetate. The coating was dried

b) 2nd dip, which contained 43.7g lead picrate, 25g aluminum (prepd by crushing Al foil to a particle size of 10 to 20 microns), 25g cerium-magnesium and 0.25g alderwood, all suspended in 75ml or a 3% soln of NC in amyl, or butyl acetate

c) 3rd dip which was a lacquer consisting of a 15% solution of NC in butyl acetate/ethanol-75/25, to which was added (20% of the dry weight of NC) Sipalin AOM, which is the methylecyclohexyl ester of adipic acid. This lacquer was fairly impermeable to moisture and cracked less readily than straight NC lacquers.

d) 4th dip which consisted of the 3rd dip to which was added 0.8g of Sudan Brown dye for each 10l of lacquer. Fuseheads made with G3 composition developed heat amounting to 580 cal/g, the pressure developed by 1g was 880 atm and the volume of gases 190 cm³ per g at NTP. The disadvantage of G3 was its hygroscopicity, which made it unstable in storage.

References:

- 1) BIOS Final Report 833, Item 2 (1946), p A3/34
- 2) PB Rept 95,613 (1947) Section D.

Fusehead Manufacture. The bridge wire ("fuse") made from an alloy 80/20-Ni/Cr. (or 60/15/17/7/1-Ni/Cr/Fe/Mo/Mn) was soldered to two lead-in wires (made of soft iron 0.60 mm in diameter) by means of a 60/40-Sn/Pb solder and Zn chloride flux. The wires were coated with a 0.25 mm layer of lacquer. Without cleaning the flux from solder, the tip of the fusehead (bridge wire) was dipped into an igniter composition, such as fusehead composition A6, fusehead composition G3, Spalt, or Marspille. Each fusehead required four dips which were conducted as follows:

A number of fusehead assemblies were inserted in a special frame placed over a pan containing an appropriate dip mixture, and the frame lowered until the tips of the fuseheads were immersed in the liquid (dip). Then the frame was removed from the dip, turned upside down and slowly moved (with the fuseheads uppermost) through a semi-circle for 15-30 seconds. After this, the frame was hung by the handles from cleats affixed to endless chains leading to drying tunnels. The tunnels were about 50 feet long and were heated by steam from below the bottom plates. The 2nd, 3rd and 4th dips were conducted in the same manner as the 1st one. After being dipped and dried, the fuseheads were graded for resistance, using a special automatic machine. For low tension fuseheads the requirement was 1.0 to 2.4 ohms and they were graded in ten steps; 1.0 to 1.2, 1.2 to 1.4.....2.2 to 2.4. For high tension fuseheads (such as "Spalt"), the usual resistance range was 3,000 to 15,000 ohms but the upper limit was not specified because it was found that fuseheads of 100,000 ohms, or even more, functioned satisfactorily.

Notes:

a) Preparation of dry ingredients for fusehead dips. The dry ingredients for fusehead dips, with the exception of Mischmetall, were usually mixed behind a barricade in a graphited papier maché drum, 6" diameter and 10" long, provided with an aluminum lid. The drum was rotated at 14 rpm. Six No 6 soft rubber stoppers were placed inside the drum to aid mixing.

The Mischmetall was considered to be too inflammable to mix in the dry state with the other ingredients and was always added separately after the other ingredients had been added to the NC varnishes. The Mischmetall was previously pulverized by grinding it under xylol in a small ball mill. Then the xylol was decanted and the slurry was transferred to filter paper on a funnel, where it was

washed with benzene, spread on trays and dried.

b) Preparation of NC varnishes for fuseheads. Before 1943, amyl acetate was used as the solvent but when it became unavailable, butyl acetate had to be used although the workers objected to it because it affected their breathing even more than amyl acetate.

Two grades of NC were used for the preparation of fuseheads E 620 and E 1160 (N content was not given) and both of them were received at the fusehead factory wet with about 30% ethanol.

The preparation of the varnish consisted in a thorough blending of the alcoholic NC with the desired amount of butyl acetate in an iron drum provided with a wooden paddle stirrer.

c) Mixing of the dry ingredients with NC varnish. A slightly smaller amount of NC varnish than required by the formulation was measured into an 8" diameter "Pollopas" plastic bowl and the dry ingredients were slowly added while continually stirring with a wooden spatula. Any Mischmetall required was then stirred together with the remainder of the NC varnish. The dip was thoroughly mixed by hand, using a wooden spatula, for at least one-half hour. The viscosity of the dip was then measured and if it was too high, it was reduced by adding small quantities of butyl acetate.

References:

- 1) R. Ashcroft et al, Investigation of German Commercial Explosives Industry, BIOS Final Report No 833, Item No 2, London, HM Stationery Office (1946), Appendix A3, p 27
- 2) Anon, Manufacture of German Detonators and Detonating Compositions, PB Rept No 95,613 (1947), Section D.

FUZE (Zünder) German fuzes may be subdivided into Bomb Fuzes and Projectile Fuzes. The first group was used in aerial bombs, some booby traps and in some pyrotechnic devices and the second group in shells and rockets.

A. **Bomb Fuze (Bombenzünder).** The Germans employed both mechanical and electrical bomb fuzes. The mechanical types were used in smaller bombs (such as 2 kg, 12 kg and 50 kg) and in some booby traps, whereas the electrical fuzes (developed and manufactured by the Rheinmetall-Borsig Co) were used in all kinds of HE bombs and in flares. Among the electrical fuzes was the "proximity fuze", type 6 used in incendiary bombs C 250 Flam and C 500 Flam.










According to Ref 1 there were ten basic types of bomb fuzes:

- 1 Mechanical impact and flare fuzes; used in 2 kg Butterfly bombs and 2 & 4 candle flares
- 2 No record
- 3 Mechanical impact fuze; used in 12 kg A/P bomb
- 4 Mechanical impact fuze; used in SC 2500 bomb
- 5 Impact fuze: instantaneous or short delay; (land targets); used in HE (SC or SD) bombs
- 6 Proximity fuze; used in C 250 and C 500 Flam bombs
- 7 Long delay time bomb fuze; used in HE bombs
- 8 Impact fuze (sea targets) with slight delay to effect detonation at some depth below the surface used in HE (SC or SD) bombs
- 9 Aerial burst (short time) fuze; used in parachute flares and photoflash bombs
- 10 Protective fuze; used in booby traps and SC 250 & 500 kg bombs.

Each of the above basic types existed in one or several variations. The following chart, based on the information obtained from Refs 2 and 4, lists these variations according to their numerical designations:

- 1) Mech Imp Nose Fz (3) AZC 10 (Hot)*, Type 3 used in SC 12 kg A/P bomb (Ref 4, p 134)
- 2) (5) Elec Fuze was forerunner of Type 5 fuzes, but is now obsolete. The A variety was manufd in Spain (Ref 1,

FUZES (BOMB)



File No 2321.5)

- 3) Elec Short Time Aerial Burst Fz EIzZ (9) or (9)* used in parachute flares and photoflash and gas bombs (Ref 4, p 167)
- 4) Elec Imp Fz EIAZ (15), or EIAZ C 50 (15) (obsolete) was used in SC 50 to 2500 kg, SD 50 to 1400 kg and SHe 50 kg bombs (Ref 2, file 2321.5 and Ref 4, p 139)
- 5) Elec Mech Long Delay Time Fz EIAZ (17), Type 7 used in SC 250 and 500 kg bombs having two pockets (Ref 4, p 152)
- 6) Elec Mech Time Fz EIAZ (17)A, EIAZ (17)A*, EIAZ (17)B* used in the same bombs as EIAZ (17) (Ref 4, p 154)
- 7) Mech Time Fz Z 17Bm used in PC 500 & 1000 kg, PC 1000 kg and HSB 1000 kg bombs and Hs 293 flying bomb (Ref 4, p 155)
- 8) Mech Imp Tail Fz (23)A used in Brand 10 kg, Nb 2 kg and SG 3 kg bombs, as well as in single unit parachute flares (Ref 4, p 134)
- 9) Mech Imp and Antibreak-up Fz (24) and (24)A used in the forward pocket of SC 2500 bomb (Ref 4, pp 135-8) (See a brief description under Antibreak-up Fuzes)
- 10) Elec Imp Fz EIAZ (25), (25)A, (25)A* & (25)A* used in HE bombs (Ref 4, p 140)
- 11) Elec Imp Fz EIAZ (25)B, (25)B, (25)C & (25)D used in SC 50 to 500 kg and some Inc bombs (Ref 4, pp 141-2)
- 12) Elec Proximity or Imp Fz, Special EIAZ (26) used in Inc bomb KC 250 "Flam" (Ref 4, p 144)
- 13) Elec Imp Fz EIAZ (28)A used in HE bombs SC 50 to 2500 kg and Inc bomb C 250 (Ref 4, p 162)
- 14) Elec Imp Fz EIAZ (28)A* or EIAZ C 50 28 (*) used in HE bombs (Ref 4, p 162)
- 15) Elec Imp Fz EIAZ (28)B used in SC bombs against sea targets (Ref 4, p 163)
- 16) Elec Imp Fz EIAZ (28)B², (28)B⁶ & (28)B^{0.7} used in HE bombs (Ref 4, pp 163-4)
- 17) Mech Aerial Burst Fz (29) used in LC 10f parachute flare (Ref 4, p 168)
- 18) Elec Imp Fz EIAZ (35) used in HE and AP bombs (Ref 4, p 142)
- 19) Elec Imp Fz EIAZ (38), (38umg) & (38u) used in HE bombs (Ref 4, pp 165-6)
- 20) Elec Imp Fz EIAZ (38sl) used in SC 250 kg bombs when employed as depth charges against U-boats (Ref 4, p 166)
- 21) Elec Imp Fz EIAZ (38)B & (38)C used in FX 1400 and HE bombs (Ref 4, pp 166-7)
- 22) Mech Antiwithdrawal Device ZusZ 40, Types I, II & III used in SC 250 & 500 kg bombs under fuzes (17), (17)A or (17)B (Ref 4, pp 177-81) (See a brief description under Antiwithdrawal Fuzes)
- 23) Mech Imp Fz AZ 41 or 34-41 used in SL 2A "Butterfly" bomb (Ref 4, p 132)
- 24) Mec Imp or Aerial Burst Fz AZ (41)A cot" was used in SD 2B "Butterfly" bomb (Ref 4, p 132)
- 25) Elec Imp Fz EIAZ (45); uses are unknown (Ref 4, p 142)
- 26) Elec Imp Fz EIAZ (45)A used in SC 50 bombs (Ref 4, p 142)
- 27) Electrically Armed Mech Imp Tail Fz AZ (46) used in KC 50 gas bombs (Ref 4, p 145)
- 28) Rocket Bomb Fz Assemblies (49)A & (49)B, Type 9 used in PC 500RS, 1000RS bombs and 1800 kg "Erdstuka" (Ref 2, file 2324.92 & 4, p 169)
- 29) Rocket Bomb Fz Assembly (49)C used in PC 1800RS (Ref 4, p 170)
- 30) Elec Antidisturbance Fz 50 and (50) used in SC 250 and 500 kg bombs in conjunction with fuzes (17), (17)A or (17)B (Ref 4, pp 181-3)
- 31) Elec Antidisturbance Fz 50b or "Y" (See under Antidisturbance Fuzes) used in HE bombs alone, or in conjunction with other Rheinmetall fuzes (Ref 4, p 184)
- 32) Elec Imp Fz EIAZ C50 (5) (obsolete) & C/50 (15) used in HE bombs (Ref 4, p 139)
- 33) Elec Imp Fz EIAZ (55)(tp), (55)A/M & (55)A* used in SL & SB and other bombs requiring instantaneous

action (Ref 4, pp 143-4)

- 34) Elec Chemical Time Fz EIAZ (57) used in "Stabo" bombs (Ref 4, p 157)
- 35) Mech Aerial Burst Fz (58) used in single & four candle parachute flares and 250 photoflash bombs (Ref 4, p 171)
- 36) Elec Aerial Burst Fz (59)A used in A/P and Inc containers (Ref 4, p 171)
- 37) Elec Aerial Burst Fz (59)B used in some HE bombs and parachute flares (Ref 4, p 171)
- 38) Mech Aerial Burst Fz (59)C used in supply-dropping containers (Ref 4, p 186)
- 39) Special Imp Fz Z 66 used in SD 250 bomb (Ref 4, p 146)
- 40) Mech Time Fz AZ (67)Zeit used in SD 2B "Butterfly" bomb. It was located centrally in the upper longitudinal surface of the bomb (Ref 4, p 159)
- 41) Mech Time Fz (67)W used in Mk AB 70 container to ignite 2 of the 40 units housed in the container (Ref 4, p 160)
- 42) Elec Aerial Burst Fz, (69)A, (69)B, (69)C, (69)D, (69)E & (69)F (Ref 4, p 173) used in SC 250, 500 & 1000 and HSB 1000 containers
- 43) Chem Mech Long Delay and Antidisturbance Fz (70)A used in SD 2B bomb (Ref 4, p 187)
- 44) Mech Antidisturbance Fz (70)B & (70)B/1 used in SD 2B bomb (Ref 4, p 187)
- 45) Modified Mech Antidisturbance Fz (70)Bumg used in aircraft towed paravane bomb (Ref 4, p 188)
- 46) Elec Aerial Burst Fz, Pyrotechnic Delay EIzZ 79, (79) & (79)A used in parachute flares, SC 250 & 500 bombs, A/P & Inc containers and photoflash bombs (Ref 4, p 174)
- 47) Mech Imp "All-Ways" Action Fz VZ (80) used in Hs 293 flying bomb (Ref 4, p 189)
- 48) Ditto VZ (80)A used in V-1 flying bomb (Ref 4, p 190)
- 49) Mech Aerial Burst Fz Z (89) used in photoflash bomb, parachute flares and some containers (Ref 4, p 175)
- 50) Ditto Z (89)B, (89)C & (89)D used in some containers (Ref 4, p 177)
- 51) Elec Imp Fz EIAZ (106)* used in Flying Bomb "Peene-münde 16" (Ref 4, p 149)
- 52) "Dust Fuze" used in SD 10 bombs (Ref 4, p 191) (See description under D.)

Following are abbreviations and designations used for bomb fuzes:


| | | |
|------|------------------------------|----------------------|
| AZ | Aufschlagzünder | Impact fuze |
| EIzZ | Elektrischer Zeit- zünder | Electrical time fuze |
| EIZ | Elektrischer Zünder | Electrical (fuze) |
| LZt | Langzeit | Long time (delay) |
| VZ | Vorzugszünder | Safety fuzing |
| Z | Zünder | Fuze |
| ZtZ | Zeitzünder | Time fuze |
| Zu | Zusatz | Addition |
| ZZSt | Zünderzwischen- stück | Fuze extension cap |

Other German abbreviations are given at the end of this German section, following the Vocabulary






Several of the German bomb fuzes were examined at Picatinny Arsenal as can be seen from the following reports:
 a) A.B.Schilling, Pic Arsn Tech Rept 1572 (1945) (Chemical Long Delay BombFuze, EIAZ)
 b) A.B.Schilling, *ibid*, 1574 (1945) (Mechanical Time Long Delay BombFuze, L Zt Z)
 c) A.B.Schilling, *ibid*, 1581 (1945) (Instantaneous and Long Delay BombFuze, EIAZ 55A)
 (See also Aerial Burst, Antidisturbance and Electric Fuzes)

D. Projectile Fuze (Geschosszünder) existed even in a greater variety than bomb fuzes. The former may be subdivided into Point Detonating (PLIz) and Base Detonating (BLIz) types. A brief description of typical


FUZES (BOMB)



Mechanical Antifreak-up Fuze (24)



FUZES (PROJECTILE) POINT DETONATING















German projectile fuzes is given by Englesburg (Ref 2). The following types are listed and briefly described in Refs 3 and 5.

I. Point Detonating Fuze













1. Imp Fz AZ 1 used in 75 mm and larger caliber shells (Ref 5, p 586)
 2. Imp Fz AZ 2 uses not indicated (Ref 5, p 588)
 3. Perc Fz AZ 23 Series were the most important and used throughout for German Artillery Ammunition, mostly for 75 mm and larger calibers. All the different fuzes bearing the number 23 were similar in functioning and major differences among them were in the delay. The 23 type fuzes existed in the following variations:
 - a) Perc Fz (with delay 0.15 and 0.25 sec) aluminum body AZ 23V(0.15) and 23V(0.25) used in shells for 75 mm Gun and 105 mm Howitzer (Ref 3, p 575 & 5, p 571)
 - b) Perc Fz AZ 23Nb used in the 75 mm Mountain Gun (Ref 5, p 576)
 - c) Perc Fz plastic body AZ 23V(0.15)(Pr) and AZ 23V(0.25)(Pr); uses not indicated (Ref 3, p 573)
 - d) Perc Fz plastic body AZ 23Nb(Pr) used in 150 mm Smoke shells (Ref 5, p 607)
 - e) Perc Fz zinc body AZ 23V(0.15)(Zn) and AZ 23V(0.25)(Zn); uses not indicated (Ref 5, p 573)
 - f) Modified Perc Fz AZ 23umg used in 75 mm and 105 mm HE shells (Ref 5, p 575)
 - g) Perc Fz AZ 23/28 used in 88 mm HE AA shells (Ref 3, p 349)
 - h) Perc Fz (delay 0.15 sec) AZ 23/42V(0.15); uses not indicated (Ref 5, p 573)
 - i) Perc Fz (modified) 1JgrZ 23nA used in 75 mm Light Infantry guns. Another model of 1JgrZ 23nA was used in 210 mm Rocket 42 (21 cm Wgr 42 Spr) (Ref 5, p 583)
 - j) Perc Fz and Perc Fz (delay 0.4 sec) sJgrZ 23 and 23V(0.4); uses not indicated (Ref 3, p 346 & 5, p 575)
 - k) Perc Fz sJgrZ 23Nb (sJgrZ 23Nb) used in Smoke shells (Ref 5, p 575)
- Note: Other, less important, versions of fuze 23 included: AZ 23 (obsolete), AZ 23V(0.8), AZ 23(0.2) and AZ 23(0.2)umg (Ref 5, pp 573-4)
- 4) Small Perc Fz klAZ 23 Series existed in the following variations:
 - a) Perc Fz (small) klAZ 23 used in 75 mm HE and 75 mm & 105 mm Smoke shells (Ref 5, p 576)
 - b) Perc Fz klAZ 23Nb used in Smoke shells (Ref 5, p 578)
 - c) Perc Fz with delay 0.2 sec, modified klAZ 23V(0.2)umg used in 75 mm A/T Guns 40, 42, 76.2 mm Russian A/T Gun 36 and Field Gun 39 (Ref 5, p 574)
- Note: Other, less important, versions of small fuze 23 included klAZ 23V(0.2), klAZ 23/1, klAZ 23V(0.2)(Pr) and klAZ 23Nb(Pr) (Ref 5, pp 574 & 578)
- 5) Igniferous DA and Graze Type Fz (with a combined graze and DA mechanism) AZ 35K used in 170 mm HE Shell (Ref 5, p 580)
 - 6) Mech Imp Fz AZ 38 used in HoC projectiles (Refs 3, p 333 & 5, p 568)
 - 7) Detonating Imp Type Fz (with DA mechanism) AZ 39 used in 50 mm HE shell (Refs 3, p 337 & 5, p 569)
 - 8) Perc Fz klAZ 40Nb & 40Nb(Pr) used in Smoke projectiles (Ref 5, p 579)
 - 9) Perc Fz AZ 47 & AZ 48, similar in construction to AZ 49, were used in 20 mm Ammo (Ref 5, p 571)
 - 10) Perc Fz AZ 49 used in 20 mm Shell (Ref 5, p 571)
 - 11) DA Imp Fz AZ 150 & 150RhS used in 20 mm Shell (Ref 2, p 315 & 5, p 564)
 - 12) Imp Fz AZ 1502F used in 20 mm Shell (Refs 3, p 303 & 5, p 547)
 - 13) Imp Fz AZ 1503 used in 20 mm Shell (Refs 3, p 309 & 5, p 547)
 - 14) Imp Fz AZ 1504 used in 20 mm Shell (Refs 3, p 309 & 5, p 547)
 - 15) Imp Fz AZ 1531 used in 20 mm Shell (Refs 2, p 315 & 3, p 307 & 5, p 549)

- 16) Imp Fz AZ 1532 used in 13 mm Projectile (Ref 5, p 550)
- 17) Imp Fz AZ 1551 used in 15 mm Projectile (Refs 2, p 316 & 5, p 550)
- 18) Imp Fz AZ 1552 used in 15 mm Projectile (Ref 5, p 546)
- 19) DA and Graze Fz AZ 2492; uses not indicated (Ref 5, p 590)
- 20) Imp DA Fz AZ 5045 used in 88 mm Shell (Ref 5, p 552)
- 21) Mech Imp Fz AZ 5072 used in 26, 20 mm and 57/28 mm HE shells for Lapered Lue guns (Refs 3, p 314 & 5, p 553)
- 22) Imp Fz AZ 5075, AZ 5075 mK & DAAZ 5075 used in 37 mm Rodded A/T Bomb (3.7 cm Pak Stielgranate) (Ref 3, p 319 & 5, p 554-5)
- 23) Imp Fz AZ 5075 used in 88 mm A/T Bomb Rocket (Ref 5, p 554)
- 24) Imp Fz AZ 5116 used in 170 mm Shell with BC (Ref 5, p 586)
- 25) Mech Time and Imp Fz Dopp Z 28K used in 210 & 280 mm projectiles (21 cm KGr 38 & 28 cm Gr 39) (Ref 5, p 605)
- 26) Mech, Time and/or Imp Fz DoppZ S/60 F1 used in 88 mm and 105 mm HE AA shells (Refs 3, p 383 & 5, p 605)
- 27) Ditto DoppZ S/60s; uses not indicated (Ref 2, p 318)
- 28) Mech Time and Graze Action Fz DoppZ S/90/45 used in 170 mm Gun in Mortar Mounting (17 cm KiMrsLaf) (Ref 5, p 601)
- 29) Combination Fz DoppZ S/160Geb used in shells for Mountain guns (Ref 5, p 596)
- 30) Supersensitive Imp Fz EKZ C/28 used in shells for Naval guns (Ref 5, p 565)
- 31) Elec Time Fz ElZtZ S/30; uses not indicated (Ref 5, p 605)
- 32) Imp Instantaneous and Delay Fz under BC HbgrZ 35D used in 210 mm Rocket (21 cm Wgr 42 Spr) (Ref 5, p 585)
- 33) Ditto HbgrZ 35K used in 170 mm HE Shell (Ref 3, p 391)
- 34) Imp Fz (Russian Design) KTM-1 used in 76.2 mm HE Shell (Ref 3, p 377)
- 35) DA Detonating Type Fz KZ f4.7 cm Pak Sprgr used in 47 mm HE Shell (Ref 5, p 566)
- 36) Mech Imp Fz (with a self-destroying arrangement) KZ ZerIPv used in 37 mm HE AA Shell (Ref 5, p 557)
- 37) DA Mech Imp Fz (with a safety device which is released by the disintegration of a pellet of gunpowder) KZ ZerIPv used in 37 mm HE A/T Shell (Ref 5, p 558)
- 38) Mech Imp Fz KZ 38 used in 40 mm HE Shell for Bofors Gun (Refs 3, p 325 & 5, p 561)
- 39) DA Imp Fz KZ 38; uses not indicated (Ref 5, p 561)
- 40) Mech Imp Fz (self-destroying) KZ 40ZerIPv used in 37 mm HE AA Shell (Refs 3, p 315 & 5, p 557)
- 41) Graze and DA Fz KZ C/27(1M) used in projectiles for Naval Guns (Ref 5, p 565)
- 42) DA Detonating Type Fz used in 47 mm HE A/T Shell (4.7 cm Pak Sprgr) (Ref 3, p 327 & 5, p 566)
- 43) Imp Fz (Czech Design) M 35ENZ 3/40 used in 47 mm German Ammo (Refs 3, p 331 & 5, p 568)
- 44) Perc Fz (Skoda Design) used in 75 mm and 83.5 mm projectiles (Ref 5, p 589)
- 45) Combination Time and Imp Fz VZ 25; uses not indicated (Ref 2, p 318)
- 46) Perc Fz WgrZ 36 used in 150 mm Rodded Bomb & 200 mm Spigot Mortar Bomb (Ref 3, p 389)
- 47) Mech Imp Fz WgrZ 38 used in 50 mm HE Mortar Bomb (Refs 3, p 335 & 5, p 592)
- 48) Imp Fz WgrZ 50 used in 280 mm, 300 mm & 320 mm Rockets (Refs 3, p 397 & 5, p 593)
- 49) Imp Fz (plastic body) WgrZtZ ACB used in 80 mm Smoke Mortar Shell (Ref 3, p 381 & 5, p 591)
- 50) Imp Fz Z 45 used in 20 mm Shell (Ref 3, p 304 & 5, p 551)
- 51) Mech Time Fz ZtZ S/30 & ZtZ S/30Fgl used in 88 mm & 105 mm HE AA shells (Refs 3, p 359 & 365 and 5, p 594 & 597)









FUZES (PROJECTILE) POINT DETONATING



FUZES (PROJECTILE) POINT DETONATING



FUZES (PROJECTILE) PD & BD



52) Self-Destroying Fz ZZ 1505 used in 20 mm Mousier Gun (Refs 3, p 411 & 5, p 548)

II. Base Detonating Fuzes (BDFs)

- 1) Imp Fz BdZ 1511 used in 20 mm Shell (Refs 3, p 399 & 5, p 608)
- 2) Imp Fz BdZ 1512 used in 20 mm Shell (Refs 3, p 399 & 5, p 608)
- 3) Imp Fz BdZ 1513 used in 20 mm Shell (Ref 5, p 609)
- 4) Imp Fz BdZ 5127 used in 88 mm APC BC Shell (Refs 2, p 319 & 5, p 609)
- 5) Graze Action Fz BdZ 5130 used in 37 mm Rodded Bomb (3.7 cm Stielgranate 41) (Refs 3, p 401 & 5, 611)
- 6) Imp Delay Fz BdZ C/38 used in heavy Naval guns (Ref 5, p 612)
- 7) Imp or Graze Action Fz BdZ D0V used in 150 mm Rocket (Ref 3, p 421 & 5, p 622)
- 8) DA Imp Fz (Small Cavity) 50 mm AP and 75 mm HE shells (Refs 3, p 411 & 5, p 617)
- 9) DA Imp Fz (Large Cavity) BdZ f 7.5 cm Pzgr used in 75 mm APC Shell (Refs 3, p 411 & 5, p 619)
- 10) Imp Fz BdZ f 7.62 cm used in 7.62 mm Russian design shells (Ref 3, p 413)
- 11) DA Imp Fz (Small Cavity) BdZ f 8.8 cm Pzgr used in 88 mm AP Shell (Refs 3, p 415 & 5, p 619)
- 12) Mech Imp Fz (Large Cavity) BdZ f 8.8 cm Pzgr used in 88 mm AP Shell (Refs 3, p 417 & 5, p 619)
- 13) Imp Selective Delay Fz BdZ f 15 cm Gr 19Be used in 150 mm Anticoncrete Shell (Refs 3, p 419 & 5, p 622)
- 14) Imp Fz BdZ M35 used in 47 mm AP Shell (Refs 3, p 407 & 5, p 615)
- 15) DA Impact Fz (Skoda Design): BdZ 15-28-39; uses not indicated (Ref 5, 611)
- 16) Elec Rimvent Fz ERZ 39 used in 150 mm & 210 mm Rockets (Refs 3, p 423 & 5, p 623)
- 17) Imp or Graze Fz (Polish Design) 27/34 WZ 36 used in 37 mm Polish Design Shell (Ref 5, p 614)
- 18) Mech Imp Fz WZ 36 used in 37 mm Polish Design Shell (Refs 3, p 405 & 5, p 615).

Following are abbreviations and designations used for projectile fuzes:

| | | |
|-------|--------------------------|--|
| AZ | Aufschlagzünder | Impact fuze, point detonating (PD) fuze |
| BdZ | Bodenzünder | Base detonating (BD) fuze |
| DoppZ | Doppelzünder | Combination fuze (time and impact) |
| EKZ | Empfindlicher Kopfzünder | Sensitive type of PD fuze (under ballistic cap) |
| EIZ | Elektrischer Zünder | Electrical fuze |
| KIAZ | Kleinaufschlagzünder | Small impact fuze, small PD fuze |
| KpZ | Kopfzünder | PD fuze |
| KZ | - | PD fuze under a ballistic cap, except in the case of KZ 38 an ordinary PD fuze |
| WgrZ | Wurfgranatzünder | Mortar shell fuze, infantry gun or howitzer shell fuze |
| ZtZ | Zeitzünder | Time fuze |

Note: The letters Nb following the fuze number signify smoke shells; the letters ZerIP signify the presence of a gunpowder pellet which is destroyed on firing to release a centrifugal firing device. Fuzes with a setting device for optional delay are stamped with the letters "m", "v", "o" to indicate the position to which the slot in the setting plug must be set to cause either delay or non-delay. The "o" stamping indicates the setting position for "without delay", the "v" stamping, followed by numerals such as V(0.25), indicates delay and the figures, the period of delay. The letters "oV", stamped together, signify "ohne

Verzögerung" (without delay), while "mV" signify "mit Verzögerung" (with delay).

Other German abbreviations are given at the end of this German section following the Vocabulary "American and British Abbreviations"

American and British Abbreviations: AA Antiaircraft; AC Aircraft; AP Armor-piercing; A/P Antipersonnel; A/T Antitank; B Base; BC Ballistic cap; BDFx Base detonating fuze; C Capped; D Detonating; DA Direct action; Elec Electrical; Fz Fuze; HE High explosive; HoC Hollow charge; Imp Impact; Inc Incendiary; M Mark; Mech Mechanical; Perc Percussion.

References:

- 1) Anon, "Enemy Bombs and Fuzes", War Dept TM E9-1983 (1942)
- 2) E. Engleburg, "The Components of German Artillery Ammunition", The Ordnance Sergeant, May 1944, pp 315-19
- 3) Anon, "German Artillery Projectiles and Fuzes", Ordnance Bomb Disposal Center, Aberdeen Proving Ground and U S Navy Bomb Disposal School Washington DC (about 1945)
- 4) Anon, "German Explosive Ordnance" (Bomb Fuzes), TM 9-1985-2 (1953)
- 5) Anon, "German Explosive Ordnance" (Projectile Fuzes), TM 9-1985-3 (1953).

Fuze Train (HE Train; Artillery Ammunition Train) (Zünder-satz) is described in the general section).

The information in Table 17 is taken from Picatinny Arsenal Technical Report No 1555, pp 11-15 and some Chemical Laboratory Reports. (See next page).

"G 3" Fusehead. See Fusehead "G 3".

Galno. See Detonators Used in Fuzes.

Gelocan. See Gelose.

Gallery, Testing. See Versuchsstrecke.

Gasdruckpatronen (Gas Pressure Cartridges). See general section and also the article entitled "Die Entwicklung der Gasdruckpatronen in Deutschland" by E.R. von Herz, in Explosivstoffe, 1954, Heft 5/6, pp 64-8.


Gaseous Metal Treatment, such as chromatizing of iron or steel articles by the diffusion of chromous chloride vapor at high temperature, is briefly described in BIOS Final Repts 839 (1946) and 1534 (1946).

Gasless Delay Detonators (Electric). German gasless delay detonators of WWI were usually prepared as follows: Al or Cu detonator shells (Hülse) having an outside diameter of 7.20 mm (for Al) and a length ranging from 52.5 to 85 mm (depending on the delay required) were thoroughly cleaned and dried before loading. Tetryl was loaded first in two increments. A total of 0.7g, to serve as a base charge; this was followed by an initiating charge of 0.3g of 60/40 L A /L St mixture and a perforated (reinforcing) cap all pressed at 250 kg/cm².


Note: Tetryl, as well as L A and L St, were previously dried to a maximum moisture content of 0.1%.

After keeping the loaded detonators for 3 days at 50° in order to remove all traces of moisture, 50 mg of loose intermediate composition was placed on top of the reinforcing cap.


Note: The intermediate composition (powdered mixture of Sb and KMnO₄) forms a loose connection between the delay composition (to be loaded next) and the initiating composition (L A /L St). The intermediate composition burns with a strong flame which facilitates the ignition of L A /L St mixture. Misfires are possible if the delay mixture is placed in direct contact with L A /L St (Cont'd on p 65).



BdZ C/38




FUZES BASE -




BdZ für 7.5 cm Spgr (Small Cavity)


(PROJECTILE) DETONATING





BdZ f 7.5 cm Pzgr (Large Cavity)




BdZ f 15 cm Gr 19Be



BdZ DOV




BdZ 27/34 f 3.7 cm Pzgr (Polish Design)



BdZ f 3.7 cm Pzgr (WZ 36) (Polish Design)

Skoda BdZ 15-28-39



BdZ M35 f 4.7 cm Pzgr




Table 17
Fuze Trains

| Primer charge | Detonator charge layers | | | Uses |
|---|---|---------------|-----------------------------------|---------------------------------------|
| | Upper | Inter-mediate | Lower | |
| 60/44-KClO ₃ /Sb ₂ S ₃ /abrasive | L St | - | L A | 47mm AP shell |
| Same as above | Black powder (cover charge) | L A | PETN/TNT | 47mm AP shell |
| Same as above | 55/45-L A /L St | - | PETN | 50mm AP and HE shell 80mm CM shell |
| Same as above | 39/54/7-L A /L St /abrasive | - | PETN | 88mm AP shell |
| Same as above | M F | - | 50/50-TNT/tetryl | Land mine |
| None | 63/37-L A /L St | - | Tetryl | 40mm HE shell |
| None | L A /Ca silicide | - | PETN | 50mm HE shell and HE taper bore shell |
| None | (24/43/32/1- Black powder/M F /KClO ₃ /Sb ₂ S ₃)over(L A /grit) | - | PETN | 37mm AP shell |
| None | 82/7/11-L A /Sb ₂ S ₃ /abrasive | - | PETN | 47mm and 50mm HE shells |
| 29/40/31-M F /KClO ₃ /Sb ₂ S ₃ | L A | - | PETN | 47mm HE shell |
| 12/46/34/8-M F /KClO ₃ /Sb ₂ S ₃ / abrasive | L A | - | PETN | 47mm HE shell |
| 54/34/12-KClO ₃ /Sb ₂ S ₃ /grit | L A /L St | - | PETN/wax | 50mm AP shell |
| 8/60/29/3-M F /KClO ₃ /Sb ₂ S ₃ / glass | L A /L St | - | PETN/wax | 75mm AP shell |
| 59/27/10/4-KClO ₃ /Sb ₂ S ₃ /C/abrasive | 14/86-L A /L St | - | 95/5-PETN/wax | 47mm AP shell |
| Same as above | 55/45-L A /L St | - | PETN | 75mm AP shell |
| 26/37/30/7-M F /KClO ₃ /Sb ₂ S ₃ /glass | L A /L St | - | PETN/wax | 88mm AP shell |
| None | 65/35/-L A /L St | - | RDX | 88mm AP shell |
| None | 55/45/-L A /L St | - | PETN | 88mm HE Mech TF shell |
| 13/45/34/8-M F /KClO ₃ /Sb ₂ S ₃ / abrasive | 55/45/-L A /L St | - | PETN | 105mm HE How shell |
| None | 94/6-L A /tetracene | - | PETN | A/T Stick grenade 41 |
| 51/24/25-KClO ₃ /Sb ₂ S ₃ /grit | L A /L St | - | PETN | 50mm Mor bomb |
| None | (5/76/19-NC/lead oxide/silicon)over (25/52/23 - KClO ₃ /PbCrO ₄ /silicon) | - | PETN | 80mm Mor bomb |
| 14/38/42/6-M F /KClO ₃ /Sb ₂ S ₃ / glass | M F | - | 40/60-tetryl/TNT (pressed) | Tellermine 35 |
| 41/41/3/15-L St /Ba(NO ₃) ₂ /Sb ₂ S ₃ /Ca silicide | 59/39/2-L A /L St /graphite | - | PETN | Tellermine 42 or 45 |
| 65/35-L A /Ca silicide over PETN | L A /L St | - | 87/13-PETN/wax and tetryl booster | 75mm HoC shell 38, 105mm HoC shell 39 |
| None | 94/6-L A /tetracene | - | PETN | A/T Rocket 30 |
| None | 94/6-L A /tetracene | - | PETN | 88mm A/T, HoC Rocket |
| None | L A /L St | - | PETN | 88mm A/T HoC Rocket, 150mm Rocket 41 |
| None | 60/40-L A /L St | - | PETN | 210mm Rocket 42 |

Abbreviations: AP Armor-piercing; A/T Antitank; BD Base detonating; CM Chemical mortar; F Fuze; HE High explosive; HoC Hollow charge; How Howitzer; L A Lead azide; L St Lead stypnate; M F Mercuric fulminate; Mor Mortar; PD Point detonating; PETN Pentaerythritol tetranitrate; T Time; Tellermine Land mine

The next step was to press into contact with the intermediate composition the delay element containing a compressed pulverulent mixture of Sb and $KMnO_4$. The detonator shell was then crimped just above the upper end of the delay sleeve in order to provide a seat for the Mipolam sealing plug.

Note: According to CIOS Rept 24-3, pp 5-6, the gasless delay powder (also called gasless delay fuze powder) consisted of about 70% Sb powder and 30% K permanganate for slow burning, or about 46% Sb and 54% K permanganate for fast burning. The permanganate was ground in a disc or plate crusher mill to approximately 80 mesh. The Sb was ground from lumps in a vibratory ball mill and the powder was transferred by a screw feed into an air separator. The fines which did not exceed 10 microns in size were collected and blended with the permanganate by means of a tumbling mill. The resulting mixture was compressed into tablets in a rotary multiple punch press. (It is assumed that the tablets were formed to give more intimate contact between the ingredients). The tablets were then broken down in a plate crusher mill and the resulting powder used for filling detonators.

The fusehead assembly (see Fusehead Manufacture) consisting of bridge wire, igniter head, two lead-in wires (insulated by Mipolam) and the Mipolam plug was inserted in the detonator shell in such a manner that the plug rested on the shoulder of the detonator shell formed by crimping. A second crimping was then made above the plug and the lead-in wires were connected to a source of electricity when the detonator was to be fired.

References:

- 1) A. Ashcroft et al, B I O S Final Rept 833, Item 2, H M S O London (1946), Appendix A3
- 2) Anon, Manufacture of German Detonators and Detonating Compositions, PB Rept 95,613 (1947) (Section B to L incl).

Gaspatronen. See Gasdruckpatronen.

Gegenläufige oder Kumulative Zündung (Running Toward or Cumulative Priming). In order to increase the efficiency of an explosive charge it was initiated simultaneously from the opposite ends, using two electric blasting caps or pieces of detonating fuse.

[A. Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), p 135].

Gelatine-Astralit (Gelatin-Astralite). A plastic low-freezing explosive based on dinitrochlorohydrin (DNCH). Several varieties existed, of which the composition manufactured before WWI by the Dynamit A-G was widely used in shaft sinking by the freezing process and also in other rock work where low-freezing dynamite is desired during the colder parts of the year, such as in building water power plants. It had approximately the following composition and properties: gelatinized dinitrochlorohydrin (DNCH), including NG 30, mixture of DNT and TNT 10, and Am and Na nitrate with wood meal 60%; Trauzl test value 400cc, Pb block crushing 18.0 mm, sensitiveness to initiation required at least a No 3 cap, propagation (gap) using two 25 mm cartridges 20.0 mm, velocity of detonation 7300 m/sec, heat of explosion 1127.5 kcal/kg, temperature of explosion 2534°, density 1.45.

The gelatine-Astralit which was permitted to be transported on German railroads was required to contain gelatinized dinitroglycol 30, aromatic dinitrocompounds 8, aromatic trinitrocompounds 4, Am nitrate and vegetable meal 58%. Its properties were: Trauzl value 415 cc, Pb block crushing 19.0 mm, sensitiveness to initiation required at least No 1 cap, propagation (gap) using two 25 mm cartridges 50.0 mm, velocity of detonation about 6500 m/sec

at a density of 1.45, heat of explosion 1158 kcal/kg, temperature of explosion 2485°, volume of gases at NTP 864.4 l/kg, specific pressure 9733 atm.

Reference: P. Naoum, Nitroglycerin (1928), pp 378 and 381.

Gelatine-Carbonit (Gelatin-Carbonite). Several varieties of these permissible explosives are described by Naoum, Nitroglycerin, Baltimore, (1938), pp 407, 411 & 441, as can be seen from Table 18

Table 18

| Ingredients and some properties | Gelatin-carbonites | | | |
|---------------------------------|--------------------|------|------|----------------|
| | I | III | D | No designation |
| Am nitrate | 31.0 | 46.4 | 31.5 | 41.5 |
| Na nitrate | 4.4 | 7.0 | - | - |
| K nitrate | - | - | 5.1 | - |
| NG (mixed with collod cotton) | 23.6 | 10.1 | 30.0 | 26.0 |
| Glycerin plus gelatin | 4.0 | 5.0 | 2.5 | 6.9 |
| Na chloride | 24.0 | 27.5 | 30.9 | 25.5 |
| Vegetable meal | 10.0 | 4.0 | - | - |
| TNT | 3.0 | - | - | - |
| Ultramarine | - | - | - | 0.1 |
| Oxygen Balance, % | -13.1 | +2.2 | +5.3 | - |
| Trauzl Test, cc | 220 | 200 | 225 | 260 |
| Veloc of Detonation, m/sec | - | - | - | 2300 |

Gelatine-Cheddite (Gelatin-Cheddite). Gelatinous explosives based on chlorates, such as Na chlorate 70, and collod cotton gelatinized with liquid TNT 30%.

Reference: P. Naoum, Nitroglycerin, Baltimore (1928), p 353.

Gelatine-Dahmenit (Gelatin-Dahmenite). A type of low-freezing gelatinous explosive manufactured before WWI.

Table 18a gives two types A and B

Table 18a

| Ingredients and some properties | Gelatin-dahmenites | |
|---------------------------------|--------------------|------|
| | A | B |
| Dinitroglycerin | 27.4 | 27.4 |
| Collodion cotton | 0.6 | 0.6 |
| Nitrotoluenes | 4.5 | 3.5 |
| Naphthalene | 0.5 | - |
| Ammonium nitrate | 32.0 | 32.0 |
| Potassium nitrate | 2.0 | 2.0 |
| Sodium nitrate | 5.5 | 4.5 |
| Alkali chloride | 27.5 | 30.0 |
| Trauzl Test, cc | 233 | 205 |
| Charge limit in firedamp, grams | 350 | 700 |

Reference: P. Naoum, Nitroglycerin (1928), p 419.

Gelatine-Donarit (Gelatin-Donarite). A type of gelatinous industrial explosive containing about 50% of Am nitrate, 30% of mixture of dinitrochlorohydrin with nitroglycol and 20% of other ingredients. Its properties are: temp of explosion 3225°C, vol of gases at NTP 803 l/kg, cartridge density 1.45, specific pressure 10100 kg/cm², veloc of deton 6250 m/sec, Trauzl test 380 cc and impact sensitivity with 2 kg weight 20 cm.

(See also Donarit Gelatin Type, under Donarit).

Reference: F. Weichelt, Sprengtechnik, C. Marhold, Halle/Saale (1933), pp 37 & 375.

Gelatine-Dynamit (Gelatin Dynamite) - the first gelatinous NG explosive. It was prepd by A. Nobel in 1875 (See Swedish Section). The current gelatin-dynamites consist of 20 to 65% of a liquid nitric ester (such as NG) mixed with a small amount of collodion cotton and 80 to 35% of "Zamischpulver", called in the U S A "dope".

They may be subdivided into the following types:

- A) Gewöhnliches und schwerfrierendes (Ordinary and difficultly freezing (low freezing))
- B) Phlegmatisiertes, transportsicheres (Phlegmatized, safe to transport)
- C) Schlagwetteres. Safe in the presence of firedamp (permissible dynamites).

To the A type of dynamites belong the blasting gelatin and the dynamites shown in Table 19 with the exception of those which contain only a small amount of NG. Any of these explosives may be rendered low-freezing by incorporating nitroglycerol, dinitroglycerin, dinitrochlorhydrin, etc.

The following composition, listed by Stettbacher (Ref 4, p 85), may be given as an example of the "schwergefrierbares" dynamite: NG with nitroglycerol 62.5, collod cotton 2.5, Na or K nitrate and/or K perchlorate 27.0, and wood meal or rye meal 8.0% with prepared chalk (Schlämme) added 0.5%.

To the B group belong dynamites in which part of the NG is replaced by dinitrochlorhydrin.

Note: Aromatic nitrocompounds have been used in other countries to replace part of the NG.

To the C group belong explosives containing small amounts of NG and appreciable amounts of cooling agents such as alkali chlorides. Dynamites which contain larger amounts of ammonium nitrate (see Ammongelatine) also belong to the permissible group.

Table 1 which follows gives composition and some properties of typical gelatin-dynamites

Table 19

| Components and some properties | High-strength gelatin-dynamites | | | | Other gelatin-dynamites | | | | | |
|--|---------------------------------|------|-----|------|-------------------------|----------|------|--------|--------|----------|
| | Plasting gelatin | 81% | 80% | 75% | No 1 | No 2 | No 3 | No 4 a | No 4 b | No 5 |
| NG | 92 | 75.8 | 75 | 70.4 | 62.5 | 56 to 61 | 40.0 | 40.0 | 40.0 | 18 to 20 |
| Collod cotton | 8 | 5.2 | 5 | 4.6 | 2.5 | 1 to 5 | - | - | - | - |
| Vegetable meal | - | 3.8 | 5 | 5.7 | 8.0 | 3 to 8 | 6.0 | 7.0 | 2.0 | 2 to 4 |
| TNI & DNT | - | - | - | - | - | 0 to 4 | 10.0 | - | - | 12 |
| Hydrocarbon | - | - | - | - | - | - | - | - | 5.0 | - |
| K nitrate | - | 15.2 | 15 | 19.3 | - | - | - | - | - | - |
| Na nitrate | - | - | - | - | 27.0 | - | 44.0 | 41.0 | - | - |
| Alkali nitrate and/or K perchlorate | - | - | - | - | - | 25 to 30 | - | - | - | - |
| K perchlorate | - | - | - | - | - | - | - | - | 41.0 | 54 |
| Cooling agents, such as alkali chlorides | - | - | - | - | - | - | - | 12.0 | 12.0 | 12 |
| Oxygen Balance, % | +0.4 | - | - | - | +4.4 | - | +7.0 | +12.0 | +2.5 | +11.0 |
| Density | 1.6 | - | - | - | 1.55 | - | 1.6 | 1.7 | 1.8 | 1.8 |
| Trauzl Test, cc | 560 | - | - | - | 400 | - | 290 | 230 | 330 | 250 |
| Pb Block Crushing, in mm | 24.0 | - | - | - | 20.0 | - | 18.0 | 19.0 | 20.0 | 18.0 |
| Max Veloc of Detonation, m/sec | 8000 | - | - | - | 7000 | - | 6500 | 6500 | 6500 | 6500 |
| Heat of Explosion, kcal/kg(H ₂ O vapor) | 1560 | - | - | - | 1235 | - | 1030 | 850 | 1150 | 800 |
| Temp of Expln, °C | 3200 | - | - | - | 2950 | - | 2800 | 2500 | 3000 | 2650 |

Note: Due to the shortage of nitroaromatic compounds during WWII the Germans used some commercial dynamites in demolition charges as well as in some hand grenades. (See also Ammondynamit, Ammongelatine, Donarit and Gelatine-Dynamit).

References:

- 1) P. Naoum, Nitroglycerin etc., Baltimore (1928), pp 331, 334 and 349-50
- 2) J. Pepin Lehalleur, Poudres etc, Paris (1935), p 333
- 3) Anon, Allied and Enemy Explosives, Aberdeen Proving Ground, Md (1946) pp 151-2
- 4) A. Stettbacher, Spreng- und Schiesstoffe, Zürich, pp 85-86.

Gelatine-Leonit (Gelatin-Leonite). One of the permissible gelatinous low-freezing explosives manufd by Westdeutsche Sprengstoffwerke at Dortmund [Naoum, Nitroglycerin (1928), p 418].

Table 20 (Gelatine-Prosperit)

| Components and some properties | Designation | |
|--------------------------------|-------------|------|
| | 1 | 2 |
| DNCII (dinitrochlorhydrin) | 20.0 | 20.0 |
| NG (nitroglycerin) | 5.0 | 5.0 |
| NC (nitrocellulose) | 0.5 | 0.5 |
| DNT (dinitrotoluene) | 5.0 | 5.0 |
| Cereal meal | 2.5 | 2.0 |
| Am nitrate | 36.0 | 30.0 |
| Na nitrate | 4.0 | 10.0 |
| Na chloride | 21.0 | 27.5 |
| K oxalate | 6.0 | - |
| Oxygen Balance, % | +0.4 | -1.2 |
| Trauzl Test, cc | 225 | 210 |

(See next page).

Gelatine-Prosperit (Gelatin-Prosperite). According to Naoum (Ref 1 & 2) gelatin-prosperites were low-freezing gelatinous explosives based on dinitrochlorohydrin. Table 20 lists two such explosives.

(See previous page).

References:

- 1) Naoum, Schiess- und Sprengstoffe, Dresden (1927), p 152
- 2) Naoum, Nitroglycerin, Baltimore, (1928), p 118.

Gelatine-Romperit. Same as Gelatine-Donarit [Weichelt, (1953), p 37].

Gelatine-Telsit. See under Swiss Explosives.

Gelatine-Tremont (Gelatin-Tremonte). Gelatinized low-freezing explosives, manufd for many years by the Castropoer Sicherheitssprengstoffe in Westphalia. E.g.: a) gelatinized di- and trinitroglycerin 47.5, DNT 5.0, wood meal 5.0, Am nitrate 22.5, and Na nitrate 20.0%; Trauzl value 400 cc; b) gelatinized di- and trinitroglycerin 30.0, DNT 10.0, wood meal 2.0, Am nitrate 40.0, and Na nitrate 18.0%; Trauzl test value 375 cc.

Reference: Naoum, Nitroglycerin (1928), p 368.

Gelatine-Wetter-Astralit. Gelatinous low-freezing dynamites used prior to WWI: a) dinitrochlorohydrin 20.0, NG 5.0, collod cotton 0.5, DNT 5.0, meal 2.5, Am nitrate 36.0, Na Nitrate 4.0, K oxalate 6.0, and Na chloride 21.0%; Trauzl test 225 cc and oxygen balance + 0.4% (Ref 1); b) dinitrochlorohydrin 16, NG 4.0, collod cotton 0.5, MNB 1.6, DNT 4.0, Am nitrate 7.5, flour or potato meal 7.5, Na nitrate 5.0, charcoal 0.5, casior oil 2, Am oxalate 2.5, and Na chloride 14% (Ref 2).

References:

- 1) Naoum, Nitroglycerin, Baltimore, (1928), p 418
- 2) Thorpe's Dictionary, London, v 4 (1940), p 554.

Gelatine-Wetter-Nobelit. A permissible explosive for use in gaseous coal mines: gelatinized NG 30, Am nitrate 26.5, wood meal 0.5, Na chloride 40 and 3% of a 50% aqueous solution of Ca nitrate [A. Stettbacher, Spreng- und Schiessstoffe, Zürich (1948), p 91-2].

Gelatinerfähigkeit von Nitrocellulose (Gelatinizing Ability of NC). See Kast-Metz, (1944) pp 111 & 201-4.

Gelatiniermittel oder Lösemittel. See Gelatinierungsmittel für Nitrocellulose.

Gelatinerung (Gelatinization). See general section.

Gelatinerungsmittel für Nitrocellulose (Gelatinizing Agent for NC). See Kast-Metz (1944) pp 109-162.

Gelatinerverfahren (Gelatinization Process). Gelatinization of NC is described in the general section.

Gelalit I (Gelalite I). A mining explosive consisting of 30 to 37.5 Am nitrate, 30 of NG (containing some collod cotton), 0.5 to 1.5 wood flour, 0 to 2 DNT (contg 0 to 50% TNT) and 32% alkali chloride. It was permissible in gaseous coal mines, provided the charge was not higher than 200g. In dusty and non-gaseous mines the maximum charge was 600g.

References:

- 1) J. Pepin Lehalleur, Poudres, etc, Paris (1935), p 414

- 2) C. Beyling and K. Drekopf, Sprengstoffe- und Zündmittel, Springer, Berlin (1936), p 100.

Gelbmehl (Yellow Flour). Same as Tetranitrocarbazole.

Gelbmehl S (Yellow Flour S). Same as Tetranitrodiphenylsulfone.

Gelignit II. One of the gelatin dynamites manufactured before WWI: NG 47.5, collod cotton 2.5, K nitrate 37.5, wood meal 3.5 and rye meal 9%. [Naoum, Nitroglycerin (1928), p 330].

Gelose or Galactan (Cairaghan Moss). $(C_6H_{10}O_5)_x$, m wt (162.08)_x. Carbohydrate obtained from agar-agar. Its aqueous solutions were used in some ammonium nitrate explosives for controlling the plasticity, such as in Wetter-Wasagit B: NG 27.8, NC 0.7, Am nitrate 30.5, rock salt 39.5, gelose 0.7, wood meal 0.3, and talc 0.5%.

References:

- 1) R. Ashcroft et al, B I O S Final Rept 833, Item 2, M S O, London (1946), p A1/11
- 2) PB Rept 62,877 (1946), Table 1.

Gelsenkirchen Testing Gallery (Schlagwetter-Versuchsstrecke in Gelsenkirchen). See under Testing Galleries in the general section.

Gerät 38. See "DO Gerät 38", under Abbreviations at the end of the German section.

Gerät 040. Same "60 cm Mörser Karl" listed under Weapons.

Gerlich Type Gun (Gerlich Reducing Bore Gun). Same as Tapered Bore Gun or Squeezebore Gun.

Geschossplitterprobe (Projectile Fragments Test). See Fragments Density Test.

Geschütz (Artillery Piece, Gun). See under Weapons.

Geschwindigkeit der Drucksteigerung (Rate of Pressure Increase). The relation between pressure and time of burning of propellants may be determined as described in H. Brunswick, Das rauchlose Pulver, Berlin, (1926), pp 215-20. If the rate of burning is great, the propellant is called Schnell (quick) and if the rate is low, the propellant is called Langsam (slow).

Gesilit (Gesilite). Gesilites were permissible explosives used during and after WWI. Table 21 gives two examples

Table 21

| Components | Designation | |
|----------------------|-------------|-------|
| | No 1 | No 2 |
| NG (nitroglycerin) | 30.75 | 30.75 |
| DNT (dinitrotoluene) | 5.25 | 5.25 |
| Am nitrate | - | 22.00 |
| Na nitrate | 18.00 | - |
| Dextrin | 39.00 | 21.00 |
| Na chloride | 7.00 | 21.00 |

References:

- 1) E. Colver, High Explosives, N Y (1911), p 167
- 2) F.M. Turner, Condensed Chemical Dictionary, Reinhold, N Y (1942), p 289.

Gessner Projectile. According to W. Dornberger "V-2" Viking (1951), pp 122-3, Dr Otto Gessner of Peenemunde developed during WW II a tremely slender, fin-stabilized sub-caliber projectiles which could be fired from ordinary gun barrels. It seems that these projectiles were identical with the "arrow projectiles", briefly described under A. These projectiles were used in the 105 mm Antiaircraft Gun (10.5 cm Flak) and in the 280 mm Gun Type 5 (28 cm K-5). It was claimed that by using such projectiles in the Gun K-5 the range was increased from 37 miles, for the ordinary projectile, to 56 miles with the arrow projectile carrying a sabot behind thick-walled fins. With a lighter type of projectile, which instead of a sabot had an obturation skirt attached to its middle, a range of about 90 miles was attained. When using this projectile the lateral dispersion was only about 2 mils. (See also under Arrow Projectile).

GESTEINSSPRENGSTOFFE (Blasting Explosives).

These are explosives suitable for blasting rocks, ores, constructions etc, but not for gaseous coal mines. The following types have been used:

Gesteins-Albit. Na perchlorate 80, DNN 12, wood meal 3, phenanthrene 3 and NG 2% (Ref 5, p 129)

Gesteins-Dorfit. Am nitrate 65, TNT 15, K nitrate 5, rye flour 5 and Na chloride 10%; velocity of detonation 4605 m/sec at d 1.17 with a 50 mm diameter confined charge (Ref 2, p 195).

Gesteins-Koronit (Gesteins-Coronite). A type of commercial explosive several varieties of which are given in Table 22

Table 23 (Gesteins-Persalit)

| Components and some properties | Designation | |
|--------------------------------|-------------|------|
| | No 1 | No 2 |
| K perchlorate | 35 | 34 |
| Am nitrate | 43 | 48 |
| DNT | 8 | 10 |
| DNN | 8 | - |
| Carbon (powder) | - | 2 |
| NG | 2 | - |
| Wood meal | 4 | 6 |
| Oxygen Balance, % | -0.3 | +1.7 |
| Trauzl Test, cc | 330 | 325 |

Gesteins-Westfalit (Gesteins-Westphalite). An ammonal type explosive consisting of Am nitrate 84.5, DNT 12.0 and Al 3.5% (Ref 2, p 114).

References:

- 1) A. Marshall, Explosives, Churchill, London, UK (1917), p 384
- 2) E. Barnett, Explosives, Van Nostrand, N Y (1919), p 114
- 3) P. Naoum, Schiess- und Sprengstoffe, Steinkopf, Dresden (1927), pp 129,133
- 4) P. Naoum, Nitroglycerin etc, Williams & Wilkins, Baltimore (1928), p 428
- 5) C. Beyling & K. Drekopf, Sprengstoffe und Zündmittel, Springer, Berlin (1936)
- 6) T.L. Davis, The Chemistry of Powder and Explosives, Wiley, N Y (1943), p 364.

Table 22 (Gesteins-Koronit)

| Components and some properties | Designation and source of information | | | |
|-----------------------------------|---------------------------------------|--------------------|----------------|----------------|
| | No 1 Ref 3,p129 | No 2 Ref 3,p129 | T1 Refs 3&6 | T2 Refs 3&6 |
| Na chlorate | 76.0 | 83.0 | 72.0 | 75.0 |
| Mononitronaphthalene (MNN) | 5.0 | 8.0 | - | - |
| Dinitronaphthalene (DNN) | 5.0 | - | - | - |
| DNT & TNT | - | - | 20.0 | 20.0 |
| Nitroglycerin (NG) | 4.0 | 3.0 | 3.0 to 4.0 | - |
| Wood meal | 2.0 | 1.0 | - | - |
| Vegetable meals | - | - | 1.0 to 2.0 | 1.0 to 2.0 |
| Paraffin | 8.0 | 5.0 | 3.0 to 4.0 | 3.0 to 4.0 |
| Oxygen Balance | - | - | +3.0% | +1.9% |
| Trauzl Test | - | - | 290cc | 280cc |
| Pb Block Crushing | - | - | 20 mm | 20 mm |
| Sensitiveness to Initiation | Required at least : | | No 3 cap | No 1 cap |
| Gap Test (using 25 mm cartridges) | - | - | 8 cm | 8 cm |
| Veloc of Detonation | - | - | 5000 m/sec | 4300 m/sec |
| Density of Cartridge | - | - | 1.57 | 1.46 |
| Heat of Explosion | - | - | 1219 cal/g | 1241 cal/g |
| Temp of Explosion | - | - | 3265°C | 3300°C |

Gesteins-Permonit oder Permonit I. Perchlorate explosive manufactured before WWI by the Sprengstoff A-G Carbonit for use in potash, and ore mines: K perchlorate 30, Am nitrate 40, Na nitrate 7, TNT 15, flour 4, wood meal 3, and jelly 1%. Its Trauzl test value was 320 cc, gap test 7.0 cm and sensitiveness to impact with a 2 kg weight 70 cm. (Ref 1).

Gesteins-Persalit (Gesteins-Persalite). A type of commercial explosive described in Ref 3, p 133. The composition and some properties of these explosives are given in Table 23.

Gestreckte Dynamit (Stretched Dynamite). See under Füllstoffe.

Gewehr (Rifle). See under Weapons.

Gewehr 43. German semi-automatic rifle, caliber 7.92 mm, developed in 1943. This rifle incorporated some features of a similar Russian weapon, particularly the Degtyarev LMG (light machine gun) and the Tokarev semi-automatic

title. The Gewehr 43 weighed 9.75 lbs together with a 0.25 pound sling and a 0.4 pound magazine. [M. Johnson, Jr, Ordnance 29, 306-310, (1945)]

Gewerblichesprengmittel (Industrial or mining explosives). See Commercial Explosives.

Gewichtsverlustprobe (Loss of Weight Test) to determine the stability of an explosive or a propellant, is described in Kast-Metz (1944), p 246 et..

Gichtstaub (Flue Dust or Blast Furnace Dust). It was used as a component of liquid air explosives. Kast-Metz (1944), p 467).

Glasmine 43 (Glass mine 43). See under Landminen and also TM 9-1985-2 (1953), p 275.

Glide Bomb (Gleitbombe) is a streamlined missile provided with wings and stabilizers to allow it to glide towards a target in free flight, after it is released from a plane flying in approximately horizontal position.

The bomb is used to attack targets at a greater horizontal distance from the releasing plane than would be attacked by normal bombs.

This method of bombing is designed in order to keep the releasing plane out of the range of enemy's AA guns.

A short description of principles of a glide bomb may be found in the following paper:

E.W.Sponder, "Untersuchung der Seitenstabilität einer Gleitbombe mit einer automatischen Steuerung ohne Voreilung", Zentrale für Wissenschaftliches Berichtswesen der Luftfahrtforschung des Generalluftzeugmeisters (ZVW), Berlin-Aldershof, Forschungsbericht Nr 1819, May (1943) (Included are 12 references). Note: English translation is available as Technical Memorandum 1248 of the National Advisory Committee for Aeronautics August 1950.

Glycerin (Glycerin). See general section.

Note: According to M.L.Sheely, "Synthetic Glycerin", BIOS Miscellaneous Report No 24, (1948), the Ludwigshafen Plant of the IG Farbenindustrie manufactured synthetic glycerin during WW II by the "Five Stage Method", starting from propanol, chlorine, Na carbonate and Na hydroxide. A brief description is included in the above Reference.

Glycerogen. A colorless, viscous, glycerin-like liquid consisting of about 35% glycols, 35% glycerin, 25-28% hexitol, erythritol and other compounds. It can be prep'd by continuous catalytic hydrogenolysis of sugar at 200° and 325 atmospheres. The detailed process, operated commercially at the Höchst Plant of IG Farbenindustrie, is described in Ref 1.

Glycerogen was used as a substitute for glycerin in cellulose films, sausage casings, printing pastes, pharmaceuticals, etc and its nitrated product was used as a substitute for NG in dynamites.

References:

1. M.L.Sheely, Glycerogen, a Substitute for Glycerin, BIOS Miscellaneous Report No 23, (1948)
2. F.M.Turner, Condensed Chemical Dictionary, Reinhold, N Y (1950), p 320.

Glykol (Glycol) (abbrev here to Gc). See general section.

Glykolnitrat (Nitroglycol, abbreviated to NGc). See general section.

Glycerin oder Glycerin (Glycerin, abbreviated to G). See general section.

Glycerintrinitrat oder Glycerintrinitrat (Nitroglycerin, abbreviated to NG). See general section under Glycerin.

GM-1 (Liquid Nitrous Oxide) was used as a fuel booster for airplane engines (CIOS 25-18, p 5).

GP (Powder). A powdered sodium picrate combined with a binding agent such as Igetex SS (copolymer of butadiene and styrene). It was used as a propellant in Panzerfaust ammunition (CIOS 25-18, p 28).

"G" Pulver ("G" Propellant) (Known in the German Air Forces as "K" Pulver). It is a "cool" smokeless propellant developed before WW II by Gen Uto Gallwitz and collaborators. Historical:

The use of nitroglycerin (NG) propellants had the following disadvantages:

a) Glycerin needed as the starting material for NG was obtained in those days from food materials contg fats and oils which were in short supply during the war.

Note: With the development of synthetic methods of manufacture of glycerin there probably will be no shortage in future wars.

b) The manufacture of NG propellants involved some danger to personnel, particularly during the rolling and extruding operations

c) NG is comparatively a slow and poor gelatinizing agent for NC

d) NG propellants are "hot", i.e. they have a high heat of combustion and a high flame temperature which results in a rapid erosion of the gun barrel and a decrease in its serviceable life.

Note: The marked effect of the heat of combustion on the gun barrel, (erosion), is shown by the following example: a gun using a propellant with 950 kcal/kg was good for only 1700 firings, while one with 820 kcal/kg could stand 3500 firings.

Due to the above disadvantages of NG propellants, work was started in Germany about 1934 under the direction of Gen U. Gallwitz to develop a propellant which would be less erosive than NG propellants and at the same time possess the high ballistic potential required for muzzle velocities of the order 3300 ft/sec.

At first nitroglycol (ethyleneglycoldinitrate) (EGDN) was tried as replacement for NG, but this proved unsuccessful due to the extreme volatility of EGDN even at moderate temperatures. Then, in 1935, Gen Gallwitz proposed use of nitrated "Polyglykol", a product easily available from non-food materials. Polyglycol, which is a mixture of diethyleneglycoldinitrate (DEGDN), (called in Germany Diglykol) with a small amount of EGDN, was considerably less volatile than straight EGDN and although it was more volatile than NG, it could be used in moderate climates such as in Europe. It proved however, to be unsuitable for tropical climates, such as in Africa.

Polyglycol (or straight DEGDN) was a better gelatinizer for NC than NG, but the most important fact was that it produced considerably "cooler" (calorific value about 690 kcal/kg) propellants than it was ever possible to obtain with NG. The diminished erosion prolonged the life of gun

barrels to a much greater degree than was expected. (See under Erosion of the Bore).

The new propellant was called "G" Pulver (G stands for the first letter of Gallwitz).

Due to the fact that "Polyglykol" (or straight DEGDN) is a good gelatinizer for NC, it was possible to prepare propellants more homogeneous than NG propellants and with smoother surface grains. Manufacture of "G" propellants, especially the rolling operation, was much easier and less dangerous and no rolling flaws (often observed in NG propellants) were observed. Another advantage of G propellants was that they permitted the incorporation, without becoming brittle, of materials which do not take part in the gelatinization, such as K sulfate (flash reducer), nitroguanidine (NGu), etc (See also "Gudolpulver").

Being a good gelatinizer, DEGDN may be used in smaller quantities than NG and in a wider range. For instance, while the amount of NG should be 40-45% for optimum results, DEGDN may be used in the range of 20 to 45%, the remainder being NC stabilizer (such as centralite, or acar-dite) and one of the following: urethanes, phthalates, flash reducers (such as K sulfate or NGu), vaselinc, graphite, Mg oxide, etc.

One such propellant: 61.53% of NC (blend of soluble and insoluble NC giving an average nitrogen content 12.2%), 26.37 of DEGDN 7.50 of ethyl centralite, 1.60 of vaselinc, 0.65 of phthalate, 0.25 of Mg oxide, 0.1 of graphite and 2.00% of K sulfate had a calorific value of 690-700 kcal/kg as against 820-950 kcal/kg for NG propellants.

As was mentioned above, the DEGDN is more volatile than NG (4-5 times more volatile) and is unsuitable for tropical climates.

Inasmuch as the German troops had trouble with "G" propellants during the African campaign, Gen Gallwitz proposed using the nitrated product of triethyleneglycol (TEG), (called Triglykol in Germany). This nitrated product (TEGDN) was only slightly more volatile than NG (about 1 1/2 times) and was quite suitable for hot climates. The replacement of DEGDN by TEGDN permitted the production of propellants with even lower calorific value than the ordinary "G" propellants. For instance one containing 58.55% NC (a blend with an average N content of 12.2%) 25.10 TEGDN, 12.00 ethyl centralite, 0.25 MgO, 0.10 graphite, and 4.00% K sulfate had a calorific value of 650 kcal/kg.

TEGDN possesses the same advantages from the point of view of its gelatinizing properties as DEGDN and likewise permits the incorporation of non-gelatinizers such as K sulfate and NGu.

"G" propellants are slow burning and are efficient in weapons where a projectile remains in the barrel long enough for complete combustion of the propellant. All kinds of guns large howitzers and mortars are in this class.

All of these weapons have sufficiently long barrels for complete combustion of the powder. "G" propellants in flake form were found unsuitable, however, in medium and small caliber howitzers and mortars because a projectile does not remain for a sufficient time in the barrel for complete combustion of the propellant. In these cases "Gudol" propellants were found to be quite suitable. (See also "Gudolpulver", Erosion of the Bore and under Propellants).

References:

1) Uto Gallwitz, Die Geschützladung (Propelling Charge) Heereswaffenamt, Berlin (1944) (English translation is available)

2) O.W.Stickland et al, General Summary of Explosive Plants,

PB Rept 925 (1945), p 13 and Appendix 9, p 90

3) H.H.M.Pike, Report on Visit to Düneberg Factory of D A-G, CIOS Rept 31-68 (1946), pp 4-5.

GRANATE (Gr oder gr). The term "Granate" is used in Germany as a base word for various types of rounds. By adding a prefix and/or a suffix to the word the exact nature of the projectile is indicated, E.g.:

| | | |
|---------------------------------|----------|--|
| Sprenggranate | Sprgr | HE shell |
| Sprenggranate 41 | Sprgr 41 | HE shell for tapered bore gun |
| Nebelgranate | Nbgr | Smoke shell |
| Gewehrgranate | Gewgr | Rifle grenade |
| Handgranate | Hdgr | Hand grenade |
| Panzergranate | Pzgr | Armor-piercing (AP) shell |
| Panzergranate 39 | Pzgr 39 | APCBCHE (Armor-piercing capped, ballistic cap, high explosive) shell |
| Panzergranate 40 | Pzgr 40 | AP shell with a tungsten carbide core |
| Panzergranate 41 | Pzgr 41 | AP shell with a tungsten carbide core for tapered bore gun |
| Gewehrsprenggranate | Gewspgr | Antipersonnel rifle grenade |
| Gewehrpanzergranate | Gewpazgr | Antitank rifle grenade |
| Gewehrpropagandagrana-te | — | Propaganda rifle grenade |
| Gewehrfallschirm-leuchtegranate | — | Illuminating parachute rifle grenade |
| Granate Beton | GrBe | Anticoncrete shell |
| Granate Hohlladung | GrHL | Hollow charge shell |

German Artillery rounds of ammunition may be divided into Patronenmunition and Kartuschmunition:

A) **Einheitsmunition oder Patronenmunition** (One-piece ammunition or cartridge ammunition). It is an ammunition, the complete round of which may be loaded into the weapon in one operation. This corresponds to American fixed ammunition. The complete round consists of a cartridge case containing a primer and a propelling charge. The case is permanently crimped to the projectile.

E.g.: Rounds used in AA guns, caliber 20 mm, 28 mm, 30 mm, 37 mm, 40 mm, 42 mm, 50 mm, 75 mm, 88 mm, and 105 mm.

Note: The Germans designated the caliber of guns in centimeters but we designated them in millimeters in order to conform to the American practice

B) **Kartuschmunition oder Getrenntmunition** (Separated cartridge ammunition) is an ammunition somewhat intermediate between American semi-fixed and separate-loading ammunition. It consists of a projectile which is placed into the weapon first and a cartridge case (containing a primer and one or several bags with propelling charge), which is loaded into the breach afterwards. The cartridge case is not fixed to the projectile. The number of bags with propellant could be varied, according to the range requirement, at the place of firing.

Note: The Germans employed cartridge cases for all their ammunition in order to prevent the escape of gases to the rear of the weapon when the breach is opened; they never

used the rounds corresponding to the American separate loading ammunition.

The Kartuschenmunition was used in some 75 mm rounds as well as in 105 mm, 150 mm, 170 mm, 210 mm, 240 mm, 280 mm, and 353 mm guns, or howitzers.

The German Artillery projectiles as well as numerous captured Austrian, Belgian, Czech, Dutch, French, Polish, Rumanian, Russian and Yugoslav projectiles used by the Germans during WW II are briefly described in TM 9-1985-3, pp 358-544. (See also Smoke Projectiles)


Following is the list of these projectiles, arranged by calibers together with the references to TM 9-1985-3.

- 1) 20 mm included: Oerlikon AP, Mauser AP, Solothurn AP, Oerlikon HE, Mauser HE and Solothurn HE are described in TM 9-1985-3, pp 358-60
- 2) 28/20 mm included: HE 2.8/2.0 cm SpgrPatr and AP PzGr used in Tapered Bore Gun, PzB 41 (pp 371-3)
- 3) 30 mm included: AP, HE, HE-T, AP with Core and Inert-Loaded projectiles used in Solothurn AC Guns (pp 379-82)
- 4) 37 mm included:
 - a) HE-T (3.7 cm Spgr L'spur) used in Naval C/30 Gun (p 382)
 - b) AP Without Cap (3.7 cm Pzgr) used in Pak (p) captured from the Polish (p 382)
 - c) Rodded Bomb (3.7 cm Stielgranate 41) used in Pak 41 (p 383)
 - d) AP Without Cap (3.7 cm PzgrPatr 18) used in Flak 18 and Flak 36 (p 384)
 - e) HE (3.7 cm SpgrPatr 40) used in Pak (p 385).
 - f) AP Without Cap (3.7 cm PzgrPatr) used in Pak (p 386)
 - g) HE (3.7 cm SpgrPatr umg) used in Pak (p 386)
 - h) HE (3.7 cm SpgrPatr C/30) used in C/30 Gun. (p 388)
- 5) 40 mm included: HE (4 cm SpgrPatr) and HE-Inc (4 cm Br Spgr Patr) used in Flak 28 (pp 388-9)
- 6) 42/28 mm included:
 - a) HE (4.2-2.8 cm SpgrPatr L Pak 41) used in L Pak 41 (Tapered Bore Gun) (p 374)
 - b) AP With Core (4.2-2.8 cm Pzgr Patr L Pak 41) used in L Pak 41 (Tapered Bore Gun) (p 374)
- 7) 47 mm included:
 - a) AP With Tungsten Carbide Core Arrowhead Design (4.7 cm PzgrPatr 40) used in Czech design tapered bore guns Pak (t) and K36 (t) (p 375)
 - b) HE (4.7 cm SpgrPatr 36) used in some Czech design guns (p 390)
 - c) HE Austrian design [4.7 cm SpgrPatr (ö)] used in Bühler K (ö) (p 391)
 - d) APC [4.7 cm PzgrPatr 36 (t)] used in Czech design guns Flak 37 (t) and Pak (t) (p 392)
- 8) 50 mm included:
 - a) AP With Tungsten Carbide Core, Arrowhead Design (5 cm PzgrPatr 40 KwK) used in the Tank Gun, 5 cm KwK (p 376)
 - b) AP Without Cap (5 cm PzgrPatr KwK) used in KwK (p 394)
 - c) HE (5 cm Spgr Patr 38) used in KwK 39 and Pak 38 (p 395)
 - d) APC (5 cm PzgrPatr KwK) used in the same guns as above (p 395)
 - e) HE-Inc-T (5 cm Br Spgr Patr 41 L'spur) used in Flak 41 (p 397)
 - f) HE Mortar projectile used in 5 cm LGr W 36 (p 330)


9) 75 mm included:

- a) AP With Tungsten Core, Arrowhead Design (7.5 cm PzgrPatr 41) used in the Antitank Gun, Pak 41 (p 378)
- b) HE (7.5 cm SpgrPatr KwK 34) and AP With Ballistic Cap and AP Cap (PzgrPatr 39 KwK 40) used in KwK, KwK 40, StuG 40 and Pak 40 (p 398)
- c) HoC Type 39 [7.5 cm GrPatr 39 (HL)] used in GebK 15 (p 399)
- d) HoC [7.5 cm Gr Patr 38 KwK (HL)] used in KwK, StuG, KwK 40, StuG 40, GebK 36 and the Recoilless Gun for Airborne Troops (LG 40) (p 400)
- e) HoC [7.5 cm GrPatr KwK (HL/B)] used in the same guns as above (p 401)
- f) Smoke (7.5 cm Nbrg Patr KwK) used in the same guns as above (p 402) (See also Smoke Projectiles)
- g) HE (7.5 cm GebG 15 Aluminium) used in GebK 15 (p 403)
- h) HoC (7.5 cm Igr) used in LIG 18 and L Geb IG 18 (p 404)
- i) HE (7.5 cm Igr 18 AZ 23 nA) used in LIG 18 and L Geb IG 18 (p 405)
- j) HE (7.5 cm SpgrPatr 75/50) used in Skoda Dual-Purpose Gun (p 406)
- k) HoC, Type 38 (7.5 cm GrPatr 38 HL/A) used in LFK 18 (p 407)
- l) AP [7.5 cm Pzgr 40 (W) Pak 40] used in Pak 40 (p 408)
- m) APC (7.5 cm PzgrPatr KwK 38) used in KwK, StuG, LFK and in Recoilless Gun for Airborne Troops (p 409)
- n) HoC (7.5 cm GrPatr 38 HL/A KwK) used in KwK 38, KwK 40, LFK 18, GebK 36, StuG 40, Pak 40, FK 15 and Recoilless Gun 40 (p 409)
- o) APC (7.5 cm Pzgr 39 FES) used in Pak 40, 40/1, 40/2 and 40/3 (p 410)
- p) HoC (7.5 cm GrPatr 38 HL/B) used in same guns as given under (n) (p 411)
- r) HE (7.5 cm SpgrPatr 34) used in StuK 40 (L/45), StuK 40 (L/48) and Pak 40, 40/1, 40/2 and 40/3 (p 417)
- s) HoC (7.5 cm Jgr 38 HL/A) used in L.JG 18 and L GebG 18 (p 425)
- t) Projectiles used in captured 75 mm Belgian, Dutch, French, Polish and Yugoslav guns are described on pp 410, 413, 415, 419, 420, 421, 423 and 425 of TM 9-1985-3
- 10) 75/58 mm was the Brandt Sabot projectile developed in France by E.Brandt (p 369)
- 11) 76.2 mm included the following projectiles used in captured Russian weapons:
 - a) HE (7.62 cm Spgr 284/4) used in GebK 307(r) (p 426)
 - b) HE (7.62 cm SpgrPatr 39) used in FK 36 (r) and Pak 36(r) (p 426)
 - c) AP (7.62 cm PzgrPatr 40) used in FK 296(r) FK 36(r) and Pak 36(r) (p 427)
 - d) APC (7.62 cm PzgrPatr 39 rot) used in Pak 36 (r) (p 428)
 - e) HE (7.62 cm Spgr 280/2) used in JKH 290 (r) (p 429)
 - f) HE (7.62 cm Spgr 284/4) used in GebK 307(r) (p 430)
 - g) HoC (7.62 cm Gr 38/2 HL/B) used in JKH 290 (r) (p 430)
 - h) HE (7.62 cm Spgr 39/2) used in JKH 290 (r)


PROJECTILES (GRANATEN)



Czechoslovak Navy HE 20mm Complete Rounds of Ammunition




28-20mm HE Shell for Tapered Bore Gun




30mm HE and AP Shells for AC Guns



Solothurn HE




37mm HE Shell Type 40




37mm HE Shell for Gun C/30


37mm AP Shell Without Cap




40mm HE Shell for AC Gun




42-28mm HE Shell for Tapered Bore Gun



42-28mm AP Shell for Tapered Bore Gun




47mm AP Shell (Arrow-head)






47mm HE Shell for Böhler Gun (Austrian Design)

PROJECTILES (GRANATEN)






- 12) 76.5 mm projectiles were used in captured Austrian, Czech and Yugoslav 7.65 cm weapons (pp 432-435)
- 13) 80 mm included:
- a) HE Mortar proj (8 cm Wgr 38 and Wgr 39) used in sGrW 34 (p 529)
 - b) Colored Smoke proj (8 cm Wgr 38 Deut) used in sGrW 34 (p 533). (See also Smoke Projectiles)
 - c) HE, Smoke proj (8 cm Wgr 34 Nb) used in Mortar, MGrW 31 and KzGrW 42 (p 532)
- 14) 83.5 mm included: 8.35 cm Pzgr(t) and Gr 23/20(t) used in captured Czech AA Gun, Flak M/2 2(t) (pp 436-7)
- 15) 88 mm included:
- a) APC (8.8 cm PzgrPatr 39) used in Flak 41 (p 438)
 - b) HE (8.8 cm SpgrPatr L/4.5(Kz)) used in Flak 18, Flak 36 and Flak 37 (p 438)
 - c) AP (8.8 cm Pzgr 41) used in Flak 36 and Flak 41 (p 439)
 - d) AP with Tungsten Carbide Core, Type 40 (8.8 cm Pzgr 40) used in Flak 36 and Flak 41 (p 439)
 - e) HE (8.8 cm Spgr Patr L/4.7 FFS) used in Flak 41 and Flak 43 (p 441)
 - f) APC (8.8 cm Pzgr Patr 40 BdZ) used in Flak 18, Flak 36 and Flak 37 (p 441)
 - g) HE, Type 43 (8.8 cm SpgrPatr 43) used in KwK 43, Stuk 43 (L/71) and Pak 43 and 43/71 (L/71) (p 442)
 - h) HE (8.8 cm Pzgr 39/43) used in Pak 43 and Pak 43/41 (p 442)
 - i) HE (8.8 cm Spgr Flak 41) used in Flak 41 (p 443)
 - j) HoC (8.8 cm GrPatr HL) used in KwK 36 (L/56) (p 444)
 - k) HE (8.8 cm Spgr L/4.5) used in KwK 36, Flak 18, Flak 36, Flak 37 and in Modified Russian AA Gun 8.5/8.8 cm Flak 39 (r) (p 444)
 - l) HE, with Controlled Fragmentation (8.8 cm Spgr L/4.5 ZtZ) used in KwK 36 (L/56) (p 445)
 - m) AP (8.8 cm Pzgr) used in Flak 18, 36, 37 and in Flak 39 (r) (p 446)
 - n) AP (8.8 cm Pzgr 39/1) used in Pak 43, Pak 43/41 (L/71) and Stuk 43(L/71)(Self-propelled gun)(p 446)
 - o) AP (8.8 cm Pzgr 39) used in Flak 18, 36 & 37, KwK 36 (L/56) and in Flak 39 (r) (p 448)
 - p) Incendiary Shrapnel (8.8 cm Gr Br Schr Flak) used in Flak 18, 36 and 37 (p 448)
- 16) 100 mm included:
- a) HoC proj Type HL/B and Type HL/C are described in TM 9-1985-3, pp 450-1, but their uses are not given
 - b) HE Czech proj [10 cm DoppZGr M 21 (t)] used in captured Czech, Polish and Yugoslav Light Field Howitzers (p 451)
 - c) HE Yugoslav proj [10 cm Spgr DoppZ 311 (j) and Spgr (AZ) 310 (j)] used in captured Czech, Polish & Yugoslav Light Field Howitzers and Mod 28 Yugoslav Mountain Howitzer (p 452)
 - d) HE Czech proj [10 cm DoppZGr 30 (t)] used in Czech, Polish and Yugoslav Light Field Howitzers (p 453)
 - e) HE Polish proj [10 cm StgGr (p)] used in Czech, Polish and Yugoslav Light Field Howitzers (p 455)
 - f) HE German proj (10 cm Spgr 38) used in Czech, Polish and Yugoslav Light Field Howitzers (p 454)
 - g) HE Mortar proj (10 cm Wgr 37) used in NbW 35 (p 533)
- 17) 105 mm included:
- a) HE (10 cm Gr 19) used in K 18 (p 456)
 - b) HE used in K 17/04 nA and K 17 (p 457)
- c) AP used in several Light Field Howitzers (pp 457 and 459)
 - d) HE (10 cm Spgr L/4.4) used in Flak 38 (p 467).
 - e) AP-T (10 cm Pzgr rot) used in Flak 38, Flak 39, sK 18 and sKT (p 468)
 - f) AP (10 cm Pzgr rot L'spur) used in Light Field Howitzer (LFH 16). (p 470)
 - g) HE used in Light Field Howitzer LFH 16) (p 471)
 - h) Smoke used in Howitzers (LFH 16, LFH 18, LFH 18MB and Stuk 42) (p 472)
 - i) HE for Long Distance Use in Light Field Howitzers 18 with Muzzle Brake (LFH 18MB) (p 473)
 - j) HoC Type A, HoC Type B and HoC Type C used in the same Light Field Howitzers as listed under (h) (pp 474-77)
 - k) HE, Model 15, Model 23 and Model 28 used in the 10 cm Skoda Howitzer (pp 477-80)
 - l) HE (10 cm Spgr Patr L/4.4 Kz) used in Flak 38 and Flak 39 (p 480)
 - m) HE (10 cm Gr 19 Kz 13) used in sK 18, KT and lgKT (p 481)
 - n) HE proj with disintegrating band is described briefly on p 369 of TM 9-1985-3
 - o) Projectiles used in captured 105 mm Belgian, French, Polish, Russian and Yugoslav guns are described on pp 459, 461 and 463-467 of TM 9-1985-3
 - p) HE (10 cm FHGrStg mR 11) used in Light Field Howitzers: FH 18, FH 18/1, FH 18/2, FH 18 mM, FH 18/39 and FH 18/49 (p 536)
- 18) 122 mm included HE projectile 12.2 cm Spgr FEW (r) used in captured Russian guns K 390/1 (r) and K 390/2 (r) (p 481)
- 19) 128 mm included:
- a) HE (12.8 cm SpgrPatr L/4.5), described briefly on p 482
 - b) AP (12.8 cm Pzgr FES) used in Flak 40 (p 483)
 - c) AP (12.8 cm KPS) used in Flak 40 (p 483)
 - d) AP (12.8 cm Pzgr 43) used in Flak 44, self-propelled (p 484)
- 20) 150 mm included:
- a) HE With Disintegrating Bands, Sabot Type (p 370)
 - b) HE [15 cm AZGr 37 (t)] used in Czech Medium Howitzer sFH 25 (t) (p 485)
 - c) HE (15 cm KGr 42) used in K 18 (p 486)
 - d) HoC (15 cm Jgr 39 HL/A) used in Stuk 43(L/12) and sJG 33 (p 486)
 - e) A/C (15 cm Gr 19 rot Be) used in K 18 and K 39 (p 487)
 - f) Czech projectiles, such as 15 cm GrM 25 (t) (p 488), 15 cm AZGrM 34 (t) (p 488), 15 cm MinGr M 13/19 (t) (p 489), 15 cm MinGr 28 (t) and 15 cm MinGr M 28 (t) (p 490) used in captured Czech Field Howitzers
 - g) HE (15 cm Jgr 38 FES) used in the Assault Howitzer StuH 43 (p 491)
 - h) AP (15 cm PzSpgr L/37 mHbe) used in K 18 (p 491)
 - i) HE (15 cm Gr 36 FES) used in sFH 18 (p 492)
 - j) HoC (15 cm Gr 19 HL) used in sFH 18 and sFH 13 (p 492)
 - k) A/C (15 cm Gr rot Be) used in K 18, K 39 and in K (E) (p 493)
 - l) HE (15 cm Gr 19m Zdlg 36) used in sFH 18 (p 494)
 - m) HE proj of cast steel (15 cm Gr 19 Stg) used in sFH 18, sFH 13 and sHT (p 495)
 - n) Smoke (15 cm Gr 19 Nb) used in sFH and sFH 13 (p 497)

PROJECTILES (GRANATEN)



PROJECTILES (GRANATEN)




PROJECTILES

Case 78


(GRANATEN)




100 mm HE Shell L/45




120 mm AP Shell (Pzgr KP)



128 mm AP Shell (Pzgr 43)




150 mm HE Shell (Gr 42)




150 mm HoC/A Howitzer Shell (Jgr 39 H/A)




150 mm Anticoncrete Shell Type 19




150 mm HE Howitzer Shell (Gr M 34(f))




150 mm HE How Shell (Jgr 38 FES)




150 mm AP Shell for Heavy Gun 18



150 mm HoC/A Shell Type 39




150 mm Anti-concrete Shell (Gr 19 Rot Be)




150 mm HE Shell Type 19 with Gaine 36



150 mm HE Shell (Cast Steel)



150 mm AC Shell 19 Be



152 mm HE Shell FEW

- o) Smoke (15 cm Jgr Nb) used in sIG 33 (p 497) (See also Smoke Projectiles)
- p) Rodded Bomb (15 cm Stielgranate 42) used sIG 33 (p 498)
- r) HE (15 cm Gr 18) used in sFH 13 (p 500); HE (15 cm Jgr 38) used in sIG 33; HE with Base Fuze and Ballistic Cap (15 cm Spgr L/4.4 BdZ mit Haube) used in Ki Mrs Laf (p 504); HE with Nose Fuze (15 cm Spgr L/4.6 Kz) used in K39 (p 504).
- s) SAP (15 cm Hpzgr) used in K 39 (p 504)
- t) AP (15 cm Pzgr) used in K 39 (p 504)
- u) Smoke (15 cm Gr 38 Nb) used in sFH 18 (p 506)
- v) A/C (15 cm Gr 19 Be) used in sFH 18 (p 507)
- w) APC projectile for unknown weapon (p 509)
- x) Rocket Assisted Projectile (15 cm RGr 19) (p 509)
- 21) 152 mm included the following types used in captured Russian weapons:
- HE (15.2 cm Spgr 436) used in KH 433/1 (r) and KH 433/2 (r) (p 510)
 - A/C (15.2 cm Gr 434 Be) used in the same weapons as above (p 511)
- 22, 155 mm included the following projectiles used in captured French (f) and Polish (p) Weapons
- HE [15.5 cm StgGr 422 (f)] used in K 418 (f), K 419 (f) and K 420 (f) (p 512)
 - Smoke [15.5 cm Gr 427 (f)] used in K 420 (f) (p 512) (See also Smoke Projectiles)
 - HE [15.5 cm Gr 417 (f) and Langgr 415 (f)] used in sFH 414 (f) and sFH 17 (p) (p 513-4)
 - HE [15.5 cm Gr 421 (f)] used in 15.5 cm K 420 (f) (p 515)
- 23) 170 mm included:
- HE (17 cm KGr 38Hb) used in Ki Mrs Laf (p 516)
 - HE (17 cm KGr 39) used in Ki Mrs Laf (p 517)
- 24) 194 mm included the HE proj [19.4 cm StgGr 486 (f)] used in captured French Railroad Gun, K(E) 486 (f) (p 517)
- 25) 200 mm included the HE Mortar Projectile 20 cm Wgr 40 (p 534)
- 26) 203 mm included:
- A/C [20.3 cm Gr 503/2 Be (r)] used in captured Russian Heavy Howitzers H 503 (r) and H 503/2 (r) (p 518)
 - Flare projectile (20.3 cm Leuchtgr) used in K(E) (p 520) (See under Flares)
 - HE [20.3 cm Spgr L/14 Kz (Hb) and Spgr L/4.7 Kz mHb used in K(E) (p 521)
 - SAP (20.3 cm Spgr L/4.7 BdZ mHb) used in K(E) (p 520)
- 27) 210 mm included A/C proj (21 cm Gr 18 Be) used in Mrs 18 and in Ig Mrs 18 (p 522)
- 28) 240 mm included:
- HE (24 cm Spgr L/4.5 BdZ mlib and Spgr L/4.2 mHb) used in Theodor Bruno Railway Gun, ThBrK(E) (p 524)
 - HE (24 cm Gr 40) used in Czech Heavy Gun, sK (t) (p 525)
- 29) 280 mm included:
- Rifled 28 cm projectile. Its nomenclature and uses are unknown (p 526)
 - HE Rocket Assisted Rifled proj (28 cm RGr 433 and Gr 35) used in K 5 (E) (p 527-28)
- 30) 355 mm included A/C project (35 cm GrBe) for Howitzer M (p 529) (Its caliber was also given as 353 mm).
- 31) 380 mm included HE Mortar proj (38 cm Wgr 40) and Smoke proj (38 cm Wgr 40 Nb) (p 535).
- American and British Abbreviations: AA Antiaircraft; AC Aircraft; A/C Anticoncrete; AP Armor-piercing; APC

Armor-piercing, capped; HE High-explosive; HoC Hollow charge; Inc Incendiary; SAP Semi-armor-piercing; T Tracer
German Abbreviations: See Abbreviations at the end of this German section.

Reference: Anon, Technical Manual TM 9-1985-3 (1953), pp 358-544.

The same information is given in the following references:

- 1) Anon, Enemy War Materials Inventory List. Ammunition, Supreme Headquarters AEF, (1945), pp 1-154
- 2) Anon, Recognition Handbook of German Ammunition, Supreme Headquarters AEF (1945)
- 3) Anon, German Artillery Projectiles and Fuzes, Ordnance Bomb Disposal Center Aberdeen Proving Ground and U S Navy Bomb Disposal School, pp 1-177 (No date).



Note: According to Ref 1, pp 131-3, the following larger caliber projectiles were used by the Germans: 380 mm HE and AP for 38 cm Siegfried Kanone C/34; 406 mm HE and AP for 40.6 cm Adolf Kanone or for Navy gun, Schiffskanone C/34; 420 mm HE, Anticoncrete for 42 cm howitzer, called Gamma Mörser; 540 mm HE for 54 cm heavy howitzer, called Karl Mörser; 615 mm HE for 61.5 cm heavy howitzer, called Karl Gerät and 800 mm HE for 80 cm super heavy gun, called Sevastopol or Gustav Geschütz.

Granate Hand und Granate Gewehr (Hand Grenade and Rifle Grenade).


The following types of grenades are described in TM 9-1985-2 (1953), pp 319-345:

- 1) Stick Hand Grenades, Models 24, 39 and 43 (Stielhandgranaten 24, 39 und 43) (pp 319-20)
- 2) Egg Type Hand Grenade, Model 39 (Eierhandgranate 39) (p 321)
- 3) Shaving Stick Offensive Hand Grenade (p 322)
- 4) Magnetic Antitank Hand Grenade, 3kg (Haft-hohlladungsgrenate, 3kg) (p 323) (See Haft-hohl-ladung)
- 5) Hollow Charge Stick Type Hand Grenade (p 324)
- 6) Antitank (Hollow Charge) Hand Grenade (Panzer-wurfmüne) (p 324)
- 7) Smoke Hand Grenades, Models 39 and 41 (Nebelhandgranaten 39 und 41) (pp 325-6)
- 8) Smoke Hand Grenade 14 (Blendkörper 14) (p 327)
- 9) Smoke Hand Grenade 24 (Blendkörper 24) (p 328)
- 10) Smoke Hand Grenade, Egg Type (p 329)
- 11) Hand Smoke Signal, Red (Handrauchzeichen-Rot) (p 329)
- 12) Lacrymatory Hand Grenade (Tear Bomb) (p 330)
- 13) 46 mm Antitank (Hollow Charge) Rifle Grenade (S S Gewehrpanzergranate, 46 mm) (p 331)
- 14) 61 mm Antitank (Hollow Charge) Rifle Grenade (S.S.Gewehrpanzergranate, 61 mm) (Two types, pp 331 and 332)
- 15) Antipersonnel Rifle or Hand Grenade (Gewehr-oder Hand-Sprenggranate) (p 332)
- 16) Antitank (Hollow charge) Rifle Grenade (Gewehr Panzergranate) (p 334)
- 17) 37 mm Antitank (Hollow Charge) Stick Grenade (p 335)
- 18) Large Antitank (Hollow Charge) Rifle Grenade (Grosse Gewehr Panzergranate) (p 336)
- 19) Hollow Charge Rifle Grenade (Schuss GgP 40) (p 337)
- 20) Propaganda Rifle Grenade (Gewehr Propaganda-granate) (p 338)
- 21) Illuminating Parachute Rifle Grenade (Gewehr Fallschirmleuchtgranate) (p 339)
- 22) Hollow Charge Grenade, called Faustpatrone (p 339)
- 23) Pistol Grenade (Wurfkörper Leuchtpistole) (p 340)
- 24) 27 mm Pistol Grenade HE Egg Type, fired from a Walther pistol (p 341)

PROJECTILES (GRANATEN)



240 mm HE Shell Capped Type L/45 240 mm HE Shell Capped Type L/42 Rifled Design Shells 88mm HE 280 mm HE



280 mm Rocket Assisted Rifled Shell Type 4331 280 mm HE Rifled Shell Type 35 280 mm HE Shell Type 39 353(355) mm A/C Howitzer Shell M1

- 25) 26 mm Pistol Grenade (26 mm Wurfgranatepatrone für 326 Leuchtpistole) (p 342)
 26) HE Cartridge for 27mm Pistol Grenade (Sprengpatrone für Kampfpistole) (p 343)
 27) Hollow Charge Signal Pistol Grenade (Panzerwurfkörper 42 Leuchtpistole) (p 344)
 28) 27 mm Message Pistol Grenade (p 345)
 29) 27 mm Multistar Signal Cartridge for Pistol (p 345)

Several of the German grenades were examined at Picatinny Arsenal, as shown by the following References:

- 1) A.B.Schilling, Pic Arsn Tech Rept 1460 (1945) (Offensive Hand Grenade, Egg Type)
- 2) A.B.Schilling, *ibid.* 1467 (1945) (Hand Grenade, Stick Type)
- 3) A.B.Schilling, *ibid.* 1494 (1945) (Hand Grenade and Rifle Grenade for use in the Mauser Rifle Grenade Discharger)
- 4) F.G.Haverlak, *ibid.* 1507 (1945) (61 mm Rifle Grenade)
- 5) F.G.Haverlak, *ibid.* 1509 (1945) (46 mm Rifle Grenade)

Note: A brief description of pistol and rifle grenades is given under P and R.

Great Enzian or E-4. One of the guided (directed) missiles used by the Germans during WW II (See also Enzian, under Guided Missiles).

Reference: TM 9-1985-2 (1953), pp 229-33.

Grenade. See Granate Hand und Granate Gewehr.

"Griess". An "atomized" aluminum powder consisting of small spherical particles. Its density was about twice as high as for Pyroschiff (q v). It was used in pyrotechnic compositions.

Reference: Dept of the Army TM 9-1985-2 (1953), p 82.

"Grizzly Bear". See Brumbär.

Grobes Blätchenpulver. Large Grain Smokeless Propellant formerly used in larger caliber German guns is described in Daniel, *Dictionaire* (1902), p 364.

Grundladung (Base Charge). This term applies to the base (main) charge of a blasting cap or a detonator or to a special ignition charge mentioned under Ignition. It does not, however, apply to the main charge of a propellant, which is called Hauptkartusche (See also under Cordite Charge Casings).

G-Salz is one of the names for Nitroguanidine, also called Nigu; it is abbreviated in this work as NGu.

Gudolpulver (Gudol Propellant), invented in 1937 by Dynamit A-G may be considered as a G Pulver (DEGEN or TEGN propellant) in which a large amount of nitroguanidine (NGu) is incorporated.

As G Pulver is slow burning in comparison with NG propellants, it was found unsuitable for use in medium and small caliber mortars and howitzers. This is because the barrels of these weapons are too short to permit complete combustion of the G Pulver while the projectile is still in the gun barrel. In order to obtain satisfactory results in such weapons, the rate of combustion of the propellant should be higher than in the regular G Pulver but at the same time its flashlessness should be low. This can be

achieved by incorporating into the G Pulver some nitroguanidine (NGu).

Due to the fact that nitrated glycols contained in G Pulver are good gelatinizers for NC, comparatively large amounts of NGu can be incorporated without making the propellant too brittle (NGu is not a gelatinizer for NC and is not gelatinized by nitrated glycols). In order to have a propellant of good performance, the crystals of NGu should be short and fine and uniformly distributed throughout the mass of the propellant. This was accomplished in the following manner:

After preparing the nitrocellulose - dinitrodiglycol (or dinitrotriglycol) jelly by kneading in a Werner-Pfleiderer apparatus, short fibered nitroguanidine was gradually added and thoroughly incorporated. Then the mass was rolled for about 25 minutes and the resulting sheets cut to the desired size.

Following is an example of a flake Gudolpulver suitable for howitzers: NC(N=13%) 38.03, DEGDN 31.12, NGu 30.00, acardite 0.50, MgO 0.25 and graphite 0.10%.

Nitroguanidine was also found to be suitable for incorporation in cool tubular cannon propellants, as for instance: NC(N=12%) 39.48, DEGDN 16.92, NGu 30.00, ethylphenylurethane 5.00, diphenylurethane 4.25, K nitrate 4.00, MgO 0.25 and graphite 0.10%.

Other formulations of NGu propellants are given under Propellants.

Among the advantages of NGu propellants may be cited: low erosion of gun barrels and practically complete absence of smoke and muzzle and breech flash. This was achieved without addition of any flash reducing agents such as K_2SO_4 .

With the introduction of rapid-fire weapons, such as AA guns or those used on armored vehicles, the problem of breech flash became of utmost importance because the breech has to be opened immediately after each firing and less time is given for cooling the chamber gases than in the case of slow-firing weapons. It should be noted that modern rapid-fire weapons are provided with semi-automatic breech closures and muzzle brakes. The brakes tend to retain the gases back in the barrel and when the breech is opened, the gases emerge in a glowing condition, endangering the lives of the personnel and are capable of igniting any combustible or explosive substance in the vicinity. With Gudol propellant this breech flash was practically eliminated. (See also "Flash Reductants in German Propellants").










References:

- 1) U.Gallwitz, *Die Geschützladung (Propelling Charge)*, Heereswaffenamt, Berlin (1944)
- 2) O.W.Stickland et al, *General Summary of Explosive Products*, PB Rept 925 (1945), Appendix 8.

Guhrdynamit. See the Swedish Section.

Guhrhellhoffit. An explosive prepared about 1880 by mixing Kieselguhr with nitrobenzene and fuming nitric acid [Colver (1918) p 143].

Guidance Systems for Missiles. The principal German devices for guiding space-traversing unmanned missiles which carried within themselves the means for controlling their flight paths, are listed below and in some cases briefly described in References 1, 2 & 3. The systems may be subdivided into the following groups:



GUIDED MISSILES

A. **Acoustic Homing Devices.** These utilized the sound produced by airplane engines as a guiding medium. Two such devices were developed and were intended for guiding the X-4 missile. Both systems received the sounds from two separate entrance ports and determined the direction of the target by comparing the phase of the incident sound front. Phase comparison circuits were used to command the missile to maneuver so that the phase angles became equal. This made the missile point directly at the target. The principal advantage of the acoustic homing missile was the impossibility of jamming its receivers (such as is done with radio controlled guidance systems (Ref 3, pp 602-5)).

Note: According to Ref 2, pp 216-19 & 229, the original acoustic homing system was called **Kranich** and the later version **Pudel**. The Pudel acoustic proximity fuze consisted essentially of a mica and 0.03 mm aluminum foil diaphragm connected to a carbon microphone the output of which was fed to a single stage amplifier and relay output. The assembly was mounted at an angle of about 40° to the axis of the body and the sound passed into the diaphragm through a series of wire mesh screens which served to attenuate differences of air pressure due to rotation but not the sound of motors and propellers of enemy aircraft. A small lyre arrangement was attached to the vibrating system in such a way as to broaden the mechanical resonance curves of the individual components of the system. If the missile, such as an X-4, was homing directly on the target, the output of the microphone was constant and as there was no modulation, no steering corrections were necessary. If the missile was not aimed directly at the target, there was generated a modulation frequency of 1 1/2 cycles per second, the rotation speed of the missile. This modulation frequency transmitted the information to the spoiler solenoids in the tail fins, through the gyro commutator system. This arrangement converted the left-right and up-down signals into the proper pulses which were to be fed to the solenoids actuating the spoilers. The range of this device was expected to be about 1000 meters, so that if it were launched at a range of 2000 m, the first 1000 m of its flight would be uncontrolled. The Pudel fuze was not sufficiently developed to be used in combat, but the Kranich fuze was. The Kranich consisted of a light diaphragm actuated mechanism which responded to the sound of airplane propellers at a range of 15 meters. It was constructed on the same principle as the Pudel fuze. It was planned to install the Kranich system on some Rheintochter missiles.

B. **Ballistic Guidance System,** also called **Inertial-Gravitational Guidance System.** This was essentially similar to a long-range gunfire guidance. As with a gun for surface fire, a missile such as a V-2 (A-4), was aimed in the desired direction in azimuth and pointed at such a pre-calculated elevation angle that the projectile would fall to the surface at the correct target range. The V-2 was directed in heading during its burning period by four external and four internal vanes. The external vanes, located in the outer trailing edge of each large fin, created aerodynamic moments, whereas the internal vanes, made of carbon and located to the rear of the motor, varied the direction of thrust of the motor. For control in azimuth, the external and internal vanes were interlocked but they were so connected as to permit separate control in pitch. (Ref 3, pp 36-8 & 583-4)

According to Ref 2, p 211, the V-2 missile was regulated in flight by fins which were positioned by hydraulic servo-mechanisms controlled by an elaborate intelligence system. This system consisted of:

- a) Two gyroscopes to provide stability about the three axes of the missile
- b) Radio (optional) to provide azimuth control by flying on a beam
- c) Radio or integrating accelerometer for turning the motor at a specific velocity, to provide range control
- d) Time switch control to bend the missile over toward the target after it was launched vertically.

After elaborate preparations requiring much time, personnel and equipment, the V-2 was fired vertically from a metallic launcher. A few seconds after the V-2 was in the air, the time switch control caused the missile to bend gradually over in the direction of the target. After 1 minute of flight, the motor was turned off leaving the missile at about a 45° angle and having a velocity of about 3,100 mph. For the remainder of the flight, the V-2 followed

the trajectory of a free body in space reaching a maximum height of about 50 miles before returning to the surface of the earth. About 5 minutes after take-off, the V-2 struck the earth some 200 miles from the launching site with a velocity of approximately 1,800 mph causing the warhead and any remaining fuel to explode.

C. **Infrared (IR) Guidance System** consisted essentially of a concave mirror directed toward a target emitting the infrared radiation. A rotating disc and a photocell connected by a wire to a mechanism regulated the right-left and up-down movements of the missile. A schematic view of such device is given on p 11 of Ref 1 and a general description on detection of the infrared is given in Chapter 5 of Ref 3. One of the IR homing devices was used on the Rheintochter, R-3 (Ref 2, p 229), while another IR device, called **Madrid**, was installed on the Enzian, E-4 missile (Ref 2, p 232).

D. **Magnetic-Ballistic Guidance System,** such as used in the V-1 (FZG-76) missile, called also a "Buzz Bomb", was simple, rugged and reasonably reliable. In this system the azimuth was controlled by a magnetic compass, the altitude by a barometric altimeter and the range by an air mileage measuring unit. Prior to launching the missile, the devices were manually set for the desired course, altitude and range. The compass was linked to the directional gyroscope, whereas the altimeter acted directly on the elevator control system. All of the controls and amplifiers were pneumatic and the high-pressure air was stored in two tanks. When the predetermined range was reached in flight, the warhead was actuated and aimed. The controls were then locked causing the missile to dive. The accuracy of the terminal portion of the flight depended upon the ballistics of the missile. (Ref 3, pp 35-36, 327-8 & 335-7). For more information on guidance systems for V-1 see Ref 2, pp 207-9. Some V-1 bombs were equipped with a one-tube radio transmitter for enabling the launching crew to follow the flights with direction finding equipment in order to obtain plotting and wind data (Ref 2, p 209).

E. **Radar Guidance System or Radio Detection and Guidance System** was not sufficiently developed to be used on a wide scale. Radar tracking of the target was used for guiding the Wasserfall and Rheintochter missiles (Ref 2, p 227 and Ref 3, p 41).

F. **Radio Controlled Guidance Systems** consisted essentially of a radio receiver (located in a missile), a missile tracker and a radio transmitter (located near a missile launcher) for conveying the command to the receiver. This system was used in the majority of German guided missiles including the PC 1400 RX Glider Bomb (Ref 2, pp 195-6), Hs 117, called also Schmetterling (Ref 2, p 196 & 199), Hs 293 A-1 (Ref 2, pp 201 & 203), Hs 298 (Ref 2, p 204), some V-1 missiles (Ref 2, p 207), some V-2 missiles (Ref 2, p 211), Wasserfall C-2 (Ref 2, pp 219-23), Feuerlilie F-55 (Ref 2, p 226), some Rheintochters (Ref 2, p 227), Great Enzian (Ref 2, p 232) and some others.

Note: Hs 293A was the first German radio controlled bomb. It was made in 1940 by Henschel, by equipping with radio control devices, the non-guided glide bomb designed in 1939 by the Gustav Schwartz Propellerwerke (Ref 2 p 202).

The following German radio controlled systems are listed or briefly described in Refs 2 and 3:

- a) Burgund system consisted of an optical (visual) missile tracker, Knüppel, with a joy stick control, a radio receiver Strassburg and a transmitter, Kehl. The Strassburg-Kehl combination was used in the PX-1400 glider bomb, Schmetterling (Hs 117) rocket, Wasserfall (C-2) rocket and Great Enzian rocket (Ref 2, pp 215-16, 223 & 232 and Ref 3, pp 38-43).

Note: As a substitute for the Strassburg-Kehl command link, the Kran-Brigg system was developed late in WW II (Ref 3, p 41).

- b) Elsass system was similar in operation to the Burgund's, except that radar tracking of the target replaced the optical tracking. It was proposed for use with the Rheintochter 3 and some other missiles (Ref 2, p 227 and Ref 3, p 41).

- c) Sonne radial guidance system was based on the method which a navigator of a ship uses to determine its position by plotting the reverse bearings obtained from the radio transmitters of two known locations. The device Sonne was more complicated than the systems used in ship navigation. A brief description of the principles applied in the Sonne is given in Ref 2, p 595.

d) Frosicke & Hoptner radio receiver, first mounted on a V-1 missile proved to be too heavy and complicated for use. It was replaced by the Staru radio receiver (Ref 2, p 199)

e) Stuttgart radio telemetering system was tested on the Feuerlicke F-55 missile (Ref 2, p 226)

f) Straßfurt radio control system designed by the Rundfunk Co was planned to be used in the Enzian missiles (Ref 2, p 232)

g) Kögge radio control system designed by the Telefunken Co was intended for use in Enzian missiles (Ref 2, p 232)

v. Wire Controlled Guidance Systems. Owing to the fact that radio command guidance systems were susceptible to electronic countermeasures (jamming), a control by wires was developed. The system was installed in the X-4 air-to-air missile and was planned to be installed on the X-7 surface-to-air missile and some Henschel missiles (Ref 2, pp 205 & 210-17 and Ref 3, p 41). The wire links system was effective over short distances without fear of enemy countermeasures.

According to Ref 2, p 211, the wire controlled system used in the X-4 missile consisted essentially of a small optical joy stick control target tracker mounted in the aircraft, a pair of control wires and a receiving unit in the missile consisting of a gyroscope and a pair of relays. The control unit in the plane contained two revolving drums, one of them controlling azimuth and the other elevation. The control wires consisted of two insulated single strand Swedish spring-steel wires 6000 m in length and 0.22 mm in diameter. The receiving unit in the missile consisted of a polarized relay for azimuth control and an unpolarized marginal relay for elevation control. The first relay responded only to polarity changes in the direction of current flow through the wires, while the marginal relay responded only to changes in the value of the current regardless of its polarity. In this way, both azimuth and elevation control signals were transmitted simultaneously over the same pair of wires. The relays were connected to the spoiler solenoids in the tail fins, through the gyro commutator system. This arrangement converted the left-right and up-down signals into the proper pulses which were fed to the solenoids actuating the spoilers. The power supply consisted of a small 9-volt dry battery located in the afterbody of the missile.

Note: The mechanical difficulties encountered in earlier models were solved by paying out the wire from the spools on the missile and similar spools on the parent plane simultaneously (such as the Me 262 fighter plane).

According to the description given in Ref 3, pp 41-2, the launching and guiding of the X-4 missile were conducted as follows:

- 1) The missile was aimed and launched from the parent airplane
- 2) Simultaneously with this, sections of wire were ejected by means of black powder charges located in the wire spools, one in the airplane, another in the missile. The length of insulated steel wire in each spool was 18 km and there were two additional reels containing 18 km of wire located on opposite wing tips of the X-4
- 3) Immediately after launching the X-4, the gyroscopic autopilot (located in the missile) was put into operation, the warhead became armed for ready detonation and flares (located on the wing tips of the X-4) were ignited
- 4) As the X-4 proceeded on its flight, the wires continued to pay out from both the airplane and the missile spools and thus the missile was continuously guided by command along the optical line of sight between the pilot and the target
- 5) The X-4 missile rotated about its longitudinal axis 60 rpm and because of this rotation, there was a cancellation of aerodynamic misalignments resulting from production tolerances. This simplified the stabilization problem and a single gyro was sufficient to properly orient the pitch and yaw signals as the missile revolved
- 6) To prevent the inductance of the wire on the spool from distorting the command signals, one centimeter of insulation of each turn of wire was removed in order to create a short for the whole reel

Note: Since the above method of control restricted the maneuverability of launching planes and required that they remain in the vicinity of missiles, thus exposing themselves to the weapons of enemy's bombers, the wire control method was replaced in the latter model of the X-4 by an acoustic homing device called Kranich. With the latter device the parent plane could execute an evasive maneuver the moment the missile was launched and to

withdraw itself beyond the range of enemy bombers weapons. (Ref 2, p 216).

The following varieties of wire command links systems are briefly described in Ref 3, pp 41-2:

a) Dortmund-Duisburg system consisted of an optical joy-stick control unit, a transmitting unit, two spools with wires (as described above) and a receiver located in the fuselage of X-4. The transmitting equipment consisted of an oscillator (operated by pulses from the joy-stick control) and an audio power amplifier which transmitted two audio-frequency signals through wires to the receiving set in the missile. The audio signals were demodulated by the receiver to operate two polarized relays, one for pitch and another for yaw control:

b) Deren-Deimold wire command link was a simple direct-current device which employed no vacuum tubes. The signals were transmitted to the receiver, which consisted of three relays. The 1st relay was sensitive to the polarity of the direct current signals (pitch control), the 2nd relay was sensitive to the amplitude of the signal (yaw control) and the 3rd served to disconnect the other two when the transmitting wires were broken. In this case, the missile continued to follow the course of the last command received. The wires were the same as with the Dortmund-Duisburg system except that insulation was not removed, since it was essential in this system to keep the resistance of wires constant.

Note: In all wire control systems, the fall of wire to the earth proved to be a nuisance and a hazard.


References:

- 1) L.E.Simon, German Research in World War II, J.Wiley, N.Y. (1947)
- 2) Anon, German Explosive Ordnance, Dept of the Army Technical Manual, TM 9-1985-2 (1953), Washington, D.C.
- 3) A.S.Locke, et al, Guidance, Van Nostrand, N.Y. (1955) (Vol 1 of series edited by G.Merrill and entitled: Principles of Guided Missile Design).

Note: According to the A.W.Gatland's book, "Development of the Guided Missile", "Flight" Publication, London (1952), pp 13-16, the current European and American guidance systems may be subdivided into:

A. Beam Rider Control System. With this system a ground radar tracks the target (such as an airplane), while the attacking missile climbs within the cone of a radar beam towards the target. The system is usually considered in conjunction with a self-homing device which monitors the gyropilot of missile so that in the final stage of an attack the missile is self-directing. This system is not as good as the:

B. Command Guidance System. With this system one radar tracks the target, while the other tracks the missile. Each radar feeds data into a computer, whereby steering commands are transmitted to the missile.



Guided Missile (Gesteuerte Geschoss). Beginning about 1938 several successful guided missiles were developed at Peenemünde, Volkenrode, etc. One of the first German guided missiles was the Rheinbote (Rhein Messenger) (Ref 2, p 34).

Other successful guided missiles were:

- a) **Schmetterling** (Butterfly), also known as the Hs-117 (Ref 2, p 35)
 Note: Hs is an abbreviation for Henschel, the name of the builder
- b) **Wasserfall** (Waterfall) (Ref 2, p 37)
- c) **Rheintochter** (Daughter of the Rhein) series such as Rheintochter 1, II and III (Ref 2, p 40)
- d) **Enzian** (Gentian, a species of blue flower) series, ranging from E-1 to E-5 (Ref 2, p 43 Ref 3, p 99)
- e) **Feuerlilie** (Fire Lilly) series, of which the Hecht (pike) was one of the first successful. T-Stoff and Z-Stoff were used in it. The Hecht was succeeded by the Feuerlilie F-25. The last of the series was the F-55, used only for research (Ref 2, pp 45-47, Ref 3, pp 95-6)
- f) **Bachem BP-20 Natter** (Viper) (Ref 2, p 47)
- g) **Ruhrstahl** (Steel of the Ruhr) series ran from X-1 to X-7, of which the X-4 was the most important (Ref 2, p 50 and Ref 3, pp 90-2)
- h) **Hs** (Henschel, the name of builder) series, including the previously mentioned Hs-117 (Schmetterling), as well as Hs-117H, Hs-293, Hs-294, Hs-295, Hs-296 and Hs-298 (Ref 2, pp 52-54 & 56-60, Ref 3, pp 92-3)
- i) **Fritz X** (FX-1400), a glide bomb (Ref 2, p 55)
- j) **Beethoven Apparatus** - an odd looking guided missile (Ref 2, pp 61-62)
- k) **BV-246** (Ref 2, p 63)
- l) **V-2**, is briefly described separately under V-2. It could be launched as a guided missile
- m) **Antipodal Bomber** (Ref 4, pp 57-58)
- n) **Taufun**, a biliquid rocket (Ref 5, p 223).

References:

- 1) Anon, Army Ordnance 31, pp 28-30 & 121-24 (1946)
 - 2) F. Ross, Jr., Guided Missiles, Rockets and Torpedoes, Lothrop, Lee & Shepard Co, Inc, N Y (1951), pp 14-66
 - 3) A. Ducrocq, Les Armes Secrètes Allemandes, Berger-Levrault, Paris (1947) pp 90-99
 - 4) K.W. Gatland, Development of the Guided Missile, "Flight" Publication, London (1952), pp 2-19, 47 & 49-59
 - 5) Anon, Dept of the Army Technical Manual TM 9-1985-2 (1953), pp 195-233
- Note: Additional information on guided missiles, also called **Directed Missiles** may be found in the following CIOS Reports: 28-56, 29-45, 31-13 and 32-66, which were published in 1945 and 1946
 (See also Great Enzian Guided Missile, Rockets and V-2).

Gummidynamit. A rubberlike elastic explosive mass obtained on dissolving collodion cotton in NG. This is called also Sprenggelatine (Blasting gelatin).

Gun (Geschütz). See Kanone and also Weapons.

Guncotton-Dynamit. See Trauzl Dynamit.

H. One of the abbreviations for Hexogen or Hexo (Cyclonite).

H₅, H₁₀ etc. Hexogen phlegmatized with 5%, 10% etc Montan wax.

H-1, H-2, H-5, H-8 Explosives. German Ammonites,

described under Ersatzsprengstoffe.


HA. One of the abbreviations for mixture of RDX (Hexogen) and Al (aluminum).

Hafthohlladung (Adhering or Sticking Hollow Charge). One of the devices consisted of a conical metallic container (filled with 3 lb 5 oz of a HX) to which was attached an elongated apex, serving as a hand grip and containing the exploder pellet (PETN/Wax) and a pull (friction) delay igniter (3/2 or 7 seconds). Attached to the base of the conical section was a plywood frame-work carrying three powerful horseshoe magnets. A brass chain with a hook was attached to the framework. Total weight 3 kp.


The device could be used either as a hand grenade or as a land mine. In the first case the cord of the friction igniter was pulled off and the grenade thrown against the approaching vehicle. In the second case, the device was buried in the ground, close to the surface, with the magnets up and with the igniter cord attached to the ground. At the approach of a vehicle the magnetic attraction caused the grenade to jump towards some iron or steel part and attach itself to it. Simultaneously the cord was pulled, thus setting off the explosive train consisting of delay igniter, exploder and main charge. (Ref 2). It was claimed that this charge could penetrate as much as 110 mm of armor. (Ref 1, pp 323-4).


Another magnetic antitank charge is described in Ref 1, pp 262-3 under the name of Panzerhandmine 3. It consisted of a bottle-shaped cardboard container with 2 1/3 lb of hollow charge (TNT or RDX/TNT). Three pairs of magnets were mounted at the bottom of the bottle, and a 7/2 sec friction igniter was located in the neck of the bottle. Total weight of the device was 8 lb.

The device was apparently designed to be placed by hand on the tank and the igniter pulled after it has been positioned. If the target was of non-magnetic material such as wood, the charge could be attached by means of 3 spikes located at the bottom of the device. (pp 262-3).



HAND GRENADES





In another type of adhering (sticking) antitank hollow charge there were no magnets but a sticky pad (located at the wide part of the conical body) served for attaching the charge to a tank (Ref 1, p 324).

- References:
- 1) Dept of the Army Tech Manual TM 9-1985-2 (1953), pp 262-3 & 323-4
 - 2) H.H. Bullock, Picatinny Arsenal; private communication.

Haftmine (Adhering Mine). An antitank, hollow charge device consisting of a conical container (filled with HE), provided with a flat top and a handle. The wide portion of the cone was covered with a layer of a low melting colophony-oil plastic resin (mp ca 50°) retained on the surface by means of an open mesh cloth. In back of the flat top, which consisted of sheet metal, was placed a thermite-type charge ($Mg + Al + KClO_3$) and in back of the latter a time fuse. The operator hid in a hole and, at the approach of the tank, ignited the fuse which, in turn, ignited the thermite. Just as soon as the heat of the thermite melted the resin, the device was stuck (by the operator) to the bottom armor plate of the tank. At the same time the heat of the thermite set off the detonator and this in turn initiated the main charge.

This device was in an experimental stage when the war terminated.

Reference: E.E. Richardson et al, CIOS Rept 25-18 (1945), pp 23-5.

Haloklastit. Same as Petroklastit.

Haltbarkeit oder Lagerbeständigkeit (Stability in Storage). See in the general section.

Handfeuerwaffen (Small Arms). See under Weapons.

Handhabungssicheresprengstoffe (Explosives Safe to Handle and to Transport). See Davis (1943), p 347.

Harnstoff (Urea). See general section.

HC Mixture. A smoke mixture consisting of hexachloroethane and powdered zinc.

Reference: Anon, Field Artillery Journal 33, 352-3 (1943).

Heavy A/T Mine. See under Landminen and also on pp 265-7 of TM 9-1985-2 (1953).

Höhelzünder (Lever Type or Schuko Igniter). See Pressure Igniter under Igniter.

Hecht Guided Missile. See Pike (Hecht) Missile.

Hellhoff Explosive. According to Ger P 12,127 of 1860, it was prepared by the nitration of purified tar oil, followed by washing, drying and mixing of the nitrotar with oxygen carriers, such as K (or Na) nitrate (or chlorate), etc. It was claimed that this explosive mixture was very powerful.

Reference: See under Hellhoffit.

Hellhoffit (Hellhoffite). One of the Sprengel type explosives, invented about 1870 by Hellhoff and Gruson. It consisted of 28 parts of nitrobenzene and 72 parts of fuming nitric acid. This liquid was sometimes used absorbed on kieselguhr (see Guhrhellhoffit). The disadvantage of these Sprengel type explosives was their extreme corrosiveness (Ref 1).


According to Thorpe (Ref 2), Hellhoffit was tried in shells, the two ingredients being mixed during flight exploded on impact (see also Anilite under Fremd explosives).

Stettbacher (Refs 3 and 4) investigated Hellhoffit and its modifications and found that the glass-lined depth charges (Tiefenbomben) containing Hellhoffit, were much more effective than those loaded with picric acid. The mixture consisting of fuming nitric acid (d 1.52) 64.51, nitrobenzene 25.81 carbon disulfide 6.45 and aluminum bronze 3.23% was found to be one of the most effective. A mixture prepd by dissolving 66.7 parts of dinitrobenzene in 100 parts of fuming nitric acid was also claimed to be effective.

References:

- 1) Davis (1943), p 354
- 2) Thorpe's Dictionary, v 4 (1940), p 545
- 3) A. Stettbacher, SS 3B, 158 (1943)
- 4) A. Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), p 71.

HAFTMINE



Hengst Smokeless propellant, patented in 1888; was based on nitrated pulped straw previously treated with some chemicals as described in Daniel, *Dictionary* (1932), p 373.

Hörschell or **Hs.** A guided missile (q v) developed during WW II.

Heroklin of Dickerhoff. An explosive prep'd by soaking sawdust in a concentrated aqueous solution of equal parts of picric acid and Am nitrate. The resulting product was dried and mixed with various amounts of pulverized sulfur and K, or Na nitrates. Reference: L.Gody, *Traité des Matières Explosives*, Namur (1907), p 551.

Hetzer (Baiter). A Czech designed and constructed Tank Destroyer, Jagdpanzer 38 (t) (See under Panzer).

Heuschrecke (Grasshopper). A series of weapon carriers (Waffenträger) such as for 105 mm Gun, developed by the Germans early in the WW II. They are described in vol III of the Illustrated Record of German Army Equipment 1939-1945, War Office, London (1947).

Note: The above British books were not consulted for fear that they are "confidential" or "secret" as is usual with British sources.

Hexo, Hexamin, Hexanitrodiphenylamin, oder Hexyl (Hexanitrodiphenylamine) (HNDPhA). Described in the general section under Diphenylamine. The following information concerning the manufacture and use of Hexa in Germany during WW II is available:

At Allendorf Fabrik of W A S A -C. the method of manufacture was as follows:

To a charge of 1000 kg of 99% nitric acid placed in a V2A stainless steel nitrator of 2 cubic meter capacity, fitted with an agitator rotating at 60 RPM, a cooling jacket and cooking coils) 300 kg of diphenylamine was added gradually while the temperature was maintained at 95°. The solution was diluted with weak nitric acid and cooled to 30-40°. The precipitated HNDPhA was filtered off, washed thoroughly with water, then dried, screened and packed.

HNDPhA was used by the Germans at the start of WW I in an underwater explosive containing HNDPhA 40 and TNT 60%. During WW II, this explosive was replaced by the one containing HNDPhA 27.9, TNT 55.7 and Al 16.4%. Another underwater explosive contained HNDPhA 23.9, TNT 61.8 and Al 15.2%. Stettbacher (Ref 5) cites a mixture consisting of HNDPhA with 30-40% TNT and 16% Al (See also Hexamite, Schießswolle 18, TSMV-1-101 and Ersatzsprengstoffe). References:

- 1) A.Stettbacher, *Protar* (Switzerland) 9, 33-45 (1943)
- 2) US Naval Tech Mission in Europe, Tech Rept 513-45. Hexanitrodiphenylamine Manufacture in Germany, PB Rept 38, 154 (1945)
- 3) O.W.Stickland et al, PB Rept 1820 (1945), pp 13-17
- 4) Anon, *Allied and Enemy Explosives*, Aberdeen Proving Ground, Md (1946)
- 5) A.Stettbacher, *Spreng- und Schießstoffe*, Zürich (1948), pp 78-29.

Hexo S-22, S-26 and E-4. German substitute explosives containing hexanitrodiphenylamine described under Ersatzsprengstoffe.

Hexadi German name for **Hexamethylenetetramine Dinitrate**, $(C_6H_{12}N_4 \cdot 2H_2O)$. (See KA-Verfahren under Hexogen).

Hexal. An explosive mixture consisting of 75% Hexogen (desensitized with 5% of wax) and 25% A powder; was used in underwater ammunition. [PB Rept 1820, p 40].

Hexamethylenetetramin (Hexamethylenetetramine) (HMeTeA), called also Hexamin, Methenamine, Amiaform or Brotropine. See general section.

Hexamethylenetetramine Derivatives (Explosives). To this group belong explosives containing Hexogen (RDX or Cyclonite) and K-Salz (Cyclotrimethylenetrinitrosamine) described elsewhere. In addition, G.Römer et al investigated two explosives (see Aliphatic Nitramines of WW II) obtained as by-products in the manufacture of Hexogen by the E-Salz and KA-Salz processes.

Both of these substances were claimed to be more powerful explosives than Hexogen.

Reference: G.Römer, PBL Rept 85,160 (1946), p 16.

Hexamethylenetriperoxyddiamin (HMTPPDA) (Hexamethylenetriperoxyddiamin). Preparation and properties are given in the general section. The explosive was proposed in 1912 for use as initiating component for detonators. For instance, the No 8 copper cap might contain 0.1 g of HMTPPDA and 1 g of TNT. Reference: C. von Girsowald, Ger Pat 274,522 (applied for in 1912, issued in 1914).

Hexamin. One of the German designations for Hexanitrodiphenylamine. The same designation was used for Hexamethylenetetramine.

Hexamit, or Hexonit. An explosive used during WW I for cast loading torpedoes, sea mines, and depth charges. It consisted of hexanitrodiphenylamine (HNDPhA) 60-70 and TNT 40-30%. Its properties are described in the general section.

After termination of WW I, the Hexamit was used as a component of a commercial explosive known as "Neurodit".

The term Hexamit was also used for the following commercial explosive prep'd from surplus materials of WW I: 60 to 90 parts of HNDPhA, in which might be present up to 40% picric acid, 10 to 40% DNT, TNT, and/or TNN, and 0 to 4% vegetable meal.

Reference: J.Pepin Lehalleur, *Poudres*, etc, Paris (1935), pp 157-8.

Note: According to TM 9-1985-2 (1953), p 15, the Hexamit was used in the warhead of Kurt Apparat (q v).

Hexonit. Same as Hexamit.

Hexanitrodiethylnitramine. See general section under Diethylnitramine.

Hexanitrodiphenylamine. Same as Hexa.

Hexo. One of the abbreviations for Hexogen (H) (Cyclonite or RDX).


Hexo (S-19 and S-22). German substitute explosive containing Hexogen (RDX); described under "Ersatzsprengstoffe".

Hexogen or H(RDX), also called W-Salz, E-Salz, K-Salz, SH-Salz and KA-Salz, depending on the method of manufacture. It is described in the general section as Cyclonite (Cyclotrimethylene Trinitramine).


Although Hexogen was known in Germany since 1899 (Henning, Ger Pat 104 260, 1899), it was not used as an explosive until about 1935 when its manufacture was started using the **W-Verfahren** described below. Four other methods of manufacture were later introduced and production reached its peak with 7,000,000 lb produced during the month of June 1945. Out of the five methods developed in Germany and described briefly below, the so-called **KA-Verfahren** proved to be the best because it was the most economical, required less space and equipment and used readily available raw materials.

Following are the German V.W.H. methods of manufacture, arranged in approximate chronological order:


1. **W-Verfahren** (W-Process), developed in 1935 by Dr Wolfram of the IG Farbenindustrie, was based on the reactions indicated by the following equations, starting from sulfur trioxide and ammonia:




The resulting mixture of Am aminosulfonate and Am iminosulfonate was treated with a soln of Ca hydroxide, which gave a soluble Ca aminosulfonate and a ppt of Ca sulfate




The liberated ammonia was recovered and used in reaction a). The Ca sulfate was removed by filtration and the Ca aminosulfonate treated with K sulfate.



The resulting K aminosulfonate was separated by filtration and treated with formaldehyde at 30° at a pH of 5.




The resulting condensation product, K methyleneaminosulfonate, called **Weiss-Salz** (white salt), was nitrated with mixed nitric sulfuric acid at 30° in a stainless steel nitration of 500 l capacity



This procedure (which under certain conditions gave yields up to 80% based on the formaldehyde used) was followed at the Krümmel Fabrik of Dynamit A-G until an explosion in 1943 completely destroyed the plant. Other German plants did not use the W-Verfahren because other methods such as the SH, E, and K proved to be more economical.

Note: A similar method was patented later by R.W. Schiessler and J.H. Ross, U.S. Pat 2,434,230 (1948).


2. **E-Verfahren** (E-Process), developed between 1935 and 1938 by Drs Eberle and Fischer, was based on the reaction of paraformaldehyde with Am nitrate, dissolved in acetic anhydride, which acted as a dehydrating agent:



The resulting Cyclonite was separated by means of a nutsch, from the acetic acid produced by the reaction, washed with water, stabilized and dried. The finished crystalline product had a mp of only 190-195° and the yields varied between 60 and 75%, calculated on paraformaldehyde.

The E-Verfahren was used at the Bobingen Fabrik, Dynamit A-G and produced 125 metric tons per month. It was replaced in 1944 by the KA-Verfahren which enabled the production to be doubled with the same equipment. Note: The Cyclonite obtained by this method contained the same impurities as described under KA-Verfahren but in larger amounts.

3. **SH-Verfahren** (SH-Process), developed in 1937-1938 by Dr Schnurr was based on the original method of Henning (1899), which involved direct nitration of hexamethylenetetramine (called also hexamine or urotropine) with nearly absolute nitric acid, according to the following equation:



A similar method was independently developed by Dr G. Cillate at Picatinny Arsenal.

The improvement introduced by Dr Schnurr consisted in carefully controlled heating ("cooking-off") of the contents of the nitator directly after the completion of the reaction.


Under these conditions the unstable products formed during the reaction were partly decomposed and partly nitrated to cyclonite.

The nitration in the SH-process was conducted at -5° using white 99% nitric acid. The purified Cyclonite had a mp between 200° and 202°C.

While in the original (Henning's) method the yield was very low (about 40% based on $C_6H_{12}N_4$ used), the improved method was much more economical (yields up to 71.5% were reported).



The SH-process was used in at least three plants: all of them belonging to the Dynamit A-G: Christianstadt (producing up to 3000 metric tons per month), Döberitz (producing up to 500 t/mo) and Uckermünde (producing up to 250 t/mo). The SH-process was considered to be more economical than the W-, E- or K- processes, but inferior to the KA-process.

4. **K-Verfahren** (K-Process), developed by Dr Knöffler of W.A.S.A.-G., somewhat later than the E-Verfahren, was based on the following consideration: As the hexamethylenetetramine contains 6 CH_2 groups and only 4 NH_2 groups, there is a deficiency of two NH_2 groups which are required for the production of each two molecules of Cyclonite, this can be remedied by introducing into reaction two mols of Am nitrate as shown in the following equation:



Nitric acid of 99% strength was used and was required in larger quantity than for the other methods. This made the recovery of spent acid a very difficult and expensive problem. Only one German plant used this method (Elsnig Fabrik of W.A.S.A.-G.), producing 200 metric tons per month.

5. **KA-Verfahren** (KA-Process), developed by Dr Knöffler of W.A.S.A.-G. was actually a combination of parts of the K- and E- processes. It consisted in treating the hexamethylenetetramine dinitrate with acid Am nitrate in acetic anhydride, as can be seen from the following equations:



In this method, considered to be one of the most economical, paraformaldehyde was not used, because all the necessary CH_2 groups were supplied by hexamethylenetetramine. A similar procedure was developed in the U.S.A. by W.E. Bachmann (See general section under Cyclonite).

In the KA-process, as practiced at the Bobingen Fabrik, hexamine was treated with weak nitric acid (35-50%) at about 5° and the resulting dinitrate (called in Germany **Hexodi**), was dried. The dry product was dissolved in acetic anhydride using a stainless steel vessel equipped with a paddle-type stirrer) and then acid Am nitrate (previously prep'd by treating Am nitrate with 1 mol of 100% nitric acid) was added. The resulting solid product was separated from acetic acid, then washed with water and dried. The cyclonite obtained by this method was called **KA-Salz**. It contained, as impurities, 1 to 2% of HMN (cyclotetramethylenetetramine, called in Germany **Octogen**), $(H_2C \cdot N \cdot NO_2)_4$, and a small amount of cyclotrimethylene dinitromonoacetylamine, $(CH_2)_3N_3(NO_2)_2 \cdot OCH_3$. Higher percentages of these impurities were produced when the E-Verfahren was used. Note: The advantage of the KA-process over the E-process was that by using hexamine instead of paraformaldehyde only half of the amount of water was produced, thus requiring a much smaller amount of acetic anhydride. Hence, it was possible, without increasing the size or amount of equipment, to increase the production of the Bobingen Fabrik, Dynamit A-G from 125 to 250 metric tons per month when the method was changed in 1944 from the E- to the KA-process.

Yields, when calculated on the basis of formaldehyde (from which the hexamine was produced), were 80-82% for the KA-process, as against 73-75% in the E-process. In the KA-process the production of 100 parts of Cyclonite required 40p of hexamine, 43p of Am nitrate, 68p of nitric acid and 240p of acetic anhydride (of which 195p were recovered as acetic acid).

A recent article of Mayer (Ref 7) described some German methods of preparation of RDX and lists its properties as follows: mp 201-3, d 1.82, explosion

temperature 230°, impact sensitivity with 2 kg weight 13-15 cm, velocity of detonation 8400 m/sec.

Straight Hexogen was used by the Germans as a booster, sub-booster and as a bursting charge in rifle grenades and some small caliber shells. It was also used with a small amount of wax, e.g., 3%, as a sub-booster in the African campaign to replace PETN-wax mixtures. With a larger amount of wax, e.g., 10.3%, it was used in 75 mm shells. Hexogen was also used with other proportions of wax as well as with TNT, Al etc. See Fillers Nos 86, 89, 90, 91-115, 92-110, 4, 92-113, 95-II/Fp 02, 105 (or Trialen 105), 106 (or Trialen 106) and 109 (or Trialen 109), described under Fillers.

References:

- 1) PB Rept 925 (1945)
- 2) PB Rept 16,669 (1945)
- 3) Allied and Enemy Explosives, Aberdeen Proving Ground (1946)
- 4) A. Stettbacher, Spreng- und Schießstoffe, Zürich (1948), pp 68-69
- 5) J. Mayer, Explosivstoffe, 1954, No 7/8, pp 83-5 (Über Hexogen, seine Fabrikationsmethoden und Eigenschaften).

Hexonit One of the explosives invented by Stettbacher. See under Swiss Explosives.

Hexoplast 75. Plastic explosive, developed during WW II at the Krümmel Factory of Dynamit A-G. It contained RDX 75, NC 1.2 to 1.4, liquid DNT 20.0 and TNT 3.8 to 3.6%. This mixture was prep'd by heating the required amount of RDX to 90° in a Werner-Pfleiderer mixer, and blending it with a small amount of NC. This was followed by the addition of a DNT-TNT mixture and further blending. By using this order of addition, lumping was avoided.

The mixture was put out in cylinders about 220 mm long by 28 mm in diameter. Due to difficulty with direct cap initiation, a booster was provided. It consisted of compressed, phlegmatized PETN pellets about 40 mm long by 21 mm diam and equipped with a detonator well 20 mm deep.

Note: This explosive was developed as a substitute for the plastic explosive, which used RDX plus American vaseline, because the latter component was no longer available in Germany. This vaseline, called "long fibrous" by Meyer, had much greater adherence than vaselines manufactured in other countries.


Reference: O.W. Stickland, General Summary of Explosive Plants, PB Rept No 925 (1945) Appendix 7 (R. Meyer, Development Work on Explosives at Krümmel).

Hexyl. Same as Hexa.

High Pressure Pump. See Hochdruckpumpe.

High Speed Tunnels for testing various weapons are described in CIOS Rept 28-47 (1945) and in L.E. Simon, German Research in WW II, J. Wiley, N.Y. (1947).

Hochdruckpumpe oder V-3 (High Pressure Pump, called also "Busy Lizzie" or "Multipede") was a constant-pressure gun developed during WW II by Conders, an engineer of the firm Röchling, Saarbrücken, and intended to fire the Arrow (Needle) Projectile (qv) across the Channel to London. The barrel, caliber 150 mm (5.9"), was of unalloyed crucible cast steel made up of a great many Y-shaped sections, each 12 to 16 ft long. With the gun about 450 ft long containing about 28 propellant chambers (distributed along the bore), it was expected to achieve a muzzle velocity of about 4500 ft/sec and a range of about 130 km (when using a projectile 8 ft long and weighing 150 lb).



**HDP SUPERGUN
(VERGELTUNGSWAFFE 3)
(V-3)**

The gun could lie on the ground without any carriage on wooden and concrete blocks sloped at a 45° angle. The fin-stabilized, arrow projectile was inserted in the barrel and the base propellant charge electrically ignited. As the projectile passed the separate Y-pieces, additional propellant charges in the side arms were electrically ignited one after another (in pairs) thus accelerating the velocity of the projectile as it progressed along the gun barrel.

For servicing (reloading the Y-sections with propellant charges between the rounds), the gun required a great many soldiers. It was planned to fire one round per gun every 5 minutes but this rate could not always be achieved because the sections often exploded and it was necessary to insert new Y-pieces.

References:

- 1) L.E. Simon, German Research in World War II, J. Wiley, N.Y. (1947), pp 191-3
- 2) W. Dornberger, "V-2", Viking, N.Y. (1954), p 247
- 3) A.I. Sprinz and H.H. Bullock of Picatinny Arsenal; private communication.

Hochoxplivkörper oder Blitzstoffe (High Explosives) (HE). See general section.

Hoch- und Niederdruckkanone (High and Low Pressure Gun, abbreviated to H/L Gun) (Canon à tuyère, in French). It has been known for a long time that the lower the peak pressure in a gun the thinner may be the walls of the projectile. This means that for a given total weight of a projectile, that used in a gun with lower peak pressure can contain more explosive and do more damage to a target.

This is of particular importance in the use of shaped charges because the penetration of targets does not depend upon the strength of the case (shell) but on the amount of the explosive charge. In order to achieve low pressure in a gun of conventional design, the barrel should be made longer and the chamber and cartridge case larger. Such guns were built but were found to be unsuitable because the propellant was difficult to ignite and it burned irregularly (due to the low pressure in the chamber). Also, the initial velocity of the projectile varied from round to round which means that no precision firing could be achieved.

Better results were obtained in 1943 when Dr Hermann and collaborators of the Rheinmetall-Borsig A-G constructed the 8 cm PWK 43 (80 mm Antitank gun). The description of this gun called in French "canon antichar modèle 1943", was given by Travers and Touchard (Ref 3). They claim that the "turbocanon Delamare-Maze" invented in France about 20 years earlier may be considered as the predecessor of both the H/L and recoilless guns.

The German gun 8 cm PWK 43 had a comparatively thin barrel with an inside diameter of 81 mm and was 34 calibers long; the chamber had an enlarged diameter (105 mm) and much thicker walls. The projectile (fintail type, 81 mm in diameter, contained a shaped charge and weighed 3kg) was inserted first in the bore (in separate-loading ammunition). This was followed by the cartridge (120 mm long and 108 mm in diameter) which contained the propellant. The cartridge was closed by means of a disc provided with eight perforations (each 14 mm in diameter). When the propellant burned the pressure of the gases developed inside the cartridge was about 850 kg/cm² but the pressure acting on the projectile was only 550 kg/cm² because the gases lost part of their velocity on passing through the holes in the disc.

The relation between the high pressure inside the cartridge case and the lower pressure in the bore could be varied by increasing or decreasing the size or number of the openings in the separating disc. In order to protect the propellant in the container from spilling and from moisture, the perforated metallic disc was covered with a solid disc of paraffined cardboard.

The ballistics for the H/L gun were worked out by Travers and Touchard in France and by Corner in England. Note: Corner states that towards the end of WW II the Germans started to manufacture two light antitank guns: the 8 cm PAW 600 and the 10.5 cm PAW 1000, but does not describe them. He also mentions the 8.8 cm W71 gun, which was built on the "three-pressure principle".

References:

- 1) J. Corner, J Franklin Inst 246, 233 (1948)
- 2) J. Corner, Theory of the Internal Ballistics of Guns, J. Wiley, N Y (1950), pp 312-327
- 3) S. Travers & L. Touchard, Mém Artil Fr 26, 835-58 (1952)
- 4) Ibid, 27, 219-36 & 245-78 (1953).

Hohlladung (Shaped or Hollow Charge). Considerable work was done in Germany before and during WW II on the development of shaped charges. Among the most prominent contributors in this field were the personnel of Krümmel Fabrik, D A-G. Among the shaped charge weapons developed at Krümmel may be mentioned:

- a) Magnetic anti-tank shaped charge weighing 3 kg; blast penetration of armor was up to 250 mm
- b) Shaped charges for Faustpatrone, Panzerfaust, Panzerschreck, etc.

Note: At Krümmel it was found that the best explosives for

shaped charges were RDX-TNB and next, RDX-TNT mixtures. Substituting PETN for RDX lead to a decrease in efficiency. The addition of aluminum powder was desirable but not in large quantity.

Krümmel was not the only place where work on shaped charges was conducted. Elsewhere the Germans developed a shaped charge shell which was shot from an 80 mm mortar called "Panzerwurfkanone", and the warheads for several guided missiles.

Historical. Discovery of the hollow (shaped) charge (HoC) effect is usually attributed to C.E. Munroe (U.S.A.) who described the effect in the Amer J Sci 36, 1888. It was claimed by H. Schardin that Max von Forster of Germany had in 1883 already shown that bare hollow charges gave an enhanced effect along the axis of the charge. The first practical application of the HoC effect for demolition charges, sea mines, torpedoes, projectiles etc. was patented in 1910 by E. Neumann & the Westfälisch-Anhaltische Sprengstoff A-G (DRP Anm 436269). Neumann's work is described in S S 6, 356 (1911) and S S 9, 183 (1914). Important work on military applications of the HoC effect was done, prior and during WW II, by H. Schardin et al in Berlin. Some work was also carried out by A. Stettbacher of Switzerland during this period.

Note: According to A. J. Dere, Ordnance Sergeant, October 1945, pp 3-13, hollow (shaped) charge ammunition was used by the Germans in many 75 mm caliber weapons. There were at least four types of such projectiles III, III/A, III/B and III/C. Most of these projectiles are listed in this dictionary under Granite and are briefly described to PM 9-1985-1 (1953). Some projectiles of calibers 80 mm, 100 mm, 195 mm and 240 mm also had shaped charges. The enclosed drawings represent some typical German hollow charges. (See next page).

References:

- 1) A. Stettbacher, Nitrocellulose 8, 83-84 (1937)
- 2) O.W. Stickland et al, PB Rept 925, Appendix 3, p 46 and Appendix 7
- 3) L.E. Simon, German Research in WWII, Wiley, N Y (1947), pp 118-120, 188
- 4) A. Stettbacher, Spreng- und Schiesstoffe, Rascher, Zürich (1948), pp 133-34
- 5) H.L. Porter et al, CIOS Report 33-27 (1945). This report is classified and information contained therein has not been used for this dictionary.


(See also Shaped Charge in the General Section)

"Hoko" (Hochkonzentriert = Highly-concentrated) Process for the manufacture of 98-99% nitric acid, developed during WW II, was used in several German plants. In this process, the concentration of the weak acid (50%) was effected by mixing it with liquid nitrogen tetroxide (N₂O₄) and adding the necessary extra oxygen under 50 atm pressure in an autoclave.


Description of this method as practiced by the IG Farbenind A-G subsidiary, the Wirtschaftliche Forschungsgesellschaft mbH (WIFO), Embesen, Kr Lüneburg is given in the following BIOS Final Reports: 1232 (1947), pp 15-16 and 1442 (1947), pp 84-98.

Hollow Charge. See Hohlladung.

Hollow Charge Nose Attachment for AP Bombs. In order to



HOLLOW (SHAPED) CHARGES



permit greater penetrating power from low altitudes some German 250 kg AP bombs had a hollow charge (weighing about 1 kg) attached to the nose. This charge was detonated by its own nose fuze as soon as it hit the armor. The explosion of the Hnf produced a hole in the armor (as deep as 7 cm) which permitted the AP bomb to enter inside the target. The AP bomb being provided with a short delay fuze did not explode until it was inside the target. In order to protect the bomb from premature detonation the space between the Hnf and the nose of the bomb was filled with sawdust and cement.
Reference: TM 9-1985-2 (1953), p 5.

Holzgeist (Wood Spirits) See Methanol in general section.

Holzmehl (Wood Meal) See Wood Flour in the general section.

Holzmine 42 See under Landminen and also on p 203 of TM 9-1985-2 (1953).

Holzpech (Wood Pitch) See general section.

Holzstoffmasse (Wood Pulp) See general section.

Holzteer (Wood Tar) See general section under Tar.

Holzzellstoff (Wood Cellulose or Chemical Wood Pulp) See general section.

Homing Guidance Systems for Missiles, such as Acoustic, Radar and Infrared are briefly described under Guidance Systems for Missiles.

Howitzer (Haubitze). See under Weapons.

Hs 117 (Henschel 117), also known as **Schmetterling** (Butterfly), was a rocket propelled, radio controlled, missile for use against bomber formations. Some versions were for ground-to-air and some for air-to-air. It used liquid fuel called Tonka and an oxygen carrier called Salbei.
TM 9-1985-2 (1953), pp 196-201.

Hs 293 (Henschel 293) was a radio controlled missile released and directed to the target from an aircraft. The model fully developed and used was the **Hs 293 A-1**. Other models such as Hs 293 A-2, Hs 293 B, Hs 293 C, Hs 293 D, etc were not fully developed. TM 9-1985-2 (1953), pp 201-3.

Hs 298 (Henschel 298) was a rocket-propelled, radio-controlled missile designed primarily as an air-to-air weapon to be carried on fighter aircraft as well as the bomber types. There were several versions but the basic type was called **Hs 298 V-2**. It used a solid propellant.
TM 9-1985-2 (1953), pp 203-5.

HTA. An abbreviation for mixtures of RDX (Hexogen), TNT (Trotyl) and Al (aluminum), such as in "the proportions 40/40/20." See also PBI. Rept No 85,160 (1946), p 15.

Hübner Propellants, patented in 1895, were prep'd by mixing NC (gelatinized by means of 2-3% soln of K xanthogenate in ether-alcohol) with small quantities of nitronaphthol, nitromolasses, or nitrosugar. For instance, a propellant used for military purposes contained 4 to 5% of nitronaphthol. [Daniel, Dictionnaire, Paris (1902) p 378].

Hummel (Bumble Bee). Nickname for a self-propelled mount consisting of 150 mm Medium Howitzer on the chassis of a PzKpfw III/IV tank. (See also under Panzer).

Hydrazine Hydrate is described in the general section. Its manufacture in Germany at the IG Farbenindustrie Plants at Gersthofen, Leverkusen, Ludwigshafen and Oppau is described in BIOS Final Reports 815 and 1682 (1946).

Hydrocellulose oder Hydrozellulose (Hydrocellulose).

Described in the general section. It was reported that the Germans used it in some rocket propellants, presumably to improve the burning characteristics. For instance the so-called Ammonpulver contained 5% hydrocellulose and the EP (Einheitspulver) contained about 3%. Hydrocellulose was also used in some rocket propellants to increase the rate of burning at low temperature. (See Standard Propellant).
Reference: CIOS Report 31-68 (1945), pp 6-7.

Hydrogen Peroxide (Wasserstoffsuperoxyd). Its preparation and properties are described in the general section under Peroxides. It was used in liquid rocket propellants and in a special turbine designed for submarines by Walter. Several German methods of manufacture are described in the following References:

- 1) B.E.A. Vigers et al, Hydrogen Peroxide Production by Electrolysis of 35 Per Cent Solutions (Deutsche Gold and Silver Anstalt), BIOS Final Report 683 (1945)
- 2) V.W. Slater et al, The Anthraquinone Autoxidation Process for the Production of Hydrogen Peroxide, CIOS Report 31-15 (1945)
- 3) J. McAulay, Hydrogen Peroxide Manufactured by All-Liquid Process From Ammonium Persulfate, $(\text{NH}_4)_2\text{S}_2\text{O}_8$, CIOS Rept 33-43 (1945)
- 4) J. McAulay, Direct Synthesis of Hydrogen Peroxide by Electric Discharge, CIOS Rept 33-44 (1945).

See also T-Stoff, Rocket Propellants, Liquid and U-Boat (Unterseeboot) of Walter.

Hygroskopizität oder Feuchtigkeit (Hygroscopicity, Humidity or Moisture). Methods of determination are given in the general section.

Igniter (Zünder). The following igniters are briefly described or listed in Refs 1, 2 & 3












A. Friction (Full) Type (Brennzünder).

- a) BZ 24, with delay pellets, was used in stick grenades (Ref 1, p 83.13 & 3, p 283)
- b) NbbZ 38, with delay pellets was used in smoke grenades (1, p 83.13 & 3 p 283)
- c) BZE, with pellet, was used with egg grenades, shaving stick grenades and message box flares (1, p 83.12 & 3, p 284)
- d) BZ 39, used in smoke hand grenades (3, p 285)
- e) Zdschn ANZ 29, used to ignite safety fuses or detonators, to set booby traps, to ignite safety fuses for some demolition charges, to ignite some smoke candles and to booby-trap some Teller mines and grenades. (1, p 83.10 & 3, p 285)
- f) Zdschn ANZ 39, used for the same purposes as above (1, p 83.11 & 3, p 285)
- g) BZ 42, delay 4 1/2 sec; uses not indicated (1, p 165)


B. Pressure Type (Druckzünder).

- a) DZ 35(A), used in heavy antitank mines and some prepared charges (1, p 83.03 & 3, p 295)
- b) DZ 35(B), used in some booby traps and prepared mines (1, p 83.03 & 3, p 296)
- c) **Hebelzünder** (Lever Igniter), also called **Schuko Igniter**, consisted of an inverted L-shaped tube, the vertical arm of which was screwed into a mine. The horizontal arm contained the percussion cap, striker, striker spring and striker retaining pin. On top of the arm was attached a lug, an actuating lever (consisting of a hollow metal tripping piece pivoted on a rivet), and a safety pin. After removing the pin, the downward pressure (as little as 40 lb) on the actuating lever forced out the striker retaining pin, thus releasing the striker to fire the percussion cap. The igniter was used in Glasmine 43 (as an alternative to the Buck Igniter) and in some booby traps (1, p 83.14 & 3, p 296)
- d) PX 32, used in some improvised mines (1, p 83.03 & 3, p 297)
- f) **Weissmann Igniter** consisted of a spring loaded striker bolt at the top of which was a pressure head. The bolt was held against the spring by a safety device consisting of a small pair of tongs. After removing the tongs, pressure or a blow on the pressure head chattered the glass rod thus allowing the spring to drive the


IGNITERS





IGNITERS




*Pressure Igniter
7MiZ-35*




*Pressure Igniter
7MiZ-42*




*Pressure Igniter
FLEMiZ*




*Pressure Igniter
7MiZ-43*




*Pressure Igniter
MiZ 530(c)*



*Pressure Igniter
10b1*



*Pull Igniter
22-35*



*Pull Igniter
22-31*

striker against the percussion cap etc. The igniter was designed for use as a push igniter in improvised mines, or as an impact igniter for HE charges when used in an assault (3, p 298)

c) SMIZ 35 designed for use in Schützeminne, also called Bounding Mine (3, p 299)

d) FMZ 35 (Tellerminenzünder 35), used in T-Mi 35 (3, p 301)

e) FMZ 35, used TMI 35 (steel), TMI 42 and TMI 43, also called Pilzmine (Mushroom Mine) (3, p 303)

f) TMI 43, used as above (3, p 304)

g) HESMIZ used in Flaschenmine 42 (Antipersonnel glass bottle mine) (3, p 307)

D MiZ 530(c), an igniter manu'd in Germany for use in the British Antitank Mine 530 (3, p 367)

h) Topfminenzünder (Pot Mine Fuse) consisted of a hollow, cylindrical, glass body into which fitted a solid pressure head. Inside the cylinder were located two glass ampoules containing liquids which on mixing ignited the explosive train of the Pot Mine (Topfmine). A pressure of about 150 kg was sufficient to crush the ampoules (3, p 306)

C. Pull Type (Zugzünder).

a) ZZ 35, used in S-Mines, some prepared charges, booby traps employing trip wires) and for booby trapping of Teller mines (1, p 83.04 & 3, p 288)

b) Type 31 designed for use in antipersonnel mines and booby traps (3, p 289)

D. Pull and Shear Type (Zug- und Zerschneidezünder), also called Pull and Tension Wire Igniter, such as ZuZZ 35, consisted of a brass case containing a percussion cap, striker, striker spring (located inside a sliding cylinder and held on top by a plunger), an outer compression spring, a retaining (locking) pin and a safety pin. The top of plunger was connected to a trip wire held under tension. The igniter was fired either by pulling on the trip wire or by loosening (cutting or breaking) it. In the first case the trip wire caused the plunger to be pulled upward against the resistance of the outer spring. This permitted the two locking pins to be forced outward into the upper open space thus freeing the striker. In the second case, breaking or cutting of the trip wire allowed the outer (compression) spring to force the sliding cylinder downwards. This permitted the locking pins to be forced outwards into the lower open space, thus freeing the striker. This igniter was used with S-mines, booby traps and prepared charges. (1, p 83.05 & 3, p 293)

E. Percussion Type (Schlagzünder oder Aufschlagzünder).

a) Schlagzünder 35 was a modified version of ZuZZ 35; uses not indicated (2, p 163)

b) Safety Fuse Igniter consisted of a cylindrical brass body containing a spring-loaded striker held in position by a friction fit of the Z type with a cap to which was attached a large steel ring. A strong pull on the ring detached the striker release plate from the striker thus permitting the spring to drive the striker into the percussion cap. The device was used to ignite a safety fuse (3, p 287)

c) Type 2 (Pull Percussion) Igniter was designed for use with the new type parachute antipersonnel bomb but was suitable for use with mines and booby traps. For operation, a sharp pull on the split ring caused the striker release plate to be drawn from the igniter body thus releasing the striker spring, which was under tension (3, p 288)

d) Aufschlagzünder 355(h) for use in Dutch Antitank Mine 355 (2, p 164)

F. Pull and Pressure Type (Zug- und Druckzünder).

a) Z10Z 29 Igniter, used in the assembly of antitank, nontvehicle or antipersonnel mines, could be operated either by pull on a trip wire attached to the loop of the pull pin, or by pressure against the setting head (3, p 292)

b) ZZ 42, consisted of a bakelite cylindrical casing containing a percussion cap, a striker retaining washer and a striker spring held under tension by the trip wire loop. Pulling on the trip wire attached to the release pin withdrew the pin thus allowing the striker to hit the percussion cap. The igniter could also be operated by attaching a trip wire under strong tension to the end hole in the striker and carefully removing the release pin. This igniter was designed for use in

Stock mines and booby traps (1, p 83.06 & 3, p 293). Note: This igniter is listed in Ref 1 as "Pull" Type, whereas Ref 3 lists it as a "Pressure and Pull" Type

c) SMIZ 44, developed for use in S-Mine 44 and in some improvised mines, consisted of a steel cylindrical case containing a percussion cap, striker and spring. The striker was retained in a cocked position by two winged detents, to which two trip wires were attached. The detents were held in position by a retaining collar (mounted on the case) and by a safety pin. After arming the device (by withdrawing the safety pin), a pressure of 21 lb or a pull of 14 lb on the winged detents opened them sufficiently to release the striker (3, p 294)

G. Electric Type (Elektrischer Zünder), ESMIZ 40 consisted of an ebonite, Gorch funnel-shaped housing, provided with a spike and containing a striker, a spring, a release plunger, a glass ampoule and two electrodes. In order to enlarge the igniter area for one mine, usually an S-Mine, eighteen of these igniters were wired up in parallel, nine igniters in each chain, and spiked in the ground around the mine. The chains were connected by means of wires to two plugs fitted into sockets of the electric bridge (aluminum wire), surrounded with a flash composition and screwed on to the mine. Pressure on the prongs of any of the 18 igniters, depressed the release plunger and liberated the two steel locking balls in the head of the striker. This caused the spring to drive the striker into the glass ampoule. The liberated electrolyte set up a current between the electrodes and the current was transmitted to the bridge wire. The heat of the wire fired the flash composition and finally exploded the HE charge of the mine (1, p 83.08 & 3, p 300-1)

H. Chemical Igniter (Chemischer Zünder).

a) "Buck" Igniter (Chemical Crush-Actuated Type), used with the antipersonnel "Pot" mine, consisted of a thin aluminum foil drum containing a glass ampoule with sulfuric acid surrounded with a white, powdered flash composition. The drum was secured by crimping to the brass base. When pressure was applied, the foil drum was dented the ampoule broken and the acid mixed with the flash composition. This resulted in a chemical reaction which ignited the mixture and fired the detonator inserted in the mine (3, p 308-9)

b) CMZ 41W (Chemisch-mechanischer Zünder), used for delayed action demolitions consisted of a cylindrical bakelite housing containing a glass ampoule and other items shown on the drawing. When the ampoule was broken by pressure, the acid trickled through four perforations in the plastic lid into the reaction chamber (plastic cylinder) where the metal delay rod was located. As soon as the rod was sufficiently weakened and broke, the spring was released thus allowing the striker to hit the percussion cap. The resulting flash initiated the detonator, booster and the main HE charge (3, pp 313-14)











I. All Explosive Pressure Release Device, designed for use as a booby trap, was also suitable as an igniter in mines and other items. The body of the device consisted of two oblong blocks of molded explosive, (believed to be Nipolit), held together by two hollow brass bolts. The inner surfaces of both blocks were provided with molded recesses to retain the metal striker mechanisms. For operation, the device was placed under the object to be booby-trapped and as soon as the object was lifted the striker retaining arm of the device pivoted upwards, thus releasing the striker which fired the percussion cap, etc (3, p 307-8).

J. Long-Delay Clockwork Igniter.







a) 21-Day Delay Igniter was used in conjunction with large scale demolitions where a long delay was required (3, p 309)

b) J-Föder 504 Igniter was used for the same purposes as the previous igniter, but it could be set for delays ranging from 1/4 hour to 21 days. The igniter consisted of a Büchner funnel-shaped aluminum or bakelite body, housing a clockwork mechanism in the upper (wide) portion and a striker assembly in the lower (narrow) portion. At the end of the predetermined delay period, the lever arm on the rotating control disc bore against the trip lever, causing it to disengage the striker. The striker, driven by a spring, exploded the percussion cap thus initiating the main HE charge (1, p 83.09 &

IGNITERS



IGNITERS



3, p. 100

K. Tilt-Type Igniter (Kippzunder)

a) KIZ 43 consisted of a tilt rod, and a 24-inch extension rod connected to a cylindrical body containing the striker mechanism and a percussion cap. Lateral pressure of 18 to 25 lb exerted in any direction on the tilt rod for 1/2 in. if the extension rod was used, caused the pressure piece to slide down. This allowed the retainer balls to slide outwards, thus releasing the striker and its spring. The impact of the striker against the percussion cap set off the explosion train. This igniter was used in antitank and antipersonnel mines as well as in booby traps (1, p. 83, 076 & 3, pp 313-14)

b) KIZ 43 (New Type) retained the basic principles of KIZ 43 except that it had an entirely different safety device. It is described in Refs 1, p. 83, 076 and 3, pp 313-14)

L. Antilifting Igniter (Entlastungszunder), such as EZ 44 consisted of the flat cylindrical upper casing, the base plate, the clockwork and striker mechanism and the explosive filling. After winding the clockwork mechanism, the device was placed under a mine or other object and the arming bar was pulled out by means of a cord or wire attached to the ring. When released, the clockwork, which ran only for 35-40 seconds gradually forced the safety pin ring outwards, thus withdrawing the safety pin. The striker was now retarded by means of the catch (sear), which in turn was held in place by the compressed spring of the release button. Removal of the weight from the release button of the igniter allowed the striker spring to force up the sear by means of the leveled stop, thus releasing the striker (2, p. 163 & 3, pp 318-19)

M. Snap Igniter (Knickzunder).

a) KnZ 43/I consisted of a metallic cylindrical body and an extension composed of five tubular sections placed end to end and enclosed in a thin metal sheath. The extension housed five interconnected tension hooks, while the body contained the hollow striker transversely drilled above the striker pin, to accommodate the cross pin to which was assembled the snapping piece. The upper end of the snapping piece engaged the lower tension hook. This igniter was designed for use in mines lying between two tracks of enemy mines or for use in thick snow layers which prevent the functioning of the usual type igniters. The igniter operated (after removal of the safety pin) when the lateral pressure on the extension caused it to bend and to snap at the junctions. As a result of this the tension hooks exerted a pull on the snapping piece and the striker, thus breaking the snapping piece at its weak link. This action released the spring and allowed the striker to hit the percussion cap, thus exploding the mine (2, p. 163 & 3, pp 316-17)

b) KnZ 43/II consisted of a metallic cylindrical body (housing the percussion cap, striker and spring) and a plastic tubular extension (housing the plastic striker extension, retaining stud and retaining pin). Lateral pressure on the igniter caused the tubular extension, as well as the brittle plastic striker extension, to snap. This released the striker and allowed it to impinge upon the percussion cap, and consequently to explode the mine. Uses of this igniter were the same as for KnZ 43/I (2, p. 163 & 3, pp 317-18).

References:

- 1) Anon, Land Mines and Booby Traps, War Dept Field Manual FM 5-31 (1943)
- 2) Anon, Enemy War Materials Inventory List, Supreme Headquarters Allied Expeditionary Force (1945)
- 3) Anon, German Explosive Ordnance, Dept of the Army Tech Manual TM 9-1985-2 (1953).

Igniter Bags. According to E. Englesburg, The Ordnance Sergeant, May 1944, p. 321, the Germans employed igniter bags in all their artillery ammunition. The bags took the place of the large primers used by the U.S. Army in fixed and semi-fixed rounds of ammunition. The bags were either sewn to the base of the propelling charge or they were attached by means of a string. The standard substance employed in the bags during WW II was a finely grained nitrocellulose (See also Ignition and under Propellants).

Igniter Compositions (Zundsätze). Igniter compositions used for propellants are listed under Propellants and the igniter compositions used for Tracers are listed under Tracers.

Ignition (Zündung). Ignition of a propellant in weapons up to 50 mm was accomplished in Germany by means of a primer, while larger weapons required a primer combined with an igniter containing black powder. Army weapons caliber 50 to 280 mm had an igniter contg 2g of black powder, while the usual practice in the Navy was to use 1% of black powder per total weight of propellant. For guns larger than 280 mm an extension called Zunderstarker was used.

In addition to the primer extra igniters were sewn to both the front and rear of each section of the propelling charge.

For Flak and some Army guns the use of black powder was considered undesirable on account of its hygroscopicity and brittleness. It was reported that charges subjected to jolting contained broken up grains which caused too rapid ignition of the propellant. Much better results were obtained on replacing black powder by a charge called Beiladung which contained NzManNP (Nitrozellulose Manover Nudelpulver), a porous propellant prepared by leaching with water colloided NC contg some K nitrate. This propellant was also used in blank cartridges. Another replacement for straight black powder was NSP (Nitrozellulose-Schwartzpulver) which contained: NC 21.0, black powder 75.8 and diphenylamine 0.2%. This amount of NC was sufficient to bind the black powder together into hard grains.

In some cases, particularly at low loading densities, where th. Beiladung did not give satisfactory ignition, a Grundladung (base charge) of special flake propellant was used. The flake was of a size intermediate between the main charge of the tube propellant and that of the above NzManNP.

Practically all German cannon propelling charges consisted of long tubes and it was considered essential to ignite these at both ends. In order to ensure for the primer flash a clear passage to the front of the propelling charge, a thin-walled cordite tube of fairly large diameter was placed along the axis of each section of the charge. Reference: H.H.M. Pike, CIOS Report 31-68 (1946), pp 7-8.

Ignition (Inflammation or Deflagration) Temperature Test

Entzündungs- (Inflammations- oder Verpuffungs-) Temperaturprobe. For description of the test see Kast-Metz, Chemische Untersuchung der Spreng- und Zündstoffe Braunschweig, (1944), pp 224-6 and in the general section.

The ignition temperature of some explosive and pyrotechnic compositions was determined by F. Lenze, SS 27, 369-71 (1932).

(See also Flammability Test).

IG Wachs (IG Wax). During WW II, the I.G. Farbenindustrie developed several synthetic waxes some of which had higher melting points than natural waxes. These waxes were used for phlegmatizing explosives such as PETN and RDX.

Reference: A.G. Warth, The Chemistry and Technology of Waxes, Reinhold, N.Y. (1947), p. 389.

Illuminating Compositions and Illuminating Bombs (Leuchtsätze und Leuchtbomben). See under Pyrotechnic Compositions and also in Sterzbacher, Spreng- und Schießstoffe, Zürich (1948), pp 124-9.

Incendiary Bomb. See under Bombe.

Incendiary Compositions and Incendiary Bombs. (Brandstoffe oder Brandsätze und Brandbomben.) According to Ref 2, p. 18) most German incendiary projectiles consisted of an Elektron (such as MgAl₃ or MgAl alloys) casing filled with thermite (such as Fe oxide 70-76 and

Al 30-24%). Other fillings were white phosphorus, oil or compositions such as: petroleum 37.7, polystyrene 11.8 and phosphorus 0.5% (Ref 3, p 56). One type of projectile was prep'd by filling a container with pea-size lumps of dried paper pulp, followed by evacuation of air and running in molten white phosphorus (Ref 3, p 6). Another type, (TRP), consisted of a steel outer case into which two tubes were inserted, the outer of celluloid and the inner of paper; the space in between these two tubes was filled with naphthalene, and the inner tube with thermite (Ref 1, p 2).

Most incendiary bombs resembled in appearance the ordinary HE bomb. They ranged in sizes from 1 kg magnesium bomb (BIE) to the 500 kg oil-filled bomb (Flam 500). Several incendiary bombs are listed under Bombe. The smaller types were usually carried in containers, whereas the larger bombs were carried in bomb racks like a similar size high explosive bomb. The 1 kg and 2 kg magnesium bombs often had a small antipersonnel charge incorporated in the bomb to discourage fire fighters. Some larger types also had a small explosive charge but this was for the purpose of scattering the incendiary mixture.

(See also Bombe Brandbombe, Flammbombe and Sprengbrand bombe).

Only few of the German shells listed in Ref 5 were incendiary. One of them, 50 mm HE-Inc-1 (5 cm BrSpgrPatr 41 L'spur) was used in AA Gun, Flak 41 (p 397). Another was 88 mm Inc-Shrapnel (8,8 cm GrBrSchr Flak) used in AA guns Flak 18, 36 and 37 (p 448).

Some German incendiaries are described by Stettbacher (Ref 3).

References:

- 1) Lt Lisowski, BIOS Final Report 1233 (1945), p 2
- 2) E.M. Bateman, CIOS Report 32-13 (1945), pp 6 & 18-19
- 3) A. Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), pp 12, 9
- 4) TM 9-1985-2 (1953) 5) TM 9-1985-3 (1953).

Industrial Explosives. See Commercial Explosives.

Inertial Gravitation Guidance System or Ballistic Guidance System. See under Guidance Systems for Missiles.

Infra-Red Camouflage. See Infra-Rot Tarnung.

Infrared Guidance System. See under Guidance Systems for Missiles.

Infra-Rot Tarnung (Infra-Red Camouflage). Due to the fact that cloth covered objects could be readily detected by infra-red photography, even if camouflage coloring had been adopted, several dyes were developed by the IG Farbenindustrie which minimized or even prevented such detection. The following types of dyes were considered to be worthy of consideration: Aniline Black, Diphenylamine Black, Carbon Black (when printed with organic binders) and Indanthrene Oliv GW Suprafix.

Reference: CIOS Report 25-18 (1945), pp 14-17.

Ingolin. The name given by Dr. Welter to hydrogen peroxide of very high concentration (such as 85%). Ingolin can be used as a fuel or as a source of stored oxygen. As a fuel it produces superheated steam which can be used for driving either piston engines or turbines. As a source of oxygen, it was tried in submarines in order to allow them to use their main engines while submerged.

(See also Hydrogen Peroxide and T-Stoff).

Inhibiting Coating, intended to control the burning of rocket propellants and those for assisted-take-off (ATO), was developed during WW II at the Düneberg Fabrik, D A -G. Its composition was: polyvinyl acetate 25, lithophone 30, methylacrylate 5 and water 40%.

Reference: CIOS Report 29-24 (1945), p 5.

Initialexplosivstoff oder Initialsprengstoff (Initiating or Priming Explosive). See Priming and Initiating Composition.

Initialsatz (Initiating Composition). See Priming and Initiating Composition.

Initiating Compositions (Initialexplosivstoffe). See Primary and Initiating Compositions.

Initilivermögen (Zündkraft). The initiating property or power of primary or initiating explosives may be determined by loading an empty cap (such as the types used for No 8 detonators) with a weighed quantity of an explosive to be tested, compressing the sample and subjecting the loaded cap to one or both of the following tests: 1) Lead Plate Test or 2) Lead Block Compression Test.

These tests are used for the same purpose as the American Sand Test and Nail Test, described in the general section.

Reference: A. Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933), p 134.

J (Pulver). One of the sporting propellants: guncotton 79, Am bichromate 14.0, K bichromate 3.0, moisture 1.5, and gelatinizer: 2.5% Brunswick, Das rauchlose Pulver (1926) p 134].

Jagd pulver (Hunting or Sporting Propellant) Two kinds of propellants were used in shotguns and sporting rifles, black powder and smokeless propellants. The first successful sporting smokeless propellant was "Schultze-Pulver". Other smokeless propellants used for sporting purposes were: Amberit, E.C (Pulver), J (Pulver), Saxonia and Walsrode.

Reference: Brunswick, Das rauchlose Pulver (1926), p 134.

Jagd Tiger (Tank Destroyer Tiger). A self-propelled mount consisting of 128 mm A/T gun on PzKpfw VI (See under Panzer).

Jet Propulsion is briefly described in the general section. Some information on German jet units designed and manufactured by the Walter Werke, Kiel is given in CIOS Report 30-115 (1945).

Jet Propulsion Fuel. See under Sondertreibstoff.

J-Feder-504. Clockwork long-delay (1/2 hour to 21 days) igniter used in demolition charges. TM 9-1985-2, (1953), pp 309-13.

Jonckit. See Yonckite in the Belgian section.

Junkers Schmetterling. One of the guided missiles (q v) developed during WW II.

Reference: A. Ducrocq, Les Armes Secrètes Allemandes, Paris (1947) pp 93-95.

Kalkammonsalpeter (Chalk-Ammonium Nitrate) was an intimate mixture in granular form of chalk and Am nitrate. It contained 20.5 to 21% N and was used as a fertilizer. Reference: R.J. Morley, BIOS Final Rept 889, Item 22 (1946), pp 12-29.

Kaltspritzen (Cold-squirting). See Cold Extrusion in this and in the general section.

Kaltrecken, Kaltreckung (Cold Stretching). See Autofrettage in the general section.

Kampher (Camphor). See general section.

Kanone (K) (Cannon, Piece or Gun) Table 25a gives designations of German artillery weapons with their English equivalents:

Table 25a

| | | |
|---------------------------------------|-----------|---|
| Feldkanone | FK | Field Gun |
| Flugabwehrkanone | Flak | Antiaircraft gun |
| Gebirgshaubitze | GebH | Mountain howitzer |
| Gebirgskanone | GebK | Mountain gun |
| Kampfwagenkanone | KwK | Tank gun |
| Kanone Eisenbahn | KfE | Railroad gun |
| Kanone ohne Rücklauf | KoR | Recoilless gun |
| leichte Feldhaubitze | lFR | Light field howitzer called by the British "gun-howitzer" |
| leichte Kanone oder leichtes Geschütz | lK (IG) | Light gun |
| leichtes Infanteriegeschütz | lIG (lJG) | Light infantry gun |
| Panzerabwehrkanone | Pak | Antitank gun |
| schwere Feldhaubitze | sFH | Heavy field howitzer |
| schwere Kanone oder schweres Geschütz | sK | Heavy gun |
| schweres Infanteriegeschütz | sIG (sJG) | Heavy infantry gun |

Kanone ohne Rücklauf. See Recoilless Guns.

"Karl" Mortar. See "Thor" and "Karl" weapons.

Kartusche. See Cartridge.

KA-Salz The term assigned to RDX (Hexogen) prepd by the interaction of hexamine, Am nitrate, nitric acid and acetic anhydride. It is described in this section under Hexogen.

"Kaskade" Target Indicating Flare. See under Flare.

Kessen Explosives. Several explosive mixtures were proposed by W.Kessen of W A S A -G. One such explosive was patented in 1938 (Ref 1). It consisted of a regular blasting explosive plus an additional charge consisting of NG and/or nitroglycol mixed with a large amount of alkali bicarbonate. This mixture tended to produce inert gases and to absorb heat. If desired charges containing bicarbonate could be inserted between normal charges. These explosives were suitable for use in gaseous coal mines (See also Bikarbit and under Sheathed Explosives).

Another patent granted to the same person (Ref 2) dealt with the manufacture of moist Am nitrate explosives contg carbonaceous materials.

References:

- 1) W.Kessen and W A S A -G, Brit P 493 984, (1938) C A 33, 2719 (1939)
- 2) Ibid, Ger P 679,511 (1939); C A 33, 9647 (1939).

KH-Charge The designation for a compressed charge consisting of 4-8 pellets of TNT wrapped in paper glued on the inside with an acid-free glue (such as dextrin, Vinnapas, etc). The wrapped charges were dried at 60-70° and then dipped in paraffin. They were used as bursting charges in Naval mines. See PB Rept No 925 (1945), p 48.

Kinetit (Kinetite). One of the oldest (1884) gelatinous explosives containing no NG gelatine. It consisted of K chlorate 75, antimony sulfide 3, nitrobenzene or nitrotoluene 21 and collodion cotton 1% | Naoüm, Nitroglycerin (1928), p 353.

King Tiger or Royal Tiger. See Königstiger, under Panzer.

Kippzunder 43 (Tilt-Type Igniter). See under Igniter

Kitchen Salt Explosives. See Kochsalzsprenstoffe.

KIAZ 40. An impact-firing nose fuze used in some rockets, such as 8.6 cm R(L/4.5) and 8.6 cm R(L/5.5). | TM 9-1985-2 (1953), p 256.

KMA Block. One of the substitute explosives. See under Ersatzsprenstoffe.

Knallquecksilber (Mercury Fulminate)(MF) is described in the general section under Fulminates. German methods of preparation (from mercury, nitric acid and alcohol) are given in PB Rept No 95,613 (1947), section Q. MF was used by the Germans in some priming compositions. See also A.Stettbacher, Spreng- und Schiessstoffe, Zürich (1948), pp 95-96.

Knallsilber (Silver Fulminate). See general section under Fulminates and Stettbacher's book (1948) p 96.

Knallzündschnur (Detonating Fuse). See general section under Fuses.

Knetmaschine (Kneading Machine). An apparatus used for mixing solid ingredients in the presence of liquids. Several types were used in Germany such as the Columnar Type (Säulenknetmaschine) (Ref 2, pp 105, 106 and Ref 3, p 237), Werner-Meiderer Misch- und Knetmaschine (Ref 1, p 75 and Ref 3, p 227) and others.

References:

- 1) E. de B. Barnett, Explosives, Van Nostrand, N Y (1919)
- 2) P.Naoum, Schiess- und Sprengstoffe, Steinkopf, Dresden (1927)
- 3) A.Stettbacher, Schiess- und Sprengstoffe, Barth, Leipzig, (1933).

Knickzunder 43 (Snap Type Igniter). See under Igniter.

Kochsalzsprenstoffe (Kitchen Salt Explosives) Substitute explosive mixtures containing large amounts of Na chloride, which were used during WW II. Some of these mixtures are described under Ersatzsprenstoffe.

Kohlen-Carbonit

Kohlen-Koronit III, See under Kohlensprengstoffe.
Kohlen-Salit

Kohlensprengstoffe (Coal Explosives)

This was a group of explosives permitted for use in coal mines:

Kohlen-Carbonit. NG 25, K nitrate 34, Ba nitrate 1, flour 38.5, spent tan meal 1 and soda ash 0.5%; heat of explosion 506 kcal/kg, temp of explosion 1561°C, velocity of detonation 3160 m/sec, density 1.16 and Trauzl test value 235 cc (Ref 2, p 401 and Marshall, 2, p 492).

Kohlen-Koronit III. NG 4, K chlorate 68, Na chloride 14, paraffin 8, nitronaphthalene 5 and wood meal 1%; oxygen balance -12% and Trauzl test value 195 cc (Ref 1).
Kohlen-Salit, NG (gelatinized) 12.5, meal 2.5, nitro-compounds 7.0, Am nitrate 41.0 and alkali chloride 37.0%; oxygen balance -2.6% and Trauzl test value 260 cc. (Ref 2, p 441).

Kohlen-Westfalit I. NG 4.0, Am nitrate 83.0, K nitrate 7.0, Ba nitrate 2.0, meal 2.0 and TNT 2.0%; oxygen balance -16.4% and Trauzl test value 230 cc (Ref 2, p 435)

Kohlen-Westfalit IV. NG 3.2, Am nitrate 73.0, K nitrate 2.8, alkali chloride 15.0, meal 1.0, and DNT 5.0%; oxygen balance +8.8% and Trauzl test value 200 cc (Ref 2, p 435)

Kohlen-Westfalit V. NG 4.0, Am nitrate 83.0, K nitrate 8.0, Ba nitrate 2.0, potato meal 1.5 and Montan wax 1.5%; oxygen balance +13.5% and Trauzl test value 230 cc (Ref 2, p 435).

References:

- 1) P. Naoum, Schiess- und Sprengstoffe, Dresden (1927), p 147
- 2) P. Naoum, Nitroglycerin, etc, Baltimore (1928), pp 435 & 441.

Kohlen-Westfalit. See under Kohlensprengstoffe.

Kolax. An explosive of the carbonite type, such as: NG 25, K nitrate 26, Ba nitrate 5, wood meal 34, and starch 10%. There was also a Super-Kolax, an explosive used in England (Marshall 1 (1917), p 375).

Kolfit (Kolfite). A smokeless propellant patented in 1890 by H. Kolf of Bonn, which consisted of mixtures of nitrated cereal flours, moss, oil cakes, residues of factories manufacturing organic products such as starch, sugar, beer, alcohol etc. with saltpeter previously saturated with nitrobenzene.

Reference: J. Daniel, Dictionnaire. Paris (1902), p 394.


Kontinuierliche Verfahren (Continuous Methods) of manufacture of explosives such as those of Schmid, Meissner and Biazzi were used in several German plants.

Some of these methods are briefly described under Nitroglycerin, Pentrit and Trinitrotoluol, as well as in the Belgian, Dutch, French, Swedish and Swiss sections.

- References:**
- 1) A. Stettbacher, Schiess- und Sprengstoffe, Barth, Leipzig (1933), pp 174 & 333
 - 2) A. Stettbacher, Spreng- und Schiesstoffe, Rascher, Zürich (1948), pp 60 & 97
 - 3) A. Stettbacher, Pólvoras y Explosivos, Gili, Buenos Aires (1952).

Kopfring (Head Ring). When it was desired to avoid excessive penetration against land targets and to prevent ricochet against sea targets, rings were attached over the noses of bombs such as SC (HE cylindrical, general purpose) or some SD (A/P cylindrical, thick walled). (See also Anti-Ricochet Plates)

Reference: TM 8-1985-2 (1953), p 3.



Koronit V. One of the permissible explosives developed during WW I: NG 4, K chlorate 65, Na chloride 14, naphthalene 16, nitronaphthalene 5 and wood meal 2%. (Naoum, Schiess- und Sprengstoffe, Dresden (1927), p 147 j.

Note: According to Marshall, v 3 (1932), p 112, the name Koronit was given in 1931 to Chloronit 1.

K Pulver. Same as G Pulver.

Kraftzahl (KZ) (Strength Number). In the usual determination of power (strength) of an explosion by the standard Trauzl Lead Block Test, (see general section) one of the principal errors is due to weakening of the walls of the cavity, which is observed with powerful explosives such as blasting gelatin, P A, TNT and NG. In order to eliminate this error, Neubner proposed that, instead of measuring the expansion produced by a standard weight of an explosive, the weight of explosive required to produce a standard expansion of 300 cc be determined. This may be done by firing several charges of different weights in order to obtain values below 300 cc and above it. After drawing a curve giving the relationship expansion vs weight of sample, the expansion in cc corresponding to a 10 g sample can be determined by interpolation. This calculated expansion is called Kraftzahl (strength number).

Table 25b lists KZs for some explosives

Table 25b

| Substance | Trauzl Test Values observed by various investigators using a 10 g sample | KZ calculated by Neubner for a 10 g sample |
|------------------|--|--|
| Blasting gelatin | 520 to 610cc | 554cc |
| NG | 515 to 600 | 540 |
| NC(1.5%) | 325 to 420 | 400 |
| P A | 300 to 365 | 385 |
| TNT | 285 to 300 | 350 |
| DNB | 250 | 311 |

Note: It may be concluded from the above values that the KZ values for highly powerful explosives are lower than are determined by the standard Trauzl test, while for less powerful explosives (such as TNT or DNB) the KZ is higher.

References:

- 1) R. Neubner, S S 23, 54 (1928)
- 2) A. Marshall, Explosives, v 3 (1932), p 143
- 3) A. Stettbacher, Spreng- und Schiesstoffe (1948), p 113.

"Kranich". An acoustic proximity fuze intended for some guided missiles as, for instance, Rocket X-4.
Reference: TM 9-1985-2 (1953), p 216.

Kreuzrohr (Cross Tube). See Distance Piece.

Krumbach Nitrat (KN) Pulver. Double-base DEGDN-NC propellant with a calorific value of 710-730 kcal/kg, used in Flak. It contained a small amount of K nitrate as a flash reducer, in lieu of K sulfate used in G Pulver (CIOS 31-62, p 5).

Krumbach (Pulver) ohne Nitrat oder mit Dinitrotoluol (KOD). Double base DEGDN-NC propellant similar to Krumbach Nitrat Pulver except that K nitrate was replaced by DNT (CIOS 31-62, p 5).

Krümmler Fabrik of Dynamit A-G, located at Krümmel near Hamburg (See under War Plants) manufactured during WW II various explosives propellants etc and was engaged in research and development work for the Armed Forces (Wehrmacht).

Following are some of the achievements of Krümmel Fabrik personnel:

A. Pressing of explosives. In loading ammunition (such as detonators, boosters and projectiles) one of the most important requirements is to maintain the same density of loading for each type of ammunition and for each kind of explosive. As a rule, the effectiveness of an explosive is higher at maximum density, but in some cases such high density is undesirable because it might cause dead-pressing (as in the case of mercuric fulminate) or cracking of pellets (as in the case of Np10, which is PETN densitized with 10 parts of wax). The exact required density of charge was obtained by weighing accurately each portion of the explosive and proceeding as described below:

In the preparation of pellets for boosters, the weighed masses of an explosive were transferred to one or two dozen molds placed in portable holders underneath a corresponding number of filling funnels fastened together in perforated plates. During filling, loss of explosive was carefully avoided so that the required density would be obtained. After ascertaining that each mold was properly filled, the foreman placed the holder with molds under a press located behind a strong wall and operated by remote control. Any spilled material was collected and blended with the next batch of explosive. The pressed pellets were removed and inspected for dimensions and density.

Note: Most of the pressing was done with phlegmatized PETN (usually with 10% wax), which was used to form charges for the 37mm tank shell, 70mm solid or hollow charges, 20mm high explosive charges and incendiary explosive charges, colored smoke charges, etc. The 20mm incendiary charge consisted of about 80 parts of PETN (previously phlegmatized with 10% wax) and 20 parts of aluminum. The charge weighed 6.6g. Some TNT charges were also compressed, such as those for shrapnel burster tubes, explosive charges for some mines, etc.

B. Ejecting projectiles. Special projectiles which ejected incendiary missiles on approaching a target (such as an airplane) were developed but did not come to the manufacturing stage. These projectiles contained several hollow steel cylinders, each of which was filled with an incendiary mixture consisting of Ba peroxide, aluminum and iron. A charge of about 15 g of HE was required for ejecting each cylinder from the projectile and to impart to it an acceleration of about 1000 m/sec. Each of these cylinders burned in flight and if one of them hit a combustible object (such as a gasoline tank of an airplane) a fire or even an explosion could take place.

C. Space explosions with carbon dust. Preliminary work was done on the development of a bomb which was charged with a HE and coal dust. It was presumed that the detonation of the HE would explode the coal dust which would become scattered in the air surrounding the bomb, thus producing a high pressure (blast) effect at distances as far as 50 m from the center of the explosion. These bombs were intended for anti-aircraft purposes. Experiments with coal dust were not

successful, but Al or Mg dusts could be exploded in air when charged into a bomb mixed with a powerful HE and a small amount of chlorate. The research was not completed (See also Explosive Powered Vortices)

D. Shaped charges. See under Hohlladung

E. Flash reducing compounds are described separately


F. Structural explosives are described separately.

Reference:

O.W. Stickland et al, General Survey of Explosives Plants, PB Rept No 925 (1945), Appendix 3 and Appendix 7.

Krummerlauf (Bent Barrel). A special bent-barrel attachment to a gun, invented by Col H. Schade of the Rheinmetall-Borsig Co, was available in two degrees of bend 90° and 30°. The first type changed the course of the bullet by a right angle and was known as the "Around the Corner Gun". It was intended to be used (in a ball joint) in the parts of the tank where it was necessary to protect the blind spots. The barrel was 18 1/4" long and about 1" in diameter. Its range was short and its fire was not accurate. It was fired at random because no sight was provided. The second type (30° bent) barrel could be attached by means of an adapter to one of the service rifles, such as the MP 44. It was provided with a prismatic optical sight (designed by Zeiss), which permitted fairly accurate shooting from behind a solid barricade. The operator of this equipment was thus protected from enemy fire. Both barrels used the 7.92 mm short (kurz) bottle-necked cartridge.

A more detailed description may be found in the book: Ph. B. Sharpe, The Rifle in America, Funk & Wagnalls Co, N Y, pp 638-40.



Krupp Maus (Krupp Mouse). See Experimental Tanks, under Panzer.

K-Salz. The term assigned to Hexogen (RDX) prepd from hexamine, ammonium nitrate and nitric acid (See under Hexogen in this section).

K₃Stoff (K₃ Substance) A highly dispersed silicon SiO₂ prepd by a special process. It was used during WW II in some Tetan Explosives [PBL Rept 85,160 (1946), p 3].

"Kugelblitz" (Bullet Lightning). An armored AA vehicle having a 30 mm twin gun mounted on a PzKpfw III (See under Panzer).

Kugel K-"Kurt" Apparatus. See item 11 under Bombe.

Kugeltriebmine 41 (KTrMi 41). A spherical floating mine weighing about 90 lb. Recognition Handbook for German Ammunition, Sup 11qs AEF (1945), p 241.

Kumulative Zündung. See Gegenläufige Zündung.

"Kurt" Apparatus (SB 400 Skip Bomb). See item 11 under Bombe.

Kurzschlusszünder (Short-Circuit Primer or Igniter). Several varieties, such as the Schäffler, Reinecke and Eindrahtzünder (one-wire primer) are described in Beyling-Dreikopf, (1936), pp 216-222.

Lagerbeständigkeit oder Haltbarkeit (Stability in Storage or Keeping Quality). Several tests are described in Kast-Metz, Chemische Untersuchung (1944), pp 258-61, 220-27, 311-15 and 460-61. (See also Warmlagerversuche).

LANDMINEN (Land Mines). A great variety of land mines were used during WW II by the Germans as can be seen from the following information taken from References 1 - 6:

- 1) Antitank Mine, called **Pappmine**, because it was made of special cardboard "Pappe", a non-metallic substance used to prevent the detection of the mine by electric detectors. Pressure on the "pressure plate" forced it down onto the head of a glass igniter, containing a central glass tube filled with a reddish ignition mixture of unknown composition. Crushing of the central tube produced a flash which passed to the detonator which exploded the mine. Pressure on the cardboard of the mine would not set it off. The mine was filled with 11 lb of TNT (Ref 6, p 261)
- 2) Antitank Mine, called **Panzerschnellmine**, consisted of a wooden box filled with picric acid (13.2 lb). There were two types, A and B, very similar in construction. The booster in both cases consisted of 200 g of an explosive such as PETN/wax. Type A was actuated by pressure on the box lid, causing the shearing of two 1/2-inch wooden dowels and pressing out the link pin of the ZZ 42 igniter. Type B was actuated by pressure on the box lid shearing 3/4-inch wooden dowels and exerting pressure on the heads of two Buck igniters (Ref 5, pp 34-5 and 6, p 262)
- 3) Magnetic Antitank Mine, called **Panzerhandmine 3** was designed to be placed on enemy tanks or other targets to which it adhered by means of magnets (See under *Haftrohlladung*)
- 4) **Wooden Box Antitank Mine (Holzmine 42)** was filled with 50/50 Amatol (18 lb). The mine was in the shape of a flat box. A pressure of 200 lb or more on the pressure block sheared the dowels and forced down the shear flange, which in turn pushed out the pin in the igniter ZZ 42. The freed striker, driven by a spring, set off a percussion cap, detonator, booster and main charge (Ref 4, pp 81.06a-e and 6, pp 263-4)
- 5) Antitank Mine, called **Sprangriegelmine** (Explosive Bar Mine) was of two varieties: Riegelmine 8 kg and Riegelmine 43. The latter variety, abbreviated as R-Mi 43 was in the form of a long, flat box and consisted of a sheet steel tray, an encased charge of 8.8 lb of TNT and a lid which fitted over the tray and acted as a pressure plate. The mine could be fired in one of five ways: a) Pressure on the lid sufficient to shear one or two shear wires; b) Functioning of an antilifting or trip wire; c) Electrically, by remote control; d) Booby-trapping the mine, as by attaching a trip wire to the lid; e) Reversing of one igniter ZZ 42 with its wings below the end pressure plate so that the mine could function in case an attempt was made to lift the charge of TNT from the tray. Total weight of mine was 20.5 lb (Ref 6, pp 264-5 & 272-3)
- 6) Heavy Antitank Mine (**Schwere Panzermine**) was made of cast iron and contained 37 lb of Picric Acid. Total weight was 300 lb. The mine was fired by a downward pressure exerted on the cover plate, which pivoted on the trunnions. This pressure compressed the main pressure igniter, which fired the charge. The mine was used for road blocks where action had been static for a period of time. Total weight was 300 lb (Ref 6, pp 265-7)
- 7) Antitank Mines, called **Tellerminen** (Plate-Shaped Mines), were of the following varieties: Tellermine 35, Tellermine 42, Tellermine 43 and Tellermine 29. Type 35 mine existed in two varieties, both of them made of steel and similar in construction. The 2nd variety, designated Tellermine 35 (Steel) had the pressure plate made of corrugated steel for extra strength.












They were filled, respectively, with 11 and 12 lb of TNT. Both mines operated by pressure on the lid of 200 lb or more. This depressed the igniter housing and sheared the pin holding the striker in the cocked position. etc. The Tellermine 42 was similar to the 35 except that the pressure plate was smaller and did not include the entire upper surface. Pressure of 250 lb and over forced the pressure cap down. This compressed the heavy pressure plate spring and detonated the mine. The **TiMi 43 [also called Pilzmine (Mushroom Mine)]** was similar to the TiMi 42 except that the pressure lid was solid, i.e. there was no threaded hole for the insertion of the igniter and no screw cap. The walls of the mushroom shaped plate were thin and there was no heavy spring under the pressure. Like Tellermine 42 it was filled with 12 lb of TNT. The mine operated by downward pressure on the mushroom lid. This crushed its light walls and forced the head of the striker down, thus igniting the mine. Tellermine 29, also designated T-5 was a light antitank mine constructed of sheet steel. It was filled with 10 lb of TNT. The top was slightly domed and had three adapters for ZZ 29 igniters. The mine was exploded when sufficient pressure was applied to one or several igniters. Total weights of mines were as follows: TMI 35 20 lb, TMI 35 (steel) 21 lb, TMI 42 20 lb, TMI 43 18 lb and TMI 29 13.25 lb (Ref 1 & 2; Ref 4, pp 81.01-81.04 & 6, pp 267-70).

Note: According to Ref 2, the **TiMi 43 (Pilz)** examined during WW II at Picatinny Arsenal contained as the burster charge 10.87 lb of Amatol, consisting of Am nitrate 44 and TNT 56%. The booster pellets consisted of about 88% PETN and 12% Montan wax.













- 8) **Pot-Shaped Antitank Mine (Topfmine A)**, also called **Saucepan Mine**, consisted of a plastic body filled with 12.5 lb of TNT or 50/50 Amatol. Total weight of the mine was 20 lb. Under a load of at least 150 kg (330 lb) the pressure plate sheared along its groove and thus came to rest on the head of the igniter. This in turn moved down and crushed two small glass capsules located inside the igniter body. The capsules contained chemicals* which on mixing produced a flash. This in turn set off the detonator and then the HE charge of the mine (Ref 4, p 81.08; 5, pp 26-9 and 6, pp 271-2)
- 9) **Clay Mines** were of two types: Antitank and Antipersonnel. The Antitank Mine consisted of a baked clay pot 8 1/2" in diameter and 10" high with a wall 3/8" thick covered with a clay pressure lid about 3" thick. On opposite sides of the top of the pot were two round bulges which housed ZZ 42 igniters. Two hollow passages leading down inside each bulge carried the lengths of instantaneous fuse connecting ZZ 42 igniters with booster charges located at the bottom of the main charge, such as Picric Acid. Pressure on the lid pushed the pins out of the igniters, thus releasing the spring loaded strikers, etc. The Antipersonnel Clay Mine consisted of a round clay pot 8" in diameter and 3" high, with a wall 3/8" thick, provided with a cover. The charge of Picric Acid was detonated by means of the explosive train consisting of four ZZ 42 igniters, a detonator and a booster, when a pressure equal to as little as a man's weight was applied to the lid (Ref 5, pp 38-41)
- 10) **Antipersonnel or Antitank Aluminum Mine** was filled with Cheddite (7 lb) and had a TNT booster. The body and the lid were of a flattened cylindrical shape. Three DZ 35 igniters together with No 8 detonators were inserted in boosters located 120" apart inside the main explosive charge. Pressure on the sides or in the center of lid set off one or more of the three igniters and the mine went off. Total weight of mine was 20 lb (Ref 6, pp 273-4)
- 11) **Light Antitank Mine, IPzMi (Leichte Panzermine)**, which could be converted to antipersonnel use, consisted of two saucer-shaped, sheet metal covers forming an O-shaped container for 5 lb of TNT and an outer cover which served as a pressure plate. Five igniters were built into the mine and spaced radially around it. Pressure crushed the mine cover and forced one or more igniter housings downward over their plungers. This action compressed the outer spring, allowing the steel locking balls to be forced outward into upper recesses, releasing the striker, etc. For converting the mine to antipersonnel use the bottom igniter nuts were

*Note. According to Dr Hans Walther, one capsule contained liquid K-Na alloy and the other ethyl nitrate or nitric acid.

LAND MINES



Ger 106
LAND MINES



removed and the mine, resting on threaded ends or plungers, was placed on a hard flat surface. Light pressure on the mine cover depressed the entire mine and forced the plungers upward into the igniter housings. The mine weighed 9 lb (Ref 1, p 81.08 and 6, pp 273-5).

- 1.) Antipersonnel Mine, **Glasmine 43(f)**, was made of glass and contained 1 oz of HE such as TNT or Picric Acid. The lid was a thin glass plate and served as a shear plate. When sufficient pressure was applied, the lid was broken and this action crushed the top of the Buck igniter or tripped the actuating lever of the Schuko igniter (Mittelzunder), depending on which device was used. The mine was made waterproof by applying a cement putty around the lid (Ref 3, p 82.06; 5, p 30 and 6, pp 275-6).
- 13.) concealed Antipersonnel stickmine, called **B-Stobmine**, was made of wood, as a box 3/4 x 6 x 10 inches. It contained a HE which was not specified. On top of the box was mounted a wooden support to hold a wooden block with an initiating stick. In the base of the block was a metal hook to which was attached a wire connected with the eye of the pull igniter ZZ 35, located in the cover of the box. Movement of the stick pulled the wire which set off the igniter (Ref 6, pp 276-7).
- 14.) Antipersonnel Mine, called **Stockmine**, consisted of a concrete cylindrical body attached to a wooden stick, about 1.4' long, driven into the ground. The mine contained a standard borehole cartridge weighing 100g and a pull igniter-detonator assembly. The concrete of the body held some pieces of shrapnel which were thrown in all directions when the mine exploded. A pull pressure of 9 to 13 lb was sufficient to set off the mine (Ref 1, pp 82.02 and 6, pp 276-7).
- 15.) Antipersonnel Concrete Ball Mine, which weighed about 2.2 lb, contained HE (about 1 1/2 lb) and an igniter-detonator assembly. Some shrapnel pieces were embedded in concrete. The mine could either be placed in the ground or rolled down a hill or cliff into enemy troops. In the last case the igniter was pulled by hand, prior to rolling the ball, thus igniting the time (safety) fuse connected to the primary charge of the detonator (Ref 1, p 82.05 and 6, pp 277-8).
- Note: It seems that this mine was also called the **Rollbombe** (Rolling Bomb).
- 16.) Antipersonnel Mine, called **Schützenmine 42**, abbreviated as **Schürmine 42**, consisted of a wooden box containing a 1 lb demolition block together with a ZZ 42 igniter and a detonator. The box was covered with a hinged lid. Pressure on the lid pushed the pin out thus freeing the striker. Total weight was 1.1 lb. A modified version of Schürmine used the ZZ 35 igniter (Ref 1, p 82.04 and 6, pp 278-9).
- 17.) Antipersonnel Improvised Mine (**Behelfsmine W-1**) was made from captured French 50 mm mortar shell from which the nose fuze and tail fins had been removed. A Buck chemical igniter and a detonator were fitted inside the cavity in the HE charge, which was either Picric Acid or granulated TNT weighing 4 oz. A pull or pressure of not less than 35 lb was required to set off the mine (Ref 6, p 279).
- 18.) Antipersonnel Mine, **S-Mi 35**, which might mean either **Schrapnellmine 35** or **Schützenmine 35**. The mine was also called **Bouncing Mine** because prior to the explosion the inner case of the mine was projected upward 3 to 5 feet. The British called this mine the "Fruit Tin" because it resembled a tin can in size and shape. The mine consisted of an outer steel case and an inner canister which held about 6 1/2 oz of TNT or Amatol surrounded by about 350 shrapnel balls. A central steel tube running axially through the mine, contained in its upper part an igniter and in its lower part a 4 1/2 second delay pellet. A black powder charge for ejecting the mine, was located beneath the inner canister. Three detonator tubes were spaced radially around the inner canister, 120° apart, and a short delay element was fitted into the bottom of each tube. The mine operated by pressure or by pull. In either case, when the igniter was fired its flame ignited the 4 1/2 second delay element which in turn ignited the expelling charge. The resulting gas pressure forced the inner container upward into the air and at the same time ignited the short delay pellets in the three detonator tubes. The delay in these

tubes was sufficient to permit the mine to rise in the air before the detonators in the tubes were set off. The detonators then exploded the main charge and the shrapnel balls were dispersed in all directions. The effective range was 200 yards. Various antilifting devices were employed with this mine (Ref 1; 4, p 82.01 and 6, pp 280-1).

- 19.) **S-Mine 44** was similar in design to S-Mi 35, except that the S-Mi 44 used a push-pull type igniter (SMiZ 44) (which was not located in the center as in S-Mi 35) and the mine detonated at a predetermined height of about 36" (Ref 6, pp 279-80).

Note: According to Ref 5, p 82.01-e there were other modifications of S-Mine and Ref 3 describes S-Mi 41.

- 20.) **Eismine 42** (Flascheneismine) was an A/P Mine in the form of a wide-mouth bottle, intended for use under ice. The bottle contained 5 lb 10 oz of Gelatine-Donarit and was provided with a pull or pressure igniter. The mines were also used as antipersonnel land mines. For this they were encased in concrete containing shrapnel (Ref 6, pp 281-2).
- 21.) **Behelfsschützenmine** was an improvised A/P mine in the form of a mustard pot and was loaded with powdered Picric Acid (4 oz). The mine was covered by a pressed steel lid with the Buck igniter attached by means of an adaptor. The detonator was inserted in the center of the HE charge. A moderate pressure on the top of the igniter was sufficient to set off the mine (Ref 6, pp 282-3).

Abbreviations: **A/P** Antipersonnel, **A/T** Antitank, **HE** High Explosive.

References:

- 1) A.B.Schilling, Pic Arsn Tech Rept 1246 (1943) (Tellermine)
 - 2) A.B.Schilling, ibid 1377 (1944) (Tellermine Land Mine Type 4)
 - 3) J.P.Wardlaw, ibid, 1387 (1944) (Antipersonnel Mines S-35 and S-41)
 - 4) Anon, Land Mines and Booby Traps, War Department Field Manual FM 5-41 (1943-1944), pp 81.01-82.06
 - 5) Anon, Mines in the Spotlight, Intelligence Bulletin, March 1945, pp 24-43
 - 6) Anon, German Explosive Ordnance, Dept of the Army Technical Manual TM 9-1985-2 (1953), pp 261-83
- Note: The following mines (which are not described in the above references) are listed in the "Enemy War Materials Inventory List", Supreme Headquarters, Allied Expeditionary Force (1945), pp 156-7: **Rampenmine** (Improvised Ramp Mine), **Landmine T 40 (h)** and **No 2 (h)** (Dutch Land Mines), **Panzerabwehrmine (b)** (Belgian A/T Mine), **Behelfsschützenminen S 150, A 200 & A 202** (Belgian Improvised Pot Mines), **Stangenladung** (A/P Mine, Pole Charges), **Behelfsmine E 5** (Improvised A/P Mine, consisting of 5 "egg" hand grenades), **Geschossmine 27 cm** (Improvised Mine, made from 270 mm shell), **Rollbombe** (Rolling Bomb), **Kugeltreibmine 41**, abbreviated as **KTrMi 41** (Spherical Drifting Mine, GL) and **Flusstreibmine 41**, abbreviated as **FTTrMi 41** (River Drifting Mine, GLP).

Lead Azide. See Bleiazid.

Lead Peroxide. See Bleiperoxyd.

Lead Picrate. See Bleipikrat.

Lead Styphnate (Bleitrinitroresorsinat). See Trizinat.

Leaflet Rocket. See Propaganda Rakete.

Leont (Leontite). Permissible explosive consisting of K perchlorate 35, Am nitrate 10, Na nitrate 3, crude TNT 11, wood flour 7, NG 4 and alkali chloride 30%.

Reference: M.Giua et al, Dizionario di Chimica, UT-ET, Torino, (1951), p 166.

"**Leopard**". See Experimental Tanks under Panzer.

"Leopold" or "Anzio Annie". A 280 mm Railroad Gun, Model 5 (28 cm K-5), designed during WW II by Gessner (See also Gessner Gun and under Weapons).

Leuchtbombe (Illuminating Bomb). See under Bombe and Flare.

Leuchtpursätze oder Lichtpursätze. See Tracer Compositions.

Lever Igniter (Hebelzündler). See Pressure Igniter, under Igniter.

Lignofol. A highly compressed laminated wood used for the construction of the cas of some rockets; e.g. the Rheintochter, TM 9-1985-2 (1953), p 227.

Lignose Sprengstoffwerke G m b H, Berlin. See under Warplants and Arsenal.

Liquid Rocket Propellants. See Rocket Propellants, Liquid.

Littlejohn Gun or Squeeze-Bore Gun. See Note under Tapered Bore Gun.

LPZ Mine. A light antitank or antipersonnel land mine. It is briefly described in TM 9-1985-2 (1953), p 274.

LT (Low Tension) Electric Detonator. See Gasless Delay Detonator.

Luchs (Lynx). See under Panzer.

Lurgi Spaltenlage (Lurgi Cracking Plant) operated during WW II at the Schlebusch Fabrik, D A G. It regenerated SO_2 (and later SO_3) from strong sulfuric acid contaminated with organic materials and suspended solids.

The procedure was essentially as follows: Dirty sulfuric acid was volatilized in the cracker (in an oxidizing atmosphere) by means of two burners utilizing producer gas from a coke fired furnace. By maintaining the temperature above $800^\circ C$, the acid was dissociated into SO_3 and H_2O and then the bulk of the SO_3 was dissociated into SO_2 and O_2 . At the same time organic compounds burned to CO_2 and H_2O and the sulfur to SO_2 . The gases leaving the cracker were rapidly chilled in a system containing dust separators, an air cooler and two water circulated gas cooling towers. The resulting SO_2 was used for the manufacture of oleum.

Reference: F. Heppenstall et al, BIOS Final Report 1634 (1946), pp 9-13.

Luvicar. Trade name of Polyvinylcarbazole. According to CIOS Rept 21-3 (1945), p 5 this plastic was unsatisfactory for injection molding since it had a melting point of over $200^\circ C$.

Lynx. See Luchs, under Panzer.

M/71 Normal-Pulver. Black powder used by German Infantry previous to the invention of smokeless propellant [Daniel (1902), p 414].

M 88/91, M 91/94 (Pulver). Smokeless propellants manufactured at the end of the last century by the Vereinigte Köln-Rottweiler Pulverfabriken at Rottweil, Würtemberg [See Daniel, Dictionnaire (1902), p 414].

Machine Gun (Maschinengewehr). See under Weapons.

Machine Gun, MG 42 (Maschinengewehr 42) is a 7.92 mm weapon developed in 1942 and which served during WW II as the basic weapon of the infantry squad. All its parts were manufactured by stamping. It could

fire up to 1,200 rounds per minute. For a more detailed description see: M.M. Johnson, Jr, Army Ordnance 30, 352-58 (1946) and G.M. Chinn, The Machine Gun, US Navy, Bureau of Ordnance, Washington, D C, v 1 (1951), p 484.

Made-up-Charge. According to the description given in PB Rept 925 (1945), p 18, the Germans designed the following system of propellant loading intended to replace the bag loading in large caliber guns:

A large cylindrical casing, 18" diameter and 6 ft long, made of sheet smokeless propellant $3/16$ " thick, was closed at each end with a disc of the same material. Each disc had a hole, 3 " diameter, through which was inserted a long pipe which was made of smokeless propellant, and perforated with numerous holes $1/2$ " diameter. The space between this inner tube and the walls of the cylinder was filled with grains of a propellant of desired shape, size and calorific value. The inner perforated tube served to convey the flash from the igniter charge to the propellant charge.

It was claimed that the propellant charge of the so-called "Sevastopol Gun" was made on the above principle.

"Madrid" Infrared Homing Device. See under Guidance Systems for Missiles.

Magnesium Oxide (MgO), described in the general section, was included as a component of many German solventless extruded propellants. It was claimed that MgO greatly facilitated the extrusion process. The composition of some propellants contg 0.05 to 0.25% Mg is given in PB Rept 925 (1945), p 85-91. (See also under Propellants).

Magnetic-Ballistic Guidance System for Missiles. See under Guidance Systems for Missiles.

Magnuskraft (Magnus Effect). See general section and also books on Ballistics.

Mannol. Trade name for Ethylacetanilide described in the general section. Its 20% alcoholic soln is a good gelatinizer at 55° or higher temperatures for collodion cotton.

Reference: Kast-Metz, Chemische Untersuchung (1944), p 160.

Manöverpulver (Maneuver or Blank Fire Propellant). The following compositions are given in Brunswick, Das rauchlose Pulver, (1926), p 136: a) guncotton 97, diphenylamine 1.0, moisture 1.0 and gelatinizer 1.0%; b) guncotton 67, NC 32, moisture 0.5 and gelatinizer 0.5%.

MAN-Salz (Man-Salt). Described as Methylamine Nitrate in the general section. The German technical salt had a m p ca 103° , while the purified material was $109-110^\circ$.

One of the German methods for preparation of MAN-Salz was as follows:

Methylamine (97-98.5% purity) and weak technical nitric acid (45 to 66%) were mixed continuously at the rates of 1240 and 5600 parts by weight per hour respectively. The temperature was held at

about 70° so that the heat of neutralization could be utilized at the same time for the vacuum concentration of the salt in order to avoid using too much steam. The resulting solution of methylamine nitrate in acidic water was concentrated at about 50° to about 85% strength. The concentrated aqueous liquor, which had a pH of 6.5 to 7 was cooled to 20° with water while being stirred, and the first crop of crystals collected (about 40% of the total salt). Then the solution was cooled to -10° to recover another 40% of the product. A centrifuge was used to remove the crystals. The mother liquor (about an 87% solution of MAN-Salz) was used to wash both batches of crystals in the centrifuge; a total of about 10% by weight of the centrifuge charge was used for a washing. Three washings were made. About 2/3 of the final mother liquor was returned to the evaporation cycle, the other 1/3 to the salt regeneration and purification. Final drying was done in stoves or by blowing hot gas through the molten salt; pH control was necessary for economical recovery (Ref 1, p 22).

According to German sources, the heat of explosion of MAN-Salz is 1200 kcal/kg vs 1000 for TNT, the volume of gases produced at NTP (0° and 760 mm Hg) 834 l/kg vs 780 for TNT and the velocity of detonation 6600 m/sec vs 6200 for TNT, at a density not indicated. The salt is practically insensitive to shock and stable even when held at temperatures ranging up to 150°. In order to insure the maximum detonation rate of MAN-Salz, it is advisable to mix it with a small amount (as low as 5%) of RDX (or PETN). MAN-Salz is hygroscopic, but the hygroscopicity is reduced on the addition of Na nitrate or other substances. A mixture of MAN-Salz with Am nitrate and 15% RDX has a heat of explosion of 1120-1260 kcal/kg, volume of gases 740 l/kg and velocity of detonation 6700 m/sec. It is insensitive to shock and can be cast-loaded (Ref 3).

Uses: Due to the high m p of MAN-Salz, it was considered unsafe to cast-load it into shells or bombs. This difficulty was overcome by incorporating some Am nitrate, as for instance: MAN-Salz 25 to 30, Tri-Salz 1 to 3 and Am nitrate 67 to 74%. This mixture called *Formit* softened and exuded at 60-70° and was considered not very suitable for use in shells. However, suitable m ps were obtained when ammonium nitrate was replaced by Na nitrate, as in the following mixture: MAN-Salz 58 parts, Na nitrate 42 and RDX 15. (Ref 3). This explosive composition was practically oxygen balanced and proved to be suitable for use in shells and bombs. It proved also safe against shock or bullet impact, but it detonated when hit by a bomb or shell. A similar mixture was known as C6 (see Ref 2).

In order to eliminate the danger of detonation of projectiles (filled with MAN-Salz) in the course of shipping them to the front, it was proposed to incorporate 10-15% of water in the MAN-Salz. This amount of water was sufficient to render the MAN-Salz insensitive to shock or to sympathetic detonation. In order to make these mixtures sensitive to initiation, it was only necessary to add to the contents of projectiles (before use) some highly concentrated nitric acid

and about 15% of a highly dispersed inorganic agent, such as silica or alumina. In order to prevent corrosion from the nitric acid the inside of the projectile was coated with acid-proof paint, such as a hydrocarbon-type high polymer.

MAN-Salz was also used in mining explosives, where it was usually mixed with Na nitrate (the eutectic melts below 50°) and a small amount of hydrated starch or other gel (to render the mixture plastic). Small quantities of RDX or PETN could be incorporated when it was desired to increase the velocity of detonation of the explosive.

References:

- 1) O. Stickland et al, General Summary of Explosive Plants, PB Rept 925 (1945), p 22
- 2) G. Römer, Report on Explosives, PBL Rept 85,160 (1946), p 25
- 3) H. Walter et al, German Development in High Explosives, PB Rept 78,271 (1947), pp 4-7.

MAN-Salz Perchlorat (Man-Salt Perchlorate, Methylammonium Perchlorate) was prepd by Walter et al by neutralizing monomethylamine with perchloric acid. As this explosive had a high m p and was highly sensitive to shock, it was necessary to use it in mixtures with substances which would lower its sensitivity as well as its m p. The low m p was desirable in order to be able to cast-load the explosive. Such mixtures could be obtained by boiling under reflux, a solution of Am perchlorate in commercial aqueous formaldehyde. After distilling off the water and other volatiles, a solid explosive, m p 90-100°, was obtained. It was compatible with RDX. As it was inferior to MAN-Salz, no further investigation was made [Walter, PB Rept 78, 271 (1947), p 7].

Mantelpatrone (Sheathed Cartridge). A short description of sheathed explosives is given in the general section. During WW II, the Germans used "active sheaths" (q v) for housing explosives such as *Wetter-Wasagit A*.

(See also References under Active Sheath).






Marabu, One of the proximity fuzes developed during WW II in Germany. The device is mentioned on p 229 of TM 9-1985-2 (1953).

Marder (Marten) (Called by the French "torpille humaine") A device developed in 1944 consisting of a torpedo with a warhead and another on top of it containing no explosive, but a small cabin to house one man. The two torpedos were attached to each other in such a manner that it was easy to disconnect them when necessary. The ensemble was launched from a ship or shore against a target and when it approached to within 100 or 200 m the operator took good aim and detached the lower torpedo contg the warhead. This left the upper torpedo (contg the cabin) afloat by itself. After this, the operator had to swim towards his ship or shore on the upper torpedo.
[A. Ducrocq, Les Armes Secrètes Allemandes, Berger-Levrault, Paris (1947), pp 33-34].

Marder II, A self-propelled mount (also called tank destroyer) consisting of the 75 mm A/T Gun or of the 150 mm Heavy Infantry Gun on PzKpfw II tank (See also under Panzer).

Marder 38, A self-propelled gun mount utilizing one of the varieties of Czech tank T-38 (See under Panzer).

MARKERS



Marine Explosives of WW I and WW II. Under this title A. Stettbacher, in Protar (Switzerland) 9, 31-45 (1943), describes the explosives used by the Germans for filling torpedoes, sea mines, depth charges etc:

- a) Explosive of WW I: TNT 60, HNDPhA (hexanitrodiphenylamine) 40%
- b) Explosive of WW II: TNT 61.8, HNDPhA 23 and Al powder 15.2%

The second mixture was much more effective than the first one.

Marine-Geschütz Pulver. Black powder used as a burster in photoflash bombs, such as BLG 50/A bomb. The composition of the powder was: K nitrate 75, sulfur 9 and beech charcoal 16%. The granulation was 0.68 to 1.3 mm and the moisture content 1.3%.

Reference: TM 9-1985-2 (1953), p 82.

Mark 50 Koskude (Cascade Flare Bomb). See under Pyrotechnic Anti-Pathfinder Devices.

Marker (Anzeiger). A pyrotechnic device used to mark a position. Most of the German markers consisted of cylindrical cardboard containers filled with a colored flare composition which was ignited by an impact type fuze. Some markers merely contained a brightly colored powder, which was dropped into the sea from low altitudes to mark positions. Others were modified parachute flares of various colors.

The following devices, described in TM 9-1985-2 (1953), could be classified as markers:

- 1) NC 50 WC NC 13/Sheet. Smoke Marker Bomb resembled an ordinary HE bomb. It consisted of an aluminum outer casing (empty except for metal ribs and braces), tail cone, nose and central cylinder which protruded from the nose and extended aft to the forward part of the tail where it was terminated by a fuze housing crimped to it. Waterproofing at the tail was provided by a rubber seal. The central cylinder contained the smoke producing agent. Four fins and a plate (called drogue) were attached to the tail end. Impact of the bomb on water caused the drogue, together with the fuze release rod, to be wrenched off. This action fired the fuze and ignited the smoke mixture. At this time the bomb would be floating on the surface. Eventually the heat from the burning smoke composition destroyed the rubber seal and the smoke was vented to the outside, thus indicating the position of the marker (pp 58-9)
- 2) Mark S Flare, Types 1 and 2. Floating devices which could serve as markers or for signalling purposes (See under Flare and in TM 9-1985-2, pp 77-8)
- 3) Target Indicator (Red) consisted of an aluminum cylindrical casing housing a flare composition enclosed in a cardboard cylinder. The suspension plate at the tail held an eye to take the parachute shackle, and a pull igniter which was connected by a 4 1/2 inch length of safety fuse to a small bag contg black powder. This served both to set off the igniter pellet in the top of the candle and to eject the latter from the casing when it fell freely to earth and acted as a ground marker. The pull igniter was attached to the loop of the shroud lines by a cord and the opening of the parachute gave the necessary pull for operating the igniter. There were (for some unknown purpose) two small fins at the nose end of the container (pp 84-5)
- 4) Sea Marker Bomb consisted of sheet steel, bomb-shaped container, supported internally by a series of annular strengthening bulkheads. The tail end of the bomb was provided with four stabilizing fins and an extension housing a lamp unit covered with a lucite dome. A battery of six dry cells was housed in the center of the bomb. At the moment of the release of the bomb from the aircraft, the inertia bolt was positioned between the plates of the spring switch in such a manner that one side of the circuit between the lamp and the batteries was broken. On impact of the bomb, the inertia bolt was forced out of position and the circuit between the lamp and battery was completed. As the batteries filled only a portion of the bomb body and as all joints were made tight by rubber washers, the marker floated on the surface of water. It is assumed that the marker provided a recognition or bearing point for

aircraft (pp 85-6)

5) Sea Marker LUX EZ 50 SC was constructed of sheet steel in two parts (nose and tail) loosely joined together about 1/3 the distance from the nose. Its external view and a brief description are given on p 87 of TM 9-1985-2 (1953).

6) Mark 3 Grün (Single Unit Ground Marker, Green) consisted of a sheet steel cylinder enclosing a cardboard container with the pyrotechnic composition, a fuze with gaine (filled with black powder), an arming spindle and an arming vane, which was loosely fitted within the housing. On release of the marker from the aircraft, the current of air rushed through the vent holes in the arming vane, thus ejecting it from the housing. By reason of its shape, the arming vane rotated as the missile was falling. This rotation unscrewed the arming spindle of the fuze thus permitting its clockwork mechanism to function. At the expiration of predetermined delay, the black powder in the gaine became ignited. The resulting flash ignited the pyrotechnic composition and at the same time a slight explosion took place which ejected the cover cap, fuze and arming vane housing. The pyrotechnic filling burned for about 3 1/2 minutes

7) Lux N Flame Float. A bomb-like device constructed of sheet steel and provided with four fins. When released over water the device went under the surface thus allowing the water to enter the ports and to pass down the inlet tube into the calcium phosphide chamber. The resulting reaction produced phosphine gas which passed up the outlet tube through the nonreturn valve to the burner where it ignited spontaneously to form a pilot jet. At the same time, water entered through the channels in the nose and passed through a perforated tube into the calcium carbide compartment. The acetylene evolved passed through the perforated diaphragm into one compression chamber and thence to the burner where it was ignited by the pilot jet (pp 91-2)

8) Lux S Flame Float (Types 1, 2 and 3) was cylindrical in shape and contained, as in the previous device, Ca phosphide and Ca carbide (pp 92-3).

Marspille or Mars Priming Drops. Low tension fuseheads intended for ordinary instantaneous detonators. They were manufactured by dipping the tip of the electric bridge wire into the following liquids:

- a) 1st dip composition consisted of 100 g of dry Pb picrate suspended in 50 ml of a 2% solution of NC in amyl or butyl acetate. After the drop on the tip became dry it was dipped into
- b) 2nd dip composition consisting of Pb picrate 40 g, K perchlorate 35 g and alderwood charcoal 25 g, suspended in 50 ml of a 2% solution of NC in amyl or butyl acetate
- c) 3rd dip composition contained K perchlorate 85.7 and alderwood charcoal 14.3 g, suspended in about 50 ml of a 3% solution of NC in amyl or butyl acetate
- d) 4th dip composition was a lacquer consisting of a 15% solution of NC in 75/25 butyl acetate ethanol to which was added (20% of the dry weight of NC) Sipolin AOM (which is the methylcyclohexyl ester of adipic acid) and 17 g of Sudan Brown for each 10 l of liquid.

Notes: A) For material to be used in tropical countries, the 4th dip contained Al powder (200 g per liter of lacquer), which was supposed to protect the fusehead against static electricity
 B) Marspille possessed the property of not igniting firedamp, which was a great advantage
 C) The soldering of the bridge wire to lead-in wires, the preparation of dry ingredients for fusehead dips, the preparation of NC varnishes and the process of dipping the fuseheads are described under Fusehead Manufacture.

References:

- 1) B.I.O.S. Final Rept No 833, Item 2(1946), p A3/36
 2) PB Rept No 95,613 (1947), Section D.

Maschinengewehr (Machine Gun) See under Weapons.

"Maus" (Moose). A heavy tank designed by Porsche (See Experimental Tanks, under Panzer)

Meganit (Meganite). One of the WW I straight dynamites: NG 60.0, nitrated wood pulp 10.0, nitrated ivory nut meal (corozo) 10.0 and Na nitrate 20.0% P.Naoum, Nitroglycerin, Baltimore (1928), p 284

Mehlpulver (Meal Powder). A finely pulverized black powder used in pyrotechnic compositions. Its preparation is described by A.Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933), p 103 (See also Meal Powder in the general section).

Melan. A jelly originally prepared by Sprengstoffe A-G Carbonit, Schellusch, by boiling glycerin with an aqueous solution of glue. It was incorporated in some dynamites in order to increase their plasticity. Some glycerin-glue mixtures contained dextrin (See also Gelatine-Carbonit and Safety Jelly Dynamite).

Reference: P.Naoum, Nitroglycerin, Baltimore (1928), p 406.

Meldebüchse (Message Container or Message Tube). A device for dropping messages. Two types of containers used for this purpose are described in TM 9-1985-2 (1953), pp 120-1:

a) Sea Message Tube consisted of an aluminum cylinder in which the upper compartment contained a smoke composition, whereas the lower (airtight) compartment carried a message. On dropping the missile from a plane, the friction igniter was pulled and the resulting flash ignited the delay fuse, which in turn ignited the bottom part of the smoke composition. When persons for whom the message was intended, saw the smoke, they approached the missile and removed the message container by opening the cap (at the rear of the tube) and pulling the chain (p 120)

b) Land Message Tube was also cylindrical in shape and consisted of two compartments. The smoke composition in the upper compartment was ignited by means of four strands of quickmatch which extended down the side of the smoke container and met several pieces of quickmatch below the smoke container. The strands were ignited when the friction igniter was pulled on dropping the missile from a plane. The message was withdrawn by unlocking the nut and removing the cover. (p 121).

Mercuric Fulminate. See Knallquecksilber.


Message Pistol Grenade (Nachrichten Pistolengranate). See under Pistol Grenades.

Message Tube. See Meldebüchse.

Messel (Measuring Egg). A device designed at the Krupp plant for measuring the pressure developed in guns. The extent to which a copper cylinder was compressed by the gases of combustion of a propellant served as a measure of the maximum pressure developed in chamber. For more information on this subject, see H.Brunswig, Das rauchlose Pulver, Berlin (1926), p 412.

Metacelluloid. Trade name for m-Toluensulfamide, $H_3C.C_6H_4.SO_2NH_2$; white crystals, mp 107° . Its solution in some organic media was claimed to be a good gelatinizer for NC.

Reference: Kast-Metz, Chemische Untersuchung, Braunschweig (1944), p 162.



Methylamine. Its preparation and properties are given in the general section. According to Dr H. Walter, methylamine was never used in Germany per se but in the form of its nitrate, called Man-salz (qv).

Methylamine Nitrate. See Man-Salz.

Methylnitropropanediol Dinitrate,

$$\begin{array}{c} O_2N \\ | \\ H_3C - C - CH_2ONO_2 \\ | \\ CH_2ONO_2 \end{array}$$

described in the general section, was examined in Germany during WW II as a possible substitute for NG in propellants. It was found to be fairly stable but not a very good gelatinizer for NC.

Reference: PB Rept 925 (1945), p 15.

Methylstaff. A mixture of aluminum dichloromethyl, AlCl_2CH_3 , and aluminum chlorodimethyl, $\text{AlCl}(\text{CH}_3)_2$, proposed as a substitute for phosphorus in incendiary compositions. The mixture was prepared by passing methyl chloride vapor through copper-free aluminum turnings. Reference: R.E. Richardson et al. CIOS 25-18 (1945), pp 4-5.

Metrioltrinitrat (Metriol Trinitrate), (Methyltrimethylol-methane Trinitrate or Pentaglycerin Trinitrate), $\text{H}_3\text{C}_4(\text{CH}_2\text{ONO}_2)_5$, described in the general section, was developed in Italy before WW II by Bombrini Parodi-Delfino and adopted later by the Germans.

The following method of preparation was used at the Krümmel Fabrik of D A -G :

- 50 kg of finely pulverized and sieved Metriol was slowly fed with stirring by means of a worm screw, into a stainless steel nitrator containing 175 kg of mixed acid, (65% HNO_3 and 35% H_2SO_4) maintained at 20° . Formation of lumps had to be avoided because this could lead to overheating and decomposition of metriol and acid
- After 20 minutes of nitration, 15 minutes were allowed for separation of the oil from the acid
- The separated oil was washed, first with water, then with soda ash soln and finally with water. The temperature during all the washings was maintained at 40° because at a low temp the mixture was too viscous. The soda ash wash lasted for 20 minutes. The yield was 200 parts MtrT per 100 p of Mtr
- The washed oil was taken to a storage tank from which it was withdrawn when needed for the preparation of "Rohpulvermasse" (Rawpaste) (q v).

German technical MtrT was a heavy oil, practically insol in water, with the following properties: N=16.00% to 16.32%, d 1.460 at 20° , stability by Abel test at 82° 20 mins, decomposition temperature ca 187° , impact sensitivity with a 2 kg hammer 4 cm, calorific value 1270 kcal/kg (water in liquid phase), volatility less than NG.

It was used in some smokeless propellants as an explosive plasticizer for NC in lieu of NG.

Reference: PB Rept 925 (1945), pp 15 & 61.

Miedziankit (Miedziankite). A type of chlorate explosives manufactured in Germany and Poland before WW II: a) K or Na chlorate 88-91 and liquid, hydrocarbons (with flash point not below 30°C) 12-9% (Ref 1); b) K chlorate 90 and petroleum 10%. The first mixture belonged to the group of Chloratites 3.

References:

- P. Naoum, *Shiess- und Sprengstoffe* (1927), p 131
- A. Stettbacher, *Spreng- und Schiessstoffe* (1948), p 91.

Mikroverzögerung beim Sprengen (Microdelay in Blasting) is described by Z. Peithner, *Explosivstoffe* 1954, Heft 5/6, pp 68-70.

Mine, Land. See Landminen.

Minenhund (Mine Dog), called by the Allies "Doodlebug" or "Goliath", was a miniature two-track tank operated by remote control through a 550 yd 3 strand cable which unwound from a drum on the tankette. Separate electric motors, each powered by its own storage battery, drove the two tracks of the tank at a speed up to 4 mph. Steering was done by braking the tracks. The tank contained about 250 kg HE demolition charge which the remote-control operator was supposed to touch off after stopping the vehicle at its target.

These mobile mines were not very effective because they could not move in reverse. On account of their low speed and thin armor, they were easily destroyed by the Allies' artillery.

Reference: Anon, *Field Artillery Journal* 34, 505 (1944).

Miniature Tornadoes. See Explosive Powered Vortices.

Mining Effect. See Earth-Displacement Test.

Mining Explosives. See Commercial Explosives.

Mipolam and Mipolam Sealing Plugs. Mipolams are plastic compositions developed in Germany during WW II and used in the prepn of seals for some delay detonators. Previous to WW II lead seals were used. The Mipolam sealing plugs were made in three types:

- Long greyish-green plug with a single hole
- Short greyish-green plug with two holes. The Mipolam was composed of polyvinyl chloride 50, tricresyl phosphate 30 and talcum 20%
- Short reddish plug with two holes. The Mipolam was composed of polyvinyl chloride 51, Special Mixture 31, and talcum 18%.

Note: The Special Mixture consisted of 2 parts tricresyl phosphate 2 pts Palatinol HC and 2 pts Palatinol K. The composition of Palatinol HC was not given, and the Palatinol K was butyleneglycolphthalate.

Mipolam was also used for covering the lead-in wires of electric detonators. The thickness of coating for 60 mm wires was only 0.25 mm on detonators not intended for underwater operations and 0.35 mm on those intended for such operations.

References:

- W. Krannich, *Kunststoffe im technischen Korrosionsschutz*, Lehmann, Berlin (1943), p 25
- BIOS Rept (Final), No 833, Item No 2, London (1946) or PB Rept No 63,877 (1946)
- PB Rept No 95,613 (1947), Sections II, I and J.

Note: According to M.F. Fogler et al, CIOS Rept 21-3 (1945), p 5 there were three types of Mipolam: a) Plasticized polyvinyl chloride b) Copolymers of polyvinyl chloride and acrylic esters and c) Polyvinyl chloride and malic esters.

Mischmetall (Mixed Metal) was an alloy of rare earths of the following approx compn: Ce 49.0, La 25.6, Nd 16.0, Pr 4.6, Sm 2.0, Tb 1.0, Y 1.0, and Fe 0.8%. It was used as a component of delay elements for electric blasting caps. Other ingredients of delay elements included: Mg, Al, Ni and Zn homogeneously mixed with a fuel such as Si and an oxidizing agent such as Pb_3O_4 .

Reference:

H.M. Kerr, C.R. Hall, *JSP* 2,560,452 (1951), C A 46, 1259 (1952).

Mischsatz (Mixed Charge). Designation for a mixture of lead azide and lead styphnate for use in detonators. (See also Sprengkapsel A und Sprengkapsel B).

Reference:

W. Schneider, *Sprengtechnik*, 1952, No 10/11, p 186.

Mittel AEP (Agent AEP). Trade name for Ethyl Ester of p-Toluenesulfonic Acid, $\text{H}_3\text{C}_6\text{H}_4\text{SO}_2\text{OC}_2\text{H}_5$; white crystals m p $31-32^\circ$. Its solution in organic media was claimed to be a good gelatinizer for NC.

Reference:

Kast-Metz, *Chemische Untersuchung*, Braunschweig (1944), p 161.

Mittel KP (Agent KP). Trade name for Cresyl Ester of p-Toluenesulfonic Acid, $H_3C.C_6H_4.SO_2OC_6H_4.CH_3$; brown oil d 1.20 at 15°. Its soln in organic media was claimed to be a good gelatinizer for NC.

Reference: Kast-Metz, *Chemische Untersuchung*, (1944) p 161.

Mollit I. German trade name for Centralit I.

Mollit II. German trade name for Centralit II.

Monachit (Monachite). According to Marshall (Ref 1) monachites were Tavier type explosives. According to Colver (Ref 2) these explosives were invented by Kast in Germany. Table 26 gives the composition of some monachites.

Table 26

| Designation | Am nitrate | K and/or Na nitrate | TNX | Collod cotton | Flour | Char coal | Alkali chloride |
|---------------|------------|---------------------|-----|---------------|-------|-----------|-----------------|
| Monachit I | 81 | 5 | 15 | - | 1 | - | - |
| Monachit II b | 64 | 3 | 14 | 1 | - | 1 | 17 |
| Monachit II d | 64 | 3 | 12 | 1 | - | 1 | 19 |

Abbreviation: TNX Trinitroxylen

According to Stettbacher (Ref 3), Monachit was an explosive suitable for loading projectiles and it was prepared by mixing ammonium nitrate with the solid and liquid products of nitration of solvent naphtha.

(See also Filler No 57, under Fillers).

References:

- 1) Marshall v 1 (1917), p 392
- 2) Colver (1918), pp 258 & 634
- 3) Stettbacher, *Schiess- und Sprengstoffe* (1933), p 270.

Monobel. See general section.

Mortar (Mörser). See under Weapons.

Mortar Bomb. See under Bombe.

Mortar Shell. See under Granate and under Spigot Mortar Projectile.

MP-14 (Solid Catalyst) used for decomposing the T-Stoff (hydrogen peroxide) of liquid rocket propellants.

Broken porcelain pieces, previously soaked in a 50% soln of Z-Stoff (qv) and dried at 110° for 24 hours, were cooked for 10 minutes in a 50% soln of 2 parts Calcium manganate and 1 part K chromate and then redried at 110° for 24 hours.

When generating steam from T-Stoff, copper coils were mixed with MP-14 in order to accelerate initial decomposition. The ratio of catalyst to copper was about 2 to 1.

Reference: CLOS Rept 30-115 (1945), p 11.


M-Stoff (commercial methyl alcohol, sp gr 0.796, used as a component of some liquid rocket fuels, such as C-Stoff (CLOS 30-115, p 10).

"Multipede". Same as Hochdruck Pumpe (High-Pressure Pump).

Munition. See Ammunition.

Mustard Pot Mine. See under Landminen.

Muzzle Charging Device, used for finer adjustment of the range of some electrical time fuzes, consisted of a cylinder which fitted around the barrel of a gun just behind the muzzle and was connected by means of an electrical cable to a battery and a voltage-control mechanism located at the breech end of the gun. A charging ring, located in front of the muzzle, was held by means of three arms placed 120° apart. These arms also served for conducting the electric current from the cylinder to the ring. When a projectile equipped with an electrical time fuze, such as the type S/30 (Elzetz S/30), reached the muzzle, the "feeler wire" (located on the outside of the fuze and connected to



its storage condenser) touched the charging ring for a short time. This resulted in the condenser of the fuze receiving an electrical charge called "vernier" charge which could range from -90 to +120 volts, depending on the voltage-control mechanism referred to above. The "vernier" charge was a supplementary charge to the initial charge of about 500 volts received by each electrical fuze prior to firing. If no vernier charge was applied, the time of burst was 16.0 seconds, but with the vernier charge the time could be adjusted between 3 to 30 seconds, depending on the voltage applied at the charging ring.

References:

- 1) Anon, Dept of the Army Tech Manual, TM 9-1985-3 (1953), pp 605-7
- 2) H. Bullock, Picatinny Arsenal; private communication.

Muzzle Flash Reduction in Propellants. See Flash Reduction in Propellants.

Myrol (Myrol). A liquid explosive consisting of a solution of methyl nitrate in methanol or other solvents. The term Myrol was also used to designate straight methyl nitrate. The material prep'd prior to WW II (by cautiously dropping methanol into a mixture of nitric and sulfuric acid) proved to be impure, unstable in storage and very sensitive to heat and shock. During WW II, Walter et al (Ref 2), developed a continuous method of manufacture of methyl nitrate from methanol and dilute nitric acid, which gave a pure and much more stable product than that prep'd previously. A detailed description of the method of preparation is given in Ref 2, pp 9-10. Pure methyl nitrate proved to be an explosive more powerful than NG, with a brisance exceeding any other high explosive known and with a sensitivity to shock comparable to that of PETN. Pure methyl nitrate is a clear mobile liquid with a bp of about 63° (145° F) and is insoluble in water.

Inasmuch as methyl nitrate is very sensitive to mechanical action, it was found much safer to use it in solution in methanol. Such solutions, called Myrol may be obtained directly in the process of manufacture of methyl nitrate, all that is necessary is to use an excess of methanol. One of the most suitable solns proved to be the azeotropic mixture consisting of about 75% methyl nitrate and 25% methanol. This mixture has a bp of 57.5°.

Myrols contg at least 25% methanol will not evaporate to leave hazardous 100% methyl nitrate.

Note: Römer (Ref 1) calls Myrol, the mixture consisting of 73% methyl nitrate and 27% of technical methanol containing 4% H₂O. Tschinkel (Ref 3) says that Myrol consisted of 80 weight percent methyl nitrate and 20 weight percent methanol.

Following are some properties of methyl nitrate-methanol mixtures: velocities of detonation ranging from 2400-4900 to 7500-8200 m/sec, volume of gases about 873 l/kg, heat

of explosion 1610-1700 kcal/kg, power and brisance-comparable to those of NG, sensitivity to shock-comparable to that of DNB, and toxicity-comparable to that of aliphatic nitrates, such as NG and PETN. Like NG Myrol causes headaches and pulse excitation, but they disappear more rapidly than with NG. Caffein or coffee proved most successful in decreasing pulse excitation.

References: See under Myrol Explosives.

Myrol Explosives. Methyl nitrate and its mixtures with methanol, benzene, nitrobenzene, etc found extensive application during WW II as ingredients of numerous liquid plastic and solid propellants and explosives. Some of these mixtures were known as Ersatzsprengstoff (substitute explosives).

In the case of liquid explosives or propellants, Myrol (methyl nitrate plus methanol) was used either by itself or in mixtures with other liquids, such as benzene, MNB etc. In some cases methanol was replaced completely by benzene, MNB etc. In the case of plastic explosives or propellants, Myrol was treated with small amounts of NC to form a soft jelly. In the case of solid explosives or propellants, Myrol was treated with a large amount (25-30%) of NC to form a hard jelly, or was mixed with the usual solid ingredients of dynamites, such as kieselguhr, sawdust, inorganic nitrates, lignin, etc.

Due to the fact that Myrol is a volatile liquid, all mixtures contg it had to be kept in air-tight containers.

Several Myrol manufacturing plants were built in Germany during the 2nd half of WW II and the total capacity was as high as 20,000 metric tons per month. The largest of these plants was the Christianstadt Fabrik of Dynamit AG. Its capacity was 400 tons/month.

Myrol explosives were used for the following purposes:

- 1) Liquid Myrol mixtures were used as rocket propellants, as charges for bangalore torpedoes, land mines, bombs, special fuzes and for clearing out trenches, foxholes, etc
- 2) Plastic Myrol mixtures were used as military demolition charges and mining explosives
- 3) Solid Myrol explosives were used as bursting charges in land mines, 50 kg projector mine, hand grenades, warheads of rockets V-1 and V-2, the bursting charge of Panzerfaust (A/T shaped charge), boosters, etc.

More detailed information on Myrol Explosives and their uses follow:


A) Liquid Myrol explosives could be used for military or commercial blasting operations. When used for destroying enemy installations, rocks, etc, Myrol could be poured directly into holes or cracks, thus avoiding boring of holes. If no holes or cracks were present, they could be easily produced by exploding small demolition charges (such as in tin cans or boxes) directly on the surface of a rock, concrete etc. When used for underground work, liquid Myrol could be placed in several boxes connected by pipes (also filled with Myrol) and one end of the train detonated.

B) Liquid Myrol explosives were found to be suitable for use in bangalore torpedoes

C) Liquid Myrol mixture, such as methyl nitrate 75-80 and methanol 20-25% was considered to be satisfactory as a liquid rocket fuel. Since the rate of propagation in this liquid is slow, there seems no danger that the combustion zone might run back from the combustion chamber to the supply tank. It was found that this mixture could not be exploded unless heated somewhere in the range of 200 to 300°

D) Liquid Myrol was found to be suitable for clearing out enemy trenches, foxholes, woods, etc. This clearing out operation was necessary sometimes in order to destroy mines, or other explosive or toxic devices left by the enemy. The following ingenious method, using Myrol in the form of vapor, was developed by the Germans:

A bomb provided with two fuzes, filled with Myrol and contg a small box with liquid carbon dioxide was dropped from a plane on the target. The impact of the bomb caused the first fuze to burst the box with CO₂ and to break the bomb. This caused the vaporization and distribution of the Myrol throughout the trench (or foxhole) without igniting or exploding it. The second fuze (time fuze) caused the detonation of the explosive mixture consisting of Myrol and atmospheric oxygen. With sufficiently strong initiation the following reaction has been postulated:



When using this bomb in cold weather, the vapor pressure of the mixture can be increased by incorporating a small amount of methyl nitrite, CH₃ONO

E) Liquid Myrol, or straight methyl (or ethyl) nitrate was used in the following device developed by Staudinger:

Two small glass ampoules (bulbs), one filled with methyl nitrate (or with less volatile ethyl nitrate), and the other with metallic sodium were placed inside a fuze close to an HE filler of a land mine, but separated from it by a thin sheet of plastic material. On top of the bulbs was placed a glass stopper. Pressure on the stopper caused crushing of the bulbs. This was followed by an explosive reaction between methyl (or ethyl) nitrate and sodium. As a result of this the sheet of plastic was pierced and the explosive charge inside the mine or bomb detonated. Based on this principle, several land mines were developed. The smallest and simplest land mine consisted of a flask containing 80-90 g of Myrol. Through the neck of the flask was inserted a test tube reaching nearly to the bottom of the flask. An ampoule containing metallic sodium was placed in the test tube and on top of it a long plunger was carefully inserted. The pressure of this plunger caused breakage of the ampoule in the test tube thus bringing sodium in contact with the Myrol. This action caused the detonation of the Myrol in the flask. The efficiency of these small mines was sufficient to disable a motor vehicle etc. Larger mines consisted of rectangular sheet-iron boxes filled with 2kg of 88/12-Methyl nitrate/MNB mixture and used the Myrol-sodium fuze

F) Liquid Myrol explosives were also used to increase the penetrating effect of shaped charges, such as of 40/60-TNT/RDX explosive. For this, a small glass ampoule (bulb) filled with 90/10-Methyl nitrate/MNB mixture was placed in the air space (stand-off space) between the concave surface of the shaped charge and the object to be pierced, such as armor, concrete, etc. For maximum effect the initiator (fuze) should be placed at the end of charge farthest from the target and pointing towards it. For instance, in shaped charge torpedoes, initiation of the explosive should be started from the tail end and not from the nose, as it is done in ordinary torpedoes

G) Soft jellied explosives could be obtained by incorporating 3 to 5% of NC in any of the Myrol explosives, as for instance, the ones containing MNB. These jellies could be also mixed with pulverized solids, such as sodium nitrate and/or cork powder, thus obtaining solid explosives. The solid mixtures were found suitable for filling the 50 kg projector mines. These mines exerted a strong blast effect

ii) The best propellants could be prepared by incorporating 70-90% Myrol (such as the ones contg. 75-80% of methyl nitrate and 20-25% of methanol, or MNM) comparatively large amount (20-30%) of nitrocellulose. Such mixtures formed very uniform, hard colloids without pores or cracks and for this reason were found to be suitable as solid rocket propellants. It is believed that some of these mixtures were used toward the end of WW II as a fuel for V-1 and V-2 rockets.

Because of high volatility of Myrol, the propellant sticks used in rockets had to be coated with a special material impermeable to Myrol.

D) A hard yellow explosive prepd by gelatinizing NC with a mixture of 91-95% methyl nitrate and 5-9% of MNB, was used in some boosters.

D) A solid, highly brisant, explosive consisting of 30 to 40% of 75-25 Myrol mixed with such amounts of hydrated Ca nitrate and lignin that the oxygen balance was equal approximately to zero. The mixture was found suitable for filling bombs and land mines.

a) The high brisance and fairly high sensitivity to shock of the last mixture was presumed to be due to the fact that Ca nitrate extracted and bound some methanol of the mixture, thus leaving part of methyl nitrate as free sensitive droplets. Another explanation of free methyl nitrate was partial evaporation of methanol, which is more volatile than methyl nitrate. According to Dr H. Walter, Myrols vaporize in the form of azeotropic mixtures contg about 25% methanol.

b) In order to prevent an excessive liberation of free methyl nitrate, it was proposed to use a solvent less volatile than methanol such as benzene or nitrobenzene. In order to prepare such a mixture, the regular Myrol, which is a mixture of 75% methyl nitrate and 25% methanol, was shaken with benzene or MNB in presence of some water. This caused the methanol to go into the aqueous layer, while methyl nitrate remained mixed with benzene or MNB.

K) A solid explosive contg 30% of a mixture consisting of 90 parts of methyl nitrate and 10 pts of benzene, plus 55% of hydrated Ca nitrate, 10% of finely pulverized aluminum and 5% of pulverized peat, had an oxygen balance equal approximately to zero. It was highly brisant and powerful, although its nitrogen content was much lower than that of TNT (14.2% vs 18.5% for TNT). This mixture was proposed as a filler for warheads in rockets V-1 and V-2.

Note: Mixtures of methyl nitrate 90% with benzene 10%, do not undergo any significant change in composition in storage. The composition of Myrol mixtures may be easily and rapidly determined by checking its refractive index.

L) A solid Myrol explosive consisting of 85/15 Methyl nitrate/MNB gelatinized with NC and mixed with sawdust and hydrated Ca nitrate was suitable for use in hand grenades or in mining.


M) A solid brisant explosive consisting of Myrol and a pulverized mixture of K nitrate, aluminum, and peat was suitable for hand grenades, land mines, and rock blasting.

- References:
- 1) G. Römer, Report on Explosives, PBL Rept 85,160 (1945)
 - 2) H. Walter et al, German Development in High Explosives, PB Rept 78,271 (1947)
 - 3) J. G. Tschinkel, Chem Eng News 32, 2586 (1954) (Propellants for Rockets and Space Ships)

"Nashorn" (Rhino). A self-propelled mount formerly known as the "Homisse" consisting of an 88 mm A/T gun on a PzJäg III/IV or on a modified PzKpfw IV (See also under Panzer).

Natter Ba 349A. A surface-to-air, piloted missile developed in 1944 at the Bachem Werke GmbH. It was propelled by hydrogen peroxide/methanol + hydrazine hydrate and carried 34 R4M rocket projectiles in its nose. Launching weight 4800 lb, overall length 21.25 ft, width 36.0", max range 24.8 miles and max altitude 49,400 ft. It took off from a vertical ramp and climbed at a velocity of 35,800 ft/min.

Reference: K.W. Gatland, Development of the Guided Missiles, "Flight" Publication, London (1952), pp 10 & 114-15.



Natter Ba 349B. A surface-to-air, piloted missile developed in 1945 at the Bachem Werke GmbH. It was propelled by hydrogen peroxide/methanol + hydrazine hydrate and carried in its nose 24 RZ 73 Föhn (qv) rocket projectiles. Launching weight 4,925 lbs, overall length 20.6 ft, width 36.0", and max altitude 50,000 ft. It was launched vertically and controlled by a radio link to the pilot in conjunction with ground radar.

Reference: K.W. Gatland, Development of the Guided Missile, "Flight" Publication, London (1952) pp 114-5.

Nebelsäure (Fog Acid) is a smoke-screen agent consisting of 50/50 - Chlorosulfonic acid/Sulfur trioxide (by weight) Reference: R.E. Richardson et al, CIOS Rept 25-18 (1945), p 6.

Nebelwerfer 41. See under Rocket Launchers.

Nebenschlusszunder (Shunt-Circuit Igniter) is described in the book by Beyling-Drekopf (1936), p 216.

Needle Point Projectile. See Arrowhead Projectile.

Needle Projectile. See Arrow Projectile and also Gessner Projectile.

Neorodit. The name given after WW I to explosives used for rock blasting, up-rooting stumps, etc. These explosives were prepared from a surplus military explosive called Hexamin, which consisted of Hexamin (hexanitrodiphenylamine) 60-70 and TNT 40-30%.

Reference: P. Naoum, Schiess- und Sprengstoffe, Dresden (1927), p 71.

Neudahmit (New Dahmenite). One of the earlier permissible mining explosives: Am nitrate 68, TNT 10, flour 2.5, K nitrate 2.0, Na chloride 15.5, and coke dust 2.0% (Colver, (1918) p 249).

Neudynamit Austrian name for Gelatin Dynamite.

Neunkirchen Testing Gallery (Schlagwetter-Versuchsstrecke in Neunkirchen). See general section under Galleries, Testing and A. Stettbacher, Schiess- und Sprengstoffe, p 248.

Neu-Nobelit (New Nobelite). A class of permissible explosives used before and after WW I. Table 27 gives some examples.

Table 27

| Composition (%) and some properties | New-Nobelites | | | | | |
|---|---------------|------|------|------|----------|------|
| | 1 | 12 | 14 | 15 | 16 | C |
| Am nitrate | 27.0 | 36.0 | 30.5 | 54.0 | 54.0 | 50.0 |
| NG + NC jelly | 26.0 | 30.0 | 30.0 | 12.0 | 12.0 | 12.0 |
| Glycerin | - | - | - | - | - | 4.0 |
| Gum-sugar | - | 3.5 | - | - | - | - |
| Cereal meal | 9.0 | - | 6.4 | - | - | 6.0 |
| Wood meal | 1.0 | - | - | 4.0 | 3.0 | - |
| Nitrocompounds | - | - | - | 2.0 | 3.0 | - |
| Na nitrate | - | - | - | - | - | 3.0 |
| Alkali chloride | 29.0 | 30.5 | 33.1 | 28.0 | 28.0 | 20.0 |
| DNT | 8.0 | - | - | - | - | - |
| Talc | - | - | - | - | - | 5.0 |
| Oxygen Balance, % | -14.9 | +4.6 | -1.6 | +0.6 | +2.8 | -0.6 |
| Trauzl Test, cc | 230 | 220 | 230 | 225 | 225 | 220 |
| Pb Block Crushing, mm | - | - | - | - | 13.0 | - |
| Velocity of Detonation, m/sec | - | - | - | - | 4600 | - |
| Density of Cartridge | - | - | - | - | 1.20 | - |
| Sensitiveness to Initiation. Requires at least: | - | - | - | - | No 1 cap | - |
| Gap Test, cm | - | - | - | - | 25 | - |
| Heat of Explosion, kcal/kg | - | - | - | - | 643 | - |

(See also Nobelit).

Reference:

P. Naoum, Nitroglycerin, etc, Baltimore (1928), pp 411, 441 and 444.

Neuwesfalit (New Westphalite) One of the permissible explosives used after WW I: Am nitrate 70.3, DNT 10.9, flour 2.0, and Na chloride 16.8%; Trauzl Test 309 cc. References:

1) Marshall, v 1 (1917), p 391 2) Barnett (1919), p 138.

Nigu. German abbreviation for Nitroguanidin, also called "G-Salz". Abbreviation used in this book is NGu.

Nipolit. Nipolite. A type of NC-DEGDN-PETN propellant or explosive, developed during WW II at the Kraiburg plant of the Deutsche Sprengchemie GmbH. The following compositions are listed in Refs 2, 3 & 4 (See Table 27a).

TABLE 27a

| Composition (%) and dimensions | Nipolit tubes | Nipolit Sticks |
|--------------------------------|---------------|----------------|
| NC(12.6-12.7% N) | 34.1 | 29.1 |
| DEGDN | 30.0 | 20.0 |
| PETN (unwaxed) | 35.0 | 50.0 |
| Stabilizer | 0.75 | 0.75 |
| MgO | 0.05 | 0.05 |
| Graphite | 0.1 | 0.1 |
| Length of grain | 80 mm | 50 mm |
| Diameter of grain | 27 mm | 21 mm |
| Hole Diameter | 9.1 mm | - |
| Hole Depth | 30 mm | - |
| Weight of grain | 42 g | - |
| Calorific value, cal/g | 1300 | - |

Note: MgO was added to neutralize acid developed on decomposition, and graphite was added to prevent the accumulation of hazardous static electrical charges.

For the preparation of Nipolit, a water slurry of NC was air-agitated in a lead-lined vessel, with the desired amount of DEGDN. After 15-20 minutes stirring, the mass was centrifuged to remove all but about 25% of water and the resulting cake was kneaded, at about 50°C, in a Werner-Pfleiderer machine with the calculated amount of pulverized PETN, some water, stabilizer, MgO and graphite. After about 15 minutes of kneading the mass (paste) was transferred to rubber lined bags where it was allowed to age for 48-72 hours.

Notes:

a) According to Ref 4, all raw materials with the exception of PETN were added in the paste mixing stage, while PETN was added during incorporation.

b) It was claimed that the aging process insured better gelatinization and reduced the tendency to fire during the rolling operation which followed.

c) The calorific value of the materials was carefully adjusted to between +30 and -10 calories as permissible variation from specification value for the propellant being processed. If outside these limits, the material was returned to the mixers and the calorific value either reduced by adding centralite or hydrocellulose or increased by adding wet paste consisting of NC and DEGDN. Each mixer was sampled at least every 8 hours. For a total charge of 18 kg a maximum of 3 kg of rework material was permitted.

Rolling and granulation were carried out as follows:

About 18 kg of the aged paste was passed, about 15-20 times, through a pair of vertical rolls maintained at 90-100° (Ref 3).

Note: According to Ref 4, rolling was conducted at a temperature not higher than 75°C.

The resulting sheet (moisture content about 3%), was made by hand into a carpet roll and transferred to the press-house where it was kept in a steam heated oven, prior to transfer to the extrusion press. Then the mass was extruded at a pressure of 200 kg/cm² and at a temperature of about 80° and the resulting tubes (or sticks) cut into desired lengths.

After drying the cut material for about 24 hours at 40-50°, the moisture content was reduced to about 1%.

The next operation consisted of wetting each stick of Nipolit with acetone and pushing the stick into a tube of Nipolit flush with one end. This left a cavity 30 mm long in each tube to accommodate a detonator. The stick Nipolit (core) acted as a booster.

References:

- 1) O.W. Stickland et al, PB Report 1820 (1945), p 3P
- 2) A.A. Swanson & D.D. Sager. CIOS Report 29-24 (about 1946), pp 3-4
- 3) T. Urbanski, Przemysł Chemiczny 27(4), 487-94 (1948) C A 43, 4465 (1949) "Recent Development in the Field of Explosives" (Translated by Dr Ivan Simon of Arthur D. Little Inc.)
- 4) A.A. Swanson, D.D. Sager & L.M. Sheldon, Ordnance Target Report No 88 (Spec Rept No 2071), Manufacture of Solventless Type Powder and Nipolit by the Deutsche Sprengchemie, Kraiburg Wks.

Nitric Acid (Salpetersäure). Its preparation, properties and uses are described in the general section. Nitric acid was produced in Germany during WW II, mostly by the ammonia oxidation process, in quantities exceeding 140,000 tons per year. In addition, there was also available the 17,000 tons produced in occupied Austria, Czechoslovakia and Poland.

For the manufacture of highly concentrated (hochkonzentrierte) nitric acid, the so-called "Hoko" (qv) process was developed.

Production of nitric acid in Germany was controlled by the Stickstoff-Syndikat.

Following is a partial list of the principal producers of nitric acid in the Western Zone of Germany:

- a) Badische Anilin- und Sodafabrik A-G, Oppau (formerly IG Farbenind A-G)
 - b) Bergwerksgesellschaft Hibernia, A-G, Herne, Stickstoffwerke, Wanne-Eickel
 - c) Chemische Fabrik Kalk GmbH, Köln-Kalk (Founded in 1857)
 - d) Elektro-Nitrum A-G, Rhina, bei Laufenburg (Haden)
 - e) Farbwerke Höchst, bei Frankfurt a/Main (formerly IG Farbenind A-G)
 - f) Gewerkschaft, Victor Chemische Werke, Castrop-Kauxel 2, Westfalen
 - g) IG Farbenindustrie A-G with plants at Leverkusen (formerly Fried Bayer & Co), Bochum-Gerthe, Ruhr (later called Chemische Werke Lothringen GmbH) (was founded in 1916) and Herne-Sodingen, Ruhr (formerly GAVF(G))
 - h) Ruhrchemie A-G, Oberhausen-Holten, Ruhr (founded in 1927 under the name of Kohlenchemie A-G)
 - i) Wirtschaftliche Forschungs GmbH (WIFO) with plants at Embsen, Kr Lüneburg (founded in 1939-1940) and at Langelsheim, Harz (founded in 1939).
- According to Ref 3 the following plants in the Eastern Zone were dismantled and shipped to Poland or Russia:
- j) Christianstadt a/d Hober, Brandenburg (Dynamit A-G)
 - k) Bitterfeld South (described in Ref 1)
 - l) Döberitz
 - m) Heydebreck
 - n) Lanna
 - o) Piesteritz (Bayerische Stickstoff A-G)
 - p) Sonderhausen
 - r) Wolfen (described in Ref 1)

References:

- 1) R.J.Morley, BIOS Final Rept 889, Item 22 (1946)
- 2) W.Kenworthy & F.R.Dell, BIOS Final Rept 1232, Items 22 & 31 (1946)
- 3) F.M.Irvine et al, BIOS Final Rept 1442, Item 22 (1946).

Nitrobaronit (Nitrobaronite). An early type of aluminized explosive. The following mixtures, described by L.Médard, Mém Artil Fr 22, 596 (1948) are given in Table 28.

Table 28

| Composition (%) and some properties | Nitrobaronite A | Nitrobaronite B |
|--|-----------------|-----------------|
| Aluminum | 5.0 | 2.0 |
| Am nitrate | 82.0 | 69.0 |
| Nitroglycerin | 5.0 | 22.0 |
| Collodion cotton | - | 0.75 |
| Liquid DNT | 5.0 | 3.0 |
| Petroleum tar | 1.5 | 2.0 |
| Wood meal | 1.5 | 1.25 |
| Pb Block Expansion (Picric acid = 100) (See "C u p" in the French Section) | 124.0 | 125.5 |

Nitrocellulose, Nitrozellulose oder Schiessbaumwolle, abbreviated in German to Nz (Nitrocellulose, abbreviated in this work to NC). See general section under Cellulose.

Due to the absence of native cotton in Germany, their nitrocellulose was prepared from wood pulp.

Following is a brief description of the method used during WW II at the Krümmel Fabrik of DA-G, as given in Refs 1 & 2:

- a) Bleached cellulose in the form of crêpe paper (made from wood pulp), was broken down in special machines into flocks and then blown into large drying chambers where the moisture content was reduced from 6-7% to 1-2%.
- b) 25 kg of cellulose flocks were fed with stirring into a nitrator of 0.7 m³ capacity containing 1125 kg of mixed acid (MA), prep'd by fortifying the spent acid (SA) from previous batches.

Note: For NC of 11.25-11.50% N, called PE-Wolle, the MA consisted of 20% nitric, 62-64% sulfuric and 16-18% water; for NC of 13.2-13.3% N called Schiesswolle, the composition of MA was 22.5% nitric, 67.5-68.5% sulfuric and 9-10% water. The time of nitration was 30 minutes and the temperature 30°.

- c) The contents of the nitrator were emptied into a centrifuge (one for every 4 nitrators) and spun for 6 minutes at 900 rpm.
- d) The separated spent acid (SA) went to rotating filter drums where the small torn particles of NC were separated and then to the fortifier.
- e) The NC which was removed from the centrifuges and the filters was carried by a stream of water into pre-washers where the bulk of the acid was removed by stirring with water.
- f) The slurry was then pumped to a preliminary boiling vessel provided with a double bottom of which the upper one was false, consisting of a screen through which the wash water was allowed to flow off at the end of the boiling period. Boiling was carried out at atmospheric pressure: 3 hours for PE-Wolle and 6-8 hours for Schiesswolle.
- g) After removing the acid water, the NC was carried by a stream of water into the pressure boiling plant, where the material was cooked for 6 minutes in stainless steel autoclaves, starting at 100° and finishing at 142-145°.

Note: Pressure cooking had a double purpose: it reduced the viscosity of NC, to the desired level and it speeded up the stabilization. The details of the pressure cooking varied from plant to plant.

- h) A sample of cooked NC was sent to the laboratory and if the viscosity of the NC (as det'd by the Höppler method in a 3% acetic soln) was within the desired range, the charge was dropped into a pulping machine such as the Hollander or Banning-Seybold. Here the NC was beaten for several hours, while the pH of the slurry was maintained between 7 and 9 by adding soda periodically. It usually required 3 to 4 kg of soda.
- i) The pulped NC plus water was pumped into vertical rotating sieves where more water was added. Here the smaller particles of NC passed through a 0.4 mm sieve while the latter particles were retained by it. Then the larger particles were removed by scrapers to be repulped, while the slurry of smaller particles went to a dewatering device (rotating drum sieve).
- j) The dewatered small-particle material was transferred

to a final stabilizer consisting of a cylindrical vessel where the NC was treated with live steam until the slurry was brought to a boil. Then the water was decanted, the NC washed with water and a sample sent to the laboratory. In case of collodion cotton (PE-Wolle), the above treatment was usually sufficient and the material would pass the Bergmann-Junk Test (Heating for 2 hours at 132° C should not produce more than 2 ml of NO per 1 g of PE-Wolle)

k) If the material was guncotton (Schiesswolle) the above treatment was not sufficient and heating had to be continued until a satisfactory B-J Test value was obtained (Not more than 2.5 cc NO per 1 g of Schiesswolle)

l) In order to obtain NC of the desired N content and viscosity, several batches were blended in large vats provided with stirrers. The blended material was then stirred with a large quantity of water and run through grit traps.

Note: Grit traps were round vessels, conical at the base. The slurry entered from below and its velocity decreased as it flowed upward (due to the increase in diameter of the vessel) to such an extent that all the heavier particles (such as grit or dirt) dropped to the lower part of the vessel while the particles of NC continued to travel upward

m) After "de-gritting", the slurry was thickened up by passing it through a dewatering rotating drum for final dewatering. The partly dewatered material was sent to a centrifuge where it was spun at 1000 rpm

n) The resulting NC was shovelled into a zinc-lined iron container (provided with a cover), where it was weighed, labelled and dispatched either to propellant plants or to a plant manufacturing "Rohpulvermasse" (Raw Paste)

o) As the waste waters from the manufacture of NC contained an appreciable amount of suspended small particles of NC, it was required that these particles be removed before the water was allowed to leave the plant site. One method was to allow the water to run through so-called Dunsch traps. These were conical vessels with the narrow part at the bottom. The water flowed from the bottom upward; as the area of the vessel increased, the velocity of flow was reduced to such an extent that the suspended particles settled. The accumulated fines were periodically removed from the vessel.

Note: In many German propellants that were examined at Picatinny Arsenal during WW II, the nitrogen content of the NC was around 12±0.2%, which means that the NC was intermediate between the PE-Wolle and Schiesswolle. One of the DEGIN propellants contained NC with N=10.3% (See under Propellants).

Stettbacher (Ref 3) describes briefly various methods of manufacture of NC and gives compositions of mixed acids used for the preparation of NC with nitrogen contents of 11.6, 12.5, 12.75, 13.2, 13.4 and 13.7%. Yields and solubilities of various nitrocelluloses in 3/1-ether/alcohol mixture are also given.


References:

- 1) O.W. Stickland et al, General Summary of Explosives Plants, PB Rept 925 (1945), pp 50-55
- 2) Lee Nutting et al, Manufacture of NC at the Krümmel Plant of the Dynamit A-G, PB Rept 16,666 (1945)
- 3) A. Stettbacher, Spreng- und Schiessstoffe, Rascher, Zürich (1948) pp 62-66.

Nitrocellulosepulver (Nitrocellulose Propellant or Single-Base Propellant). See under Propellant.

Nitrochlorin. A low-freezing explosive oil used in the manufacture of some dynamites. It consisted of 40% dinitrochlorohydrin and 20% NG and was prepared by nitration of commercial monochlorohydrin containing glycerin. P. Naoum, Schiess- und Sprengstoffe (1927), p 113.

Nitroform or Trinitromethane, described in the general section, was prepared and investigated during WW II in Germany by Dr Schimmelschmidt. He recommended the preparation of nitroform from tetranitromethane, potassium hydroxide and hydrogen peroxide, according to the following reaction:



His preference for the above method was based on the claim that the method previously suggested by Otton and McKee, depending on the reaction between tetranitromethane, K hydroxide and hydrazine, is hazardous since, in addition to K salt of nitroform, hydrazoic acid and not nitrogen (as was previously believed), is formed.


Nitroform was liberated from its K salt by distillation at reduced pressure in the presence of sulfuric acid. The resulting product had a m.p. of 26.4° as against 22° obtained by some previous investigators.

Dr Schimmelschmidt also found that nitroform may be extracted from the reaction product of acetylene and nitric acid using liquid nitrogen dioxide at 0° as a solvent. This method of nitroform recovery was considered to be of great importance, since the product so obtained could be converted to tetranitromethane using only a small amount of sulfuric acid (See also under Tetranitromethane). Note: Due to the shortage of sulfuric acid, which developed in Germany during WW II, any substance which could be used in place of sulfuric acid was considered highly desirable. For this reason, the use of liquid nitrogen dioxide was proposed also for the extraction of other nitrocompounds, in addition to nitroform.

Nitroform was found to be an excellent rust inhibitor when incorporated in polyvinyl acetate emulsions and also was found to be superior to Na nitrite in that it did not destroy the emulsion.


In the course of the investigation of the reactions between nitroform and organic compounds Dr Schimmelschmidt obtained several substances which were highly explosive, as for instance:

a) On treating nitroform with vinyl-methyl ketone, the following reaction took place:




The resulting Trinitropropylmethyl ketone was an explosive comparable in power to RDX

b) When a stream of acetylene was bubbled through nitroform containing a little mercuric nitrate the following reaction took place:



Interaction of this compound with nitroform gave an extremely powerful explosive, believed to be a mixture of 1,4 Di(trinitro)butane and Hexanitrosobutane:



c) Reaction of nitroform with formaldehyde gave Trinitroethanol:



Reference: W. Hunter, BIOS Final Rept 709 (1946), pp 2 & 6-10.

Nitrogelatine picrique. Under this title J. Daniel, Dictionnaire des Matières Explosives, Paris (1902), p 523 described an explosive, consisting of NG+NC jelly mixed with about 10% of picric acid. This mixture, patented in 1887 by the Deutsche Sprengstoff Gesellschaft of Hamburg, did not prove to be very stable.

Nitroglycerin und Nitroglykol (Nitroglycerin and Nitroglycol, abbreviated in this work to NG and NGc). The manufacture and properties of these substances are described in the general section under Glycerin and Glycol, respectively.

In Germany the nitration of glycerin or of glycol (ethyleneglycol) was conducted either by a batch process or by a continuous method, such as that of Schmid, Meissner or Biazzi. The nitration was made either separately for glycerin and glycol, or more often as mixtures, such as glycerin 60 and glycol 40%.

The batch method of nitration of glycerin, or of glycol or of their mixtures at the Krümmel Fabrik Dynamit A-G may be given as an example:

- a) 300 kg of glycerin was run into 1470 kg of mixed acid, consisting of HNO_3 50, H_2SO_4 52 and H_2O -2%, contained in a stainless steel nitrator which was provided with an air stirrer and cooling coils
- b) In order to maintain the mixture in the nitrator at about room temperature, the brine, cooled to as low as -12° was circulated through coils
- c) After about 25 minutes of nitration, the air agitation was stopped and the mixture allowed to stand. In order to accelerate the separation of the nitration products, 70 g of an 80/20 mixture of Na flouride and of ignited kieselguhr was added
- d) The separated oil was air-stirred at 12° with 400 liters of water and after removal of the water, the oil was air-stirred for 12 minutes at 40° with 500 l of 2% soda ash solution
- e) After cooling the mixture to 28° , while still continuing to stir, 50 g of pulverized talc was added and then the mass was allowed to stand
- f) The separated oil was run through a pipe which ended some distance short of the storage tank. From that end of the pipe, the oil was transported to the tank by means of hand trucks
- g) The spent acid, which in the case of NG weighed about 1200 kg and had the approx compn: HNO_3 7.5, H_2SO_4 75 and H_2O 17.5%; and in the case of NGc (nitroglycol) weighed about 1030 kg and had the approx compn: HNO_3 8.5, H_2SO_4 74.5 and H_2O 17%, from which the bulk of oil had been removed, was allowed to stand for several days in lead-lined vessels, called "After-Separators". The separated oil was washed in a small auxiliary vessel first with water and then with 2% soda ash solution.

Note: The total yield of oil was reported to be about 233 parts per 100 of glycerin. Other plants reported yields ranging from 231 to 234, and for NGc 230.

- h) The spent acid of (g), was blown by compressed air to a tank and from there to a separator in order to recover some more of the explosive oil. Then the acid was transferred to the Recovery Plant where the nitric acid was distilled off, leaving weak sulfuric acid as a residue
- i) As the waste wash waters of operations (d) and (g) contained small amounts of oils (NG, or NGc) it was necessary to remove the oils before allowing the waters to run into a stream, lake, etc. This was accomplished by allowing the waters to run through large settling tanks, sometimes installed in cascade form
- j) In order to economize on the consumption of nitric acid and to prevent poisoning of personnel all nitric acid fumes (as well as nitrogen oxide gases) were drawn from both the nitrator and separator by means

of a suction device and led to an absorption tower in which they were met by a spray of water to dissolve them and form nitric and nitrous acids

k) A sample of washed oil [see operations (d) and (g)] was sent to the laboratory for testing. The Abel test at 82° was usually about 40 minutes.

Note: The results of the Abel Test were usually higher than in the US practice. The high German results are presumably due to the fact that talcum was used in the separation of the oil [see operation (e)]. The Americans do not use talcum to improve the separation of NG or of NGc from spent acids.

The Sythen Fabrik of W A S A -G also used the batch process, while the Schlebusch Fabrik of Dynamit A-G had three different NG installations:

- a) Batch plant
- b) Continuous plant with Meissner nitrator and Biazzi separators and washers
- c) Continuous plant with Biazzi nitrator, separators and washers, installed by Mario Biazzi, Switzerland.

In the Biazzi installation, which had an output of 800 to 1000 kg per hour, the nitrator was a cylindrical stainless steel vessel approximately 2 ft in diameter by 8 ft 6 in deep (See Fig 1, p A2/9 of Ref 5). Cooling was carried out by running chilled brine through a series of six concentric coils suspended inside the nitrating vessel. Stirring was carried out with a mechanical stirrer situated in the center of the inner cooling coil and running at about 400 rpm. A tangential separator was placed about 2 ft below the level of the outlet of the nitrator and a 2nd separator followed the 1st. The mixed acid used in the nitration was approximately 50/50-nitric acid/sulfuric acid, stored in a tank for at least 10 days and then passed through a stainless steel gauze before use.

Procedure:

- a) The mixed acid, 5 parts, and glycerin (or glycol, or glycerin plus glycol) 1 part, each metered by means of a rotameter, entered continuously and simultaneously, the lower part of the nitrator
- b) The emulsion consisting of nitrated product (oil) and spent acid left the nitrator and was run straight to a tangential separator placed about 2 ft below the level of the outlet from the nitrator
- c) The separated acidic oil went to a stainless steel vessel $1\frac{1}{2}$ ft in diameter and 2 ft deep, provided with a mechanical stirrer, where the oil was washed with an equal volume of water, while the spent acid (which in case of NG, had the approximate composition: HNO_3 11, H_2SO_4 73.5, H_2O 14 and NG 1.5%) went to a special lead separator, called Scheider. This operation permitted the removal of some additional oil before the acid was fortified to be reused for nitration of the next bath, or before the acid was sent to the recovery plant
- d) After pre-washing the oil with water, the emulsion flowed continuously into a tangential separator from which the separated oil went to the next part of the process
- e) The acidic water (which in the case of NG had the approximate composition: HNO_3 10.6, H_2SO_4 1.1, H_2O 87.6 and NG 0.7%) went to another separator outside a mound surrounding the nitrating house where some oil was recovered
- f) The pre-washed oil of the operation (d) went through two vessels in series, each of them equipped with a stirrer. Simultaneously with the oil a 15% soda ash

solution, measured by a rotameter, entered the vessels. There was no separation of the emulsion between these vessels, and the oil/soda emulsion went from them to an annex (wash-house), located outside the mound surrounding the nitrating house.

Note: All the above listed operations were conducted in the nitrating house. It should be mentioned that the nitrator was provided on the bottom with a glass plate which could be broken when it was required to drown a charge. A pneumatic hammer operated by a handle at the door of the building was used for breaking the glass. The drowning tank, located below the nitrator, contained about 5 times the volume of the nitrator of 95% sulfuric acid.

g) The emulsion from the previous operation went through two separators located in the wash house. The separator oil was collected in a rubber lined aluminum truck, holding 600 kg, while the wash waters went via a cascade system to a tunnel leading to the Rhine River.

h) The truck containing neutralized oil was emptied into a storage tank where it was allowed to stay for at least one day to permit the water to separate.

Note: In a newer type of final settling house, there were 6 Biazzi tangential lead separators placed in cascade and working continuously.

i) The dried oil was removed from the storage tank, as needed, by means of heavy rubber buckets of capacity.

The average yield of dry NG from the Biazzi plant was 232 parts by weight per 100 pts of dry glycerol. The stability was 14 minutes by the Abel Test at 81°. When the nitrating acid was made from acids recovered from TNT manufacture, it was sometimes necessary (in order to obtain satisfactory stability for NG) to include from 0.1 to 0.2% of Na sulfite in the soda washing liquor. During the war, however, diphenylamine stabilizers were sometimes used when the quality of the NG was unsatisfactory.

In the manufacture of double-base propellants, NG was used alone, while in the manufacture of commercial dynamite-type explosives it was used in mixtures with NGc (nitroglycol).

References:

- 1) R. Escales, Nitroglycerin und Dynamit, Veit, Leipzig (1908)
- 2) P. Naoum Nitroglycerin and Nitroglycerin Explosives, Williams & Wilkins, Baltimore, 1928 pp 25-178 & 210-239
- 3) A. Stettbacher, Schiess- und Sprengstoffe, Barth, Leipzig, (1933), pp 146-172
- 4) O.W. Stickland et al, General Summary of Explosive Plants, PB Rept 925 (1945), pp 67-8
- 5) R. Ashcroft et al, Investigation of German Commercial Explosives, B I O S, Final Rept 833, Item 3, HMSO, London (1946), pp A 1/4 and A 2/4
- 6) A. Stettbacher, Spreng- und Schiessstoffe, Zürich, (1948), pp 59-62.

Nitroglycerin-Nitrocellulose Explosives. Commercial explosives suitable for blasting rocks were prepared by mixing double-base propellants (left as surplus after the termination of WW I) with other ingredients, such as inorganic nitrates and organic nitrocompounds.

Following are the compositions of some of these explosives:

- a) Mining List No 33 Explosive: NG 30 to 40, NC 60 to 70, with added 0 to 5% of nitroderivatives of toluene (and/or naphthalene) and 0 to 10% of paraffin (and/or urethane, and/or centralite, and/or dicyandiamide)

- b) Mining List No 35 Explosive: NG+NC jelly 94 to 96 and 4 to 6% of a 50% aqueous solution of Ca nitrate
- c) Mining List No 36 Explosive: NG+NC jelly 97 to 99, and 1 to 3% of substituted urethanes.

References:

- 1) P. Naoum, Nitroglycerin etc, Baltimore (1928), pp 449-50
- 2) J. Pepin Lehalleur, Poudres, etc, Paris (1935), p 458.

Nitroglycerinsprengstoff (Nitroglycerin Explosive). See Dynamit.

Nitroglycerinpulver (Nitroglycerin Propellant). A propellant based on NC and NG, also called double-base propellant. Prep'n and properties of typical NG propellants are given in the book of A. Stettbacher, Spreng- und Schiessstoffe, Zürich (1948), pp 41-43

See also under Propellants.

Nitroglykol (Nitroglycol), abbreviated in this book to NGc is described in the general section under Glycol. The manufacture of NGc in Germany was conducted in the same manner as for NG. Because of high volatility, it is not advisable to use NGc alone in explosive compositions (although the Germans sometimes did), but it is satisfactory to add NGc to NG in order to depress the freezing point of the latter. Such mixtures were used extensively in the preparation of commercial dynamite-type explosives. References: Same as under Nitroglycerin.

Nitroguanidin (NGu) [Nitroguanidine (NGu)], described in the general section under Guanidine was prep'd in Germany by treating guanidine nitrate (GuN) with conc'd sulfuric acid as described by Schnurr (Ref 4).

Briefly, the method was as follows:

In order to obtain 100 kg of NGu, 135 kg of GuN was added gradually to 300 kg of 98% sulfuric acid while stirring and cooling so that the temperature was not allowed to go above 45°. The resulting mixture was run into a dilution vessel (maintained at 0°) in which the precipitation of the crude NGu took place. By using a centrifuge, the crude product was separated from the liquid phase which contained about 20% H₂SO₄. The crude material was dissolved in boiling water, mixed with the mother liquor from the previous batch (see below), made exactly neutral by means of ammonia, filtered and the filtrate cooled to at least 45° at low pressure. The resulting crystalline suspension was transferred by air pressure to a centrifuge. This gave purified NGu with a water content of about 6% and a mother liquor which was later used for dissolving the crude NGu of the next batch (see above) (Ref 4).

The preparation of NGu was also described by Stettbacher (Ref 1).

Uses of NGu:

A) According to Davis (Ref 2), NGu in admixture with Am nitrate and wax or paraffin was used during WW I for loading various bombs. These compositions were fairly insensitive to shock

B) During WW II NGu was used either in propellants such as the cool, erosionless and flashless triple-base propellant, called Gudolpulver, or in explosive compositions.

Note: When intended for use in propellants, the NGu crystals were required to be of such size and shape that when the ingredients of a propellant were rolled into sheets, the

incorporation was smooth and rapid. When intended for use in explosives, two kinds of NGu crystals were used: a) finest grain crystals (dust) obtained by rapidly evaporating a hot aqueous solution of NGu under high vacuum. These crystals were found to be suitable for press-loading b) crystals with high bulk density (above 1.0), obtained by crystallizing NGu in the presence of colloids. Such crystals were found to be suitable for the cast-loading of TNT-NGu mixtures.

C) As an example of the uses of NGu as a high explosive may be cited the 1800 kg AP bomb in which some NGu was placed in the nose as a sort of protection (bumper) for the more sensitive main charge consisting of "Filler 109".

Note: According to CIOS Rept 32-38 (1945), German production of NGu towards the end of WW II was about 1500 tons per month.

References:

- 1) A. Stettbacher, Nitrocellulose 7, 141-145 (1936) (Nitroguanidin)
- 2) F. L. Davis, Army Ordnance 20, 93 (1938)
- 3) PB Rept 925 (1945), pp 22 & 116
- 4) W. Schurr, PB Rept 16 665 (1945)
- 5) Allied and Enemy Explosives, Aberdeen Proving Ground, Md (1946), p 149
- 6) A. Stettbacher, Spreng- und Schiesstoffe (1948), p 44.

Nitroisobutylglycerintrinitrat (Nitroisobutylglycerin Trinitrate)-See general section and also A. Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), p 69.

Nitrol . See general section.

Nitrolit. An amatol type explosive in which TNAns (trinitroanisole) was used to replace TNT. The mixture of TNAns 60 and Am nitrate 40% was of light yellow color with a mp about 75° which permitted cast-loading. Its strength, brisance and sensitivity to mechanical action were similar to those of 40/60 Amatol. It was hygroscopic and in the presence of moisture the TNAns hydrolyzed to picric acid, which would attack metals with the formation of dangerous picrates, while the Am nitrate could hydrolyze to form ammonia. Nitrolit was used in some sea mines and torpedoes.

Reference:

Allied & Enemy Explosives, Aberdeen Proving Ground, Md, (1946), pp 110-11.

Nitroparaffins. German research on the preparation and properties of nitroparaffins is described in CIOS Rept 33-41 (1945). See also general section under Paraffins.

Nitropenta (Np) . See Pentrit (PETN).

Nitropentaerythrit . See Pentrit .

Nitrostärke (Nitrostarch) . See general section under Starch .

Nitrotoluol . See general section under Toluene .

Nitrous Oxide, N₂O. Same as GM-1. See also general section.

Nitroxylol . See general section under Xylene .

Nitrozellulose . Same as Nitrocellulose .

Nitrozucker (Nitrosugar) . See general section under Sugar .

Nizol . See under Swiss Section .

Nobelit (Nobelite). A type of permissible gelatin-dynamites used before and after WW I. Two examples are given in Table 29

Table 29

| Composition (%) and some properties | Nobelite | Nobelite 19 |
|-------------------------------------|----------|-------------|
| NG (gelatinized with NC) | 28.7 | 26.0 |
| DNT | - | 2.0 |
| Dextrin | 2.5 | - |
| Wood meal | 1.0 | 1.0 |
| Potato flour | 10.0 | - |
| Vegetable oil | 0.5 | - |
| Am nitrate | 39.7 | 34.0 |
| Am chloride | 17.6 | 32.0 |
| Saturated soln of Ca nitrate | - | 5.0 |
| Oxygen Balance, % | - | 5.0 |
| Density | - | 1.75 |
| Velocity of Detonation, m/sec | - | 3750 |
| Trauzl Test, cc | 270 | 220 |

(See also Wetter-Nobelit)

References:

- 1) P. Naoum, Schiess- und Sprengstoffe (1927), p 150
- 2) P. Naoum, Nitroglycerin (1928), p 407.

Nobels' Sprengöl oder Sprengöl . Same as Nitroglycerin.

Nobels' Wetterdynamit I. One of the older permissible dynamites: NG 20, Na nitrate 31, flour 30, wood meal 6, naphthalene 2 and alum 1%. Veloc of detonation 3860 to 3930 m/sec at d 1.16 [Marshall 2 (1917), p 492] .

Non-Destructive Testing of Materials. Some of the German methods of testing are described in BIOS Final Rept 609 (1946). See also general section.

Normales Gasvolumen (Normal Gas Volume). Volume of gas at normal temperature (0° or 20° C) and normal pressure (760 mm) or Gas volume at NTP. Calculation of the volume of gas developed on explosion is described in the general section.

[See also A. Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), pp 13-14] .


NSP . See under Ignition.

NzManNP . See under Ignition.

Oberflächenbehandlung (Surface Treatment). See general section under Surface Treatment of Explosives, Propellants, Pyrotechnic Compositions, etc.

Oberon Gerät. A device designed in 1944 for controlling the bursting point of the air-to-air incendiary rocket, R 100 BS. It was claimed that the Oberon device improved the chance of a strike from a negligible value to a probability of about 0.4.
Reference: TM 9-1985-2 (1953), p 255.

Observing Bullet, caliber 7.92 mm, developed by the Deutsche Waffen- und Munitionsfabriken A-G, Lübeck, exploded with a flash on hitting the target. The bullet consisted of a steel casing, containing a charge of white phosphorus, a detonator and a striker with a steel spring. The base of the casing was closed with a lead plug.
Reference: H. Peplow et al, CIOS Rept 33-20 (1946), pp 26-7 (See drawing on next page).



Octogen. German name for Cyclotetramethylene Tetranitramine, ($H_2C_4N_4O_{12}$), called by the British HMX (His Majesty's Explosive or High Melting Explosive). This compound was present as an impurity in Hexogen (RDX or Cyclonite) when prepared either by the E-Verfahren or by the KA-Verfahren. It was found by the Germans that Octogen is more sensitive to friction than Hexogen, but is more stable to heat. (See HMX in the general section).

Ofenrohr (Stove Pipe). See under 88 mm Weapons.

Offensivität eines Treibmittels (Offensiveness of a Propellant). In order to be sure that a weapon (such as a rifle or gun) will not burst on firing, it is necessary to know the pressure developed on combustion of the propellant and the rate of pressure increase (Geschwindigkeit der Drucksteigerung). If any of these values are greater than calculated for a given weapon, the propellant is not suitable. Also, it must be certain that the combustion of a propellant will not develop into a detonation. The faster the rate of increase of pressure of a propellant the greater is the Offensivität.

This property of a propellant may be judged from the following test:

Usual fixed charges of various propellants to be tested are fired in a weapon provided with a device for deter-

mining the gas pressure. The tests are repeated with charges increased 25% and then with charges increased 50%. Table 30 gives results of tests conducted by Brunswig. (See below).

Reference:

H. Brunswig, Das rauchlose Pulver, W. de Gruyter, Braunschweig (1926), pp 220-221.

Optolene. A liquid rocket fuel consisting of about 50% Visol, 10-20% aniline and the rest being Optol (a coal tar product containing phenol), benzene and xylene. Density 0.9. It was used in the Wasserfall missile in conjunction with coned nitric acid (contg about 10% sulfuric acid), which served as an oxygen carrier. The ratio was 0.24 parts of Optolene per 1 part of acid. The theoretical specific impulse for this mixture was 214 lb/lb/sec, but they actually obtained only 183. This value was nearly equal to that obtained when using Visol/nitric acid. Reference: Gollin, CIOS Rept 28-56 (1945), p 19.

Pak oder PAK. Abbreviation of Panzerabwehrkanone, which means Antitank Cannon, or more literally Anti-Armor Defense Cannon.

Palatinol. Trade name for aliphatic ortho-phthalic acid esters of the general formula $C_6H_4(COO.C_{12N+1}H_{2N+1})_2$, proposed in 1927 by Noll as plasticizers for NC. Palatinols were manufactured during WW II by the I G Farbenindustrie and used in some propellants and explosives.

Following are examples of Palatinols:

Palatinol A. Diethylester of o-phthalic acid

Palatinol C (Elaol). Dibutylester of o-phthalic acid, d 1.0543 and b p 320°C

Palatinol HC. Di-iso-butylester of o-phthalic acid; d 1.0490 and b p 305 to 315°C

Palatinol M. Dimethylester of o-phthalic acid.

Palatinols are practically non-volatile (an advantage over camphor) and do not become rancid in storage (an advantage over castor oil).

References:

- 1) W. Krannich, Kunststoffe, Lehmann, Berlin (1943), p 40
- 2) Kast-Metz, Chemische Untersuchung der Spreng- und Zündstoffe, Vieweg, Braunschweig (1944), p 161.

Pantopolit. A dynamite manufactured more than 50 years ago at Opladen, near Köln: NG mixed with naphthalene 70, kieselguhr 20, Ba sulfate 7 and chalk 3%. Daniel, Dictionnaire, Paris (1902), p 599 J.

Table 30
(Offensivität)

| Charges | Sample 1 | | | Sample 2 | | | Sample 3 | | |
|---------------|--------------------|-------------------|----|--------------------|-------------------|----|--------------------|-------------------|-----|
| | Gas pressure (atm) | Pressure increase | | Gas Pressure (atm) | Pressure increase | | Gas Pressure (atm) | Pressure increase | |
| | | Atm | % | | Atm | % | | Atm | % |
| Usual fixed | 620 | - | - | 540 | - | - | 400 | - | - |
| Increased 25% | 1000 | 380 | 61 | 800 | 260 | 48 | 890 | 490 | 122 |
| Increased 50% | 1160 | 160 | 16 | 1040 | 240 | 30 | 1300 | 410 | 46 |

Note: Of the three samples the last has the highest Offensivität because the percentage increase in pressure is the greatest.

PANZER (Armor or Armed Vehicle) (In collaboration with Col G.B. Jarrett and Mr K.F. Kempf of Museum, Aberdeen Proving Ground, Md).

Under the term Panzer, the Germans included the following armed vehicles:

- a) Aufklärungspanzer (AufklPz). Light armored reconnaissance vehicle
- b) Flakpanzer (FlakPz). Special vehicle with full armor cover; used as AA weapon
- c) Fliegerleitpanzer. Armored observation car used

with front line support aircraft

d) **Funklenkpanzer**. Radio guided, light armored vehicle for special uses.

e) **Funkpanzer**. Armored vehicle for troop radio communication

f) **Gepanzerte Munitionstransport Kampfwagen**. Armored vehicle for transporting ammunition. It belonged to the class of Schützenpanzerwagen

g) **Jagdpanzer (JgdPz)**, called also **Panzerjäger (PzJäg)**. Tank destroyer, tank hunter or pursuit tank. It was a highly mobile, lightly armored and heavily armed combat automotive vehicle constructed of a half track or tank chassis and designed to catch up with and destroy enemy tanks. Like a tank it was able to leave roadways and maneuver over rough terrain

h) **Landeapanzer**. Armored amphibious troop carrier.

i) **Luftlandepanzer**. Light armored vehicle used with Airborne

j) **Munitionstransport Kampfwagen**. See Gepanzerte Munitionstransport Kampfwagen

k) **Panzerbefehlswagen (PzBefWg)** Commander's tank. It carried a superstructure, a two-way radio and a minimum of armor and arms

l) **Panzerbeobachtungswagen (PzBeoWg)**. Armored car used for artillery spotting

m) **Panzerjäger**. See Jagdpanzer

n) **Panzerkampfwagen (PzKpfw or PzKpfw)**, called also **Kampfwagen (KpfWg)**, **Panzerwagen (PzWg)**, or simply **Panzer**. was a heavily armored automotive combat vehicle mounted on a tractor (such as a caterpillar type) and capable of traversing very rough terrain;

used in organized front line units for a spearhead.

Note: The first tank was built during WW I by the British and used in September 1916 on the Somme. In order to keep secret the construction of the new weapon, it was listed in shop orders as "A Water Carrier from Mesopotamia" and this name was later shortened to "Tank" (Ref 8)

o) **Panzerkampfwagen Flammenwerfer**. Armored vehicle equipped with a flame thrower

p) **Panzermunitionstransport Kampfwagen**. See Gepanzerte Munitionstransport Kampfwagen

r) **Panzererspähwagen (PzSpW or PSW)**. Rapid, lightly armored vehicle for reconnaissance

s) **Panzerwagen**. See Panzerkampfwagen

t) **Panzerwerfer**. Armored rocket projector

u) **Schützenpanzerwagen (SPW)** Multi purpose armored car used with Armored Infantry, e.g. to transport personnel or ammunition

v) **Selbstfahrlafette (Sfl or St)**. Self-propelled artillery consisting of gun mounts (gun carriages) which had their own motor power to carry them into combat. Each mount could have protective armor and heavy caterpillar treads to enable it to leave roadways and maneuver over rough terrain. It differed from Towed Guns

w) **Sonderkraftfahrzeug (SdKfz)**. Any specialized vehicle, such as a tank, tank destroyer or self-propelled mount, might be designated as SdKfz

x) **Sturmpanzer (StuPz)**, called also **Sturmgeschütz (StuGesch)**. Front line support armored vehicles supplying overhead fire power against infantry

Following is a brief description of tank development in Germany before and during WW II:

Due to the restrictions imposed by the Treaty of Versailles (1919), the Germans did not have the right to build tanks. Nevertheless they by-passed the restrictions and started to build tanks as early as 1926 when Rheinmetall Co came out with a 21-ton tank armed with a 75 mm gun. In 1927-1928 the so-called **Landwirtschaftlicher Schlepper**, abbreviated as **LAS (Agricultural Tractor)** was constructed, which by a clever arrangement, could be easily converted into a tank and this was later done. The resulting tank was designated as **PzKpfw I or SdKfz 101**. Its first variation (Model a), which appeared before the Spanish Civil War (1934), weighed 5.7 tons and had a max speed of 25 mph, while its second variation (Model b) weighed 6 tons and had a max speed of 32 mph. Both models were armed with 7.92 mm machine guns, MG-13 (Dreyse). The chassis of Model b, was also used for the commander's tank (**PzBefWg I**), for the tank destroyer **PzJag I** which was armed with a 4.7 cm Pak (r) j and for a self-propelled mount carrying a 15 cm sIG 33 (150 mm medium infantry gun)

Several other tanks were constructed in the period before the Nazis repudiated the treaty of Versailles, but the real work started after 1933 when the following plants went into tank development and production: a) Friedrich Krupp, Essen; b) MAN, Nürnberg; c) Daimler-Benz, Berlin-Marienfelde; d) Henschel, Kassel and e) Rheinmetall, Düsseldorf.

The first design project was a 10-ton tank begun in 1934 out of which the **PzKpfw II or SdKfz 121** was eventually developed. The handling of this project set the pattern for nearly all the tanks developed up to about 1941, such as 30-t, 35-t and even 60-t tanks (designed by Henschel in 1937-1939), but they were never mass-produced.

PzKpfw II

The original tank, **PzKpfw II (SdKfz 121)** weighed about 11.5 tons and carried one 20 mm gun (either 2 cm KwK 30 or 2 cm Pak 38) and one 7.92 mm MG. Its max speed was 30 mph. The tank was made in several modifications (a, b, c, f, g & j). Its chassis was also used for a tank destroyer, a self-propelled mount, etc. such as:

a) Tank destroyer, nicknamed **Marder II (Marten II)** and designated 7.5 cm Pak auf Sf II (SdKfz 131) which carried one 75 cm A/T gun pattern 40/2, 48 calibers long. Wt 11.6 tons and max speed 25 mph. Its modification carrying one Russian 76.2 mm A/T gun was designated 7.62 cm Pak (r) auf Sf II Ausf B (SdKfz 132).

Note: Marder 38 is described at the end of this section under Czech tanks.

b) Self-propelled mount nicknamed **Wespe (Wasp)** and designated 10.5 cm lfl auf Sf II (SdKfz 124) carried one 105 mm light howitzer known as 10.5 cm lfl 18 M total wt 12.5 tons, max speed 25 mph

c) Self-propelled mount, designated 15 cm sIG 33 auf Sf II, carried one 150 mm medium infantry gun (howitzer), pattern 33, total wt 12 tons, max speed 25 mph

d) Flame thrower tank designated as **PzKpfw II (FlW)** or **Panzerkampfwagen II (Flammenwerfer)**, carried two flame throwers and one MG 34, wt 12.6 tons and max speed 34 mph

e) Reconnaissance tank, nicknamed **Luchs (Lynx)** and designated as **AufklPz II, lPzSpWg II (SdKfz 123)** carried one 20 mm gun (2 cm KwK 38) and one MG. Wt 13 tons and max speed 40 mph.

PzKpfw III

Although the design of **PzKpfw III** started several years before WW II, the tank did not reach the front until 1941, later than the **PzKpfw IV**. The tank III was known in several modifications and some of them were equipped with torsion bar suspension designed by Dr Porsche.

In general **PzKpfw III** was considered one of the most original and successful German tanks. About 6700 of them were produced between 1941 and 1943, most of them at the Daimler-Benz factory.

Following are the principal tank III versions as well as a flame thrower and self-propelled mounts utilizing **PzKpfw III chassis**:

a) **PzKpfw III (Models A, B, C, D & E)** (SdKfz 141) were tanks weighing 18 to 20 tons armed with one 50 mm short barrel gun (5 cm KwK) and two MGs 34. Max speed 28 mph

b) **PzKpw III (Models F, G & H)** were tanks weighing about 25 tons and armed with one 50 mm short barrel gun (5 cm KwK) and two MGs 34. Max speed 28 mph.

Note: The above gun fired a 4½ lb shell at a muzzle velocity of 2250 f/s.

c) **PzKpfw III (Models J, J(Tp) & K)** were tanks weighing about 24.5 tons and armed with one 50 mm long barrel gun (5 cm KwK 39) and two MGs 34. Max speed 28 mph.

Note: As the short gun of previous models proved to be inefficient against American medium tanks M3 (General Grant), it was replaced by a long gun (60 calibers long) which had a much higher muzzle velocity. Model J marked Tp (Tropen) was insulated against African desert heat.

d) **PzKpfw III (Models L, M, N & O)** were tanks weighing about 24 tons and armed with two MGs 34 and one 75 mm gun (7.5 cm KwK) or one 37 mm long barrel gun (3.7 cm KwK 39). Max speed 28 mph

e) Commanders tank, **PzBefWg III (SdKfz 143)** weighed 24.5 tons and carried a dummy 37 mm or 50 mm gun and two MGs which might also have been dummies. Max speed 25 mph.

- d) Flamethrower tank, PzKpfw III (E) or Panzerflamwagen III, weighed 25 tons and carried one flamethrower and two MGs 34. Max speed 22 mph
- e) Antiaircraft tank, nicknamed **Kugelblitz** and designated **Flopkpanzer III**, carried one 30 mm twin AA gun called 3 cm Flakzwilling Mk 103
- h) Self-propelled mounts designated as **Sturmgeschütz III** (StuG III) were in three versions:
 - 1) SdKfz 142 carried one 75 mm short assault gun (7.5 cm KwK L. 24). Wt 26 tons and max speed 28 mph
 - 2) SdKfz 142/1 carried one 75 mm long assault gun (7.5 cm KwK L. 43 or 7.5 cm KwK L. 48). Wt 26 tons and max speed 25 mph
 - 3) SdKfz 142/2 carried one 105 mm assault howitzer (10.5 cm StuH 42 L. 28). Wt 27 tons and max speed 25 mph.

PzKpfw IV

The work on the development of PzKpfw IV began at the Krupp plant as early as the summer of 1936 and the tank was actually used in the Polish (1939) and French (1940) campaigns.

Following are the versions of tank IV as well as the self-propelled mounts utilizing chassis of PzKpfw IV, PzKpfw III/IV, PzJäg IV or PzJäg III/IV:

- a) PzKpfw IV (Models A, B, C, D & E) (SdKfz 161) were tanks weighing 22.1 to 24.6 tons and armed with one 75 mm gun, 24 calibers long and two MGs 34. Max speed 28 mph
- b) PzKpfw IV (Models F & G) (SdKfz 161.1) and (Models F, J & K) (SdKfz 161.2) were tanks weighing about 26 tons and armed as follows: one 7.5 cm KwK L/24 or one 7.5 cm KwK 40 L. 48 for models F and G, and one 7.5 cm KwK L/48 for models F, J & K.

Notes: The 75 mm gun, 24 calibers long, fired a 15.5 lb shell with a velocity of 1650 f/s, while the 75 mm gun, 48 calibers long, fired the same shell with a velocity of 2600 f/s

- c) Tank destroyer designated as **Jagdpanzer IV** (JgdPz IV), **Panzerjäger IV** (PzJäg IV) or **SdKfz 162**, weighed about 26.5 tons and carried either a 75 mm assault gun, 48 calibers long (7.5 cm StuK 42, L/48) or a 75 mm assault gun, 70 calibers long (7.5 cm StuK 42, L/70). The ensemble weighed about 26.5 tons and had a max speed of 25 mph

Note: This weapon was listed by G.B. Jarrett as a self-propelled mount

- e) 8.8 cm Pak 43/1 auf PzKpfw IV (SdKfz 164), nicknamed **Hornisse** (Hornet) consisted of an 88 mm A/T gun on a tank IV chassis. Muz vel of the gun was 3281 f/s. The weapon served successfully at the Russian front and was later redesignated as **Nashorn** (see below)

- f) 8.8 cm Pak 43/1 auf PzJäg III/IV, designated also 8.8 cm Pak auf Sf IV and nicknamed **Nashorn** (Rhinceros) consisted of an 88 mm A/T gun, 71 calibers long on a tank IV chassis. The ensemble weighed 26 tons and its max speed was 22 mph

Notes: The gun of the Nashorn fired a 22 lb shell with a muz vel of 3280 f/s. The gun in the Tiger II had the same muzzle velocity and used the same ammunition

Both the Hornisse and the Nashorn were listed by G.B. Jarrett as self-propelled mounts

- g) Self-propelled mounts (**Selbstfahrlafetten IV**, abbreviated Sf), called also assault guns (**Sturmgeschütze**) existed in the following models:

- 1) 2 cm Flakvierling auf Sf IV, nicknamed **Wirbelwind** (Whirlwind) was a 20 mm four-barreled AA gun on a tank IV chassis. It was used since 1944
- 2) 3.7 cm Flak auf Sf IV, nicknamed **Ostwind** (East Wind) was a 37 mm AA gun on a tank IV chassis. It was used since 1944
- 3) 10.5 cm StuH 42 L/12 auf PzKpfw IV, designated also as 10.5 cm IFH 42 auf Sf IV, consisted of a 105 mm light howitzer, 12 calibers long on a modified tank IV chassis. It weighed 19.2 tons and had a max speed of 25 mph
- 4) 15 cm StuH 43 (or 15 cm sIG 33) auf PzKpfw IV, designated as SdKfz 163, consisted of a 150 mm medium heavy infantry gun 33 on a tank IV chassis. It weighed 29 tons and had a max speed of 25 mph. It was also called **Sturmpanzer 43** and nicknamed **Brummbär** (Grizzly Bear)

5) 15cm sFH 18 L auf PzKpfw III/IV, also designated 15 cm sFH auf Sf IV (SdKfz 166), consisted of a 150 mm medium heavy howitzer on a tank III/IV chassis. It was nicknamed **Mummel** (Bumble-Bee). Wt 28 tons and max speed 25 mph

Some modified tank IV chassis were used as ammunition carriers (**Munitionsträger**) and one of the units carried a crane and shells for heavy mortars **Karl** and **Thor**. (See Thor and Karl Mortars)

Most of the above tanks were very successful in the invasion of Poland (1939), Belgium, Holland and France (1940) but proved to be inadequate during the campaign in Russia (1941) when the heavier T-34 tank was encountered. As result of this failure, a complete revision of the German tank program was ordered (in 1941) by the High Command. It was decided to develop much heavier models, e.g., 50 tons. This did not mean, however, that the production of all previous models stopped. Over 10,000 PzKpfw III and PzKpfw IV were produced in 1943-1944 and only about 100 PzKpfw II tanks

The first tank constructed under the new program was the **Tiger I (P)** or **PzKpfw VI (P)** designed by Porsche. As it did not prove to be very successful as a tank, its chassis was modified and used for the tank destroyers **Ferdinand** and **Elefant** (Elephant) (See below)

Slightly later (in 1942) appeared the tank developed by Henschel Co and designated as **Tiger I (H)**. This model was adopted for service and its production started in the fall of 1942

At about the same period another heavy tank known as the **Panther** was developed and went into production early in 1943. This tank was intended to replace Panzer III and Panzer IV because Tiger I, called since 1943 **Tiger E** or **PzKpfw VI (E)**, gave rather inadequate service at the Russian front. Redesign of the tank was ordered by the High Command in order to meet all the requirements of the front. The newly designed tank was called **Tiger II** or **King Tiger** (See below).

Following is the list of Panthers and Tigers:

Panther (PzKpfw V)

- a) Basic model of the PzKpfw V (SdKfz 171) **Panther** weighed 47 tons and carried one 75 mm gun, pattern 42 (7.5 cm KwK 42) and two MGs 34. It carried a 4" gun in the top front, a 3" gun in the bottom front and 2" guns at the sides. Max speed 30 mph

Notes: The tank enjoyed immunity from most Allied projectiles as far as its front was concerned, but the sides could be penetrated. Its 75 mm gun was capable of firing a 15 lb shell with a muz vel of 3066 f/s. The most striking feature of this tank was the long frontal plate similar to the one found in the Russian T-34 tank. Many of the Panthers were covered with a cement-like paste, which had a very rough surface. The paste was intended to prevent magnetic mines sticking to the tanks, (some mines were drawn to the tanks by means of magnets)

- b) Tank destroyer **Jagd Panzer V** (JgdPz V), **PzJäg V**, **SdKfz 173** or **8.8 cm Pak 43/3 auf PzKpfw V**, weighed 51 tons and had a max speed of 30 mph. Its 88 mm A/T gun, pattern 43 was capable of firing a 22 lb shell with a velocity of 3280 f/s.

Tiger (PzKpfw VI)

- a) Original model, **PzKpfw VI (P)** or **Tiger I (P)**, was an 80 ton tank developed by Porsche, the designer of the Volkswagen and Porsche automobiles. The tank was equipped with an air-cooled engine and an electric drive. About 100 tanks were built and shipped to the Russian front for testing under battle conditions. Because of some mechanical failures, the tank was not accepted for service and preference was given to the tank **Tiger I (H)** developed by Henschel (See below). Meanwhile Porsche modified the chassis of his tank and converted it to a self-propelled motor carriage known as "**Ferdinand**", **PzJäg VI Ferdinand**, **SdKfz 184**, **Jgd Pz VI (P)** or **Tiger Porsche**. It was equipped with one MG and one long-barreled 88 mm gun (8.8 cm KwK 36), very effective against armor. This tank destroyer was superseded by **Elefant** (Elephant), designated as **SdKfz 184s**, which carried one MG and one 88 mm A/T gun, 71 calibers long (8.8 cm Pak 43, L/71). The ensemble weighed about 75 tons and had a max speed of 22 mph.

Note: F. von Senger und Etterlin (Ref 9, p 192) called the above tank destroyer, the **JgdPz VI Aufz Porsche**, and gave

its properties as follows: wt 68.8 metric tons (about 75.6 short tons), max speed 35 km (22 mph) and it carried one 128 mm A/T gun, 55 calibers long (12.8 cm Pak, L 55) and one MG.

b) **Tiger I** tank, designed by Henschel Co and adopted by the High Command for service, was called PzKpfw VI (H) or SdKfz 181. The designation was changed in 1943 to PzKpfw VI (E) or **Tiger E** and about 1000 of these tanks were produced that year. The wt of the tank was about 60 tons, max speed 25 mph and it carried one 88 mm gun, 56 calibers long (8.8 cm KwK, L 56) and two MGs 34.

c) **Tiger II** or **Tiger B** tank, designated PzKpfw VI (B) or SdKfz 182, called also **Königtiger** (King Tiger or Royal Tiger) weighed 75 tons, had a max speed of 24 mph and was equipped with two MGs 34 and one 88 mm gun 71 calibers long (8.8 cm KwK L 71). It incorporated the sloping frontal plate armor (6" thick), which had proven very successful in the Panther design. Its side armor was slightly thicker than 3". The tank was designed for submersion up to 13 ft and all the joints were made waterproof by using rubber seals. It resembled the Panther in appearance but was larger and more effective in performance. Although its design was finished only in 1943, more than 500 Tigers II were produced by Henschel Co before the war was over.

d) Tank destroyer, **Jagdpanzer VI** (JagdPz VI) or **Panzerjäger VI B** (PzJäg VI B) was a 77 ton armored vehicle built by the Nibelungenwerke, it carried one MG and one 128 mm A/T gun, 55 calibers long (12.8 cm Pak, L 55). Max speed 22 mph.

e) **Jagd Tiger** or **Tiger Jäger** was a 77 ton tank destroyer equipped with a 128 mm gun, 66 calibers long (12.8 cm Pak 44 or 12.8 cm PJK 44). Max speed 25 mph.

f) **Sturmiger** (Sturmpanzer VI mit 38 cm Mörser), called also **Sturmörser**, was a self-propelled mount consisting of a 380 mm Rocket Projector (38 cm Raketenwerfer (R)) mounted on a Tiger E chassis. It weighed 68 tons and had a max vel of 25 mph.

Czech Tanks

During World War II the Germans also used some Czech tanks, such as the T-38, manufactured by Skoda Werke, Pilsen. The original model, built before WW II, was designed by the Germans as PzKpfw 38(t). It weighed 11.7 tons and carried one 37 mm gun 37 (Czech) [3.7 cm KwK 37(t) and one MG 37 (Czech). Its maximum speed was 16 mph.

Because the above 37 mm gun had insufficient armor penetration, it was replaced in 1942 by a more powerful gun, the 7.5 cm KwK 40, L/48. It had no muzzle brake. At the same time the speed of the tank was increased by installing a more powerful engine. The resulting ensemble was a tank destroyer designated as **Jagdpanzer 38(t)** nicknamed **Hetzer** (Haiter). It weighed 17.5 tons and had a max speed of 23.5 mph. It also carried one MG 34. Note: "Hetzer" resembled in appearance PzJag 13 (Schweiz) except that the gun on this Swiss tank had a muzzle brake.

Another version of T-38, designated **JagdPz 38 Flam**, carried a flame thrower in lieu of a gun. Other T-38 versions served as self-propelled mounts: the first SP mount, designated 15 cm sIG 33/1 auf PzKpfw 38(t), carried a 150 mm medium heavy infantry gun (howitzer) 33/1, the second, designated 2 cm Flak auf PzKpfw 38(t), carried a 20 mm AA gun, and the third, nicknamed **Marder 38** (Marten 38), existed in two modifications: one, designated SdKfz 138, carried a 15 cm Pak 40/3 L/46, while the other designated SdKfz 139, carried a 7.62 cm Pak 36 (russ). Note: There was also a tank destroyer **Marder II**, which is briefly described above under PzKpfw II.

Some of the French tanks, such as the Lorraine, Renault, Hotchkiss, and Char B served as gun carriers. One of the foreign tanks used by the Germans was the Swedish **Landsverk (L-60)**, designed by Weiss. The tank was built during WW II at Budapest (Ref 7, pp 110-115).

There were also many wheeled armored cars built in Germany. Some information about them is given by Jarrett (Ref 7, p 116).

Several Experimental Tanks other than those previously mentioned and also tank destroyers were designed by the Germans, but none of them was put into production.

Following is a partial list of these vehicles:

a) **Leopard** (Leopard), A 28-ton tank developed in 1942

at Daimler-Benz plant (Ref 5, p 10)

b) **Maus** (Mouse) A 100-ton tank developed in 1942 by Porsche at Nibelungen Werke. It was equipped with a gas-electric drive, same as in Tiger I (P) and carried one 150 mm gun, several MGs and a flame thrower. (Ref 5, pp 11-12)

c) **Krupp-Maus** (Krupp Mouse), Heavy tanks; 110- 130- 150- and 170 ton, developed in 1942 by Krupp Co. (Ref 4, p 6)

d) **Series E** tanks of which **E-100** was a super-heavy tank of 130-140 tons. The E-100 was designed in 1943-1944 by the engineering staff of Adlerwerke, Frankfurt a/M under direction of HWA (Heereswaffenamt) (Refs 3 and 5)


e) **Bär** (Bear) was a 100-ton tank which carried a 305 mm breech-loading mortar (not rocket type) (Ref 4, p 6)

f) **1500-ton** tank mounting an 800 mm gun as main armament and two 150 mm guns in rear quarter turrets. The frontal armor was 250 mm thick and placed at 15 degrees (Ref 4, p 6).

References:

- 1) Anon, Field Artillery Journal, 34, 368-9 (1944)
- 2) G.B. Jarrett, Ibid, 35, 354 (1945)
- 3) CIOS Rept 28-3 (1946), Development of "E" Tank
- 4) CIOS Rept 29-2 (1946), History of German Tank Development
- 5) CIOS Rept 32-33 (1946), Tank Development at the Daimler-Benz Factory
- 6) CIOS Rept 32-35 (1946) Development of New Series of German Tanks up to End of March 1945
- 7) G.B. Jarrett, "Achtung Panzer! The Story of German Tanks in World War II, Great Oaks, RD 1, Aberdeen Md (1948)
- 8) Merriam-Webster's New International Dictionary, Merriam Co., Springfield Mass (1951), p 2577
- 9) Dr F. v Senger u Etterlin, Taschenbuch der Panzer 1913-1954, Lehmanns Verlag, München (1954).

Panzerfaust (Armored Fist). A hollow charge antitank rocket grenade fired from a tubular discharger. Its smaller model **Panzerfaust 30 klein**, was formerly called **Faustpatrone 1** and its larger model **Panzerfaust 30** was called **Faustpatrone 2**. The latest models were **Panzerfaust 60** and **Panzerfaust 100** (See also 44.5 mm Recoiless Grenade Discharger, under Weapons and also Faustpatrone).



Panzergranate Pzgr (Armor-piercing Projectile; Antitank Shell). Major types of such projectiles are listed under Granate and described in TM 9-1985-3 (1953).

Besides the conventional types of AP projectiles, and projectiles with hollow (shaped) charges, the Germans used some Sabot projectiles such as Type G Sabot Projectile (p 367) and the 75/88 mm Brand Sabot Projectile, developed by the French establishment of Edgar Brand. More effective were the **Arrowhead Type** Projectiles with a Tungsten Carbide Core such as: 2.8-2.0 cm Pzgr used in Tapered Bore Gun PzB 41 (p 372), 3.7 cm Pzgr/Patr 40 used in (2 3.7 cm Pak (p 373), 4.2-2.8 cm Pzgr/Patr used in Tapered Bore Gun LPak 41 (p 375), 4.7 cm Pzgr/Patr 40 used in Czech guns 4.7 cm Pak(t) and 4.7 cm K 36(t) (p 375), 5 cm Pzgr/Patr 40 used in Tank guns 5 cm KwK & 5 cm KwK 39 and in A/T Gun 5 cm Pak 38 (p 376), 7.5 cm Pzgr/Patr 41 used in A/T Gun, 7.5 cm Pak 41 (p 378).

A unique, light and effective AP projectile was designed for use in the Russian 76.2 mm A.T guns. At first the Germans attempted to adopt the arrowhead type projectile Pzgr 40 but found it unsuitable. In its place they developed a projectile of normal shell design, but employed a plastic interior sleeve to give body to the shell and still keep it relatively light. This shell, described by E. Englesburg in the Ordnance Sergeant, May 1944, p 312, consisted of the following components: a) a ballistic cap of an aluminum alloy, screwed onto the shell, b) an armor-piercing core, consisting of tungsten carbide plated with nickel, which was pressed into c) a steel core holder, d) a sleeve of molded plastic surrounding the core and its holder and filling the space between the body and these components, forming an ogival head with the ballistic cap. The plastic had a fairly high shock resistance.

Still more effective were **Arrow or Needle Type Projectiles** designed by O. Gessner.

The projectiles constructed at the Röchling Plant at Saarbrücken were very effective for penetrating concrete. (See also under Arrow Projectiles, Arrowhead Projectiles, Granite, Gessner Projectiles, Röchling Projectiles and Sabot Projectiles).

Panzerhandmine. See under **Hafthohlladung**.

Panzerschnellmine. See under Landminen and also p 262 of TM 9-1985-2 (1953).

Panzerschreck, Panzerfaust, Panzerwurfkanone und Püppchen were the shaped charge weapons developed before and during WW II in Germany.

The Panzerschreck was the shaped charge rocket, similar to the American Bazooka, but was heavier and had a shorter range than the latter. It was superseded by the Panzerfaust, which was a better weapon with a range of 150 meters. Another weapon, called the Püppchen, was essentially the 8.8 cm Panzerschreck mounted on a light carriage. The Panzerwurfkanone was a long-range weapon for shooting a shaped charge, developed by the Rheinmetall Co. It was a smooth-bore 8.0 cm mortar.

(See also under 80 mm and 88 mm Weapons).

References:

- 1) L.E. Simon, German Research in WW II, Wiley, N Y (1947), pp 187-8
- 2) A. Stettbacher, Spreng- und Schiesstoffe, Rascher, Zürich (1948), p 134.


Panzerwerfer 42. See under Rocket Launchers.

Panzerwurfkanone. See under Panzerschreck.

Panzerwurfmine 1(L). A shaped charge hand grenade, introduced by the Luftwaffe for use in close combat against armored vehicles of all types. Diameter of body 11", overall length 21", weight 2.1 lb. It was provided with four collapsible cloth vanes which were folded against the handle. When the grenade was thrown, the vanes sprang open and stabilized projectile in flight.

Reference:

- 1) A.J. Dere, Ordnance Sergeant, Oct 1945, p 8
- 2) Anon, Intelligence Bulletin 3, No 7 (1945).



PANZERWURFMINE 1(L)

Pappmine. See under Landminen and also on p 261 of TM 9-1985-2 (1953).

Parachute Flare. See under Flare.

Parommon. Mixture of Am perchlorate 90 and paraffin 10% used for military purposes. [A. Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), p 91.]

Pathfinder Bombing. A night bombing tactic developed during WW II in Great Britain and used against the Germans. The tactic consisted of dropping bombs on a target previously illuminated by flares dropped from the leading planes.

This method permitted more accurate bombing of the target.

Reference: A.B. Schilling of Picatinny Arsenal; private communication (1955).

(See also Pyrotechnic Antipathfinder Devices).

Patrone. See Cartridge.

PC 1400 FX was a radio controlled glider bomb, released from aircraft and designed to attack against capital ships or smaller objects. TM 9-1985-2 (1953), pp 195-6.]

Peenemünde. A rocket research center, including an air tunnel, constructed in 1936-1937 in an isolated spot on the German Baltic coast. The first rocket developed at Peenemünde was the A-3, the predecessor of the A-4 Rocket, commonly known V-2.

A fairly detailed description of Peenemünde Rocket Center and its activities is given in Ref 4.

Peenemünde is now in the Eastern Zone of Germany.

References:

- 1) A. Ducrocq, Les Armes Secrètes Allemandes, Paris (1917), pp 103-110
- 2) L.E. Simon, German Research in WW II, Wiley, N Y (1947) pp 33 & 130
- 3) J.G. Tschinkel, Chem Eng News 32, 2582 (1954)
- 4) W. Dornberger, V-2, Viking, N Y (1954).

Penta. Same as Pentrit (PETN).

Pentastit. See Swiss section.

Pentol oder Pentritol corresponds to the American Pentolite, described in the general section.

(See also Fillers Nos 16, 17, 28, 42 and under Pentrit).

Pentrit. See under Swiss Explosives.

Pentrit oder Nitropenta (NP). See general section under Pentaerythritoltetranitrate (PETN). It was manufactured in Germany by batch, continuous or semi-continuous methods.

A) The batch method was essentially the same as that used in the USA

B) The continuous method, as conducted at Troisdorf Fabrik, DA-G consisted essentially of the following operations:

a) Nitric acid of the highest concentration and PE in the ratio of 5 to 1 were introduced simultaneously into a nitrator of 54 liter capacity. The PE was added by means of a "dosing" machine feeding at the rate of 600g every 47 seconds. The temperature was maintained at 15-20° by means of cooling coils

b) The solution-suspension of PETN in nitric acid was led to an after nitrator, where the mixture was maintained at 12°

c) After this it went to a third vessel, where a strong jet of water diluted the acid and precipitated that part of PETN, which was dissolved in the stronger acid

d) The slurry was run through a vacuum filter and the ppt was rinsed several times with water

- e) The precipitate was transferred to a vessel where it was heated in dilute soda ash soln to 80-85° and from which PETN was run to a 2nd stabilizer.
- f) After separating the liquor by vacuum filtration, the PETN was washed with water and aspirated to a moisture content of 7-10%.
- g) The moist material was dissolved in 98% acetone preheated to 50°, and allowed to run gradually and with stirring into a vessel containing cold water.
- h) The acetone was distilled off and the crystallized PETN separated from the bulk of the water by vacuum. It was then packed in rubber bags and carried to the phlegmatizing house.
- i) For phlegmatizing (desensitizing) PETN, the Troisdorf Fabrik, D A -G used either Montan Wax, or a synthetic IG Wax - 41a. The amount of wax added to PETN was usually 10%, although mixtures with as high as 60% were known. The crystals of PETN were suspended in cold water containing some common salt in solution. The temperature was raised to about 40° and molten wax was added in a thin stream. The temperature was raised and the mass maintained at the boiling point until about 20% of the water had evaporated.
- j) The slurry was then cooled (by adding cold water) and filtered. After washing the phlegmatized product with water and removing as much water as possible by suction, the product was dried to reduce the moisture content to below 0.1%. The material was then screened and packed.
- C) The semi-continuous method as practiced at the Krümmel Fabrik, D A -G was essentially as follows:
- a) The nitrating apparatus consisted of 3 stainless steel vessels connected in series. A charge of 200 kg of PE and 1000 kg of 99% nitric acid was fed into the first nitrator (which was cooled with brine circulated in coils and in a jacket) where the main nitration took place at 15-20° during about 10-15 minutes. A second charge of PE and HNO₃ was meanwhile weighed and transferred to the first nitrator immediately after the 1st batch was transferred to the 2nd nitrator (which was also provided with jacket cooling). Following this, the 1st batch was transferred to the 3rd nitrator, the 2nd batch to the 2nd nitrator, and a 3rd charge was introduced into the 1st nitrator, etc. The total time of nitration was about 40 minutes.
- b) In the 3rd nitrator, the mixture was diluted with water to give a waste acid of about 30% strength.
- c) After filtering off PETN from waste acid, PETN was washed with water and then digested with soda ash solution in a stabilizing vessel at 60° until the slurry was weakly alkaline (time, about 1½ hours). This was followed by water washing directly on the filters.
- d) The next operation, crystallization from acetone, was done in a continuous manner in a battery of 6 distillation vessels connected in series. In these vessels, water was added to the solution and the acetone gradually evaporated leaving a water slurry of PETN. After removing the bulk of the water by vacuum filtration, the moist PETN (10% H₂O) was transferred to the wax phlegmatizer.
- e) Phlegmatization was carried out in a water slurry of 315 kg of PETN (contg 10% H₂O) plus 1200 kg of water at 85°, to which wax, usually Montan or IG Wax -41a, in the proportion of 1 part wax to 9 parts PETN by dry weight, was added with stirring.

Note: According to German Railroad regulations, phlegmatized PETN was permitted to be shipped if it contained at least 6% wax. Unphlegmatized PETN required at least 30% of water for shipping.

PETN was also phlegmatized by the addition of TNT (20 to 50%) and the operation was conducted by suspending PETN in about 6 parts of water at 70°, heating to about 80° and adding molten TNT with agitation. This was followed by cooling, filtering and drying. The mixture was allowed to be shipped dry (Ref 1).

The manufacture of phlegmatized PETN at the Wolfratshausen Plant was described by Swanson Ref 3 and CIOS Rept 25-16 (1945).

Abbreviations: PE Pentaerythritol.

References: Same as under Pentritsprængstoffe.

Pentritsprængstoffe (Pentaerythritol Tetranitrate Explosives). Straight Pentrit (PETN) was used under the name of Filler No 3-NI as a bursting charge in some grenades and small shells (such as the 20 to 50 mm), as well as in a lower detonator. Straight PETN was also used in a propellant called Nipolit.

The use of PETN desensitized with 8-10% wax was much more common.

Note: The wax used in German explosives was usually Montan Wax, obtained from the lignites found in many parts of Germany and countries occupied by her during WW II. The properties of Montan wax are comparable to those of Carnauba wax imported from Brazil. German PETN-wax mixtures were usually dyed pink. The explosive properties of such mixtures were the same as those of the corresponding American mixtures described under Pentaerythritol Tetranitrate in the general section.

The principal uses of PETN-wax mixtures were as follows: fillers for various shells, bombs, grenades, and some sea mines; fillers in some shaped charge ammunition; standard boosters in chemical and incendiary ammunition; standard sub-booster in all types of ammunition and as the core in a detonating fuse.

Explosives, desensitized with TNT, are briefly described under Pentol or Pentritol as well as Fillers Nos 16, 18, 28, 32-34, 36, 37, 42 etc). In some mixtures Al was incorporated and these were used in underwater ammunition.

Besides these mixtures there was also a plastic explosive (see Filler No 43) and explosives consisting of PETN, RDX and wax (See Filler No 45).

References:

- 1) Anon, Allied and Enemy Explosives, Aberdeen Proving Ground, Md, (1946) pp 138-142
- 2) O.W. Stickland et al, General Summary of Explosive Plants, PB Rept No 925 (1945), pp 42-45
- 3) A.A. Swanson et al, Manufacture of Phlegmatized PETN, PB Rept No 320 (1945)
- 4) A. Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), pp 66-67.

Pentritol oder Pentol (Pentolite). See general section and also under Pentrit.

Perchlorate Explosives. See Perchloratsprengstoffe.

Perchloratit (Perchloratite). A type of industrial explosive based on perchlorates. Table 31 gives some perchloratites listed in the book of Naoum (Ref 1).

Table 31

| Ingredients | Composition, % | | |
|---|----------------|-------|-------|
| | 1 | 2 | 3 |
| K perchlorate, of which up to 10% of the total explosive may be replaced with Am nitrate and/or K nitrate | 60-75 | 62-75 | - |
| K and/or Am perchlorate | - | - | 30-40 |
| Am nitrate | - | - | 35-45 |
| Note: When Am perchlorate is incorporated some of the Am nitrate is replaced by K nitrate in an amount chemically equivalent to the amount of Am perchlorate. | | | |
| Vegetable meal | 1-5 | - | - |
| Vegetable meal and/or solid hydrocarbon | | 1-8 | 3-8 |
| Nitroglycerin(ungelatinized) | 3-6 | - | - |
| Nitroderivatives of toluene and/or naphthalene and/or diphenylamine in which up to 4% of the total explosive may be substituted with nitrocellulose | 20-30 | 20-30 | 15-20 |

Stettbacher (Ref 2) lists the following perchloratites:

Table 32

| Composition, % | Perchloratites: | | |
|----------------------------|-----------------|----|----|
| | 1 | 2 | 3 |
| K perchlorate | 68 | 35 | 34 |
| Am nitrate | 10 | 42 | 48 |
| TNT and DNT | - | 14 | - |
| DNT | 16 | - | 12 |
| Wood (or vegetable) meal | 1 | 5 | 6 |
| NG (nitroglycerin) | 4 | 4 | - |
| MNN (mononitronaphthalene) | 1 | - | - |

References:

- 1) P.Naoúm, Nitroglycerin, etc, Baltimore (1928), p 431
- 2) A.Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933), p 316.

Perchloratminensprengstoff (Perchlorate Explosive for Trench Mines). According to P.Naoúm, Schiess- und Sprengstoffe (1927), p 133, the following castable mixture, developed during WW I at Zentralstelle für wissenschaftlich-technische Untersuchungen in Neubabelsberg, was found to be suitable for use in Wurfminen (trench mortars): K perchlorate 56, DNB 32 and DNN 12%.

Note: This explosive was called Perdit by Davis (1943), p 364, but on p 118 Naoúm gives a different formulation for Perdit.

Perchloratsprengstoffe (Perchlorate Explosives). Explosives based on the perchlorates of ammonium, potassium or sodium were used to a limited extent in Germany, as for instance: Parammon, Perchloratite, Perchlorit, Perdit, Perkoronit, etc.

(See also Perchlorate Explosives in the general section). Note: According to Davis p 364 the perchlorates recovered from surplus bombs etc of WW I (see Perchloratminensprengstoffe and also Perdit) were used in the German post

WW I commercial explosives, such as Perchloratit, Perchlorit, Perkoronit and Persalit. When the supply of surplus perchlorates became exhausted the manufacture of perchlorate explosives was nearly discontinued because the price of new perchlorates was too high.

Perchlorit (Perchlorite). A type of perchlorate explosive used in mining before and during WW I. Table 33 gives the composition of two perchlorites

Table 33

| Ingredients and properties | Composition, % | |
|----------------------------|----------------|------|
| | 1 | 2 |
| K perchlorate | 35 | 34 |
| Am nitrate | 42 | 48 |
| DNT* | 10 | 10 |
| DNN | 4 | 0 |
| Wood meal | 5 | 6 |
| Coal powder | - | 2 |
| NG | 4 | - |
| Oxygen Balance, % | +1.7 | +1.7 |
| Trauzl Test, cc | 340 | 340 |

*DNT was prepd by the nitration of m-MNT.

Reference: Naoúm, Nitroglycerin, Baltimore (1928), p 134.

Perkoronit (Perkoronite). A blasting explosive which replaced Coronit in stone quarries and ore mines: K perchlorate 65, NG 5, aromatic nitrocompounds 25 and vegetable meal 5%.

Reference: J.Bebie, Manual of Explosives, Macmillan, N Y (1943), p 116.

Perdit (Perdite). An explosive developed during WW I as a replacement for the Corps of Engineers Explosive, (Pioneerammunition) Donarit. The composition and properties of Perdit were: Am nitrate 72, K perchlorate 10, wood meal 3 and a eutectic mixture of DNT and TNT 15%; density 1.20-1.25, Trauzl test value 370-380cc, sensitivity to initiation required at least a No 3 cap for detonation.

It was used not only as a demolition charge but also for loading bombs and trench mortar shells.

References:

- 1) P.Naoúm, Schiess- und Sprengstoffe, Dresden (1927), p 118
- 2) A.Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933), p 309.

(See Note under Perchloratminensprengstoffe).

Perkoronit (Perkoronite). A type of mining explosive manufactured after WW I from K perchlorate recovered from surplus military explosives. Table 34 gives two examples. (See next page).

Permonit (Permonite). A type of mining explosive manufactured before WW I by the Sprengstoff A-G Carbonit. One such explosive, called Gesteins-Permonit, was described in this section under Gesteinsprengstoffe. Table 35 gives two examples of permonites. (See next page).

Table 34
(Percoronites)

| Components and Properties | 1 | 2 |
|--------------------------------|----------|----------|
| K perchlorate | 58 | 59 |
| Am nitrate | 8 | 10 |
| DNT + TNT + vegetable meal | 30 | 31 |
| NG (nitroglycerin) | 4 | - |
| Oxygen Balance, % | +2.2 | +1.8 |
| Density | 1.58 | 1.52 |
| Velocity of Detonation, m/sec | 5000 | 4400 |
| Trauzl Test, cc | 340 | 330 |
| Pb Block Crushing, mm | 20.0 | 18.0 |
| Requies for initiation minimum | No 3 cap | No 3 cap |
| Gap Test, cm | 6.0 | 4.0 |
| Heat of Explosion, kcal/kg | 1170 | 1160 |
| Temperature of Explosion, °C | 3145 | 3115 |

References:

- 1) P. Naoum, Nitroglycerin, etc, Baltimore (1928), p 430
- 2) T.L. Davis, Chemistry of Powder and Explosives, Wiley, N Y (1943), pp 364-5.

Table 35
(Permonites)

| Components and Properties | 1 | 2 |
|---------------------------------|------|---------|
| K perchlorate | 32.5 | 31-34 |
| Am nitrate | 42.5 | 39-43 |
| NG | - | 3-4 |
| Collodion cotton | - | .5-1 |
| TNT | 10.0 | 11-13 |
| Starch | 12.0 | 5-9 |
| Wood meal | 3.0 | 1.5-3.5 |
| Moisture | - | 0-2.5 |
| Veloc of Detonation, m/sec | 3780 | - |
| Density | 1.13 | - |
| Trauzl Test, cc | - | 365 |
| Gap Test, cm | - | 8.0 |
| Impact Sensitivity (2kg weight) | - | 20 cm |

Permonites were used in potash and in ore mines. Some permonites were on the British Permitted List and on the Belgian SGP List.

Reference: A. Marshall, Explosives, London, v 1 (1917), p 384 and v 2 (1917), p 493.

Persalut (Persalite). One of the perchlorate mining explosives manufactured from left-over stocks of WW I military explosives. The name Persalut is mentioned in P. Naoum, Schiess- und Sprengstoffe (1927), p 126, but the composition is not given.

Petroklastit oder Haloklastit. One of the pre-WW I explosives used in potash mines and stone quarries: Na nitrate 69, K nitrate 5, sulfur 10, coal tar pitch 15 and K bichromate 1%, Trauzl Test value 157 cc (vs black powder 108) and Sensitivity to Impact with a 2 kg wt 100 cm (black powder 65).

References:

- 1) A. Marshall, Explosives, London, 1 (1917), p 89
- 2) A. Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933), p 111.

PETN. See Pentrit.

PE-Wolle. A nitrocellulose of 11.25-11.50% nitrogen content, used for the manuf of some smokeless propellants. See Nitrocellulosea and also Propellants.

Pfeilgeschoss. See Arrow Projectile.

Phenanthren (Phenanthrene) was proposed by Römer to be used as one of the ingredients in explosives based on cyclotrimethylenetrinitrosamine (R-Salz), such as: R-Salz 96.5, phenanthrene 2.5, and DPhA 1.0%.

Reference: G. Römer, Report on Explosives, PBL Rept No 85,160 (1946), pp 10-13.

Phenix Sprengstoffe (Phenix Explosives) were mining explosives patented in 1899 by the Sprengstoffwerke Dr Nahsen & Co in Hamburg.

Table 36 gives some examples

Table 36

| Ingredients | Composition % | | | | |
|-------------|---------------|----|----|----|----|
| | 1 | 2 | 3 | 4 | 5 |
| NG | 25 | 25 | 30 | 30 | 30 |
| K nitrate | 34 | - | - | - | - |
| Na nitrate | 1 | 35 | 32 | 30 | 32 |
| Sawdust | 40 | - | 38 | - | - |
| Rye flour | - | 40 | - | 40 | 38 |

References:

- 1) Daniel, Dictionnaire, des Matières Explosives, Paris, (1902), p 449
- 2) L. Gody, Traité des Matières Explosives, Namur (1907), p 715.

Phenol (Phenol). See general section and also BIOS Final Repr 1246 (1946).

Phosphorus Bombs. Some incendiary bombs contained phosphorus. For instance, the 50 kg Brand C50B bomb contained white phosphorus whereas the 50 kg Brand C50A bomb was filled with 30 lb of a mixture containing phosphorus 4, benzene 86 and pure rubber 10%.



Reference: TM 9-1985-2 (1953), pp 54-5.

Phosphorus Grenade. One of the incendiary grenades manuf during WW II in Germany was described in BIOS Final Rept 1233 (1946), p 2. It weighed 1390 g and was prepd from a casing weighing 300 g, having a diameter of 105 mm. After filling the casing with a mixture of cotton wool (40 g) and naphthalene (300 g), the air was exhausted and the mouth of the grenade was immersed into molten yellow phosphorus. This operation allowed about 750 g of phosphorus to enter the grenade and impregnate the cotton and naphthalene.

Photoflash Bomb (Blitzlichtcylindrische Bombe, abbreviated as BLC or BLC), called also Photographic Flash Bomb. German bombs were similar in external appearance to conventional 50 kg bombs and parachute flare cases. Their fillings, which could be either flare compositions or incendiary mixtures, were ignited by electrical or mechanical aerial burst fuzes.

Following are examples of photoflash bombs:

- a) BLC 50 bomb weighed 30 lb and resembled in appearance the SC kg Type 1 bomb except that the case was made of sheet steel with a heavy nose section. Body diameter 7.8", body length 26.4" and overall length 43.0". (See also under Bombe)
- b) BLC 50/A bomb consisted of a light steel casing 42.9" long and 8" in diameter. Its nose was filled with



concrete which acted as a ballast to stabilize the flight of the bomb. The outer section of the bomb contained 15 kg of Al Pyroschliff (qv), while the inner tube contained 3.5 kg of black powder, called Marine-Geschütz Pulver. This served for expelling, scattering and igniting the Al powder, which continued to burn in the air. The black powder was exploded by means of an 80 mm long detonating fuze placed inside the tube passing through the black powder charge. The fuze was initiated by means of an electric delay fuze inserted in the fuze well in the side of the bomb. Total weight of the bomb was 42 kg. The bomb was insensitive to bullet impact.

Note: The Pyroschliff aluminum could be replaced with an atomized Al powder called Griess, or by mixtures containing magnesium powder described under Photoflash Compositions.

Reference: TM 9-1985-2 (1953), pp 65 & 81-3.

Photoflash Compositions. Among the compositions used by the Germans, may be mentioned the ones used in the BLC 50/A bomb:

- 15 kg of flaked aluminum, called Pyroschliff (qv). It was insensitive to bullet impact and had the following characteristics: peak light intensity 450 million Hefner candles, time to reach peak intensity 70 milliseconds and total light output 63 million International candle seconds.
- 30 kg of atomized aluminum, called Griess (qv). It was insensitive to bullet impact and had a peak light intensity of 800 million Hefner candles. The time to reach peak intensity and the total duration of the flash were longer than for the 15 kg Pyroschliff.
- 28 kg of pellets (13 mm diam and 1 mm high) composed of magnesium powder 39, Fe nitrate 53, synthetic phenolic resin, 6 and talcum 2%. It was sensitive to rifle bullet impact. Its peak intensity was 80% of that of Pyroschliff, and the time to reach peak intensity was 100 milliseconds.
- 28 single-perforated pellets (60 mm diam and 220 mm high), each weighing 900 g (total weight of pellet 25.2 kg) and consisting of Mg powder 50, Na nitrate 45 and wax 5%. A length of detonating fuze was passed through each pellet and the ends of the fuze bound together. It was sensitive to rifle bullet impact and had a peak intensity (measured through a yellow filter) 20% greater than for 15 kg of Pyroschliff. The time to reach peak intensity was the same as for Pyroschliff, but the duration of flash much longer.

Reference: TM 9-1985-2 (1953), pp 82-4.

PH-Salz (PH-Salt). German name for Ethylenediaminedinitrate (EDDN), described in the general section. In Germany PH-Salz was prepd by treating ethylenedichloride with ammonia and NaOH, followed by nitration with nitric acid not stronger than 50%. Although PH-Salz has a high m.p. (185°), it has the property of depressing the m.p. of other high m.p. compounds. For this reason, the Germans used it to obtain castable explosive mixtures. For instance, a mixture of 45% PH-Salz and 55% Am nitrate melts at 105° and can be cast-loaded. Such a mixture has an explosive power equal to that of TNT or Amatol, but it has the disadvantage of shrinking considerably on cooling. Addition of aqueous Ca nitrate to this mixture practically eliminates shrinkage and results in a very good cast. The following mixtures contg PH-Salz were used for filling some shells as a substitute for TNT.

- Ammonit: NH₄NO₃ 46, PH-Salz 46 and Ca(NO₃)₂·4H₂O (tech) 8%; density of fragments 39-40 m. (See Fragments Density Test)
- Ammonit: NH₄NO₃ 55, PH-Salz 10, Ca(NO₃)₂·4H₂O 10, RDX 20, and NaNO₂ 5%; d 1.53, casting temp 108°, density of fragments 40 m (Ref 3)
- H-5 (Ammonit): PH-Salz 10, NH₄NO₃ 50, NaNO₂ 5, Ca(NO₃)₂·4H₂O 15, and RDX 20% (Ref 2)
- S-16: PH-Salz 10, NH₄NO₃ 32, NaNO₂ 6 or 8, KNO₃

- 2 or 0, RDX 10 and Al (powder) 40% (Ref 2)
 e) S-22 (Hexa): PH-Salz 14, NH₄NO₃ 45, NaNO₃ 9, KNO₃ 3, RDX 14, and Al (powder) 15% (Ref 2)
 f) S-22 (Hexa): PH-Salz 14, NH₄NO₃ 45, NaNO₃ 9, KNO₃ 3, HNDPhA 14, and Al (powder) 15% (Ref 2)
 g) Amatol 41: NH₄NO₃ 52, PH-Salz 30, Ca(NO₃)₂·4H₂O 6, RDX 10 and Montan wax 2% (Ref 3).

Composition containing Al were particularly suitable for underwater weapons because they possessed high blast effect. PH-Salz could also be used straight or slightly phlegmatized. In the latter case, it was particularly suitable for use in anticongrete shells, called Be-Granate (Be is the abbreviation for Beton=concrete).

References:

- 1) PB Rept No 925 (1945), p 24
- 2) PB Rept No 1820 (1945), p 29
- 3) PBL Rept No 85 160 (1946), p 23.

Picric Acid. See Pikrinsäure.

Piercing or Penetration Test. For this test an explosive enclosed in an iron tube, 30 mm in diameter and 100 mm long with walls 3.5 mm thick, was detonated horizontally against a lead sheet 30 mm thick with sides 100 mm long. The penetration produced was compared with that of a standard explosive such as TNT.

Reference: G.Römer, PBL Rept 85160 (1946), p 10.

Pike (Macht) Missile. An experimental guided missile developed in 1941 by the Rheinmetall-Borsig Co.
 Reference: K.W.Gatland, Development of the Guided Missile, London, (1952), pp 116-17.

Pikrinsäure (Picric Acid) (P A). Methods of preparation and properties are given in the general section. It would be of interest to know that in 1892 the Chemische Fabrik Griesheim, Ger Pat 69 837, developed a unique process for loading HE shells with P A. This was carried out as follows: a mixture of P A and 5 to 10% of TNT was placed in a suitable mold which was heated for a short time to a temperature of about 82°C which is slightly above the m p of TNT. On cooling there was formed a solid block consisting of crystals of P A cemented to the thin intermediate layers of solid TNT. In place of TNT other solid nitrocompounds with not too high a m p may be used (such as DNT, DNPh, DNCrs, TNCrs, DNB, nitrated naphthalenes, xylenes, etc). It was claimed that the resulting explosives had high density, were safe to prepare, and were appreciably less sensitive to a mechanical action than a straight P A (see Ref 1).

During WW II P A was manufactured for use as a booster (compressed), as well as a filler for some shells, land mines, depth charges (see Filler No 2) and as a filler in stick hand grenades (see Filler No 3).

Cast P A was used under the name of Filler No 24.
 Abbreviations: DNB Dinitrobenzene; DNCrs Dinitrocresol; DNPh Dinitrophenol; DNT Dinitrotoluene; TNCrs Trinitrocresol and TNT Trinitrotoluene.

References:

- 1) E. de W. Colver, High Explosives, Van Nostrand, N Y, (1918), pp 319-20 & 697
- 2) Anon, Allied and Enemy Explosives, Aberdeen Proving Ground, Md, (1946)
- 3) A.Stettbacher, Spreng- und Schiesstoffe, Rascher, Zürich (1948), pp 75-77.

Pikrit. See Silvit.

Pirat (Pirate). A solid propellant rocket used as an assisted take-off unit for Feuerlicie -55. TM 9-1985-2 (1953), p 226.

Pistol (Pistole). See under Weapons.

Pistolenpulver (Pistol Propellant). The following composition is given in Brunswig, Das rauchlose Pulver, (1926) p 136: guncotton 96, Ba nitrate 1, DPhA 1.5, residual volatile gelatinizer 0.5 and moisture 1%.

Pistol Grenades (Pistolengranaten). Several types of German grenades were fired from special pistols, such as the 27 mm Walther signal pistol, etc.

Following types of pistol grenades are described in TM 9-1985-2 (1953), pp 340-46:

a) Pistol Grenade (Wurfkörper für Leuchtpistole 361) consisted of a normal egg hand grenade attached to a plastic stem (body) by a retaining tube. The plastic stem contained the firing pin, delay igniter, detonator and a base adapter for the propellant. The end of the stem was closed before firing by a cardboard cap. After arming the grenade by withdrawing the safety pin, the plastic stem was placed in a barrel reinforcing tube which was previously placed in the barrel of the 27 mm Walther signal pistol. The cap and the propellant in the rear section of the stem were fired and the grenade went towards its target (maximum range 80 yds). The impact of the grenade caused the firing pin to strike the primer and the resulting flash ignited (through the flash tubes) the delay igniter. After a delay of about 4.5 sec the grenade exploded (pp 340-1)







b) 27 mm Egg Type Pistol Grenade, described on pp 341-2, was fired from the latest type 27 mm Walther signal pistol, without the insertion of a rifled liner (as a reinforcing tube) in the barrel. The grenade was similar to the type 361 except in the construction of the stem

c) 26 mm Pistol Grenade (Wurfgranatepatrone), fired from the smooth-bore pistol, 326 Leuchtpistole, consisted of a projectile having the appearance of a small mortar shell. A brass cartridge case, containing about 0.1 ounce of rifle propellant, was crimped over the rear section of the grenade where the fins were located. The projectile itself consisted of an outer casing (body) and a loosely inserted inner casing containing the detonator and the main charge. The fixed firing pin, held by a creep spring, was located in the nose section of the body. The inner case was prevented from moving forward before firing by two metal balls fitting into a hole in the tail section of the projectile and resting in grooves. An arming (safety) rod fitted between the balls holding them apart. The withdrawal of the rod, caused by the setback on firing the projectile, allowed the retaining balls to move towards the center thus releasing the rear section of the inner case. The case would now be free to move forward if it was not held by the tension of the creep spring. This tension was overcome on impact thus allowing the detonator (contained in the inner case) to move forward and strike the fixed firing pin (pp 342-3)

d) 27 mm HE Grenade (Sprengpatrone) for the rifled pistol (Kampfpistole) consisted of a die cast aluminum body provided on the outside with five grooves making one quarter turn of the projectile. Inside the body was a steel cylinder containing two PETN/wax pellets separated by a cardboard disc. The nose section contained the direct action fuze fitted with a protruding striker head. The striker was held away from the fuze primer by 6 steel balls which rested in the groove of the striker and on a platform of the fuze. The balls were kept in position by a steel collar which was supported on three aluminum pins. A creep spring was located between the striker and the primer, and beneath the primer was an aluminum gaine containing in the upper part a mixture of lead azide and lead stypnate and in the lower part pressed PETN. Between the gaine and the main filling there was an air space. The propellant charge was contained in a cup which was placed in the cartridge attached to the tail section of the grenade. There were 10 holes in the cup to lead the propellant gases to the base of the grenade. On firing, the gases propelled the grenade and rotated it because of the rifling. The setback caused the collar in the fuze to move back crushing the aluminum pins and the centrifugal force caused

PISTOL

GRENADES



the balls to fly outward. This partly freed the striker, but it still was held by the creep spring until the striker head hit a solid object (pp 343-4)

e) 23 mm Hollow Charge Signal Pistol Grenade, PzWK 42 LP (Panzerwaffkörper 42 für Leuchtpistole) was fired from the 27 mm Walther signal pistol fitted with a 23 mm rifled liner, a special sight and a folding butt. The warhead of the grenade was pear-shaped and contained the shaped charge and an impact cap. To the rear of the warhead was attached the tube containing the graze fuze-detonator and the gaine. A short length of this tube was perforated. A thinner tube containing a shearing bolt, propellant and a percussion cap was attached by a shear pin to the perforated section. On firing, the propellant gases drove the shearing bolt forward causing it to break the shear pin. This released the grenade and armed the graze fuze (by setback) (pp 344-5)

f) 27 mm Pistol Grenade Message was fired from a 27 mm rifled signal pistol (Kampfpistole). The round consisted of a perforated aluminum cylinder (containing a smoke generator, a colored silk streamer and an ejection charge), a black plastic lead (containing a message or other small object) and an aluminum cartridge case. On firing, the flash from the propellant ignited the delay pellet in the grenade base plate and this, in turn, ignited the ejecting charge which expelled the message container, silk streamer and smoke generator. (p 345)

g) 27 mm Multistar Signal Cartridge fired from a signal pistol, consisted of a light alloy outer cylindrical casing (the base of which contained the propellant and percussion cap) and an inner cylinder which contained six green and red star units. Running through the center of the star units was an assembly of two concentric brass tubes which were held in position by a central cannellure into which the inner cylinder was indented and fixed by means of a steel pin. The outer brass tube had one set of 6 flash holes adjacent to the inner surfaces of the six stars. The inner brass tube also had a set of flash holes which by means of a setting cap could be aligned so as to permit the ignition of a selected number of combinations consisting of red and green stars as shown below:

a) 3 red & 3 green, b) 1 red & 2 green, c) 3 red & 1 green, d) 1 red & 3 green, e) 2 red & 2 green and f) 2 red & 1 green.

The inner brass tube was filled with black powder and was closed at the lower end by a screwed plug which contained a delay pellet.

In firing, the inner cylinder was ejected (by propellant gases) from the outer light alloy case, and after the delay pellet had burned through the flash passed immediately along the whole length of the inner brass tube, igniting and ejecting the star in accordance with the setting. The stars which were not ignited fell to earth intact (pp 346-7).

Plastic Explosives. Several plastic explosives based on PETN and RDX were used in Germany during WW II. One of the earlier compositions consisted of RDX treated with American vaseline (see Note) until this vaseline became unavailable. Thereafter mixtures called Plastit and Hexaplast, which did not contain vaseline, were used.

Note: American vaseline was considered most suitable because it is "long fiber" and can be stretched like dough to form threads. European vaseline, such as the Russian, is not tacky and does not produce good plastic explosives. (See also Plastic Explosives in the general section).

Reference: PB Rept 925 (1945), pp 74 & 77.

Plastics. (Kunststoffe, Pressstoffe). Manufacture and properties of plastics are described in the following References:

- 1) W. Krannich, Kunststoffe im technischen Korrosionsschutz, Lehmann, München-Berlin (1943)
- 2) H.S. Bergen, PB Report 7032 (1943)
- 3) Anon, PB Report 91836 (1945)
- 4) BIOS Final Reports: 282, 433, 445, 926, 1191, 1246 and 1729 (After WW II)
- 5) BIOS Miscellaneous Reports: 1, 85, 87 and 98 (After WW II)
- 6) BIOS Reports: 29-62, 32-26 and 33-23 (After WW II)
- 7) H. Sachting u. W. Zebrowski, Kunststoff-Taschenbuch, Hanser, München (1952).

Plastics in German Ordnance. During WW II there was a growing use of plastics in plants which manufactured acids, explosives and ammunition. For instance, linings for tanks and pumps, funnels, pipes, plastic trays for drying explosives, sealing plugs in delay detonators etc, were fabricated from plastic material. One of the plastics developed in Germany was Mipolam. Others were Novolac, Lignofol, Igelitpulver, Trolital etc.
Reference: PB Rept No 925 (1945), pp 7 and 25.

Plast: A plastic explosive of WW II: RDX (4, colloid cotton 3.5 and liquid or semi-liquid nitrohydrocarbons 32.5%. It was less efficient than the American Composition C2 because it contained less PDX (Allied and Enemy Explosives, Aberdeen Proving Ground (1946), p 127).

Plastol, Celludol, Celludin oder Comphrosal Trade names for p-Toluenesulfamide, $\text{CH}_3\text{C}_6\text{H}_4\text{SO}_2\text{NH}_2$, white flakes, mp 137°, obtained as a by-product of saccharine manufacture. Its 20% alcoholic solution gelatinizes colloid cotton completely at 55°. (Kast-Metz, Chemische Untersuchung, Braunschweig (1944), p 163).

Plastomenit (Plastomenite). According to Daniel (Ref 1) plastomenites were propellants invented about 1889 by Gütler. They consisted of mixtures of the nitrated products of cellulose, sugar, starch, aromatic compounds, etc with oxidizing substances such as inorganic nitrates, chlorates, chromates, etc. These compositions were modified beginning 1897 by incorporating 0.5 to 10% of colophony.

According to Marshall (Ref 2). Plastomenite was an early (1889) sporting smokeless propellant prepared by gelatinizing NC with DNT.

Colver (Ref 3) stated that Plastomenite was a German propellant prepared by blending 5 parts of molten DNT with one part of nitro lignin and sometimes small amounts of Ba nitrate. After incorporation the fused mass was granulated.

Brunswick (Ref 4) gave Plastomenit as containing guncotton 67, Ba nitrate 13, TNT 13, DNT 6 and moisture 1%.

References:

- 1) Daniel, Dictionnaire des Matières Explosives, Paris (1902), p 634
- 2) A. Marshall, Explosives, 3, (1932), p 98
- 3) E. Colver, High Explosives (1918), p 169
- 4) H. Brunswick, Das rauchlose Pulver (1926), p 134.

Plastrit. See Plastrotlyl.

Plastrotlyl or Plastrit. According to Colver, High Explosives (1918), p 249, plastrotyls were plastic explosives patented by C.E. Richel in 1906 (Ger P 181 574). They were prepd by mixing 85 to 87 parts of TNT with liquid or solid resins, such as copaiba balsam, benzoin gum or styrax, with or without liquid DNT. The plasticity could be increased by incorporating some colloid cotton. Table 37 gives some examples (See next page).

Plattenbeschuss (Plate Shooting). A plate test for the estimation of the brisance of explosives similar to the one described in the general section.

Table 37

| Ingredients | % Composition | | | |
|------------------|---------------|------|------|------|
| | 1 | 2 | 3 | 4 |
| TNT | 87.0 | 85.0 | 85.0 | 85.0 |
| Capitol balsam | 12.0 | - | - | - |
| Larch turpentine | - | 14.0 | - | - |
| Liquid nitro | - | - | 4.3 | - |
| Benzoin gum | - | - | - | 4.5 |
| Liquid DNT | - | - | 10.0 | 10.0 |
| Collod cotton | 1.0 | 1.0 | 0.5 | 0.5 |

Platzpatronenpulver (Blank Cartridge Propellant). The following composition is given in Brunswig, Das rauchlose Pulver (1926), p 136: collod cotton 23, guncotton 74, diphenylamine 0.7, soot 0.3, moisture 1.0 and residual volatile gelatinizer 1.0%.

PMF-109. Same as Füllpulver 109 (Fp 109), described under Filler.

POL (Pulver ohne Lösungsmittel) (Solventless Propellant). See under Propellants.

Pollopos One of the plastic materials developed prior to WW II by the Dynamit A-G, at Troisdorf. It is a urea-formaldehyde condensation product.

References:

- 1) W. Krannich, Kunststoffe in Technischen Korrosionsschutz, Lehmann, München-Berlin (1943), p 21
- 2) H. Sachtling & W. Zebrowski, Kunststoff-Taschenbuch, C. Hanser, München (1952), pp 240 & 254
- 3) H.A. Tisch, Picatinny Arsenal; private communication.

Polpulver. See FOL

Polyamide. According to CIOS 21-3 (1945), a Nylon type polyamide was developed at the Troisdorf Plant of Dynamit A-G. No description of its manuf and properties is given.

Polyglykol (PGK) (Polyglycol). A liquid product consisting of about 75% diethyleneglycol (DEG), called in Germany Diglykol, and 25% ethyleneglycol (EG) called Glykol (Gc). This product was manufd before and during WW II by IG Farbenindustrie starting with ethylene which in turn was obtained either from blast furnace gases (by liquefaction and subsequent fractionation) or by hydrogenation of acetylene. This means that no food materials were required for its manufacture, whereas for the manufacture of glycerin critical food materials such as fats were required.

When this product was nitrated, a liquid explosive was obtained which proved to be a better gelatinizer for NC than NG. Another advantage of nitrated polyglycol (NPGc) was that it produced much cooler propellants (possessing low calorific value) than was ever possible with NG. (See "G" Pulver).

Reference: O.W. Stickland et al, General Summary of Explosives Plants, PB Rept No 925 (1945), p 13.

Polygon. A plastic composition which when applied to the surfaces of combustible solids prevented them from burning. It was used for coating the non-burning surfaces of solid rocket propellants.

Reference: TM 9-1985-2 (1953), p 201.

Polystyrene Plastics. According to CIOS 21-3 (1945), p 5, the IG Farbenind at Ludwigshaven produced two types of polystyrene which softened at 64° and 72° respectively. No copolymers of styrene were used.

Polyurethane Plastics. Preparation and properties are described in CIOS Report 29-12 (1945).

Polyvinylcarbazol Plastic, called Luvtran, was unsatisfactory for injection molding because of its high melting point (over 200°). Considerable pressure was required to mold it and this caused rapid wear of the molds. Reference: CIOS Rept 21-5 (1945), p 5.

Polyvinyl Chloride (PVC) was used in Germany for the preparation of various plastics (Ref 1) and in some pyrotechnic compositions (Ref 2).


The following polyvinyl chloride plastics are mentioned in Ref 1:

- a) Vinidur (q v)
- b) Mipolam (q v)
- c) After-chlorinated PVC. It contained up to 60% of Cl and was very stable. It dissolved in methylene chloride in which the original PVC was not soluble.

References:

- 1) M.F. Fogler - F.J. Curtis, CIOS Rept 21-3 (1945), p 5
- 2) T. Urbanski, Przemysl Chemiczny, 27 (4), 487 (1948).

Porofor N. Code number for the product prepd by IG Farbenindustrie by condensation of acetone with sodium cyanide and hydrazine sulfate, followed by treatment with sodium hypochlorite:



The product was used in the manufacture of porous materials such as foam rubber sponge and as a coating for Schnorkel tubes and submarine periscopes (see under Zell-Igelit). It has the property of evolving nitrogen when heated together with vinyl chloride in an autoclave at 130°.

Similar properties were displayed by Porofor DB (Diazoamidobenzene) and Porofor 254 (prepd similarly to Porofor N by using cyclohexanone instead of acetone). Reference: CIOS Report 25-18 (1945), p 30.

Potato Masher or Stick Hand Grenade (Stielhandgranate) consisted of a wooden stick (handle) to which was attached a metallic can filled with an explosive. A similar type was the Japanese Type 98 Stick Hand Grenade and also the Russian Stick Hand Grenade.

Reference: TM 9-1985-2 (1953), pp 319-320 (Stielhandgranaten 24, 39 and 43).


Powder Metallurgy. See Pulvermetallurgie.

Pre-engraved Projectile. See general section.


Pre-rifled Projectile. See Rifled Projectile.

Pressing of Explosives. German procedure is briefly described under Krümmel Fabrik, Dynamit A-G, Pressing of Explosives, etc.

Pressling. C. Monard et al, Mém poud 34, 179 (1952) stated that Pressling was a German explosive of WW II containing some tetra-nitrosulfoxidiphenylamine,



a yellow solid with mp 368°. The tetra compd was prepd by nitration and oxidation of thiodiphenylamin (phenthiazine)



with concd nitric acid. No other information is given by Monard.

Primärladung (Primary Charge) is a top charge of a blasting cap or detonator. Explosives used for primary charges are described under Primary and Initiating Compositions.

Primary and Initiating Compositions. The following German terms are used in connection with this subject: Zündladung (Primer Charge), Zündhütchen (Primer Cap), Initialsatz (Initiating Composition), Initialzünder (Initiator). A general

description of primary and initiating explosives may be found in Refs 1, 2, and 3 as well as in the general sections. In Refs 4, 5, 6, 7, and 8 are listed explosives used during WW II. Mercuric fulminate was used extensively during WW I, but only in a few types of primers during WW II. Table 38 lists some German primary and initiating compositions used in fuzes, primers and detonators.

Table 38

| | Composition % | | | | | | | | | Uses |
|---|---------------|------|------|--------------------------------|------------|---------|-------------|--|----------|---------------------------------------|
| | M F | L A | L St | Sb ₂ S ₃ | Tetra-cene | NC | Ca silicide | Oxidizer | Abrasive | |
| a | 23.5 | - | - | 23.5 | - | - | - | KClO ₃ 43.0 | Glass 10 | Primers in shells and some bomb fuzes |
| b | - | - | 94 | - | - | 6(*) | - | - | - | Electric fuze primers |
| c | - | - | 88.7 | - | - | 11.3(*) | - | - | - | Same as above |
| d | - | - | 37.5 | 7.4 | 4.2 | - | 12.4 | Ba(NO ₃) ₂ 38.5 | - | Primers |
| e | - | - | 49.1 | - | - | - | 15.4 | Ba(NO ₃) ₂ 35.5 | - | Primers |
| f | - | - | 52.1 | - | - | - | - | Ba(NO ₃) ₂ 47.9 | - | Primers |
| g | - | 82 | - | 7 | - | - | - | - | Glass 11 | Primer-detonators |
| h | - | 60 | 40 | - | - | - | - | - | - | Standard detonators |
| i | - | 55 | 45 | - | - | - | - | - | - | Same as above |
| j | - | 14.4 | 85.6 | - | - | - | - | - | - | Detonators |

*In compositions (b) and (c) the NC was made into a paste using amyl acetate. Then the paste was beaded to the ignition bridge of a primer.

Table 39 lists some cartridge case primer compositions used during WW II

Table 39

| Composition % | Uses |
|---|--|
| L St 88.7 and NC lacquer 11.3 | 50 mm HE, 50 mm APRN, 50 mm APHV, 75 mm HE and 75 mm APC |
| KClO ₃ 35, Sb ₂ S ₃ 7.7, M F 21.5 and abrasive 6.5 | 20 mm III SD, 20 mm APLC, 50 mm APC IC, 50 mm APC SC, 50 mm APHV LC, 88 mm HEMTF and 88 mm APC |
| KClO ₃ 44, Sb ₂ S ₃ 24, M F 23 and abrasive 9 | 37 mm HE, 37 mm HEMB, 37 mm APRN, 37 mm APHV and 105 mm HE How |
| KClO ₃ 28.2, Sb ₂ S ₃ 31.1, M F 25.7 and abrasive 15 | 47 mm AP, 47 mm APRN, 47 mm APHV NP and 47 mm HE |
| KClO ₃ 29.1, Sb ₂ S ₃ 43.4, M F 16.7 and abrasive 10.8 | 47 mm HE |
| Ba nitrate, L St and abrasive | 20 mm APHV |
| Ba nitrate 47.9 and L St 52.1 | 7.92/13 mm HE |
| L St 19.2, Sb ₂ S ₃ 6.1, Pb-nitrate 53.6 and abrasive 21.1 | 80 mm CM |
| L St 26.4, Sb ₂ S ₃ 18.2, Pb-nitrate 50.1 and abrasive 5.3 | 50 mm TM |

Table 40 lists some primer compositions used in fuzes during WW II.

Abbreviations: AP Armor-piercing; APC Armor-piercing, capped; CM Chemical mortar; HE High explosive; HoC Hollow charge; How Howitzer; HV Hyper-velocity; I Incendiary; IC Inert charge; L A Lead azide; LC Long

Table 40

| Composition % | Uses |
|---|---|
| KClO ₃ /Sb ₂ S ₃ | 20 mm HE Shell |
| KClO ₃ 61, Sb ₂ S ₃ 33 and abrasive 6 | 37 mm APMB, 37 mm APRN, 47 mm APRN, 50 mm HETM, 50 mm APC LC, 50 mm APRN, 50 mm APC SC, 80 mm CM and 88 mm AP Shells; some Land Mines |
| KClO ₃ 58.5, Sb ₂ S ₃ 27.5, carbon 9.5 and abrasive 4.5 | 47 mm AP and 75 mm APC Shells |
| KClO ₃ 40, M F 29 and Sb ₂ S ₃ 31 | 47 mm HE Shell |
| KClO ₃ 45, Sb ₂ S ₃ 34, M F 12 and abrasive 9 | 47 mm HE Shell and 105 mm How Shell |
| KClO ₃ 29.5, Sb ₂ S ₃ 54.6, carbon 10.7 and abrasive 5.2 | 75 mm HE Shell |
| L A 65 and Ca silicide 35, over PETN | 75 mm HoC and 105 mm HoC Shells |
| KClO ₃ 37, M F 26, Sb ₂ S ₃ 30 and glass 7 | 88 mm AP Shell |
| KClO ₃ 51, Sb ₂ S ₃ 24 and abrasive 25 | 50 mm Mortar Shell |
| KClO ₃ 38, M F 14, Sb ₂ S ₃ 42 and glass 6 | Land Mine (Tellermine 35) |
| L St 41, Ba nitrate 41, Sb ₂ S ₃ 3 and Ca silicide 15 | Land Mines (Tellerminen 42 and 43) |

case; L St Lead styphnate; MB Monoblock; M F Mercuric fulminate; MTF Mechanical time fuze; NC Nitrocellulose; PETN Pentaerythritol tetranitrate; RN Round nose; SC Short case; SD Self-destroying; TM Trench mortar.

During WW II, the Germans also developed several types of gasless delay detonators with fuseheads containing lead picrate, among other ingredients. (See Fuseheads A6 and G3 and Fusehead Manufacture).

References:

- 1) R. scales, A. Stettbacher, Initial Explosivstoffe, Veit, Leipzig (1917)
- 2) A. Stettbacher, Schiess- und Sprengstoffe, Barth, Leipzig, (1933) pp 324-355
- 3) Anon, Allied and Enemy Explosives, Aberdeen Proving Ground, Md (1946), pp 64 & 71
- 4) Collective, PB Rept II, 544 (1945), part III, Tables I, II and III
- 5) W.R. Tomlinson Jr, Pic Arsn Tech Rept 1555 (1945)
- 6) F. Pristera, Picatinny Arsenal Chem Lab Rept No 127,024 (1949)
- 7) Anon, Army Ordnance 31, No 161, pp 451-2 (1947), German Electric Primers of WW II
- 8) A. Stettbacher, Spreng- und Schiesstoffe, Rascher, Zürich (1938), pp 95-109.

Primary Compositions described in TM 9-1985-3 (1953), pp 355-6 were used in the following primers:

- a) Percussion Primer C/12nA, used in 50 mm QF cartridges for HE shell, contained: MF 28, K chlorate 34, Sb sulfide 32, and glass powder 6%. The upper recess (magazine) of the primer contained 0.65g of granular black powder and a 1.44g pellet of black powder which served to ignite the propellant (pp 354-5).
- b) Percussion Primer C/13nA used in QF cartridges, contained: MF 52.0, K chlorate 23.0, Sb sulfide 19.7 and abrasive 5.3%. The upper recess of the primer housed 8.7 grains of black powder which served to ignite the propellant (p 355)
- c) Percussion Primer C/33, used in QF cartridges, contained: MF 24.6, K chlorate 37.6, Sb sulfide 29.6 and abrasive 8.3%. The upper recess of the primer housed 8 grains of black powder, which served to ignite the propellant (pp 355-6)
- d) Percussion Primer M 33, used in 47 mm cartridges, contained: MF 16.7, K chlorate 29.1, Sb sulfide 43.4 and abrasive 10.8%. A charge of black powder (3.1 g), placed above the primer, served to ignite the propellant (p 357).

In CIOS Rept 33-20 (1946), p 37 is described in the following primary composition used in caps for 7.92 mm steel cartridges manufd by the Deutsche Waffen- und Munitions-Fabriken A-G, Lübeck: Ba nitrate 42, Pb styphnate 40, Tetracene 3, Pb peroxide 5 and Ca silicide 10%.

Abbreviations: C Construction; HE High explosive; K Potassium; MF Mercury fulminate; nA New Pattern; QF Quick firing; Sb Antimony. (See also Abbreviations under Table 40).

Primer (Zündhütchen). According to E. Engleburg, The Ordnance Sergeant, May 1944, pp 320-1, German Artillery primers were all threaded on the outside and were screwed into the base of a cartridge case. The primers were small in comparison with those used in US ammunition, and contained only a small amount of explosive to amplify the action of the initial fire. To facilitate ignition and to insure complete and uniform burning of the propellant, an igniter bag was employed at the base of all propelling charges whether fixed or semi-fixed.


Note: No separate-loading ammunition (such as in the USA) was used by the Germans.

The body and the inner components of a primer were originally made of brass, but there was a tendency during WW II to make the bodies of steel.

Two types of Artillery primers were used: electric and percussion.

A. Electric primers were employed in all ammunition for anti-tank guns above 5 cm in caliber, for tank guns of 5 cm and larger, for the 7.5 cm StuG, for the 8.8 cm Flak 41 & 43 and for all calibers of anti-aircraft guns larger than 8.8 cm.


The C/22 Electric Primer consisted of a brass primer body, a plastic primer plug insulator, a brass primer plug, an igniter assembly, a sheet brass igniter retainer,



a brass retaining screw, a loose black powder charge, a pressed black powder charge, a cloth black powder disk, and an aluminum closing disc crimped in position to close the forward end of the primer. The igniter assembly consisted of two thin aluminum lead-ins placed on each side of a fiber strip and connected to each other by means of a platinum-iridium bridge. One lead-in was in contact with the primer plug, the other with an igniter retainer. The bridge and the fiber assembly were encased with a small quantity of lead styphnate coated with a green colored nitrocellulose lacquer and around this was placed a loose black powder charge.


When the firing circuit was closed the current passed from the insulated primer plug, up one of the lead-ins, through the wire bridge, and down the other lead-in, to the igniter retainer which grounded the current. The passage of the current heated the bridge sufficiently to ignite the lead styphnate surrounding it and this in turn ignited the black powder.

B. Percussion primers existed in the following types: C/12nA, C/12nAst (Steel), C/13nA, C/33 and M/33. All these types, as well as the Russian Primer 42/M used by the Germans, are described in TM 9-1985-3 (1953), pp 354-58. The C/12nA Percussion Primer consisted of a primer body threaded on the outside and recessed in the center to receive a brass anvil plug. The plug had a central flash channel and was recessed at the rearward end to form an anvil and to hold a brass primer





cup containing the primer mixture. The cup held the mixture against the anvil. Directly above the plug was placed a small amount of granular black powder with a black-powder pellet covering it. The pellet was held in position by a brass washer crimped over a varnished fabric disc. When the firing pin hit the primer, the cap pushed the primer mixture against the anvil, thus causing the mixture to ignite. The flash from the mixture went through the channel toward the black powder charges and ignited them and these in turn fired the propelling charge. This primer was used in ammunition for field guns and howitzers from 7.5 cm to 21 cm (excluding the 7.5 cm StuG) and also for the 5 cm Pak and the 8.8 cm Flak 18 and 36. (See also Primary and Initiating Compositions).

Primer, Electric, Bridgeless Type was developed by the Deutsche Waffen- und Munitionsfabriken A-G, Lübeck. It consisted of a cylindrical casing (zinc plated steel) containing a primer mixture (presumably lead dinitrocresylate and azide), a pole piece, insulating cup, lead tin foil washer (attached by shellac to an insulating material washer) and a contact ring. A current of 120-160 volts was required to fire the primer.
Reference: H.Peploe, CIOS Rept 33-20 (1945), pp 75 & 77.



Primer, Electric, Bridge Type was developed by the Deutsche Waffen- und Munitionsfabriken A G, Lübeck and manufactured by the Rheinmetall-Borsig AG. It consisted of a cylindrical BRASS CLOSURE DISC (0.05 MM THICK) FILLING COMPOSITION (UNPRESSED)



casing (nickel plated brass or nickel plated steel) containing essentially the following items:

- a) A bridge wire soldered to two metal foil strips separated by a millboard (insulator). The bridge wire was coated by successive dips in a paste formed by mixing an igniter compound (such as lead styphnate or lead picrate) suspended in a NC varnish. (See under Fusehead)
- b) A filling composition: K perchlorate 47, Pb styphnate 23 and Ca silicide 30%, loaded loosely around the fusehead.

Ammunition with electric primers were used mostly for synchronized aircraft guns, such as Mausers: 15 mm MG 151, 20 mm MG 151, 200 and 20 mm MG 213. The bridge-wire primer existed in two types: C/25 and C/27, each requiring a firing current of 24 volts.

In addition to their use for synchronized guns, electric primers were used in some Turret guns and in AA guns. Reference: H.Peploe et al, CIOS Rept 33-20 (1945), pp 73-6.

Priming Compositions Used for Tracers. See under Tracers.

Progressive Rifling or Increasing System of Twist (Zunehmender Drall oder Wachsender Drall) is briefly described in the general section under Rifling.

Following German weapons used progressive rifling:

- a) 75 mm KwK (6° to 9° twist)
- b) 75 mm KwK 40, L/43 (6° to 9°)
- c) 75 mm Stk 40, L/43 (6° to 9°)
- d) 88 mm KwK (4° to 6°)
- e) 88 mm Flak, Modifications 36 & 37 (4° to 6°)
- f) 100 mm K 18 (4° to 6°)
- g) 105 mm Howitzer (6° to 12°)
- h) 150 mm Howitzer (5° to 10°)
- i) 150 mm K 39 (4° 17' to 5° 59')
- j) 170 mm Gun (4° 16' 40" to 5° 58' 42")
- k) 210 mm H 18 (5° 7' 45" to 5° 58' 42")
- l) 210 mm K 38 (4° 29' 27" to 5° 30')
- m) 240 mm Gun (3° 35' 43" to 7° 9' 25").



Reference: R.P.Baumann of Picatinny Arsenal, Dover, N J, private communication.

Projectile. See Granite.

Projectile, Flare. See under Flare.

Propagandagrante (Leaflet Projectile). One such projectile (caliber 105 mm), designated as 10 cm Weiss-Rot Geschoss, is described in TM 9-1985-3 (1953), p 462. It contained 28 1/2 lb of leaflets and a small charge of black powder serving as a burster. The shell was fired from light field howitzers such as IFH 18, 18/1, 18/2, 18mM, 18/39 and 18/40 (See drawing next page).

Propagandarakete 41 (Leaflet Rocket), caliber 73 mm, consisted of two steel tubes screwed into a central joint. The lower part contained the rocket motor with propellant consisting of a cylindrical stick with nine longitudinal perforations—one in the center and eight in a circle around the central hole. Below this were 12 venturi set in two concentric rings. The upper section of the missile contained an inner cylinder (which was split longitudinally) with leaflets wrapped around a steel spring which was kept under compression. The missile was spin-stabilized and was fired from a single-tube launcher called the Propagandawerfer. The propellant was ignited by means of the percussion cap and when the rocket reached its destination, the igniter (located between the propellant and leaflets) fired the bursting charge. The resulting gas pressure ejected the inner cylinder and the plastic cap. As the split cylinder emerged, it fell apart and allowed the compressed spring to scatter the leaflets packed around it.
Reference: TM 9-1985-2 (1953), pp 234-5.
(See drawing on next page).



PROPELLANT; SMOKELESS POWDER (Treibmittel, Treibpulver oder Rauchlose Pulver). A general description of German propellants is given in Refs 1, 2, 3 and 4 listed at the end of this section.

Propellants used by Germans during WW I were described by H. Muraour, *Mém Artill Fr.* 2, 507 (1923) and by J. Pepin Lehalleur, *Poudres etc., Bailliéie, Paris* (1925), pp 290-291. They included the following propellants:

A) **S (Rifle)**: NC (12%N) 24, NC (13%N) 72.5, DPhA 0.5, Cent 0.5, Am oxalate 0.7, gelatinizer (residual solvent) 0.5, and moisture 1.3%

B) **Tube (Cannon)**: NC (12%N) 21, NC (13%N) 70, Cent

or Acar 5, K bitartrate 2, residual solvent 0.7, and moisture 1.3%

C) **Würfelpulver** (Flaked propellant) (Rifle): NC (12%N) 60, NG 38.5, Cent or Acar 1 and moisture 0.5%

D) **Würfelpulver**(Cannon): a) NC (12%N) 29, NC (13%N) 29, NG 40, Cent 1, and moisture 1%; b) NC (12%N) 31, NC (13%N) 31 NG 30, Cent 7 and moisture 1%; c) NC (12%N) 30, NC (13%N) 31 NG 20, TNT 14.5, DNT 3.5, Cent 0.3, and moisture 0.7%

E) **Röhrenpulver** (Tubular propellant) (Cannon): NC (12%N) 32-34, NC (13%N) 32-34, NG 25-29, Cent 4-7, Am oxalate 0.5, Na carbonate 0.5, graphite 0.5 and moisture 0.9%.

Table 41 lists some propellants of WW I described in Ref 2, pp 134-6

Table 41
WW I Propellants

| Composition % | For Small Arms | | For Ordnance | | | | | |
|------------------|---------------------|----------------------|--------------|------|----------------------|------|------|------|
| | Strip | Cube | Tubular | | | Cube | | |
| NC (soluble) | 24.0 | 60.0 | 21.0 | - | 32-34 | 29.0 | 31.0 | 30.0 |
| NC (insoluble) | 72.5 | - | 70.0 | 66.0 | 32-34 | 29.0 | 31.0 | 31.0 |
| NG | - | 38.5 | - | - | 25-29 | 40.0 | 30.0 | 20.0 |
| TNT | - | - | - | 25.0 | - | - | - | 14.5 |
| DNT | - | - | - | 5.5 | - | - | - | 3.5 |
| Centralite | 0.5 (or camphor) | 1.0 (or acardite) | 5.0 | 0.5 | 4-7 (or urethane) | 1.0 | 7.0 | 0.3 |
| Diphenylamine | 0.5 | - | - | - | - | - | - | - |
| K tartrate | - | - | 2.0 | 2.0 | - | - | - | - |
| Na oxalate | 0.7 | - | - | - | 0.5 | - | - | - |
| Am oxalate | - | - | - | - | 0.5 | - | - | - |
| Na bicarbonate | - | - | - | - | 0.1 | - | - | - |
| Graphite | - | - | - | - | 0.9 | - | - | - |
| Moisture | 1.3 | 0.5 | 1.3 | 1.0 | - | 1.0 | 1.0 | 0.7 |
| Volatile solvent | 0.5 | - | 0.7 | - | - | - | - | - |

Note: The Am oxalate was added to diminish the danger of ignition during rolling.

Abbreviations: See under Table 44.

Propellants of WW II

The information contained below was derived from results of analyses of captured German propellants conducted at Picatinny Arsenal, Dover, New Jersey (mostly by P.R. Hosken, Jr and H. Judowitz of the General Laboratory) and also from documentary materials gathered by various American and British missions sent to Germany directly after termination of the War. (See Refs 4 and 10).

Following is a general survey of propellants used during WW II:

- a) Both single and double-base propellants were used by the Germans during WW II. In double-base propellants it was the tendency to replace NG by DEGDN. This was partly due to the excessive erosion caused by NG propellants, and partly because of the shortage of glycerin while DEG could easily be prep'd synthetically from acetylene. Also, DEGDN is a better gelatinizer for NC than NG and for this reason smaller amounts of DEGDN could be used. The DEGDN propellants possessed much lower calorific values than NG propellants but they were not suitable for use in tropical climates on account of the high vapor pressure (and consequently high volatility) of DEGDN (see also "G" Pulver). Still cooler propellants, which were also less erosive and practically free from muzzle-flash were obtained when large amounts of nitroguanidine (NGu) were incorporated, as for instance, in the composition: NGu 30, NC 43, DEGDN 20, stabilizers and plasticizers 7% (see also Gudolpulver)
- b) As flash reducers the Germans used salts of potassium such as sulfate, chloride, nitrate and oxalate. They were frequently supplied in bags for use only at night as they produced smoke which was visible in the day time. (See Vorlage) In propellants contg NGu there was no necessity to use the above salts because NGu acts as a flash reducer
- c) Some German propellants contained between 1.5 and 3.0% of hydrocellulose, presumably to improve the burning characteristics, or to reduce flash
- d) An interesting feature of German propellants of low calorific value was the use of mixed gelatinizers-stabilizers, such as centralites, acardites and urethanes. It was claimed that these mixtures had a better effect on the working properties and stability than when used individually
- e) Of the other ingredients, magnesium oxide was included as a lubricant to facilitate rolling and extruding operations, graphite was added to reduce the formation of static electricity during manufacture, and the inclusion of about 3% alpha-MNN resulted in reducing the charge of low calorific propellants as much as 10%
- f) It seems that there were no restrictions regarding the composition of the propellants provided the ballistic properties and stabilities complied with specifications. The composition of propellants manufactured at different plants but intended for use in the same type and caliber of gun were not the same, although they all passed inspection tests.

Table 12 gives compositions of some single-base (nitrocellulose) propellants examined at Picatinny Arsenal.

(See next page)

Remarks on Table 42

The propellants listed in Table 42 contained a number of features which are worth noting, such as:

- a) None of these propellants contained a sufficient amount of non-volatile plasticizer to colloid the NC as effectively as is generally required. It is assumed that a volatile solvent was used in their manufacture which was later removed by drying. The amount of centralite present in some of these propellants would not be sufficient to gelatinize the high-nitrogen NC that was used in them but would be sufficient as a stabilizer
- b) Since an insufficient amount of centralite was present for the complete gelatinization of the NC, it is presumed that camphor was used in some propellants to superficially gelatinize the surface of the grains. Thus, it would act as a deterrent and cause the propellant to burn more progressively
- c) Several propellants were not only coated with graphite, but some of the graphite was incorporated in the grains. Coating with graphite was usually done for the following purposes: to decrease the possibility of ignition by static electricity, to make the grains more "free flowing" while loading the cartridge cases and to decrease (slightly) the initial rate of burning. Incorporation of graphite in the grains was apparently done to improve the burning characteristics of the propellant
- d) When graphite was used for coating only, it is probable that the grains were previously given a surface treatment with centralite or other stabilizer-gelatinizer as a deterrent coating to make the propellant more progressive burning
- e) Potassium salts (such as K sulfate) found in some German propellants, were evidently used as flash reducers. In some cases, however, markings on the bags included the abbreviation Man Pulv which stands for Manover Pulver Note These were usually rapid-burning propellants because they were porous. The porosity was obtained by incorporation and subsequent elimination of most of the potassium salt by leaching with water
- f) Some of the propellants examined at Picatinny Arsenal contained DPhA as well as DBulPh. As none of the German pre-WW II single-base propellants contained DPhA, it was presumed that these samples were reworked captured French or Belgian propellants
- g) One of the samples examined at the Arsenal contained a large amount of PETN (63.8%) dispersed through the mass of NC. None of the Allied propellants had such composition.

One of the single-base (nitrocellulose) propellants used during WW II was prep'd by gelatinizing a blend of two nitrocelluloses one of N content less than 12.5% and another of N content more than 13%. The gelatinizer used was an alcohol-acetone solution. See Nitrochemie Industrieanlagen A-G, Ger P 715,811 (1941), C A 38, 2211 (1944)

In Ref 1, p 41 is described Nitrocellulose-Blattchenpulver (Nitrocellulose Flake Propellant) which was prep'd by thoroughly mixing in the presence of ether-alcohol, 3 parts guncotton (Schiesswolle) of at least 13.1% N content, 1 part of soluble NC (Kollodiumwolle) of at least 12.6% content with 0.5% of stabilizer (such as diphenylamine) and 1% of flash reducer (such as Na oxalate). After the mass was flaked, the surface of the grains was treated with centralite and finely pulverized graphite. The flakes were about 0.3 mm thick and their surface was 1.3 mm².

Table 42
Single Base (Nitrocellulose)
Propellants of WW II

| Form | Composition, % | | | | | | | Uses |
|--------|----------------|----------|------|------|------|-----------|------------------------------|--|
| | NC | %N in NC | DPhA | Cent | Acar | Graph | Other Ingredients | |
| Square | 95.1 | 13.2 | - | - | 1.8 | - | Unac 3.1 | 7.63 mm Mauser |
| Square | 95.2 | 13.0 | - | - | 0.3 | - | Unac 4.3 | 7.92 mm AP |
| SP | 34.3 | 12.2 | - | 0.2 | - | 0.3 | PETN 63.8 | 7.92 mm AP |
| Square | 95.1 | 13.1 | - | - | 1.0 | 1.0 | Unac 1.4 | 7.92 mm AP |
| Square | 95.0 | 13.2 | - | - | - | - | Unac 2.9 | 7.92 mm AP |
| | | | | | | | Et carbamate & K sulfate 5.0 | 7.92 mm Ball, 7.92 mm Semi-AP, 7.92 mm AP and 7.92 mm HE |
| SP | 32 | 12.5 | - | 0.4 | - | 0.6 | PETN 60.0 | 7.92 mm HVAP |
| Square | 98.4 | 13.1 | 0.9 | - | - | - | Unac 7.0 | 7.92 mm Rifle |
| - | 99.5 | 13.0 | 0.5 | - | - | - | Unac 0.7 | Granade A/T |
| SP | 56.0 | 13.2 | - | Some | - | Graphited | - | 7.92/13 mm AP |
| Square | 94.1 | 12.7 | - | 2.6 | - | 0.3 | PETN 34.0 | 7.92 mm HVAP |
| SP | 95.0 | 12.2 | - | 2.0 | - | 0.1 | Cent & DNT 10.0 | 7.92 mm AP |
| | | | | | | | Unac 3.0 | 7.63 mm Mauser |
| | | | | | | | Unac 2.9 | Pistol, 9.0 mm |
| - | 95.0 | 13.1 | - | - | 1.7 | - | Unac 3.3 | Pistol and 28/20 mm APHV |
| - | 97.4 | 13.0 | - | - | 0.5 | - | Unac 2.1 | 9.0 mm Pistol |
| SP | 96.4 | 13.0 | - | - | 0.7 | 0.2 | Unac 2.7 | 9.0 mm Ball |
| | | | | | | | Unac 2.7 | 9.0 mm Ball, 9.0 mm Pistol and 50 mm Trench Mortar |
| SP | 95.0 | 12.9 | 0.5 | 2.0 | - | 0.4 | Unac 2.1 | 13.0 mm AP and 13.0 mm HE |
| SP | 93.7 | 13.1 | - | 1.95 | - | 0.25 | Camphor 0.95 | 20 mm AP |
| SP | 94.7 | 13.1 | 0.3 | - | - | 0.3 | Unac 3.15 | 20 mm HE Mauser |
| Square | 93.7 | 13.2 | 0.3 | 3.4 | - | 0.5 | DBuPh 0.1 | 20 mm HE Mauser |
| | | | | | | | Unac 4.6 | 20 mm HE Mauser |
| SP | 93.5 | 13.1 | - | 2.8 | 0.6 | 1.5 | K sulfate 0.3 | 20 mm HE Mauser |
| | | | | | | | Unac 1.8 | 20 mm Inc |
| SP | 93.3 | 13.1 | 0.2 | 1.2 | - | 0.3 | K sulfate 1.1 | 20 mm Solothurn |
| | | | | | | | Unac 0.5 | 20 mm Solothurn |
| SP | 94.1 | 13.0 | 0.4 | 2.4 | - | 0.4 | Unac 1.0 | 20 mm Solothurn |
| | | | | | | | Unac 4.0 | 20 mm Solothurn |
| SP | 93.1 | 13.1 | 2.3 | - | - | 0.6 | Unac 2.7 | 13.0 mm AP, 13.0 mm HE, 15.0 mm HE and 28/20 mm APHV |
| | | | | | | | Camphor 1.0 | 20 mm APHV, 20 mm AP, 20 mm HE and 20 mm Inc |
| Tube | 98.1 | 13.1 | - | - | 0.02 | - | Unac 1.88 | 50 mm Trench Mortar |
| SP | 94.5 | 13.1 | - | - | - | 0.8 | Camphor 1.3 | 75 mm APC and 75 mm HE |
| SP | 96.1 | 13.1 | - | - | 0.5 | - | Unac 3.4 | 75 mm HE |
| Square | 93.9 | 13.0 | 0.3 | 2.6 | - | - | Unac 3.4 | 75 mm HE |
| Square | 98.4 | 13.1 | 0.9 | - | - | 1.0 | Unac 2.2 | 80 mm Expulsion Powder |
| | | | | | | | Unac 0.7 | 7.92 mm Rifle Grenade (A/T) |

Abbreviations: See under Table 44.

Compositions listed in Table 43 are for double-base (NC-NG) propellants analyzed at Picatinny Arsenal during WW II.

(See next page).

Table 43
Double-Base (NC-NG) Propellants

| Form | Composition, % | | | | | | | Uses | |
|--------|----------------|----------|------|------|------|-------------------|-------------------|---|--|
| | NC | %N in NC | NG | Cent | Acar | Graph | Other Ingredients | | |
| Tube | 58.1 | 12.5 | 37.2 | 3.9 | - | - | - | - | - |
| Tube | 69.7 | 11.9 | 27.3 | 1.5 | 0.2 | - | - | K sulfate 0.3 Unac 0.5 | 37 mm APHV |
| SP | 63.7 | 11.8 | 28.5 | 6.3 | - | - | - | K sulfate 0.6 Unac 0.7 | 37 mm APMB |
| Strip | 64.6 | 12.3 | 30.0 | 6.0 | - | 0.1(incorporated) | - | Unac 1.5 | 37 mm HoC |
| Strip | 64.0 | 12.3 | 30.0 | 6.0 | - | - | - | - | 37 mm Czech |
| Strip | 63.0 | 12.2 | 28.0 | 9.0 | - | - | - | - | 40 mm Czech |
| Strip | 63.1 | 12.4 | 30.3 | 6.0 | - | - | - | - | 47 mm AP |
| Strip | 62.9 | 12.7 | 29.1 | 7.3 | - | - | - | K sulfate Unac 0.3 | 47 mm HE |
| Tube | 61.1 | 12.0 | 22.4 | 12.7 | - | - | - | K sulfate 0.3 Unac 0.4 DNT 0.9 Vaseline 1.5 K salts 1.4 | 47 mm APCHE and APKN 50 mm APC |
| Disc | 59.6 | 12.9 | 39.0 | - | 0.7 | - | - | - | - |
| Disc | 59.5 | 13.0 | 38.7 | - | 0.8 | 0.2(incorporated) | - | Unac 0.6 Unac 0.8 | 75 mm HE How 75 mm HoC (Semi-fixed) |
| Square | 59.5 | 12.2 | 38.6 | 1.6 | - | 0.3 | - | - | 80 mm HE Mortar |
| Disc | 59.2 | 13.0 | 38.5 | - | 0.6 | 0.3 | - | Unac 1.4 | 80 mm HE Mortar |
| Disc | 61.5 | 12.9 | 38.1 | - | - | - | - | DPHuret 0.4 | 80 mm CM |
| Square | 58.3 | 13.1 | 39.0 | 0.8 | - | 0.2 | - | Unac 1.7 | 80 mm HE |
| Square | 59.6 | 13.0 | 38.8 | - | 0.8 | - | - | DNT 0.4 Unac 0.4 | 105 mm How |
| Square | 59.4 | 12.9 | 31.4 | - | 8.9 | - | - | Unac 0.3 | 105 mm How |
| Square | 53.7 | 13.0 | 44.4 | - | 1.1 | 0.5 | - | Unac 0.8 | 150 mm How (Base Charge) |
| Square | 56.8 | 13.1 | 40.8 | 0.3 | 0.7 | 0.1 | - | Unac 1.3 | 155 mm How and 80 mm HE |
| Square | 59.0 | 13.1 | 39.0 | - | 1.0 | - | - | Unac 1.0 | 155 mm How |
| Disc | 56.5 | 13.3 | 41.6 | - | 0.8 | 0.2 | - | Unac 0.9 | Miscellaneous Mortars |
| Flake | 59.9 | 13.36 | 39.0 | 0.9 | - | 0.2 | - | - | 80 mm Mortar |
| Square | 62.5 | 12.0 | 33.0 | - | 0.2 | 0.1 | - | DPHuret 1.5 EtPhUret 1.5 Unac 1.2 | 150 mm Rocket |

Abbreviations: See under Table 44

Remarks on Table 43:

The double-base nitrocellulose-nitroglycerin propellants listed in Table 43 were somewhat different from the American and British propellants, as can be seen from the following remarks:

a) In cases in which large amounts of centralite were present, it served not only as a stabilizer, but also as a plasticizer, especially for low-nitrated NC. The amount of NG in such propellants was correspondingly decreased. In other cases where the amount of centralite was small, or even absent, the amount of NG was increased.

b) It has been shown that when centralite is used in large amounts, it also acts as a flash reducing agent. The same applies to acardite (asymmetrical diphenylurea). When acardite was used as a stabilizer, an amount as low as 0.8% was sufficient.

c) Vaseline, present in some propellants, was supposed to act primarily as a cooling agent (to lower the temperature

of combustion and to reduce erosion). It also acted as a stabilizer to a certain extent because the unsaturated hydrocarbons present in vaseline combine with the oxides of nitrogen and thus stabilize the powder. It has been found, however, that vaseline is not particularly effective in reducing hygroscopicity.

d) Graphite was used for coating some propellants (see Remarks (c) and (d) to Table 42, but in propellants of large grain size, such as the 155 mm, 150 mm and 120/45mm weapons, no graphite coating was used.

e) As in some other German propellants, graphite was used not only as a coating agent but it was also distributed throughout the mass of material. [See Remark (c) on Table 42].

Table 44 gives compositions of some double-base propellants based on DEGDN (diethylneglycoldinitrate) and on triple-base (NC-DEGDN-NGu) propellants. (See next page).

Table 44

Double-Base (NC-DEGDN) and Triple-Base (NC-DEGDN-NGu) Propellants

| Form | Composition, % | | | | | | | Uses | | |
|--------|--|----------|-------|------|------|----------------|-------------------|------|---|--|
| | NC | %N in NC | DEGDN | Cent | Acar | Graph | Other Ingredients | | | |
| Tube | 66.1 | 11.9 | 30.2 | 1.8 | 0.2 | - | Unac | 1.7 | 37 mm AP Shell | |
| Tube | 65.1 | 12.1 | 31.5 | 2.7 | - | 0.3 | K sulfate | 0.4 | 37 mm HE | |
| Tube | 66.3 | 11.8 | 29.4 | 2.7 | - | 0.2 | Unac | 1.4 | 47 mm APHV | |
| Tube | 61.4 | 11.8 | 29.8 | 8.4 | - | - | Unac | 0.4 | 50 mm AP | |
| Tube | 61.5 | 12.0 | 26.0 | 7.4 | - | 0.3 | Vaseline | 3.5 | | |
| | | | | | | | K salts | 0.5 | | |
| Tube | 68.7 | 11.8 | 28.4 | 1.5 | 0.1 | - | Unac | 0.8 | 50 mm APHV | |
| | | | | | | | K salts | 0.4 | | |
| Square | 38.4 | 12.6 | 32.0 | - | - | 0.3 | Unac | 0.9 | 50 mm HE | |
| | | | | | | (incorporated) | NGu | 29.3 | | |
| | | | | | | | K sulfate (added) | 2.7 | | |
| Tube | 60.0 | 13.1 | 38.4 | - | 0.7 | 0.1 | Unac | 0.8 | 50 mm HE | |
| Tube | 97.1 | 12.9 | 0.9 | 0.1 | - | 0.3 | Unac | 1.6 | 50 mm TM | |
| Tube | 65.1 | 12.4 | 32.7 | 0.5 | 0.7 | - | Unac | 1.0 | 50 mm APHV | |
| Tube | 66.4 | 11.8 | 29.8 | 2.2 | - | 0.2 | K sulfate | 0.5 | 50 mm APHV, 47 mm APHV, 37 mm HE and 37 mm AP | |
| | | | | | | | Unac | 0.9 | | |
| - | 37.6 | 12.2 | 29.8 | - | - | 0.1 | NGu | 31.4 | 42/28 mm Tapered Bore and 42/28 mm APHV | |
| | | | | | | | Unac | 1.1 | | |
| Tube | 65.0 | 11.9 | 23.2 | 8.8 | - | 0.1 | K sulfate | 1.5 | 75 mm AP | |
| | | | | | | | Unac | 1.4 | | |
| Tube | 39.0 | 12.5 | 30.5 | - | - | 0.1 | NGu | 28.9 | 75 mm HE | |
| | | | | | | | Unac | 1.5 | | |
| Tube | 62.3 | 13.0 | 34.4 | - | 0.4 | 0.1 | K sulfate | 2.5 | 75 mm HE | |
| | | | | | | | Unac | 0.3 | | |
| Strip | 63.5 | 12.4 | 33.9 | 1.4 | 0.4 | 0.1 | Unac | 0.7 | 75 mm HoC, Semi-Fixed | |
| Strip | 59.6 | 12.8 | 38.6 | - | - | 0.2 | EtPhUret | 1.2 | 75 mm HoC, Semi-Fixed | |
| | | | | | | | Unac | 0.4 | | |
| Tube | 60.3 | 11.9 | 28.2 | 7.3 | - | 0.4 | Vaseline | 2.0 | 75 mm Tank Gun | |
| | | | | | | (incorporated) | K sulfate | 1.1 | | |
| | | | | | | | Unac | 0.7 | | |
| Square | 38.4 | 12.4 | 23.5 | - | - | 0.2 | NGu | 29.0 | 75 mm HEHoC, 75 mm HE Pak 40 and 50 mm HE | |
| | | | | | | (incorporated) | Unac | 0.9 | | |
| Square | 62.0 | 12.4 | 26.0 | 7.6 | 0.2 | 0.2 | EtPhUret | 3.1 | 76.2 mm AP | |
| Note: | 76.2 mm and some 88 mm weapons were those captured in Russia | | | | | | | Unac | 0.9 | |
| Flake | 38.6 | 12.2 | 30.9 | - | - | 0.3 | NGu | 30.2 | 76.2 mm HE | |
| Tube | 67.2 | 11.8 | 28.2 | 3.3 | - | - | Unac | 1.3 | 88 mm AP | |
| Tube | 43.0 | 11.0 | 18.5 | - | 0.2 | - | NGu | 31.2 | 88 mm AP | |
| | | | | | | | DPhUret | 3.2 | | |
| | | | | | | | EtPhUret | 2.2 | | |
| | | | | | | | Unac | 1.7 | | |
| Tube | 66.7 | 11.8 | 28.2 | 3.3 | - | - | Unac | 1.8 | 88 mm HE | |
| Square | 61.6 | 13.1 | 37.3 | 0.3 | 0.4 | 0.1 | Unac | 0.3 | 150 mm How (Zones 1-6) | |
| Square | 62.1 | 13.0 | 36.6 | 0.4 | 0.3 | 0.1 | Unac | 0.5 | 150 mm How (Zone 7) | |
| Disc | 59.6 | 13.0 | 38.7 | 0.4 | 0.5 | 0.2 | Unac | 0.6 | 150 mm How (Zones 7&8) | |
| Tube | 59.6 | 12.6 | 33.6 | - | - | 0.2 | DPhUret | 1.5 | 75 mm Rocket | |
| | | | | | | | EtPhUret | 3.0 | | |
| | | | | | | | Unac | 2.1 | | |
| Tube | 61.1 | - | 33.3 | - | 2.1 | 0.2 | Unac | 3.3 | 150 mm Rocket | |
| Tube | 59.6 | 12.5 | 34.8 | - | 0.2 | 0.2 | EtPhUret | 1.2 | 210 mm Rocket | |
| | | | | | | | DPhUret | 2.0 | | |
| | | | | | | | Carnauba wax | 0.3 | | |
| | | | | | | | Unac | 1.7 | | |
| Tube | 60.0 | - | 35.4 | - | - | - | Unac | 4.6 | 300 mm Rocket | |

(See also G Pulver and Gudpulver).

Abbreviations: AA Antiaircraft; AC Aircraft; Acar Acaridite; Am Ammonium; AP Armor-piercing; A/P Antipersonnel; APC Armor-piercing, Capped; A/T Antitank; Cent Centralite; CM Chemical Mortar; DBuPh Dibutylphthalate; DEG Diethylene glycol; DEGDN Diethylene glycol Dinitrate; DNT Dinitrotoluene; DPhA Diphenylamine; DPhUret Diphenylurethane; Et Ethyl; EtPhUret Ethylphenylurethane; Flok Ger designation for AA; Graph Graphite; HE High Explosive; HoC Hollow Charge; shaped charge; HV Hyper-Velocity; Hydrocel Hydrocellulose; Inc Incendiary; K (Kannone) Cannon; K salts Potassium salts; LC Long Case; MB Monoblock; MNT Mononitrotoluene; N Nitrogen; NC Nitrocellulose; NG Nitroglycerin; NGu Nitroguanidine; Pok German designation of A/T; PETN Pentaerythritol Tetranitrate; RN Round Nose; SC Short Case; SP Single Perforation; T Tracer; TEG Triethylene glycol; TEGDM Triethylene glycol Dinitrate; TM Trench Mortar; TNT Trinitrotoluene; Unac Unaccounted.

Remarks on Table 44 (See previous page).

Although the above DEGDN and NGu plus DEGDN propellants were similar in composition to NG propellants listed in Table 43, they had some features which are worth noting, such as:

- There was a definite relationship between the percentage of NC and DEGDN used, as the percentage of NC was decreased the amount of DEGDN (which has about the same potential as NG) was increased. It was also noted that decreasing amounts of centralite were accompanied by increasing amounts of DEGDN.
- The use of low nitrogen content NC, such as 11.8-12%, in DEGDN propellants may be explained by the fact that high N content NC is much more difficult to gelatinize with DEGDN.
- Several propellants contained about 30% NGu and only about 40% of NC, without any stabilizer. In most of these compositions graphite did not serve for coating but was uniformly distributed throughout the grains. It is to be noted that NGu does not gelatinize NC even of low N content.
- All the DEGDN propellants, especially those containing NGu were much cooler burning than the corresponding NG propellants.
- From the American point of view the DEGDN propellants have the following disadvantages over propellants based on NG:
 - They are more volatile
 - Less sensitive to flame and thus more difficult to ignite
 - More toxic to personnel handling them
 - They contain an ingredient (DEGDN) which is more difficult to stabilize than NG.

H. Muraoui et al, *Mém poud* 35, 280 (1953), gives the composition of a German propellant, used in rounds for 50 mm airplane cannon, as follows: NC (N content 11.81%) 63.5, DEGDN 26.5, centralite 8.0 and vaseline 2.0%.

Some information on DEGDN-NC propellants prepared at the Düneberg Fabrik, D A-G may be found in Ref 7. Two of these propellants used in cannons are listed in Table 45a.
(See next column).

The same Ref 7 gives the composition and properties of the DEGDN propellant manufd by the Wolff Co Plant at Bömlitz, near Walsrode: NC (N content 12.15%) 28.6, DEGDN 17.4, DPhA 0.5, Cent I 0.5 and TNT 53.0%. Oxygen balance -16.51% and calorific value 750 kcal/kg.

Some double-base (NC-DEGDN) and triple-base (NC-DEGDN-NGu) propellants manufactured at the Düneberg Fabrik, Dynamit A-G were described in Ref 5. Their composition is given in Table 45b.

(See next page).

Table 45a
NC-DEGDN Propellants of Düneberg Fabrik D A-G

| Composition and properties | German Designation | |
|----------------------------|--------------------|--------|
| | S6702 | B14232 |
| NC | 29.45 | 48.59 |
| % N in NC | 12.0 | 12.5 |
| DEGDN | 29.45 | 26.16 |
| Am nitrate | 40.00 | - |
| Dicyandiamide | - | 25.00 |
| Centralite I | 1.00 | - |
| MNN | - | 1.00 |
| Mg oxide | - | 0.15 |
| Graphite | - | 0.10 |
| Moisture | 1.10 | 0.80 |
| Total | 101.00 | 101.90 |
| Oxygen Balance, % | +3.29 | -22.47 |
| Calorific Value, kcal/kg | 1143 | 719 |

Abbreviations: (See under Table 44).

In Ref 6 is described the manuf of NC and propellants at the Krümmel Fabrik, Dynamit A-G, while in Ref 8 is described the manufacture of NC and propellants at the following plants: Troisdorf Fabrik D A-G, Ebenhausen Fabrik D A-G, Rottweil Fabrik D A-G and Bömlitz Fabrik of Wolff Co.

In the prepn of propellants at the Rottweil Plant the blend consisted of 20 parts NC, N content 12.5%, and 80 parts of NC, N content 13.3%.

Table 46 gives some properties, including the burning characteristics, of several German propellants examined at Picatinny Arsenal during WW II (Refs 4, 10a, 10f and 10g).
(See next page).

Remarks on Table 46:

- In the compositions given in Table 46 only the main ingredients are included. Other components, such as stabilizers, graphite, etc were given in Tables 42, 43 & 44.
- Force of a Propellant ($H \times V$) is a function of its chemical composition.
- Quickness (Δ) of a Propellant is a function of granulation as well as of its composition. The most important variables are total volatile content and web size. The quickness is approximately inversely proportional to the web size. In small arms propellants, the concentration gradient of the deterrent coating is used to alter the quickness.
- The relative quickness of propellants is obtained by comparing their burning rates with the rate of a standard. If comparison is made between a German propellant and a standard American propellant, the results are likely to be misleading since the German guns (made with a heavy breech) used propellants designed to develop the maximum pressure rapidly and after the shell had travelled only a

Table 45b

Double-Base (NC-DEGDN) and Triple Base (NC-DEGDN-NGu) Propellants of Düneberg Fabrik, DA-G

| Form | Compositions, % | | | | | | | | | | Calorific value kcal/kg | Uses | |
|-------|-----------------|----------|-------|-------|-------|------|-------|------|-------------------|-------|-------------------------|------|--|
| | NC | %N in NC | DEGDN | NGu | Cent | Acar | Graph | MgO | Other Ingredients | | | | |
| Flake | 63.65 | 13.0 | 35.80 | - | - | 0.50 | - | 0.05 | - | - | - | - | Various Hows |
| Flake | 54.40 | 13.0 | 44.50 | - | - | 0.50 | 0.05 | 0.05 | K sulfate | 0.50 | - | - | Various Hows |
| Flake | 38.03 | 13.0 | 31.12 | 30.00 | - | 0.50 | 0.10 | 0.25 | - | - | - | - | Various Hows |
| Tube | 67.65 | 12.0 | 29.00 | - | 3.00 | - | 0.10 | 0.25 | - | - | - | 825 | 88 mm AA and Heavy 100 mm Gun (K18) (Army) |
| Tube | 68.22 | 12.0 | 29.23 | - | 1.70 | 0.50 | 0.10 | 0.25 | - | - | - | 870 | 37 mm AA and 37 mm A/T (Army) |
| Tube | 62.33 | 12.0 | 26.72 | - | 8.00 | - | 0.10 | 0.25 | Vaseline | 1.80 | 760 | - | Heavy Army Field Hows |
| Tube | 61.53 | 12.0 | 26.37 | - | 7.50 | - | 0.10 | 0.25 | Phthalate | 0.80 | - | - | 100 mm Army Gun (K 18) |
| Tube | 64.08 | 12.0 | 27.47 | - | 5.35 | - | 0.10 | 0.25 | Vaseline | 1.60 | - | - | Hows |
| Tube | 43.51 | 12.0 | 18.64 | 30.00 | - | 0.50 | 0.10 | 0.25 | Phthalate | 0.65 | - | - | 88 mm Army AA Gun |
| Tube | 39.48 | 12.0 | 16.92 | 30.00 | - | - | 0.10 | 0.25 | K sulfate | 2.00 | - | - | 88 mm Army AA HE Gun |
| Tube | 69.92 | 12.0 | 14.83 | - | 3.00 | - | 0.10 | 0.15 | DPHuret | 3.25 | 750 | - | 88 mm Army AA and AP Guns |
| Tube | 60.55 | 12.0 | 25.95 | - | 3.75 | - | 0.10 | 0.15 | EtPhUret | 3.75 | 730 | - | 88 mm Army AA and AP Guns |
| Tube | 44.00 | 12.0 | 18.85 | 20.00 | - | 0.40 | 0.10 | 0.15 | DPHuret | 4.25 | 730 | - | 88 mm AA and other Army Guns |
| Tube | 69.38 | 12.2 | 25.27 | - | 5.00 | - | 0.10 | 0.25 | K nitrate | 4.00 | 820 | - | Naval Guns |
| Tube | 65.53 | 12.2 | 23.87 | - | 9.00 | - | 0.10 | 0.25 | DNT | 10.00 | 730 | - | Naval Guns |
| Tube | 65.71 | 12.2 | 23.94 | - | 2.50 | 0.50 | 0.10 | 0.25 | alpha-MNN | 2.00 | 730 | - | Naval Guns |
| Tube | 58.55 | 12.2 | - | - | 12.00 | - | 0.10 | 0.25 | Hydrocell | 3.00 | 650 | - | Naval Guns |
| Tube | 35.50 | 12.2 | 21.75 | 40.00 | - | 0.50 | 0.10 | 0.25 | DNT | 4.00 | - | - | 37 mm Naval Gun |
| Tube | 42.45 | 12.0 | 18.20 | 25.00 | - | - | 0.10 | 0.25 | alpha-MNN | 2.50 | - | - | Naval Guns |
| - | 60.17 | 12.6 | 35.33 | - | - | - | - | 0.25 | DPHuret | 1.50 | - | - | Naval Guns |
| - | 59.03 | 12.6 | 34.82 | - | - | 0.50 | - | 0.25 | EtPhUret | 1.50 | - | - | Naval Guns |
| - | | | | | | | | | K sulfate | 4.00 | - | - | Universal composition for Rocket Launchers |
| - | | | | | | | | | Hydrocel | 1.50 | 900 | - | Universal composition for Rocket Launchers |
| - | | | | | | | | | DPHuret | 1.00 | - | - | Universal composition for Rocket Launchers |
| - | | | | | | | | | EtPhUret | 1.40 | - | - | Universal composition for Rocket Launchers |
| - | | | | | | | | | IG Wax E | 0.35 | - | - | Universal composition for Rocket Launchers |
| - | | | | | | | | | K nitrate (added) | 0.80 | - | - | Universal composition for Rocket Launchers |
| - | | | | | | | | | Hydrocel | 3.00 | 865 | - | 300 mm Rocket Launcher |
| - | | | | | | | | | EtPhUret | 1.90 | - | - | 300 mm Rocket Launcher |
| - | | | | | | | | | Vaseline | 0.50 | - | - | 300 mm Rocket Launcher |

Abbreviations: See under Table 44.

Table 46
Properties of Some German Propellants

| Form | Composition, % | | | | | Uses | Some Properties | | | | Burning Characteristics | | |
|----------|----------------|----------|------|-------|------|--------------------------|------------------------|--------|-------|--------------|-------------------------|------|-----|
| | NC | %N in NC | NG | DEGDN | NGu | | Δb (in inches) | H | V | Force (litV) | Δ | A | C |
| SP Tube | 63.6 | 11.8 | 28.5 | - | - | 37 mm HE HoC | .0304 | 881.5 | 776 | 674,846 | 6.62 | - | - |
| Cord | 65.7 | 13.08 | 20.8 | - | - | Antitank Gun | .0628 | 890 | 842 | 749,386 | - | - | - |
| SP | 59.6 | 12.5 | - | 38.8 | - | Rocket | 2.46 | 829.7 | 705.8 | 585,602 | 5.53 | - | - |
| SP | 63.0 | 11.9 | - | 26.5 | - | 100 mm K 18 | .0337 | 740.1 | 407.4 | 597,556 | 5.08 | - | - |
| SP | 38.5 | 11.3 | - | 16.5 | 34.8 | 88 mm HE HoC | .0577 | 706.9 | 680.1 | 466,762 | 1.2 | - | - |
| Square | 36.0 | 12.0 | - | 31.0 | 32.2 | 76.2 mm A. T | .0209 | 877 | 777 | 681,429 | - | - | - |
| SP | 65.0 | 11.93 | - | 23.2 | - | 75 mm AP HoC | .0600 | 712.1 | 722.3 | 512,349 | 4.21 | - | - |
| Strip | 63.5 | 12.4 | - | 33.9 | - | 75 mm HE HoC | .203 | 893.8 | 711.3 | 635,760 | 7.0 | - | - |
| Square | 39.4 | 12.9 | - | 30.9 | 28.9 | 75 mm HE HoC | .0249 | 910.6 | 706.2 | 643,066 | 7.26 | - | - |
| Cylinder | 59.6 | 12.55 | - | 33.6 | - | 75 mm Leaflet Rocket | .333 | 856.6 | 21.0 | 617,608 | - | - | - |
| Square | 40.0 | 12.4 | - | 30.3 | 28.7 | 75 mm HE Tank | .0261 | 991 | 767 | 691,067 | - | - | - |
| SP | 37.4 | 12.2 | - | 30.2 | 31.3 | 42/28 mm AP HV | .0279 | 883.2 | 716.2 | 632,228 | 5.6 | - | - |
| SP | 94.8 | 12.8 | - | - | - | 28/20 mm AP HV | .0237 | 829.7 | 705.8 | 585,602 | 0.94 | - | - |
| SP | 92.75 | 13.03 | - | - | - | 28/20 mm AP HV | .0211 | 829.7 | 705.8 | 585,602 | 0.94 | - | - |
| Square | 53.15 | 13.0 | 44.4 | - | - | 150 mm How (Base Charge) | .0067 | 1235.1 | 588.6 | 727,333 | 9.9 | .05 | 211 |
| Square | 61.64 | 13.1 | - | 37.3 | - | 150 mm How (1-6 zones) | .0484 | 1015.9 | 685.2 | 696,094 | 8.5 | .017 | 167 |
| Square | 62.13 | 13.0 | - | 36.6 | - | 150 mm How (7 zone) | .0313 | 993.6 | 696.7 | 692,242 | 8.4 | .009 | 144 |
| SP Disc | 59.6 | 13.0 | - | 38.7 | - | 150 mm How (7-8 zones) | .0722 | 989.4 | 704.5 | 697,037 | 8.8 | .21 | 158 |

Abbreviations: A Constant called Vivacity, C Rate of evolution of hot gases at a pressure of 20,000 psi in liters at atmospheric pressure / sq cm of surface / second; H Heat of Combustion in kcal/kg; P Pressure of propellant gases in psi; V volume of gases liberated in l/kg; Δ Burning rate (quickness) of the propellant at 20,000 psi in inches/sec; (HxV) Force or Thermodynamic Potential.

Other abbreviations are given under Table 44.

short distance along the bore of the gun. On the other hand, in American guns with a lighter breech the propellants are designed to develop the maximum pressures more slowly and after the shell has travelled a greater distance along the bore of the gun

e) In the relation of quickness to composition, it may be noted that the single-base propellants are the slowest and are comparable to those double-base propellants which contain NGu. Propellants containing NG are usually the fastest, followed by DEGDN propellants. In some cases, however, DEGDN propellants are faster than those containing NG. This is usually the case when the NC in a DEGDN propellant is of considerably higher nitrogen content than that used in a corresponding NG propellant
f) The burning rate of the German 210 mm rocket propellant was given equal to: $0.35 + (29.4 \times 10^{-5} P)$ while the corresponding value for the standard American double-base 7/8" stick propellant is: $48.6 \times 10^{-5} P$. This means that the rate for the American propellant is about 65% greater than for the German propellant

g) Experimental procedures for the determination of the burning rates of propellants are described in Pic Arsn Tech Rept 1235 (1943)

h) Methods of computation of properties of propellants are given in the DuPont, Burnside Laboratory Memorandum Report 31.

References (Propellants):

1) A.Marshall, Explosives, Churchill, London, v1 (1917)

v 2 (1917) and v 3 (1932)

2) H.Brunswig, Das rauchlose Pulver, W. de Gruyter: Berlin (1926)

3) A.Stettbacher, Schiess- und Sprengstoffe, J.A.Barth, Leipzig (1933)

4) Collective, PB Rept 11,544 (1945)

5) O.W.Strickland et al, PB Rept 975 (1945)

6) L.Nutting et al, PB Rept 16,666 (1945)

7) F.J.Krieger, M.Plesset, PB Rept 7826 (1945)

8) R.Ashcroft et al, BIOS Final Report 833 (1946), Item 2

8a) H.H.MPike, CIOS Report 31-68 (1946), Report on Visit to Duneberg Factory of D A - G

9) A.Stettbacher, Spreng- und Schiessstoffe, Rascher, Zürich (1948)

10) Picatinny Arsenal Technical Reports:

a) Collective, 1282 (1943) (Foreign Propellants)

b) A.B.Schilling, 1358 (1944) (Propelling Charge for 155 mm Separate Loading Ammunition)

c) A.B.Schilling, 1439 (1944) (Separate-Loading Propelling Charge Assembly for 105 mm Recoilless Gun, LG 41)

d) J.P.Wardlaw, 1443 (1944) (Propelling Charge for Separate-Loading 100 mm Gun, K 18)

e) A.B.Schilling, 1453 (1944) (Propelling Charge for 210 mm Separate-Loading Ammunition)

f) Collective, 1456 (1944) (Foreign Propellants)

g) W.R.Tomlinson, Jr, 1555 (1945) (Chemical Composition of Material used in German Ammunition)

Propellants: Artillery. According to H.H.M. Pike, CIOS Report 31-68 (1946), pp 4-8 and tables, the following types of propellants were used by the Germans in their artillery weapons:

- A. Nitrocellulose (NC) Propellant, designated as NzP (Nitrozellulose Pulver) was of the following varieties:**
- NzBIP (Nitrozellulose Blättchenpulver)** was used in 105 mm light field howitzer
 - NzManNP (Nitrozellulose Manöver Nudelpulver)** was used in blank (practice) ammo
 - NzRP (Nitrozellulose Röhrenpulver)** was used in some 20 mm & 30 mm AA guns, 75 mm tank and self-propelled guns, 75 mm Navy gun C/34, 105 mm casemate and tower gun and 105 mm light field howitzer 18
- B. Nitroglycerin (NG) Propellant, designated as NgIP (Nitroglycerin Pulver) was of the following varieties:**
- NgIBIP (Nitroglycerin Blättchenpulver)** was used in 75 mm mountain gun 15 and 80 mm heavy mortar 34
 - NgPIP (Nitroglycerin Plättchenpulver)** was used in 75 mm infantry gun 18 and in 75 mm tank and self-propelled guns
 - NgIRgP (Nitroglycerin Ringpulver)** was used in 80 mm heavy mortar 34
 - NgLRP (Nitroglycerin Röhrenpulver)** was used in 75 mm Navy gun C/34, 75 mm mountain gun 15 and 88 mm torpedoboat gun
- C. Diethyleneglycol Dinitrate (DEGDN) Propellant, designated as DigIP (Diglykol Pulver) was of the following varieties:**
- DigIBIP (Diglykol Blättchenpulver)** was used in 50 mm casemate and tower gun, 105 mm light howitzer 18, 105 mm mountain howitzer, 150 mm heavy infantry gun 33, and 150 mm heavy howitzer 18
 - DigILgP (Diglykol Leuchtgeschoss Pulver)** was used for propelling star shells in 88 mm Navy guns C/30, C/32 & C/35, 105 mm Navy guns C/28, C/32 & C/33, 88 mm torpedoboat gun, 105 mm Navy guns C/28, C/32 & C/33, 128 mm Navy gun C/34, 149.1 mm U-boat gun L/45, 149.1 mm Navy guns C/25, C/28, L/45, & L/55, 172.6 mm Navy gun L/40, 203 mm Navy gun C/34a, and 209.3 mm Navy gun L/45
 - DigLPIP (Diglykol Plättchenpulver)** was used in 75 mm field gun 18
 - DigLRgP (Diglykol Ringpulver)** was used in 105 mm mountain howitzer, 150 mm heavy howitzer 18, and 210 mm mortar
 - DigLRP (Diglykol Röhrenpulver)** was used in 37 mm AA guns, 37 mm A/T guns, 42/28 mm tapered-bore gun, 50 mm A/T guns, many 75 mm Army guns, and 88 mm 105 mm, 128 mm, 149.1 mm Navy, 150 mm Army, 172.6 mm Navy, 203 mm Navy, 203 mm Navy, 209.3 mm Navy, 210 mm, 238 mm, 240 mm 283 mm Navy, 280 mm, 283 mm, 305 mm, 350 mm, 380 mm, and 420 mm weapons
 - DigLStrP (Diglykol Streifenpulver)** was used in 42/28 mm tapered bore gun
- D. Triethyleneglycol Dinitrate (TEGDN) Propellant, designated as TrigIP (Triglykol Pulver), was used instead of DigIP in hot climates because Diglykolnitrat (DEGDN) is very volatile. One such propellant TrigILgP (Triglykol Leuchtgeschoss Pulver) was used by the Navy in star shell ammo**
- E. Nitroguanidine (NGu) Propellant, designated GuP (Gudolpulver), existed in the following varieties:**
- GuBIP (Gudol Blättchenpulver)** was used in 50 mm A/T gun, 105 mm mountain howitzer, 150 mm heavy infantry gun 33, 150 mm heavy howitzer 18 and 150 mm heavy howitzer for fortification
 - GuRgP (Gudol Ringpulver)** was used in 210 mm mortar 18
 - GuRP (Gudol Röhrenpulver)** was used in 42/28 mm tapered-bore gun, 88 mm tank and A/T gun 43, 105 mm recoilless gun, 128 mm AA gun 40, 128 mm tank destroyer gun 44, 211 mm gun 12, 380 mm Siegfried gun, 406.4 mm Adolf gun, 533.4 mm gun called Gerät 36 and 800 mm Sevastopol gun
- F. Ammonium Nitrate (AmN) Propellant, designated as Ammon P (Ammonpulver), was developed towards the end of WW II to combat shortages of some materials. The propellant AmmonStrP (Ammonstreifenpulver) was in the shape of strips, 500x20x2.3 mm, and its composition was: NC (12%) 22, DEGDN 22, Am nitrate 50, hydrocellulose 5 and central-lite 1%. The strips were coated with a regular DigIP in order to overcome the hygroscopicity**

Table 47 gives composition and some properties of most common artillery propellants used during WW II by the Germans. (See following pages).

Propellants, Internal Ballistic Data is given in tables at the end of CIOS Report 31-68 (1946).

Propellants, Rocket. See Rocket Propellants.

Propellants, Stability of. The stability characteristics of some German propellants were determined during WW II at Picatinny Arsenal and described in Technical Report 1456 (1944).

In cases where sufficient material was available, both the 120° and 134.5° Heat Tests were made. The results of tests showed a tendency toward greater stability for those propellants which contained a stabilizer-gelatinizer (such as centralite) in combination with another stabilizer, such as acardite.

Sufficient amounts of propellants were not available for reaching a definite conclusion concerning the merits of disubstituted urethanes in combination with acardite.

Propellants containing NG, DEGDN and NGu-DEGDN proved to be of satisfactory stability, judging by the 120° Heat Test of the U S Army (the test paper should not turn a salmon pink color in less than 40 minutes).

As to the single-base propellants, only a few of the German propellants met the U S Army Specification which requires that the test paper in the 134.5° Heat Test shall not turn salmon pink in color in less than 45 minutes.

Propellant Charge in Fixed and Semi-Fixed Ammunition. According to E. Englesburg (The Ordnance Sergeant, May 1944, p 321), German propelling charges may be subdivided into two main classes:

- Class No 1 (Fixed round)** used flaked and tubular propellants. In this case, the grains were packed in a silk bag with an igniter bag sewed to the end facing the primer. With tubular grains, they could be either packed in a silk bag (as above) or tied in a bundle by means of a fine twine. The lower end of the bundle of tubes was placed in a short silk bag, which had sewn to its bottom, a coarser silk bag containing igniter composition
- Class No 2 (Semi-fixed round)** consisted of base and increment charges (zones) contained in silk bags. An igniter bag was sewn to the base charge. The charges were shipped inside the cartridge case and if there were too many increments for the desired range some or all increments, but not the base charge, could be removed (before firing) and substituted by the "distance piece" (q v). In case of long range firing a super charge, packed in a cardboard or metal container, was provided. Some propellant charges had a bag with a flash reducing agent (which was placed between the propellant and projectile) while others had a decoppering agent such as lead wire wrapped around the bag.

Propellant Grains and Their Dimensions. The following typical German propellants are listed by H.H.M. Pike in CIOS Report 31-68 (1946), pp 4-5 and tables:

- Tubular (Röhrenpulver), designated as RP 40 (810 x 13x4.3)** consisted of tubes 810 mm long having external and internal diameters of 13 mm and 4.3 mm respectively.
- Strip (Streifenpulver), designated as StrP (100 x 10 x 0.6)** consisted of grains 100 mm long, 10 mm wide and 0.6 mm thick
- Flake (Blättchenpulver), designated as BIP (3 x 3 x 0.8)** consisted of grains 3 mm long, 3 mm wide and 0.8 mm thick
- Disc (Plättchenpulver), designated as PIP (50 x 0.2)** consisted of discs 50 mm in diameter and 0.2 mm thick
- Ring or annular (Ringpulver), designated as RgP (0.2 x 50/10)** consisted of grains 0.2 mm thick, 50 mm in diameter and a central hole of 10 mm in diam

TABLE 47
(Artillery Propellants)

| TYPE | COMPOSITION, % | | | | | | | | | | Temp of combustion °K | Uses | |
|---|----------------|-------|-------|-------|----|----|-------|------|-------|--|-----------------------|------|-------------------------|
| | NC | N | NG | DE | GN | Gu | Centr | MgO | Graph | Other ingredients | | | Calorific value kcal/kg |
| NgBlIP-12.5 | 54.40 | 12.90 | 44.20 | - | - | - | 1.00 | 0.05 | 0.05 | Akar 0.30 | 1290 | 4065 | Army guns and mortars |
| NgBlIP-11.5 | 57.75 | 12.75 | 38.50 | - | - | - | 3.60 | 0.05 | 0.10 | - | 1150 | 3550 | Army guns and mortars |
| NgIRP-9.5 (RpC/12 or RP 12 of the Navy) | 64.13 | 11.90 | 29.77 | - | - | - | 5.75 | 0.25 | 0.10 | - | 950 | 2975 | Army & Navy guns |
| NgIRP-3 | 67.07 | 11.40 | 26.08 | - | - | - | 6.50 | 0.25 | 0.10 | - | 840 | 2650 | Army guns |
| (NgIRP-32 or RpC/32) | 66.60 | 11.50 | 25.90 | - | - | - | 7.25 | 0.15 | 0.10 | - | 830 | 2630 | Navy guns |
| DigIBIP-10.5 | 63.62 | 13.00 | - | 35.78 | - | - | 0.25 | 0.05 | 0.05 | Akar 0.25 | 1020 | 3150 | Army howitzers |
| DigIRP-9.5 | 61.80 | 12.60 | - | 36.45 | - | - | 1.50 | 0.15 | 0.10 | - | 950 | 2940 | Army guns |
| DigIRP-8-0.3 | 68.30 | 11.90 | - | 29.25 | - | - | 2.20 | 0.15 | 0.10 | KNO ₃ 0.30 | 870 | 2650 | 37mm AA guns |
| DigIRP-8.2 | 67.70 | 11.90 | - | 29.05 | - | - | 3.00 | 0.15 | 0.10 | - | 820 | 2570 | AA and Army guns |
| DigIRP-38 or RpC/38 | 69.45 | 12.20 | - | 25.30 | - | - | 5.00 | 0.15 | 0.10 | - | 810 | 2495 | Navy guns |
| (DigIRP-38N or (DigIRP-E | 68.72 | 12.20 | - | 25.03 | - | - | 1.50 | 0.15 | 0.10 | MNN 4.50 | 810 | 2545 | Navy guns |
| | 60.55 | 12.00 | - | 25.95 | - | - | 3.75 | 0.15 | 0.10 | MNN 2.50 DNT 4.00 Hvdr 3.00 | 730 | 2175 | Army and Navy guns |
| DigIRP-KO or DigIRP-K1 | 64.15 | 12.00 | - | 27.50 | - | - | 5.35 | 0.15 | 0.10 | Vasel 1.85 DAmpPh 0.90 | 725 | 2125 | AA guns |
| DigIRP-KN | 61.08 | 12.00 | - | 26.17 | - | - | 7.00 | 0.15 | 0.10 | Vasel 1.25 DNT 0.25 KNO ₃ 4.00 | 730 | 2125 | AA guns |
| DigIRP-KOD | 69.92 | 12.00 | - | 14.83 | - | - | 3.00 | 0.15 | 0.10 | MNN 2.00 DNT 10.00 | 730 | 2190 | AA guns |
| DigIRP-GO | 62.40 | 12.00 | - | 26.75 | - | - | 8.00 | 0.15 | 0.10 | Vasel 1.80 DAmpPh 0.80 | 700 | 1910 | Army guns |
| DigIRP-GO.5 or DigIRP-G1 | 61.88 | 12.00 | - | 26.52 | - | - | 7.75 | 0.15 | 0.10 | Vasel 1.80 DAmpPh 0.80 KNO ₃ 1.00 | 700 | 1905 | Army guns |
| DigIRP-G1.5 or DigIRP-G2 | 61.60 | 12.00 | - | 26.40 | - | - | 7.50 | 0.15 | 0.10 | Vasel 1.60 DAmpPh 0.65 KNO ₃ 3.00 | 700 | 1920 | Army guns |
| DigIRP-G2.5 or DigIRP-G3 | 51.42 | 12.00 | - | 26.33 | - | - | 7.00 | 0.15 | 0.10 | Vasel 1.50 DAmpPh 0.50 KNO ₃ 3.00 | 700 | 1965 | Army guns |
| DigIRP-G5 | 60.73 | 12.00 | - | 26.02 | - | - | 6.50 | 0.15 | 0.10 | Vasel 1.25 DAmpPh 0.25 KNO ₃ 5.00 | 700 | 2020 | Army guns |

Note: May contain up to 1% K₂SO₄

Table 47 (cont'd)

| | | | | | | | | | | | | | |
|---------------------------|----------------|----------------|---|----------------|-------|-----------|--------------|--------------|--|------------|--------------|--------------|------------------------|
| (Di)LRP-40 (Di)LRP-40N | 67.55 64.87 | 11.45 12.20 | - | 21.60 23.63 | - | 7.50 - | 0.25 0.15 | 0.10 0.10 | Akar 0.50 EPhUr 2.75 DPhUr 1.00 MNN 7.00 TEGDN 22.58 MNN 5.25 KNO ₃ 4.00 (added) | 720 730 | 610 635 | 2040 2165 | Navy guns Navy guns |
| (Di)LRP-40N | 67.72 | 11.50 | - | - | 4.20 | - | 0.15 | 0.10 | MNN 7.00 TEGDN 22.58 MNN 5.25 KNO ₃ 4.00 (added) | 650 | 504 | 1755 | Navy guns |
| GuP-AO to GuP-A1.2 | 38.17 | 13.00 | - | 31.23 | 30.00 | - | - | 0.10 | Akar 0.50 | 930 | 920 (914) | 2880 | Army guns |
| GuRP-39 | 35.49 | 12.20 | - | 21.76 | 40.00 | - | 0.25 | 0.10 | Akar 0.50 EPhUr 0.70 DPhUr 0.70 K ₂ SO ₄ 0.50 | 830 | 794 | 2550 | Navy guns |
| GuRP-7.5 | 42.70 | 12.00 | - | 18.90 | 30.00 | - | 0.15 | 0.10 | EPhUr 3.75 DPhUr 5.00 | 750 | 590 | 2020 | A.A. and Army guns |
| GuRP-8 | 48.13 | 12.00 | - | 20.62 | 30.00 | - | 0.15 | 0.10 | EPhUr 1.00 | 810 | 827 | 2630 | Army guns |
| GuRP-KN | 35.55 | 12.00 | - | 16.95 | 30.00 | - | 0.15 | 0.10 | EPhUr 5.00 DPhUr 4.25 KNO ₃ 4.00 | 730 | 600 | 1995 | A.A. guns |
| GuRP-G0 to GuRP-G1 | 42.70 | 12.00 | - | 18.30 | 30.00 | - | 0.15 | 0.10 | Akar 0.50 EPhUr 3.75 DPhUr 4.50 | 730 | 590 (588) | 2005 | Army guns |
| GuP-G5 | 42.50 | 12.00 | - | 18.25 | 25.00 | - | 0.15 | 0.10 | EPhUr 4.50 DPhUr 4.50 K ₂ SO ₄ 5.00 | 730 | 567 | 1890 | Army guns |

Abbreviations: A such as in GuP-AO or GuP-A1.2 indicated a hot NG₀ propellant (calorific value about 920 kcal/kg) which contained either 0% or 1.2% K₂SO₄; Akar Akardit (Acardite); Am Ammonium; Ammo Ammunition; A/T Antitank; BIP Blättchenpulver (Rectangular flaked propellant); C Konstruktion (Pattern) such as in C/38 (pattern 1938); Centr Centralite; D Indi- cated the presence of DNT (See also: KOD); DAMPh Diamylophthalate; DEGDN Diethyleneglycol dinitrate; DigIP Diglykol (nitrate) Pulver (DEGDN propellant); DNT Din. toluene; DPhUr Diphenylurethane; E Einheitspulver "Standard" propellant, such as (Di)LRP-E; EPhUr Ethyphenylurethane; Exper Experimental; G, such as in DigLRP-G0 to DigLRP-G5, indicated the presence of 0% to 5% of K₂SO₄; Graph Graphite; GuP Gudolfpulver (NG₀ propellant); Hydr Hydrocellulose; K (Krumbach) indicated DEGDN propellants containing K nitrate. These propellants were slightly hotter than the "G" pulvcr, having calorific values of 710 to 730 kcal/kg; KN indicated an unspecified amount of K nitrate present; KOD indicated that K nitrate was not present but some DNT; Mennp Manöverpulver (Blank propellant); MNN Mononitronaphthalene (alpha); N Nitrogen; N such as in RP-39N, indicated the presence of MNN; M, such as in KN, indicated Kaliumnitrat (K nitrate); NC Nitrocellulose; NG Nitroglycerin; NG₀ Nitro- guanidin; NP Nudelpulver (Cropped cord propellant); Nz Nitrozellulose (NC); OD See KOD; PIP Plättchenpulver (Circular discs, without holes, propellant); RgP Ringpulver (Circular discs, with central holes, propellant); RP Röhrenpulver (Long tube propel- lant); StrP Streifenpulver (Long strip propellant); TEGN Triethyleneglycol dinitrate; Temp Temperature; Theor Theoretical; TrigIP Triglykol (nitrate) Pulver (TEGDN propellant).

Table 48

Propellant Igniters and Propellant Igniter Bag Compositions

| Form | Composition, % | | | | | | | Other Ingredients | Uses |
|----------------|----------------|----------|--------------------|-------|------|-------|---|--|---------------------------------------|
| | NC | %N in NC | NG | DEGDN | Cent | Graph | | | |
| Cord Grains | 79.1 | 13.1 | - | - | - | - | - | DPhA 0.9 | 20 mm Solothurn |
| | 91.3 | 13.0 | - | 5.2 | 1.0 | 0.3 | - | K sulfate 0.5 Unac 1.7 | 37 mm APHV |
| Bag Grains | 89.6 | 12.4 | - | 9.6 | 0.8 | - | - | - | 37 mm APHV (Bag) |
| | 91.4 | 13.0 | - | 6.0 | 0.6 | - | - | Camphor 0.4 K sulfate 0.3 Unac 1.3 | 37 mm APRN |
| Bag Cord | 88.9 | 12.4 | - | 10.3 | 0.8 | - | - | - | 37 mm APRN (Bag) |
| | 92.8 | 12.7 | 3.2 | - | 1.9 | 0.3 | - | DPhA 0.3 Unac 1.5 | 37 mm HEHoC |
| Grain Grain | 85.6 | 12.9 | - | 10.3 | 1.0 | 0.9 | - | Unac 2.2 | 42/28 mm APHV |
| | 89.5 | 13.0 | - | 7.2 | 0.9 | 0.4 | - | Unac 2.0 | 42/28 mm AP Tapered Bore Gun |
| Cord | 88.8 | 13.1 | - | - | 6.8 | 0.35 | - | Acar 0.15 | 50 mm APC |
| | | | | | | | | DNT 2.5 K salts 0.8 Unac 0.6 | |
| Bag Grains | 91.0 | 12.3 | 6.1 | - | 1.8 | - | - | DNT 1.1 | 50 mm APC (Bag) |
| | 92.8 | 13.0 | - | 4.3 | 0.4 | 0.30 | - | K sulfate 0.45 Unac 1.75 | 50 mm APC |
| Bag Grains | 90.4 | 12.3 | - | 8.7 | 0.9 | - | - | - | 50 mm APC (Bag) |
| | 88.2 | 12.3 | - | 7.0 | 2.5 | 0.60 | - | K sulfate 0.3 Unac 1.4 | 50 mm APRN |
| Bag Grains | 88.9 | 13.0 | - | 10.3 | 0.8 | - | - | - | 50 mm APRN (Bag) |
| | 87.7 | 12.9 | - | 7.9 | 1.9 | 0.40 | - | Camphor 0.7 Unac 1.4 | 50 mm APRN |
| Bag Grains | 89.1 | 12.4 | - | 10.0 | 0.9 | - | - | - | 50 mm APRN (Bag) |
| | 91.3 | 13.0 | - | 5.0 | 0.9 | 0.25 | - | K sulfate 0.5 Unac 2.05 | 50 mm HE |
| Bag Cord | 96.6 | 12.6 | - | - | - | - | - | Unac 3.4 | 50 mm HE (Bag) |
| | 83.4 | 13.1 | - | 11.7 | 1.5 | 1.0 | - | Unac 2.1 | 75 mm HE HoC |
| Bag Cord | 87.9 | 12.6 | - | 10.8 | 1.3 | - | - | - | 75 mm HEHoC (Bag) |
| | 88.7 | 13.1 | - | 6.6 | 1.4 | 0.5 | - | Unac 2.8 | 75 mm HE, A/T (Pak 40) |
| Cord Grain | 77.3 | 13.0 | - | 18.8 | 2.6 | 0.5 | - | Unac 0.8 | 75 mm APCLC |
| | 89.1 | 13.0 | - | 7.3 | 0.7 | 0.5 | - | Unac 2.4 | 76.2 mm A/T Gun (Captured Russian) |
| Cord | 90.7 | 12.9 | - | 5.9 | - | - | - | K sulfate 0.4 | 88 mm HE |
| | | | | | | | | Unac 3.0 | |
| Cord | 92.7 | 13.1 | - | 1.7 | 1.3 | - | - | K nitrate 1.3 | 88 mm HE:LC |
| | | | | | | | | Unac 3.0 | |
| Cord | 89.1 | 13.0 | 5.1 | 2.1 | 0.8 | - | - | Acar 0.8 | 100 mm Gun (K 18) |
| | | | | | | | | Unac 2.1 | (Charge 1) |
| Square | 56.7 | 13.1 | 32.1 | 7.0 | 0.6 | - | - | DPhUret 0.8 | 100 mm Gun (K 18) |
| | | | | | | | | DEtUret 0.5 | (Charge 2) |
| Bag | 34.9 | 12.1 | 63.1 (or DEGDN) | - | - | 0.8 | - | Unac 1.2 | 100 mm Gun (K 18) (Bag) |
| | 61.6 | 13.3 | - | 36.8 | 0.4 | - | - | Acar 0.3 Unac 0.9 | 155 mm How |
| Bag | 73.4 | 12.4 | 23.0 | - | - | 2.4 | - | Unac 1.2 | 155 mm How (Bag) |
| | 84.1 | 12.7 | 10.0 | - | - | 0.8 | - | Acar 2.4 Unac 2.7 | 210 mm Rocket Igniter Pad |

Abbreviations: See under table 44

Note: Due to the difficulty of igniting propellants containing DEGDN and NGu, the igniters for these materials consisted of NC of a high degree of nitration with not more than 5% DEGDN.

f) Nodular or noodle (Nudelpulver), designated as NP (or NdP) (1.5 x 1.5), consisted of grains 1.5 mm long and 1.5 mm in diameter.

g) Long (Langpulver), used for Naval star shells and designated as LgP (480 x 3.9/2.8), consisted of tubular grains 480 mm long having external and internal diameters of 3.9 mm and 2.8 mm respectively.

(See also Table 46 of this book where web dimensions and ballistic characteristics of typical German propellants are given).

Propellant Igniters and Propellant Igniter Bag Compositions.

According to the work conducted at Picatinny Arsenal during WW II most of the bags (containers) used for propellant igniter compositions were made of colloided smokeless propellant materials. The same investigation showed that the propellant igniter compositions may be subdivided into three classes:

- NC-NG compositions
- NC-DEGDN compositions and
- Black powder compositions.

Table 48 gives the composition of typical propellant igniters, classes (a) and (b), and of their containers (bags). It is to be noted that the values shall be considered as only approximate because there was a possibility that some of the NG or DEGDN volatilized and passed from the propellant to the bag or vice versa.

(See previous page).

Some propellant igniter compositions of Class c (black powder) are given in Table 49

Table 49

| Form | Composition, % | | | Uses |
|-------|------------------|--------|----------|------------|
| | KNO ₃ | Sulfur | Charcoal | |
| Grain | 75.9 | 9.5 | 14.6 | 20 mm Inc |
| Grain | 77.5 | 9.5 | 13.0 | 20 mm AP |
| Grain | 74.9 | 9.9 | 15.2 | 20 mm HE |
| Grain | 74.2 | 8.96 | 16.84 | 47 mm APC |
| Grain | 76.2 | 9.8 | 14.0 | 47 mm APLN |

Abbreviations See under Table 44

According to Ref 4, one of the propellant igniter compositions manufd at the Düneberg Fabrik D A -G contained: NC (13%N content) 54.39, NG 44.51, Acardite 1.00, MgO 0.05, and IG Farben Wax E 0.05%. Oxygen balance + 10.96% and calorific value 1284 kcal/kg.

According to Ref 5, one type of German igniter for propellants consisted of NC (13.15%N) 75.8, NG 24.0, and DPhA 0.2%.

References:

- Picatinny Arsenal Technical Reports 1282 (1943) and 1456 (1944)
- PB Rept 11,544 (1945)
- Pic Arsn Tech Rept 1555 (1945)
- PB Rept 7826 (Technical Intelligence Rept 1-70) (1945)
- J. Corner, Theory of Internal Ballistics, Wiley (1950, p 29.

Propellant Substitutes. See Treibsätze.

Proving of Ammunition and Weapons. Preliminary testing was done at proof ranges attached to most of the explosives, ammunition or weapons plants such as those of the Dynamit A-G, WASA-G, Krupp, etc, but final (acceptance) tests were conducted either at the Hillersleben (for the Army) or at the Meppen (for the Navy) Proving Grounds.

Most of the German proof ranges were built in the form of a V, the gun being placed at the point of intersection, so that it could fire into one butt while the other was being prepared. The officer in charge sat in an upstairs office behind the gun and overlooking it. The LeBoulogne chronographs were in other buildings further back and results were sent to the officer through a pipe conveyor system. The LeBoulogne screens were usually placed 50 m apart at approximately 30 and 80 m from the gun.


The proof procedure for a propellant was to fire it in comparison with a standard propellant, using 7 rounds of each lot under proof. A normal lot was 50 tons. The firing temperature was 10°C for the Army and 15°C for the Navy. Propellant charges for use in the tropics were made to give the same ballistics at 25°C as the normal charge at 10°C. The upper temperature for tropical A/I propellants was 60°C. Propellants were stored at the required temperature for at least two days prior to firing. Chamber pressures were measured by copper cylinders (crusher gages).

The proof procedure for a gun was to heat a Service propelling charge to 35°C and use it in the gun being proved, attempting to develop a pressure (design or true pressure) of about 300 atm (sq tons/sq in) above the proof pressure, as measured by a copper crusher gage. For the Adolf gun the pressure above the proof pressure, was only 150 atm (1 ton/sq in).

Reference: H.H.M. Pike, CIOS Rept 31-68 (1946), pp 10-12.

Proximity Fuze. According to TM 9-1985-2 (1953), three types of proximity fuzes, for use in bombs, were developed in Germany: the Acoustic, the IR (infrared) and the Electronic.

Among these the Kronich (briefly described on pp 216-17) was acoustic, the Madrid (developed by Kapka of Vienna and mentioned on p 232) was infra-red, and there were also electronic fuzes developed by the Telefunken Co and others. Several other names of proximity fuzes are mentioned on p 229, such as Kokadu, Marabu and Fuchs, but the type of each of these was not stated.



A different type of proximity fuze is described in TM E9-1983 (1942), File N 2322.6. This fuze, designated as EIAZ (26), was cylindrical in shape and contained the charging plungers A and B (surrounded by insulating material), a charging condenser C₁, a firing condenser C₂, resistances R₁ & R₂, an igniter bridge IB, a trembler switch TS and an air pressure switch. The latter switch consisted of a fixed and a movable plate. The switch was placed just inside of an opening in the fuze case and was aligned with the air tube leading from the nose of the bomb C250 Flam. (See drawing).

The base of the fuze case was threaded to receive the gaine, which housed the primer (containing a match composition and black powder), the detonator (containing lead azide/lead styphnate mixture over PETN and PETN/wax) and the booster (picric acid).

Before the bomb was dropped from a plane the current from the plane batteries passed through B (plunger A was a dummy) into C, and at the release of the bomb the current leaked slowly through R, to C, where it accumulated. As the bomb approached its target the pressure of air built up in the tube leading to the pressure switch pushed the movable plate of the switch towards the fixed plate, thus closing the circuit through IB and firing the fuze and eventually the main charge of the bomb.

If the pressure fuze should fail to operate then the trembler switch TS was supposed to act on impact of the bomb.

Note: According to G.E. Rogers of Picatinny Arsenal, this type of fuze could be initiated by the air burst produced by other bombs exploding in the vicinity and this would be undesirable if the bomb was not yet close to its target. On the other hand this property of the fuze could be used to intentionally produce air bursts of bombs by dropping them in a train.

Proximity Fuze, Electric, ELAZ (26). See under Proximity Fuze.

Pudel (Poodle). An acoustic homing device intended for the control of some guided missiles. Its construction was essentially the same as for the Kranich acoustic proximity fuze. Reference: TM 9-1985-2 (1953), p 217.

Pull Type Igniter (Zugzünder). See under Igniter.

Pulver (Powder). See also Propellant.

Following are the principal German abbreviations used to designate various types of propellants:

- a) **Pulver Digi (Typ Digi).** A double-base propellant containing as principal ingredients DEGDN and NC.
- b) **Pulver Gu (Gudol).** A triple-base propellant consisting of NGu, NC, and DEGDN.
- c) **Pulver Ngl (Typ Ngl).** A triple-base propellant consisting of NGu, NC, and DEGDN.
- d) **Pulver Nz (Typ Nz).** A single-base (NC) propellant.
- e) **Pulver OL (Pulverlöse- und Lösungsmittel)** A solventless propellant.
- f) **Blättchenpulver (BlP).** A leaf or flake propellant.
- g) **Ringpulver (kgP).** An annular propellant, resembling a washer.
- h) **Röhrenpulver (RP).** A tubular propellant.
- i) **Streifenpulver (StrP).** A strip propellant.
- j) **Würfelpulver (WP).** A propellant in small rectangular tablets; it is called sometimes cube-cut propellant.

Reference: TM 9-1985.

Pulvermasse G. A double-base propellant containing K sulfate as a flash-reducing agent.

Pulvermetallurgie (Powder Metallurgy). The technique of powder metallurgy was applied on a considerable scale during WW II, chiefly in the production of carbide tools and some ammunition and weapon components. For instance, the following articles were made from sintered iron or steel: shell driving bands ranging from 20 to 210 mm in caliber (sintered iron), fuze bodies and bullet cores (sintered steel) and also bearings, rings, gears, etc.
Reference: C.J. Leadbeater, Sintered Iron and Steel Components, BROS Final Rept 595, Item 21 (1945).

Pulvermetallurgie (as practiced by the WPG). A jet of molten iron together with a strong jet of water were directed against a fast rotating horizontal disc enclosed in a cylinder having a conical bottom provided with an outlet. The resulting product, powdered iron slightly oxidized on the surface, was dusted with a small amount of yellow lead oxide and then reduced in an atmosphere of hydrogen at about 400°C. By this process the iron particles became coated with lead and thus rendered rust-proof. This powder was used for the prepn of sintered iron rotating bands (in lieu of copper bearings) and other articles. Dr H. Walter - Private communication.

Pulwitz of Berlin patented in 1895 the following permissible explosive: Am nitrate 92.0, phenanthrene 5.5 and K bichromate 2.5%. Daniel, Dictionnaire, Paris (1902), p 659.

Püppchen (Dolly), called also **Wheeled Bozooka** was a carriage-mounted 88 mm rocket launcher with breech-block. It used ammunition containing the same shaped-charge warhead as the **Panzerschreck (Ofenrohr)** but with a shorter rocket motor body. It was fired by means of a propellant contained in a cartridge placed in the breech. The flash from the cartridge ignited the rocket propellant and the missile proceeded towards the target.

Reference: Intelligence Bulletin, March 1945, p 14 (See also under 88 mm Weapons).



Pyrofulmin. See general section.

Pyrolit (Pyrolithe). According to Naoum (Ref 1) Pyrolit was a type of explosive prepd from smokeless propellants left over after WW I. The finished product also contained 5 to 12% gypsum and at least 18% moisture. Na nitrate and/or K perchlorate (max 30%) and TNT (max 15%) were sometimes incorporated in Pyrolit.

J. Pepin Lehalleur (Ref 2) lists the following compositions, called pyrolithes:

- a) Ballistite 74-76 and Na nitrate with or without KClO₄ 26-24%
- b) Ballistite 40-42, K chlorate with or without Na nitrate 45-43 and aromatic nitrocompounds 13-15%.

Note: The aromatic nitrocompounds of the last composition should not increase the sensitiveness to shock to any greater extent than the addition of 13-15% TNT.

References:

- 1) P. Naoum, Nitroglycerin, etc, Baltimore (1928), p 451
- 2) J. Pepin Lehalleur, Poudres, etc, Paris (1935), pp 457-8.

Pyroschliff. Pulverized aluminum intended for use in pyrotechnic compositions. It was required that the moisture content be 0.4% (max), and fats 0.6% (max).

Reference:

Kast-Metz, Chemische Untersuchung der Spreng- und Zündstoffe, Vieweg, Braunschweig, (1944), p 516.

Note: According to TM 9-1985-2 (1953), p 82, the Pyroschliff was an extremely fine, low density, flaked aluminum (Al) powder having the following characteristics: Al metal content 87-92, fat content less than 0.1 and moisture content 0.5%; the rest being unspecified impurities. Straight Pyroschliff was used for filling the BLC 50/A bomb described under Photoflash Bombs.

Pyrotechnic Antipathfinder Devices, such as the 15 cm simulator rocket and Mark 50 cascade flare bomb, were employed as a counter measure for the Allies' Pathfinder Bombing (qv). The German devices were intended to confuse the raiders by false signals which closely resembled the signals employed in the Pathfinder system. The devices were launched into the air by means of rockets, or were dropped from planes about 5 miles away from the true targets and over unimportant territory.

Against the daylight raids each rocket was equipped with either three smoke flares or with about 400 pellets designed to produce black smoke trails. Against the night raids there were many different arrangements of colored lights.

It was reported that the German devices were used also to designate landing fields to the Luftwaffe pilots during heavy fog. Another use was to indicate the direction and magnitude of Allied air attacks to Flak batteries and Luftwaffe fighter pilots.

Following is a brief description of some Antipathfinder devices:

A. 15 cm RSSG (Raketen Scheinsschussgerät (Rocket Signal Simulating Device) was constructed of two sections: the rocket motor tube and the rocket head.

The tube contained seven 2 lb sticks of NC-DEGDN rocket propellant, while the head contained a pyrotechnic charge such as:

1) "F" (Fallschirm) Patronen (Parachute Flare Cartridges) which contained, among other items, the red, green, yellow or white flare compositions.

For instance, the red flare cartridge consisted of the following components:

- First fire (1.5 g of black powder)
- Intermediate (1.5 g of a mixture of K nitrate 46.7, S 11.4, Al 10.3, black powder 29.3 and Zr 2.8%)
- Igniter (17 g of a mixture of Sr nitrate 61, PVC 22 and Mg 17%)
- Red flare (6.7 kg of a mixture of Sr nitrate 60, CPVC 18, Mg 18, IG wax 3 and vaseline 1%). Burning time 5 minutes.

Other flares had the following compositions:

Green flare: Ba nitrate 60, CPVC 20, Mg 17, IG wax 1 and vaseline 2%. Burning time about 5 minutes.

Yellow flare: Na nitrate 45, Sr nitrate 2, Mg/Al alloy (50/50) 40, wood meal 3, IG wax 8 and vaseline 2%. Burning time 5 minutes.

White flare: Ba nitrate 68.5, K nitrate 8.0, Al 17.5, S 4.0 and vaseline 2.0%. Burning time 5 minutes.

Note: The composition of the first fire and of the intermediate mixture was the same for all flares, but the ignition compositions were as follows:

For green flare: 17 g of a mixture of Ba nitrate 60, CPVC 23, Mg 14, IG wax 1 and vaseline 2%.

For yellow and white flares: 17 g of a mixture of Ba nitrate 67, Ba fluoride 6, S 10, Al (flakes) 20 and Al (grains) 2%.

The cartridge for the green star consisted of the following items:

- Primer
- First fire (1.5 g of black powder)
- Intermediate (1.0 g of mixture: K nitrate 15, S 13, Al 10 and black powder 32%)
- Red star (10.0 g of a mixture of Ba nitrate 57, Mg 20 and CPVC 23%).

The composition for the red star was: Sr nitrate 60, Mg 24 and CPVC 16%. The first fire was the same as for the green star, but the intermediate contained: Ba nitrate 41.2, K nitrate 15.4, Al 10.9, S 11.7 and black powder 30.9%.

Note: Most of the intermediate compositions containing black powder and sulfur were replaced, in 1945, by mixtures containing tetranitrocarbazole, K nitrate and Al and the reason for this is explained under Tetranitrocarbazol (TeNCbz).

2) "Ks" (Kaskade) Patronen (Cascade Cartridges) contained flares (green, red, yellow or white) without parachutes.

The following combination was used for green flare:

- Igniter (5 g of black powder)
- Intermediate (7.5 g of a mixture of K nitrate 34, TeNCbz 34 and Al 32%).

c) Green flare: 320 g of a mixture of Ba nitrate 61, CPVC (63% Cl) 21, Mg 11 and IG wax 7%. Burning time 2 minutes and candlepower 10000.

Note: The composition of the red flare was: Sr nitrate 62.5, Mg 13.5, CPVC (63% Cl) 18.0 and IG wax 6.0%. Burning time 2 minutes and candlepower 10000.

3) "Rz" Rauch Patronen (Smoke Cartridges) contained three smoke candles (Nebelkerzen 39B) consisting of a mixture of HCE 40, Zn dust 50 and Ba nitrate 10%. Burning time 1 minute.

4) Black Smoke Cartridges, which contained about 300 smoke producing pellets of the following composition: HCE 61.5, Mg 14.5, anthracene 8.0 and naphthalene 12.0%. The igniter train consisted of a black powder and an ignition composition containing K nitrate 24.0, HCE 24.6, TeNCbz 18.0, anthracene 5.6, naphthalene 2.4, Al powder 18.0 and Mg powder 7.4%.

Note: There were two types of 15 cm RSSG rockets (1 and 2). Type 1 was equipped with a delay igniter V-22 (g.v.) which was fired by the hot gases from the propellant, while type 2 was equipped with the electrical igniter for the rocket motor tube and was ignited separately.

B. 15 cm RLGS (Raketen Leuchtgerät Scheinsschuss Rocket Illuminant Simulating Device) was an improved version of the 15 cm RSSG rocket. The RLGS rocket used flares of the following types:

1) Single color flares: red, green or yellow

2) Red, green and yellow flares which ejected seven groups of colored stars, at intervals of about 25 seconds.

For instance, the green flare cartridge consisted of the following items:

- First fire (1 g of black powder)
- Intermediate (1.5 g of a mixture of TeNCbz 30, Al 30 and K nitrate 40%)
- Igniter (20 g of a mixture of Ba nitrate 60, Mg 20 and PVC 20%)
- Green flare [1.15 kg of a mixture of Ba nitrate 57.5, Mg 7.5, Mg/Al alloy (50/50) 6.5 and PVC 28.5%. Burning time 4 minutes].

For flares which burned with the ejection of stars, the composition was not the same as for ordinary flares. For instance, the green flare employed for ejection of stars contained: Ba nitrate 53, Mg 25, PVC 20 and graphite 2%. The corresponding stars contained: Ba nitrate 55, Mg 18, PVC 25 and graphite 2%.

The composition of other flares and their stars is given on pp 27-29 of the Reference

C. Mark 50 Kaskade (Cascade Flare Bomb) was employed to simulate the cascades of the Pathfinder system used by the Allies. It consisted of a cardboard case filled with about 62 candles. Each candle burned for about 2 minutes with either a red or green flame. The composition of the candles was the same as described for item A2, "Ks" (Kaskade) Patronen.

Abbreviations: CPVC Chlorinated polyvinyl chloride; DEGDN Diethyleneglycol dinitrate; HCE Hexachloroethane; PVC Polyvinylchloride; TeNCbz Tetranitrocarbazol.

Reference: H.J. Eppig, Pyrotechnic Antipathfinder Devices, CLOS, Item Nos 3 & 1, File No 32-56 (1948).

PYROTECHNICS (Feuerwerkerei). The compositions of various pyrotechnic devices in use between WW I and WW II were given by Langhans (Ref 1) and Lenze (Ref 2). The latter investigator also described various tests applied to pyrotechnic compositions, such as Entzündlichkeit (Ignitability), Entzündungstemperatur (Ignition Temperature, Empfindlichkeit gegen Schlag und Reibung (Sen-

sitivensens to Shock and Friction), Detonationsgeschwindigkeit (Velocity of Detonation) and Brisanz (Brisance).

A brief historical description of the development of the science of pyrotechnics in Germany is given by Lotz (Ref 3).

Izzo (Ref 5) lists numerous German pyrotechnic compositions as can be seen in Table 50. (See next page).

Table 50
Pyrotechnic Compositions

| Designation | Components | | | | | | | | | | | | Reference |
|--------------------|--------------|------|-------------|------|------|------|------|------|-----|-----|----------|----------------------------------|----------------------|
| | Chlorate of: | | Nitrate of: | | | Al | Mg | S | Sr | Zr | Shel-lac | Other In-gredients | |
| | Ba | K | Ba | K | Sr | | | | | | | | |
| Green Star signal | 64.0 | 18.0 | - | - | - | - | - | - | - | - | 18.0 | - | 5,p 211 |
| Green Light (1944) | - | - | 58.0 | - | - | - | 7.5 | - | - | - | - | - | 5,p 211 |
| Signal Light | - | 23.8 | 57.1 | - | - | - | - | 19.1 | - | - | - | PVC 22.5 Si 7.0 Res Ac 5.0 | 5,p 212 |
| Signal Light | - | 21.4 | 57.2 | - | - | - | - | 10.7 | - | - | - | - | 5,p 212 |
| Signal Light | - | 11.1 | 66.7 | - | - | - | - | - | - | - | - | Charcoal 10.7 | 5,p 212 |
| Signal Light | - | 36.0 | 40.0 | - | - | - | - | 24.0 | - | - | 22.2 | - | 5,p 212 |
| Signal Light | 81.1 | - | - | - | - | - | - | 10.8 | - | - | - | - | 5,p 212 |
| Signal Light | - | 32.7 | 52.3 | - | - | - | - | - | - | - | - | Charcoal 2.7 Calomel 5.4 | 5,p 212 |
| Ignition | - | - | 16.0 | 16.0 | - | 10.0 | - | 9.8 | - | - | - | Charcoal 5.2 | 5,p 212 |
| Composition | - | - | - | - | - | - | - | 8.0 | - | - | - | Black powder 50.0 | 5,p 221 |
| " | - | - | - | 46.0 | - | 11.0 | - | 11.0 | - | - | - | - | 5,p 221 |
| " | - | - | - | 40.0 | - | 30.0 | - | - | - | 3.0 | - | Black powder 29.0 | 5,p 221 |
| Green Star Signal | - | - | 58.0 | - | - | - | 8.0 | - | 7.0 | - | - | TeNCbz 30.0 PVC 22.0 | 5,p 221 5,p 228-9 |
| Green Star Signal | - | - | 55.0 | - | - | - | 16.0 | - | - | - | - | Gallie or Res Ac 5.0 PVC 29.0 | 5,p 221 |
| Red Star Signal | - | - | - | - | 55.0 | - | 28.0 | - | - | - | - | PVC 17.0 | 5,p 221 |
| Red Star Signal | - | - | - | - | 50.0 | - | 32.0 | - | - | - | - | PVC 18.0 | 5,p 221 |
| Red Star Signal | 86.0 | - | - | - | - | - | - | - | - | - | 11.0 | Carbon 3.0 | 5,p 229 |

Abbreviations: PVC Polyvinyl chloride; Res Ac Resorcylic acid; TeNCbz Tetranitrocarbazole.

Notes:

a) Duration of flame for a 12g star signal was about 7 seconds

b) For igniting each star composition of the signal about 1 g of black powder was used. This in turn ignited about 1 g of the intermediate mixture containing K nitrate 30.6, Ba nitrate 39.1, carbon 9.2 and Al 21.1%.

In the article by Goldenson and Danner (Ref 4) the following compositions are listed:

A) Hand smoke signals:

- Red: K chlorate 17, lactose 24 and *o*-methoxyphenylazo- β -naphthol 59%
- Blue: K chlorate 30, lactose 20 and 1-methylamino-4-p-toluidinoanthraquinone 50%
- Green: K chlorate 29, lactose 24, 9,10-dianilinoanthracene 30 and 1-methylamino-4-p-toluidinoanthraquinone 16% (Adds to 99%)
- Violet (Rauchbündelpatrone Violett): K chlorate 25, 1-methylamino-4-p-toluidinoanthraquinone 15, lactose 50 and "Rhodamine B" 10%. It was fired from a V \acute{e} ry-type pistol to produce four streaks of bright violet smoke.

B) Whistling cartridge (Pfeifpatrone) Contained two mixtures:

- Ba nitrate 55.5, Al powder 35.5 and sulfur 9%
- K chlorate 65.5 and gallic acid 33.5% (Adds to 99%).

Note: Mixture (a) was for producing light while mixture (b) produced a whistling sound. The cartridge was designed to be used as a gas attack warning.

C) Frangible grenade which produced a white screening smoke by the hydrolysis of titanium tetrachloride with water in which was dissolved 27 parts of Ca chloride (to prevent freezing)

D) Tank-gun smoke-screen projectile which contained oleum adsorbed on pumice. Another projectile was filled with solid SO_3 .

Additional information, given below, was obtained from Refs 9-17:

A. Pyrotechnic items of Ref 9 are discussed in this work under Incendiary Compositions and Smoke Compositions.

B. Pyrotechnic items briefly discussed in Ref 10 include:

- LC 50 flares, 8" diameter
- Ground flares, 4.5" diameter
- Self contained signal rocket
- 2 star red signal, hand operated by a pull igniter.

C. Pyrotechnic items of Ref 11 are discussed in this work under Pyrotechnic Antipathfinder Devices.

D. Pyrotechnic items of Ref 12 are discussed in this work under Tracers.

E. Pyrotechnic items of Ref 13 include the following:

- Compositions for the different colored candles used in Mk 50 kaskade Bombe include Red: Sr nitrate 56, Mg 16, Igelit 21 and IG wax 7%; Green: Ba nitrate 56, Mg 16, Igelit 21 and IG wax 7%; Yellow: Ba nitrate 61.5, Mg 15, cryolite 8.5, IG wax 4, Igelit 6 and Ca oxalate 5%; White: Ba nitrate 59, Mg 11, K nitrate 21, IG wax 1 and igelit 3%

b) Flare composition used in the ground flare, Bodenleuchte (P) F-156217: Mg (granular) 34.6, Na nitrate 11.3, gypsum 45.5 and water 8.6%

c) Blue light composition used for ship signals consisted of K nitrate, sulfur and Sb sulfide

d) Red light composition for ship signals contained K chlorate, shellac and Sr oxalate

F. Items mentioned in Ref 14 include some firework devices, such as paper caps for toy pistols, etc. A typical cap composition was made by mixing K chlorate 70, phosphorus 15 and sulfur with lime suspended in water 15%

G. Pyrotechnic items of Ref 15 include the amorces (a v) and some firework compositions such as Bengal light and star compositions

H. Pyrotechnic items of Ref 16 include the following red colored light mixture used for signalling: Sr nitrate 50-61, Mg 17-35, polyvinyl chloride or chlorinated polyvinyl chloride 1-28 and vaseline or synthetic wax 1-5%

I. According to Ref 17, the Germans made great use of kieselguhr as an extender for expensive organic dyes and dye intermediates used in their pyrotechnic compositions.


References:

- 1) A. Langhans, S S 17, 34-36, 43-45, 61-62, 68-70, 77-78, 90-93, 105-106 (1922) Leuchtsätze (Pyrotechnic Compositions,
- 2) F. Lenze, S S 27, 366-71, 406-9 (1932); *ibid*, 28, 14-17 (1933)
- 3) A. Lotz, Das Feuerwerk, Hiersemann, Leipzig, (1940), pp 19-45, 86 & 89-103
- 4) J. Goldenson & C. E. Danner, Chem Engr News 26, 1976-8 (1948); C A 42, 6116 (1948)
- 5) A. Izzo, Pirotecnia e fuochi artificiali, Hoepli, Milano (1950), pp 211, 212, 221 & 227-229
- 6) F. G. Haverlak, Pic Arsn Tech Rept 1440 (1944) (Tank smoke candles, NbK 39B)
- 7) F. G. Haverlak *ibid*, 1505 (1945), Aircraft colored smoke signals
- 8) F. G. Haverlak, *ibid*, 1519 (1945), Colored smoke signals
- 9) E. W. Berman, CIOS Report 32-13 (1945), Production of Smoke, Incendiary and Chemical Warfare Weapons
- 10) C. G. Bridge, CIOS Rept 32-27 (1945), German Pyrotechnics
- 11) H. J. Eppig, CIOS Rept 32-56 (1945), Pyrotechnic Antipathfinder Devices
- 12) H. Peplow et al, CIOS Rept 33-20 (1945), Deutsche Waffen- und Munitionsfabriken, A-G
- 13) F/Lt Lisowski & P. Milholland, BIOS Final Rept 1233 (1946), German Pyrotechnic Factories
- 14) C. G. Davies et al, BIOS Final Rept 1594 (1946), Some German Pyrotechnic and Paper Firms
- 15) T. M. Bennett, BIOS Final Rept 1313 (1947), German Methods of Production of Amorces and Sundry Pyrotechnic Stores
- 16) T. Urbański, Przemysł Chemiczny 27 (4), 487 (1948), Progress in the Field of Explosives During the Past Decade (Translated from Polish by Dr Ivan Simon)
- 17) J. Kanegis, PB Rept 102.500 (1951), Colored Smokes (General discussion and some bibliography).

(See also under Illuminating Compositions, Incendiary Compositions, Tracer Compositions, Smoke Compositions, Signal Devices, Flares, and Antipathfinder Pyrotechnic Devices).

Quellungsgrad Swelling Coefficient). See general section.

R-4M. A 2 inch solid propellant rocket, which carried about 1 lb of a HE and had tail surfaces that could be folded back. It was mass produced towards the end of WW II by the Deutsche Waffen- und Munitionsfabriken at Lübeck. As many as 48 of these missiles could be carried on the underwing racks of a fighter plane and fired practically simultaneously against a bomber formation at a range of 1200 to 1500 yards. It was claimed that a single hit with such a rocket was sufficient to bring down a bomber.



Reference: W. Domberger, V-2, Viking, N Y (1954), p 270. Note: According to K. W. Gatland, Development of the Guided Missile, "Flight" Publication, London (1952), pp 122- the R 4/M was an air-to-air missile developed in 1944 by modifying the RZ 73 Föhn. Its diameter was 2.16", overall length 2.75 ft, launching weight 7.75 lb, range 1/2 mile. It used a single tubular grain propellant which had a burning time of 0.8 sec.

Radar Guidance System for Missiles. See under Guidance Systems for Missiles.

Radio Command Guidance Systems. See under Guidance Systems for Missiles.

Rakete. See Rocket.

Raketenpanzerbüchse. See under Weapons, caliber 88 mm.

Raketenwerfer. See under Weapons, caliber 88 mm.

Ramjets. See general section. Some information on German ramjets is given in CIOS Rept 31-13 (1945).

Raschig's White Powder (Weisspulver) (See also Raschig). A cheap blasting powder prepared by F. Raschig in 1911 as follows:

A concentrated solution of a mixture of 65-70 parts of Na nitrate and 35-30 parts of Na cresolsulfonate was run in a thin stream onto a rapidly rotating drum heated by high pressure steam. The thin layer of dehydrated material which formed on the surface of the drum was scraped off in the form of flakes which were packed in waterproof paper cartridges. Compositions patented in 1912, consisted of: a) Na nitrate 68 and "Zellpech" 32% and b) K nitrate 70 and Zellpech 30%.

Note: In selecting the components of such explosives, it was necessary to bear in mind that if their solubility is not of the same order there will be a tendency for the ingredients to separate during the evaporation.

"Zellpech" is a pitch obtained by evaporating the liquor from the sulfite cellulose industry.

References:

- 1) Marshall, v 1 (1917), p 90
- 2) Naoum, Schiess- und Sprengstoffe (1927), p 16
- 3) Davis (1943), p 50.

Raschit (Raschite). A class of mixtures invented by F. Raschig, and prepared in the same manner as Raschig's White Powder. Some Raschites were used as blasting explosives, others were used during WW I as propellants, called wasserlösliche Schießpulvern, which means water-soluble Propellants. Table 51 gives the composition of several Raschites.

Table 51

| Designation | Composition, % | | | | |
|----------------|----------------|------------|---------------------|--------------------|----------|
| | Am nitrate | Na nitrate | Na benzenesulfonate | Na cresolsulfonate | Zellpech |
| Raschit 1 | 74 | - | 26 | - | - |
| Raschit 2 | 87 | - | 13 | - | - |
| Raschit 3 | 86 | - | - | 14 | - |
| Raschit 4 | 69 | - | - | 31 | - |
| Raschit Type 1 | - | 65 | - | 35 | - |
| Raschit Type 2 | - | 68 | - | - | 32 |

Note: Colver (Ref 4, p 352) stated that Raschit was invented in 1911 by Adolf Voight of Germany.

References:

- 1) F. Raschig, Angew Chem 25, 1194-97 (1917)
- 2) F. Raschig, S S 7, 292, (1912)
- 3) Marshall, v 1 (1917), pp 90 & 392
- 4) Colver (1919), pp 352, 707 and 738
- 5) J. Pequin Letailleur, Poudres, etc, Paris (1935), p 287.

Rauchlose Pulver. Smokeless Propellant, also called **Rauchschwaches Pulver**, which means Weak Smoke Propellant or Semi-smokeless Propellant. (See Propellants).

Rauchloses Geschützpulver 1889. See RGP 89 (Pulver).

Rauchloses Rottweiler Pulver. See RPP.

Pauppenschlepper (Caterpillar Tractor) was used for towing or carrying large guns and other items for military use. Some information on caterpillar tractors is given in the book by Dr F.v Senger u Etterlin, Taschenbuch der Panzer 1943-1954, Lehmanns' Verlag, München (1954) G.B. Jarrett, "Achtung Panzer", The Story of German Tanks in WW II, Great Oaks, RDI, Aberdeen, Md (1948).

Raw-Paste See Rohpulvermasse.

RCP (Rottweiler Cellulose Pulver) (Rottweil Cellulose Propellant). The first German gelatinized military smokeless propellant which was invented in 1883-1884 by Carl Duttenhoffer (born 1843, died 1903) independently of P. Vieille who invented Poudre B (see in the French Section). The first RCP was prepared at the Rottweil Plant by nitrating partially carbonized wood (the same kind as was used for prepn of brown powder, called Pulver C/82) by a method similar to that used in prepn of Schultze's Powder. The nitrated product was stabilized by boiling water, then dried and gelatinized by means of ethyl acetate. The gelatinized product was grained either in the form of small

balls (Blattchenpulver) for use in rifles or in the form of strips (Streifenpulver) for use in cannons.

References:

- 1) H. Brunswig, Das rauchlose Pulver, Berlin (1926), pp 6-7
- 2) P. Tavernier, Mémoud 32, 244 (1950)

Recoilless Gun (Kanone ohne Rucklauf). Several models were developed in Germany between 1937 and the beginning of WW II. Most of these were of Rheinmetall - Borsig Co design. One of the best known was the LG-1-Rh (later designated as LG-40) which was a 75 mm gun with a range of about 6800 yards. It weighed 325 lb (complete), was 45 inches overall and had a barrel 29.5 inches long. It used the Rheinmetall horizontal sliding breechlock which carried the counterblast nozzle.

The larger caliber recoilless guns included:

- a) 105 mm, known as LG-2Kp and as LG-40. This had a breech system very similar to that in the Russian recoilless gun which was developed before the Russo-Finnish War. The German model weighed 850 lb complete
- b) 105 mm, known as LG-2-Rh, LG-40-1 and LG-40-2, which used the Rheinmetall breech design. It weighed 1200 lbs
- c) 155 mm, designated in service as LG-42, weighed about 1400 lb in firing order and projected a shell weighing about 90 lbs
- d) DKM (Düsen-Kanone-Marine), developed by Rheinmetall-Borsig Co, was made in two versions: the DKM-43, cal 88 mm, for use on light patrol craft and the giant DKM-44, cal 280 mm. These two guns were still under development at the end of the war, but the DKM-43 was almost ready to be put into production. Both guns were supposed to use the Rheinmetall horizontally sliding breechlock with counterblast nozzle
- e) Aircraft recoilless weapons, developed by Rheinmetall-Borsig Co, included the Device 104 (a 14-inch gun firing a 1500 pound AP projectile) and the SG-113A, designed primarily to attack tanks from the air
- f) DUKA 50 and DUKA 88. Two recoilless aircraft weapons produced by Rheinmetall. Data and description of these guns are contradictory and little is known of them
- g) Rheinmetall Mk-115 was a 55 mm weapon of very original construction. It was still under development at the end of war

The above weapons were briefly described by R. March, Ordnance 38, 887-78 (1954).

F.G. Haverlack, in Picatinny Arsenal Technical Report 1487 (1945), described a complete round of unfired hollow (shaped) charge used in 75 mm Recoilless Gun, LG-40.

W.W. Fahr, in CIOS Rept 32-108 (1945), described the recoilless gun development of the Rheinmetall-Borsig Co.

Recoilless Mortar, caliber 2", was briefly described by W. Dornberger, V-2, Viking, N Y (1954), p 270. Its projectile weighed 15 lb and travelled at a velocity 1300 ft/sec. The weapon was optically triggered by means of a selenium cell. When the plane's silhouette appeared on the cell, the round was automatically fired.

Recoilless Weapons. Besides recoilless guns and the recoilless mortar described above, the Germans used numerous tubular rocket launchers, such as Panzerfaust, Ofentohr, Panzerschreck, Püppchen, Panzerwurm, etc, which also were, strictly speaking, "recoilless weapons".

References: Intelligence Bulletins, US War Department, Washington, D C . Vol III, No 3 (1945), pp 74-79 and Vol III, No 7 (1945), pp 9-16.

Reducing Bore Gun Gerlich Type Gun, Squeeze-Bore Gun. See Tapered-Bore Gun.

Reibungsprobe (Friction Test). See in the general section.

Reinforcing Igniter. See Zündverstärker.

Reintri (Pure Trinitrotoluene). See under Trinitrotoluol.

Remote Control Systems for Controlling the Missiles. See Guidance Systems for Missiles.

Research and Development Establishments for ammunition, rockets, rocket fuels, guided missiles, aircraft and weapons are briefly described by L.M.Simon et al in CIOS Report 30-71 (1945).

Resins. The thermoplastic and thermosetting resins used by the Germans during WW II are briefly discussed by B.Schools in BIOS Final Report 1191 (1946).


Revolver (Revolver). See under Weapons.

Rexit. See Rhexit.

RGP 89 (Rauchloses Geschützpulver 1889) (Smokeless Cannon Propellant of 1889). A propellant similar in composition to Italian Ballistite.

Reference: Daniel, Dictionnaire, Paris (1902), p 682.

Rheinbote (Rhein Messenger). An unguided, three-steps + booster, surface-to-surface missile, developed in 1943 by the Rheinmetall-Borsig Co under the direction of Klein and Vüllers. It contained 45 lb of a HE, used 1287 lb of a solid diethyleneglycol dinitrate propellant, was provided with a six-finned booster, and could be launched from a stationary or mobile ramp. Total weight of rocket was 3,781.5 lb and overall length 37.4 ft. Diameters of the 1st and 2nd steps were 0.88 ft and of the 3rd step 0.53 ft. The lengths of the 1st and of the 2nd steps were 11.4 ft and of the 3rd 13.1 ft. Maximum range, when using 65° elevation was 136 miles and velocity at final step 5,380 ft/sec.



References:

- 1) K.W.Gatland, Development of the Guided Missile, 'Flight' Publication, London, (1952), pp 55 & 122-3
- 2) W.Dömberger, V-2, Viking, N Y (1954), p 248.

Rheinisch Dynamit. A dynamite patented in 1874 consisted of NG (contg 2-3% of dissolved hydrocarbons such as naphthalene) 75, washed and dried kieselguhr 23 and chalk 2%.

Reference: Daniel, Dictionnaire, Paris (1902), p 682.

Rheinmetall Ammunition. The Rheinmetall-Borsig Co was one of the principal manufacturers of ammunition. Some items manufd before WW II were examined at Picatinny Arsenal.

Reference: G.Taliaferro, Pic Arsn Tech Rept 982 (1939).

Rheintochter (Daughter of the Rhein). A type of guided missile used against England during WW II. Several models were known, such as R-1, R-2 and R-3.

References (See also under Guided Missiles):

- 1) Anon, Army Ordnance, 31, 28 (1946)
- 2) A.Ducrocq, Les Armes Secrètes Allemandes, Paris (1947), pp 89-90 and 96-98
- 3) Anon, TM 9-1985-2 (1953), pp 226-9.

Rhexit oder Rexit (Rhexite). According to Colver (Ref 1) Rhexit was one of the earlier permissible explosives. It contained: Am nitrate 64 to 68, NG 6.5 to 8.5, TNT 6.5 to 8.5, Na nitrate 13 to 16, wood meal 3 to 5 and moisture 0.5 to 1.5%.

According to Naoúm (Ref 2), Rhexit was one of the pre-WW II straight dynamites, such as: NG 64.0, wood meal 7.0, partly decomposed wood 11.0 and Na chloride 18.0%. Its properties were: density 1.54, Trauzl test value 385 cc, oxygen balance -11%, and Pb block crushing value 20 mm.

References:

- 1) Colver, High Explosives, London (1918), p 249
- 2) Naoúm, Nitroglycerin, Baltimore (1928), pp 283-284.

Rhinoceros. See Nashorn, under Panzer.

Riegelmine. See under Landminen.

Rifle (Gewehr). See under Weapons.

Rifled Projectile (Pre-rifled Projectile). Three such projectiles were described in TM 9-1985-3 (1953), pp 526-528. All of them had a rifled design which took the form of 12 longitudinal splines inclined about 5° and spaced about 60 mm apart. The splines were not machined from the main projectile body but constructed separately on strips of steel which were then fitted into grooves cut in the projectile body. The grooves were undercut to provide secure attachment.

It is assumed that the splines were intended to engage in the rifling of the gun.

To the rear of the projectile there was a copper or bimetallic driving band, the probable function of which was to act as a gas seal.

Two of these projectiles were used in the Railroad Cannon 28 cm K 5 (E), while the use of the third projectile is unknown.

One of the projectiles [28 cm (280 mm)] was rocket-assisted. It weighed about 546 lb (loaded and fuzed, but without rocket ignition fuze). The weight of HE charge was about 31 lb and the wt of propellant 43 lb. The maximum range of the gun was about 53 miles.

Another type of 280 mm projectile weighed 562 lbs (loaded and fuzed) and was filled with about 67 lbs of TNT/Wax - 95/5, pressed in blocks in a cardboard container. (See drawings under Granate and under Rocket Assisted Shell).

(See also Pre-engraved and Pre rifled Projectiles in the general section).

Rifle Grenades (Gewehrgranaten); Rifle Antitank Grenades (Gewehrpanzergranaten). The following types are briefly described in Refs 1, 2 & 3:

- a) Small Antitank Rifle Grenade (Gewehrpanzergranate) was fired from the rifled 30 mm discharger cup (SchieSSbecher), which could be fitted to most types of German rifles. The grenade was constructed in two parts, the head and the stem (body) which was screwed to the head. The head was a seamless steel tube, the forward portion of which contained a steel cone and the bursting charge consisting of 1.75 oz of TNT poured around the cone. Directly behind the TNT was located the PETN wax exploder (auxiliary booster). The stem was made of a light alloy of aluminum and was provided with a pre-engraved driving band. The upper section contained the fuse (detonator-booster assembly), and the lower section the primer assembly. Total weight of the grenade was 6.8 oz, the overall length 6.4", the maximum diameter 1 3/16" and the range 50 yds (Ref 1, p 8 and Ref 2, pp 334-4).
- b) Antitank Mauser Rifle Grenade, designated as C Pzgr 42, described in Ref 3a was similar in appearance to the one described immediately above. The C Pzgr 42 contained 49 g of 50/50 Cyclotol as the bursting charge. Its booster and auxiliary booster consisted of 91.4/8.6-PETN/Wax and weighed 12.7 g. The fuse assembly consisted of an upper primer charge of 0.018 g of K chlorate 62, Sb sulfide 30 and abrasive 8%, and a lower primer charge of 0.01 g of carbon. Its detonator contained 0.33 g of 76/36 - Lead azide/Lead styphnate (upper charge) and 0.49 g of PETN (lower charge). (See general Section under Carbon). The grenade was propelled by a 1.0 g charge containing 96.5% NC (13% N), 0.6% diphenylamine and 0.1% graphite, the rest being organic impurities in NC, total volatiles and water soluble substances. The primer charge consisted of 0.028 g of a mixture of Ba nitrate 46, Pb styphnate 35, Ca silicide 15 and Sb sulfide 4%. Total weight of the grenade was 0.525 lb and the overall length 6.36" (Ref 3a).
- c) Large Antitank Rifle Grenade (Grosse Gewehrpanzergranate) was fired from the same 30 mm discharger cup (SchieSSbecher) as the small grenade described under (a). The head of this grenade was larger (max diam 1 1/2"). The length of the ensemble (head and stem) was 7", the total weight 13 1/2 oz and the wt of the filler (TNT) 4 1/2 oz. Its range was 100 yd. The fuse and booster were similar to the grenade (a) (Ref 1, p 8 and Ref 2, pp 336-7).
- d) Antitank Rifle Grenade (Schuss Gg P40) consisted of a streamlined bell-shaped body, with a slightly convex closing disc of aluminum, a graze fuze which screwed into the base of the body, and a vaned tail unit which screwed on the base of the fuze and was closed by a rubber plug. The bursting charge consisted of cast Cyclonite/Wax with a hemispherical cavity in the head. The cavity was fitted with an aluminum liner. The grenade was fired from a spigot type discharger using the 7.92 mm small type cartridge with a hollow wooden billet. The propelling gases overcame the spring of the cutting piece (see drawing) and drove the pin forward causing it to cut the shearing pin away from its screwed end. The pin was then ejected (by the spring held in compression under its head) and thus left the striker which had been held away from the detonator only by the creep spring. On grazing impact the momentum of the striker overcame the tension of the creep spring and the detonator was pierced. The grenade assembly was 9.3" long, the head 3.1" and its maximum diameter 2.4" (Ref 1, p 9 and Ref 2, pp 347-8).

A more detailed description of the grenade is given in Ref 3c. The composition of the propellant was: NC (13% N) 96.5, diphenylamine 0.6, graphite 0.1, total volatiles 0.9 & organic impurities 1.7%, and of the percussion primer water soluble 0.2, Ba nitrate 46, Pb styphnate 35, Ca silicide 15 and Sb sulfide 4%. The weight of propellant 1.0 g and of primer charge 0.028 g. The bursting charge (34.1 g), consisting of PETN 88 and wax 12%, was initiated either by the friction igniter or by the detonator. The igniter contained as the upper charge

0.020 g of red lead 74.7, silicon 17.8 and binder & fuel 7.5%; as the intermediate charge 0.120 g of NC; and as the lower charge 0.010 g of K perchlorate 55 and Pb ferrocyanide 45%. The delay element contained 0.090 g of black powder and the flash element consisted of 0.150 g of NC. The detonator contained as the upper layer 0.240 g of 68/32 - Pb azide/Pb styphnate, as the 1st intermediate layer 0.20 g of PETN, as the 2nd intermediate layer 0.120 g of Pb azide and as the lower layer 0.150 g of red lead 74.7, silicon 17.8 and binder & fuel 7.5%.

e) 37 mm Antitank Rifle Grenade, fired from a 3.7 cm Pak, consisted of a thin-walled steel head of bulbous shape to which was attached a closed steel pipe surrounded by a multi-perforated sheet steel tube to which six vanes were welded. The head was loaded with 5.2 lb of either Dinitroaniline/TNT mixture or with pressed Cyclotol consisting of RDX 62.3, wax 2.4 and TNT 35.3%. Its nose fuze assembly (AZ 5075) consisted of a primer-detonator (with 0.31 g of lead azide as the upper charge and 0.30 g of PETN as lower charge) and a detonator-booster (with 0.50 g of 69/31 - Lead azide/Lead styphnate as the upper charge, 0.30 g of PETN as the lower charge and 6.8 g of 90/10 - PETN/Wax as the booster). Its base fuze assembly (Bdz 5130) consisted of a primer (containing 0.150 g of 41/30/20/9 - K chlorate/Sb sulfide/Mercury fulminate/glass and a binder mixture of 0.050 g of black powder consisting of 73/15/12 - K nitrate/charcoal/sulfur) and a detonator-booster (contg 0.50 g 69/31 - Lead azide/Lead styphnate, 0.30 g of PETN and 6.8 g of 90/10 - PETN/Wax). The propelling charge consisting of 217 g of NC/NG or NC/DEGDN tubular propellant was contained in a steel cartridge case. The charge was ignited by 4 g of NC granular propellant and a percussion type primer consisting of 41.7/25.5/20.5/12.3 - K chlorate/Mercury fulminate/Sb sulfide/Abrasive and 0.5 g of black powder (75.9/14.7/9.2 - K nitrate/Charcoal/Sulfur). The impact fuze functioned in the case of direct impact, whereas the base fuze functioned in the event of graze action. Total weight of the grenade was 18.7 lb, over-all length 12 1/8" and length of body 12 1/4" (Ref 2, pp 335-6).



A more detailed description of the grenade is given in Ref 3b.

f) Antipersonnel Rifle and Hand Grenade (Gewehrpanzergranate), fired from a Mauser Rifle Grenade Discharger, consisted of a cylindrical body (5.5" long and 1.2" max diameter) which contained a bursting charge, an igniter, delay elements and a detonator. A point-detonating (PD) fuze initiated the bursting charge when the grenade was fired from the discharger, and a friction igniter (similar to BZ 24) initiated a delay element (consisting of black powder pellet burning for 1/2 seconds) when the grenade was thrown by hand. The grenade also had a self-destructing feature which functioned in case of failure of the PD fuze when fired from the discharger. Total weight of the of the missile was 9 oz and maximum range 550 yd. (Ref 2, pp 332-4).

g) 46 mm Antitank Rifle Grenade (SS Gewehrpanzergranate) consisted of a base-fuzed thin walled steel bulbous-shaped streamlined head (46 mm in diameter and 93 mm long), to which was attached a pre-rifled cylindrical stem 30 mm in diameter and 102 mm long. Its bursting hollow charge consisted of 143 g of 50/50 - RDX/TNT which was initiated by the following devices: a fuze primer (contg 0.068 g of K chlorate 49.8, Sb sulfide 43.0 and Hg fulminate 7.2%), a detonator (contg 0.33 g of 77/23 - Pb azide/Pb styphnate as the upper layer and 0.46 g of PETN as the lower layer) and a booster (contg 6.4 g of 94.5/4.5 - PETN/Wax mixture). It was propelled by 1.44 g of single-base propellant (contg 97.3 % of NC with a N content 13.2%) which was primed by 0.027 g of a mixture contg Ba nitrate 49.5, Pb styphnate 35.6 and Ca silicide 14.9%. The total weight of the grenade was 15 1/2 oz and overall length 195 mm (Ref 1, p 9; Ref 2, p 331 and Ref 3e).

h) 61 mm Antitank Rifle Grenade (SS Gewehrpanzergranate). This grenade was similar in construction, except for some dimensions, to the previous grenade.

RIFLE GRENADES



The total weight was 19 oz, overall length 238 mm, length of stem 102 mm and its diameter 30 mm, length of head 136 mm and its max diameter 61 mm. Its bursting and propellant charges, as well as its primers, detonator and booster were the same as for the 46 mm grenade (Ref 1, p 9, Ref 2, p 331 and Ref 3d)

i) 61 mm Antitank Rifle Grenade, briefly described on p 332, Ref 2, was similar in construction to the previous grenade. Its overall length was 244 mm.
 j) Leaflet Rifle Grenade (Gewehr Propagandagranate) was fired from the rifled 30 mm discharger cup (Schiessbecher) which could be fitted to most types of German rifles. It consisted of a cylindrical steel body (with a perforated base) containing a delay fuze, a thin cylindrical container for the pamphlets and an ejecting charge for this cylinder. On firing the grenade, the propellant gases ignited the delay fuze and, after about 9 seconds of delay, the fuze fired the ejecting charge. The resulting deflagration blew off the cap and forced the leaflets out the nose. Total weight of grenade 8 oz, overall length 5.7" and range 500 yd (Ref 2, p 338)

k) Illuminating Parachute Rifle Grenade (Gewehr Fallschirmleuchtgranate) consisted of a thin-walled cylindrical body, within which was another container which housed the parachute and illuminating star. The rear of grenade contained two delay pellets and two ejection charges. When fired the flash from the propellant gases ignited delay (1), and after 6.5 sec of light ejection charge (1) was initiated. The pressure of the gases forced out the nose, the container (which held the parachute) and the star. At the same time, delay (2) was ignited and after it burned through (2 seconds) the ejection charge (2) became initiated. The resulting gases ejected the parachute and the star from the container and ignited the star. It was claimed that distances up to 650 meters could be illuminated by this star. (Ref 2, p 339)
 (See also Faustpatrone and Pistol Grenades).

References:

- 1) A.J. Dere, The Ordnance Sergeant, October 1945, pp 8-10;
- 2) Anon, TM 9-1985-2 (1953), pp 331-39
- 3) Picatinny Arsenal Technical Reports:
 - a) A.B.Schilling, No 1342 (1944)
 - b) A.B.Schilling, No 1398 (1944)
 - c) A.B.Schilling, No 1494 (1945)
 - d) F.G.Haverlak, No 1507 (1945)
 - e) F.G.Haverlak, No 1509 (1945).

Rifle (Gewehr). See under Weapons.

Rifling of Weapons. See general section.

RLGS (Raketenleuchtgerät Scheingeschoss). Rocket Illuminant Simulating Device. See under Pyrotechnic Antipathfinder Devices and also in CIOS Rept 32-56 (1945), p 21.

R-Mine 43. See under Landmines and also in TM 9 1985 2 (1953), p 272.

Roburit (Roburite). A type of permissible explosive patented by Roth about 1886. The earliest type consisted of Am nitrate 90 and dinitrochlorobenzene 10%. It was claimed by the inventor that a nitrated chloro-compound gave a higher velocity of detonation and greater power than the corresponding nitro-hydrocarbon. The above Roburite was sensitive to friction; when ignited with a flame or a spark it burned without exploding.

Table 52 gives the composition and some properties of several Roburites
 (See next column).

References:

- 1) J.Daniel, Dictionnaire des Matières Explosives, Paris (1902), p 687


2) Marshall, v 1 (1917), p 391

3) Colver (1918), p 141.

Table 52
Roburites

| Components and Some Properties | Designation | | |
|--------------------------------|-------------|------|------|
| | I | II | III |
| Am nitrate | 87.5 | 71.5 | 55.0 |
| K nitrate | - | 5.0 | 9.5 |
| K permanganate | 0.5 | 0.5 | 0.5 |
| Am sulfate | 5.0 | - | - |
| m - DNB | 7.0 | - | - |
| TNT | - | 12.0 | 12.0 |
| Flour | - | 6.0 | 6.0 |
| Na chloride | - | 5.0 | 7.0 |
| Am chloride | - | - | 5.0 |
| Magnesite | - | - | 5.0 |
| Trauzl Test, cc | - | 325 | 257 |

Röchling Anticoncrete Projectile (Röchlingsgranate 42 Beton, abbreviated as RÖGr 42 Be). According to German photographs available at the Picatinny Arsenal and Aberdeen Proving Ground Museums, it was a subcaliber shell which resembled in appearance the "arrow projectile", except that instead of the fin assembly of the arrow shell it had a discarding flange serving as a driving band. The front flange acted as bourrelet. These projectiles were fired from regular guns, such as caliber 21 cm and 34 cm. The 21 cm shell weighed 193 kg and was 2.1 m long. The corresponding characteristics for the 34 cm shell were: 913 kg and 3.7 m.



RÖCHLING PROJECTILES

The shells were designed and manufactured by the firm Röchling at Saarbrücken, Saar.

References:


- 1) K.F.Kämpf, Museum of Aberdeen Proving Ground, Md; private communication
 - 2) H.H.Bullock and G.Coghlan, Picatinny Arsenal Museum; private communication.
- (See also Arrow Projectiles and Gessner Projectiles).

Rocket (Rakete). German rockets of WW II were propelled either by solid propellants (such as colloided smokeless double-base NC-NG propellants) or by liquid propellants. The liquid propellants consisted of combustibles (such as alcohol, benzene, aniline, gasoline etc) and oxygen carriers, such as liquid oxygen, hydrogen peroxide, nitrogen peroxide, nitric acid, etc. (See under Rocket Propellants).


The following rockets were briefly described in Ref 3. (Some information on these rockets may be found in Refs 1 and 2).

- a) Butterfly (Schmetterling) Rocket Hs117 (Hs297) (Ref 3, p 196) (See under Guided Missiles)

ROCKETS





73 mm HE Rocket (7.5cm R.Sprgr)




86 mm HE Aircraft Rocket (8.6cm R.Sprgr)


86 mm Naval Antiaircraft Rocket



86 mm Naval HE Rocket (8.6cm R.Sprgr Wsm)




88 mm Hollow Charge A/T Rocket (8.8cm RPz BÜGr)






150 mm HE Rocket 41 (15cm Wgr 41 Sprgr)

152 mm Naval Antiaircraft Rocket (Aerial-Wire Barrage Type)



ROCKETS



- b) Daughter of the Rhine (Rheintochter) Rocket (Ref 3, p 226)
- c) Fire Lily (Feuerlilie) Rockets F-25 and F-55 (Ref 3, p 221)
- d) Great Enzian Rocket (Ref 3, p 229)
- e) Henschel Rockets Hs 293 and Hs 298 (Ref 3, p 200)
- f) Long Range Rockets A-9 and A-10 (Ref 3, p 233)
- g) Radio-Controlled Glider Bomb PC 1400 FX (Ref 3, p 195)
- h) Rockets V-1 and V-2 (Ref 3, p 205)
- i) Rocket X-1 (Ref 3, p 214)
- j) Taifun Rocket (bifluid) (Ref 3, p 225)
- k) Wasserfall/Wasserfall Rocket C-2 (Ref 3, p 219)
- l) 73 mm Propaganda Rocket (73 cm Propagandagranaat) (Ref 3, p 234) and 73 mm HE Rocket Shell (73 cm Raketensprenggranaat) (Ref 3, p 235)
- m) 80 mm HE Rocket Shell (8 cm Raketensprenggranaat) (Ref 3, p 237)
- n) 86 mm HE Rocket Shell (8.6 cm Raketensprenggranaat) (Ref 3, p 239), 86 mm R Sgr L 4.5 Rocket (Ref 3, p 256), 86 mm Illuminating Rocket (Naval) (Ref 3, p 240) and 86 mm Antiaircraft Rocket (Naval) (Ref 3, p 241)
- o) 88 mm HoC, A.T Rocket (shaped charge antitank) (Ref 3, p 242)
- p) 150 mm HE Rocket (spin-stabilized) (Ref 3, p 245) and 150 mm Smoke and Chemical Rocket (spin-stabilized) (Ref 3, p 245)
- r) 152 mm Antiaircraft Rocket (fin-stabilized) (Ref 3, p 247)
- s) 200 mm Antiaircraft Rocket (fin-stabilized) (Ref 3, p 248)
- t) 210 mm HE Aircraft Rocket (spin-stabilized) (Ref 3, p 248) and 210 mm Illuminating Rocket R-Lg (Ref 3, p 258)
- u) 280 mm HE Rocket (spin-stabilized) (Ref 3, p 250)
- v) 300 mm HE Rocket (spin-stabilized) (Ref 3, p 251)
- w) 320 mm Incendiary Rocket (spin-stabilized) (Ref 3, p 253)
- x) 380 mm HE Rocket (spin-stabilized) (Ref 3, p 254)
- y) R 100 BS Air-to-Air Rocket (Ref 3, p 255)

Abbreviations: HE High explosive; HoC Hollow charge (See also Guided Missiles).

References:

- 1) A. Dueroq, Les Armes Secretes Allemandes, Berger-Levrault, Paris (1947), pp 140-149
- 2) A. Stettbacher, Spreng- und Schiesstoffe, Rascher, Zürich (1948), pp 50-5.
- 3) Dept of the Army Tech Manual TM 9-1985-2, (1953) pp 193-266
- 4) J.G. Tschinkel, Chem Eng News 32, 2582-2587 (1954)

The following Picatinny Arsenal Technical Reports were devoted to German rockets:

- 5) A.B. Schilling, Pic Arsn Tech Rept 1427 (1944), 90 mm Bazooka type rocket
- 6) A.B. Schilling, ibid 1568 (1945), Warhead and Fuzes of A-4 Rocket (Called also V-2 Rocket)
- 7) V. Lindner, ibid 1817 (1951), Evaluation of Some Rocket Propellants Used in VW II (Confidential).


Note: None of the confidential reports were used as sources of information for this work.

The following CIOS Reports contain some information on German rockets:

- 8) Gollin, CIOS 28-56 (1946), Rockets and Guided Missiles. (Included is the article of Dr W. von Braun, Survey of Development of Liquid Propellant Rockets in Germany)
- 9) F.G. Ewing & M.M. Mills, CIOS 29-45 (1945), Luftfahrt-forschungsanstalt Hermann Göring (Rockets)

- 10) R.C. Stitt, CIOS 30-115 (1945), Rocket Power Plants Designed and Constructed by Walter Werke, Kiel
- 11) F.J. Ewing & M.M. Mills, CIOS 31-13 (1945), Ramjet and Rocket Works Heerte
- 12) H.J. Eppig, CIOS 32-56 (1945), Pyrotechnic Antipath-finder Devices (Includes description of pyrotechnic rockets: 15 cm RSSG, 15 cm RLGs and 15 cm Smoke Rocket)
- 13) A.B. Meinel, CIOS 32-114 (1945), 21 cm RLG Rocket (Flare).

Rocket-Assisted Shell. A projectile which contained a rocket propellant in a special device attached to the base of the shell was developed and used during WW II. The shell was fired in a regular manner from an 8 inch gun, but during the flight the rocket composition became ignited and the shell started to function as a rocket. This method of propulsion increased the range of the shell from 38 to 60 miles without appreciable increase of dispersion. Reference: PB Rept 925 (1945), p 19.



The following rocket-assisted projectiles are briefly described in TM 9-1985-3 (1953), pp 509-10 and 527-8: a) 150 mm Projectile (15 cm RGr 19) weighed 99.5 lb and was fired from the Heavy Field Howitzer 18 (15 cm

SH 18). Its cartridge case (semi-fixed) contained 17.4 lb of tubular, diethyleneglycol dinitrate type propellant


b) 280 mm Projectile (28 cm RGz 4331) weighed (without rocket ignition fuze) 546 lb and was fired from the Railway Gun, 28 cm K 5(L). Its propellant charge was 43 lb of double-base propellant, and the bursting charge was 30 lb of unknown HE. The shell was provided with a rocket ignition fuze (Ztz S/30) which functioned after 19 seconds to ignite the rocket propellant and with two fuzes (AZ 4331) and two PETN boosters (Zzdlg C/98Np) which initiated the bursting charge on impact

c) In CIOS Rept 30-115 (1945), pp 26-27 and enclosure 26 are briefly described the Rocket Assisted Take-Off Units, designated as RI 203 and RI 209.

The following unclassified Picatinny Arsenal Technical Reports describe some rocket-assisted shells which were examined during WW II.

- 1) A.B.Schilling, 1604 (1946), 105 mm Rocket-Assisted, HE
- 2) A.B.Schilling, 1605 (1946), 105 mm Rocket-Assisted, HE
- 3) A.B.Schilling, 1606 (1946), 128 mm Rocket-Assisted, HE
- 4) A.B.Schilling, 1607 (1946), 150 mm Rocket-Assisted, HE
- 5) A.B.Schilling, 1608 (1946), 150 mm Rocket-Assisted, HE
- 6) A.B.Schilling, 1609 (1946), 150 mm Rocket-Assisted, HE
- 7) A.B.Schilling, 1610 (1946), 150 mm Rocket-Assisted, AP

Rocket Bomb Fuze Assembly, described on pp 169-71 of TM 9-1985-2 (1953) operated as follows: On release from the aircraft the electric charge passed from the charging head to the distributor and thence directly to the bomb fuze. Then, after a delay, the current passed to the



rocket propellant igniter. During the flight, the rocket was ignited and when the bomb hit the target the impact initiated the fuze. After a short delay (for penetration purposes) the bursting charge was detonated.

Rocket Bullet. According to CIOS Rept 33-20 (1946), pp 6, 6A & 7, a 9 mm rocket missile was under development during WW II by the Deutsche Waffen- und Munitionsfabriken A-G, Lübeck. A drawing is enclosed in CIOS Rept 33-20 but no description given.

Rocket Launcher or Projector (Raketenwurfmaschine oder Wurfgerät). According to the Intelligence Bulletin, War Department, Washington, D C, vol 3, No 7, March 1945, pp 1-9, the first German rocket launchers were *Schweres Wurfgerät 40* (heavy throwing apparatus 40) and *Schweres Wurfgerät 41*. Each of them could fire either 280 mm or 320 mm rockets weighing 180 and 196 lb respectively. The 300 mm HE rocket also could be fired from these launchers.

The SWG 40 launcher consisted of a wooden frame (Wurfgestell 40) on which were placed wooden shipping crates containing rockets. The frame was inclined at

the desired angle and the rockets were fired directly from the crates.

The SWG 41 launcher consisted of a frame of steel tubing (Wurfgestell 41) on which could be placed either wooden or steel shipping crates containing rockets.

The so-called *Schweres Wurfrahmen 40* (heavy throwing rack 40) consisted of six inclined plates mounted on the sides of an armored half truck (three on each side). The rocket carrying crates were secured to the plates, and the latter then inclined at the required angle of firing.

One of the most important rocket projectors was the 15 cm *Nebelwerfer 41* (literally "smoke thrower"), nicknamed by the US soldiers "Screaming Meemie". It consisted of six grooved tubes, 5.9" in diameter, mounted on a light two-wheeled carriage with a split trail. The crew of two men loaded the weapon, took shelter in a slit trench and then discharged the rockets (a six-round salvo each 8 minutes) by remote control. The maximum range of these rockets was 8,000 yd.

Similar to the 15 cm *Nebelwerfer 41* was the five-tube 21 cm *Nebelwerfer 42* which fired 8 inch rockets as far as 8,600 yd.

Note: None of the *Nebelwerfers* were accurate and for this reason they were not very suitable for launching HE rockets. Besides using these launchers for rockets to lay down smoke concentrations, they were also suitable as projectors for gas-loaded (chemical) rockets. In both cases no accuracy of fire was required.

In order to give their larger rocket projectors greater mobility and speed of fire, and to increase the accuracy of fire of the rockets the Germans mounted the steel frames of the *Wurfgerät 41* on two-wheeled carriages with pneumatic tires. The resulting weapons were called 28/32 cm *Nebelwerfer 41* and 30 cm *Nebelwerfer 42*. The steel shipping crates containing rockets were inserted in the frames and then, when ready to fire, the crew (seven men per each launcher) took cover in two slit trenches to the rear of the right side of the weapon and one of the men fired a six-round salvo by remote control. It took about 5 minutes to reload the weapon. The maximum range for the 280 mm HE rocket was only 2,100 yd and for the 320 mm incendiary rocket 2,400 yd. The range for the 300 mm rocket is not given.

Dissatisfied with the slow rate of fire of the above launchers, the Germans in 1942 introduced a quicker firing weapon called the 15 cm *Panzerwerfer 42* (150 mm anti-tank thrower 42). It consisted of two banks of 15 cm *Nebelwerfer 41* launching tubes (with six tubes in each bank) mounted on an armored half-track. Since the crew did not need to dig slit trenches, but could take cover in the vehicle instead, the rockets could be fired somewhat faster than from the *Nebelwerfer 41*.

According to TM 9-1985-2 (1953), p 193, multibarrel projectors carrying up to 42 rocket rounds were developed by the Germans to effect a greater rate of fire. Reloading of these projectors was carried out mechanically.


The same TM 9-1985-2 mentions or briefly describes the following rocket launchers used during WW II:

- a) A two-armed cradle type launcher for the Hs 117 (Hs 297) Schmetterling rocket-propelled missile (p 201)
- b) A rail type launcher, 60 cm long (hung on the carrier aircraft) for the Hs 298 missile (p 205)
- c) An inclined ramp type launcher used for the Feuerlilie F-55 rocket-propelled guided missile (p 225)
- d) A launcher for the Great Enzian rocket consisted of two iron rails 6.8 m long; mounted on a standard 88 mm gun carriage (p 229)
- e) A single-tube type launcher (*Propagandawerfer*) for 7.3 cm *Raketengranate 41* (p 234)
- f) A 35-frame launcher (*Föhngerät*) for 7.3 cm *Raketensprenggranate* (p 235)
- g) A multiple-frame ground launcher (*Raketen Vielfachwerfer*) for 8 cm *Raketensprenggranate* (p 237)
- h) A single-barreled launcher, designated as 8.6 cm *R Ag M42*, for the 86 mm flare rocket (R Lg 1000) or wire rocket (RDg 1000) (p 240)
- i) A single tube, two-wheel launcher (8.8 cm *Raketenerwerfer 43*) for the 88 mm hollow charge rocket, designated as 8.8 cm *R PzHGr 4322* (*Raketen Panzerbuche Granate*) (p 245)
- j) A single-barreled launcher designated as 21 cm *R Ag M42*, with a barrel 1.12 m in length, used for the 210 mm rocket designated 21 cm *RLg* (p 259)


ROCKET LAUNCHERS



Launcher Panzerschreck
(New Long Model)
(6.8cm RPzBü 54)





Launcher Panzerschreck
(Short Model)
(6.8 cm RPzBü 54)



Launcher Panzertfaust

Rocket Launcher
(Wurfrahmen 40)




IGNITION WIRES


Rocket Launcher
(28/32 cm Wurfgerät 41)




Launcher (28/32 cm Nebelwerfer 41)



Launcher (15 cm Nebelwerfer 41)



Launcher (Do-Werfer or Wurfgerät)




Launcher (15 cm Panzerwerfer 42)

k) A four frame launching stand (Wurfgerät) for the 280 mm HE rocket (28 cm Wk Spr) (p 251). (See also under Weapons).

Rocket Projectile. See Rocket-Assisted Shell.


Note: Rocket-assisted projectiles were fired either from howitzers or guns. For instance the 15 cm RGr 19 was fired from the 15 cm sFH 18 (heavy field howitzer 18) and the 28 cm RGr 4331 was fired from the 28 cm K5 (E) (railroad gun 5). See TM 9-1985-3 (1953), pp 501 & 527.

Rocket Propellant. According to T. J. Rudański, Przemysł Chemiczny 27 (4), p 487 (1948), (translated by Dr L. Simon), the Germans used solid double-base propellants containing nitrocellulose and nitroglycerin in their smaller rockets. The larger types, such as the V-2, used liquid propellants consisting of a fuel (such as alcohol, hydrazine, fuel oil etc) and an oxygen carrier (such as hydrogen peroxide, nitric acid, t-tranitromethane, etc). Mixtures of easily oxidizable organic liquids with hydrogen peroxide of 80-85% concentration were the most widely used. Hydrogen peroxide could also be used as the driving force, without any fuel, because the heat liberated according to the reaction of decomposition:




was sufficiently great. Water (vapor) and oxygen served as driving forces.

Rocket Propellant Igniter ERZ 39, briefly described on p 623 of TM 9-1985-3 (1953), fitted into one of the venturi of the 15 cm and 21 cm rockets. Its body, made of a plastic with an aluminum band around the shoulder, contained an igniter bridge from which ran two wires. One wire was connected to the aluminum band around the shoulder and the other to a metal disk in the base of the fuze. Just above the igniter bridge was located a black powder charge. When an electric current passed through the bridge it ignited the black powder, which in turn ignited the propellant. This modified version of igniter (ERZ 39B) was manufactured from heat resistant material.



ERZ 39



Rocket Propellant. Inhibiting Coating. In order to prepare a stick of propellant so that it would burn from an end and not on the sides, the claim was made that it was sufficient to cover the sides of each stick by dipping it twice into a special composition developed at the Duneberg Fabrik of the Dynamit A-G. This composition consisted of: polyvinylacetate 25, lithopone (2nS + BaSO₄) 30, methylacrylate 5 and water 40%.

Reference: A.A. Swanson and D.D. Sager, CIGS Rept 29-24 (1946), p 5 (As reported by Dr H. Leunig).

Rocket Propellants, Liquid. The following liquid rocket propellants were used by the Germans during WW II:

a) Concentrated hydrogen peroxide and C-Stoff was used in the Ba 349B Natter Rocket (surface-to-air)

Note: C-Stoff is a 50/50 mixture of methanol and hydrazine hydrate, N₂H₄·H₂O

b) Concentrated nitric acid and Visol-6 was used in the Enzian E-4 Rocket, Rheintochter R-3 Rocket and Wasserfall Rocket

Note: Visol-6 is vinyl ethyl ether

c) Concentrated nitric acid and Tonka were used in the Rautstahl X-1 Rocket

Note: Tonka is a mixture of aniline, monoethylaniline, dimethylaniline, gasoline, naphtha, triethylamine and isohexylamine

d) Concentrated hydrogen peroxide with K permanganate was used in the Liecht Rocket

e) Liquid oxygen alcohol and water were used in the V-2 Rocket and Feuerlilie-55 Rocket

Note: The noncombustible substance, water, was incorporated in order to keep the flame temperature as low as possible so as to reduce the mechanical strain on the motor without sacrificing too much performance. It was found that the addition of 25% of water to absolute alcohol lowered the chamber temperature 7%, while the exhaust velocity was lowered only 3.5%

f) Concentrated nitric acid, xylidine and triethylamine were used in the Schmetterling Hs117 Rocket

g) Concentrated nitric acid and butyl ether were used in the Taifun Rocket

h) Compressed oxygen and gasoline were used in the V-1 Rocket

Note: In addition to these, the following substances were used in liquid fuels: aniline, ethyldeneaniline, ethylidinedianiline, acetaldehyde, naphtha, gasoline, dimethylaniline, monomethylaniline, triethylamine, isohexylamine, etc. In some of these liquids, such as aniline, Visol-6 etc pyrocatechol (Brenzkatechin in German) was dissolved.

References:

- 1) H. Garmann, Weltraumfahrt 6, 134-9 (1951), Jato and Auxiliary Rocket Propellant Plants
- 2) K.W. Gatland, Development of the Guided Missile, Philosophical Library, N Y (1952), pp 112-127
- 3) J.G. Tschinkel, Chem Eng News 32, 2582-87 (1954), Propellants for Rockets and Space Ships.

Rocket Propellants, Solid. All known German propellants of WW II were based on NC and a nitric ester, such as NG, DEGDN, or TEGDN.

Table 53 lists some of the rocket propellants examined at Picatinny Arsenal during WW II

(See next page).

Donin and Donovan (Ref 3) give the burning rates (in inches per second) at various pressures for the solid propellant used in the 210 mm Rocket (See Table 54 on next page). The composition of the propellant is given in Table 53.

The same investigators give the rates of burning for the Jet-Assisted-Take-Off-Unit Propellant listed in Table 53

(See Table 55 on next page).

Table 53
Rocket Propellants, Solid

| Form | Composition, % | | | | | | | | Uses |
|------|----------------|----------|------|-------|------|------|-------------|--|--|
| | NC | %N in NC | NG | DEGDN | Cent | Acar | Graphite | Other Ingredients | |
| SP | 62.5 | 12.0 | 33.0 | - | - | 0.2 | 0.1 (incor) | EtPhUret 1.5 DPhUret 1.8 Unac 0.9% | 150 mm HE Rocket |
| SP | 58.7 | 12.7 | - | 35.3 | - | 0.2 | 0.3 (incor) | EtPhUret 1.3 DPhUret 2.5% Unac 1.7% | 210 mm Rocket |
| - | 84.1 | 12.7 | 12.7 | - | 0.8 | 2.4 | - | - | 210 mm Rocket (Igniter Pad) |
| - | 89.2 | 12.7 | - | 5.3 | 0.9 | - | - | DPhA 2.6% Unac 2.0% | 210 mm Rocket (Head Igniter Diaphragm) |
| Cyl | 59.6 | 12.5 | - | 33.6 | - | - | 0.2 (incor) | DPhUrea 1.5 DPhUret 3.0 Unac 2.1% | 75 mm Leaflet Rocket |
| - | 61.7 | 12.0 | - | 29.3 | - | 0.2 | 0.1 | EtPhUret 3.5 DPhUret 1.3 (TiO ₂ +BaSO ₄) 0.9% | Jet Assisted Take Off Unit |

Abbreviations: Acar Acardite; Cent Centralite; Cyl Cylinder; DEGDN Diethylene glycol dinitrate; DPhA Diphenylamine; DPhUrea Diphenylurea; DPhUret Diphenylurethane; EtPhUret Ethylphenylurethane; HE High explosive; incor Incorporated; N Nitrogen; NC Nitrocellulose; NG Nitroglycerin; psi pounds per square inch; Unac Unaccounted. Notes:

a) The composition of the German 150 mm rocket propellant containing NG does not represent anything new except the combination of several stabilizing agents. The same combination was noted in rocket propellants containing DEGDN.

b) While the characteristics of the German rocket propellants containing DEGDN are of interest, they show nothing that is new as far as the composition is concerned. The 210 mm rocket propellant was made from NC, with a viscosity of 5.38 poises at 25°, which was plasticized with DEGDN and rolled into a sheet. This in turn was rolled into a "carpet" which was extruded through a hot die to give a single-perforated cylinder. It seems that a small amount of carnauba wax was used as a lubricant to facilitate extrusion.

c) Combinations of disubstituted urethanes with either centralite or acardite (asym diphenylurea) were used as stabilizers because it was believed that mixtures are more effective than single stabilizers such as DPhA. To this may be added that, according to M. Tonogutti [S S 32, 302 (1937)], the disubstituted urethanes are very good stabilizers for double-base propellants, especially when used in combination with acardite, while without the latter they are much less effective.

Note: Some rocket propellants and igniters analyzed at Picatinny Arsenal are listed under Propellants (See Tables 43, 44, 45b and 48).

Table 54
Burning Rates of 210 mm Rocket Propellant
(Inches per second)

| Temp °C | Pressure in psi | | | | |
|---------|-----------------|------|------|------|------|
| | 500 | 1500 | 2500 | 3500 | 4500 |
| - 25 | - | 0.30 | 0.42 | 0.55 | - |
| + 50 | 0.21 | 0.43 | 0.55 | 0.73 | 0.93 |

Table 55
Burning Rates of the Jet-Assisted-Take-Off-Unit Propellant

| Temp °C | Pressure in psi | | | | | |
|---------|-----------------|------|------|------|------|------|
| | 800 | 1000 | 1500 | 2000 | 3000 | 3500 |
| - 25 | 0.15 | 0.18 | 0.25 | 0.33 | 0.43 | 0.48 |
| + 50 | 0.22 | 0.27 | 0.39 | 0.47 | 0.59 | 0.66 |

According to Ref 4, the Reinsdorf Fabrik W A S A - G manufactured during WW II several types of rocket propellants. Their compositions are given in Table 56.

Table 56
Rocket Propellants, Solid of W A S A - G

| Components and some properties | Designation | | | | |
|--|-------------|-------|-------|-------|-------|
| | R61 | R6m | Z135 | Z193 | Z167 |
| Nitrocellulose (NC) | 59.80 | 57.70 | 49.10 | 63.25 | 54.90 |
| % Nitrogen in NC | 12.5 | 12.5 | 12.7 | 12.5 | 12.5 |
| Diethylene glycol dinitrate (DEGDN) | 35.30 | 38.00 | 30.00 | - | 16.35 |
| Triethylene glycol dinitrate (TEGDN) | - | - | - | 22.00 | - |
| Pentaerythritol tetranitrate (PETN) | - | - | 20.00 | 6.00 | 6.00 |
| Ethylphenylurethane | 1.10 | - | - | - | - |
| Diphenylurethane | 0.80 | - | - | - | - |
| Dibutylphthalate | - | 3.00 | - | - | - |
| Acardite 1, CO(NH ₂)N(C ₆ H ₅) ₂ | 0.30 | 0.50 | 0.75 | 0.50 | 0.50 |
| Graphite | - | 0.30 | 0.10 | - | - |
| Magnesium oxide | 0.25 | 0.50 | 0.05 | - | - |
| IG Farben Wax F | 0.35 | - | - | - | - |
| Potassium nitrate | 0.60 | - | - | - | - |
| Lignin | - | - | - | - | 0.75 |
| Hydrocellulose | 1.50 | - | - | 0.75 | - |
| Trinitrotoluene (TNT) | - | - | - | 3.00 | 12.50 |
| Dinitrotoluene (DNT) | - | - | - | 4.50 | 9.00 |
| Moisture (not included in total) | 1.00 | 0.65 | 1.00 | 1.00 | 0.90 |
| Oxygen Balance, % | -7.11 | -7.93 | +0.10 | -9.31 | -9.92 |
| Calorific Value kcal/kg | 905 | 887 | 1071 | 868 | 826 |

* Titanium oxide (TiO₂)


References:

- 1. A. J. Phillips, *Exp. Aiso. Tech. Rep. 1282* (1944); *Ibid* 1284 (1949).
- 2. Collective Data on Foreign Ammunition, PB Rept 11,544 (1945).
- 3. M. S. Loom & J. J. Donovan, Captured Enemy Propellants, OSRD of AFPC, Div 3, Sect H, Final Rept, Series P, No. 102 (1945) (Unclassified) (OSRD 5853).
- 4. J. L. K. ... & M. Plosser, PB Rept 1826 (1945), p. 6.
- 5. J. L. K. ... *Engng. Chem.* 36, 1609 (1946).
- 6. *J. Appl. Chem. & Industrie*, 57, 211 (1947).
- 7. J. L. Schinkel, *Chem. Eng. Prog.* 32, 2582-87 (1954) Propellants for Rockets and Space S... .

Rocket Signal Simulating Device (15 cm Raketen Schein-schuss Gerat, abbreviated as ESSG). See under Pyrotechnic Antipathfinder Device.


Rodded Bomb or Stick Grenade (Stielgranate). The following roddeed projectiles are described in TM 9 1985-3 (1953), pp 383-5 & 198-500:

- a) 3.7 cm Stielgranate 41 used in the Antitank Gun, 3.7 cm Pak 41 (Panzerabwehrkanone 41) consisted of an egg-shaped head (body) and a cylindrical tail provided with 6 fins. The head contained a shaped bursting charge consisting of 5.28 lb of 60/40-RDX/TNT (2 blocks wrapped in wax paper), two boosters (KzZdlg).



a nose fuze (AZ 5075) and a base fuze (BdZ 5130). The tail portion of the projectile consisted of a rod which fitted into the bore of the gun, and a concentric perforated sleeve which fitted over the barrel of the gun. Tubular double-base NC-NG propellant (NgIRP), 6.61 oz. enclosed in a cartridge case, closed by two cork discs, was used as the propellant. Total weight of projectile 18.26 lb and overall length 27.362"

b) 15 cm Stielgranate 42 used in 15 cm ulk. 33 (schwer. Infanteriegeschütz 33) (Heavy Infantry Gun) consisted of an elliptical-shaped body, 11.5" max diameter, and a roddeed tail section provided with large fins. The body contained 66.0 lb of 60/40-Am nitrate/TNT (bursting charge), a long booster and a nose fuze (WgrZ 36). Small, secondary fins were attached to the rear of the body. A cup with a machined surface was attached at the base. It is presumed that the bomb was provided with a large rod which fitted over the cup and



entered the muzzle of the gun before firing. This rod dropped from the projectile about 150 yd from the muzzle. The bomb was propelled by 12.1 lb of propellant contained in a semi-fixed cartridge case. Total weight of the projectile was 105.0 lb and overall length 50.5". It was used against personnel and to clear minefields and wire obstacles.

c) 37 mm Hollow Charge Stick Rifle Grenade, briefly described under Rifle Grenades, was similar to the 3.7 cm Stielgranate 41 (See also Stick Hand Grenade).

Rohsenszunder Pulver (RZP). Finely pulverized iron prepared by atomizing molten cast iron by a cone of moist air at a pressure of 2 to 3 atm. During this process most of the carbon was oxidized to CO₂ and thus removed. A large part of the iron was also oxidized during atomizing but it was recovered as pure iron on subsequent cooling in water and reduction with hydrogen. This powder was used in the manufacture of sintered iron items many of them of military use.

Reference: CIOS Final Rept 395 (1945), p 52.

Röhrenpulver (RP) (Tubular Propellant). A propellant similar in form to the British Cordite. The compositions of some tubular propellants are given in Refs 1 and 2.

- a) NC 64, NG 43 and vas. line 3% (Ref 1)
 b) Guncotton (Schliesswolle) 66, TNT 25, DNT 5.5, centralite 0.5, K bitartrate 2.0 and moisture 1.0% (Ref 2, p 134)
 c) Collodion cotton Q-34, guncotton 32-34, NG 25-29, centralite or urethane 1 to 7, Am oxalate 0.5, Na bicarbonate 0.5, graphite 0.1 and moisture 0.9% (Ref 2, p 136).

References:

- 1) E. de B. Barnett, Explosives, Van Nostrand, N Y (1919), p 78
 2) H. Brunswig, Das rauchlose Pulver, W. de Gruyter, Berlin (1926), pp 131 & 136.

Rohrenpulver C 32 (RPC/32). (Tubular propellant, pattern 1932). It contained: NC 64.76, NG 26.87, Et centralite 5.7, Na nitrate 0.56, graphite 0.20 and volatile matter 0.56. Was used in fixed artillery ammunition, calibers 150 mm, 170 mm, 203 mm and 240 mm.
 Reference: TM 9-1985-3 (1953), p 504.

Rohrenpulver C/38 (RPC/38). (Tubular propellant pattern 1938). According to the Manual entitled: German Artillery Projectile and Fuzes, published during WWII at the Aberdeen Proving Ground, Md, p 183, the RPC 38 propellant was used in 150 mm HE Projectile, 4.5 calibers long, with point detonating fuze under ballistic cap. Although the composition is not given in the above manual, it is safe to assume that the RPC/38 was one of the diethyleneglycol-dinitrate propellants developed at that time by Gallwitz (See "G" Pulver).

Rohpulvermasse (Raw Propellant Mass, called also Raw Paste). This was a mixture of water-wet nitrocellulose with an explosive oil which consisted of one or several organic nitric acid esters, such as NG, DEGDN or TEGDN. Such mixtures could be safely transported when the smokeless propellant plant was not located adjacent to the plants manufacturing NC and nitric esters. For instance, the Krümmel Fabrik of DA-G manufactured NC and organic acid esters, while the Dünneberg Fabrik, situated about 4 miles away, made the solventless propellants. As it was not safe or convenient to ship liquid explosives, the Krümmel plant mixed them with water-wet nitrocelluloses prep'd by blending guncotton (Schliesswolle) (N=13.15% to 13.2%) and collodion cotton (PE-Wolle) (N=11.30 to 11.45%), packed the mixture in rubber-lined linen bags and shipped them to the Dünneberg plant to be used for the preparation of solventless propellants.

For the prep'n of Rohpulvermasse about 290 kg of NC (calculated on the dry weight) was stirred for about 10 minutes with water. About 120 kg of a nitric ester was added to the mixture and stirring was continued for 10 minutes. The slurry was then transferred to a centrifuge where the water content of the mass was reduced to 30-35%. The resulting Rohpulvermasse was packed in rubber-lined linen bags and transported to the Dünneberg plant.

When received at the plant, the required number of bags were emptied into large drums. After the contents of the bags were blended, the mixture was transferred to the preheated Werner-Pfleiderer kneaders. The other ingredients of propellants such as stabilizers, graphite, Mg oxide, etc were added in the kneader and, after allowing the blend to mature for about one week (two weeks for NGu propellants), it was passed through a helical screw press in order to reduce the moisture content from 30-35% to about 8%. The partially dehydrated product was fed to horizontal rolls, diameter 0.4 m length 1.0 to 2.0 m and

rotating at 11 rpm. A temp of 70-80° was used for DEGDN powders. The time of processing was 18 to 30 minutes for a 15 kg sheet. Between 3 and 5% of moisture was allowed to remain in cannon propellants. The resulting sheet was trimmed to size and wound on a brass mandrel about 1 3/4" diam. The sheet could also be used for the preparation of extruded propellants. The extrusion should immediately follow the rolling while the sheet is still hot. It was claimed that the inclusion of 0.25% MgO facilitated the extrusion. It does not seem that any wax was used for lubrication. The resulting extruded propellant contained 3 to 5% moisture and had to be dried in stoves to reduce the moisture to 1.0-1.2%.

Reference:

O.W. Stickland et al, General Summary of Explosive Plants, PB Rept 925 (1944), pp 6, 10 and 65.

Rohtri. German designation for Crude Trinitrotoluene.

Romperit 1 (Komperite 1). A mining explosive contg approximately, Am nitrate 86, NG with nitroglycol 8 to 10%, the rest being TNT, aluminum and other ingredients.

Reference:

F. Weichelt, Handbuch der gewerblichen Sprengtechnik, C. Marhold, Halle/Saale, (1953), p 37.
 (See also Donarit and Gelatine-Komperit).

Rotierende Trommel (Rotating Drum). An apparatus for determining the velocity of detonation and for other purposes. See general section and also A. Stettbacher, Spreng- und Schiesstoffe (1948), pp 11-12.

"Rotram" Separator. This apparatus, installed at the Krümmel Fabrik A-G in conjunction with the Holländer beater, was used to remove the fines of NC from the slurry as fast as they were produced on beating. A considerable saving in power and in time was claimed for the Rotram.
 Reference: A.A. Swanson & D.D. Sager, CIOS Rept 29-24 (1946), p 7.

Royal Tiger (Königstiger). See under Panzer.

RPC/12. One of the earliest solventless propellants. It was prep'd about 1909 by Thieme and collaborators at the Zentralstelle für Wissenschaftlich-technische Untersuchungen in Neubabelsberg by incorporating 70 parts of NC (N=11.7%) with 25 p of NG and 5 p of centralite. It was suitable for use in large caliber guns (P. Tavernier, Mémoires 32, 253 (1950)).
 (See also under Propellants, Artillery).

RPC/32 (Röhrenpulver Konstruktion 32). A tubular propellant introduced in 1932 for use in the 150 mm Naval Gun (15 cm SK), 150 mm Gun in Mortar Mount (15 cm K ins MrsLuf), 170 mm Railroad Gun (15 cm K(E)), and in some other guns. Its approximate composition was: NC 64.7, NG 26.9, ethyl centralite 5.7, Na nitrate 0.6, graphite 0.2 and volatile matter 1.9%.
 Reference: TM 9-1985-3 (1953), pp 504-516.

RRP (Rauchloses Rottweiler Pulver). Smokeless propellant manufactured at the beginning of the present century by Vereinigte Köln-Rottweiler Pulverfabriken in Württemberg. This propellant was exported to Belgium and other countries.
 Reference: J. Daniel, Dictionnaire des Matières Explosives, Dunod, Paris (1902), p 696.

R-Salz (R-Salt) described in the general section as **Cyclo-trimethylenetrinitrosamine**, was prep'd in Germany by Römer et al by treating hexamethylenetetramine (hexamine) with sodium nitrite in acid solution.

R-Salz was proposed as an ingredient of explosive mixtures.

Table 57 lists these explosives

Table 57
R-Salt Explosives

| Ingredients and Some Properties | Composition (%) of Mixtures: | | | | | | | |
|---|---|--------|-------|-------|-------|------|------|------------------------|
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| R - Salz | 96.5 | 46.5 | 36.5 | 46.5 | 36.5 | 96.5 | 36.0 | 40.0 |
| Phenathrene | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | - | - | - |
| Diphenylamine | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | - |
| RDX (Hexogen) | - | 50.0 | 50.0 | - | 40.0 | - | 50.0 | 40.0 (H ₅) |
| Aluminum powder | - | - | 10.0 | - | 20.0 | - | - | 20.0 |
| K nitrate | - | - | - | 50.0 | - | - | - | - |
| Dimethylethylenedinitramine | - | - | - | - | - | 2.5 | 12.0 | - |
| Unaccounted | - | - | - | - | - | - | 1.0 | - |
| Casting Temp °C | 92 | 92 | 95 | 94 | 95 | 92 | - | - |
| Dens ^g (cast) | 1.55 | 1.65 | 1.64 | 1.77 | 1.74 | 1.55 | - | - |
| Veloc of Deton, m/sec | 7600 | - | - | 6100 | 7750 | 7850 | - | - |
| Pb Plate Test: The mixture is more effective than | TNT | Cyclo- | 40/60 | 40/60 | 40/60 | - | - | - |
| Fragment Density | 44 m | 47 m | 47 m | 47 m | - | - | - | - |
| Test (TNT = 40 m) | | | | | | | | |
| Stability at 100° | Satisfactory stability for all explosives | | | | | | | |
| Exudation at 70° | No exudation for any of the explosives | | | | | | | |

Notes:

a) H₅ is Hexogen (RDX) phlegmatized with 5% Montan wax

b) Mixture (8) was claimed to be very powerful

c) R - Salt forms with 28% dimethylethylenedinitramine (DMEDNA) a eutectic mixture, freezing point (fr p) 74°. Fr p of R - Salt with 10% DMEDNA is 89° and with 5% DMEDNA 93°. Fr p of R-Salt alone 104-106° and of DMEDNA 137°.

Reference: G.Römer, Report on Explosives, PRL Rept 85,160 (1946), pp 3-15.

RSSG (Raketen Scheinsschussgerät). Rocket Signal Simulating Device. See under Pyrotechnic Antipathfinder Devices and also in CIOS Rept 32-56 (1945), p 3.

RZ 73 "Flight". A 73 mm air-to-air missile developed in 1941 by converting an Army rocket. It used a solid propellant and could be considered as the predecessor of RAM (qv).
Reference: K.W.Gatland, Development of the Guided Missile, "Flight" Publication, London (1952), pp 122-3.

"RZ" Smoke Cartridges. See under Smoke Composition and Devices.

S-1 to S-18 Explosives. See under Unterwassersprengstoffe.

S-6 and S-6 Mod Explosives. See under Ersatzsprengstoffe.

S-16 and S-19 Explosives. See under Ersatzsprengstoffe.

S-19 and S-22 Hexo Explosives. See under Ersatzsprengstoffe.

S-22 and S-26 Hexo Explosives. See under Ersatzsprengstoffe.

Sabot Projectile (Treibspiegelgeschoss) consisted of a relatively small subcaliber projectile carried in a relatively large casing (sabot) of softer material. The latter was discarded as the projectile left the bore of the gun. The principle of this projectile was to have a large surface exposed to the pressure of propelling gases and then to have the surface reduced so that the air resistance became small. These projectiles were never very accurate.

One type of German sabot projectile was armor-piercing and consisted of a sintered tungsten carbide core and the softer sabot which was not discarded until the core began to penetrate the target (such as the armor of a tank). After this the core disintegrated, which caused a deadly spray of fine fragments inside the target (such as a tank).

Some of the sabot projectiles, described in Ref 2, were provided with one or two discarding bands, each in one piece. They were fired from normal rifled guns. Some of these projectiles were called Disintegrating Rotating Bands Projectiles (qv).

References:


- 1) L.E.Simon, German Research in WW II, Wiley, NY (1947), p 189
- 2) Dept of the Army Tech Manual TM 9-1985-3 (1953), pp 363-70 (See drawing on next page).

Safety Jelly Dynamite. One of the older permissible explosives: NG 32.25, collod cotton 1.25, glue-glycerin-dextrin jelly 9.60, rye flour 18.00, Am nitrate, 22.60, Na nitrate 10.80 and K chloride 5.50%.
Reference: P.Naoum, Nitroglycerin, Baltimore (1928), p 407.

"Salbei" Code name for either 99.5% HOKO nitric acid or its mixture with 5 to 10% sulfuric acid, when used as an oxygen carrier in liquid rocket propellants. One of the liquid fuels used in conjunction with Salbei was Tonka (qv). H₂SO₄ was added to suppress corrosion.

References:

- 1) CIOS Rept 28-56 (1945), p 76
- 2) TM 9-1985-2 (1953), pp 216 & 231.



Ballistic Cap


Armor Piercing Cap

Discarding Sabot Element

Bursting Charge

Discarding Sabot Element

Sabot Projectiles



Fuze

Fuze Adapter Discarding Sabot Element

Bursting Charge

Discarding Sabot Element

Solit (Salite). One of the older permissible explosives: NG 11.8, collodion cotton 0.5, Am nitrate 53.6, DNT 3.5, Na chloride 25.1 and carbohydrates 2.5%; Trauzl test value 287 cc and charge limite 660 g. Reference: A. Marshall, Explosives, London v I (1917), p 397.

Salpetersäure. See Nitric Acid.

Sünger-Bredt Missile, called **Antipodal Bomber,** was a supersonic rocket designed by Dr. E. Sünger before 1942, but the project work was abandoned without any practical development. This design embodied many unique features, which are briefly described by Gatland on pp 57-8. It was planned to use the rocket in regions above a dense atmosphere. Each time it dived and hit a denser layer of air, the missile was supposed to bounce upwards. These movements would produce a kind of wave-shaped trajectory, similar to that obtained when a flat stone is ricocheted across water, but much less pronounced. As each plunge into a denser air would result in a partial loss of kinetic energy of the missile, the initially long jumps would gradually become shorter, finally to be transformed into an even gliding flight. It was presumed that this method would achieve a stable flight and a more accurate trajectory in a region above dense air, where conventional missiles usually behave rather erratically. The rocket was designed to be catapult launched and to be propelled by an oil/liquid oxygen mixture. Its calculated characteristics were: launching weight 220,500 lb, overall length (less booster) 91.8 ft, width of rectangular section 5.9 ft x 11.8 ft, maximum range 11,000 miles and maximum altitude 93 miles.

Reference: K.W. Gatland, Development of the Guided Missile, "Flight" Publication, London, (1952) pp, 57-8 & 124-5.

Sarin. See under Trilons.

Satzröcher. An igniter contg a compressed mixture of meal powder (Mehlpulver) with a slow-burning substance such as a mixture of sulfur and K nitrate. Reference: Kast-Metz, Chemische Untersuchung, (1944), p 535.

Sauerstoffbilanz oder Sauerstoffwert (Oxygen Balance or Oxygen Value), abbreviated to O.B. It may be determined in the manner described in the general section or by the method given in A. Stettbacher, Spreng- und Schießstoffe, Zürich (1948), pp 16-18.

Säulenketmaschine. See under Knetmaschine.

Saxonia Pulver. One of the pre-WW II sporting smokeless propellants: guncotton 95.0, TNT 4.0 and gelatinizer with some moisture 1.0%. Reference: H. Brunswig, Das rauchlose Pulver (1926), p 134.

Schaffler - Glückl Fusehead Comb, invented before WW II in Austria, was later improved and used at the Troisdorf Fabrik, D.A.G. It is briefly described in BIOS Final Rept 644 (1945), pp 9-11. In Germany, this comb replaced the previously used Krannichfeldt pressboard galvanotype comb.

Scheidemehl (Dust of Picked Ore). A mixture consisting chiefly of Ca and Mg silicates was used during WW II in some substitute explosives (Ersatzsprengstoffe) as an extender of nitrocompounds which were not available during the war in sufficient quantity. Reference: PB Rept 1820 (1945), p 11.

Schiessbaumwolle. See Schiesswolle.

Schiessbecher. A rifled, caliber 30 mm, discharger cup which could be fitted to most types of German rifles. Was used for launching some antitank rifle grenades. A photo of the Schiessbecher but no description is given in the Ordnance Sergeant, October 1945, p 9.



This photo is by courtesy of Aberdeen Proving Ground, Maryland.

Schiessmörser (Shooting Mortar). A device used for testing mining explosives in galleries filled with firedamp and or coal dust.

Reference: M.Lopus, S S 20, 190 (1925).

Schiesswolle (Guncotton). Nitrocellulose of 13.2-13.3% nitrogen content, corresponding approximately to the Amer Guncotton. It was used in the manufacture of some smokeless propellants (See also Nitrocellulose and under Propellants).

Schiesswolle (Schw) Explosives. See under Unterwasser-sprengstoffe.

Schieswolle 18 oder TSMV1-101. An explosive described as Hexamita (Hexanite) in the general section. It consisted of TNT 60, hexanitrodiphenylamine 24 and Al powder 16% and was used in sea mines, torpedoes, depth bombs and underwater demolition charges.

References:

- 1) A.Stettbacher, Protar 9, 33-45 (1943)
- 2) H.Muraour, Protar 9, 62-63 (1943)
- 3) Allied and Enemy Explosives, Aberdeen Proving Ground, Md, (1946)
- 4) A.Stettbacher, Spreng- und Schiesstoffe, Rascher, Zürich (1948), p 78.

Schlagweite. (Striking Distance). Same as Detonations-übertragung.

Schlagwettersichere Sprengstoffe, oder Wettersprengstoffe. Explosives safe for use in coal mines with fire damp. (See **Wettersprengstoffe**, p226 and also **Sicherheitsprengstoffe**)

References:

- 1) A.Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933), p 246
- 2) C.Beyling, K.Drekkopf, Sprengstoffe und Zündmittel, Berlin (1936), p 105
- 3) A.Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), p 91.

Schlagwetterversuchstrecke, oder Versuchstrecke (Firedamp Testing Gallery). Description of galleries for testing explosives in regard to their suitability for use in gaseous coal mines is given in the general section. The first German gallery was constructed in 1885 by Lohmann in Neunkirchen (Westfalen). Other German galleries were: Derne, near Dortmund, Gelsenkirchen-Schalke, Grube-Maria and several galleries belonging to the plants manufacturing mining explosives, such as Schlebusch, Haltern, Castrop etc. One of the newest galleries was in the Sächsischen Braunkohlenrevier zu Freiberg (Sachsen).

References:

- 1) A.Marshall, Explosives, London, v 2 (1917), p 584
- 2) A.Schrimpl, S S 24, 288 (1929)
- 3) A.Stettbacher, Schiess und Sprengstoffe, Leipzig (1933), pp 248-250.

Schmidding Gerät 33 (SG 33). A rocket booster unit invented by Schmidding to increase the thrust of Hs 117 missile, thus assisting its take-off [TM 9-1985-2(1953), p 201].

Schnecken Presse (Worm Press). In order to reduce the time of the rolling operation and to reduce the power consumption in the manufacture of solventless propellants, the Düneberg Fabrik of Dynamit A-G rolled the NC-NG (or NC-DEGDN) paste (Rohpulvermasse). The water content of this paste had previously been reduced to 8%, instead of 25-30% as was used in the other propellant plants. In order to achieve such good dewatering the usual centrifuging of the paste was followed by passing it through the Schnecken press. The press consisted of a slotted barrel and an endless screw. When the paste was pressed some water escaped through the slots while the partially dehydrated paste was squeezed out ready for rolling into sheets (carpets).

Reference: A.A.Swanson & D.D.Sager, CIOS Rept 29-24 (1946), p 7.

Schnellmine. See Panzerschnellmine under Landminen.

Schnellzeitzündler (Quick Time Igniter), called also Instantaneous Fuse and Quickmatch. Some German igniters, such as **Donnarzündler** and **Eschbachzündler** are described in Beyling-Drekkopf, Sprengstoffe und Zündmittel, Berlin (1936), p 229.

Schnorkel oder Schnörkel (Misspelled North-German word Snorkel oder Snort, meaning Nose). The Dutch had fitted their submarines with an air intake back in 1940, and the Germans modified the device and called it Schnörkel. It consisted of a tube (about a dozen meters long), one end of which was connected to submarine Diesels, while the other end protruded above the surface of the water. The tube was divided lengthwise into two compartments - one for suction of air from the outside and the other for removing the gases of combustion of the Diesels. This device permitted the submarine to operate its Diesels while remaining in the submerged condition. In case of danger, the Schnörkel folded horizontally and the submarine submerged to a depth of as much as 200 m (or even 400 m as was reported for the Submarine 21). As the material of the Schnörkel was usually non-metallic, it could not be detected by radar.

Due to the fact that the Schnorkel used during WW II did not supply an amount of air sufficient to replace all the foul air in submarine, it was necessary to resurface the submarine after several hundred kilometers of underwater travel or equivalent duration. The maximum achieved in an uninterrupted submerged condition was 500 km.

References:

- 1) A. Ducrocq, Les Armes Secrètes Allemandes, Paris (1947), pp 20-24
- 2) H. Schaeffer, U-Boat 997, Norton, N Y (1950), pp 182-3.

Schopper-Riegler Test. According to Sheldon (Ref 1) this test was used in Germany to determine the suitability of crepe paper intended for the manufacture of nitrocellulose. The Schopper-Riegler Tester was originally introduced into the paper industry to determine the freeness (slowness) of the wood pulp. The tester operates on the same principles as the Canadian Standard Freeness Tester (Ref 2).

References:

- 1) L. Sheldon, PB Rept 12,662 (1945)
- 2) J. N. Stephenson, Edit, Preparation and Treatment of Wood Pulp, McGraw-Hill, N Y vol 1 (1950), pp 944, 951 & 955 (See also Freeness and Its Testing, in the general section).

Schrapnellgranate. See Shrapnel Shell.

Schrapnellmine (S-Mine). See under Landminen.

Schuko Zünder (Pressure Type Igniter), also called Hebelzünder (Lever Type Igniter) is briefly described under Igniters and in TM 9-1985-2 (1953), p 296. It was used in the Glasmine 43 as an alternative to the Buck igniter.

Schuler Pulver (Schuler Powder). An explosive patented in 1893: K chlorate 60, pulverized anthracite 25 and sugar 15%. A similar explosive was used by the British under the name Schindler Powder.

Reference: Daniel, Dictionnaire, Paris (1902), p 305.

Schultze Pulver (Schultze Propellant). A smokeless propellant prep'd about 1865 by Major Schultze of the Prussian Artillery, by nitrating purified (de-resinated) wood (in the form of small square-cut pieces), followed by washing and boiling the resulting Nitrolognose with water and then drying. After this the grains were impregnated with a concentrated solution of saltpeter, with or without its nitrate, and dried again.

Although this propellant was appreciably slower burning than earlier smokeless propellants consisting of straight compressed nitrocotton (such as Von Lenck Propellant), it was still too quick for use in rifles, although quite suitable for shotguns.

Schultze propellant was manufactured not only in Germany but also in England (1868) and Austria (1870), but it did not achieve any success until it was modified in England by Griffiths and in Austria by Volkmann. The Austrian propellant was made by partly gelatinizing the Schultze propellant with a mixture of ether-alcohol and it became known as Collodin. The British modifications beginning in 1883 contained nitrated wood pulp instead of previously used nitrated wood. The composition of the British sporting Schultze propellant is given in Marshall (Ref 1, p 327).

The composition of German Schultze propellant given by Brunswick (Ref 2) was as follows: collodion cotton 40, guncotton 40, Ba nitrate 10, vaseline 8, moisture 1.5 and gelatinizer 0.5%.

References:

- 1) A. Marshall, Explosives, London v 1 (1917), pp 47 & 327
- 2) H. Brunswick, Das rauchlose Pulver, Berlin (1926), p 134.

Schümne One of the Land Mines. See under Landminen . Reference: TM 9-1985-2 (1953), p 278.

Schuss Gg P-40. Hollow charge rifle grenade described in TM 9-1985-2 (1953), pp 337-8. (See also under Rifle Grenades).

Schützenmine. Same as Schümne.

Schwarzpulver (Black Powder). Composition, preparation and properties of black powders are given in the general section.

Table 58 lists some German military and commercial black powders

Table 58
Black Powder

| Designation | Composition, % | | |
|--|------------------------------|------------------------------|------------------------------|
| | K ni- trate | Char- coal | Sulfur |
| Geschützpulver, PPC/75 (Cannon propellant 1875) | 74.0 | 16.0 | 10.0 |
| Militär-Gewehrpulver 71 (Military rifle propellant 1871) | 76.0 | 15.0 | 9.0 |
| Militärpulver (current) | 75.0 | 15.0 | 10.0 |
| Marine Geschütz Pulver (Navy Gunpowder) | 75.0 | 16.0* | 9.0 |
| Jagdpulver (Hunting, or sporting powder) | 78.5 | 11.5 | 10.0 |
| Sprengpulver (Blasting powder) manuf'd by the Pulverfabrik Spandau | 65.0 70.0 74.0 66.0 | 20.0 16.0 16.0 21.5 | 15.0 14.0 10.0 12.5 |
| Blasting powder | 65.0 (Na ni- trate) | 18.0 | 17.0 |
| Blasting powder B | 76.0 | 14.0 | 10.0 |

* Beech charcoal

References:

- 1) Gody, Traité des Matières Explosives, Namur (1907), p 71
- 2) R. Escales, Schwarzpulver, Leipzig (1914), pp 160, 169 & 353
- 3) A. Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933), pp 97-112
- 4) E. Sancho, Química de los Explosivos, Madrid (1942), pp 277-9
- 5) A. Stettbacher, Spreng- und Schiessstoffe, Zürich (1948), pp 58-9.

Schwefelsäure. See Sulfuric Acid.

Schwergefrierbare Dynamite (Difficultly Freezing Dynamites), called also Ungefrierbare Dynamite (Non-freezing Dynamites). See Low-freezing Dynamites in the general section.

Screaming Mimi or Screaming Meemie. According to H. H. Bullock of Picatinny Arsenal, Screaming Mimi was the nickname for any ammunition giving off a loud shrill sound in flight. One such item was the WW I 75 mm shell fired from the light, muzzle-loaded rifled mortar, called Minenwerfer. The shell had in the base several vented holes that allowed air to pass through thus giving a shrill noise. Another item nicknamed Screaming Mimi was the 150 mm Smoke Rocket Projector, 15 cm Nebelwerfer 41, or its ammunition; used successfully during WW II. The

weapon, also nicknamed **Wolf-Wolf**, is briefly described in this section under **Rocket Launcher**.

(See also the **general section**).

References:

- 1) W.B.Larson, *Infantry Journal*, September 1914, p 23
- 2) Anon, *Intelligence Bulletin*, March 1915, pp 2-4.

See Dog. See **Seehund**.

Sea Marker Bomb. See under **Marker**.

Securite. See **Sekurit**.

Securophore. See **Sekurophor**.

Seehund (Sea Dog) (Chien de mer, in French). The "pocket" submarine (16 tons) with a radius of action of 500 km invented near the end of WW II. Its crew consisted of 1 or 2 men and it carried 2 torpedoes. It was provided with a small Diesel generator, storage batteries, electric motor, oxygen tanks, and an arrangement which allowed it to submerge to as much as 50 or 60 m. This was an effective weapon which could do considerable damage if used in large numbers.

In addition to the Seehund there were two other models of pocket submarines both propelled by electricity. The one, slightly larger than the Seehund, was called **Moleh** (salamander), while the other, considerably smaller, was called **Biber** (beaver).

(See also **U-Boat, One-Man**).

Reference:

- A.Ducrocq, *Les Armes Secretes Allemandes*, Paris (1917), pp 31-33.

Seidler Sprengstoff. A permissible explosive patented in 1892 by Seidler of Berlin. It was prepd by blending 77 parts of K nitrate with 23 p of the Na salt of napt'lene-beta-monosulfonate, $C_{10}H_7SO_2ONa$. Daniel, *Dictionnaire* (1902), p 712.

Sekundärladung (Secondary Charge), called also in English **Base Charge**, **Main Charge**, or **Lower Charge**. A charge in detonators or blasting caps which is placed underneath a primary or an intermediate charge. A secondary charge usually consists of a high explosive more sensitive to initiation than cast P A or TNT. The usual base charges were: compressed tetryl, PETN, or RDX, while charges occasionally used included compressed P A and hexanitromannitol.

Sekurit (Securite). A type of mining explosive based on mono or dinitrobenzenes mixed with an oxidizer such as Am or K nitrate, patented about 1886 by F.Schönweg.

Table 59 lists some securites

Table 59

| Components | Securites | | | | |
|-----------------|-----------|------|------|------|------|
| | 1 | 2 | 3 | 4 | 5 |
| Am nitrate | - | - | 37.0 | - | - |
| K nitrate | 74.5 | 77.7 | 34.0 | 81.8 | 18.9 |
| MNB w/lt. m-DNB | - | - | 29.0 | - | 70.5 |
| m-DNB | 25.5 | 19.4 | - | 15.2 | - |
| Am oxalate | - | 2.9 | - | 3.0 | - |
| Nitrocellulose | - | - | - | - | 10.6 |

References:

- 1) J.Daniel, *Dictionnaire des Matieres Explosives*, Paris (1902), pp 710-12
- 2) L.Gody, *Traité des Matières Explosives*, Namur (1902), pp 597 & 705
- 3) E.Glover, *High Explosives*, London (1918), p 141
- 4) F.M.Turner, Edit, *Condensed Chemical Dictionary*, Reinhold, N Y (1942), p 291.

Sekurophor (Securophore). A type of mining explosive manufd in Germany prior to w. I.

Table 60 gives some examples

Table 60

| Components | Securophores | | |
|-----------------------------|--------------|------|------|
| | 1 | 2 | 3 |
| Am nitrate | 27.0 | 24.6 | - |
| Ba nitrate | - | - | 1.0 |
| K nitrate | 4.0 | 3.6 | 34.0 |
| NG | 40.0 | 36.4 | 25.0 |
| Collod cotton | 1.0 | 0.9 | - |
| Sebacic acid or its salts | 12.5 | 11.4 | - |
| Na chloride | - | 9.0 | - |
| Rye flour | 10.0 | 9.1 | 38.5 |
| Wood meal | 2.0 | 1.8 | 1.0 |
| Liquid hydrocarbon | 3.5 | 3.2 | - |
| Na carbonate or bicarbonate | - | - | 0.5 |

References:

- 1) L.Gody, *Traité des Matières Explosives*, Namur (1902), pp 713-714
- 2) A.Marshall, *Explosives*, London, v 1 (1917), p 376.

Selbstzündung Probe (Spontaneous Ignition Test) for pyrotechnic compositions and their ingredients is described in *Kast-Metz, Chemische Untersuchung* (1944), p 535.

Self Carrying Demolition Charge is described under **Krümml Factory, Dynamit A-G**.


Self-Destroying Bullet. See **Self-Destroying Tracer Bullet**.

Self-Destroying Fuze, ZZ 1505, developed by the Deutsche Waffen- und Munitionsfabriken A-G, Lübeck, was used in the 20 mm Mauser ammunition in air to ground firing. Like fuze AZ 1502 it was of the sensitive type required to function on a 2 mm paper screen at 100 meters. When the projectile was fired, the centrifugal force caused the steel balls (B) to fly out into the enlarged portion of the retainer ring thus locking the percussion plunger and its compressed spring in place. The same force caused the brass spiral ribbon to unwind and increase in diameter until the shoulder on the striker could pass through its center. By this time the projectile was a few meters away from the muzzle of the gun and the projectile was armed. On hitting the target the steel balls went back into their housings and the firing pin, activated by the compressed spring, pierced the primer cap.


If no impact took place within a range of about 2000 meters, the speed of rotation dropped to such an extent that the thrust of the balls against the angle surface was insufficient to support the firing pin spring. The primer was then fired and the projectile destroyed in the air.

References:

- 1) H.Peploe, *CIOS Rept 33-20* (1945), pp 69-70
- 2) Anon, *TM 9-1985-3* (1953), pp 548-9.



Self-Destroying Tracer Bullet (Spitzgeschoss mit Stahlkern, Leuchtspur mit Zerlegung) caliber 7.92 mm, developed during WW II by the Deutsche Waffen- und Munitionsfabriken A-G, at Lübeck, was intended to be used for air to air practice firing. It consisted of a steel casing containing a lead sleeve which enclosed a mild steel tip, a steel capsule with HE explosive filling and pistol powder, and a steel tube with tracer and primer compositions. The HE filling consisted of PETN 40, Pb azide 45 and Tetracene




15%, whereas the pistol powder contained nitrocellulose with an ignition temperature of 160°. The bullet was self-destroyed (at 500-600 m range), because the heat produced by the burning of the last portion of tracer composition ignited a small charge of pistol powder, which in turn set off the HE charge. The primer composition was ignited by the propellant in the cartridge.
Reference: H. Peplow et al, CIOS Rept 33-20 (1945), pp 28-9.


Self-Destroying Tracer Shells, caliber 20 mm, developed by the Deutsche Waffen- und Munitionsfabriken A-G at Lübeck, included the following:

a) HE Shell for Aircraft Guns. It was of conventional design and contained: a percussion fuze, a HE filling (PETN pellet), an incendiary pellet (Mg/Al alloy 50, Ba nitrate 49 and phenol formaldehyde resin 1%), a loose pistol powder (nitrocellulose), a pressed pistol powder, a heat transmitter, a tracer composition (two

increments, each pressed at 3500-4000 kg/cm²) and a priming composition (pressed at 3200-3500 kg/cm²). If the shell was not exploded by the percussion fuze, it was self-destroyed after about 0.3 seconds of flight. At this moment the flame from the last portion of the tracer ignited the pistol powder which in turn ignited the incendiary pellet. The intense heat produced by the burning pellet caused the HE charge to deflagrate. The diameter of the tracer was 9 mm.



b) APHE Shell was of conventional design and contained: a HE filling (PETN pellet), two detonators, a pistol powder pellet, a heat transmitter, a heating composition (Ba nitrate 41.0, ferrosilicon 36.0, Ba peroxide 22.5 and phenol formaldehyde resin 0.5%), a tracer com-



position (two increments) and a primer composition with its surface sprayed with NC lacquer. The shell was designed to give a trace of 4.7-6.7 sec duration, to penetrate a 20 mm armor plate and to explode 40-50 cm behind it. If the shell was not exploded in the above manner it was self-destroyed by deflagration of the PETN pellet caused by the intense heat produced on deflagration of the pistol powder which, in turn, was ignited by the heating composition. This composition was incorporated in the shell because the heat produced by the tracer alone was not sufficient to ignite the pistol powder owing to the small diameter (6 mm) of the tracer compared with the diameter of the HE shell (70 mm).

Reference: H. Peplow et al, CLOS Rept 33-20 (1945), pp 51-61.

Self-Igniting Cushion. See Brandkissen.

Self-Propelled (SP) Gun Mount. Selbstfahrlafette (Sf or Sfl). See under Panzer.

Sevastopol Gun. A mortar gun, caliber 800 mm, used effectively by the Germans during WW II at the siege of Sevastopol, Russia. The gun fired an 8 ton projectile with muzzle velocity of 2200-2400 ft/sec and maximum range of 29 miles. Weight of explosive was 2000 lb, wt of propellant 2500 lb, wt of gun 1375 tons and length of barrel 105 ft. It is probable that the propellant charge was contained in a cylindrical casing made of a propellant composition, as described under Made-Up Charges.

Note: This gun was nicknamed Dora or Gustav Geschütz (See also under Weapons).

References:

- 1) PB Rept 925 (1945), p 18
 - 2) Aberdeen Proving Ground, Museum; private communication.
- Note: The projectile can be seen at the Museum.

"S" Geschoss. See Spitzgeschoss.

Shaped Charge or Hollow Charge. See Hohlladung in this section and Shaped Charge in the general section.

Sheathed Charge. See Mantelpatrone.

Shell. See Granate.

Shell Mold Process or "C" Process of Precision Casting of Metals (Called also Croning Process or Cronite Molding) developed in Germany during WW II by J. Croning, made possible the production of foundry molds and cores for cast metals in more intricate shapes and in larger sizes than were formerly considered practicable. In this process the thin shell molds were formed by the adherence of a mixture containing dry sand and plastics to heated metal patterns. Each shell mold was then hardened by further polymerization of the plastic bond by heating for a short time in an oven with a pattern still attached. After removal from the oven, the molds were stripped from the patterns, clamped together in pairs in a box, backed with loose metal shot or other porous material, and filled with molten metal for casting.

The process is applicable to the manufacture of shells, bombs, grenades and rockets.


References:

- 1) J. Croning, Ger Pat Application No 48679 (1949), described in PB Repts 83891 and 81284
- 2) B.N. Ames et al, The Foundry, August 1950, pp 92-96 and 206-17
- 3) H.L. Day, The Iron Age, 169, 28 (Jan 1952)
- 4) B.N. Ames et al, The Foundry, June 1952, pp 112-17 and 287-95
- 5) K.W. Tindula, PB Rept 106640r (1952) (47 references).

Shotgun or Sporting Propellant. See Jagdpulver.


Shrapnel Mine (Schrappnelmine, abbreviated as S-Mine, sometimes called Schürzenmine). Two types, S-35 and S-44, are described in TM 9-1985-2 (1953), pp 279-81. The S-35 mine was called the Fruit Tin by the British. Owing to the fact that these mines rose into the air (to the height of 3 to 5 feet) before explosion, they were nicknamed Bounding Mines (See under Landminen).

Shrapnel Projectile (Schrappnelgranate). Only one such projectile, namely the 8.8 cm Granate Brand Schrappnel Flak (88 mm Incendiary Shrapnel Projectile for AA Guns) is described in TM 9-1985-3 (1953), p 448-49. The projectile consisted of a thin steel shell of conventional design containing: 72 incendiary pellets, a point detonating



time fuze (Z&ZS/30 kurz), an expelling charge (about 2 oz of smokeless propellant) and a bursting charge (about 4 oz of TNT or Amatol and wax pressed pellets). The pellets were filled with an incendiary composition consisting of Ba nitrate 48.0, Mg alloy 24.6, Al alloy 24.6 and acid insoluble substances 2.8%.

Shrapnel Projectile, Russian. In addition to the previously mentioned shrapnel projectile, the Germans during WW II, used the 76.2 mm Shrapnel Projectile, 42M, captured from the Russians. The shell was filled with about 48 triangular pieces of steel, 2.25" long, which were ejected from the nose by a steel forcing plate behind which was a charge of black powder. The threads and the two retaining screws



of the collar were sheared by this action. The shell was fired from Russian field guns 7.62 cm FK 296(r) and 7.62 cm FK 36(r).
Reference: Anon, German Artillery Projectiles and Fuzes, Ordnance Bomb Disposal Center, Aberdeen Proving Ground, Maryland (about 1945), pp 120-1.

SH-Salz. The term used for RDX (hexogen) prepared by the direct nitration of hexamethylenetetramine as described briefly in this section under Hexogen.


Sicherheitsdynamit (Safety Dynamite). According to Stettbacher, Spreng- und Schiesstoffe (1948), p 86, the dynamites which are safe to handle and transport are called *Handhabungssichere* and those of them which are safe to use in coal mines are known as *Sicherheitsdynamite*. The latter dynamites contain 20-25% of NG (or a low-freezing mixture of NG and nitroglycol-4/1, mixed with dinitrochlorohydrin which serves as a phlegmatizer) and a "dope", such as Am nitrate, wood meal, etc. If the NG is phlegmatized by means of collodion cotton, the resulting dynamite belongs to the *Gelatinedynamite* class, such as the *Ammongelatine*. Note: In countries other than Germany, for example France and Switzerland, aromatic nitrocompounds, such as DNT, TNT, etc., were used as phlegmatizers in lieu of dinitrochlorohydrin. Such dynamites were known as *Nitrogelatinedynamites*.

(See also under Swiss Explosives).

Sicherheits Sprengstoffe (Safety Explosives). According to Stettbacher, Spreng- und Schiesstoffe (1948), pp 86-7, explosives under this name were allowed to be transported by rail. They contained 70-90% Am nitrate and not more than 4% NG, the remainder being wood meal, aromatic nitrocompounds, etc. These explosives, known also as *Ammonsalpetersprengstoffe* were pulverulent, very insensitive to impact, fairly stable and difficult to ignite. An example of such explosives is *Donarit*. Most of the *Sicherheits Sprengstoffe* are also *Schlagwettersichere* (safe to use in coal mines contg firedamp). (See *Wettersprengstoffe*, pages 226 and 260-7, and also *Schlagwettersichere Sprengstoffe*).

Signal Device (Signalmittel). Under this term might be included: Hand Smoke Signal (*Handrauchzeichen*), Signal Cartridge (*Signalpatrone*), Signal Flare (*Signalbombe*), Signal Hand Grenade (*Signalhandgranate*), Signal Pistol (*Leuchtpistole, Kampfpistole*), Signal Projector (*Signalwerfer*), Signal Rocket (*Signalrakete*) and Signal Torch (*Signalfackel*). Many of the signal items are either described or mentioned in TM 9-1985-2 (1953), as for instance the following:

- a) Smoke Signal Flare (p 80), is also briefly described under Flare
- b) Smoke Signal Flare ARDR (p 80) is also briefly described under Flare
- c) Distress Signal Torch (p 81) consisted of a sheet aluminum cylinder containing three pressed blocks of a flare composition and a pull igniter with a flash pellet and an ignition mixture
- d) Red Smoke Signal Hand Grenade (*Handrauchzeichen-Rot*) (p 329) consisted of a cardboard cylinder containing 34g of the red smoke composition, ortho-methoxy phenylazo-β-naphthol 5%, K chlorate 20, lactose 10 and light oily material (unidentified) 15%, a black powder disc, a quickmatch, a match head and a pull tape. By striking the striker ring on the match head, the quickmatch was ignited and after it burned the



entire length the black powder disc was ignited. The flame was then communicated to the smoke mixture which started to burn emitting the smoke at both ends of the cylinder. The signal could be placed or thrown. There were also similar orange, yellow and violet signals.

e) Hollow Charge Signal Pistol Grenade (p 341) is described under Pistol Grenades.

f) Multistar Signal Cartridge (p 345) is briefly described under Pistol Grenade.



Some of the smoke compositions used in Hand Signals (*Handrauchzeichen*) are listed under Pyrotechnics.


A smoke signal generator, designated as **RSSG Patrone 15 cm RZ** is described in CIOS 32-13 (1945), p 14. The device consisted of a pasteboard cylinder enclosing 1.4 g of smoke composition containing Hexa (hexachloroethane) 52.5, Zn dust 38.0, ZnO 4.0 and Mg powder 5.5%. The time of emission was 45 to 75 seconds. This device appears similar to the 150 mm Rocket Signal Simulating Device (15 cm *Raketen Scheinschuss Gerät*) described in CIOS Rept 32-50 (1955), pp 3-5 and in this section under Antipanzender Pyrotechnische Devices.

F. Gallavert in Pic Army Arsenal Technical Report 1505 (1945), described the Aircraft Colored Smoke Signal (*Abwurfrauchzeichen*). This consisted of a cardboard cylinder covered with an aluminum cap and containing four increments of a colored smoke mixture, four perforated aluminum tubes serving as smoke stacks and a firing device assembly. The smoke composition (which on heating gave either blue, red or violet colored smoke) consisted of approximately 50% organic dye, 21% lactose, 21% K chlorate, 3% binder (gum) and 5% insolubles in water (SiO₂ dirt, etc). The device was fired by pulling the cord attached to the firing pin spring thus allowing the pin to strike the priming cap. This fired 0.015 g of a mixture of K chlorate

and mercury fulminate which ignited the delay element, which consisted of an upper charge (0.060 g of mixture: K nitrate 75, charcoal 15 and sulfur 10%) separated by a perforated lead disc from an intermediate charge (0.030 g of ground colloided nitrocellulose) and a lower charge (0.030 g of K nitrate 73, charcoal 17 and sulfur 10%). After burning for about 1 second the flash was transmitted to the quickmatch composition (black powder) located in the center of the top igniter disc. This center charge transmitted the fire to the "cross" of quickmatch composition on the underside of the top igniter disc and in turn, to the quickmatch fuses (K nitrate 78, charcoal 13 and sulfur 9%), both of which caused ignition of the top layer of the smoke charge. The heat and pressure of the generated gases burned through the paper coverings on the four tubes and dislodged the paper discs (over four 1/2" diameter vents in the top cover of the body) thus allowing the smoke to escape outside. Upon completion of burning of the first increment of the smoke charge, the fire was transmitted through another igniter disc (by means of the quickmatch composition in its center) to the second increment and so on. It should be noted that the 2nd, 3rd and 4th discs did not have the "cross" of the quickmatch composition present.

The same investigator, in Pic Arsn Tech Rept 1510 (1945), described the Hand Smoke Signals emitting colors: green, red, violet and blue (*Handrauchzeichen Grün, - Rot, - Violett und - Blau*). The signal body was a sheet steel cylinder averaging 3.51" long by 2" in diameter, with fixed bottom, and removable cover which was held in place by a strip of adhesive tape. Each cylinder contained a smoke composition (loose grains for the red signal and four compressed cylindrical blocks with central hole for the green, blue and violet signals). In the center of each smoke mixture was located (except for the green signal) a sheet metal tube provided with small perforations. (The green signal had no tube but a cylindrical cavity extending through all four blocks of the smoke charge). The lower end of the tube was attached to the bottom of the cylinder, whereas the upper end was inserted through the bottom of a shallow cup-shaped igniter holder which supported the friction igniter assembly to which a pull chain and ring were attached. The lower part of the igniter





assembly, which included the delay element, was extended into the central perforated tube. Below the igniter, inside the central tube, were located loose pieces of quickmatch (black powder) used to facilitate the ignition of a smoke charge.

Note: In the green signal the pieces of quickmatch were located in the cavity.

Following are the compositions of smoke mixtures:

| | Green | Blue | Red | Violet |
|--|-------|------|------|--------|
| Organic dye | 45.0 | 44.7 | 53.7 | 49.7 |
| Lactose ($C_{12}H_{22}O_{11} \cdot H_2O$) | 24.7 | 23.5 | 23.7 | 17.7 |
| K chlorate | 28.5 | 23.0 | 17.8 | 26.4 |
| Insolubles in H_2O (SiO_2 , Fe_2O_3 , Al_2O_3 , etc) | - | 7.3 | 1.8 | 3.6 |
| Binder (by difference) | 1.8 | 1.5 | 3.0 | 3.6 |
| Weight of charge (in grams) | 23.9 | 31.5 | 27.0 | 28.6 |

The signal was fired by removing the cover, pulling quickly on the igniter chain (by means of the pull ring) and then throwing the signal (or placing it upright on the ground). The friction wire being pulled through: 0.04 g of the composition: antimony sulfide 50, potassium chlorate 30 and mercury fulminate 20%, caused it to flash and to ignite, in turn, the delay element (0.05 g of K nitrate 75, charcoal 16 and sulfur 9%). After burning for about 1 1/2 seconds, the flame from the delay element ignited two cords of quickmatch (black powder) which, in turn, ignited the black powder composition (1.3 to 1.8 g) on the bottom igniter disc and finally the smoke mixture. The smoke from the burning charge was forced through the small holes in the central tube (or in the central cavity in the case of the green signal), and thence around the friction igniter, and through the hole in the retainer into the space between the retainer and igniter holder. The heat and pressure of gases generated on burning ruptured the film covering the six vent holes in the igniter holder thus allowing the smoke to escape. It was assumed that the smoke charge burned from the center outward and from the bottom upward. The duration of emission of smoke was 12 to 20 seconds.

Signal Smoke Device. See Signal Device.

Silesia-Sprengstoffe (Silesia explosives) were chlorate explosives developed before WW I by the Oberschlesische A-G für Fabrikation von Lignose (Schliesswollfabrik für Armee und Marine). According to Escales (Ref 1, p 185) one type of Silesia was a mixture of K chlorate 80 (max) with 20% resin of which 4% could be in the nitrated state. Another composition contained K chlorate 75 (max) resin 8 (minim) and Na chloride 10% (minim). The resin had a m p of about 70° and the Na chloride was mixed with 1 to 4% of its weight of paraffin oil.

Following were the compositions of some of these explosives:

a) Silesia IV: K chlorate 70, resin 8 and Na chloride 22%; it was suitable for blasting rocks and ores, but not for use in gaseous coal mines (Ref 1)

b) Silesia No 4: K chlorate 80 and resin 20%; it was suitable for blasting rocks and ores, but could not be used in gaseous or dusty coal mines (Ref 2 & 3).

References:

- 1) R. Escales, Chloratsprengstoffe, Veit, Leipzig (1910), pp 143 & 185
- 2) A. Marshall, Explosives, Churchill, London, v 1 (1917), pp 382-3
- 3) E. Barnett, Explosives, Van Nostrand, N Y (1919), p 111.

Silver Azide (Silberazid) (Ag A). See general section under Azides.

Silver Fulminate (Silberfulminat). See general section under Fulminates. It was used in Germany as a primary charge in the Ansonitkapseln (q v).

Silvit oder Pikrit (Silvite or Picrite). A type of blasting explosive prepd by mixing pulverized picric acid (left over from WW I) with 5 to 10% of aqueous molasses or cellulose pitch, a tarry product obtained by evaporating sulfite liquor from the pulp industry. The composition could contain up to 20% of aromatic nitrocompounds such as TNT, DNB, etc.

References:

- 1) P. Naoum, Schiess- und Sprengstoffe (1927) p 66
- 2) J. Pepin Lehalleur, Poudres, etc (1935), pp 457-8.

Sinoxysatz oder Synoxyd. Primary explosive mixture developed in Germany about 1930 to replace previously used mercuric fulminate compositions. It has been claimed that the products of decomposition of Sinoxyd are non-corrosive and do not erode firearms. Ficherouille and Kovache (Ref 3) give the composition of a mixture used by the Germans during WW II as follows: lead styphnate 25 to 55, tetracene 1.2 to 5, Ba nitrate 25 to 45, PbO_2 5 to 10, Sb_2S_3 0 to 10, Ca silicide 3 to 15 and powdered glass 0 to 5%.

References:

- 1) E. von Herz, S S 28, 39 (1933), Die erosionsfreie Zündung
- 2) A. Stettbacher, Spreng- und Zündstoffe, Zürich (1948), pp 98 & 106-7
- 3) H. Ficherouille, A. Kovache, Mém poud 31, 26-27 (1949).

Sintered Iron and Steel Items, such as bullets, pyrotechnic devices, etc, are mentioned under Pulvermetallurgie.

Sintered Iron Projectiles. See under Tiefbender Verfahren.

Skip Bomb or Kurt Apparatus, designated as SB 400 Kugel K is described on p 14 of TM 9-1985-2 (1953). (See also under Bombe).






Small Arms (Handfeuerwaffen) . See under Weapons.

Small Arms Ammunition. According to A.J.Dere, Ordnance Sergeant, December 1943, pp 357, the German small arms ammunition was similar to American. The complete round consisted of a cartridge case, percussion cap (primer), propelling charge, and bullet. The cartridge was drawn either from sheet brass (copper 72 and zinc 28%) or from sheet steel, copper plated on both sides. The case was bottle shaped, grooved at the base and coned slightly to facilitate extraction. A primer pocket was formed in the base of the case and was connected to the interior by flash channels. In the center of the pocket an anvil was formed on which the primer composition was fired by the firing pin. The primers were of the Berdan type, either the No 88 or No 30. The No 88 primer consisted of a brass cup containing the primer composition, and a covering cap of double-size zinc-plated lead foil. The primer composition was put into the cup dry and was protected from dampness by the cap which was lacquered on the inside. The inside of the cup was also lacquered to the level of primer composition. The No 30 primer was essentially the same as the No 88 except that its primer composition was different and practically non-erosive. A charge of a typical small arms cartridge consisted of a single-base (nitro-cellulose) propellant in blackish, square, graphite-treated flakes about .25 mm thick and 1.2 to 1.5 mm long, with smooth-cut surfaces. A typical bullet had a boat-tail base and consisted of a lead core and jacket consisting of either cupro-nickel, gilding metal or copper-plated steel. There were also bullets with steel cores or made entirely of steel (See under Steel and Iron Ammunition Items). The bullet was crimped to the cartridge case in the conventional manner by means of a cannelure.

The following calibers were commonly used during WW II.

A. 7.92 mm Ammunition which can be subdivided into the following types:

- a) Patr sS (Patronen schweres Spitzgeschoss), Heavy Pointed Ball Ammunition, had a bullet with a lead core and a copper-alloy jacket. The annulus on the base of the cartridge was painted green. If labeled as simply Patr sS, the ammunition could be used either in rifles (such as Mauser or Gewehr 41) or in machine guns (such as MG 15, MG 17, MG 81, MG 34 and MG 42). In the same weapons could be used ammunition with label "Patr sS iL", in which the letters "iL" indicated that the rounds were clip packed. The label "Patr sS für Gew" indicated that the rounds were designed for use in rifles and the label "Patr sS für MG" indicated that the rounds were designed for use in machine guns.
- b) Patr SmK (Patronen Spitzgeschoss mit Stahlkern), Armor-Piercing Ammunition had a bullet somewhat longer than in (a). The core was of steel and the jacket of steel with gilding metal coating. The annulus was painted red.



c) Patr SmKH (Patronen Spitzgeschoss mit Stahlkern Gehärtet), Armor-Piercing (Super) Ammunition, had a bullet with a tungsten carbide core and a steel jacket coated with gilding metal. The bullet was painted black and the annulus was red.

d) Patr SmE (Patronen Spitzgeschoss mit Eisenkern), Semi-Armor-Piercing Ammunition, was similar to the above, except that the core was of soft steel or iron. (See also under Steel and Iron Ammunition Items.)

e) Patr SmK L'spur (Patronen Spitzgeschoss mit Stahlkern und Leuchtspur), Armor-Piercing-Tracer Ammunition, had a bullet with a steel core and lead point filler enclosed in a copper-plated steel jacket. The tracer was usually green changing to red. The point of bullet was painted black and the annulus red. This round was used principally against aircraft.

f) Patr PmK (Patronen Phosphor mit Stahlkern), Armor-Piercing-Incendiary Ammunition, had a bullet with a steel core and a phosphorus filling. It was used against aircraft and on striking the target a trace of white smoke was evolved. The annulus was painted either red or black and sometimes the case had a red band across the base.

g) Patr IS (Patronen leichtes Spitzgeschoss), Light Pointed Ball Ammunition, had a bullet with an aluminum filling. This round was used for antiaircraft practice.

h) B Patr (Beobachtungsgeschoss Patronen), Observation Ammunition had a bullet with a core of high explosive, a fuze in the central portion of the bullet, and a phosphorus filler in the base. It was an observation round, the purpose of which was to indicate by means of a puff of smoke the spot where the target was hit. The bullet was painted black except its tip.

Note: This bullet is described more fully under Observation Bullet. According to CIOS Report 33-20 (1945), p 18, it was also adopted as an incendiary bullet for use against aircraft.

i) Patr IS L'spur (Patronen leichtes Spitzgeschoss mit Leuchtspur), Light Ball-Tracer Ammunition, had a bullet with an aluminum filler and a tracer (white).

This ammunition was used in antiaircraft practice. The tip of the bullet was painted black.

j) **Potr 318R's** (Patronen 318 Reizstoff), Antitank Rifle Ammunition which contained a small charge of harassing agent. It had a very large cartridge case and an armor-piercing bullet. There were two types

of this ammunition, one used in the Polish Antitank Rifle and the other used in its German copy, the **PzB 39** (Panzerbuchse 39). The Polish round was much smaller than the German which was marked 7.92 mm/13 mm.

Note: According to CIOS Rept 33-20 (1945), pp 17-18, the Germans also developed two other tracer bullets, designated as **SmKL'spur (DI)** and **SmKL'spur (GI)**. There was also the **SmKL'spurnZ**, described in this German section under Self-Destroying Tracer Bullet.

B. 9 mm (.354") Ammunition could be subdivided into the following types:

a) **PistPatr 08** (Pistolen Patronen 08), Ball Ammunition, had a bullet with a lead core and a jacket either of cupro-nickel or gilding metal.

b) **PistPatr 08 mE** (Pistolen Patronen 08 mit Eisenkern), Semi-Armor-Piercing Ammunition which had a bullet with a mild steel core and lead point filler. The jacket was of steel coated with gilding metal.

Note: Each of these rounds could be used in the following weapons: Luger (Parabellum) Pistol, Schmeisser Carbine, Walther Automatic Pistol, Bergmann Submachine Gun and Steyr-Solothurn Submachine Gun.

C. 13 mm (.51") Ammunition could be subdivided into the following types:

a) High-Explosive-Tracer Ammunition had a bullet containing some PETN as a bursting charge, a point detonating fuze and a tracer composition. The bullet was painted yellow

b) High-Explosive-Incendiary-Tracer Ammunition had a bullet containing the same ingredients as above plus the incendiary composition. The bullet was painted yellow with a blue band

c) Tracer Ammunition had a bullet containing the tracer composition, giving either a white or green trace. The bullet was painted green with a white band

d) Armor-Piercing-Tracer Ammunition had the bullet painted black with a yellow band. The trace was pale green.

Note: The above ammunition was used in the Rheinmetall-Solothurn Fixed Aircraft Cannon MG 131.

D. 15 cm (.59") Ammunition could be subdivided into the following types:

a) High-Explosive-Tracer Ammunition had a bullet containing a PETN/Wax filler, a brass fuze (AZ 1551) and a tracer. The bullet was yellow with a black band in front of the driving band

b) High-Explosive-Incendiary-Tracer Ammunition had a bullet containing the same ingredients as above plus the incendiary pellet. The bullet was yellow with a blue band

c) High-Explosive-Tracer-Self-Destroying Ammunition had a bullet similar to (a) but provided with a self-destroying device. The bullet was painted yellow

d) Tracer Ammunition had the bullet painted olive green with a yellow band in front of the driving band

e) Armor-Piercing-Tracer Ammunition had the bullet painted black. Sometimes a yellow band was painted in front of the driving band.

Note: The above ammunition was used in Mauser Fixed Aircraft Cannon MG 151-15.

Although the ammunition of calibers 20, 25, 27, 28/20 and 30 mm was considered by the Germans as belonging in the small arms category, it is not included by us in this section because when this work was conceived, US practice classified these items as artillery ammunition. See T.C. Dhart, Elements of Ammunition, Wiley, N.Y. (1946), p 3, and only items of caliber 0.60" (15.24 mm) or smaller belonged to the small arms category.

It should be noted, however, that quite recently (fall of 1955) the US classification was changed and the calibers 20 mm and 30 mm are now included in the category of small arms.

Small Explosive Bodies. According to W. Dornberger,

V-2, Viking. N.Y. (1954), p 270, these were explosive devices suspended on wires 250 yd long attached to parachutes. They could be dropped from a plane ahead of enemy bomber formations, thus forming an effective floating barrage. The units which were not exploded eventually came to earth.


Smell Generator was a training device consisting of a sheet metal box with a press on lid. The box contained a heating composition (such as the one consisting of Ba peroxide, Ba nitrate, Fe powder and kieselsuhr) above which was pressed a chemical warfare agent (CWA) (such as chloracetophenone, Clark II, mustard gas or thiophosgene) absorbed on kieselsuhr.

Reference: E.W. Bateman, CIOS Rept 32-13 (1948).


S-Mine 35 } See TM 9-1985-2 (1953), pp 279-80 and also
S-Mine 42 } under Landminen.

Smoke and Chemical Rocket, 150 mm, Spin Stabilized (15 cm Wgr 41Nb), resembled in appearance an elongated gun projectile and was provided with a bulbous nose cap. The body consisted of a thin-walled steel cylinder housing a rocket motor (seven single-perforated double-base propellant grains, weighing 14 lb) threaded at the base to receive a cylinder containing a smoke (or chemical) composition, a bursting charge (3.05 lb of picric acid), an exploder and a base fuze. The smoke composition (not specified) was located between the outer wall of the shell and the outer wall of the burster container. The weight of smoke filling was about 8 lb and the total weight of the rocket 79 lb. The smoke composition was ignited after the shell hit the target.

Reference: TM 9-1985-2 (1953), pp 245-7.




Smoke and Message Tube, described in TM 9-1985-2 (1953), pp 120-1, consisted of an aluminum cylinder housing in its upper section some reddish-brown smoke composition (giving very bright yellow smoke) and in its lower section a message container. The top cover of the cylinder held the friction igniter (1 second delay) and through a hole in the cup-shaped aluminum piece near the cover protruded the ends of four strands of quickmatch. These strands were located on the side of the smoke container and met several pieces of fire quickmatch below the smoke container. The smoke container was 5" long, 1.75" diameter and weighed 10.3 oz.



Smoke Bomb, Cylindrical (Nebelcylindrische Bombe, abbreviated as NC). Smoke bombs were usually of conventional appearance. They were provided with a fuze (usually mechanical), which ignited a smoke producing composition. The following types are described in TM 9-1985-2 (1953), pp 58-60.

a) NC 50 (Smoke Cylindrical 50 kg) consisted of a seamless steel cylinder (body) with a cast steel nose welded to it. At the rear end were four tail fins. The




body was filled with a light grey smoke producing powder (smelling strongly of camphor). A mechanical impact fuze was located in the rear section of the bomb. Total weight of the bomb was 109 lb, body diameter 7", body length 10", and over-all length 26".

b) NC 50 WC (Smoke Cylindrical 50 kg Marker Bomb) See under Marker.

c) NC 50 D/Sec (Smoke Cylindrical 50 kg Floating Bomb) was similar in construction to the NC 50 WC. It was filled with a composition giving off a white smoke and was fitted with fuze (AZ 46). The over-all weight was about 22 kg.


d) NC 250 S (Smoke Cylindrical 250 kg) consisted of a steel body (made of two longitudinal halves crimped and welded together) and four tail fins. Inside the body was located the central tube which contained a burster charge TNT, a wooden block and an impact fuze. The smoke composition (mixture of chlorosulfonic acid 10 and sulfur trioxide 60%) filled the space between the walls of the body and the central tube. The detonation of the burster charge caused scattering of the surrounding acid mixture which, on contact with the air, emitted an intense white smoke.



Smoke Candle (Nebelkerze, Rauchkerze) is a cylindrical container with a compressed pellet emitting on burning a dense smoke. The following smoke candles are briefly described in CIOS Rept 32-13 (1945), pp 10-12 & 16-17:

a) Smoke Candle (Nbk 39E), also described by F.G. Haverack, Pic Arsn Tec Rept 149 (1944) consisted of a sheet metal cylinder, 110 mm long and 91 mm diameter. Its bottom cover was solid and provided with a handle, whereas the top cover which had 7 perforations held the igniter assembly. Inside the cylinder was a pressed pellet of the smoke composition weighing about 1.8 kg. This composition, according to CIOS Rept 32-13, consisted of Hexa (hexachloroethane) 59-60, Zn dust 39-40 and Ba nitrate 1-2 and, according to Pic Arsn Tech Rept 149, of Hexa 48, Zn powder 50 and binder 2%. Total weight of the device was 4 lb 2 1/2 oz.

For operating the Nbk 39E, the split ring of the igniter was pulled. The friction wire, being pulled through 0.035 g of composition containing antimony sulfide 51, K chlorate 33 and mercury iodinate 13, caused it to ignite the igniter. This consisted of an upper layer, 0.315 g of mixture: Pb₃O₄ (red lead) 75.4, silicon 18.0 and fuel & binder 6.7, and a lower layer, 1.82 g of Pb chlorate 40.0, K perchlorate 23.5, silicon



25.5 and binder 1.0%. After burning for about 3 seconds, the smoke charge was ignited. The smoke and gases generated on burning forced an exit through the zinc top liner beneath the two holes in the steel top. A large volume of dense grey smoke was emitted, according to CIOS 32-13, for about 3 minutes or for 4-7 min, according to PATR 1440.

b) Fast Smoke Candle (NbK S 39B) was similar in construction to the NbK 39B with the exception of the filling and the method of use. Its smoke mixture consisted of Hexa 47.5, Zn dust 47.5 and Ba nitrate 5.0%, compressed in the form of a cylinder weighing 1.7 kg and having a burning time of 100-200 sec. It was operated by firing from a projector attached to a vehicle.

c) Slow Smoke Candle (NbK L 42B) consisted of a round sheet metal container about 480 mm long and 160 mm diameter, with three compressed increments of smoke composition (Hexa 65, Zn dust coarse 25, Zn dust fine 10, and Ba nitrate added 0.75-1.5%) weighing 17.5 kg. It was ignited by means of a 300 g layer containing: Hexa 47.5, Zn dust 47.5 and Ba nitrate 5%. The emission time was 25-35 minutes.

d) Black Smoke Candle (NbK L 42Sz) was identical in structure with the previous candle but contained a different smoke composition: Hexa 28, K chlorate 38, crude anthracene 33 and kieselsuhr 1%. It was pressed in three increments, total weight 12-13 kg. Ignition was effected by means either of a safety fuse igniter or a low tension electric igniter and a gaine. The time of emission was 10-16 minutes.

e) Smoke Candle (NbK SSR 44) which served as a fixed aircraft smoke marker, consisted of a sheet metal cylinder, 140 mm long and 91 mm diameter provided with six 20 mm diameter emission holes and filled with a compressed mixture of Hexa 52.5, Zn dust 38.0, ZnO 4.0 and Mg powder 5.5%. Ignition was effected by a howitzer fuze and a gaine. The time of emission was 45-75 seconds.

f) Black Smoke Candle (NbK Sz) which served as a fixed aircraft smoke marker, consisted of a sheet metal cylinder, 140 mm long and 91 mm diam, provided with four 15 mm diameter emission holes and containing two compressed pellets (total weight 1.2 kg) of the smoke composition: Hexa 25, K chlorate 45 and crude anthracene 30%. Same ignition assembly as above. Time of emission about 2 minutes.

g) Black Smoke Candle (NbK Sz) constructed from a pasteboard 3 mm thick, was of the same dimensions as the above sheet metal container. The filling consisted of two compressed increments (total weight 1 kg) of Hexa 56, crude anthracene 30 and Mg powder 14%. Time of emission about 1 minute.

h) Smoke Candle (SBK II) which served to simulate the burning of vehicles, consisted of a pasteboard cylinder, 56 mm diameter and 280 mm high, filled with two hand pressed increments (total weight 600 g) of mixture: Hexa 2%, K chlorate 40 and crude anthracene 32%. Time of emission of black smoke about 6 minutes.

i) Smoke Candle (Tule) (NbK 1/45) which served as a light indicator, consisted of a sheet metal tube about 700 mm long and 80 mm diam. The smoke mixture consisting of Hexa 48, Zn dust 47 and Ba nitrate 5 and weighing 12 kg, was pressed indirectly. Ignition was effected by a howitzer fuze and a gaine. The time of emission was about 10 min.

Smoke Composition (Rauchsatz). Smoke compositions may be subdivided into two types:

a) Compositions which on heating developed a dense white or black smoke serving for screening purposes (Nebelstoff).

b) Compositions which on heating developed a colored smoke (Buntrauch), serving for signalling purposes. Many of these compositions are described under signal device, smoke bomb, smoke candle, smoke generator, smoke projectile, smoke signal and under pyrotechnics.

According to CIOS Rept 32-13 (1945), p 18, several smoke compositions were being developed towards the end of the W. II but were never put into service. Several compositions were prepared by adding to the mixture of Hexa (hexachloroethane) and Fe powder varying amounts of Mg, to accelerate the reaction. One such mixture contained Hexa 63, Fe 55 and Mg 2%. Very effective mixtures giving yellow to orange smokes were obtained by varying the proportion of the composition Hexa 48, Fe₂O₃ 36 and Mg powder 16. A new mixture designed for smoke candles consisted of Hexa 50, Zn dust 40 and ZnO 10%.

Among other smoke compositions may be mentioned titanium tetrachloride, designated as FM (used in some smoke hand grenades), a mixture of oleum 80 and pumice 20% (used in some projectiles) and a black smoke mixture Mg 18.5, hexachloroethane 61.5, naphthalene 12.0 and anthracene 8.0% (used the Black Smoke Cartridge).

References:

- 1) E.W. Bateman, CIOS Rept 32-13 (1945), pp 10-18
 - 2) H.J. Ppigg, CIOS Rept 32-56 (1945), pp 3-5 & 17-18
 - 3) Anon. TM 9-1985-2 (1953), pp 89, 325, 327-8 & 329
 - 4) Anon. FM 9-1985-3 (1953), pp 402, 473, 497 & 506.
- (See also References under Colored Smoke).


Smokeless Propellant or Smokeless Powder (Rauchlose Pulver oder Rauchschwaches Pulver). See Propellant.

Smoke Flare. See under Flare.

Smoke Generator (Rauchentwickler). According to E.W. Bateman, CIOS Rept 32-13 (1945), p 10, all German generators examined by him consisted of a sheet metal container with one or several emission holes) filled with one of the varieties of Berger mixtures. In these mixtures the hexachloroethane (abbreviated as Hexa) was used as the source of chlorine and this reacted with metals such as Zn or Fe. The latter metal was used when smoke of an orange-yellow color was desired. All smoke compositions were ignited by means of an igniter assembly.

Several smoke generators are described in this (German) section under Smoke Candles. They are called in German Nebelkerzen.

One of the generators, namely, **Parachute Recognition Smoke Generator** is described in TM 9-1985-2 (1953), pp 89-92. The device consisted of an aluminum cylinder divided into two sections, one housing the smoke producing parts and the other the parachute. The first section was subdivided into subsections by three metal plates which were connected by twelve metal distance rods. Eight of these rods were equally spaced around the circumference of the plates while the remaining four were spaced an equal distance from and closer to the center. The smoke canisters



Parachute Recognition Smoke Generator

were firmly held in two tiers, each with four canisters. Four 1/4 in holes were drilled in the plates for the igniting tubes. The individual smoke canisters were aluminum cylinders lined with stiff waterproof paper and containing four annular blocks, three of smoke composition and one of a clay-like substance. The smoke composition consisted of a heat stable blue dye 42 mixed with K chlorate 33 and lactose 25%. Each of the three smoke composition blanks had a small quantity of priming composition (black powder) placed in the loose condition at the base before pressing to ensure ignition between one block and the next. The ignition pellets were arranged to accept the flash from the ejection charge and distribute it to the four ignition tubes, each of which pierced the center of two smoke canisters. A total of fourteen black powder ignition pellets were packed in these tubes. The ejection charge, positioned directly below the pull igniter, consisted of 1/2 oz of fine mesh black powder. Below this was the first metal ejector plate which had a hole in the center to allow the flash to reach the ignition pellets. The second ejector plate, designed to prevent the parachute from becoming damaged or entangled in the outer container, was placed in the lower part of the upper container directly above the parachute. The parachute canopy was made of continuous filament viscose rayon. Total weight of the generator was 27.5 lb, overall length 20" and maximum diameter 8".


For operating the device, the transit cap was removed, the friction igniter cap was unscrewed and pulled longitudinally, and the ensemble allowed to fall clear. After a delay of 4 to 5 seconds, the igniter functioned and the flash from the detonator passed to the ejector charge to explode it. The pressure of the gases of explosion forced out the upper (smoke) section of the cylinder which, in turn, pulled out the parachute. At the same time, the flash from ejector charge ignited the pellets of black powder which distributed the flame to the four ignition tubes, each of which pierced the center of a smoke canister, thus igniting the smoke composition. Each canister emitted smoke of good density for about 26 seconds.

Smoke Grenade. See Smoke Hand Grenade and under Pistol Grenade and Rifle Grenade.

Smoke Hand Grenade (Netelhandgranate oder Blendkörper). The following types are described in TM 9-1985-2 (1953), pp 325-330:

a) Smoke Hand Grenade 39 (Nbhgr 39) closely resembled the HE stick grenade 24 in external form and size. It was filled with a smoke mixture containing hexachloroethane and Zn dust. Total weight 1 lb 14 oz

and overall length 14". Duration of smoke 2 minutes. Was used for screening machine gun nests and pill boxes. (pp 326-7)
 b) Smoke Hand Grenade 41 (Nbhgr 41) was similar in construction to the Nbhgr 39, except that it was not provided with the stick (handle). Maximum diameter 2.3", overall length 4.7" and total weight 21 oz. was filled with hexachloroethane - Zn dust mixture. Same time of emission and used as in the Nbhgr 39 (pp 325-6).
 Note: According to CIOS Rept 32-13 (1945), p 13, the composition of the smoke mixture was: Hexa (hexachloroethane) 55.0, Zn dust 43.5, and Ba nitrate 1.5%. The weight of the charge 400 g and the time of emission 150-250 seconds.




c) Smoke Hand Grenade (Blendkörper 14) consisted of a tear drop shaped glass flask (2 1/2" diameter), provided with a cardboard handle and filled with 10.6 oz of titanium tetrachloride (FM). Its overall length was 6" and total weight 13.2 oz. The grenade was used to produce a small smoke screen to blind the enemy or to patch gaps in larger smoke screens. The flask could be easily broken by throwing it against a hard surface. On vaporization the tetrachloride formed a dense smoke, if the relative humidity was high (pp 327-8)

d) Smoke Hand Grenade (Blendkörper 24) consisted of an outer glass bulb of molded construction containing 270 g of titanium tetrachloride and an inner glass tube containing 36 g of an aqueous solution of Ca chloride which was seated on a rubber washer in the neck of the outer container. The ensemble was sealed by a sulfur and cement plug. The contents of the inner tube served to provide the water necessary for the reaction with tetrachloride in the formation of heavy smoke. The Ca chloride was probably added as an antifreeze. The grenade was operated in the same manner and for the same purposes as the Blendkörper 14. (p 328)

e) ERK Type Smoke Grenade (NBEhgr 42) consisted of a cylindro-ellipsoidal shaped metallic container, 4.1" long and 1.7" diameter filled with a smoke composition. One end of the body was flattened to permit the insertion of the pull type igniter ZdschnAnz 29 (p 329).

Note: According to CIOS Rept 32-13 (1945), p 13, the composition of the smoke mixture in the NBEhgr 42 was: Hexa (hexachloroethane) 55.0, Zn dust 43.5 and Ba nitrate



1.5. The weight of the mixture was 170 g and the time of emission 60-100 seconds.


Smoke Hand Signal. See under Signal Device and also under Pyrotechnics.

Smoke Pistol Grenade. See under Pistol Grenade.

Smoke Projectile or Shell (Nebelgeschoss, Rauchgranate). Projectile containing a large charge of smoke producing composition and a small charge of bursting explosive. Several types of such shells were used during WW II by the Germans. These shells, on explosion, produced some fragments which were effective against personnel (but not against objects) and a dense smoke or fog which served to prevent the enemy from seeing what was going on. In some cases the smoke projectiles were used for spotting purposes, as for instance the 80 mm Colored Smoke Mortar Projectile.

The following smoke projectiles are described in TM 9-1985-3 (1953), pp 402-3, 472-3, 496-8, 506-7, 512 and 531-2:

a) 75 mm Smoke Projectile for the Tank Gun (7.5 cm NbgrPatr KwK) was machined to the same design as the HE projectile. The inner tube contained a small burster charge (2 oz of picric acid) and a large charge of oleum, 20 parts, impregnated in 20 of pumice stone. Total weight of shell was 13.6 lb. (pp 402-3)




b) 105 mm Smoke Projectile for the Field Howitzer (10.5 cm FHGrNb) was similar in construction to the previous shell. It contained 4.3 oz of P A (bursting charge) and 4.1 lb of smoke charge (oleum impregnated in pumice). Total weight of projectile 30.8 lb (pp 472-3)

c) 150 mm Smoke Projectile, Type 19 (15 cm Gr 19Nb) for the Heavy Howitzer 15 cm sFH 13 or sFH 18, was similar in construction to the previous shell. It contained 1.21 lb of P A (bursting charge) and 14.08 lb of oleum impregnated in pumice. Total weight of projectile 85.8 lb (pp 496-8)

d) 150 mm Smoke Projectile (15 cm Jgr 38Nb) for the Heavy Infantry Gun 15 cm sIG 33 had a larger inner burster tube than the previous type. It contained 4.93 lb of P A (in the burster tube) and a smaller charge of smoke mixture (oleum/pumice) than the 15 cm Gr 19Nb. Total weight 80.4 lb (pp 506-7)

e) 150 mm Smoke Shell, Type 38 (15 cm Gr 38Nb), for the Heavy Field Howitzer (15 cm sFH 18) was similar in construction to the 15 cm Jgr 38Nb, except that its bursting charge consisted of TNT. Total weight not given (pp 506-7)



f) 155 mm Smoke Projectile [15.5 cm Gr 422 (f)] for the French Heavy Gun 15.5 cm K 420 (f) L.Mle 1916 St Ch was of conventional design. Its inner (burster) tube was shorter than in the German designed smoke projectiles and extended to less than one half of the length of the shell (p 512)


g) 80 mm Smoke Mortar Projectile (8 cm Wgr 34Nb) for the medium (mittlerer) mortar (8 cm mGrW 34) and for the short (kurzer) mortar (8 cm kzGrW 42) was conventional in design. It carried a sulfur trioxide smoke mixture and a PETN/wax bursting charge. It weighed 7.85 lb and was provided with 12 fins (p 532)

h) 80 mm Colored Smoke Mortar Projectile (8 cm Wgr 38Deut) for heavy (schwerer) mortar (8 cm sGrWerfer 34) was of conventional design and carried 12 fins. It was filled with a composition which gave a colored smoke on bursting (p 531)

i) 380 mm Smoke Mortar Projectile (38 cm Wgr 40Nb) for the heavy spigot mortar (38 cm schweres Ladungswerfer) was of the same design as the corresponding HE mortar projectile described on p 535 of TM 9-1985-3 (1953)

j) 353 mm Anticoncrete Projectile (35.3 cm GrBe) for the Howitzer. (35.3 cm Hnubltze M1) is briefly described under Spotting Projectile

k) 105 mm Field Howitzer Smoke Shell (10.5 cm FHGr 40Nb) [briefly described on p 14 of CIOS Rept 32-13, (1945)] was filled with 1.8 kg of the smoke mixture



containing: hexachloroethane 55, Zn dust 43.5 and Ba nitrate 1.5%. The time of emission was 4-7 minutes. Note: According to H.H. Bullock of Picatinny Arsenal, all German smoke and chemical projectiles were loaded from the side. This was contrary to the American practice of loading projectiles through the throat.

Smoke Puff Cartridge. According to H.J. Eppig, CIOS Rept 32-56 (1945), p 6, such an item was developed by the Deutsche Pyrotechnische Fabrik at Kieselbach/Vacha, but the item is not described.

Smoke Rifle Grenade. See under Rifle Grenade.

Smoke Rocket. See Smoke and Chemical Rocket.

Smoke Shell. See Smoke Projectile.

Smoke Signal Device. See under Signal Device.

Smoke Signal, Hand. See under Signal Device and under pyrotechnics.

Smoke Stick (Nebelstab), which served as a wind direction indicator, consisted of a sheet metal tube, about 100 mm long and 16 mm diameter, attached to a wooden handle about 50 mm long. Its smoke filler consisted of six pellets containing: lactose, K chloride and Am chloride (exact composition is unknown). It was ignited by means of a cap with a friction surface.

Reference: E.W. Bateman, CIOS Rept 32-13 (1945), p 18.

Smoke Tube (Rauchrohr) was a smoke emitting device consisting of a seamless drawn tube, 250 mm long and 25 mm diameter, into which the following compositions were pressed by hand:

a) Main layer: hexachloroethane 49, Zn dust 41, Zn oxide 4 and Mg 6% and

b) Initiating layer: hexachloroethane 55, Zn dust 41 and Mg 4%. Ignited by a safety fuse.

Total weight of the device was about 200 g and time of emission not less than 60 sec.

Reference: CIOS Rept 32-13 (1945), pp 13-14.

Snap Type Igniter (Knickzunder). See under Igniter.

Snorkel oder Snort. See Schnorkel.

Sodotol. An explosive containing Na nitrate 55 and TNT 45%. It was suitable for loading bombs and shrapnel shells. A. Stettbacher, Schiess- und Sprengstoffe, Barth, Leipzig (1933), p 277.

Sodium Azide (Na A) (Natriumazid). See general section under Azides. NaA was used in Germany for the manufacture of lead azide (L A), as described in PB Rept 93,613 (1947), Section 0 (See also under Bleiazid).

Sodium Chloride Explosives or Kitchen Salt Explosives (Kochsalzsprengstoffe). German substitute explosives containing large amounts of NaCl (up to 60%). They are described under Ersatzsprengstoffe.

Sodium Nitrate Explosives (Natriumnitrat sprengstoffe). Explosives containing Na nitrate, such as Sodotol and some explosives described under Ersatzsprengstoffe.

Sodium Picrate (Natrium Pikrat). See general section under Picrates. It was used during WW II in Germany as a component of GP (Powder), proposed as a substitute for black powder and as a propellant for Panzerfaust. In this composition the picrate was mixed with a binding substance such as Igetex SS.

Reference: CIOS Rept 25-18 (1945), pp 27-28.

Solid Catalyst. See MP-14.

Solvents and Plasticizers for nitrocellulose, plastics (such as polyvinyl chloride), resins, synthetic rubbers etc were described in some BIOS, CIOS and FIAT Reports, and especially in BIOS Repts 1651 and 1652. These two reports covered the investigation during November-December 1946 in the field of solvents and plasticizers sponsored by the Raw Materials Division of the (British) Board of Trade. The field of investigation did not include petroleum and chlorinated hydrocarbons. A brief description of the methods of preparation of about 150 solvents and plasticizers were given but no data for the solubility of NC, etc. Some properties of plastics are given in the above reports.

Soman. See under Trilons.


Sondertreibstoff (Special Propelling Material), developed during WW II by IG Farbenind, was presumably intended for use as jet propulsion fuel. It contained an unsaturated compound (diketene) which reacted with concentrated (90%+) nitric acid with explosive violence. The reaction time was within hundredths of a sec.

The mixture finally developed contained: divinylacetylene (diketene) 5-6, vinyl acetate 6-12, benzine 70, diethylaniline 1 and iron carbonyl 10%.

Note: The composition does not add to 100%. The large amount of iron carbonyl appears questionable.

Reference: CIOS Report 25-18 (1945), pp 20-21.

Sound Gun. This weapon, constructed by R. Wallauschreck of Austria, was designed to cause casualties or damage by means of sound waves of great intensity. It was claimed that at short range (say 60 m) it could kill a man and at greater ranges (say 300 m) it could disable him for an appreciable length of time. A brief description of this device is given by L.E. Simon, German Research in WW II, Wiley, NY (1947), pp 181-2. The weapon consisted of a parabolic reflector, 3.2 meters in diameter, having an attachment extending to the rear of the vertex of the parabola. The attachment consisted of a firing chamber (for producing energy for sound), the length of which was $\frac{1}{4}$ of the wave length of the sound. At its rear, the chamber was provided with two coaxial nozzles, the outer nozzle emitting methane and the inner one emitting oxygen. The frequency of sound was from 800 to 1500 impulses per second and the pressure produced by the sound waves was



equal to 1000 microbars, when measured at a distance of 60 meters. The military value of this weapon was slight due to its short range.

"Sonne" Guidance System for Missiles. See under Guidance Systems for Missiles.

Space Explosions with Carbon Dust. See under Krümme! Fabrik Dynamit A-G Pressing of Explosives and Research and Development Work.

Spalt Fuseheads or Splitting Priming Drops. When shooting in coal mines where considerable uncontrolled electric currents are to be found, the fuseheads of electric blasting caps or detonators have to be constructed in such manner that they shall not ignite from a potential as high as 15 volts. This was achieved at the Troisdorf Fabrik, D A -G by using special tension fuseheads in the resistance range of 3000 to 50000 ohms.

For preparing such fuseheads the tip of the bridge wire was dipped successively into the following compositions, allowing the material to dry after each dip:

- a) 1st dip composition, which consisted of Pb peroxide 43 g, cerium - magnesium alloy 28.5 g and Al (particle size 10 to 20 microns) 28.5 g suspended in about 70 ml of a 3% soln of NC in amyl or butyl acetate
- b) 2nd dip composition consisted of red lead (particle size less than 5 microns) 90 g and silicon (particle size 20 to 40 microns) 10 g suspended in a 3% soln of NC in amyl or butyl acetate
- c) 3rd dip composition was a lacquer consisting of a 15% soln of NC in 75/25- butyl acetate/ethanol, to which was added SipalIn AOM (methylcyclohexyl ester of adipic acid) in the amount of 20% of the dry weight of NC.

The storage stability of these fuseheads in moist atmosphere was not very good.

Note: Soldering of the bridge (fuse) wire to the lead-in wires, preparation of dry ingredients for fusehead dips, preparation of NC lacquers and the process of dipping the fusehead combs are described under Fusehead Manufacture.

References:

- 1) B I O S Final Rept 833, Item 2 (1946), p A3/35
- 2) PB Rept 95,613 (1947) Section D.

Spezifische Energie oder Spezifischer Druck, designated as "f". See Specific Energy, or Specific Pressure in the general section.


Spezifisches Gewicht See Specific Gravity in the general section.

Spezifische Wärme . See Specific Heat in the general section.

Spigot Mortar (Ladungswerfer) Projectile. The following projectiles are briefly described in TM 9-1985-3 (1953), pp 354-5:

- a) 200 mm Mortar Projectile, 20 cm Wgr 40 (Werfergranate 40) for use in the light (leichter) spigot mortar (20 cm Ladungswerfer) consisted of two sections, one housing about 17 lb of bursting charge (TNT) and the other propellant in three sections each weighing 12 g. Total weight of the round was about 50 lb (p 534)
- b) 380 mm Mortar Projectile (38 cm Wgr 40) for the heavy spigot mortar (38 cm Ladungswerfer) was similar in design and shape to the 20 mm projectile. It contained 110 lb of HE bursting charge and was provided with 6 fins. Total weight of projectile was about 328 lb (p 535).

Note: There is no indication in the above manual how this projectile was fired and what kind of spigot mortar was used. It is probable, however, according to H.H. Bullock of Picatinny Arsenal, that the hollow tail section of the



projectile was placed (before firing) over a spigot which was in the form of a short tube. At the base of the tube was inserted a cartridge case with a propellant and a primer. The firing was probably done in a manner similar to that for the Sutton Mortar, i.e. by a striker held by a coiled spring and operated by a lanyard.

Spike Bomb. See Stachelbombe.

Spiralit (Spiralite). A class of smokeless propellants prepared, in 1898, by nitrating sheets of paper and impregnating them with substances which slow down the rate of burning (moderants). The exact composition of these propellants was never revealed by the manufacturer, the Explosivstoff-Werke Spiralit Gesellschaft und Max Thorn, Hamburg. The charges were made by superposing and compressing several sheets of nitrated paper.

Reference: J. Daniel, Dictionnaire, Paris (1902), p 735.

Splitterdicke (Density of Fragments). See Fragments Density Test.

Splitting Process of Manufacture of Sulfuric Acid is briefly described under Sulfuric Acid Manufacture.


Sporting Powder. See Jagdpulver.

Spotting Projectile (Schussbeobachtungsgranate). A projectile serving for observation and adjustment of artillery fire. It contained a small charge of smoke composition in a separate container inserted in the high explosive charge.

The following projectiles are described on pp 405, 494-6, 500, 529 & 533 of TM 9-1985-3 (1953):

a) 75 mm HE Projectile (7.5 cm Igr 18 AZ 23nA) for the Light Infantry Gun (IG 18) or Light Mountain Infantry Gun (LIG 18). It was about 13" long and contained 1.21 lb of an Amatol. Directly under the gaine of the PETN booster (GrZdlg C/98 Np) was located a small charge of smoke composition (pp 405-6)

b) 150 mm HE Projectile 19 with Gaine 36 (15 cm Gr 19 mZdlg 36) for Heavy Field Howitzer 18 (sFH 18). It contained 11.22 lb of cast TNT as a bursting charge and a small smoke charge directly under the booster.




Total weight of projectile was 95.7 lb. Two types of point detonating fuzes were used: AZ 23 or DoppZ s/60. The base was provided with a screwed-in plate. (pp 494-5)

c) 150 mm HE Projectile of Cast Steel (15 cm Gr 19 Stg) for Heavy Field Howitzers (sFH 13 and sFH 18) and for Heavy Turret Howitzer (sHT). It was similar in appearance to the previous projectile, except that it did not have the screwed-in base plate. (pp 495-6)

d) 150 mm HE Projectile 19 (15 cm Gr 19) for Heavy Field Howitzers (sFH 13 and sFH 18) or for Heavy Turret Howitzer (sHT). It was about 25" long and contained 9.46 lb of TNT in cardboard containers) as a bursting charge. A small charge of smoke composition was placed on the bottom of the shell. The projectile had a screwed-in base plate. Two types of point detonating fuzes were used: impact and combination AZ 23 and DoppZ s(60), and two types of boosters (GrZdlg C/98Np and GrZdlg C/98) (pp 500-501)

e) 353 mm Anticoncrete Projectile (35.3 cm GrBe) for Howitzer M1 was conventional in design and contained 75 lb of TNT as a bursting charge and a small charge of a smoke composition used for spotting purposes. Total weight of loaded projectile was 1265 lb.

Note: According to information supplied by H.H. Bullock and A.B. Schilling of Picatinny Arsenal, it might be assumed that the HE filling consisted of four sections loaded in a carton: the 1st and 2nd front sections were cast TNT containing 5-10% wax, the 3rd section was cast straight TNT and the 4th section was pressed TNT (or possibly




picric acid). It is presumed that the 4th section acted as an auxiliary booster, because it does not seem possible that the large mass of cast TNT could have been exploded by the small booster (shown on the drawing) which did not extend sufficiently into the bursting charge.

1) 100 mm Mortar Projectile (10 cm Wgr 37) used in 10 cm NW 35. It contained 3.125 lb of TNT as the bursting charge and a small charge of smoke composition located underneath the booster (GrZdlg C/98Np) and the fuze (WgrZ 38). Total weight of the projectile was 16.0 lb (p 534).

Sprengbrandbombe (Combination Demolition - Incendiary Bomb). One such bomb, the **Sprengbrand C50 Bombe**, is described on pp 50-2 of TM 9-1985-2 (1953). The bomb was of the same shape as conventional HE bombs but its filling was different. The nose section of the bomb contained 20 lb of TNT and behind the charge was placed the fuze pocket. In the fuze pocket was located a bakelite gaine contg a black powder biscuit and a steel encased gaine contg a delay pellet and detonator; the whole assembly being held in place in the base of the fuze pocket by a leaf spring. A hole drilled through the rear side of the fuze pocket and through the diaphragm (which divided the bomb into two sections) led to a silk bag contg black powder. The powder served both as the igniting and expelling charge for the middle section of the bomb contg incendiaries. The incendiary units (six fire pots and 67 small triangular metal incendiary elements) were placed around a long triangular hollow steel column. Three double grids were placed in annular fashion around this column. Each pair of grids had four orange-colored biscuits of highly inflammable material pressed between them. These biscuits were ignited by the flash from the black powder expelling charge and, in turn, ignited the small incendiary units directly and the quickmatches of the six large units. The explosion of the black powder charge also sheared the aluminum screws securing the base plate and ejected the incendiary elements over a radius of about 100 yards. About 1 second after expulsion, the delay element in the booster reached the detonator and fired the TNT charge in the nose of the bomb.

Total weight of bomb was about 75 lb, overall length 42.5", body length 24.0", body diameter 8.0", wall thickness 0.15", tail length 16.0" and its width 11.3".



Sprengelsprengstoffe. See Sprengel Explosives in the general section.

Sprenggelatine (Blasting Gelatin). According to Stettbacher (Ref 1) the German Sprenggelatine contained: NG 91-93 and collodion cotton (N content 11.8 to 12.4%) 7 to 9%.

According to Weichelt (Ref 2) the 93/7 Sprenggelatine had the following properties: temp of explosion 4210°C, vol of gases at NTP 712 l/kg, density of loading 1.55, specific pressure (f) 1200 kg/cm², velocity of detonation 7800 m/sec, Trauzl test 520 cc and impact sensitivity with 2 kg weight 12 cm.

References:

- 1) A. Stettbacher, Spreng- und Schiesstoffe, Zürich, (1948), p 82
- 2) F. Weichelt, Handbuch der gewerblichen Sprengtechnik, C. Marhold, Halle/Saale, (1953), p 374.

Sprengkapsel (Blasting Cap). See under Detonators.

Sprengkörper 02 (Spr Kpr 02) (Explosive Pattern 1907). A demolition charge weighing 200 g used during WW I for military pioneer work. It replaced a similar charge made of picric acid called Sprengkörper 88 [Colver High Explosives (1918), p 23].

Sprengkörper 28 (Spr Kpr 28). (Explosive Pattern 1928) consisted of TNT or P A in blocks 2" x 1 5/8" x 2 3/4" wrapped in wax paper or placed in bakelite containers. It was one of the demolition charges of WW II. It was used in some land mines, as for instance Glasmine 43(f).

References:

- 1) US War Dept Tech Manual FM 5-25 (1945), pp 129-132
- 2) TM 9-1985-2 (1953), p 275.

Sprengmittel. An explosive in prepared form, as distinguished from the generic term Sprengstoff.

Sprengmunition 88 (Füllpulver 88 oder Fp 88) (Explosive Pattern 1888). The name given to picric acid (P A) adopted as a military explosive in 1888.

Sprengmunition 02 (Füllpulver 02 oder Fp 02) (Explosive Pattern 1902). The name given to TNT adopted as military explosive in 1902, replacing Sprengmunition 88.

Sprengniet (Explosive Rivet). See general section and also the paper of E. R. von Herz, Explosivstoffe, 1954, Heft 3/4, pp 29-38.

The Ger Pat 708,238 gives the following composition for use in explosive rivets: Al (powder) 65, mannitol hexanitrate 25 and tetracene 10%.

Sprengöl oder Nobels Sprengöl. Same as Nitroglycerin.

Sprengpatrone 02 (Spr Ptr 02). Demolition charge weighing 1 kg used at the time of WW I for military demolition work. It replaced a similar charge, "Sprengpatrone 88", made of P A [Colver, High Explosives (1918), p 23].

Sprengriegel. See TM 9-1985-2 (1953), p 264 and also under Landminen.

Sprengsalpeter (Saltpeter Blasting Explosive). Any blasting explosive containing K and/or Na nitrate, charcoal/or

coal and sulfur, such as blasting black powder belongs to the class of Sprengsalpeter explosives.

Sprengstoff. Generic term for an explosive as distinguished from Sprengmittel.

Sprengzünder, Elektrische (Electric Blasting Cap, literally Electric Detonating Igniter). Two types of such devices are described by Beyling & Drekopf, Sprengstoffe und Zündmittel (1936), pp 222-6.

"S" Pulver (Spanlau Powder). A propellant manufactured before WW I by treating the surface of single-base powder grains with an alcoholic solution of centralite or diphenylamine. This propellant was exported to Turkey.

Another kind of "S" Pulver was a sporting propellant prepared by nitrating sawdust and gelatinizing the resulting product.

Reference:

P. Pascal, Explosifs, etc., Paris (1930), pp 227-228.

Squeeze Bore Gun. See Note under Tapered Bore Gun.

SSP (Sicherheitssprengpulver). A safety explosive which is based on ammonium nitrate.


Reference: Daniel, Dictionnaire (1902), p 737.

Stabilität oder Beständigkeit (Stability), **Lagerbeständigkeit** (Stability in Storage). Stability of explosives and the tests for stability are described in the general section.

Stabmine: See "B" Stabmine and also under Landminen.

Stabo. See Stachelbombe.

Stachelbombe, abbreviated as **Stabo** (Spike Bomb). Some German bombs, such as the SC 50, SD 70, SC 250 and SC 500 could be fitted with a spike by attaching it to a threaded lug forged to the nose of the bomb just above a




fuze. The attachment was used in low altitude attacks to prevent the bomb from ricocheting.

Reference: TM 9-1985-3 (1953), pp 21-2.

"Standard" Propellant (Einheitspulver or EP), called "Unit" Powder by H.H.M. Pike, CIOS Rept 31-68 (1945), p 6], was a "G" Pulver (diethyleneglycol dinitrate propellant) which contained 1.5% K nitrate or 3% hydrocellulose and had a calorific value of 710-730 kcal/kg. This mixture was introduced in 1944 as the "Service" propellant for all ammunition in order to minimize the differences in ballistics previously usually obtained when propellants with the same formula were manufactured at different plants. The incorporation of either K nitrate or of hydrocellulose was claimed to give much more uniform inter-plant ballistics of propellants.

Stanzprobe (Punch Test). See Analyt Section, Brisance Tests

Star Shell. One of the projectiles (10.5 cm Leichtgeschoss FES) described in TM 9-1985-3 (1953), p 404, contained a star unit attached to a parachute. When the shell reached a predetermined position over enemy territory, the time



fuze fired the expelling charge and the resulting pressure caused the star and the parachute to be ejected through the base of the shell. Simultaneously the flash from the burning gases of the expelling charge ignited the star composition. This shell served for illuminating the enemy's installations and troops in order to assist the artillery.

The shell weighed 31.3 lb and was fired from some captured 105 mm guns, such as Belgian, French, Polish and Yugoslav.

A larger projectile (203 mm) serving the same purpose but designated the Flare Projectile, is described on pp 819-20 of TM 9-1985-3. Its German designation was 20.3 cm Leuchtgranate and it was fired from the Railroad Gun, K(E). (See also under Flare).

Stauchprobe oder Brisonzprobe (Compression Test or Brisance Test, known also as Crusher Test). Two tests of this kind originated in Austria and Germany. The first method used the **Deutscher Betriebs - Stauchungsmesser**, an apparatus invented in 1879 by Hess, while the second method used the **Brisanzmesser nach Kast**, an apparatus invented in 1913 by Kast.

Both of these methods are described by Stettbacher (Refs 1 and 2) and in the general section under Brisance Determinations.

References:

- 1) A. Stettbacher, Schiess- und Sprengstoffe, Barth, Leipzig (1933), pp 365-368
- 2) A. Stettbacher, Spreng- und Schiessstoffe, Rascher, Zürich (1948), pp 113-115.

Steel and Iron Ammunition Items. Nearly all of the smaller ammunition items (such as bullets, caps, cartridge cases, etc) of the pre- WW II period were manufactured from non-ferrous metals or alloys such as copper, lead, nickel, brass, gilding metal, etc. Due to the acute shortage of the above metals which developed at the beginning of WW II, it was found necessary to replace them by the ferrous metals such as steel or iron.


The following ammunition items made of steel or iron by the Deutsche Waffen- und Munitionsfabriken A-G, Schültrup bei Lübeck, are described by H. Peplow et al, CIOS Report 33-20 (1945), pp 7-22, 30-38 & 48-50:

- a) SmlE (Spitzgeschoss mit Eisenkern) Bullet, consisted of an iron (soft steel) core surrounded by a lead jacket surrounded by a steel envelope zincated on the outside (pp 17 & 30)
 - b) SmlE (lang) (Spitzgeschoss mit Eisenkern (lang)) Bullet, was similar to the SmlE except that the lead sleeve was only in the rear section. In order to compensate for the loss of weight, the length of the iron core was correspondingly increased (pp 17 & 30).
- Note: There were also armor-piercing bullets, one with a steel core (Spitzgeschoss mit Stahlkern) and another with a tungsten carbide core (Spitzgeschoss mit Stahlkern, Gehärtet). They are briefly described under Small Arms Ammunition.

c) Steel (Leadless) Bullet, Type A, consisted of a steel core surrounded by a steel envelope. In this bullet an attempt was made to cushion it (while in the bore) on a film of gas. For this purpose, two slots were made in the base of the core in order to allow inflow of gases on firing. The core was also cannellured and the envelope had two cannellures, one to key it to the core, the other for attaching the cartridge case. It was claimed that the barrel life with this bullet was about 5000 rounds (p 30)

d) Steel (Leadless) Bullet, Type B, was a zinc-coated, turned steel slug with the bearing surface considerably reduced in comparison with ordinary bullets. Barrel life with this bullet was claimed to be about 3000 rounds, but could be increased by lubricating the bullet (p 30).

Steel Cap manufacture is briefly described on pp 36-7. The caps were zincated and then internally varnished previous to filling them with the following mixture: Pb styphnate 40, Ba nitrate 42, Ca silicide 10, Tetracene 3 and Pb peroxide 5%. Steel Cartridge Case manufacture is briefly de-



scribed on pp 8-16 and 48-50.

(See also under Cartridge Cases, Steel).

It should be noted that the Germans developed the technique of making sintered iron bullets (see under Pulvermetallurgie) and also a process for covering the steel projectiles with sintered iron or steel, described briefly in this work under Tiefbinder Verfahren.

Stick Grenade. See Rodded Bomb.

Stick Handgrenade. See Potato Masher Grenade.

Stielhandgranate (Stick Hand Grenade). See Potato Masher Grenade.

Stockmine. See under Landminen and also on p 277 of TM 9-1985-2 (1953).

Stonit (Stonite). One of the Carbonit-type explosives manu'd about 50 years ago in Germany and admitted to England. It consisted of NG 68, kieselguhr 20, wood meal 4, and K or Ba nitrate with Mg carbonate 8%. To this could be added some sulfonated oil, or lard [Daniel, Dictionnaire, Paris (1902), p 739].

Storm Matches. According to BIOS Final Rept 1313 (1947), these matches were manufactured by the Deutsches Zündwaren Monopole at Lüneburg. No description of match composition is given.

Streckungsmittel oder Streckmittel (Extender, called also Stretcher, Filler or Diluting Agent). In order to combat the shortage of aromatic nitrocompound explosives (such as TNT), the Germans incorporated some non-explosive materials which served to increase the bulk of the explosive. The most common of such extenders were

oxidizing agents, such as Am, K, or Na nitrates. These substances were not inert as they supplied oxygen to oxygen deficient aromatic nitrocompounds, such as TNT. Other German extenders, such as Na chloride, being neither oxidizers nor combustibles were not as useful, although it was claimed that mixtures of TNT/NaCl - 50/50 or 40/60 developed considerable gas pressure on explosion.

Explosive compositions in which extenders were used were called Ersatzsprengstoffe (q v).

Reference: PB Rept 85,160 (1946), p 7.

"Strassburg-Kehl" Guidance System. See under Guidance Systems for Missiles.

Streubomb C 509 (Container for Scattering Incendiary Bombs). It consisted of a metallic tube, divided along its longitudinal axis into two sections welded together, with a primacord running alongside the seam. A delay fuze with a gaine were attached to the primacord. The container was filled with 1200 green incendiary boxes immersed in water. On release of the container, the fuze was charged and, after a short delay, it fired and detonated the gaine and the primacord. The detonating wave travelled alongside the seam and caused the separation of the two halves of the container thus scattering the incendiary boxes over a target. This device did not work very satisfactorily. Reference: TM 9-1985-2 (1953), p 117.

Structural Explosives (Blast Effect Explosives). At the time of the development of rockets in Germany (during WW II) the military authorities requested the Krümmel Fabrik, D A -G, to produce high explosive charges which could be used as missiles without being confined in steel casings and thus to save dead weight. It was suggested by the Krümmel Fabrik that material consisting of layers of paper 20 parts, impregnated with 80 pts of molten TNT, previously mixed with RDX and NC, be used for the construction of such projectiles. The other suggestion was to combine synthetic resins (thermoplastic and thermosetting) with RDX and to use this mixture as the HE for such projectiles (Ref 1).

It is to be noted that such projectiles produced high blast effects (Luftdruckwirkung oder Luftstoss), but comparatively low shattering effect, called also Brisanz (Brisanz). Practically the same kind of blast effect was achieved with a HE in bombs constructed by filling a thin, light, metallic case, strong enough to withstand handling and shipping, but too weak to withstand impact with target. These bombs (called in the USA the light case bombs) were of very high capacity (about 80%) and caused considerable damage by blast effect alone, especially in residential sections. They were fuzed for superquick or non-delay action.

The larger size bombs were called "blockbusters" in Great Britain and the USA.

References:

- 1) O.W. Stickland, PB Rept 925 (1945), Appendix 7
- 2) T.C. Ohart, Elements of Ammunition, Wiley (1946), p 227.

Stubenrauch Explosives. A series of explosives patented at the end of the last century by von Stubenrauch of Rastatt. One of his explosives was prepared by blending K chlorate 80 with 0.5-1.0% of Ca carbonate (or Mg oxide) and with a mixture prepared by treating the hot pulverized charcoal with tar (goudron) previously dehydrated and desulfurated. J. Daniel, Dictionnaire des Matières Explosives, Paris (1902), p 795, under Von Stubenrauch].

Sturmbräuer (Assault Mortar). A self-propelled mount consisting of a 380 mm rocket projector on PzKpfw VI (E) (See also under Panzer).

Styphninsäure (Styphnic Acid). See Trizin.

Submachine Gun or Light Machine Gun. See under Weaponry. The Automatic Pistols (Maschinenpistolen) provided with shoulder attachments may also be called Submachine Guns.

Submarine 21. See U-Boat 21.

Submarine, One Man. See U-Boat, One Man.

Submarine, Pocket. See Seehund.

Submarine, Walter. See U-Boat Walter.

Sulfuric Acid (Schwefelsäure). Preparation, properties and uses are given in the general section. The contact method, using a vanadium catalyst, was the most common in Germany, but some plants used the old chamber process and at least one plant used the wet contact process utilizing hydrogen sulfide. The Chemische Düngstoffabrik A-G used the so-called Peterson Tower Process installed by the Lurgi Apparatebau A-G. In all of these methods sulfur was the primary material. Inasmuch as sulfur was not plentiful during WW II, a special process (Splitting or Cracking Process) which permitted the recovery of sulfur in the form of sulfur trioxide from waste weak sulfuric acids was developed and constructed by Lurgi Co (See under Lurgi Cracking Plant). This new process of manufacture of oleum was used by several German factories but it is doubtful (see Ref 13) if the process would be economical in peace time when sulfur is plentiful. Another sulfur saving process is briefly described under Sulfur Recovery.

The number of German sulfuric acid plants was very great but the following plants, briefly described in various BIOS Reports, may be considered as typical:

- a) A-G des Altenbergs für Bergbau- und Zinkhüttenbetrieb, Essen-Bergeborbeck (Chamber and contact process plants) (Ref 7)
- b) Berzelius Metallhütten GmbH, Duisburg-Wanheim (Chamber process plant) (Ref 6)
- c) Chemische Düngstoffabrik, Randsburg (Peterson Tower process) (Ref 9)
- d) Chemische Fabrik Wesseling A-G, Wesseling bei Köln (Chamber process sulfuric acid plant and also a sulfur recovery plant from spent oxides by the method of Dr Jakob) (Ref 11)
- e) Dynamit A-G plant at Leverkusen-Schlebusch (Contact process) (Ref 5)
- f) Gaswerke Frankfurt a/Main (Wet contact process from hydrogen sulfide) (Ref 12)
- g) IG Farbenindustrie A-G, Leverkusen (Contact process) (Ref 1)
- h) Krümmel-Geestacht Fabrik of D A -G (Contact process) (Ref 10)
- i) Lurgi Chemie A-G, Frankfurt a/Main (Contact process and Lurgi Cracking Unit) (Ref 3)
- j) Norddeutsche Affinerie, Hamburg (Contact process) (Ref 8)

References: BIOS Final Reports: 1) 244 (1945), 2) 1623 (1947), 3) 1631 (1948), 4) 1633 (1948), 5) 1634 (1948), 6) 1636 (1948), 7) 1639 (1948), 8) 1641 (1948), 9) 1642 (1948), 10) 1643 (1948), 11) 1644 (1948), 12) 1645 (1948) and 13) PB Rept 925 (1945), p 25.

Sulfur Monochloride - Vegetable Oil Dynamites were prepared, beginning about 1898, by the Chemische Fabrik at Winkel on Rhine by mixing NG with rubber-like products obtained on treating vegetable oils (such as linseed oil) with sulfur monochloride, S₂Cl₂. Other ingredients, such as TNT, P A, etc could be incorporated.

Similar explosives were prepared by Bielefeldt.

Reference: J. Daniel, Dictionnaire, Paris (1902), pp 71 & 134.

Sulfur Recovery from Spent Iron Oxides. To reduce the shortage of sulfur (so essential for the manufacture of sulfuric acid) the Chemische Fabrik Dr Jakob, Bad Kreuznach, before WW II, invented a method of recovery of sulfur from the spent oxides which were used for the purification of gases in the Fischer-Tropsch Process Plants or in the Gas Works. One such installation was at the Chemische Fabrik, Wesseling. It was reported that not less than 65 000 tons of sulfur were recovered annually by this method.

of sulfur recovery. (See under Lurgi Cracking Process).

- Dr Jakob's Process was essentially as follows:
- Four vertical cylindrical jacketed extractors, fitted with covers and each containing six trays were loaded with spent oxides (7.5 tons in each vessel) and extracted with carbon disulfide at 25°, entering each vessel at the top and moving by gravity
 - Of the 4 extractors, 3 were in the extraction cycle and one off for charging or discharging. As a freshly charged extractor was put on the line an extractor containing exhausted oxide, was taken off
 - The freshly charged vessel was first treated with CS₂ rich in sulfur and from there the saturated soln went to a 10 ton capacity water-heated still for distillation, while fresh CS₂ from the head tank entered the most exhausted extractor
 - When the sulfur extraction in the spent oxide had proceeded to the economic limit, the extractor was taken out of the circuit and the CS₂ soln remaining in it removed to the still by direct injection of live steam at 6 atm pressure
 - After removal of the last traces of CS₂, the extractor cover was removed and the nest of trays lifted out
 - Distillation of CS₂ was conducted batchwise at 80-90° and the CS₂ was condensed and collected. When distillation was complete, the temperature in the still was raised to 130° by direct steam and the molten sulfur run out through a jacketed pipe into a large shallow brick tray in the open air. Venting of the still was done with nitrogen.

A more detailed description of this process is given by H.A. Joynt et al, BIOS Final Rept 1644 (1948), pp 5-10.

Supergas . See Hochdruckpumpe.

Synoxyd . See Sinoxydsätze.

SV-Stoff und Brennstoff. According to CIOS Rept 30-115 (1945), p 11, the 90/10 mixture of concentrated nitric-sulfuric acid (transported in tanks made of ordinary steel) was used in conjunction with a combustible (Brennstoff), such as gasoline, in liquid rocket propellants. The above acid mixture was known as SV-Stoff. The same name was applied to the straight concentrated nitric acid (such as 98-100%) when used in rockets. This acid was also known as Salbei.

Synthetic Resins and Emulsions used in Germany during WW II for the manufacture of items employed in ammunition, are briefly described in BIOS Final Reports Nos 1715, 1794 and 1795 (1947).

Tallfun. An experimental biliquid rocket designed to be fired in groups of 65 from a launching machine known as the Dobgerät. The missile was about 2.1 m long and 10 cm in diameter, provided with a warhead containing 500 g of HE. It was propelled by a liquid fuel (Visol) and a liquid oxidizer (concentrated nitric acid).

References:

- 1) CIOS Rept 28-56 (1946), pp 24-28
- 2) TM 9-1985-2 (1953), p 223.

Tapered Bore Gun (Wärgebohrung Geschütz), called also Gerlich Type Gun, Squeeze-Bore or Reducing Bore Gun was developed in Germany in the early stages of WW II. Its barrel consisted of 3 sections (starting from the breech):

- a) Cylindrical section, such as 42 mm bore diameter
- b) Slightly conical middle section and
- c) Cylindrical section, such as 28 mm bore diameter.

There were also guns with diameters 28 mm or 75 mm for (a) section and 20 mm or 55 mm for (c) section.

Because of this construction, the projectile which

had a spoon-like body, was squeezed to a smaller diameter as it passed from the breech to the muzzle. The idea of this gun was to present a large-cross-sectional area of the projectile to the propellant gases, and to present a small cross-sectional area to the atmosphere in order to reduce air resistance and thus increase the muzzle velocity of the projectile. It was claimed that the most valuable advantage of this type of gun was the possibility of reducing the total length of a bore almost to one-half without any changes in maximum pressure and muzzle velocity and preserving almost the same weight of projectile.

Although this weapon was light and gave comparatively good armor-penetration it was given up for the following reasons:

- a) Its manufacture was very difficult
- b) It wore out too rapidly
- c) Its effective range was rather short.

Some of the tapered-bore guns and their projectiles are on display at the Aberdeen Proving Ground Museum, Maryland.

A short description of such guns is given by:

L.E. Simon German Research in World War II, J. Wiley, N Y (1947), p 189.


Note: According to E. Englesburg, The Ordnance Sergeant, May 1944, p 312, the inventor of this gun and its projectile was an American born German engineer, H. Gerlich, residing in Kiel. He worked on the development of high velocity weapons and projectiles from about 1920, and in 1932 he demonstrated at Aberdeen Proving Ground, Md a rifle firing a missile with a velocity of about 4445 ft/sec. The rifle was not accepted. After this Gerlich worked for the Germans. The first known combat use of the Gerlich principle was made in the Lybian campaign. The weapon employed in Lybia was the 2.8/2.0 Pak, a light antitank gun mounted on a two-wheeled carriage. In this gun the first 18" of the barrel, beginning from the breech, were of caliber 28 mm, the next 9" of the barrel had a rapid taper of .022" per 1" and in the last 23" of the barrel, the taper decreased to .002"/1". The projectile had no rotating band or bourrelet, but instead had two skirt-like flanges extending away from the body. During the flight of the shell through the tapered bore, the skirts collapsed and a nearly smooth shell of about 20 mm caliber emerged from the muzzle of the gun. It was claimed that muzzle velocities up to 6000 ft/sec could be achieved and that armor penetration at 100 yds was 70 mm for hard steel and 76 mm (3") for machineable plates.

Note: According to TM 9-1985-3 (1955), p 360, the Squeeze-Bore Gun consisted of an ordinary rifled gun to the muzzle of which was attached a smooth-bore tapered extension. This means that there was a difference between the Squeeze-Bore Gun and the Tapered Bore Gun. The projectiles were interchangeable in both cases. The guns and projectiles called "Squeeze-Bore" by the Americans were called "Little John" by the British.


Tapered Bore Gun Projectile or Gerlich Projectile. According to E. Englesburg, Ordnance Sergeant, May 1944, pp 319-13 the typical Gerlich projectile such as the Armor-Piercing Projectile Type 41 (Pg 41) used in the 2.8/2.0 mm Antitank Gun (2.8/2.0 cm Pak) consisted of the following parts:

- a) A tungsten carbide core which had a diameter about half the caliber of the gun at the muzzle and served for the actual penetration into the armor
- b) A thin lead sleeve which covered the core and held it in place. The sleeve served as a lubricant for the core when the skirts were separating from it on impact
- c) A magnesium alloy ballistic cap which fitted snugly into the forward skirt and served as the nose of the projectile. On impact the Mg alloy produced a flash which permitted observation of the firing


Note: The Mg cap was not used in all tapered bore projectiles, as can be seen from the drawing of PzgrPatr 41. In this projectile the cap is of aluminum and the tracer composition, fitted into the base of projectile, permitted observation of the firing.



Pzgr 41
für 2.8/2.0 Pak



Pzgr Patr 41
(4.2/2.8 cm)



Sprgr 41

d) A forward skirt, which was made of a soft iron or gilding metal and served as the bourrelet of conventional projectiles. The skirt extended as far back as the base of the core and was provided with 5 or more equidistant holes. These perforations were intended to decrease the mass of the skirt and to allow air to escape as the skirt was squeezed back and down into the recess in the projectile casing while travelling through the barrel of the gun. As a result of this squeezing the diameter of projectile decreased.

Note: In contrast to the Disintegrating Rotating Band Projectiles and to some Sabot Projectiles, the bands (skirt) of the Gerlich projectile did not break nor detach. They simply squeezed to the diameter of the muzzle.

e) A rear skirt, which was made of a soft iron or gilding metal (which served as the driving band of conventional projectiles) extended away from the body and was squeezed down and back in travelling through the barrel.

Note: The penetration of the 2.8/2.0 cm Pzgr into armor plate was about 3" at a range of about 100 yards and a muzzle velocity of 4600 ft/sec. For the 4.2/2.8 cm Pzgr the penetration was 4.52" at 200 yd and a muzzle vel of 4600 ft/sec, and for the 7.5/5.5 cm Pzgr the corresponding values were 6.67", 500 yd and 3936 ft/sec. In all cases the guns were antitank, such as 2.8/2.0 Pak, 4.2/2.8 Pak.

Somewhat different was the construction of the High Explosive Projectile, such as the Sprgr 41. The forward part of this shell was flat and there was no ballistic cap. In place of the tungsten carbide core of Pzgr 41, the interior of Sprgr 41 was filled with a HE (such as Cyclonite) which was provided with a point detonating fuze. The forward and rear skirts were similar to those of the Pzgr 41 and served the same purpose. The fuze of the Sprgr 41 was bore-safe and before firing a single coil spring kept two half-collars squeezed against the firing pin, thus preventing it from being depressed. In flight, the centrifugal force created by the rotation of the projectile forced the two half-collars apart, and the firing pin was then free to move toward the detonator on impact. The Sprgr 41 was used against personnel and light material targets.

Note: The above described Armor-Piercing projectiles had arrowhead design heads and for this reason can be classified as Arrowhead (Needle Point) Projectiles (qv).

The advantages and disadvantages of the tapered-bore gun and its projectile are listed above under Tapered Bore Gun.

The projectiles used in tapered bore guns are also described in the following References:

- 1) R.M.Dennis, Pic Arsn Tech Rept 1326 (1944) (42/28 mm AP/IV)
- 2) A.B.Schilling, Ibid, 1578 (1945) (75/55 mm HE Shell for Tapered Bore Gun, Pak 41)
- 3) A.B.Schilling, Ibid, 1579 (1945) (75/55 mm AP Shell for Tapered Bore Gun, Pak 41)
- 4) Dept of the Army Tech Manual, TM 9-1985-3 (1953), pp 371-372: 28/20 mm HE, 28/20 mm, 42-28 mm HE and 42/28 mm AP projectiles.

Torbur. See under Trilons.

Target Indicating Flare, Mark 50 Kaskade, and Target Indicator (Red) are described in TM 9-1985-2 (1953), pp 71-3 84-5 (See also under Flare and under Marker).

Teilladung (increment). See under Cordite Charge Casing.

Television Guidance System for Missiles. See under Guidance Systems for Missiles.

Tellerapparate oder Heizbare Mischmaschine (Plate Apparatus or Heatable Mixing Machine). An apparatus suitable for mixing solid and liquid ingredients of explosives, propellants and pyrotechnic compositions. It consisted of a large horizontal, cast iron, steam-jacketed, cylindrical pan on which the materials were placed. These were crushed and mixed by the combined action of a long, small diameter, horizontal roller (made from a non-sparking metal, such as Cu, brass, or Al) rotating around the center of the base at the rate of ca 3 rpm and a series of scrapers (made from non-sparking metal) following behind the roller. The scraped material was reground by the roller and then again rescraped and this action continued until all the ingredients were well mixed.

The apparatus was manuf before WW II by the Gebr Burberg, Mettmann, and could be operated either in the cold, or heated by steam.

Reference: Stettbacher, Schiess- und Sprengstoffe, Leipzig, (1933), pp 301-2.

Tellermine (Dish-like Land Mine). According to Simon (Ref 1) these mines gave the Allies considerable trouble throughout WW II. They were sufficiently powerful to put a tank out of action and to wreck almost any other vehicle. The first of such A/T mines, called Tellermine 35, was made of steel, while the models developed towards the end of WW II were made of non-magnetic materials to render mine detectors ineffective. Some of the latest mines were reported to be remote-controlled but it is not known whether they were actually used in combat.

The following models are described in Ref 2: Tellermine 35 A/T (p 267); Tellermine 35 (Steel) A/T, (p 268). Tellermine 42 A/T (p 269) and Tellermine 43, Pilsz, A/T (p 270) (Pilsz means mushroom).

Essentially the body of the mine was a circular, flat, dish-like form with a hole in the center of the cover. The body was loaded with 11-12 lb of compressed high explosive (such as TNT) and an igniter was screwed into the cover. A second (floating) cover was held down by a metal ring attached to the body and was supported in the center by a heavy spring. A pressure of 200-400 lbs on

the "floating" cover was sufficient to depress it as well as the igniter housing. The pressure of the housing on the top of the striker sheared the pin which held the striker in the cocked position, thus releasing the striker spring. As a result of this the striker set off the percussion cap, detonator, booster and the main charge such as of TNT.

References:

- 1) L.E.Simon, German Research in WW II, Wiley, NY (1947), p 188
 - 2) Anon, German Explosive Ordnance, Dept of the Army, Tech Manual TM 9-1985-2, Washington, DC (1953), pp 267-70.
- (See also under Landminen).



Testing Gallery (Schlugwetterversuchstrecke). See general section, under Galleries, Testing and also this section under Versuchsstrecke.

Teton oder X-Stoff (Tetranitromethane, abbreviated in this work as TeNM or TeNMe). A detailed description of the preparation, properties and uses of TeNMe is given in the general section under Methane. The following description concerns the German method of preparation and uses of TeNMe.

As the classical method of prepn of TeNMe from acetic anhydride and nitric acid (see general section) is very expensive, a new method was developed during WW II by Dr Schimmelschmidt (Refs 1 & 2). The laboratory scale procedure was as follows:

In an all-glass apparatus, schematically represented on the enclosed drawing, acetylene reacted with nitric acid to give nitroform and the mixture of nitroform and nitric acid yielded TeNMe on heating with sulfuric acid. The reaction was believed to proceed as follows:

Preparation of Tetra-nitromethane



$\text{CH}_3\text{CH} + 6\text{HNO}_3 = (\text{O}_2\text{N})_4\text{C} + 4\text{H}_2\text{O} + 2\text{NO}_2 + \text{CO}_2$

About 60% of acetylene reacted as above and about 40% underwent complete oxidation according to the equation: $\text{CH}_3\text{CH} + 10\text{HNO}_3 = 2\text{CO}_2 + 10\text{NO}_2 + 6\text{H}_2\text{O}$, so that the over-

The reaction could be represented by:

$$5(C_2H_2 + 3HNO_3 + 3(CO_2N)_4C + 2H_2O + 7CO_2 + 26NO_2$$

The recovery of nitrogen dioxide and of unconverted nitric acid was about 90% of theory.

In this procedure the acetylene gas, C_2H_2 , was introduced at the lowest point of the system at the rate of 93.5 liters per hour and the nitric acid (93%) containing mercuric nitrate as a catalyst, was fed at the rate of 2.4 liter per hour.

Note: The catalyst was prepared by dissolving 70 g of mercury in about 100 ml of 89% nitric acid, adding 200 ml of water and making up to 1 liter with 89% nitric acid. Twenty ml of this soln was added to every 10 liters of 98% nitric acid fed.

By circulating cold water through the cooling coil, located in the 2nd leg of the reaction system, a temperature of 50° was maintained. The solution of nitroform in nitric acid overflowed from the circulating system to three nitration vessels (3) placed in series, each nitrator being heated by a steam jacket. The sulfuric acid from the TeNMe purification tower (5) together with the nitroform mixture flowed into the 1st nitrator and the tetranitromethane and remaining acid overflowed from the 3rd nitrator. The temperature in each nitrator was maintained at 90° and the contact time of nitration was about 3 hours. Each nitrator was provided with a reflux condenser for returning TeNMe and HNO_3 as well as any condensable gases such as N_2O_4 .

The warm mixture leaving the 3rd nitrator quickly separated in (4) and the top layer of TeNMe was fed continuously to the purification tower (5). The feed of 95.5% sulfuric acid to the purification tower (5) was 1.7 l per hour and the run-off product was charged to the nitrators (3). Pure TeNMe left the top of the purification tower (5) at the rate of 440-460 g per hour and was collected in a tank (6).

The off-gases of the nitration system, such as N_2O_4 , CO_2 with small amounts of HNO_3 , $C(NO_2)_4$, $CH(NO_2)_3$ and possibly unreacted C_2H_2 , passed to the purification column (7) which was divided into 2 sections. In the lower section the last traces of C_2H_2 were removed by scrubbing with warm nitric acid (containing mercuric nitrate) fed at the rate of 2.4 l per hour. In the upper section of column (7) nitrogen dioxide and carbon dioxide were separated by distillation and the nitrogen oxide was condensed, in the pure form, by a mixture of solid CO_2 and acetone. The gases leaving the receiver were scrubbed in a smaller column (8) by cold nitric acid (to remove the last traces of nitrogen dioxide) and the nitric acid run-off was fed to column (7), whereas the CO_2 was allowed to escape.

The nitric acid (which contained sulfuric acid, nitrogen dioxide and tetranitromethane) was separated from sulfuric acid by distillation in column (9) and condensed in tank (11). The residue, consisting of 70% sulfuric acid, was concentrated to 95.5% strength in the Pauling column (11) and collected in tank (12).

Note: Although the attached diagram indicates a continuous system for the separation and concentration of mixed acid from the separated TeNMe, the process was actually conducted batchwise as sufficient material accumulated. TeNMe was proposed as a base for very powerful and brisant explosives, called in Germany Teton Sprengstoffe (qv), and also as an oxygen carrier in liquid rocket propellants to replace the corrosive strong nitric acid. Due to the fact that the freezing point of TeNMe is fairly high (about 14° C), it was proposed by Drs Schultheiss and Schinmelschmidt to mix 70 parts of TeNMe with 30 p of nitrogen tetroxide. This mixture had a freezing point of -27° and was non-corrosive, provided no moisture was present. It was proposed to use this mixture in V-2 rockets (Ref 2).

References:

- 1) R.E. Richardson et al, CIOS Report 25-18 (1945), pp 6-14
- 2) W. Hunter et al, BIOS Final Report 70 (1946), pp 1-6.

Teton Sprengstoffe (Tetranitromethane Explosives). It was mentioned under Ersatzsprengstoffe that, due to the acute shortage of TNT and of other high explosives, the Germans used during WW II, as ingredients of explosive mixtures,

substances which were not explosives. Among such substances was TeNMe (tetranitromethane), called in Germany Teton, a liquid waste product of the manufacture of TNT.

The first Teton mixture consisted of very finely pulverized aluminum (called Pyroschliff), impregnated with TeNMe, and a small amount of the following substances: a hydrocarbon rich in hydrogen and a consolidating compound called "K₃", which was a high dispersion of silica prepared by a special process. The hydrocarbon was added in order to increase the sensitivity to initiation. This Teton explosive was a solid possessing a very high blast effect and a comparatively low velocity of detonation. Explosives with such properties were found to be suitable for underwater explosions (Ref 1).

Other explosive mixtures consisted of Teton with liquid or pulverized carbon containing substances, such as hydrocarbons, coal, charcoal, nitrocompounds, etc. Some of these mixtures were more powerful and brisant than TNT, P A, PEIN or RDX, and were particularly suitable for underwater explosions.

Considerable work on this subject was done by Dr A. Stettbacher (See general section under Methane). One of the most powerful and brisant explosives known is a mixture of Teton with toluene. Its velocity of detonation is about 9300 m/sec.

There were also explosives prepared from derivatives of TeNMe, as for instance the perchloric ester of trinitroethanol. The trinitroethanol (mp 70°) was prepd by condensing nitroform (derived from TeNMe) with 40% solution of formaldehyde.

References:

- 1) G. Römer, PBL Report 85,160 (1945), pp 2-3
- 2) A. Stettbacher, Schiess- und Sprengstoffe, Leipzig, (1933), p 185 and Ibid, Spreng- und Schiessstoffe, Zürich (1948), pp 10, 16 & 148.

Tetrocene (Tetrazen) was prepd in Germany utilizing the same equipment as used for prepn of L A and L St.

The procedure was as follows:

- To a solution containing 4.0 kg of Na nitrite and 1.5 liters of normal acetic acid in 60 liters of water preheated to 50°, was added gradually and with air-agitation 40 liters of an aqueous solution of 5.3 kg of aminoguanidine sulfate. The addition took one hour
- After stirring the mixture for an additional hour at 50° and for 1 hour at 20°, the reactor was tipped and the contents caught on a filter cloth made of horse hair
- After washing the ppt with several portions of water, it was dried in the same manner as described under lead azide. This gave about 3.0 kg of dry tetrocene
- Boiling the mother liquor for several hours was sufficient to destroy any waste tetrocene remaining in it.

A similar method, used at the Fabrik Wolfratshausen Chemische Erzeugnisse and at the Stadeln Fabrik, Dynamit A-G, is described by Sheldon (Ref 3). In this description the following details of the method which are worthy of mention are given:

- A solution of aminoguanidine sulfate (5 kg per 40 l of water) was neutralized (to the litmus paper end point) with either acetic or nitric acid and then added to a preheated solution of Na nitrite (2.5 kg per 50 l of water). If the addition rate was rapid, small, slow settling crystals of Tetrocene were produced and if the addition rate was slow (2 hours), larger and faster settling crystals resulted. The detailed procedure was as follows: A temperature of 50 to 55° was maintained throughout the entire reaction period which was allowed to proceed 30 minutes after the last of the aminoguanidine sulfate solution had been added to the reactor. Then the agitator was stopped, the product allowed to settle and the mother liquor removed

by decantation.

C. After the decantation of the mother liquor, one dilution was given and then the precipitate was washed from the tilted reactor onto a large cloth supported on a natural drainage filter (as for lead azide). After three additional displacement washes, the cloth was folded over the tetracene and the ensemble placed in a plastic bucket to be transferred to the storage area.

D. For Tetracene, which had to be dried prior to use, the washing on the cloth was followed by washing with some 96% ethyl alcohol containing some methyl alcohol. After dehydrating with alcohol, the cloth was folded over the material which was then placed in a plastic bucket and transferred to the storage area.

E. The yield of Tetracene when using 4.0 kg of aminoguanidine sulfate was 2.6 to 2.7 kg.

The following priming mixtures containing Tetracene are listed in Ref 3:

- I. Priming Mixture No 50/40, used for rifle and pistol cartridges: Tetracene 3, Pb styphnate 40, Ba nitrate 42, Ca silicide 10 and Pb dioxide 5%.
- II. Duplex Cup Mixture for use in 20 mm and 37 mm, as well as in some larger shells, consisted of 0.30 g of Pb azide 92.5 and Tetracene 7.5% pressed at 100 kg/cm² over 0.05 g of unwaxed PETN pressed at 500 kg/cm².
- III. Priming Mixtures used for pistol and rifle cartridges: Tetracene 2-3, Pb azide 30-35, Ba nitrate 40-45, Ca silicide 6-12, Pb peroxide 5-8 and Sb sulfide 6-9%.

Tetracene was used in initiating mixtures called *Sin-oxydätze*.

(See also Tetracene in the general section).

Reference:

- 1) PB Rept 95,613 (1947), Section R
- 2) A. Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), pp 98 and 107
- 3) L.M. Sheldon, CIOS Report 27-38 (1945), pp 9, 11 & 13-14.

Tetra-Di-Salz (Tetra-Di-Salt), described in the general section as Tetramethylammonium Dinitrate, was prepared in Germany by dissolving the Tetra-Salz (see below) in hot 60% nitric acid and allowing the solution to cool. The crystals obtained by filtering were dried in a vacuum. The salt was stable at temperatures up to 100°. Its mixtures with ammonium nitrate and a small amount of RDX were found to be suitable for filling projectiles.

(See also general section).

Reference:

- PB Rept 78,271 (1947), p 22.

Tetrahydrofuran (Tetrahydrofurane) is described in the general section. Tetrahydrofurane and its intermediates were produced during WW II by the IG Farbenindustrie at Ludwigshafen.

Reference: CIOS Report 29-12 (1946).

Tetramethylammonium Dinitrate - Same as Tetra-Di-Salz.

Tetramethylammonium Nitrate - Same as Tetra-Salz.

Tetramethylnitraminotetramethylmethane. See in the general section under T. This compound was suggested as an ingredient of explosives containing R-Salz but was not found as satisfactory as dimethylethylene-dinitramine. Reference: G.Römer, PBL Rept 85,160 (1946), p 16.

2,4,6,8-Tetranitramino-1,3,5,7,9-pentamethylene-1,9-dinitrate (O₂NO)CH₂·N(NO₂)·CH₂·N(NO₂)·CH₂·N(NO₂)·CH₂·N(NO₂)·CH₂·N(NO₂)·CH₂(ONO₂), crystals, m p 211°. Was obtained during WW II as a by-product of manufacture of RDX using either the E-Salz or K-Salz process. Both of these processes are

described in this German section under Hexogen. The power of tetranitraminopentamethylene dinitrate, as judged by the Trauzl Test, was claimed to be higher than for RDX.

Reference: G.Römer, PBL Rept 85,160 (1946), p 16.

Tetranitrocarbazol oder Gelbmehl (Tetranitrocarbazole or Yellow Flour, abbreviated in this work as TeNCbz). Its preparation, properties and uses are described in the general section under Carbazole.

TeNCbz was proposed during WW II in Germany as a substitute for black powder in illuminating flares of the rocket type (Ref 1). Due to the fact that TeNCbz was non-hygroscopic and non-corrosive it was expected to completely replace the black powder in igniter compositions. (Ref 2).

According to Ref 2, the Germans, prior to 1945, used black powder as the main ingredient of their pyrotechnic "intermediate" igniter compositions and it was observed that their storage in contact with magnesium, containing flare or star compositions (such as Mg 20, Ba nitrate 57 and chlorinated polyvinyl chloride 23%) resulted in deterioration of the pyrotechnic devices. This was caused by the interaction between the sulfur (of black powder), magnesium (of the flare or star) and moisture (of atmosphere), giving hydrogen sulfide and magnesium oxide. On further storage, the hydrogen sulfide attacked the lead salts (such as Pb azide or Pb styphnate) of the primer thus rendering them unserviceable.

To avoid the destruction in storage of pyrotechnic devices containing magnesium, it was proposed, in 1945, to replace the black powder type "intermediate" composition by the following mixture: TeNCbz 30, K nitrate 40 and Al powder 30%.

References:

- 1) R.E. Richardson, CIOS Rept 25-18 (1945), pp 27-8
- 2) H.J. Eppig, CIOS Rept 42-56 (1945), pp 14-15.

Tetranitromethane (TeNMe). See Tetan oder X-Stoff.

Tetranitrodiphenylaminsulfon oder Gelbmehl S (Tetranitrodiphenylamine-sulfone Yellow Flour S). See general section under Diphenylamine. It was proposed, during WW II in Germany, as a substitute for black powder (See also GP Powder and Tetranitrocarbazol).

Reference: CIOS Rept 25-18 (1945), pp 27-28.

Tetra-Salz (Tetra-Salt) is described in the general section under Tetramethylammonium Nitrate. This substance is not an explosive by itself, but it forms powerful explosive compositions when mixed with oxidizing agents such as nitrates. It was prep'd in Germany in the pure state by the interaction of methyl nitrate with trimethylamine. The mixtures of Tetra-Salt with nitrates were found to be suitable for filling projectiles and for making propellants for cannon, as well as for rockets.

References:

- 1) PB Rept 85,160 (1946)
- 2) PB Rept 78,271 (1947).

Tetra-Salz-Perchlorat (Tetra-Salt-Perchlorate). This compound practically insoluble in water, was obtained by treating TETRA-Salz with perchloric acid. When ignited the substance burned with a small bluish-white, sparkling flame. This behavior suggests that it might be useful in pyrotechnic compositions.

Reference: PB Rept 78,271 (1947), p 21.

Tetryl (2,4,6-Trinitrophenylmethylnitramine) is described in the general section. Used by the Germans during WW II as a sub-booster in some projectiles and as a bursting charge in some land mines.

Following is a brief description of the semi-continuous method of manufacture as used at the Troisdorf Fabrik, D A-G. The installation consisted of two stainless steel nitrators, several stabilizers and one crystallizer.

a) After adding 60 liters of mixed nitric-sulfuric acid to the first vessel and starting the agitation, the situation was conducted by continuously adding equal volumes of a sulfuric acid solution of dinitromethylaniline and mixed acid, as above. The temperature was maintained at 40°C.

b) The slurry of tetryl and acid was run continuously into the 2nd vessel where the temperature was maintained at 25°C.

c) The contents of the 2nd vessel were run continuously through a stainless steel sieve where crude tetryl separated from the spent acid.

d) By means of a large amount of water, the crude tetryl was transferred to a series of stabilizers where it was washed, first with water, then with a dilute soda ash solution and again with water.

e) The moist tetryl was recrystallized from acetone by a special process (very vaguely described) and then dried and screened.

According to BROS Final Rept 644 (1945) Tetryl was also used in Eschbach Gasless Electric Delay Detonators manu'd at the Troisdorf Fabrik, D A -G.

References:

- 1) PB Rept 95,613 (1947), Section S
- 2) Stettbacher Spreng- und Schiesstoffe (1948), pp 77-78.

"Thor" and "Kor" Mortars were actually heavy, short barrel howitzers, designed by Krupp Co for the destruction of very strong fortifications. In some ways these weapons resembled the Big Bertha (420 mm = 16.5") gun used during WW I. The Thor and Karl weapons were furnished in two calibers, 540 mm and 610 mm. The 610 mm barrel was 8 calibers long and fired a 4400 lb shell to a distance of nearly 4 miles. In order to increase the range, the cradle was modified to take a smaller tube. This gave a 540 mm weapon which fired a 3310 lb shell to a distance of about 7 1/2 miles. To increase the mobility of each weapon, it was mounted on a modified PzKpfw IV chassis (See also under Panzer).

Reference: G.B. Jarrett, "Achtung Panzer", The Story of German Tanks in WW II, Great Oaks, RD 1, Aberdeen, Md (1948)

Note: According to the "Enemy War Materials Inventory List", Supreme Headquarters Allied Expeditionary Force, April 1945, p 133, the weapon designated Karl Mrs or Karl Gerät was made in two sizes 54 and 61.5 cm.

Thunderite (Thunderite). A permissible explosive manufactured at the beginning of this century at the Schleich Fabrik D A -G and introduced into England under the name of **Coolite**. It consisted of Am nitrate 91-93, TNT 3-5, flour 3-5 and moisture 0.5%.

Reference:

J. Daniel, Dictionnaire des Matières Explosives, Dunod, Paris (1902), p 767.

Tiefbinder Verfahren (Deep Bonding Process). This term designated a method of deep surface treatment of sintered metal projectiles developed by Dr V. Duffek and collaborators. The method was claimed to diminish the wear of gun barrels and to increase the effectiveness of armor penetration of these projectiles.

Previous to WW II, the Germans, in some of their rapid-firing guns, used projectiles containing either a lead core or a lead head with a sheath made of cast iron plated with tombak metal (an alloy of Cu and Zn). Beginning about January 1941, when a shortage of lead developed, the Germans tried to use projectiles made entirely of sintered iron. However, the use of these projectiles was not a success because the wear of the bore was so great

that after about 400 rounds the gun became unusable. In order to decrease the friction, an attempt was made to zincate the sintered iron projectiles, but this method did not decrease friction sufficiently to effect a noticeable decrease in the wear of the bore.

Knowing that some crystalline inorganic compounds possess the property of showing decreased friction when subjected to high temperatures, high pressures, or to a certain extent to impact stresses, Dr Duffek proposed to cover the sintered metal projectiles with such substances. The surface covering was achieved by the phosphatizing process (used in industry to reduce corrosion), which consisted essentially of a treatment of an iron object with an acidic phosphate solution (Parkerizing). As result of this, a thin layer of crystalline iron phosphate was deposited on the surface of the metal.

Although this method of phosphatizing decreased the friction of projectiles in the bore, the amount of phosphate deposited on the surface was so slight as to be removed by passage of the projectile through the bore. This meant that if the method were to be used for armor-piercing projectiles there would not be enough low-friction surface material left to improve the penetration of armor.

The investigation of Dr Duffek was continued and on the strength of his suggestions a process was developed by the Metallgesellschaft A -G, Frankfurt a/M (Dr L. Schuster) (Ref 2) which permitted deposition of thicker surface layers of phosphate crystals due to deeper penetration of the phosphate solutions into sintered iron objects.

This process, called **Tiefbinder-Verfahren** (Deep Bonding Process), may be conducted by one of three methods described in the patent. The following method was recommended by Dr Duffek:

a) Treat the sintered iron article with vapors of trichloroethylene in order to remove any oil or fat from the pores

b) Transfer the article to a bath containing 8 g of NaOH and 2 g NaNO₂ per liter and maintained at 95°C

c) After remaining there for exactly one minute, remove the article and, without rinsing, place it in a bath consisting of solutions of Zn phosphate and nitrate (containing 5.4 g Zn, 7 g P₂O₅ and 6.9 g NO₃ per liter). The bath is maintained at 25-95°C

d) After keeping in the bath for 5 minutes, remove the article and rinse it thoroughly under cold water

e) Treat the article for one minute at 95°C in a bath containing 5 g of a mixture consisting of 30% Na silicate, 45% NaNO₂ and 25% NaOH per liter. Then place it for 40-60 seconds in a bath containing a solution of 0.5 g Na chromate per liter of water and maintained at 95°C

f) Remove the article and dry it.

It was claimed by Dr Duffek that when sintered iron bullets treated by this method were fired from a pistol (in 1942) there was no noticeable wear of the bore even after 4600 rounds. This was considerably better than with the pre-WW II bullets with a lead core.

On the strength of this success, Dr Duffek was allowed by the German War Ministry (near the end of WW II) to develop a new type of AP (armor-piercing) projectile. After prolonged investigations, the following method was developed:

A sintered iron sheath, consisting of fine grains of iron on the inside layers and coarse grains on the outside sheath, was welded to the surface of an ordinary solid steel projectile. The welding was done by the high-frequency method (Hochfrequenz) developed by the Siemens Co. Then the surface of the shell was

treated by the Deep Bonding Process, as described above.

About 50 projectiles caliber 20 mm, and some 37 mm, were prepared by this method and then tested by firing against a 5 cm thick chromium-nickel steel armor plate placed at a distance of 700 meters. The results showed that the average penetration was about 2/3rd deeper than with an untreated standard AP shell.

References:

- 1) Dr V. Duffek, Report to the High Command of the German Forces (Document of the Chemisch-technische Reichsanstalt, Berlin) and private communication
- 2) Metallgesellschaft A-G, Frankfurt a/M, Ger Pat M 153085 VI/48d, Jan 26, 1942.

"Tiger" I, II, etc. Nicknames for a series of heavy tanks. (See under Panzer).

Tilt - Type Igniter (Kippzunder). See under Igniter.

Titanium Alloys and their methods of manufacture in Germany are described by L.S. Busch & R.H. Freyer, PB Rept 100,000 (1948-1949). Some of these alloys were used as components of ordnance items.

Titanium Tetrachloride (Titanchlorid), designated as FM, is described in the general section. It was used by the Germans as a smoke producing agent in some hand grenades. (See also under Smoke Hand Grenade).

T-Mine. See under Landminen.

TNT. See Trinitrotoluol (Trotly).

Toluol (Toluene) is described in the general section. The manufacture of toluene in Germany was discussed by W.F. Faragher and W.A. Horne, US Bur Mines Inform Circ 7376 (1946). The authors interrogated Dr Pier and the staff of IG Farbenindustrie, A G, Ludwigshafen and Oppau, C A 41, 5234 (1947).

Note: According to H. Walter et al, PB Rept 78,271 (1947), The Germans developed a method for the manufacture of toluene by the interaction of benzene and methanol in the presence of phosphoric acid. The method is not described.

The German nitration grade toluene obtained from the coal tar industry contained 0.7 - 0.8% paraffins, while synthetic toluene contained about 0.5%.

p-Toluolsulfamid (p-Toluenesulfamide). See Plastol. It was found to be a suitable plasticizer for collodion cotton.

p-Toluolsulfonsureethylester (p-Tolueneulfonic Acid Ethyl Ester). See Mittel AEP.

Tonko. A liquid rocket fuel developed in Germany during WW II. It was a mixture of aniline, monoethylaniline, dimethylaniline, gasoline, naphtha, triethylamine, and isohexylamine and was used in conjunction with nitric acid to propel the air-to-air guided missile called Ruhrstahl X-4 (Refs 1 & 2).

According to Ref 3, the so-called Tonko 250 consisted of crude m-xylidine 57 and triethylamine 43%. It was used in conjunction with strong (98-100%) nitric acid (Salbei) serving as a source of oxygen.

References:

- 1) H. Gattmann, Weltraumfahrt No 6, p 134 (1931), Jato and Auxiliary Rocket Power Plants, C A 46, 4233 (1932)
- 2) K.W. Gatland, Development of the Guided Missile,

Philosophical Library, N Y (1952), p 123

3) TM 9-1985-2 (1953), p 216.

Topfmine A (Pot-Shaped A/T Land mine). It is described on p 271 of TM 9-1985-2 (1953). See also under Landminen.

Topf Zunder. Pressure type igniter designed for use with the Topfmine, TM 9-1985-2 (1953), p 306 j.

Torpedo, Ein Man (One Man Torpedo). See U-Boat, One Man.

Totalit (Totalite). Totalites are military explosives consisting of ammonium nitrate blended with paraffin. These mixtures were the most inert and the least sensitive of all the military explosives used. Instead of paraffin, waste oils or naphthalene were tried. Stettbacher tried to use Totalit in conjunction with thermite priming (Thermitzudung) but could not get good results. This was due to the fact that only at lower densities, such as 1.25, did the Totalit detonate completely, while at higher ones, such as 1.5 or 1.6, the detonation was not complete.

Stettbacher (Ref 1) gives the following properties for the Totalit containing 5.47% of paraffin:

vol of gases at NTP 971.5 l/kg, heat of explosion at C_v water vapor 1162 kcal/kg and with water liquid 1438 kcal/kg, temp of explosion 3105^o, specific pressure (f) 12,021, brisance value (B) by Kast 49.7 x 10⁶, veloc of deton 2500 m/sec at d 1.60.

Note: Definitions of values (B) and (f) are given in the general section.

References:

- 1) A. Stettbacher, Nitrocellulose 10, 109-10 (1939)
- 2) A. Stettbacher, Spreng- und Schiesstoffe (1948), p 106.

Tot-Kuhlung (Dead-Cooling). See general section.

Tot-pressung (Dead-Pressing). See general section.

Totungskoeffizient (Killing or Destruction Coefficient). It is the ability of a unit weight of an explosive to inflict casualties or to cause destruction as compared with a unit weight of a standard explosive, such as TNT (A. Stettbacher, Spreng- und Schiesstoffe (1948), p 155 j).

Tracer Compositions (Leuchtpursatze oder Lichtpursatze). Compositions used by the Germans during WW I were described by Langhans (Ref 1), while some of those used during WW II were described in the book in Italian by Izzo (Ref 5) and in some Picatinny Arsenal Technical Reports (Refs 2, 3). PB Report 11 544, listed as Ref 4, is the condensation of some Picatinny Arsenal Reports. The following German compositions, used in tracer ammunition, are described in the book of Izzo:

- a) Ignition mixture: Zr 13, K nitrate 12 and black powder 75%
- b) Intermediate mixture: Al 15.1, Ba nitrate 29.5, K nitrate 12.0, sulfur 6.0 and black powder 37.4%
- c) Illuminating mixture (tracer): Mg 40.5, Na nitrate 54.5 and wax (synthetic, type L) 5.0%
- d) Ignition mixture: Zr 52 and K nitrate 48%
- e) Intermediate mixture: Ba peroxide 80 and Al 20%
- f) Illuminating mixture (tracer): Ba nitrate 74 and Al 26%

The following tracer and tracer igniter compositions, manufactured by the Deutsche Waffen- und Munitionsfabriken A-G, Lub:ck, are described by H. Peplow et al (Ref 6):

- a) Day tracer for the 7.92 mm bullet SmKL: Mg powder 32.5, Ba nitrate 45.5, Na carbonate (anhydrous) 12.0

Table 61 (Tracers and Igniters for Tracers)

| Item | Composition % | | | | | | | | | | | Used in | | | | |
|---------------|---------------|-----------------|----------------|------------------|-------------------|-----------------|----------------|-------------------|----------------|---------------------------|--------------|---------|------------|---|---------------------|----------------------------|
| | Magnesium | Barium peroxide | Barium nitrate | Barium carbonate | Potassium nitrate | Sodium pictrate | Sodium oxalate | Potassium nitrate | Phenolic resin | Phenol-formaldehyde resin | Diethyl fuel | | Resin | Nitro-cellulose | Other ingredients | |
| Dark ignition | 2.7 | 0.8 | - | - | 50.0 | - | - | - | - | 10.6 | - | - | - | Sulfur Carbon Sb sulfide | 6.1 15.9 13.9 | 7.92 mm APHV |
| Primer | 30.0 | 39.6 | - | - | - | 14.2 | 6.8 | - | - | 9.4 | - | - | - | - | - | Same as above |
| Tracer | 30.9 | - | 29.5 | - | 10.3 | - | 12.6 | - | - | 12.4 | - | - | - | Unac | 4.3 | Same as above |
| Igniter pad | - | - | - | - | - | - | - | - | - | - | - | - | 100% (col) | - | - | 7.92/1.3 mm |
| Igniter | 36.0 | - | 19.2 | - | - | - | - | - | - | - | 18.8 | - | - | Styphnic acid and binder | 26.0 | Same as above |
| Tracer | 35.9 | - | 36.9 | - | 15.2 | - | - | - | - | - | 10.5 | - | - | Sulfur | 1.5 | Same as above |
| Igniter | 24.1 | 73.6 | - | - | - | - | - | - | - | 2.3 | - | - | - | - | - | 20 mm AP (Inert charge) |
| Tracer | 40.9 | - | 28.0 | - | - | - | - | - | - | 14.9 | - | - | 100% (col) | Ba oxalate | 16.2 | Same as above |
| Igniter pad | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 20 mm APHV |
| Igniter | 36.7 | - | 32.7 | - | - | - | - | - | - | 18.7 | - | - | - | Na pictrate | 11.9 | Same as above |
| Tracer | 33.2 | - | - | - | 39.7 | - | 17.0 | - | - | 10.1* | - | - | - | - | - | Same as above |
| Igniter | 19.1 | 78.4 | - | - | - | - | - | - | - | 2.5 | - | - | - | Aluminum | 8.2 | Same as above |
| Tracer | 18.2 | - | 51.4 | 14.6 | - | - | - | - | - | - | 22.2 | - | - | - | - | 20 mm Inc |
| Igniter | 22.8 | 62.6 | - | - | - | - | - | 10.1 | - | 8.2 | - | - | - | Ba oxalate | 29.7 | Same as above |
| Tracer | 33.9 | - | 18.1 | - | - | - | - | - | - | 3.0 | - | - | - | - | - | 37 mm APHV |
| Igniter | 22.0 | - | 75.0 | - | - | - | - | - | - | - | - | - | - | - | - | Same as above |
| Tracer | 28.5 | - | 50.0 | - | - | - | 11.2 | - | - | - | - | - | - | - | - | Same as above |
| Igniter pad | - | - | - | - | - | - | - | - | - | - | - | - | 75.0 | DEGDN | 25.0 | 37 mm HE |
| Igniter | 30.0 | - | 36.0 | - | - | - | - | - | - | - | 23.0 | - | - | - | - | Same as above |
| Tracer | 43.1 | - | 40.9 | - | - | - | 12.0 | - | - | - | - | - | - | Sulfur Unac | 2.2 1.8 | Same as above |
| Igniter | 27.0 | - | 42.0 | - | 3.0 | - | 12.0 | - | 28.0 | - | - | - | - | Mg hydroxide Wax Unac | 6.0 2.0 1.0 | 37 mm HE Same as above |
| Tracer | 32.0 | - | 36.0 | 11.0 | - | - | - | - | - | - | - | - | 100% (col) | - | - | 37 mm HE |
| Igniter pad | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | Same as above |
| Igniter | 30.0 | - | 36.0 | - | 11.0 | - | 12.0 | - | - | - | 23.0 | - | - | Sulfur Unac | 2.2 1.8 | Same as above |
| Tracer | 43.1 | - | 40.9 | - | - | - | - | - | - | - | - | - | - | Red lead (Pb ₃ O ₄) | 13.8 | 37 mm APMB & APRN |
| Igniter | 16.6 | 66.1 | - | - | - | - | - | - | - | - | 3.5 | - | - | - | - | Same as above |
| Tracer | 34.0 | - | 60.0 | - | - | - | - | - | - | 6.0* | - | - | - | - | - | Same as above |

and Ersatz resin (phenolformaldehyde base) 10.0%.
 Note: The trace was yellow. For a white trace the Na carbonate was omitted and the amount of Ba nitrate correspondingly increased. The tracing length was 900 meters.

b) Tracer priming composition for the above bullet:
 Ba nitrate 64.5, Sr peroxide 5.5, red lead 10.8, Mg powder 15.5 and shellac 4.0%

i) Night tracer for the above bullet: Ba peroxide 53.0, Ba sulfate 22.0, Sr peroxide 7.5, K nitrate 7.5 and Ersatz resin 10.0%

Note: The Ba sulfate was used to keep the temperature down. The tracing length was 600 meters.

j) Tracer priming composition for the above bullet:
 Ba peroxide 81.0, Sr peroxide 3.0, Sr oxalate 3.0, Ca silicide 9.0 and Ersatz resin 4.0%

k) Red tracer for SmKL bullet: Sr nitrate 42.5, Sr peroxide 17.5, Mg 27.0, Fe lactate 3.8 and pine resin 9.2%

Note: The weight of the tracer was 0.3 g and the tracing length 500 yds.

l) Green tracer for the above bullet: Mg 25.0, Ba nitrate 65.0 and shellac or pine resin 10.0%

Note: The weight of the tracer was 0.22 g and the tracing length 500 yds.

m) Red tracer for 20 mm AA guns: Sr nitrate 57, Mg 19, Na carbonate (anhydrous) 8, Sr fluoride 5, Mg stearate 1 and phenol formaldehyde 10%

n) Yellow tracer for 20 mm AC guns: Ba nitrate 57, Mg 19, Na carbonate (anhydrous) 8, Sr fluoride 5, Mg stearate 1 and phenol formaldehyde 10%

o) Yellow tracer for 20 mm AP ammunition: dextrine 6.5, phenol formaldehyde 10.0, polyvinyl chloride 1.0, Ba nitrate 53.0, Mg 24.5 and Sr fluoride 5.0%

p) Red tracer for 20 mm AP ammunition: Sr nitrate 53.0, Mg 24.5, Sr fluoride 5.0, dextrine 6.5, phenol formaldehyde 10.0 and polyvinyl chloride 1.0%

r) Night tracer for 20 mm ammunition: Ba peroxide 53.0, Ba sulfate 22.0, Sr peroxide 7.5, K nitrate 7.5 and phenol formaldehyde 10.0%. Used without priming.

Note: Could be used in 7.92 mm ammunition in conjunction with dim priming composition described below:

s) Dim priming composition contained: Ba peroxide 81, Sr peroxide 3, Sr oxalate 3, Mg (fine powder) 9 and phenol formaldehyde 4%

t) Bright priming composition: Ba peroxide 63.82, Sr peroxide 5.32, lead oxide (Pb_3O_4) 10.62, Mg (powder) 15.98 and shellac 4.26%

u) Dark ignition priming: Ba peroxide 81, Sr peroxide 3, Sr oxalate 3, Ca silicide 9 and phenol formaldehyde 4%

Table 61 gives the composition of tracers and their igniters as determined during WW II at Picatinny Arsenal. (See following pages).

References: See under Table 61.

Tracer Projectiles. Many German projectiles were provided with tracers. Following are some tracer projectiles described in Refs 1 & 2:

- a) 20 mm Incendiary - Tracer, Proj (Ref 1, p 64)
- b) 20 mm Incendiary - Tracer, Self-Destroying Proj; (Ref 1, p 56) (See illustration under Self-Destroying Proj)
- c) 20 mm APHE - Tracer, Self-Destroying Proj (Ref 1, p 59) (See illustration under Self-Destroying Proj)
- d) 37 mm Projectiles: AP, Arrowhead with Tungsten Carbide Core, AP Without Cap for A/T and AA Guns. HE for A/T and C/30 Guns (Ref 2, pp 373, 382, 384, 387 and 388) (See illustration)
- e) 40 mm HE Proj for AA Gun (Ref 2, p 389)
- f) 42-28 mm AP Proj with Core, for Tapered-Bore Gun (Ref 2, p 375) (See illustration under Tapered Bore Gun)
- g) 47 mm AP, Arrowhead Proj with Tungsten Carbide Core (Ref 2, p 376)
- h) 50 mm and 75 mm Arrowhead Proj with Tungsten Carbide Core (Ref 2, pp 377-8) (See illustration under Arrowhead Projectile)
- i) 75 mm AP Projectiles (Ref 2, pp 408, 410, 423 & 424)
- j) 76.2 mm Russian Design Projectiles (Ref 2, pp 428, 429 & 431)



- k) 88 mm AP Projectiles (Ref 2, pp 43, 159-61, 144-3 & 146-8)
- l) 105 mm AP Projectiles (Ref 2, pp 156, 158-9 & 169) (See illustration)
- m) 128 mm AP Projectiles (Ref 2, pp 381-4)
- n) 150 mm HoC Proj for Howitzer (Ref 2, p 487)
- o) 194 mm French Design HE Proj for Railway Gun (Ref 2, p 517)
- p) 203 mm HE Proj for Railway Gun (Ref 2, p 521)
- r) 240 mm HE Proj for Theodor Bruno Railway Gun (Ref 2, p 524)
- s) 280 mm HE Proj for Railway Gun (Ref 2, p 528)
- t) 353 mm Anticoncrete Proj for Howitzer M1 (Ref 2, p 529).


(See also illustrations under Granate).

Abbreviations: AA Antiaircraft; AP Armor-Piercing; A/T Antitank; C Capped; HE High Explosive; HoC Hollow charge (shaped charge)

References:

- 1) H. Peploe et al, CIOS Rept 33-20 (1945)
- 2) Anon, TM 9-1985-3 (1953).





Trauzl Dynamite or Guncotton Dynamite. One of the earliest dynamites with an active base. It was prepared by Trauzl in 1867 by impregnating a mixture of guncotton 25 and charcoal 2 parts with nitroglycerin 73 p in the presence of 15 p added moisture. It was handled in the moist state, and in this condition it could be detonated with a strong blasting cap. It propagated detonation completely. A similar explosive called Glyoxilin was invented in 1867 by the British scientist F. Abel.

References:

- 1) J. Daniel, Dictionnaire des Matières Explosives, Dunod, Paris (1902), p 772
- 2) P. Naoum, Nitroglycerin, Williams and Wilkins, Baltimore (1928), p 282.

Trauzlsche Probe (Trauzl Test) oder Bleiblockausbauchungs Probe (Lead Block Expansion Test). See Trauzl Test in the general section.

Treibpulver oder Treibmittel. See Propellant.

Treibsätze (Propellant Substitutes). The following substances, described separately elsewhere, were developed as possible substitutes for black powder and smokeless propellants:

- a) Gelbmehl (Tetranitrocarbazole)
- b) Gelbmehl S (Tetranitrodiphenylsulfone)
- c) GP (Powder) and
- d) Trinitro - N - ethylaniline.

Reference: CIOS Report 25-18 (1945), pp 27-28.

Treibspiegelgeschoss. See Sabot Projectile.

Tremont II (Tremonte II). One of the permissible explosives used before and after WW I: dinitroglycerin 33, colloid cotton 1, meal 12, TNT 7.5, Am nitrate 26.5 and Na chloride 25.0%.

Reference: E. Barnett, Explosives, N Y, (1919), p 139.

Trench Mortar Bomb Explosive of WW I. According to Davis (1943) p 391, the following composition was used: NGu 50, Am nitrate 30 and paraffin 20%.

Tri. Abbreviation for Trinitrotoluene (TNT), also called Trotyl.

Triolen oder Tetranol. An underwater explosive consisting of RDX, TNT and Al powder. It was similar to Torpex described in the general section. At least four varieties of Triolens are known: Triolen 105, Triolen 106, Triolen 107, and Triolen 109 (See Filiz. 105, 106, 107 & 109). One of the Triolens was used for filling the V-2 rocket warheads. (See also under Unterwassersprengstoffe).

Tricinot oder Trizinot. See Bleitritroresorcinat.

Triethyleneglycoldinitrat. See Triglykoldinitrat.

Triglykoldinitrat (Triethyleneglycoldinitrat) (TEGDN). See also in the general section. It was proposed by General Gallwitz for use as a gelatinizer in cool double-base propellant (G-pulver) destined for tropical climates, such as Africa. Although TEGDN is much less volatile than DEGDN it is more volatile than NG (about 1.5 times). It has good chemical stability and is a good gelatinizer. Its calorific value Q is 750 kcal/kg, with H₂O liquid. It is obtained by the nitration of triethyleneglycol (TEG), a by-product of the manufacture of diethyleneglycol (DEG). The highest yield of TEG is below 20%, the rest being DEG. For safety reasons the spent acid must be drowned, which makes the process rather uneconomical.

Following is a brief description of the nitration as practiced at the Krümmel Fabrik, D A - G :

500 kg of tech TEG (which usually contained some DEG) was run slowly into mixed acid consisting of 70% nitric and 30% sulfuric acids, stirred and maintained at 25°C. After 30 minutes of nitration the mixture was drowned (see Note) in a large volume of cold water. The separated oil (TEGDN) was washed twice with cold water, once with dilute soda ash solution, and finally again with water. The yield was 650 kg, or 130% of TEG.

Note: As the mixture obtained on nitration of TEG is extremely unstable it was not allowed to stand to effect the separation of oil (TEGDN) from the spent acid, as is the general practice with other nitrated glycols, glycerin, etc. Another reason why the mixture was drowned is explained by the high solubility of TEGDN (8.9%) in undiluted spent acid and comparatively low solubility in an acid diluted by water.

Following were the properties of technical TEGDN: N=12.1 to 12.2%, vs theoretical 11.67% (see Note below). color-brownish, d=1.335, thermal stability-satisfactory (the 82° KI test gave 20 minutes), impact sensitivity-could not be exploded by the impact of 2 kg weight.


Note: The high N content of tech TEGDN may be due to the presence of as much as 21% of DEGDN.

Reference: O.W. Stickland, PB Rept 925 (1945), pp 13 & 60.

Trilons are extremely toxic products discovered before WW II in Switzerland and in Germany during research studies on insecticides derived from phosphoric acid. Dr Wirth of Berlin studied the toxic properties of these compounds with a view to their military application and recommended some of them to the German Government.

About two hundred toxic derivatives were prepared in the laboratories of IG Farbenindustrie at Ludwigshafen but only the following three were considered suitable for military applications.

a) Tabun (Trilon 83 or T 83, also called T 100) was the monoethyl ester of dimethylaminocyanophosphoric acid,




It was prepd by treating the

dichloride of dimethylaminophosphoric acid (an irritating agent called Product 39) with Na cyanide, ethanol and chlorobenzene. Technical Tabun was a dark brown oil with a fishy odor and d 1.077 at 20°. In the pure state it was colorless.

Tabun was planned to be used in chemical bombs and rockets. Initially the Tabun used in munitions contained 5% chlorobenzene (Tabun A) but, to render this product more stable and to lower its vapor tension, the amount of chlorobenzene was increased to 20% (Tabun B).

Note: This compound is called by H.A. Curtis, CIOS Report 28-62 (1945), p 24, Tarbun or Trilon 83.

b) Sarin (Trilon 46 or T 46, also called T 114) was the monoisopropyl ester of methylfluorophosphoric acid,




It was prepared either by the salt process

or by the rearrangement process mentioned but not described by Collomp. Sarin was a colorless, odorless and very volatile liquid about 3 times as toxic as Tabun.

Due to the fact that Sarin was more toxic and more resistant to heat than Tabun, it was planned to use it in munitions in preference to Tabun.

According to McLeod (Ref 2), Sarin was invented by G. Schröder and is called the "nerve gas".

c) Soman (Trilon?) was the monopropionic ester of



prepd according to Collomp in a manner similar to Sarin.

Soman was a colorless liquid having an odor of camphor. It was less volatile than Sarin but even more toxic.

Production of Trilons started about 1940 in a specially constructed factory at Dyhernfurth-an-der-Oder, 40 km from Breslau. The factory was never discovered by the Allies and is now in the hands of the Russians.

References:

- 1) Capt Collomp, Revue Mensuel de L'Armée de l'Air No 37, October, 1949
- 2) R.D. McLeod, Chem Engrg News 32, 8 (1954).

Trimethylaminoxide Nitrate, $(\text{CH}_3)_3\text{N}:(\text{OH})(\text{O}\cdot\text{NO}_2)$. This compound was prepd by Walter et al by treating trimethylaminoxide, $(\text{CH}_3)_3\text{NO}$, which is a base, with nitric acid.

The trimethylaminoxide was prepd by the oxidation of trimethylamine, $(\text{CH}_3)_3\text{N}$.

Trimethylaminoxide nitrate proved to be of low thermal stability and was considered unsuitable for use in military explosives.

Reference:

H. Walter et al, German Developments in High Explosives, P/B Rept 78,271 (1947), p 8.

Trimethylammonium Nitrate, called by the Germans Tri-Salz is described in the general section.

Trinol. One of the names for Trinitronaphthalene.

2,4,6-Trinitramino-1,3,5,7-tetramethylene-1,7-dinitrate, $(\text{O}_2\text{N})\text{CH}_2\cdot\text{N}(\text{NO}_2)\text{CH}_2\cdot\text{N}(\text{NO}_2)\text{CH}_2\cdot\text{N}(\text{NO}_2)\text{CH}_2(\text{ONO}_2)_m$, m p

155°; was obtained during WWII as a by-product of the manufacture of RDX, using either the E-Salz or the K-Salz process. These processes are described in this section under Hexogen.

The power of trinitraminotetramethylene dinitrate as determined by the Trauzl Test was claimed to be higher than for RDX.

Reference: G. Römer PBL Rept 85,160 (1946), p 16.

Trinitroanisol oder Trisol (Trinitroanisole) (TNAns).

See general section under Anisole. TNAns was used in Germany during WW I as a filler for long range projectiles (Ferngeschützgranaten) fired against Paris and also in some bombs.

(See also Dinitroanisol).

Reference: A. Stettbacher, Spreng- und Schiesstoffe, Zurich (1948), p 77.

Trinitrobenzol (Trinitrobenzene) (TNB). See general section under Benzene. TNB was used in Germany as a military explosive under the name of Filler 70.

Reference: Allied and Enemy Explosives, Aberdeen Proving Ground (1946), p 112.

Trinitrochlorbenzol (Trinitrochlorobenzene) (TNCB).

See general section under Chlorobenzene. The compressed TNCB was used by the Germans during WW II under the name of Filler 60 and was cast under the name of Filler 61. TNCB was also used in admixture with Am nitrate under the name of Filler 64.

Reference: Allied and Enemy Explosives, Aberdeen Proving Ground (1946), p 113.

Trinitrodichlorbenzol (Trinitrodichlorobenzene) (TNDCB).

See general section under Dichlorobenzene. TNDCB was used in Germany as an explosive and also as an insecticide.

Reference: PB Rept 1820 (1945), p 10.

Trinitro-N-ethylaniline is described in the general section under Ethylaniline. It was investigated during WW II as a possible substitute for black powder and smokeless propellants especially for use in mortars and Faustpatrone. The development was stopped due to the unfavorable raw material situation (See also under Treibsätze). Reference: CIOS Rept 25-18 (1945), p 28.

Trinitronaphthalin (Trinitronaphthalene) (TNN), and Dinitronaphthalin (Dinitronaphthalene) (DNN) were used by the Germans during WW II in some composite explosives. They were manufactured at Semtin Fabrik, Pardubice, Czecho-Slovakia. See also general section under Naphthalene.

Trinitroresorcin (Trinitroresorcinol) (TNR), or Styphnic Acid. See Trizin.

TRINITROTOLUOL oder TROYL (Trinitrotoluene) (TNT) Füllpulver O2 oder Fp O2 (Filler 1902). $\text{C}_6\text{H}_2(\text{NO}_2)_3$. It is described more fully in the general section under Toluene.

TNT was officially adopted in Germany in 1902 as a military explosive earlier than in any other country. Its actual use by the Army was begun in 1904, and the industrial production started in 1906 at the Schlebusch Fabrik, D A -G.

For the description of German methods of preparation of TNT, as practiced before, during and after WW I, see the books of Escalles (Ref 1) and Stettbacher (Ref 2). The same books give also the properties of TNT.

It is to be noted that before and during WW I the Germans used a rather complicated process for the manufacture of TNT. This was due to the fact that toluene in those days was rather impure. This method, described by Escalles (Ref 1, p 137) was briefly as follows:

After nitrating toluene by means of weak mixed nitric-sulfuric acid to produce MNT (mononitrotoluene), the crude product (mono-oil) was separated from the mono-spent acid, then washed with water and finally with weak soda-ash solution. After blowing live steam through the oil (in order to remove the benzene present as an impurity as well as any unnitrated toluene), it was cooled to allow the p-MNT to crystallize (m p 51.9°C). After separating the p-MNT by filtration, the remaining liquid fraction was subjected to fractional distillation under vacuum using a column apparatus. The o-MNT came off first, leaving the m-MNT as a residue. Only p- and o-MNTs were used for the prepn of military grade TNT. The m-MNT was used for the prepn of liquid DNT-TNT mixture (Drip oil) useful as an ingredient of commercial explosives. Another method was to distil the o-MNT from the washed mono-oil and then to cool the residue in order to separate the p-MNT from m-MNT.

The method of purification of TNT proposed by the Chemische Fabrik Grünau was described in Ger P 207-170 (1908).

During WW II the German capacity was as much as 55 million pounds of TNT per month, but the maximum they ever produced was 49.5 million in April 1944. The TNT used by the German Army had a m p of 80.4-80.5°.

The manufacture of TNT during WW II in various German plants is described by Stickland et al (Ref 3 and 4) and Brooks (Ref 6, pp 38-41). It seems that none of the processes used in Germany was as efficient (from the point of view of speed of manufacture and yields) as the process introduced during WW II into this country at Keystone Ordnance Works, Meadville, Penna, by Dr I.A. Grageroff, and finally adopted by all US Ordnance plants. The maximum German yield was about 200 parts of TNT per 100 pts of toluene, while the American yield was as high as 210 pts (average yield was 205-208 pts).

In one of the largest German plants, the Kimmel Fabrik of D A -G, the following batch method was used during WW II:

A) Mononitration consisted of the following steps:

a) Pre-nitration. The monomixed acid (consisting of 28% HNO_3 , 56% H_2SO_4 and 16% H_2O) was added to the charge of toluene in the nitrator 2.5 parts of acid to 1 part of toluene. The temperature was maintained at $35-40^\circ$ by cooling coils and a jacket

b) Post-nitration. The mixture was transferred to a post nitrator where it remained for several hours at $35-40^\circ$. Total time required for a full charge of MNT (5 tons) was 5-6 hours

c) Separation. The mixture was transferred to a cast iron vessel where it was allowed to stand for 6 hours. The waste acid (N_2O 0.5%, H_2SO_4 70% and a small amount of nitric acid) was separated and went to the acid recovery plant while the oil underwent purification

d) Purification. The crude oil was washed with water until nearly neutral and was then steam distilled in the presence of NaOH (1% NaOH based on the total weight of MNT). The purpose of adding NaOH was not only to neutralize the remaining traces of acidity but also to transform the nitrocresols, present as impurities, into sodium nitrocresolates, which are soluble in water). During the distillation the first fractions were collected separately because they contained some unnitrated toluene, benzene, and other volatiles. After separating the MNT from the water-soluble fractions, it went through caustic soda washes where the last traces of nitrated cresols were converted to nitrocresolates. The damp neutral MNT (yield 138-144%) was forced by compressed air into a storage tank to be ready for dinitration.

The product separated from impurities consisted of 96% o- and p-MNT and 4% of m-MNT. The purification procedure took about 2 hours. Total time for the preparation of the MNT was 13-14 hours, which was much longer than the present American practice.

B) Binitration or Dinitration consisted of the following steps:

a) Pre-nitration. A charge of MNT was mixed with bi-spent acid (previously diluted slightly with water to separate the greater part of dissolved DNT) in order to use up any residual HNO_3 as well as to extract the last traces of DNT

b) Nitration. After separation from the dilute acid, the oil was fed into the dinitrator containing the tri-spent acid, consisting of 4-5% HNO_3 , 3-4% N_2O_3 and 80% H_2SO_4 , and cooled to 30° . During the addition of

the MNT the temperature rose to $60-65^\circ$ and then fell to 55° due to the excess of unnitrated MNT

c) Post-nitration. In order to complete the dinitration, 60-70% nitric acid was added to the above mixture and the temperature was allowed to rise to $70-72^\circ$.

Note: Time required for total dinitration was not given. In order to ascertain if the nitration was completed, a sample of di-oil was taken and distilled with steam. If no MNT distilled off, the nitration was considered complete.

d) Separation. After allowing the charge to stand for 1 hour, the oil was separated and transferred to an intermediate storage vessel, while the di-spent acid (ca 5% N_2O_3 , 0.6% HNO_3 , 78-80% H_2SO_4) was, slightly

diluted with water in order to separate the greater part of the DNT and to obtain an acid containing about 1.5% N_2O_3 , 0.5% HNO_3 and 7% H_2SO_4 . This

diluted acid was mixed with MNT, as was mentioned under (a). After this, it was transferred to a storage tank where it was allowed to remain for 4-5 days before being sent to the acid recovery plant. Some additional oil separated out during the storage.

Note: Distillation in the recovery house of the di-waste, as well as of the mono-waste acids mentioned previously, gave weak nitric acid (50-55% HNO_3) and weak sulfuric (65-70% H_2SO_4).

(c) Trinitration. In the older Krümmel plant, the acid was added to the oil while in the newer plant the reverse procedure was used which is the current American practice. The new method was essentially as follows:

a) Nitration. The trinitrator was charged with tri mixed acid (11% HNO_3 , 24% H_2SO_4 , 78%) at a temp of 74-78° and the di-oil was added gradually, with agitation, while the temp was allowed to rise to 84-85°. The reaction was completed by raising the temp to 96° and maintaining it there for about 4 hours. Total time of nitration was about 6 hours.

b) Separation. The agitation was stopped and the mixture allowed to settle for 1/2 hour. The tri-oil containing residual acid (1-2% HNO_3 and 1-2% H_2SO_4) was transferred to a washing house and the tri-spect acid was slightly diluted with water (in order to precipitate out some additional TNT) and this diluted acid was used for the bintration (see above).

Note: Each nitrating house was provided with an individual fume recovery plant. The gases formed in the nitration were removed through ventilators and forced into absorption towers where they were sprayed with water, thus forming weak nitric acid (50-55% concentration). This acid was removed for use in the mononitration.

(d) Purification of TNT consisted of the following operations:

The tri-oil (called Rohtri) was given several water washes at 90° and then neutralized at 80° with bicarbonate of soda. The resulting product had a setting point of 78-78.4°, much lower than for pure TNT (80.8°) due mostly to the presence of unsymmetrical TNT's, DNT and other impurities. For further purification, the neutral tri-oil was stirred with an equal amount of water at above 80° and the emulsion cooled to 74-76° with constant stirring to effect crystallization. At this point a saturated solution of Na sulfite (Sellite) was added with continuous stirring. The resulting slurry was filtered and the precipitate washed with water.

Note: The Sellite treatment removed the isomers of TNT (mostly beta- and gamma-) present to the amount of 4-4.5%, tetranitromethane (TeNMe) present to the amount of 0.2-0.3% and some other impurities. Total loss from this treatment was 6 to 8%. The resulting product, called Reintri had a setting point (s p) between 80.0 and 80.6.

(e) Drying, Floking and Packing operations were conducted as follows:

The purified TNT was heated to 85-90°, separated (while in the molten state) from water and then dried in special water-heated vessels by bubbling dry hot air (at 85-90°) through the molten mass. The molten TNT could be sent from the driers either

directly to a shell loading plant or to a flaker. The product with a s p of 80.6° or higher was called Grade A, that with a lower s p was Grade B. There was also a Grade UK (umkristallisiert) with s p 80.7-80.8° which was prep'd by recrystallizing Grade A TNT from a water emulsion, treating the crystals with a small amount of sellite, rinsing with water and drying.

The yield at the Krümmel Fabrik was 138-142 parts of pure TNT per 100 p of MNT, or 200 p TNT from 100 p of toluene.

Capacity of the Krümmel Fabrik was 3,000 metric tons per month.

Brooks (Ref 6) and Wendes & Little (Ref 10) describe the following method of manuf of TNT at the Allendorf Fabrik of Dynamit A-G:

Semi-Continuous Method consisted of the following:

A) Mononitration (continuous process) was conducted in two stages. Toluene and nitric acid were fed into two pre-nitrators where the mixture was vigorously agitated for 1/2 hour at 35°. About 93% of the nitration was accomplished in these vessels. Toluene was fed in at a rate of 1,000 lb per hour. The resulting emulsion overflowed into one main nitrator and then to a continuous gravity separator which was a rectangular steel box packed with Raschig rings. The mono-waste acid was drawn off through a trapped bottom outlet while the mono-oil went to a washer. Here the oil was washed with water and soda-ash solution and then passed through a series of stripping towers. Live steam was blown through the towers to remove the impurities, such as unnitrated toluene, benzene and paraffins. The refined mono-oil was then sent to the bi-nitrator or shipped to other TNT plants.

B) Bi- and Trinitration (batch processes) were conducted in much larger nitrators than used in the U.S.A. As much as 10,000 lb of mononitrotoluene was treated in one batch (about 3 times as much as in the U.S.A.).

The bi-nitration took about 3 hours while the trinitration required 6 hours. For this reason there were twice as many tri-nitrators as bi-nitrators.

In the tri-nitrators, the mixed acid (consisting of nitric acid 24, sulfuric acid 76 and water 0%) was added to the crude DNT (bi-oil) while maintaining the temperature at 83°. Then the temperature was raised over a period of 20 minutes to 98° and maintained at this point for 2 hours.

Note: There were no bottom outlets in the nitrators, permitting the drowning of the charge, but in case of fire there was a quick-opening valve which permitted a large stream of 96% sulfuric acid to spray into the nitrator to extinguish the fire (Ref 6, pp 9-10).

C) Purification of TNT (at Allendorf). Tri-oil was washed with hot water, and then crystallized from fresh hot water. After drawing off the water and re-slurrying the product, it was treated with a 14% soln of Na sulfite (Sellite) of pH 5 to 6 in such a quantity that there was from 3 to 4 lb of Na sulfite per each 100 lb of TNT. When the 14% soln was mixed with the TNT slurry, there was sufficient water present to bring the strength of soln to about 3% of Na sulfite. The red water was filtered off leaving a TNT with setting point 79.5 to 80°. For a purer product (s p about 80.5°) the partially purified TNT was remelted

by treatment with hot water and then treated while in the molten state with a fresh dilute solution of sellire, using a total of 1 lb Na_2SO_3 per 100 lb TNT.

The resulting red water was decanted and the molten TNT washed twice with hot water. Then the hot wash water was passed through 6 cooling units to recover the TNT which was dissolved in the hot solution and precipitated on cooling (Refs 6 & 10).

Note: The Allendorf plant consumed 102 lb of nitric acid per 100 lb of TNT (as against 98 to 100 lb in the U.S.A.), and 195-200 lb of oleum (against 215 lb in the U.S.A.). The yield of 80.4-80.5% TNT was 200 lb per 100 lb of toluene (against 205-208 in the U.S.A.). Cost of 1 lb of TNT was 0.555 mark (about 13¢) (Ref 6, pp 11-15), which was comparable to the price in the U.S.A.

D) TNT Waste Water Treatment. In order to eliminate the expense of evaporation of waste TNT waters, a special method was developed in Germany (on the laboratory scale) for treating such waters in the cold. This method permitted the recovery of some nitro bodies (Ref 6, pp 27-28). In this process the pH of waste water was adjusted to 5 by adding some sulfuric acid. This was in order to free the organic acids so that they could be extracted by a solvent called Phenosolvan, (presumably a mixture of butyl and isobutyl acetates) made by I.G. Farbenindustrie. After separating the solvent (containing the extracted material) from water by centrifuging, the solvent was distilled off. The nitro body obtained as the residue in the still was intended for use in commercial explosives. The separated waste water was treated with lime to bring the pH to 7 and then steam distilled in order to recover the dissolved Phenosolvan. This left a yellow colored waste water from which 95% of the nitro bodies had been removed. It contained some inorganic impurities which were assumed to be harmless to fish, etc. This water was allowed to be ditched (Ref 6, p 27).

Continuous Vapor Nitration of MNT to TNT was developed by Dr A. Wille, and a pilot plant was built at Allendorf (Ref 6, p 25). The plant operated at the rate of 10 lbs of TNT an hour, or 3 metric tons a month. It consisted of four major units: a) an atomizer chamber for MNT, b) a tower for nitration, c) a reflux condenser and d) a separator.

The atomizer chamber had one spray nozzle for the MNT feed (which was preheated to 100°) and a 2nd nozzle to introduce nitrogen gas (which was preheated to 160°). The resulting mist (vapor) of MNT in nitrogen was conducted from the atomizer chamber to the bottom of the nitrating tower, 200 mm inside diam and 2.5 m high, made of stainless steel and provided with a stainless steel spiral coil for cooling. The mixed acid, containing 30-35% nitric acid, was also introduced into the bottom of the tower and it flowed upwards with the MNT and nitrogen. The temperature of the material in the tower was maintained at 92° and the current of nitrogen gas provided sufficient agitation.

The acid and nitro body mixture overflowed at the top of the tower into a rectangular stainless steel box separator, where the TNT settled to the bottom. The waste acid contained 15% total nitric acid and less nitro than with the batch process. The nitrogen gas together with nitrogen oxides and organic vapors (such as tetranitromethane) was led from the tower to a reflux condenser which returned the condensate to the bottom

of the tower (Ref 6, p 25).

Manufacture of TNT at Schlebusch Fabrik of D.A.G. Batch Process (Ref 6, p 29). The TNT plant at Schlebusch was built in 1906 - the first plant for manufacture of TNT on an industrial scale.

The TNT plant used during WW II was constructed in 1935 and consisted of one line with four houses: bi-, tri-, refining and drying. No mononitration was done because the MNT was received from I.G. Farbenindustrie in tank cars. In the bi-house batches of MNT up to 3500 kg were nitrated to DNT and the cycle was 3 hours. In the tri-house each batch of DNT was 4300 to 4400 kg (about 10,000 lb). The maximum production of one line was 2500 metric tons/month (about 5.5 million lb).

Continuous Nitration of MNT to TNT at the Schlebusch Fabrik, D.A.G. (Method of J. Meissner) is briefly described in Ref 10. The plant was dismantled after termination of hostilities and shipped to England where it has never been assembled.

Note: A similar plant is now in operation in Holland (See Dutch Section).

Continuous Nitration of MNT to TNT at the Schlebusch Fabrik, D.A.G. (Method of Demoeff). Dr Demoeff and collaborators developed and built during WW II a continuous pilot plant producing 300 metric tons per month of TNT. The equipment consisted of nine vessels placed in a row and connected in series. In the first vessel, called the dilutor, the bi-waste acid, (arriving from the 5th vessel) was diluted with water. The diluted acid was transferred to the 2nd vessel, called the extractor, in which the nitro bodies dissolved in acid were extracted with MNT (delivered from one of the I.G. Farbenindustrie plants). From there the MNT with extracted nitro bodies was transferred to the 3rd vessel, the separator. From the separator the oil overflowed to the 4th vessel, the bi-nitrator, containing some tri-spent acid which was pumped from the tri-nitrator (the 6th vessel). This acid was fortified with some 60% nitric acid. The mixture of bi-oil (DNT) and of bi-waste acid was transferred to the 5th vessel, the separator, and from there the acid went to the dilutor (1st vessel) while the bi-oil went to the trinitrator (6th vessel) which contained the mixed acid pumped from the 9th vessel (serving as a separator for the 8th vessel, called the postnitrator). The next step was separation of the tri-oil (crude TNT) from the tri-spent acid and this was done in the 7th vessel. Then the acid was pumped to the 4th vessel (the bi-nitrator) while the tri-oil went to the postnitrator (8th vessel) which contained fresh strong mixed acid. Then the mixture was pumped to the 9th vessel, the separator, and from there the partially used mixed acid went to the tri-nitrator (6th vessel) while the TNT went to the wash-house. The nitrators were cylindrical vessels, 2 ft inside diam and 3 ft deep provided with coils and agitators. The separators were of the cyclone type, the upper cylindrical part was 3 ft id and 2 ft high, and the bottom conical part 1 ft deep. The nitrators had a capacity of 200 kg bi-oil and the required amount of acid. The acid consumption for bi- and tri-nitrations was about the same as for the batch process, namely 87 lbs nitric and 195 lbs oleum for 100 lbs TNT produced (Ref 6, p 31).

Continuous Method of Refining of TNT, developed on a pilot scale by Dr Demoeff of Dynamit A.G. and tried at Schlebusch, used nine vessels connected in series. The 1st, 3rd, 5th and 7th vessels were washers, the 2nd, 4th, 6th and 8th vessels were separators and the

9th vessel was a dryer. The crude molten TNT (called Rohtri) was transferred from the nitrating plant to the 1st vessel, where it was agitated with hot water. The liquid mixture was transferred to the 2nd vessel (cyclone type separator, similar to the ones used in the nitration plant), where the oil was separated from waste acidic water. Then the oil was transferred to the 3rd vessel where it was washed, while still in the molten state, with a hot dilute solution of sodium sulfite (Sellite) at a pH 5 to 6. After this the tri-oil was separated from waste water (4th vessel) and then washed with fresh hot water (5th vessel). This waste water was separated in the 6th vessel and then in the 7th vessel the TNT was washed again with water for the last time. After separating the last wash water in the 8th vessel, the still molten TNT was dried by bubbling hot compressed air through the liquid in the 9th vessel. Finally the TNT was flaked in the usual manner (Ref 6, p 32).

Continuous Method of Washing of TNT designed by J. Meissner (Ger P 732,742, 1940-1943). The apparatus consisted of six vertical tall cylinders (columns) provided with perforated plates. Each column was enclosed in a steam jacketed kettle so that the TNT could be kept molten throughout the washing process. After separating the crude liquid TNT from the bulk of spent acid, it was emulsified by means of live steam and pre-heated air. The TNT emulsion entered continuously into the bottom of the 1st column and simultaneously some hot water, required for rinsing out the residual acid, was injected. The emulsion moved upwards and, after passing through the perforated plates (installed in order to achieve more intimate mixture between the TNT and washing medium), reached the upper part of the column where the separator was located.

After separating the acidic water, the liquid TNT went to the bottom of the 2nd column. The process was repeated as in the 1st column except that a 5% Na bicarbonate solution was used as the washing medium.

In the 3rd column, the TNT emulsion was washed with hot water, and in the 4th and 5th columns it was washed with a 5% Na sulfite solution in order to remove the beta and gamma isomers of TNT. In the 6th column, the TNT was washed with hot water, as in the 1st and 3rd columns.

It was claimed that the process possessed the following advantages over the batch processes:

- Less time consumption due to the fact that much more intimate contact was obtained between the emulsified droplets of TNT and the washing media than was possible with the older method
- Better yields - 95-96%, vs 90-93% with the older batch methods. This was claimed to be due to the fact that as actual contact between the TNT droplets and washing media is very short (less than 5 minutes in each column) there was practically no decomposition or removal of the alpha TNT and only the impurities were affected
- Better quality of product: setting point 80.5-80.7°, vs 80.3-80.5° C by the older method
- Greater economy - man power requirements were reduced.

TNT Refining by Nitric Acid. During WW II, the J. Meissner Co developed a refining process with the aim of recovering the TNT impurities for use in commercial explosives. In this process, the crude TNT was crystallized from hot nitric acid of nearly 100% concentration. The man-

ufacturing took place in Belgium but was discontinued because of a serious explosion. This was due to the fact that solutions of TNT in strong nitric acid are very sensitive liquids known as Sprengel Type Explosives.

After this accident Dr A. Wille of Allendorf modified the process to make it non-hazardous.

a) In the new process the crude TNT was dissolved in hot, weak (about 60%) nitric acid and the solution cooled to room temperature. The crystals of purified TNT were separated by filtration from the cold mother liquor which contained most of the impurities and some alpha-TNT. The TNT crystals were washed directly on the filter with fresh 60%, cold (about 30° C) nitric acid and this acid was saved to be used later as a hot solvent for one of the next batches of crude TNT

b) The washed crystals of purified TNT were melted and the molten compound washed with hot water. The resulting acidic water was removed and saved to be used later for absorption tower feed in the acid recovery plant. The molten TNT was further washed 2-3 times with fresh portions of hot water (saving the waste water each time), dried with hot air and then flaked in the usual manner

c) The first 60% nitric acid filtrate (see operation a) was distilled in a stone-lined plastic still using induction heating to eliminate hazards. The average strength of the recovered acid was about 30%.

The purified TNT was of light color and had a s p (setting point) 80.2 to 80.3°. It was claimed to be less exudable than TNT's of s p as high as 80.6° obtained by the Na sulfite purification. This could be due to the fact that nitric acid removes among other impurities the DNT, while Na sulfite does not. For some unknown reason, the TNT refined by nitric acid could not be pelleted. The loss of crude TNT on refining was around 8% (about the same as in sulfite retining) but the nitro-bodies recovered from the nitric acid could be used in commercial explosives, while in the Na sulfite process the nitro-bodies were decomposed (Ref 6, p 27).

Loading of Ammunition with TNT:

All bombs and shells were cast-loaded and the method is described in Ref 2, pp 14-15, 18-24. Items such as detonators and some boosters were press-loaded and the procedure is described in detail in Ref 3, pp 46-48.

Uses of TNT in Germany During WW II:

A) Straight cast TNT was used in: a) HE shells, such as the 37mm, 47mm, 50mm (trench mortar), 75mm, 75mm (smoke) and 105mm (howitzer) b) AP shells, such as 75mm, 75mm (capped), 47mm (round nose) c) Land mines such as the Tellermine

B) Straight pressed TNT was used in some detonators and boosters. For instance, the booster for the 47mm HE shell contained 3 pressed pellets of TNT, density 1.49, coated with wax (Ref 5)

C) TNT desensitized with wax. A small quantity was used by the Germans as early as WW I in their AP shells. At the Battle of Jutland, many British ships were sunk by German AP shells filled with desensitized TNT which exploded after penetrating through armor, while most of the German ships were undamaged, because British AP shells were filled with PA which exploded on the surface of the armor before penetration. This was due to the fact that PA is too sensitive to impact.

During WW II, the Germans used some AP and SAP shells filled with blocks consisting of mixture of TNT

with 3 to 20% of Montan wax. The higher wax content was in the nose where the shock of impact is more intense. The tail booster consisted of straight compressed TNT.

Following are the names of TNT-wax mixtures used for loading shells: Fillers No 10, No 11, No 12, No 27, No 29, No 30 and No 100 (See under Fillers).

Note: All the above mentioned mixtures, with the possible exception of Filler No 29, were less powerful and brisant than straight TNT, and their velocities of detonation were lower (Ref 4).

b) Mixtures of TNT with various explosives. In some mixtures, such as with RDX or PETN, the TNT was incorporated to make the composition castable and less sensitive to mechanical action than if RDX or PETN was used alone, although the addition of TNT resulted in the lowering of power, brisance and velocity of detonation of the RDX or PETN.

In another group of explosives, the TNT was the principal high explosive component, the other ingredients being added to stretch the available supply of TNT. Among these ingredients were: Am nitrate (such as in Amatols and Ammonals), K or Na nitrate (such as in Sodamol), DNB, DNN, TNX, DNA, Ca nitrate, common salt, etc. These explosives can be classed as Ersatzsprengstoffe (q v).

One such mixture, namely TNT & DNA, was used in some hand grenades, because it was presumed that incorporation of a comparatively weak explosive, such as DNA, prevented the formation of excessively small fragments.

There were also several TNT & TNX mixtures and they are described under Trinitroxytol.

Abbreviations: AP Armor-piercing; A/T Antitank; Ca Calcium; D A G Dynamit Aktiengesellschaft; DNA Dinitroaniline; DNB Dinitrobenzene; DNN Dinitronaphthalene; DNT Dinitrotoluene; GerP German Patent; HE High Explosive; m- meta; MNT Mononitrotoluene; mp melting point; Na Sodium; o- ortho; P Patent; p- para; P A Picric acid; PETN Pentaerythritol tetranitrate; RDX Cyclonite or RDX; SAP Semi-armor-piercing; TeNMe Tetranitromethane; TNT Trinitrotoluene; TNX Trinitroxytolene.

References:

- 1) R.Escales, Nitrosprengstoffe, Veit, Leipzig (1915) pp 142-161, 290-328, and 436-438
- 2) A.Stettbacher, Schiess- und Sprengstoffe, Barth, Leipzig (1933), pp 261-277
- 3) O.W.Stickland et al, General Summary of Explosive Plants (Germany), PB Rept 925 (1945), pp 6, 33-38 & 46-48
- 4) O.W.Stickland et al, Survey of German Practice and Experience in Filling High Explosives, PB Rept 1820 (1945), pp 6-8, 14-15 & 18
- 5) Anon, Data on Foreign Explosives, PB Rept 11,544 (1945), Part II, Tables I & II
- 6) C.H.Brooks, TNT Manufacture in Germany, PB Rept 22,930 (1945)
- 7) Allied & Enemy Explosives; Aberdeen Proving Ground, Maryland (1946), p 79
- 8) H.Walter et al, German Development of High Explosives, PB Rept 78,271 or FIAT Final Rept 1035 (1947), p 2
- 9) A.Stettbacher Spreng- und Schiessstoffe, Rascher, Zürich (1948), pp 73-75
- 10) J.C.H.Wendes & J.R.Little, Report on the Known European Processes for the Continuous Production of TNT, US Rubber Co, Kankakee Unit, Joliet Arsenal, Joliet, Illinois (1953).

Trinitroxytol (Trinitroxytolene) (TNX) is described in the general section under Xylene. The German TNX prepd by nitrating commercial xylene was a plastic product contg about 85% of trinitro-*m*-xylene of mp 182°, the rest being a liquid mixture of nitrated *o*- and *p*-xylenes. (Refs 1 & 4).

In order to stretch the available supply of TNT, the Germans, during WW II, used some explosive compositions which contained as high as 45% TNX.

Following are some examples of such explosives:

a) Mixtures of TNX 20-25 and TNT 80-75% with a mp average of about 77° were used for cast-loading some bombs and shells. For their manufacture xylene and toluene were nitrated separately by continuous methods to form MNX and MNT and the mixture of the two mononitrocompounds in the approximate ratio of 1:4 was nitrated directly to the trinitro stage, but the sulfite refining was omitted (Refs 2 & 3)

b) A mixture of TNX 45, tetryl 50 and TNT 5% with a mp about 80° and suitable for cast-loading shells, etc, was prepd by nitration of a mixture of MNX and dinitromethylaniline and incorporation in the resulting trinitrated product of 5% of TNT. The mixture was more brisant than TNT but required a stronger booster (Ref 2, p 11).

(See also under Ersatzsprengstoffe).

References:

- 1) A.Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933) pp 277-8
- 2) PB Rept 1820 (1945), p 11
- 3) PB Rept 22,930 (1945), p 15
- 4) A.Stettbacher, Spreng- und Schiessstoffe, Zürich (1948), p 75.

Tri-Solz. See Trimethylanmonium Nitrate in the general section.

Tritolol. See Filler No 108(?) under Fillers.

Tri-Trinol. An explosive consisting of 2 parts of Tri (TNT) with 1 or 2 parts of Trinal (TNN) used during WW I for filling some small caliber shells. Compressed P A was used as a booster.

Reference: T.L.Davis, Chemistry of Powder and Explosives, Wiley, N Y (1943), p 158.

Triwestphalit SN. An explosive used in potash mining. It was prepd by W A S A -G by crushing and grinding the double-base propellants left as surplus after WW I. Reference: : Naoüm, Nitroglycerin, Baltimore (1928) p 499.

Trizin, Tricin, Trinitroresorcin, Styphninsäure oder Oxyplkrinsäure (Trinitroresorsinol or Styphnic acid) is described in the general section under Resorcinol. A short description of Trizin is given by Stettbacher (Ref 1 and 3) A method of prepn of the Trizin as practiced in Germany during WW II is given in Ref 2. Trizin was used for prepn of its lead salt, called in German Trizinot and in English Lead Styphnate.

References:

- 1) A.Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933), p 287
- 2) PB Rept 95,613 (1947), Section M
- 3) A.Stettbacher, Spreng- und Schiessstoffe, Zürich (1948), p 98.

Trizinol, Trizinot, Tricinot, Blei Trizinot oder Blei Styphnat. See Blei Trinitroresorcinat and also in the general section under Styphnic Acid.

Trizinol und Tetrozen Zusatz. Same as Sinoxydsatz.

Trobach Priming Mixture, patented in 1890, contained Ba picrate 70, K chlorate 15 and 15% of a double salt prepd in the following manner:

Pyridine was added slowly to a soln of a metallic nitrate (such as of Cu, Ni or Bi), until the characteristic odor of pyridine became evident. The resulting crystals were dried and incorporated in the above mixture.

Reference: Daniel, Dictionnaire, Paris (1902), p 776.

Troisdorf Fabrik D A-G was one of the principal German factories for the manufacture of priming and initiating explosives and devices. Its WW II developments and activities are briefly described by W. Taylor et al, BIOS Final Report 044 (1945).

Trolit. Plastic material consisting of either polystyrene or polystyrene copolymers manufd during and after WW II by the Dynamit A-G, Troisdorf, Bez Köln. Some fuze bodies, such as "Wgtz. T" were made from Trolit.

References:
1) W. Krannich, Kunststoffe im technischen Korrosionsschutz, Lehmann, München-Berlin, (1943), p 425
2) H. Sachtling u. W. Zebrowski, Kunststoff-Taschenbuch, Hanser, München (1952), pp 240-241, 257
3) H. A. Tisch and R. W. Kuchkuda, Picatinny Arsenal, Dover N J; private communication (1955).

Tropföl oder Flüssige Tri (Drip Oil or Liquid Oil) is described in the general section and also in A. Stettbacher, Schiess- und Sprengstoffe (1933), p 261.

TSMV 1-101. See Schiesswolle 18.

T-Stoff (T-Stuff or T-Substance) is the German designation for concentrated hydrogen peroxide (wasserstoffperoxyd). T-Stoff was a clear, viscous liquid contg 80-85% H_2O_2 and 20-15% H_2O . It was fairly stable at ordinary temperature and pressure when in the presence of small quantities of stabilizers such as phosphoric acid. However, despite the greatest care it was not possible to prevent a slow decomposition of the H_2O_2 into oxygen and water over a long period of time.

T-Stoff was best stored in aluminum receptacles which had been previously treated with an acid and trisodium phosphate. It can also be kept in glass vessels, but in any case extreme care must be taken to exclude any dust (inorganic or organic) or any other impurities. Other T-Stoff resistant materials reported were: copper-free aluminum alloys, chromium steels (with not less than 13% Cr), polyvinylchloride plastic (when using tricresylphosphate as a softener) and polyethylene plastic. The Buna S and polyvinylchloride without a softener were less resistant whereas the polyamid was not resistant at all (CIOS Rept 30-115, pp 12-14).

In order to determine the strength of T-Stoff, either a hydrometer or titration with K permanganate was used.

T-Stoff was used as an oxygen carrier in some rocket propellants, as for instance in the Mecht guided missile which was propelled by a mixture of T-Stoff and Na or Ca permanganate. These mixtures were called Z-Stoff.

According to CIOS Rept 30-115, p 8, when T-Stoff was decomposed by a catalyst, such as Z-Stoff (see above) or MP-14 (q v), superheated steam was formed (together with oxygen) because about 552 kcal/kg were liberated and a very high temperature (400° C) was attained. The steam obtained with a solid catalyst (such as MP-14)

was suitable for driving the turbine, whereas the steam obtained with Z-Stoff was suitable for driving rockets or ATO (assisted take-off) units. The steam obtained with Z-Stoff was not suitable for driving turbines because it contained small particles of MnO_2 . When T-Stoff was mixed with B-Stoff (hydrazine hydrate) in the presence of K cuprocyanide the resulting liquid was found to ignite spontaneously.

One of the most interesting applications of T-Stoff was as a source of power for submarines as proposed by Dr Hellmuth Walter. (See U-Boot Walter). Seven such submarines (300 to 500 tons each) were accepted by the German Navy up to the end of WW II.

Dr Walter, who is now working in the U.S.A., recently published a paper (Ref 7) describing hydrogen peroxide as a source of power. Beside submarines, he lists the following German devices where hydrogen peroxide was used as a source of power:

- A 500 kg ATO (Assisted Take Off) H_2O_2 mono-fuel unit
- A 300 kg thrust, rocket propulsion unit for guided missiles
- A bipropellant 1000 to 1500 kg ATO
- A catapult with hydrogen peroxide propulsion unit (decomposition only) for launching V-1's
- Controllable propulsion of a 750 kg thrust unit for the Messerschmitt 263
- Rocket training airplane and a controllable power plant giving to 2000 kg thrust for the Messerschmitt 263 B.

References:

- Dr Nitschmann, Physical and Chemical Investigations of T-Stoff Solutions, IG Farbenindustrie Rept 597, Oppau, Germany (1944)
- H. Walter, Report on Rocket Power Plants Based on T-Substance, NACA Rept No 1170 (translated from the German)
- Logan McKee, Mechanical Engineering 68, 1045-48. (1946), Hydrogen Peroxide for Propulsive Power, Production and Use by the Germans during WW II
- E.S. Shanley & F.P. Greenspan, Ind & Eng Chem 37, 1536-43 (1947), Highly Concentrated Hydrogen Peroxide. Physical and Chemical Properties
- R. Simard, The Engineering Journal of Canada 31, 219-25 (1948)
- F. Ross, Jr, Guided Missiles, Lothrop etc, N.Y. (1951), pp 45-6
- H. Walter, Jet Propulsion 24, 166-171 (1954). Experience with the Application of Hydrogen Peroxide for Production of Power.
Note: According to H.A. Curtis, CIOS Report 28-62 (1946), p 23 the code name T-Stoff was used for 82% hydrogen peroxide, while the code names Aurol, Neuralin and Substol were used for any 80-86% hydrogen peroxide. According to R.C. Stiff, CIOS Rept 30-115 (1945), p 8, the T-Stoff was also called Ingolin.

T-Stoff. Besides being a designation of a concentrated hydrogen peroxide (see above), the word T-Stoff was used to designate the lacrymator (Tränenstoff) consisting of a mixture of bromides of o-, m- and p- isomers of xylene.

T-Stoff (S). Hydrogen peroxide containing about 20% water and stabilized with phosphoric acid (150 mg per liter). Specific gravity at 20° C: 80% solution 1.34, 83% 1.355 and 85% 1.364. Decomposition number (q v) less than 5. Used as a source of oxygen in liquid rocket propellants. Reference: R.C. Stiff, CIOS Report 30-115 (1945), p 9.

T-Stoff (SS). Hydrogen peroxide contg about 20% of water and stabilized with oxyquinoline (400 mg per liter). Decomposition Number (q v) less than 1. Specific gravity

at 20° same as T-Stoff (S). Used in liquid rocket propellants.

Reference: R.C.Stiff, CIOS Report 30-115 (1945), p 9.

Überchlorsäure. See Perchloric Acid in the general section.

Übertragungsdistanz (Transference Distance). According to A. Stettbacher Schiess- und Sprengstoffe, Leipzig (1933), p 46, the distance (d) in meters may be expressed as:

$$d = k\sqrt{c}$$
 where

(c) is the weight of an explosive in kg and (k) is the constant equal to about 2.5.

(See also Gap Test in the general section).

Übertragungskoeffizient oder Sensibilitätskoeffizient (Transmission Coefficient or Sensitivity Coefficient) According to Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933), p 45, the coefficient of transmission of detonation by influence (Le) is calculated from the following equation:

$$Le = c_1 c_2$$

(c) is the weight (such as 50 g) of an explosive to be initiated by influence and (c₁) is the weight of a standard explosive, such as picric acid (P A) serving as an initiator by influence.

If the distance between explosive charges is 15 cm, then in order to detonate 50 g of P A (c = 50), it would require 50 g of P A (c₁ = 50). This would give for the (Le) the value of 50/50 = 1.

In order to detonate 50 g of TNT (c = 50) it would be necessary to use 68 g of P A (c₁ = 68) while for 50 g of tetryl only 28 g of P A would be required. This gives for (Le) the value of 50/68 = 0.78 for TNT and the value of 50/28 = 1.80 for tetryl.


Note: The higher the value of (Le), the more sensitive is an explosive to initiation by influence.

U-Boot, One-Man; One-Man Submarine or One Man Torpedo (Ein-Man Torpedo). This device consisted of a small one man submarine to the bottom of which a torpedo was attached by means of shackles. The combination was propelled by an electric motor in the submarine operated by storage batteries. The pilot brought the device to within a fairly short distance of the target (such as an enemy ship, dock, warehouse, etc.) before releasing the torpedo. The torpedo was aimed by lining up the submarine with the target. After firing the torpedo, the pilot returned to his base or to his "mother" ship (Refs 1 & 2).

Note: Some of submarines were propelled by internal combustion engines (Ref 2).

References:

- 1) Anon, Field Artillery Journal 34, p 505 (1944)
- 2) Private communication from an engineer who worked on their construction and who requested that he remain anonymous.



U-Boot, Pocket (Pocket Submarine). See Seehund.

U-Boot-21 oder Unterseeboot 21 (U-Boat 21) (Sous-marin 21, in French) was a submarine developed in the last part of WW II but not produced in large quantity. It was 77 m long, 6½ m wide, displaced 1600 tons and was provided with 5000 HP Diesels and 5000 HP electric motors. Its speed in submerged condition was 18 knots against 7 knots of the older submarine models "7" and "9". The U-boat-21 could travel as much as 30,000 miles without refuelling or restocking.

Reference: A. Ducrocq, Les Armes Secrètes Allemandes, Paris (1947), pp 24-26.

U-Boot Walter (U-Boat of Walter) (Submarine With Chemical Propulsion) (Sous-marin à propulsion chimique, in French). In order not to be dependent on atmospheric oxygen for the operation of submarine Diesel engines when in submerged condition, H. Walter and collaborators designed a device in which concentrated hydrogen peroxide (T-Stoff) was catalytically decomposed in the presence of permanganate into water and oxygen. The oxygen liberated was used for operating the Diesels. At the same time, the energy liberated on decomposition of the hydrogen peroxide, which amounted to 690 kcal/kg (calculated for 100% peroxide), was utilized to operate a gas turbine directly connected to the propeller shaft. As a by-product of this reaction pure water was obtained which was used for drinking and cooking purposes.

According to Ref 5, the above system was called "Closed Cycle Diesel Development for Submerged Propulsion", and the idea for such an engine goes back to the time of WW I when the Germania Werft at Kiel tried to use compressed oxygen for Diesels. No work on the subject was done until 1939-1940 when the German Navy requested some firms (such as Zeppelin GmbH, Kommandit-Gesellschaft Walter) and research institutions (such as the Forschungsinstitut für Kraftfahrzeuge, under the direction of Prof Kamm and Dr Huber) to resume the project. Besides the above mentioned Walter system using hydrogen peroxide as a source of oxygen, there was also a system developed at Prof Kamm's laboratory which used compressed oxygen. A submarine, using compressed oxygen, designated as Type XVIII K (called also Seehund), was nearly completely built at the Germania Werft, Kiel, using finished Blohm & Voss Type XVII hulls, Daimler-Benz engines and two outboard cylinders with compressed oxygen. The Kamm's equipment was somewhat bulkier than that of Walter. In addition to the type XVII K submarine, it was planned to build a submarine with a smaller engine and to use liquid oxygen carried in two insulated tanks. The work on the closed cycle engine project did not progress very fast as it was considered by the High Command to be of secondary importance.

(See also Seehund and under T-Stoff).
 Note: Rocket power plants constructed at the Walter Werke, Kiel are described by R.C.Stiff, CIOS Rept 30-115 (1945).

Note: According to Chem Engrg News 32, 1356 (1954), the British, in the yard of Vickers-Armstrong, at Barrow-in-Furness, launched a submarine called the "Explorer" which is to be propelled by hydrogen peroxide.

References:

- 1) A. Ducrocq, Les Armes Secrètes Allemandes, Paris (1947), pp 26-31
- 2) R. Simard, Eng J of Canada 31, 219-25 (1948), C A 42,5622 (1948)
- 3) H. Schaeffer, U-Boat 997, Norton, N Y (1953), pp 181-2
- 4) H. Walter, Jet Propulsion 24, 168-9 (1954)
- 5) A.H. Schilling, German Naval Closed Cycle Diesel Development for Submerged Propulsion, CIOS Report 30-76 (1945).

Underwater Explosions and Explosives (See Unterwassersprengungen und Sprengstoffe).

Ungefrierbare Dynamite oder Schwergefrierbare Dynamite (Non-freezing Dynamites or Difficultly Freezing Dynamites) as described in the general section as Low-freezing Dynamites.

The following substances or their mixtures were used in Germany in order to make the NG containing explosives non-freezing at winter temperatures:

Nitroglycerol, dinitrochlorohydrin, dinitroglycerin, tetranitrodiglycerin, dinitroformin, dinitroacetin, butyleneglycolinitrate and aromatic nitrocompounds such as MNB, MNT, DNT, etc.

References:

- 1) P. Naoum, Nitroglycerin (1928), pp 356-381
- 2) A. Stettbacher, Spreng- und Schiessstoffe, (1948), p 61.

Unknown-Name Explosives. The following German compositions were described in Allied and Enemy Explosives, Aberdeen Proving Ground, Maryland (1946) and other sources, but for which no names were given.

- a) RDX/TNT - 50/50 and 53/47. Used in shaped charge ammunition (shells, grenades and demolition charges (cast-loaded)).
- b) RDX pellets embedded in TNT. Used in 4000 kg bombs (cast-loaded).
- c) RDX/TNT/Wax - 51/48/1, 55/42/3 and 58/40/2. Used for cast-loading various shells.

Unterwassersprengstoff (Underwater Explosives). Extensive study of underwater explosions (Unterwassersprengungen) and of German underwater explosives was conducted by Dr. A. Stettbacher, Zürich, Switzerland. He described some of his investigations in books and papers published in Germany and Switzerland (See Refs 1-5). Some additional information on German and Swiss explosives was communicated to the author by Dr. S. during his stay in New York in the summer of 1954. Some investigation on German aluminized underwater explosives was made by H. Mourou (See under Aluminized Explosives). Extensive information on the composition and effectiveness of various underwater explosives may be found in Naval Technical Mission Europe Technical Reports (e.g. Repts Nos 227-45, 547/45 & 548/45), some PB reports (e.g. PB No 1820), some British Armament Research Department, some British Mine Design Dept and some German reports issued by the Chemisch-Physikalische Versuchsanstalt and other institutions. One of the reports is entitled Bericht über die Arbeitstagung Unterwassersprengungen Amtsgruppe Mar Rüst/EEP in GEM, Tagungsbericht Nr 8, Oktober 1945. The data from these papers was compiled by J.S. Coles in an excellent report entitled "Summary of Underwater Explosive Comparisons", NDRC No A-363, OSRD No 6241. Although this report was written about 1945, it is still classified. For this reason the values of underwater effectiveness given in this report are not included in this work.

According to Stettbacher the principal explosives used during WWI for loading the sea mines (Seeminen), depth charges (Tiefbomben) and torpedoes (Torpedos), consisted of TNT and HNDPhA (hexanitrodiphenylamine). One such explosive composition consisted of TNT/HNDPhA - 60/40, while another contained TNT/HNDPhA - 35/65. The latter mixture was called *Schleisswolle neuer Art* (Schw NA).

Note: It is of interest to report that previous to WWI and as early as 1898, the Germans, in their underwater ammunition, used mixtures of TNT, HNDPhA, TeNA (tetranitroaniline, called Tetra in Germany) and TNB (trinitrobenzene). Straight TNT was also found to be suitable as an underwater explosive. Towards the end of WWI large proportions of aluminum powder were introduced in underwater explosives. One such mixture, known as *Schleisswolle 18* (abbreviated to Schw 18 and later called S-1) was used

extensively during WW II. Its composition was TNT/HNDPhA/Al - 60/24/16. Note: Stettbacher's reported analysis of this mixture was 61.8/23/15.2. He stated that it was very effective in all kinds of underwater charges.

At about the same time as above (1918), a mixture in which PETN was used in lieu of HNDPhA was introduced. It was called Schw 19 and contained PETN/TNT/Al - 25/48/27.

When Germany started to rearm (about 1936), the mixture called Schw 36 or S-2 (TNT/HNDPhA/Al - 67/8/25) made its appearance. At about the same time the Chemisch-Physikalische Versuchsanstalt (CPVA) proposed several explosives in which RDX (Hexogen) was used in lieu of HNDPhA (See Triolens 105 and 106, known also as Filler No 105 and Filler No 106). Similar explosives: Triolens 107 (See Filler No 107), S-17 or Mixture I (RDX/TNT/Al - 10/50/40) and Tritolital (qv) appeared before and during WW II.

Several compositions in which ammonium nitrate was used as one of the ingredients were introduced before and during WW II. They included Schw 39 or S-3 (NH₄NO₃/HNDPhA/TNT/Al ground - 30/5/45/20), Schw 39a (NH₄NO₃/HNDPhA/TNT/Al ground - 5/10/50/35), Mixture 2 (NH₄NO₃/RDX/Al/Wax - 35/28.5/35/1.5), S-16 (NH₄NO₃/Ethylenediaminedinitrate/RDX/Al/KNO₃/NaNO₃ - 32/10/10/40/2/6), Some Amotols, among them the Amotol 39 (qv), ASN explosive (NH₄NO₃/Dicyandiamide/PETN - 70/10/20) and ASN + 10% Al explosive (NH₄NO₃/DCDA/PETN/Al - 63/9/18/10).

In addition to the above mentioned ASN and Schw 19, the following other underwater explosive compositions contained PETN: PETN/Al powder/Wax - 66.5/30/3.5 and a mixture of Nipolit (qv) 70 with ground Al 30%. One of the advantages of Nipolit is that it can easily be machined and is suitable for use either for cased or uncased charges.

Mixtures of PETN with NG (nitroglycerin), in which may be incorporated some collodion cotton, were proposed in 1929 by A. Stettbacher under the name of Pentritins. (See Swiss section of this dictionary). These mixtures were found to be effective in underwater explosions.

Below are listed additional explosives proposed before and during WW II for use in underwater ammunition. It should be noted that some of these explosives were only experimental.

Straight TNT, TNT/Al - 75/25 & 60/40, TNT/RDX - 55/45, RDX/Al/Wax - 76/20/4 & 67/30/3 (called respectively Hexol 80/20 & Hexol 70/30), S-4 (matrix S-2 & pellets S-3), S-5 (matrix S-1 & pellets S-3), S-6 (Dinitrophenylene/HNDPhA/TNT/Al - 20/24/40/16), S-7 (DNN/HNDPhA/Trinitrochlorobenzene/Al - 15/24/45/16), S-8 (HNDPhA/Trinitrobenzene/TNT/Al - 24/6/54/16), S-9 (matrix S-1 & pellets S-6), S-10 (matrix S-8 & pellets S-6), S-11 (matrix S-1 & pellets S-7), S-12 (matrix S-8 & pellets S-7), S-13 (HNDPhA/Trinitrochlorobenzene/Al - 24/60/16), S-14 (matrix S-1 & pellets S-13), S-15 (matrix S-8 & pellets S-13), S-16 (see above), S-17 called also Mixture I (see above), S-18 (matrix S-17 & pellets S-16), WASAG-1 (NH₄NO₃/HNDPhA/TNT/Al - 30/5/55/10), WASAG-2 (HNDPhA/TNT/Al - 24/66/10), WASAG-3 (HNDPhA/TNT/Al - 15/75/10), WASAG-(1+2) (matrix WASAG - 2 & pellets WASAG - 1), WASAG-(1+3) (matrix WASAG-3 & pellets WASAG-1).

The following two experimental mixtures proved to be very promising as underwater explosives: NH₄ClO₄/RDX/Al - 50/10/40 and TNT/NH₄NO₃/Al - 57.1/28.6/14.3. The first mixture is about 2½ times as effective as TNT, while the second mixture has the advantage that it can be pressed to a high density of 1.84. (See also explosives S-6, S-6 modified, S-16, S-19, S-22, S-26, E-4 and KMA listed under Ersatzsprengstoffe).

References:

- 1) A. Stettbacher, S S 25,233-34 (1930) (Explosionen unter Wasser. Torpedo Wirkung)
- 2) A. Stettbacher, Schiess- und Sprengstoffe, Leipzig (1933), pp 396-401
- 3) A. Stettbacher, Protar 8, 83-92 (1942), Kriegssprengstoffe
- 4) A. Stettbacher, Protar 9, 33-45 (1943). Über die Wirkung von Torpedos, Minen, und Tiefenbomben unter Berücksichtigung

sichtigung der deutsche Marine-sprengstoffe, vom letzten und heutigen Weltkrieg)

5) A.Stettbacher, Spreng- und Schiesstoffe, Zürich (1948), pp 135-140

6) J.S.Coles et al, NDRC Report No A-363, OSRD Rept 6241 (about 1945), pp 51-9 (Confidential)

7) R.H.Cole, Underwater Explosions, Princeton University Press, Princeton, New Jersey (1948), pp 117-124

8) O.W.Stickland et al, PB Rept 1820 (1945)

9) A.Stettbacher of Zürich, Switzerland; private communication.

Unterwasserzunder (Underwater Igniter or Primer). Described in C.Beyling and K.Dreikopf, Sprengstoffe und Zundmittel, Berlin (1936) pp 174, 225 & 237.

Uresin B. Plasticizer for NC made from cellulose acetate and formaldehyde (CRS 20-62, p 24).

V-1 oder Vergeltungswaffe Eins (V-1 or Revenge Weapon One). The official German designation was FZG-76 and the British name **Buzz Bomb**. V-1 was a pilotless plane(winged rocket) which could fly at a speed of 500-560 mph at a height between 2,000 and 3,000 feet and to a distance of 220 miles. It could be launched from a catapult or released from a piloted plane. The body of the V-1 rocket was cylindrical in shape, tapering toward the nose; diameter 2.7" and total length 21.5'. Fully loaded it weighed 4,750 lb. It was propelled by a pulse-jet engine using 150 gallons of gasoline for fuel and compressed air as the oxidizer. The warhead contained some newly developed explosives (see below), which could withstand high temperatures. These rockets were fired against England, beginning in June 1944, and caused considerable damage.

References:

- 1) A.Ducrocq, Les Armes Secrètes Allemandes, Berger-Levrault, Paris (1947), p 35
- 2) F.Ross, Jr, Guided Missiles, Rockets and Torpedoes, Lothrop, Lee, Shephard, N Y (1951), pp 14-20
- 3) K.W.Gatland, Development of the Guided Missile, "Flight" Publication, London (1952)
- 4) Anon, German Explosive Ordnance, TM 9-1985-2 (1953), p 205-10

5) I.Dornberger, V-2, The Viking Press, N Y (1954), p 53-98

6) A.Saucke et al, Guidance, Van Nostrand N Y (1955), pp 44-5, 56-7, 71 & 76 (Book 1 of the "Principles of Guided Missile Design", edited by Grayson Merrill)

(See illustration on next page).

V-2 oder Vergeltungswaffe Zwei (V-2 or Revenge Weapon Two). The official German designation was A-4. V-2 was a rocket provided with 4 stabilizing fins. It could fly with a speed up to 3600 mph to a distance up to 220 miles and at altitudes up to 50-60 miles. The body of the rocket was cylindrical in shape with a nose tapering to a sharp point. The largest diameter was about 5' and the overall length was 46'. Fully loaded it weighed about 14 tons, which included 9 tons of fuel supply and about 1 ton of special explosive that could withstand high temperatures in the warhead. The first of these rockets was fired against England in Sept 1944. A total of 1115 V-2 rockets were fired up to April 2, 1945, and they caused considerable damage especially in London and vicinity.


Table 62 gives some additional information on V-2, as taken from the book of Gatland (Ref 3, p XVII).


TABLE 62

| Characteristics of V2 | Metric | US |
|-----------------------------------|------------|-------------|
| Length | 14 m | 46' |
| Diameter of body | 1.65 m | 5'5" |
| Take-off weight | 12,900 kg | 28,440lb |
| Payload | 1000 kg | 2205lb |
| High explosive carried | 750 kg | 1654lb |
| Alcohol (Contg 25% water) | 3965 kg | 8740lb |
| Liquid oxygen | 4970 kg | 10,957lb |
| Thrust at take-off | 25,000 kg | 55,100lb |
| Thrust gain near Brennschluss | 4200 kg | 13,230lb |
| Fuel consumption per second | 127 kg | 280lb |
| Alcohol / oxygen ratio in mixture | 0.81 | |
| Maximum burning time | 65 sec | |
| Temp in motor | ~2700° C | ~4890° F |
| Pressure in motor | 15.45 atm | 227 psi |
| Nozzle expansion ratio | 15.45:0.85 | |
| Exhaust velocity | 2050 m/sec | 6725 ft/sec |

References:

(Same as given under V-1).
(See illustration below).





FZG 76 "V-1" FLYING BOMB

V-1 und V-2 (Explosives Used in Warheads of). At first both the V-1 and the V-2 used mixtures of TNT and Am nitrate. These were replaced by Amatol 39 (DNB 50, Am nitrate 35 and RDX 15%) or by Amatol 40 (Dinitroanisole 50, Am nitrate 35 and RDX 15%). While Amatol 40 was suitable for cast-loading, the Amatol 39 gave occasional cavities when cast-loaded alone.

In order to eliminate the cavities in cast-loading, Römer proposed later to pour the Amatol 39 over pieces of Biscuit Mixture A which consisted of Am nitrate 50, technical Ca nitrate 25, PETN 10 and RDX 15%.

Still later in the war, when the shortage of aromatic compounds became more acute than ever, it was proposed to use mixtures not containing the nitroaromatics, as for instance: technical Ca nitrate 55, powdered peat 5, Al powder 10 and 30% of 90:10 methyl nitrate/benzene mixture, called Myrol (q.v.).

Reference: G. Römer, PBL Rept 85,160 (1946), p 19.

V-1 und V-2 (Propellants Used in) As was mentioned under Rocket Propellants (Liquid), the Germans used compressed air as the oxidizer and gasoline as the fuel in the V-1. For the V-2 rocket they used liquid oxygen as the oxidizer and ethanol containing some water as the fuel.

Note: According to J.G. Tschinkel, Chem Engrg News 32, 2584 (1954), water was added to alcohol in order to keep the flame temperature as low as possible to avoid damage to the combustion chamber of the rocket motor. For the same reason fuels of higher heating values, such as gasoline, were not used in these rockets. It was found that a mixture of alcohol and 25% water had a flame temperature 7% lower than pure alcohol while its exhaust velocity was only 3.5% lower. This means that on adding 25% of water to alcohol, it was possible to use a somewhat lower structural strength for the motor without sacrificing too much in performance. The same author on p 2585 states that in 1944 preparations were made to replace liquid oxygen in the V-2 with absolute nitric acid.

V-3 (Vergeltungswaffe Drei). See Hochdruckpumpe.

V-22 Delay - Igniter Unit was used in type 1 of the 15 cm RSSG Rocket, briefly described under "Pyrotechnic Antipathfinder Devices". The V-22 consisted of a steel tube filled with delay composition, and was screwed into the rocket chamber head. The hot gases from the burning propellant ignited the delay composition which burned for 22 + 1 seconds under a pressure of about 200 atmospheres. When the delay had burned through, a shallow dish-like structure containing the black powder expelling charge was ignited. The delay compositions which were employed were actually tracer compositions, e.g. Sr nitrate 55.1, Sr carbonate 5.0, Mg (coarse) 17.6, CPVC (chlorinated polyvinyl chloride) with 63% chlorine 9.3, synthetic phenol-formaldehyde resin 10.0 and rosin 3.0%.

Note: All Mg (coarse) had to pass through a sieve with 1 mm openings (No 16) and be retained on a sieve with 0.15 mm openings (No 100), while 60% was required to be retained on a sieve with 0.5 mm openings (No 30). The type of CPVC containing 63% Cl was called Igellit PCU.

Reference: H.J. Eppig, CIOS Report 32-56 (1945), pp 19-21.

Verbrennungswärme (Heat of Explosion). See general section.

Vernichtung von Sprengstoffen und Pulvern (Destruction of Explosives and Propellants), Beseitigung oder Un-

schädlichmachung von Explosivstoffen (Eliminating or Making Explosives Harmless). See general section under individual explosives.

Verpuffungstemperaturprobe (Deflagration Temperature Test), Entzündungspunktprobe (Ignition Point Test) is described in the general section under Ignition Temperature Test and also in the following references:

- 1) A. Stettbacher, Schiess- und Sprengstoffe (1933), pp 373-5
- 2) Kast-Metz, Chemische Untersuchung der Spreng- und Zündstoffe (1947), pp 341-345
- 3) A. Stettbacher, Spreng- und Schiessstoffe (1948), p 120.

Verstärktes Chromammonit (Reinforced Chromammonite). One of the safety explosives in which TNT was the active base: TNT 12.5, Am nitrate 70.0, K nitrate 10.0, Am chrome alum 7.0 and vaseline 6.5% (Total adds to 106%).

Reference: Colver, High Explosives (1910), p 250.

Versuchsgrube GmbH, Tremonia. Experimental Mine at Dortmund, located previously to 1943 at Hibernia Mine, Gelsenkirchen, was used for the investigation of mining explosives, such as methods of stemming in bore holes, ignition of gas and coal dust, relative safety of sheathed explosives, photographic study of flames produced at the bore-hole mouth by different explosives with various methods of loading, etc.

Reference: BIOS Final Rept 1266 (1947), pp 3-4.

Versuchstrecke (Testing Gallery). See Schlagwetterversuchstrecke and also the general section under Galleries, Testing.

Versuchstrecke, Dortmund-Derne (Testing Gallery at Dortmund-Derne) was used for the following official tests of permitted explosives (Wettersprengstoffe):

- a) Trauzl block Test. The maximum expansion allowable for permissible explosives was 240 cc for a 10 g sample initiated by a No 8 cap
- b) Gap Test (Detonationsübertragung). The minimum acceptable gap was 20 mm when testing cartridges of 35 mm diameter were initiated by No 8 caps. Nearly all permissible explosives had much higher gap values than 20 mm and the sheathed explosives usually gave a value of 300 mm due to the sensitivity of the sheathing which contained about 15% of NG
- c) Ability to Transmit Detonation (Detonationsfähigkeit) was determined by the so-called "Four Cartridge Test" (q.v.)
- d) Power of Detonators was formerly determined in a type of ballistic pendulum. Only No 8 detonators were allowed to be used in coal mines. The usual filling for such detonators was: 0.75 g tetryl and 0.5 g MF or 0.3 g L A / L St mixture
- e) Gallery Tests were conducted with methane-air mixtures and with coal dust.

Reference: BIOS Final Rept 1266 (1947), pp 1-3.

Vinidur. Code name for polyvinyl chloride without plasticizers (CIOS Rept 21-3, pp 5-6 and CIOS Rept 28-62, p 24).

Vinoflex oder Igellit PC. Highly chlorinated (65%) polyvinyl chloride (CIOS Rept 28-62, p 24).

Visol. Trade name for a liquid rocket fuel (Brennstoffe) of variable composition, such as:

- a) Vinylethyl ether straight or mixed with some aniline to promote combustion. When used in liquid rocket propellants (such as for Wasserfall) in the proportion of 0.23 parts of Visol per one part of 100% nitric acid, the theoretical specific impulse was 214 lb/lb/sec (Ref 1).

Note: Visol forms with strong nitric acid a hypergolic (self-igniting) combination.

- b) Vinyl ether (see Note) 40, iso-propyl alcohol 40, water 2. The remaining 18% consisted of four other ingredients including 1% of a dope to control the ignition

delay time (Ref 2).

Note: Vinyl ether of item b) is apparently vinylisobutyl ether, as on the same page of Ref 2 the statement is made that "Visol is a contracted code name for vinylisobutylether".

a) Visol 6 (See next item).

References:

- 1) Gollin, Rockets and Directed Missiles, CIOS Report 28-50 (1945), p 19
- 2) Anon, German Explosive Ordnance, TM 9-1985-2 (1953), p 220.

Visol 6. Trade name for Vinylethylether, described in the general section. It was used during WW II as a liquid rocket propelling fuel in guided missiles such as Enzian E-1, Rheintochter R-3 and Wasserfall. Absolute nitric acid was used in these missiles as the oxygen carrier.

References:

- 1) Anon, Army Ordnance 31, 30 (1946) (Wasserfall)
- 2) K.W. Gatland, Development of Guided Missiles, N.Y. (1952), 114-27.

Volpert of Dortmund patented in 1896 and 1897 several mining explosives, such as: a) K nitrate 40, NG 30, colloid cotton 1, Mg sulfate cryst 24, turpentine 4, and soda-ash 1%; b) K pyrosulfate ($K_2S_2O_7$) 7.5, Am nitrate 82.5, naphthalene 5.0 and ferrocyanide 5.0%.

Reference: J. Daniel, Dictionnaire des Matieres Explosives, Paris (1902), p 789.

VonDahmen Explosives. See Dahmen Explosives and also Dahmenites.

VonStubenrauch Explosives. See Stubenrauch Explosives.

Vorkortusche (Forward Charge). See under Cordite Charge Casings.

Vorlage (Antiflash Bag) (Literally "something put before"). According to Davis, Explosives (1943), p 324, the Vorlage used during WW I consisted of doughnut shaped cotton or artificial silk cloth bags filled with coarsely pulverized K chloride. Two such bags were usually placed in a cannon between the base of the projectile and the propellant charge.

In firing with Vorlage there were produced at the muzzle a red light (glow) and a red smoke. The light gave no reflection in the sky but was visible if the piece was placed in such a way that the enemy could see its muzzle. In the daytime, the Vorlage was used only when the weather was so dark that the flashes of the gun without Vorlage were more visible than the clouds of reddish smoke produced by the Vorlage.

"Vulkan". A fibrous material prepared by hydrating a cellulose with Zn chloride. It was used for self-sealing gasoline tanks.

Reference: CIOS Report 21-3 (1945), p 4.

Wachsender Drall oder Zunehmender Drall. See Progressive Rifling.

Waffen. See Weapons.

Waffenträger (Weapons Carrier). Several models of armored vehicles designed for carrying field guns were developed during WW II by the firms Krupp, Steyr, Rheinmetall-Borsig, etc.

Reference: CIOS Report 29-20 (1946).

Walsrode (Pulver). A type of sporting propellant manufactured for many years by the Wolff Co at Walsrode in Germany and by the Chilworth Gunpowder Co, Ltd in England. The original propellant was prepd by gelatinizing pure NC with ethyl acetate and adding water (25% of total volume) to the resulting jelly. Then the mixture was kneaded and, while continuing this operation, live steam was introduced. This resulted in the formation of very small grains of gelatinized NC. For removal of volatile solvent, the grains were treated under pressure with boiling water and then dried (Ref 1). The composition of such a propellant, given in Refs 2 and 4, was as follows: NC 98.6 and volatile matter 1.4%; its calorific value was 1014 kcal/kg and volume of gas at NTP 875 l/kg of which 14.8% was nitrogen.

A different composition for Walsrode was given in Ref 3: guncotton 77, Ba nitrate 10, grease 7.0, agar-agar 3.0, glue 2.0 and moisture 1.0%.

References:

- 1) J. Daniel, Dictionnaire des Matieres Explosives, Dunod, Paris (1902), pp 801-2
- 2) A. Marshall, Explosives, Churchill, London, v1 (1917) p 327
- 3) H. Brunswig, Das rauchlose Pulver, W. de Gruyter, Berlin (1926), p 134
- 4) Thorpe's Dictionary of Applied Chemistry, Longmans Green, London, v4 (1940), p 530.

Walter Explosives. See Explosives Developed by H. Walter et al.

Walter Submarine. See U-Hoot Walter.

Walther Cold Rocket Unit, such as used in the Hecht surface launcher rocket, used hydrogen peroxide/per-manganate as the propellant. No details are given. Reference: K.W. Gatland, Development of the Guided Missile, "Flight", Publication, London (1952), p 117.

Warmlogerversuch (Warm Storage Test), called also Lagerbeständigkeit oder Haltbarkeit (Stability in Storage or Stability) is a test similar to the American Surveillance Test. It was conducted by storing a 10g sample of a propellant (or an explosive) at a temp of 75° or higher in a closed glass vessel until the appearance of nitrogen oxide fumes. The longer the time required for the appearance of fumes (which might be from several days to several weeks) the more stable was considered the substance under test.

Other Stability Tests are given in the general section References:

- 1) Stettbacher, Schiess- und Sprengstoffe (1933), p 201
- 2) Kasz-Metz, Chemische Untersuchung, etc (1944), p 258.

WARPLANTS, ARSENALS, RESEARCH CENTERS, PROVING GROUNDS, etc.

(In collaboration with H.A. Tisch of Picatinny Arsenal)

This review includes both Government and private installations as complete as war possible to obtain from the literature and BIOS, CIOS and PB reports.

War plants were usually constructed in a forest with a minimum removal of trees. Buildings were of permanent and fire-proof construction such as reinforced concrete with one weaker side for blast escape. Quantities of explosives permitted in buildings were usually greater and the interdistances less than permitted by American and British regulations. The floors in the buildings were rather rough, but they were kept clean by frequent sweeping. No overshoes or powder shoes were worn by workers.

In the enclosed alphabetical list are included numerous plants and institutions more or less connected with armament during WW II. Majority of these institutions are closed or are out of existence but many of them can be reopened.

- 1) Adam und Horn Sprengstoff Fabriken. Plant at Karlsee (Explosives)
- 1a) Adam Gerhard Motorenwerke, Oskan-Friedrichsöon, Sudetengau (Motors)
- 1b) AEG. See Allgemeine Elektrizitäts Gesellschaft
- 2) Aerodynamische Versuchsanstalt (AVA), Kaiser Wilhelm Institut, Göttingen (Aerodynamic research). (See CIOS 25-22 and Ref 4a, pp 75 & 131)
- 3a) A-G des Altenbergs für Bergbau- und Zinkhüttenbetrieb, Essen/Bergeborbeck (Contact and chamber sulfuric acid plants) (BIOS 1639)
- 3b) Air Force Proving Ground. See Waffenprüfungsstelle der Luftwaffe
- 3c) Akademie der Luftfahrtforschung (ALF), Berlin. Academy of Aircraft Research (Scientific institution with elective membership). It promoted research in many fields of science (Ref 4a, p 78)
- 3d) A. Krupp Berndorfer Metallwarenfabrik (Weapons)
- 4a) ALF. See Akademie der Luftfahrtforschung.
- 4b) Alfred Krupp, Essen/Borbeck (Steel foundries) (See BIOS Final Rept 716)
- 5) Allgemeine Elektrizitäts-Gesellschaft (AEG), Berlin (Electrical equipment, cables, rockets, etc)
- 6) Amag, Hilpert, Pegnitzhütte A-G, Nürnberg (Acid plant equipment)
- 7) Anschütz & Co, Kiel (Radar, bomb sights, submarine instruments and equipment) (See CIOS 25-39)
- 8) Anschütz (IG), Zella Mehlis, Thüringen. (Small arms)
- 9a) Ardelt Werke, Eberswalde Breslau (Machinery)
- 9b) Army Proving Grounds. See Waffenprüfungstellen des Heeres
- 10) Arthur Krupp A-G. See Berndorfer Metallwarenfabrik Arthur Krupp A-G
- 11) Aschaffener Zellstoffwerke A-G, Stockstadt am Main (Wood pulp, utilization of the black liquors from the sulfite boils for the manufacture of ethanol and yeast, various chemicals) (See CIOS 26-34)
- 12) August Engels, Velbert, Rheinland (Steel foundries) (See BIOS 716)
- 13a) August Thyssen Hütte A-G, Hamborn (Metallurgy)
- 13b) AVA. See Aerodynamische Versuchsanstalt
- 14) Badische Anilin- & Sodafabrik A-G (BASF), Oppau bei Ludwigshafen a/R (Various chemicals including some explosives) (BIOS 1442, p 8)
- 15) Badische Wolframerz GmbH, Söllingen bei Karlsruhe (Ferro-alloys) (CIOS 30-55)
- 16) Bamag-Mequin A-G, Berlin (Design and construction of chemical plants) (BIOS 1442, pp 110-17)
- 17a) BASF. See Badische Anilin- & Sodafabrik A-G
- 17b) Bayerische Maschinenwerke (BMW), bei München. (Research and development of rockets using as fuel hydrazine and some amines and as oxygen carrier concd nitric acid contg about 10% sulfuric acid. The fuel was known as Tonko and the acid as Solbei) (See CIOS 28-56, pp 25-26)
- 18) Bayerische Sprengstoffwerke und Chemische Fabriken A-G, Nürnberg. Plants at Kloster, Lechfeld, Neumarkt and Parsberg (Miscellaneous chemicals and explosives)
- 19) Bayerische Stickstoff A-G, Piesteritz (Nitric acid) Note: According to BIOS 889 the plant was transferred to Russia
- 20) Becker & Holländer Waffenbau, Suhl (Small arms)
- 21) Berckholtz (J.G.W.), Hamburg/Bahrenfeld (Various pyrotechnic items) (BIOS 1233)
- 22) Bergbau A-G, Lothringen/Blankenburg, Harz (Cast iron and steel projectiles) (CIOS 28-63)
- 23) Bergbauprengstoff- und Zündmittelwerk, Schönebeck Elbe (Electric blasting caps)
- 24) Bergische Stahlindustrie, Remscheid (Steel foundries) (BIOS 716)
- 25) Bergmann Industrie Werke, Abteilung Waffenbau, Suhl und Weltena/Main (Small arms)
- 26) Bergwerksgesellschaft Hibernia A-G Stickstoffwerke Wanne - Eickel (Nitric acid) (BIOS 1442, p 29)
- 27) Berliner-Lübecker Maschinenfabriken (BLM), Lübeck (Small arms and artillery) (CIOS 3-40)
- 28) Berlin-Suhler Waffen- und Fahrzeugwerke (BSW) Berlin, Suhl und Weimar (Small arms)
- 29) Berndorfer Metallwarenfabrik Arthur Krupp A-G, Berndorf, Niederdonau (Weapons and ammunition)
- 30a) Berzelius Metallhütten GmbH, Duisburg/Wanheim (Sulfuric acid) (BIOS 1636)
- 30b) BLM. See Berliner-Lübecker Maschinenfabriken
- 31a) BMW. See Bayerische Maschinenwerke
- 31b) Blumberg & Co, Lintorf bei Düsseldorf (Various pyrotechnic items) (BIOS 1313)
- 32) Bochumerverein A-G, Bochum, Ruhr with several plants, such as:
 - a) Bochum (Metallurgy, centrifugal casting of gun tubes)
 - b) Weitmar (Metallurgy) (See BIOS 716 and CIOS 27-42 and 29-39)
- 33) Böhmsche Waffenfabrik. See Československa Sbrojovka Strakonitz in the Czechoslovakian section
- 34) Bothe (W), Wolfenbüttel, Heimstättenweg (Blasting machines)
- 35) Brown-Boveri & Cie A-G Mannheim (Electricity)
- 36) Brücker & Zinke Zündschnurfabrik, Meissen (Safety fuses)
- 37) Brück, Schlösser & Co, Osnabrück (Apparatus for testing explosives by the methods of Bichel and Mettegang)
- 38a) BSW. See Berlin-Suhler Waffen- und Fahrzeugwerke
- 38b) Buck. See Hans Buck
- 39) Buderich Werke, Germany (of Gebrüder Böhler A-G, Wien, Austria) (High quality steel) (CIOS 25-14)
- 40) Buderus Eisenwerke, Weimar (Centrifugal casting of gun tubes) (CIOS 29-39)
- 41) Burberg (Gebrüder) GmbH Maschinenfabrik, Mettmann, bei Düsseldorf (Installations for the manufacture of explosives, propellants and ammunition)
- 42a) Büscher - Gewehre, Zella Mehlis, Thüringen (Small arms)
- 42b) Busch - Jäger Lüdenscheider Metallwerke A-G, Lüdenscheid, Westfalen (Ammunition)
- 43) Büssing - NAG Vereinigte Nutzkraftwagen GmbH, Braunschweig. Several metallurgical plants, which employed during WW II up to 5500 workers nearly half of them foreigners (CIOS 28-46, p 13)
- 44) Carbonit A-G, Hamburg. Plant at Schlebusch (Explosives)
- 45) Carl Fleming, Hamburg-Neugraben (Ground and ship pyrotechnic signals). Plant was destroyed
- 46) Chemische Düngstoffabrik, Rendsburg (Sulfuric acid) (BIOS 1642)
- 47) Chemische Fabrik Kalk GmbH, Köln/Kalk, founded in 1857 (Acids and inorganic chemicals) (BIOS 1442, p 105)
- 48) Chemische Fabrik Wesseling A-G, Wesseling, bei Köln (Sulfuric acid) (BIOS 1644)
- 49) Chemische Werke A-G, Thansau (Chemicals and explosives)
- 50) Chemisch-physikalische Versuchsanstalt (CPVA) der Kriegsmarine, Daenisch Nienhof (Navy physico-chemical research institute) (See CIOS 33-2 and 33-66)
- 51) Chemisch-technische Reichsanstalt, vormals Militärversuchsanstalt (Research and development institution for Armed Forces)
- 52a) Consolidierte Alkaliwerke, Westregeln (Chemicals and explosives)

- 52b) CPAA. See Chemisch-technische Versuchsanstalt
- 54) Daimler Benz Werke, Berlin Marienfelde (Tanks and other military vehicles) (CIOS 32-33). Plants are located at Untertürkheim, Gaggenau and Mannheim
- 54a) Degussa, Frankfurt a/M. Plant at Hanau a/M (Sintered iron and steel components) (BIOS 595)
- 55) Demag A-G, Duisburg (Machinery and mechanical equipment) (CIOS 26-77)
- 56) Deutscher Pulverfabrik Kunigunde. Plant at Othfresen (Explosives)
- 57) Deutsche Cahusitwerke A-G, Gnaschwitz bei Bautzen (Dynamites, permissible explosives, blasting explosives, propellants and fuses)
- 58) Deutsche Edelstahlwerke A-G, Krefeld (Metallurgy centrifugal casting, etc) (CIOS 24-28, 25-38 and 29-39)
- 59) Deutsche Eisenwerke A-G, Hilden, Rhineland and Mülheim Ruhr (Metallurgy) (BIOS 716 and CIOS 29-39)
- 60) Deutsche Forschungsanstalt für Segelflug (DFS) Airing (German Glider Research Station) (Guided missiles) (CIOS 32-66 and Ref in, pp 7-11 & 76)
- 61a) Deutsche Metallwerke C. Ebeling A-G, Berlin/Niederschöneweide (Ammunition)
- 61b) Deutsche Präzisionswerke GmbH, Ettlingen (Industrial explosives)
- 62) Deutsche Pulvermetallurgische Gesellschaft, (DPG), Frankfurt a/Main (Sintered iron and steel ammunition and weapon components)
- 63a) Deutsche Pyrotechnische Fabriken GmbH. Plants at Clebronn in Württemberg; Kieselbach, Kremen and Neumarkt in Oberpfalz (Various pyrotechnic items) (CIOS 32-38)
- 63b) Deutsche Röhrenwerke A-G, Mülheim (Weapons and ammunition)
- 64) Deutsche Sprengchemie GmbH, Berlin/Zehlendorf with plants at:
- Dreetz (Propellants)
 - Forst, Brandenburg (Propellants)
 - Klietz (Propellants)
 - Kraiburg (NG, DEGDN, Nipolit, etc)
 - Moschwig (NC propellants)
 - Oderburg (Solventless propellants)
 - Torgelow (Propellants)
- 65) Deutsche Sprengkapseln Fabrik, Köln (Blasting caps)
- 66) Deutsche Sprengstoff A-G, Hamburg. Plant at Wahn (Commercial explosives)
- 67a) Deutsche Versuchsanstalt (DVA) für Kraftfahrzeug und Fahrzeugmotoren, Berlin (Research and development on motor vehicles, motors etc)
- 67b) Deutsche Versuchsanstalt für Luftfahrt (DVL) (German Experimental Establishment for Flying). It was established in 1915 and during WW II there were about 2000 people employed. Its ballistics division at Gatow was led by Schardin (Ref 4a, pp 71, 75 & 79)
- 68) Deutsche Waffen- und Munitionsfabriken (DWM) A-G, Karlsruhe and Berlin/Borsigwalde (Formerly Berlin-Karlsruhe Industrie Werke). Several plants, such as at Posen and Schültrup bei Lübeck (Various weapons and ammunition). Research was conducted at the Forschungsanstalt, Lübeck (See CIOS Reports 30-71 and 33-20)
- 69) Deutsche Werke A-G, Erfurt (Small arms)
- 70a) Deutsches Zündwaren - Monopolgesellschaft, Berlin (Ignition and initiation devices). Also at Lüneburg (Pyrotechnic items) (BIOS Final Rept 1313)
- 70b) DFS. See Deutsche Forschungsanstalt für Segelflug
- 71) DIZ Chemie-Abteilung Sprengstoffe, Berlin (Explosives, primers, initiators, safety fuses, sporting ammunition, pyrotechnic devices, etc)
- 72) Dornheim (G.C.) A-G, Suhl (Small arms)
- 73a) Dortmund-Derne Testing Gallery. See Versuchsstrecke Dortmund/Derne
- 73b) DPG. See Deutsche Pulvermetallurgische Gesellschaft
- 74a) Draghan. See Fabrik Draghan
- 74b) Draht- und Metallwarenfabrik, GmbH, Salzwedel (Ammunition)
- 75a) Dr Alexander Wacker Gesellschaft für Elektrochemische Industrie, Burghausen (Chemicals from acetylene) (CIOS 25-26)
- 75b) Dresdner Dynamit Fabrik, Dresden. Plant at Muldenhütten (Commercial explosives)
- 76a) DVA. See Deutsche Versuchsanstalt für Kraftfahrzeug
- 76b) DVL. See Deutsche Versuchsanstalt für Luftfahrt
- 76c) DWM. See Deutsche Waffen- und Munitionsfabriken A-G
- 77) Dynamit Aktiengesellschaft (DA-G or DAG) formerly Altra Nobel & Co. Head office at Troisdorf, Bez Köln with plants at:
- Adolfshütte, bei Heilbronn (Black powder) (CIOS 32-38)
 - Bergensdorf (Industrial explosives)
 - Böhlitz-Ehrenberg, bei Leipzig (Glycerin and other chemicals) (CIOS 32-38)
 - Draghan, Danneberg (TNT, industrial explosives, ammunition loading safety fuses, etc)
 - Düneberg a/d Elbe, bei Geestacht, Bez Hamburg, founded in 1880. During WW II the plant occupied an area of 1.8 sq miles and employed up to 8000 workers, many of them foreigners. The personnel of the plant developed (in collaboration with General Uto Gallwitz) various "cool" propellants. (See G Pulver and Gudolpulver)
Most of these new propellants were manu'd at Düneberg
No acids, NC, NG nor DEGDN were manu'd at Düneberg. The NC-NG or NC-DEGDN mixtures were received from the Krümmel plant in the form of Rohpulvermasse and blended at Düneberg by passing through hot rolls (See CIOS Reports 28-61, 29-24 & 31-68 and PB Rept 925)
 - Empelde, bei Hannover (Ammunition for Flak, Pak and infantry) (CIOS 32-38)
 - Förde an der Lenne, Grevenbrück, Westfalen (Safety fuses, blasting caps and detonators) (CIOS 32-38)
 - Hamm a/d Sieg (Black powder) (CIOS 32-38)
 - Hasloch, Baden (Propellants and cartridges for small arms)
 - Kaufbeuren bei Landsberg/Lech (NC propellants, blasting caps, detonators and ammunition loading)
Note: According to CIOS Repts 29-28 and 32-38, the Kaufbeuren plant belonged to the Dynamit A-G Subsidiary
 - Krümmel Post Geestacht, Bez Hamburg, founded in 1865 by A. Nobel and then enlarged during both WW's. During WW II it occupied 1.6 sq miles and employed up to 9000 workers, many of them foreigners
Work at this plant included some ammunition loading and the production of TNT, PETN, NC, NG, DEGDN, TEGIN, R1X, metrial trinitrate, industrial explosives, plastics, nitric acid, sulfuric acid and Rohpulvermasse. The last item was shipped to the Düneberg plant for manufacture of POL (solventless propellant)
The RDX branch of Krümmel plant was damaged in 1943 and production of RDX was stopped (See CIOS Repts 28-61 & 29-24 and PB Rept 925)
 - Nürnberg (Steel case small arms ammunition, hunting and sporting ammo and pyrotechnic items) (CIOS 27-36 and 32-38)
 - Reichsweiler, Elsass (Small arms ammunition)
 - Rottweil, Schwarzwald, founded in 1872 as a black powder factory, was changed over, prior to WW I, to single-base propellants. The plant was considerably expanded in 1939 and manu'd large amounts of small arms propellants
Note: This plant seems to be identical with the Troisdorf A-G plant described in CIOS Rept 26-70
 - Saarwellingen, Kr Saarlautern (Industrial explosives) (CIOS 32-38)
 - Schleibusch, Leverkusen, bei Köln (TNT, NC, NG, PETN, P A, M F, L A, oleum and industrial explosives) (CIOS Repts 24-4, 29-24 and 32-38)
 - Stadeln (Steel case small arms ammo, L A, L St, detonators, hunting and sporting ammunition) (CIOS 27-36 and 32-38)

- s) Troisdorf, Bez Köln, parent plant of DA-G constructed at the end of the 19th century, was considerably expanded before WW II. At the peak of production it employed up to 10,000 workers of whom 2,000 were foreigners. The plant was severely damaged in 1944 and 1945 by bombs. Following items were manufd during WW II: NC, PETN, tetryl, azides, blasting explosives, permissible explosives, initiating compositions, delay and electric detonators, propellants, fuses and luzes (See BIOS Final Rept 644 and CIOS Rept 24-3 and 32-38)
- t) Würgendorf, Burbach, Kr Siegen (Industrial explosives) (CIOS 32-38)
- 78) Dynamit A-G Subsidiary, called GmbH zur Verwertung chemischer Erzeugnisse, formed in 1943 by combining the resources of Dynamit A-G with those of OKII (Oberkommando Heereswaffenamt), had the following plants:
- a) Allendorf, bei Kirchhain, Kreis Marburg, Lahn (TNT, sulfuric anhydride from spent sulfuric acid and ammunition loading) (CIOS 32-38)
- b) Aschau, bei Mühlendorf a/Inn, Obb (Nitrocellulose) (CIOS 32-38)
- c) Bobingen, bei Augsburg (Hexogen by KA process) (Fairly detailed description is given in CIOS Rept 32-8)
- d) Bromberg, Westpreussen (DNB, TNT, NC, NG, DEGDN, solventless propellants, ammunition loading, oleum from spent sulfuric acid, etc) (CIOS 32-38)
- e) Christianstadt am Bober, covered during WW II about 6 1/2 sq miles and employed about 7000 workers many of whom were foreigners (Formaldehyde, hexogen, NC, NGU, Man-Salz, Myrol, Tetra-Salz and loading of bombs and small caliber shells) (See CIOS Rept 32-38)
- Note: CIOS Rept 28-61 lists this plant as belonging to the Dynamit A-G
- f) Clausthal-Zellerfeld, Harz was heavily damaged in 1944 (TNT and shell loading)
- g) Döberitz a/d Havel, Westhavelland (Hexogen, hexamine and NGU)
- h) Dömitz, a/d Elbe (Picric acid, TNT, propellants and ammunition loading)
- i) Ebenhausen, bei Ingolstadt und München, constructed in 1914, was destroyed in 1945 except for the propellant section. It manufd NC and solvent propellants (CIOS 32-38)
- j) Glöwen, westpriegnitz Havel, originally designed as a NC plant, was manufacturing during WW II some initiating items. Was severely damaged in 1945 (CIOS 32-38)
- k) Grünberg, Schlesien (Detonators) (CIOS 32-38)
- l) Güssen, Bez Magdeburg (NC, TNT and loading of bombs and shells) (CIOS 32-38)
- m) Hertine, bei Töplitz Schönau (Loading of bombs and mines) (CIOS 32-38)
- n) Herzberg, Südharz (Loading of bombs and mines). Was completely destroyed by bombs in 1945 (CIOS 32-38)
- o) Hessisch-Lichtenau, Bez Kassel (Picric acid, TNT, oleum from spent sulfuric acid and loading of bombs and shells) (CIOS 32-38)
- Note: It also operated a plant at Eschenstruth.
- p) Hohensaaten at Neudorf a/d Oder, Mark-Brandenburg (NC, NG and experimental station)
- q) Kaufbeuren. See item (j) under Dynamit A-G
- r) Kaufering, bei Augsburg Land (NC and mortar shell cartridges)
- t) Kuchelna, bei Ratibor (Loading of small bombs and shells) (CIOS 32-38)
- u) Ludwigsdorf, Kr Glatz (Press-loading of ammunition) (CIOS 32-38)
- v) Malchow, bei Zaaren, Mecklenburg (PETN, trinitroresorcin, blasting caps, detonating fuse, etc) (CIOS 32-38)
- w) Malmitz, Kr Sprottau, Schlesien (Loading of small bombs and shells) (CIOS 32-38)
- x) München, Bayern (Fuzes, such as Uhrwerkzunder for Flak 2.8 cm Was severely damaged in 1943, 1944 and 1945 by bombs.)
- y) Petersdorf Schlesien (Loading of small bombs and shells) (CIOS 32-38)
- z₁) Premnitz a/d Oder (Ammunition loading)
- z₂) Ückermünde, bei Stettin, Pommern (NC, NGU, ammunition loading and experimental station)
- z₃) Woltratshausen, bei München, Bayern (I. A, L St., tetracene, PETN, blasting caps, detonators and loading of some small caliber shells)
- 79a) Eckert & Ziegler GmbH, Köln-Braunfeld (Explosives) (CIOS Rept 32-38)
- 79b) Egerländer Stahlindustrie, Rothau (Centrifugal casting of gun tubes) (CIOS Rept 29-39)
- 79c) Eiba GmbH, Benefeld bei Bömlitz (NG by continuous method, explosive compositions and propellants)
- 79d) Eichhorn (Karl) Waffentabrik, Solingen (Small arms)
- 80a) Eisenacher Karosseriefabrik Assmann GmbH, Eisenach (Weapons)
- 80b) Eisen- und Hüttenwerke Bochum, Ruhr (Metallurgy)
- 80c) Eisenwerke A-G, Kaiserlautern (Metallurgy)
- 81) Eisenwerke Oberdonau. See in Austrian section
- 82) Eisfeld, (J.F.) Pulver- und Pyrotechnische Fabriken GmbH, Plant at Silberhütte, Anhalt, founded in 1790, manufd black powder and various pyrotechnic items, while plant at Kunigunde manufd only black powder (CIOS 32-38)
- 83) Elektrochemische Werke, Höllriegelskreuth (Hydrogen peroxide) (CIOS 25-44)
- 84) Elektromechanische Werke, Peenemünde with branches at Anklam, Kummersdorf, Bodensee (Lake Constance) and Bleicherode, Harz (Rockets and guided missiles using liquid propellants)
- 85) Elektro-Nitrum A-G, Rhina, bei Kleinlautenburg, Baden (Nitric acid) (BIOS 1442, p 48)
- 86a) Elektro Schmelzwerke A-G, Kempten, Allgäu, Bayern (Metallurgy) (CIOS 26-35)
- 86b) Embsen Fabrik. See under IG Farbenindustrie
- 87) Erfurter Laden Industrie, Erfurt, Nord (Ammunition)
- 88) "Erma". See Geipel (B) GmbH
- 89) Ernest Brünn GmbH Zünderwerke, Krefeld/Linn (Equipment for electrical priming and initiation, such as the "Untertag" blasting machines)
- 90) "E" Stelle, Travemünde (Air Forces research center and experimental station)
- 91) Eumuco A-G, Leverkusen - Schlebusch (Designers, manufacturers and users of "Eumuco" shell forging press) (BIOS 668)
- 92) Fabrik Aschau. See item (b) under Dynamit A-G Subsidiary
- 93) Fabrik Dragahn der Waren-Commissions A-G a/d Elbe, bei Dannenberg (TNT, detonating fuse and filling some hand grenades) (CIOS 32-38)
- 94) Fabrik Elektrischer Zünder GmbH, Köln (Electric igniters, detonators and exploders)
- 95a) Felten, Guilleaume & Co, Köln/Kalk (Electrical equipment, cables)
- 95b) FEP. See Forschungserwicklung Patente
- 96a) Ferdinand Wicke, Wuppertal - Birnen (Pyrotechnic items including amorces) (BIOS Final Rept 1313)
- 96b) FFA. See Flugfunkforschungsanstalt
- 96c) FGZ. See Forschungsanstalt Graf Zeppelin
- 96d) Firmeninstitute were institutions of commercial firms engaged in research and development of ammunition, weapons, aircraft, tanks etc. The principal firms were: Krupp, Rheimetall-Borsig, DWM-Mauser, W. ASAG, Bergmann and Gustloff Werke (Ref 4a, pp 77-8 & 82)
- 96e) FKFS. See Forschungsinstitut für Kraftfahrzeuge
- 96f) Flugfunkforschungsanstalt (FFA), Oberpfaffenhofen, Bayern. Electrical research institute for high frequency (Radio control for guided missiles, radar, etc) (Ref 4a, p 76)
- 97a) FoFlü. See Forschungsführung
- 97b) FOGVA. Forschungsgesellschaft für Verfahrensaubau, Birkgit bei Bodenbach a/Elbe (Myrols, Tetrasalt, monopropellant rockets)
- 97c) Forschungsanstalt Graf Zeppelin (FGZ) Stuttgart/Ruit (Flight research institute)
- Note: This institute, also called I.G.Z. (Luftforschungsanstalt Graf Zeppelin, is described in Ref 4a, 24-33 & 76)
- 97d) Forschungsentwicklung Patente, Berlin. Navy institution engaged in research and development of patents suitable for military application (Ref 4, p 86)
- 97e) Forschungsführung (FoFlü), Berlin, (Research Directorate) was a unit governing all research and development organizations relative to the Air Force

- (Ref 4a, pp 71 & 75)
- 971) Forschungsinstitut für Kraftfahrzeuge und Flugmotoren, Stuttgart-Untertürkheim (FKFS). Institute for Automobile and Aircraft Motors (Research and development of various types of engines including the close-cycle type Daimler-Benz U-boat Diesel) (CIOS Repts 30-70, p 3 and Ref 4a, p 76)
- 98) Franz Stock Maschinen- und Werkzeugfabriken, Berlin (Machinery and weapons)
- 99) Friedrich - Alfred Hutte, Rheinhausen (Metallurgy) (CIOS 24-74)
- 100) Friedrich Krupp A-G, Essen, Ruhr. One of the world's largest organizations manufacturing guns, tanks, U-boats and other war items. Numerous plants, among them the following:
- Blankenburg (Metallurgy)
 - Bremen (Steel works)
 - Capito und Klein Werke, Düsseldorf/Beurath (Rolling mills)
 - Essen (Home plant) (Steel works and forging)
 - Gruenow, Magdeburg-Buckau (Tanks)
 - Kiel (Shipbuilding, U-boats)
 - Meppen (Proving ground)
- (See CIOS Repts 28-64, 28-66 and 30-93)
- 101) Fritz Kiess & Co, GmbH Waffenfabrik, Suhl (Weapons)
- 102) Fritz Wolf Gewehrfabrik, Zella Mehlis, Thüringen (Weapons)
- 103) Funk & Co, Suhl (Weapons)
- 104a) Gaswerke, Frankfurt a M (Sulfuric acid) (BIOS 16-45)
- 104b) Geba, Metallwarenfabrik, Breslau (Metallurgy)
- 105) Gebrüder Behler, Buderich Hurd, bei Düsseldorf (Steel forging) (CIOS 26-69)
- 106a) Geipel (B) GmbH Waffenfabrik "Erma", Erfurt (Weapons)
- 106b) Genschow. See Gustav Genschow
- 107) Georg von Gieschess' Erben, Magdeburg (Zinc mining and smelting, alloys, sulfuric acid) (CIOS 31-56)
- 108) Gewehrfabrik H. Burgmüller & Söhne GmbH, Kreienzen, Harz (Weapons)
- 109) Gewerkschaft Victor Chemische Werke, Castrop - Raukel, Westfalen (Nitric acid, Am nitrate, synthetic fuels by Fischer - Tropisch process, etc)
- 110) GmbH zur Verwertung chemischer Erzeugnisse. See Dynamit A-G Subsidiary
- 111a) Golzern - Grimma Maschinenbau A-G, Grimma bei Leipzig (Machinery for manuf of explosives, propellants and acids)
- 111b) Gottow Proving Ground was a station for testing explosives, guns and rockets (Ref 4a, p 85)
- 112a) Graf Zeppelin Flight Research Institute. See Forschungsanstalt Graf Zeppelin
- 112b) Grossfuss, Johannes. See Johannes Grossfuss
- 113) Guss-stahlwerke Wittmann, Hagen/Hasppe (Steel foundry) (BIOS 716)
- 114) Gustav Genschow & Co, A-G, Berlin. Plants at Berlin, Durlach, Hachenburg and Wolfartsweier bei Durlach (Hunting and sporting ammunition, rifle and pistol ammunition and leather articles) (CIOS 32-38)
- 115) Gustloff Werke at Meiningen, Suhl and Weimar (Weapons)
- 116) Gutehoffnungshütte A-G (vorm Haniel & Lueg), Düsseldorf, Grafenburg and Sternkrade (Steel foundry and shell forging) (BIOS Repts 668 and 716)
- 117) Hackethal Draht- und Kabelwerke A-G, Hannover (Wires, cables, etc) (CIOS 25-32)
- 118) Haniel (C.G) Waffen- und Fahrrad Fabrik, Suhl (Small arms)
- 119) Hans Boas' Nachfolger, Berlin (Apparatus for ballistic measurements)
- 120) Hans Buck, Geradstetten (Pyrotechnic items) (BIOS Final Rept 1233)
- 121) Hanseatische Apparaturbaugesellschaft, Kiel (Apparatus, instruments, ammunition loading)
- 122) Hasenclever A-G, Düsseldorf (Shell forging using "Eumuco" press)
- 123) Hechtenberg, (H) Maschinenfabrik, Düren, Rheinland (Installations for plants manufacturing explosives, ammunition and weapons)
- 124a) Heereswaffenamt (HWA) (Army Weapons Office)
- Berlin, organized before WW I under famous ballistician Carl Czernz, was in charge of production, procurement, testing and development of all Army weapons. During WW II it became part of the Ministerium Speer (qv) (Ministry of Armaments and War Production) named after its head. The following organizations were under HWA jurisdiction: Waffenamt Prüfwesen, Waffenforschung, Firmeninstitute, Hochschulinstitute and Waffenprüfungsstellen
- 124b) Heereszeugamt, Ingolstadt (Armed Forces Ordnance Office)
- 125) Heinrich Krieghoff Waffenfabrik, Suhl (Weapons, among them Luger - Parabellums and machine gun FG-42)
- 126a) Heinrich Reining GmbH, Enger, Westfalen (Metallurgy, ammunition, chrome-plating of gun barrels, etc) (CIOS 32-64)
- 126b) Henckels Zwillingswerk, J.S.Schneid, Solingen (Ammunition)
- 127) Henschel und Sohn, Kassel transferred in 1943 to Hannover-Munden (Locomotives, trucks and tanks) (CIOS 28-46, p 18)
- 128) Herdersche (V) Pulverfabrik, Forchheim (Explosives and propellants)
- 129) Hermann Göring Aeronautical Research Institution. See Luftfahrtforschungsanstalt
- 130) Hermann Göring Organization controlled several plants, such as:
- Paul Pleigerhütte und Stahlwerke, Braunschweig (Steel works and weapons)
 - Salzgitter (Minerals and metals)
 - Wettenstedt (Shells)
- (See CIOS Repts 26-86, 29-30 & 30-84)
- 131a) Hermann Orth, Ludwigshafen/Oggersheim, Pfalz (Mixing and kneading devices for explosives plants)
- 131b) Hersteller Wehrauch, Zella Mehlis (HWZ) (Weapons)
- 132a) Hillersleben Proving Ground was one of the Army's weapon testing stations (Waffenprüfungsstellen des Heeres). It tested artillery weapons in connection with development work (Ref 4a, pp 84 & 130)
- Note: According to CIOS Rept 31-72 (1945), the small arms research section of Kammersdorf was transferred to Hillersleben in March 1945
- 132b) Hirsch Kupfer- und Messingwerk A-G, Finow/Mark (Ammunition)
- 133a) Hochfrequenz Tiegelstahl, Bochum, Ruhr (Steel foundry centrifugal casting etc) (BIOS Final Rept 716 and CIOS Repts 29-39 & 31-46)
- 133b) Hochschulinstitute (Institutes affiliated with technical colleges). These consisting of 200 establishments (as well as their governing body of twelve technical colleges) did research and development work for the Armed Forces. The technical colleges were located at: Berlin, Aachen, Braunschweig, Danzig, München, Karlsruhe, Wien, Dresden, Darmstadt, Graz, Hannover and Stuttgart (Ref 4a, pp 78, 82 & 85) (See also Reichsforschungsrat)
- 134) Holler (F.W.) Waffenfabrik, Solingen (Weapons)
- 135) Hösch A-G, Dortmund (Metallurgy, armor plates, projectile cases, steel cartridge cases and research) (CIOS 28-46 & 29-17)
- 136a) Hugo Schneider A-G, Tauscha-Leipzig (Metallurgy, copper, brass, aluminum, steel cartridge cases) (CIOS Repts 31-54 & 31-57). At Altenberg (Ammunition)
- 136b) HWA. See Heereswaffenamt
- 136c) HWZ. See Hersteller Wehrauch
- 137) IG Farbenindustrie A-G, Ludwigshafen, with numerous plants, among them:
- Bitterfeld - Süd (Nitric acid)
 - Elberfeld (Various chemicals)
 - Embsen, Kr Lüneburg (Nitric acid)
 - Frankfurt a/Main (Fuels, lubricants and weapons)
 - Herne-Solingen, (Ruhr), vorm "GAVEG" (Nitric acid)
 - Höchst a/Main (Nitric acid and other chemicals)
 - Leverkusen bei Köln (Acids and chemicals)
 - Lothringen Werke, Bochum - Gerthe (Nitric acid)
 - Mainkur Werke, Fechenheim (Various chemicals)
 - Oppau Werke, Ludwigshafen (Metallurgy and intermediates for explosives)
 - Wolfenfarbenfabrik bei Halle (Various chemicals,

- 176a) Maschinenfabrik Niedersachsen (MNI) GmbH, Hannover (Aircraft vehicles)
- 176b) Maschinenfabrik Peterson, Oldenburg, Holstein (Bombs, fuzes, pyrotechnic items, weapons and chemical warfare agents) (CIOS 32-13)
- 177) Maschinen für Massenverpackung GmbH, Schültrup bei Lübeck (Machinery and weapons) (CIOS 26-72)
- 178) Matter (O), Köln-Marienburg (Machinery for manufacture of explosives, propellants and ammunition)
- 179) Mouser Werke A-G (Waffenfabrik Mauser), Oberndorf a Neckar, with plants manufacturing various weapons located at:
- Berlin Borsigwalde (Spandau plant)
 - Karlsruhe
 - Köln Ehrenfeld
 - Oberndorf
 - Waldeck, Bez Kassel
- 180) Meissner. See Josef Meissner
- 181a) Meppen Proving Ground. See Waffenprüfungsstelle der Kriegsmarine
- 181b) Merz-Werke, Gebr Merz, Frankfurt a Main (Weapons)
- 182a) Metallgesellschaft, Rothenheimer Anlage, Frankfurt a Main (Sintered iron and steel components) (BIOS Final Rept 595)
- 182b) Metall-, Walz- und Plattierwarenfabrik, Pendericks-Auffermann A-G, **Oberbarmen Wuppertal** (Ammunition)
- 182c) Metallwarenfabrik Treuenbützen GmbH at Sebandushof and Selterhof (Ammunition)
- 182d) Metallwarenfabrik, vorm H. Wessmer A-G, Brotterode, Hessen (Ammunition)
- 182e) Metallwerke Fa Lunge A-G, at Aue/Sa and Bodenbach, Sud (Ammunition)
- 182f) Metallwerke Silberhütte, St Andre isberg (Ammunition)
- 182g) Metallwerk Treuenbützen at Belsig and Rüderhof (Ammunition)
- 182h) Metallwerk Wandhofen, Schwerte (Ammunition)
- 183a) MIAG. See Mühlenbau und Industrie A-G
- 183b) Miedziankit GmbH, Obemhof a/d Lahm (Industrial explosives)
- 183c) Ministerium Speer. Ministry named after its chief, was in charge of all German WW II production, allocation of all materials and allocation of all priorities. It exerted control over the Ordnance Department of the Army (Heereswaffenamt) and of the Navy (Marine (Kriegsmarine) Waffenamt) but it is not clear what relations it had with the Air Force (Luftwaffe), except that the Ministerium Speer was under partial control of Reichsmarschall Göring, the head of the Air Force (Ref 4a, p 68, 71 & 86). The Ministerium Speer exerted a considerable control over almost every government agency and toward the end of the war the Ministerium entered the management and prosecution of research. It established several research and development institutes of its own
- 184) Mitteldeutsche Sprengstoffwerke Miedziankit GmbH, Goslar Plant at Langelsheim (Industrial explosives)
- 185) MNI. See Maschinenfabrik Niedersachsen GmbH, Hannover
- 186) Möller & Schulze, Magdeburg (Machinery for chemical and explosives industry)
- 187) Mühlenbau und Industrie A-G (MIAG), Braunschweig, with several plants (Metallurgy, tanks, tank destroyers, trucks, etc) (CIOS 28-46)
- 188) Munitionsanstalt Cassel (Ammunition loading factory)
- 189) Munitionsanstalt Hannover (Ammunition loading factory)
- 190) Munitionsanstalt Ingolstadt (Ammunition loading factory)
- 191) Munitionsanstalt Jüterbog (Ammunition loading factory)
- 192) Munitionsanstalt Königsberg (Ammunition loading factory)
- 193) Munitionsanstalt Stettin (Ammunition loading factory)
- 194) Munitionsanstalt Zeitz (Ammunition loading factory)
- 195a) Nachrichten Versuchsanstalt (NVA), was an establishment developing and testing Naval radio devices (Ref 4a, p 86)
- 195b) Navy Proving Ground. See Waffenprüfungsstelle der Kriegsmarine
- 195c) Neufeldt und Künke, Kiel (Ammunition loading)
- 196a) Niebeckerwerke. See Austrian section
- 196b) Niebecker und Schumacher, Iserlohn, Westfalen (Ammunition)
- 197a) Norddeutsche Affiniere, Hamburg (Sulfuric acid by contact and Petersen tower methods) (BIOS 16-41)
- 197b) Norddeutsche Maschinenfabrik, Berlin (Weapons)
- 198a) Norddeutsche Sprengstoffwerke A-G, Hamburg, Plant at Quickborn (Explosives)
- 198b) NVA. See Nachrichten Versuchsanstalt
- 199) Opel A-G (Subsidiary of General Motors), Plant at Rüsselsheim, near Frankfurt a/M (Motor-vehicles)
- 200a) Oskar Fischer Fabrik, Markdorf bei Bodensee (Lake Constance) (Pyrotechnic items)
- 200b) Osnabrücker Kupfer- und Drahtwerke, Osnabrück (Ammunition)
- 201) Patronen-, Zündhütchen- und Metallwaren-Fabrik (Vormals Sellier & Bellot), Schönebeck and Bad Salzelmen bei Magdeburg, founded in 1829 by the chemist N. Bellot. (Blasting caps, detonators; pistol, revolver, sporting and hunting ammunition). See Anon, S S 74, 77 (1929) and CIOS 52-38
- 202) **Peenemünde** (Army Rocket Experimental Station), located on the Baltic coast, near the Peene estuary and southeast of Rügen island, was established about 1937 as a liquid-propellant rocket development center with General Walther Dornberger in charge. The following rockets were developed and tested at Peenemünde:
- A-3 (unsuccessfully launched in 1937)
 - A-5 (successfully launched in 1939 after several previous failures)
- Note: These two were experimental models.
- A-1 known now as V-2 (Vergeltungswaffe Zwei. Revenge Weapon 2) was successfully launched in October 1942 after some earlier failures. Its production started in the middle of 1943
 - A-9 was the winged version of A-1
 - A-9/A-10 was a two-step rocket which was designed to span the distance from Europe to the U.S.A. in 40 minutes.
 - A-10
- For more information about the activities at Peenemünde before and during WW II, see:
- L.E. Simon, German Research in World War II, J. Wiley, N.Y., (1947), and
- W. Dornberger, V-2, Viking Press (1954), pp 42-63, 76, 80, 93-8, 142-3, 239 and 250
- Note: **Greifswalder Oie**, mentioned in Dornberger's book, is a small narrow island located north of Usedom island and near the Peene estuary. The island belonged to the Peenemünde rocket center and was used for firing rockets smaller than the A-3 (such as the A-3 and A-5)
- According to L.E. Simon (Ref 4a, pp 33 & 84), the total cost of construction and equipment of Peenemünde Center was about 300 million Reichsmarks and at the height of activity the Peenemünde employed 2200 scientists and technicians, exclusive of clerical and subprofessional personnel. The divisions of the Army, **WaPrüf 10** and **WaPrüf 11** (q v) under General Dornberger, were engaged in research and development of rockets and guided missiles except those with wings, like the V-1 and glide bombs. After Peenemünde was bombed, the wind tunnel and aerodynamic work was moved to Kochel, about 25 miles south of München (See VVA), the theoretical sections were moved to Garmisch-Partenkirchen and the manufacturing and development work was moved to Nordhausen and Heisterode
- Peters (J), Berlin Nw 21 (Apparatus for chemical and physical testing of explosives)
 - Pfälzische Pulverfabrik A-G, Sankt Ingbert and Schlebusch (Explosives and propellants)
 - Polte Patronenfabrik, Magdeburg, Arnstadt and Gröneberg (Metallic cartridges and ammunition)
 - Pommersche Industrie-Werke GmbH, Barth (Pyrotechnic items, chemical warfare agents, ammunition filling). It employed, during WW II up to 3600 workers (CIOS 32-13)
 - Pulverfabrik Gebrüder Brudenbach, Junkermühle (Explosives and propellants)
 - Pulverfabrik Hasloch GmbH. See Dynamit A-G, item i)
 - Pulverfabrik Rosenheim, Stephanskirchen (Explosives and propellants)
 - Raukkammer, Proving Ground, located near Lüneburger

- 101a) was an Army establishment for testing chemical warfare weapons (Ref 4a, p 85)
- 209b) Reichlin Testing Station (Reichlin Erprobungsstelle), near Neustrelitz, Mecklenburg, was a proving ground for aircraft (Ref 4a, p 73)
- 210a) Reichsforschungsrat (State Research Council) was the governing body of the technical institutes (Hochschulinstitute) engaged in research work for the Armed Forces (Ref 4a, pp 71 & 79-80)
- 210b) Reichversuchsanstalt für Luftfahrt, Berlin-Adlershof (Government research center for aeronautics)
- 211) Reinsdorf Plant. See under WASAG
- 212a) Remo-Gewehrfabrik, Suhl, Sachsen (Weapons)
- 212b) R.F.R. See Reichsforschungsrat
- 212c) Rh or Rbm. See Rheinmetall-Borsig A-G
- 213) Rheinische Dynamit Fabrik, Köln with plants at Opladen and Mansfeld (Industrial explosives)
- 214) Rheinische Gummi- und Celluloid-Fabrik A-G, Mannheim-Neckarau (Celluloid, celluloid articles and rubber articles) (CIOS 32-38)
- 215) Rheinische Metallwaren- und Maschinenfabrik A-G, Düsseldorf. See Rheinmetall-Borsig A-G
- 216) Rheinisches Spritzguss-Werk GmbH, Köln/Braunfeld (Various items prepared by injection molding) (CIOS 32-38)
- 217) Rheinisch-Westfälische Sprengstoff A-G, Berlin (Industrial explosives)
- 218) Rheinmetall-Borsig A-G, Düsseldorf-Derendorf. One of the largest manufacturers of various machines, ammunition (including guided missiles) and weapons. The firm was founded in 1888 as the Rheinische Metallwaren- u. Maschinenfabrik A-G, Düsseldorf. In 1929 it merged with the Waffenfabrik Solothurn, Switzerland and in 1936 it merged with the then bankrupt Borsig Werke which possessed a large well-equipped plant at Tegel, a northern suburb of Berlin. The following Rheinmetall-Borsig plants were in operation during WW II:
 - a) Berlin-Mariendorf
 - b) Berlin-Tegel
 - c) Breslau
 - d) Guben
 - e) Sömmerda
 - f) Unterlüss

Note: A proving ground, called **Schiessplatz Unterlüss** was located near Celle

References:

- A) G.M.Chinn, The Machine Gun, U S Govt Printing Office, Washington, D C (1951), p 450
- B) BIOS Final Rept 716
- C) CIOS Repts 27-79, 31-12 & 32-108
- 219) Röchling - Buderus A-G, Wetzlar (Centrifugal casting of gun tubes)
- 220) Röchling Stahlwerke, Volklingen bei Saarbrücken (Steel forging) (CIOS 26-69) (See Röchling Projectile)
- 221) Rotweil A-G. See item(n) under Dynamit A-G
- 222) Ruhrchemie A-G, Oberhausen-Holten (Nitric acid) (BIOS 1442, p 22)
- 223) Ruhrstahl A-G, with several steel works, among them:
 - a) Annenerwerke, Witten-Annen (Centrifugal casting of gun tubes)
 - b) Guss-stahlwerke
 - c) Guss-stahlwerke Wetten, Gelsenkirchen
 - d) Henrickshütte, Hattingen
 - e) Stahlwerke Krieger, Düsseldorf/Oberkassel

(See BIOS Final Rept 716 and CIOS Repts 27-100, 29-26 and 29-39)

- 224a) Sächsische Metallwarenfabrik, Aug Wellner, Aug/Sa (Ammunition)
- 224b) Sauer (J.P.) & Sohn Gewehrfabrik, Suhl was founded in 1751 (Small arms)
- 225) Schiessplatz Unterlüss (Proving Ground) See also under Rheinmetall-Borsig A-G

Note: According to Simon (Ref 5a, p 130) the Unterlüss station was provided with a full-scale range and all equipment required for conducting exterior ballistics tests.

- 226) Schuckhardt A-G, Görlitz (Machinery and various weapons)
- 227) Schutze A-G, Oggersheim-Pfalz (Machinery for manuf of chemicals, propellants and explosives)

- 228) Sellier & Bellot A-G, See Patmore, Zündhütchen- und Metallwaren-Fabrik
- 229) Selver, Kronbiegel - Dornheim A-G, Sommerda bei Erfurt (Artillery primers and some incendiary bombs) (CIOS 32-38)
- 230) Siegener Dynamit Fabrik, Köln. Plant at Forde (Industrial explosives)
- 231) Siegfried Junghans, Schorndorf, Lei Stuttgart (Metal-burgy) (CIOS 26-71)
- 232) Siemens-Halske A-G, Berlin, was one of the world's greatest electrical organizations with numerous branches and affiliated companies in Germany and foreign countries

Following is a partial list of Siemens plants:
 a) Siemens-Reinicke-Werke Berlin, with plants at Erlangen and Rudolfstadt (Electrical equipment such as X-Ray apparatus)
 b) Siemens-Schuckert Werke A-G, Berlin (Electrical cables and some ammunition), with branches in Wien (Austria), London (England), Rio de Janeiro (Brazil), etc
 c) Siemens-Wernerwerke, Berlin-Siemensstadt (Dynamos, electric motors, electrical blasting devices, etc) (See CIOS Rept 28-31)

Note: The present main office and plant are located at Karlsruhe

- 233) Skoda Werke, Pilsen. See in the Czechoslovakian section
- 234) Spandau Arsenal, near Berlin. One of the oldest and most important arsenals in Europe
- 235a) Sperr Versuchsanstalt (Lit Barrier-Research Establishment) was a Naval institution engaged in research, development and testing of sea mines (Ref 4a, p 86)
- 235b) Sprewerke GmbH Metallwarenfabrik, Berlin/Spandau (Weapons)
- 236) Sprengstoff Fabriken GmbH, Kieselbach (Explosives)
- 237) Sprengstoff Fabriken Hoppecke A-G, Köln. Plants at Köln, Würzendorf and Hoppecke (Explosives)
- 238) Sprengstoff- und Zündschur-Werke, Gnaschwitz A-G. Plants at Gnaschwitz and Bautzen (Dynamites, safety explosives and safety fuses) (CIOS 32-38)
- 239) Sprengstoffwerke Dr Nahsen & Co A-G, Hamburg Plant at Dömitz (Explosives)
- 240) Staatliches Forschungsinstitut für Metallchemie, Marburg/Lahn. (Metallurgical research) See PB Rept 90651 (1946)
- 241a) Stahlwerk Krieger, Düsseldorf/Oberkassel. See Ruhrstahl A-G
- 241b) Steyr-Daimler-Puck, A-G, Werke, Steyr, Österreich (Weapons)
- 242) Stotz & Gössl, Suhl (Weapons)
- 243a) Stempel (F), Suhl (Weapons)
- 243b) Sundwiger, Messingwerke, vorm Gebrüder Von der Beck, Sundwig, Kr Iserlohn (Ammunition)
- 243c) SVA. See Sperr Versuchsanstalt
- 244a) TAL. See Technische Akademie der Luftwaffe.
- 244b) Tamewitz Testing Station (Tamewitz Erprobungsstelle), located on the Ostsee (Baltic Sea) between Lübeck and Rostock was a proving ground for aircraft weapons (Ref 4a, p 73)
- 244c) Technische Akademie der Luftwaffe, TAL, Berlin/Gatow (Technical Academy of Air Forces) (CIOS 30-71, pp 78-108)

Note: According to Simon (Ref 4a, pp 35-8 & 76-7) the TAL probably did the most advanced scientific research in Germany. Its organization consisted of 13 institutes: mathematics and mechanics, physics, chemistry, materials, mechanics electricity, communications, flight mechanics, motors aircraft devices, high-pressure work, measurements and ballistics. The Ballistic Institute of the TAL was under the famous ballistician Schardin, former student and collaborator of Carl Cranz. Nearly the entire TAL (except the Ballistics Institute) was evacuated in February 1945 to Bad Blankenburg, near Jena, while the Ballistics Institute was moved to Biberach, near Ulm

- 245) Temming (P) A-G, Glückstadt (Cotton and wood pulp suitable for manufacture of NC)
- 246a) Theodor Ehrlich Maschinen- und Zahnradfabrik, Gotha (Gears of all types) (CIOS 28-46, p 18)
- 246b) Torpedo Versuchsanstalt (TVA) was a Naval establishment engaged in research, development and testing of torpedoes (Ref 4a, p 86)

- 246a) **Tremonia Experimental Mine**. See **Versuchsgrube Gmbh, Tremonia**
- 246d) **TVA**. See **Torpedo Versuchsanstalt**
- 247a) **Udetfeld**, bei **Gleiwitz**, Schlesien, was an Air Force proving ground (named after the German fighter pilot engaged in testing of bombs and bomb fuzes (Ref 4a, p 73))
- 247b) **Unterlüss Proving Ground**. See **Schiessplatz Unterlüss**
- 248a) **VDM**. See **Vereinigte Deutsche Metallwerke**
- 248b) **Venus Waffenwerk, Zella Mehlis** (Weapons)
- 249) **Vereinigte Deutsche Metallwerke (VDM), Sintermetallwerke Neurod, Ettlingen, Karlsruhe** (Sintered iron and steel ammunition and weapon components)
- 250) **Vereinigte Leichtmetall Werke Gmbh, Hannover, Linden** (Aluminum, magnesium and their alloys) (CIOS 31-73)
- 251) **Versuchsgrube Gmbh, Tremonia** (Experimental mine) (BIOS 1,200). See in descriptive part
- 252) **Versuchsstation Heerte, Braunschweig** (Rockets, rocket fuels and guided missiles) (CIOS 31-13)
- 253) **Versuchsstrecke Dortmund/Derne** (Testing gallery for coal mine explosives) (BIOS 1,200). See in descriptive part
- 254) **Voigtlander und Sohn A-G, Braunschweig-Gliesmarode** (Physical and optical devices) (CIOS 20-26)
- 255) **Volkswagenwerke, near Fallersleben** (Automobiles, jeeps, V-1 missile, Panzerfaust, T-Mines, 250 kg bombs, etc). During WW II about 17000 workers were employed of which 4000 were foreigners (CIOS 28-46)
- 256a) **Waf**. See **Waffen-Forschung**
- 256b) **Waffenamt Prüfwesen (WaPrüf)** (Army Weapons Office for Developments) was in charge of research, development and testing of army weapons, ammunition and explosives. The **WaPrüf** consisted of several divisions of which **WaPrüf 10** was in charge of liquid-fuel rockets and **WaPrüf 11** was responsible for solid-fuel rockets. The so-called **Wof** (Waffen-Forschung), called also **Forschungsabteilung des Heereswaffenamts**, was a subordinate division of **WaPrüf**. It was in charge of research on all weapons with the exception of rockets (Ref 4a, pp 54-60 & 81-4)
- 257a) **Waffenfabrik Mauser A-G**. See **Mauser Werke A-G**
- 257b) **Waffenfabrik Solothurn**. See in the Swiss section
- 257c) **Waffen-Forschung (Waf)**. See under **Waffenamt Prüfwesen**
- 258a) **Waffenprüfstellen des Heeres** (Army Proving Grounds) were located at: **Kummersdorf, Hillersleben, Götow, Raubkammer, and Peenemünde** (Ref 4a, pp 82-5 and CIOS 27-74 and 30-71)
- 258b) **Waffenprüfstelle der Kriegsmarine** (Navy Proving Ground) was located at **Meppen**
- 259) **Waffenprüfstellen der Luftwaffe** (Air Force Proving Grounds) were located at **Rechlin, Tarnowitz and Udetfeld** (Ref 4a, pp 71 & 73)
- 260a) **Walther**. See **Karl Walther**
- 260b) **WaPrüf**. See **Waffenamt Prüfwesen**
- 261a) **WaPrüf 10 and WaPrüf 11**. See under **Peenemünde and under Waffenamt Prüfwesen**
- 261b) **Walter Werke, Kiri** (Rockets, rocket fuels, jet propulsion, guided missiles, U-boats, aircraft, etc) (CIOS 30-76 and 30-115)
- 261c) **WASAG**. See **Westfälisch-Anhaltische Sprengstoff A-G**
- 262) **Wasserbau-Versuchsanstalt (WVA) Kochelsee** (Research and development of long range and Flak rockets) (CIOS 30-71)
- Note: According to Simon (Ref 4a, pp 33-5 & 130-3), the **Wasserbau-Versuchsanstalt** was the camouflage name for a section of **Peenemünde** installations moved to **Kochelsee** in order to avoid frequent bombings. Extensive work on the exterior ballistics of long-range rockets was done at **WVA**
- 263) **Werkzeugmaschinenfabrik Oerlikon**. See Swiss section
- 264) **Werner-Pfleiderer Maschinenfabriken, Stuttgart-Bad Cannstadt, Württemberg** (Mixing and Knending machines, grainers, etc)
- 265) **Westfälisch-Anhaltische Sprengstoff A-G, Essen** (abbreviated to **WASA A-G** or **WASAG**) with plants at:
- a) **Coswig Anhalt** (Various explosives and propellants)
- b) **Elsnig, Torgau** (Hexogen and nitric acid)
- c) **Herrenwald at Allendorf, Kr Marburg, Lahn** (Hexa-nitrodiphenylamine and ammunition loading)
- d) **Osnabruck** (Nitrocellulose)
- e) **Reinsdorf, Wittenberg** (NGu, propellants, research and development, etc)
- f) **Sythen, Haltern** (NG and industrial explosives)
- 266a) **Westfälische Kupfer- und Messingwerke A-G, vorm O.Noel, Lüdenscheid/Westfalen** (Ammunition)
- 266b) **Westfälische Metallindustrie, Lippstadt** (Ammunition)
- 266c) **Westlignose A-G, Berlin**. Plant at **Nussau** (Industrial explosives)
- 267a) **Weyersberg (P) & Co Waffenfabrik, Solingen** (Weapons)
- 267b) **WIFO**. See **Wirtschaftliche Forschungen Gmbh**
- 268) **Wirtschaftliche Forschungs Gmbh (WIFG)** with plants at:
- a) **Eferbachtel bei Heiligenstadt** (Fuels)
- b) **Embsen, bei Lüneburg** (Nitric acid, research and development center)
- c) **Langelsheim, Harz** (Nitric acid) (See BIOS 1412, pp 76 & 81 and CIOS 20-68)
- 269) **WKC Waffenfabrik Gmbh, Solingen** (Weapons)
- 270) **Wolfenfabrik**. See under **IG Farbenindustrie**
- 271) **Wolff & Co, Walsrode**, with plants at:
- a) **Bomlitz** (NC propellants and DEGN solventless propellants)
- b) **Dörverden** (NC propellants)
- c) **Fuchburg-Bomlitz** (NC propellants)
- d) **Liebenau** (DEGN propellants)
- e) **Walsrode** (Black powder and NC propellants)
- 272) **Wollmerschässer & Gurth, Berlin-Babelsberg** (Stability testing apparatus for explosives and propellants)
- 273a) **Württembergische Metallwarenfabrik A-G, Geislinger Steige, Geislingen** (Weapons)
- 273b) **WVA**. See **Wasserbau-Versuchsanstalt**
- 274a) **Zeiss-Ikon A-G, Dresden** (Optical, photometrical, piezoelectrical etc devices for ballistic measurements)
- 274b) **Zeiss (Karl), Jena** (Optical instruments)
- 274c) **Zelle**. A department of the **Reichsluftfahrtministerium** in charge of construction of aircraft bodies (Ref 4a, p 73)
- 275a) **Zentrale für wissenschaftliches Berichtswesen (ZWB) der Luftfahrtforschung des Generalluftzeugmeisters, Berlin Adlershof** (Investigation of aerodynamic properties of glide bombs, etc) (See E.W.Sponder, **ZWB Forschungsbericht Nr 1819 (1943)** "Investigation of a Lateral Stability of a Glide Bomb")
- Note: According to Simon (Ref 4a, pp 60 & 79), the **ZWB** stands for "Zentralstelle für wissenschaftliche Berichterstattung" (Central Place for Scientific Reports). Originated by the **DVL (Deutsche Versuchsanstalt)**, the **ZWB** was handled during the war by the **Lilienthal Gesellschaft**. All reports on scientific subjects which were of general interest to the air forces were printed and also abstracted on cards by **ZWB**
- 275b) **Zentralstelle für wissenschaftlich-technische Untersuchungen zu Neubabelsberg bei Berlin** (Government research and development center for explosives, ammunition, etc)
- 276) **Zeppelin Gmbh, Friedrichshafen and its Subsidiary Maibach Motorenwerke** (Diesels, engines, etc) (See also **Graf Zeppelin Forschungsinstitut**)
- 277) **Zimmermann (E), Leipzig**, founded in 1887 (Devices used in ballistic measurements, such as chronographs, etc)
- 278) **Zünderfabrik Müllheim, Ruhr und Saar** (Igniters, primers, safety fuses, etc)
- 279) **Zünderwerke Ernst Brünn A-G**. See **Ernst Brünn Gmbh**
- 280) **Zündhütchen- und Patronenfabrik, vorm Sellier & Bellot**. See **Patronen-, Zündhütchen- u Metallwaren Fabrik**
- 281) **ZWB**. See **Zentrale für wissenschaftliches Berichtswesen**
- Note: Many of the war plants in occupied Austria, Belgium, Czechoslovakia, France, Holland, Poland and Russia, were forced to work during WW II for Germany. These

plants are listed under corresponding countries.

Following is a partial list of war plants presumably in operation in the Eastern Zone of Germany:

- A) Celluloidfabrik, Eilenbourg (Celluloid cotton)
- B) Chemisches Werk, Freiberg, Sachsen (Explosives and propellants)
- C) Coswig Plant (Sulfuric acid and NG)
- D) Magnesit Aken, Kr Dessau, Anhalt
- E) Stickstoffwerk, Piestritz (Celluloid cotton)
- F) VEB (Chemisches Werk) (Explosives)
- G) VEB Sprengstoffwerke, Gnaschwitz (Am nitrate, NG, commercial explosives such as "Aru", Gelatine-Dynamit, safety fuses, etc)
- H) VEB Sprengstoffwerke, Schönebeck (Am nitrate, Ammonit, ammunition, Baldurit, blasting caps, Chloratit, Donarit I, Donarit II, fuses, Gelatine-Donarit, NC, NG, NGK, TNT, Wetter-Donarit and Wetter-Dalit)
- I) VEB Walter Ulbricht, LEUNA (Rocket propellants and jet fuels)
- J) VEB WASAG, Sprengwerke, Reinsdorf (Explosives and propellants)

Note: Most of these East German plants are already listed in this section under their pre-World War II names.

Abbreviations (Used under War Plants):

A-G (Aktiengesellschaft) Joint Stock Company; Bez (Bezirk) Region; DEGDN Diethyleneglycol dinitrate; IG or IG (Interessengemeinschaft) Trust; Kr (Kreis) District; L A Lead azide; L St Lead styphnate; LEUNA or Leuna Fixed nitrogen plant in E Germany; M F Mercurifuminate; Nöchf (Nachfolger) Successor; NC Nitrocellulose; NG Nitroglycerin; NGc Nitroglycol; NGu Nitroguanidine; NRA National Rifle Association (USA); Obb (Oberbayern) Upper Bavaria; P A Picric acid; PETN Pentaerythritol tetranitrate; PG Proving Ground; RDX Hexogen (and) and; VEB (Volkseigener Betrieb) People's Own Works; vorm (vormals) formerly; WW World War.

References:

- 1) P. Naoum, Nitroglycerin, etc, Williams & Wilkins, Baltimore (1928), p 14
- 2) J. Pepin Lehalleur, Poudres, Explosifs et Artifices, Bailliere, Paris (1935), p 115
- 3) O.W. Stickland et al, PB Rept 925 (1945), The General Summary of Explosives Plants
- 4) O.W. Stickland, PB Rept 1820 (1945), Survey of German Practice and Experience in Filling High-Explosives
 - 4a) L.E. Simon, German Research in World War II, J. Wiley, N Y (1947)
 - 5) G.M. Chinn, The Machine Gun, Bureau of Ordnance, U S Navy, U S Govt Printing Office, Washington, D C, v 1 (Unclassified) (1951)

WASAG Underwater Explosives. See under Unterwasser-sprengstoffe.

Wasserfall (Waterfall). A ground to air guided anti-aircraft rocket missile developed during WW II. It was propelled by Visol/Nitric acid (See also Guided Missiles).

References:

- 1) Anon, Army Ordnance 31, 30 (1946)
- 2) A. Ducrocq, Les Armes Secrètes Allemandes, Paris (1947), pp 110-121
- 3) F. Ross, Jr, Guided Missiles, Lothrop, Lee, Sheppard, N Y (1951), p 37
- 4) K.W. Gatland, Development of the Guided Missiles, Philosophical Library, N Y, (1952), pp 16, 17, 126
- 5) Gollin, CIOS Report 28-56 (1946), pp 18-24
- 6) Anon, Dept of the Army Technical Manual, TM 9-1985-2 (1953), pp 219-23.

Wasserstoffperoxyd (Hydrogen Peroxide). See T-Stoff and in the general section under Peroxides

Wasserlösliches Schiesspulver (Water Soluble Propellant). See Raschit.

Waste or Spent Acids (Abgangssäure oder Abfallsäure) are described in the general section. German methods of recovery of nitric and sulfuric acids, from waste or spent acids resulting from the preparation of explosives and propellant plants, paralleled the practice in the USA.

The procedure used at the Krümmel Fabrik for the recovery of waste acids from explosive oils (such as DEGDN and TEGDN), serving for the preparation of

(c) P.B. Sharpe, The Rifle in America, Funk & Wagnalls, N Y (1953), pp 601-3

(7) W.H.B. Smith, The NRA Book of Small Arms, The Military Service Publishing Co, Harrisburg, Pennsylvania: v 1 (1953) Pistols and Revolvers, v 2 (1952) Rifles (pp 170 & 57-9)

(8) W.H.B. Smith, Small Arms of the World, The Military Service Publishing Co, Harrisburg, Penna: (1955)

(9) Dr M.M. Kostevitch, Formerly Colonel in the Russian Imperial Artillery, Buenos Aires, Argentina; private communication

(10) Dr A. Stettbacher, Formerly Professor at the Zürich Polytechnic Institute, Switzerland; private communication.

(11) Drs: H.M. Adam, G. Jöhr and R. Weil and Messrs: E.W. Blaszyk, J.F. Hauck, F. Schaufberger, H.A. Tisch and L.G. Van Syckle of Picatinny Arsenal, private communications

(12) G.B. Jarrett and K.F. Kempf, Museum, Aberdeen PG; private communications

(13) CIOS, Item 22, File 21-3 (1946), Troisdorf Fabrik, D A - G

(14) CIOS, item 2, File 21-3 (1946), Troisdorf Fabrik, D A - G

(15) CIOS, Item 2, File 21-1 (1946), Schleibusch Fabrik, D A - G

(16) CIOS, Item 2, File 25-16 (1946), Wolfratshausen Fabrik of Dynamit A-G, Subsidiary, GmbH zur Verwertung Chemischer Erzeugnisse

(17) CIOS, Item 2, File 26-70 (1946), Rottweil A-G

(18) CIOS, Item 2, File 27-38 (1946), Stadeln und Wolfratshausen Fabriken, D A - G

(19) CIOS, Item 4 & 6, File 28-56 (1946), Elektromechanische Werke, Peenemünde

(20) CIOS, Item 2, File 28-61 (1946), Krümmel, Düneberg, and Christianstadt Fabriken, D A - G (Same information as in PB Rept 925)

(21) CIOS, Item 2, File 27-24 (1946), German Powder and Explosives Plants

(22) CIOS, Item 2, File 29-28 (1946), Kaufbeuren Fabrik, D A - G

(23) CIOS, Item 2, File 31-68 (1946) Düneberg Fabrik, A-G

(24) CIOS, Item 2, 18, 19 & 21, File 31-70 (1946), Skoda Werke, Pilsen and Böhmisches Waffenfabrik, Strakonitz

(25) CIOS, Item 2, File 32-8 (1946), Bobingen Fabrik of Dynamit A-G Subsidiary

(26) CIOS, Item 2, 3 & 8, File 32-13 (1946), Maschinenfabrik Peterson, Oldenburg, Holstein

(27) CIOS, Item 2, File 32-38 (1946), Explosives Summary of Capacities and Production in Germany

(28) CIOS, Item 1, 4 & 5, File 32-109 (1946), Luftfahrt-Forschungsanstalt at Volkenrode

(29) CIOS, Item 2, File 33-20 (1946), Deutsche Waffen und Munitions-Fabriken A-G

(30) BIOS Reports listed at the beginning of German section

Rohpulvermasse) (q v) deserves to be described here briefly. The denitration was carried out on the spent acid coming from the separator in the nitrating house and from the wash water which resulted from washing the oil in the preliminary washer.

Procedure:

Spent acid (HNO₃, H₂SO₄ 65, water 21 & DEGDN oil 5%, density 1.66) was sent through a separator to remove the settled explosive oil and then the acid was freed from dissolved explosive oils by running it through the so-called destructor column, heated to about 120° at the bottom and to 150° at the top. In order to assure complete oxidation of explosive oils, the waste acid was usually mixed with some 50% of nitric acid before sending it to the destructor

Notes:

a) Inasmuch as spent DEGDN acid decomposed rapidly on standing (especially in the presence of moisture), it was not stored for longer than a few hours, but preferably was worked up as soon as the nitration of the DEG was completed

b) It was required that destruction of the explosive oil should be complete and that the resulting acid be light in color. If it was black, the destruction of oil was not complete and the heating had to be continued after adding some more 50% nitric acid

c) For destruction of oils dissolved in wash waters, it was sufficient to run them through the destruction column with live steam

f) The nitrous gases formed in the destructor went to a condenser from which they were drawn into an absorption tower. An acid of about 40-50% strength was recovered. The nitric acid collected in the condenser was bleached by bubbling air through it. This yielded white nitric acid of 38-40% strength.

g) The sulfuric acid which flowed from the lower end of the destructor was conducted to a cooler from which it was run to storage tanks. It contained about 1% H_2SO_4 and the density was 1.64. No oxides of nitrogen were permitted to be present and tests were made continuously for them with ferrous sulfate.

h) The recovered nitric acid was reheated and passed through an Ausbläser (blow-out column) where the remaining nitrogen oxides were removed by a stream of air. The acid then passed through a siphon into an intermediate container from which it was sent to a storage tank. Reference: *Stoll-Lau*, PB Rept 975 (1945), p. 62.

Weapons. See Table 63 and illustrations on the following pages.

Note: The illustrations of weapons were obtained from the following sources: Museum of Aberdeen Proving Ground (all artillery weapons and most of small arms), Reference 8 (some machine guns) and References 10 and 11 (some pistols and rifles).

The authors wish to express their appreciation to Messrs J.B. Jarrett, K.F. Kempf, H.M. Reed, G.M. Chinn and W.H.B. Smith for use of material listed above.

References (Weapons):

- 1) I.S. Hatcher, *Textbook of Pistols and Revolvers, Small Arms* Technical Publishing Co, Marines, N Carolina (1945)
- 2) M.M. Johnson, Jr & C.T. Haven, *Automatic Arms*, W. Morrow, N.Y. (1942)
- 3) M.M. Johnson, Jr & C.T. Haven, *Ammunition*, W. Morrow, N.Y. (1943)
- 4) M.M. Johnson, Jr, *Rifles and Machine Guns*, W. Morrow, N.Y. (1944)
- 5) Anon, *Recognition Handbook for German Ammunition*, Sup Hqs AEF (1945)
- 5a) Anon, *Enemy War Materials Inventory List*, SIAAEF, Office of AC of SG-4a (1945)
- 5b) H.H.M. Pike, CIOS Report 31-68 (1946), Tables I to 14.
- 6) L. Simon, *German Research in WW II*, J. Wiley, N.Y. (1947)
- 7) G.R. Jacobs, *Official Gun Book*, Crown Pub. N.Y. (1951)
- 8) G.M. Chinn, *The Machine Gun*, U.S. Navy, Bureau of Ordnance, Washington, D.C., v 1 (1952); v 3 (1953) (Confidential).

Note: Volume 3 was not used as a source of information for this work.

9) Anon, *German Explosive Ordnance*, Dept of the Army Tech Manual TM 9-1985-2 and 9-1985-3, Washington, D.C. (1953)

10) W.H.B. Smith, *The NRA Book of Small Arms*, Military Service Publishing Co, Harrisburg, Penna., v 1 Pistols and Revolvers (1953) and vol 2 Rifles (1952)

11) W.H.B. Smith, *Small Arms of the World*, Military Service Publishing Co, Harrisburg Penna. (1955) (Gives also an historical description of the development of German small arms)

12) Col J.B. Jarrett, and Messrs K.F. Kempf and H.M. Reed of Museum Aberdeen Proving Ground, Maryland; private communication

13) J.E. Capell, A.B. Schilling G. Coghlan and H.H. Bullock of Picatinny Arsenal, Dover, New Jersey; private communication (1955)

Note: An historical description of the development of German artillery weapons may be found in the book by Capt James F. Hicks, "Notes on German Ordnance 1841-1918", 428 Rick Ave, Mt Vernon, N.Y.

14) P.B. Sharpe, *Rifle in America*, Funk & Wagnalls, N.Y. (1953)

15) Anon, *Intelligence Bulletin* Washington D.C. (1955). Note: These bulletins were not used as sources of information for this work.

Weapons, Internal Ballistic Data. H.H.M. Pike gives, at the end of CIOS Report 31-68 (1945), several tables listing German weapons from 29 mm to 800 mm, the types of propellants used by them, size of grains, weight of charge, type and weight of projectiles, length and capacity of chamber, shot travel, total capacity, pressure and muzzle velocity.

"Weissmann" Zünder. Pressure type igniter designed for use in improvised mines (as a push igniter) or in some HE charges (as an impact igniter). See also under Igniter.

Weisspulver. See Raschig's White Powder

Weiss-Salz (White Salt). A compound, $(H_2C_2N_2O_3)_2K_2$, produced in 1941 by the IG Farbenindustrie at Höchst am Main, as an intermediate in the manufacture of Hexogen. The compound was shipped to the Nobel plant at Hamburg, where it was nitrated. The production of white salt was stopped as soon as the method of direct nitration of hexamethylenetetramine to Hexogen was improved to make it more economical. Weiss-Salz was prepared as follows:

- a) Ammonia and sulfur trioxide reacted to give the ammonium salt of aminosulfonic acid, $H_2N.SO_2.ONH_4$
- b) On treating it with KOH, the corresponding potassium salt was obtained
- c) On treating the K salt with formaldehyde the Weiss-salz was obtained.

Reference: R.E. Richardson et al, CIOS Rept 25-18 (1945), pp 28-29.

Westfalit (Westphalite). A series of explosives proposed by Bielefeldt in 1893. The original composition contained Am nitrate 95 and resin 5%. It was later modified to the one containing Am nitrate 91, K nitrate 4 and resin 5%. Its velocity of detonation was 4350 m/sec at density 1.01. The last composition was also called the Westfalit für Kohle (Coal Westphalite) (Ref 3).

Note: Although Westphalites were fairly safe for use in gaseous coal mines, the Westfälisch-Anhaltische Sprengstoff A-G proposed to add to them 3 to 5% of chromium salts to act as cooling agents. Some Westphalites were manufactured in England.

References:

- 1) Daniel, *Dictionnaire* (1902), pp 804-6
- 2) Marshall *Explosives* v 1 (1917), p 309
- 3) Barnett, *Explosives* (1919), p 113.

Westphalite. See Westfalit.

WETTERSPRENGSTOFFE (Explosives Safe for Use in the Presence of Firedamp). A series of coal mining explosives approximately corresponding to American Permissible Explosives or French Explosifs antigrisouteux. Table 64 lists these explosives (See pp 260-61).

WEAPONS (Waffen) may be subdivided into:

A. Small Arms (Handfeuerwaffen), which include: pistol (Pistole) revolver (Revolver), carbine (Karbiner), rifle (Gewehr), machine gun (Maschinengewehr) and sub-machine gun (Maschinenpistole) models

B. Artillery Pieces (Geschütze), which include: cannon (Kanone), howitzer (Haubitze) and mortar (Mörser) models

C. Rocket Launchers (Raketenwurfmaschinen), which include: Faustpatrone, Panzerfaust, Panzerschreck (Raketenpanzerbüchse 54), Püppchen (Raketenwerfer 43) and others.


Most of the German weapons used in WW I and II may be found on display in the Museum of Aberdeen Proving Ground, Maryland.

Table 63, following, gives some of the characteristics of German small arms, artillery pieces and rocket launchers.


Table 63 (Weapons)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|---|---|
| 6.35 mm (.250") Mauser Automatic Pistol M 1910, called Westraschenpistole (WTP), Vest Pocket Pistol | Length: barrel 2.03" and overall 4.06"; wt 10.22 oz and a capacity of 6 rounds. One of the best small pistols ever produced | 2, p 321; 4, pp 275-8 & 10, v1, pp 141 & 560 |
| 6.35 mm Walther Pistols Models I (1908) and 2 (1910) | Blowback vest pocket pistols using .25 CAC | 11, p 478 |
| 6.35 mm Walther Pistols Models 5 (1913), 8 (1920) and 9 (1921) | Streamlined versions of above pistols | 11, p 478 & Ref 12 |
| 6.35 mm Pistols: Bergmann, Orgies, Sauer and others | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 6.5 mm (.256") Bergmann Automatic Pistol | One of the earliest small size pistols | 7, p 27 |
| 6.5 mm Mauser Vest Pocket Automatic Pistols, Types WTP I (1910) and WTP II (1919) | Elementary blowback pistols resembling the Browning types. The Type II was the streamlined version of Type I | 11, p 485 |
| 6.5 mm Sauer & Sohn Vest Pocket Pistols, Types I and II | Resembled a Browning in external appearance. Capacity 7 | 11, p 484 |
| 7.63 mm (.300") Military Mauser Automatic Pistol, called Maschinen Pistole, developed in 1895 and used during WW I Note: According to Ref 8, v1, p 177 there was also an improved model (M1920) of the above pistol | Recoil-operated pistol weighing 45 oz. Capacity 10. Could be fired with shoulder stock holster attached | 2, p 321; 4, pp 275-8; 7, p 27; 10, v1, pp 167-176, & 11 pp 464-8 |
| 7.63 mm Mauser Machine Pistol M 1932, called Schnell-Feuer Pistole (Rapid-Fire Pistol) issued to SS troops. Was also manufd in Spain under the name of ASTRA | Recoil-operated weapon which may be considered as intermediate between the pistol and the sub-machine gun. Length of barrel 5 1/4", overall 12", wt 45 oz, capacity 10 or 12 cartridges, m2 vel up to 1500 ft/sec | 8, v1, p 177 & 11, pp 468-71 |
| 7.65 mm (.301") Automatic Pistol, introduced in Germany in 1893 by an American firm Borchardt | Considered as the forerunner of the Luger. Could use 7.63 mm Mauser ammunition | 7, p 27 & 10, v1, p 185 |
| 7.65 mm Mannlicher Pistol invented in 1900 | Was also made in caliber 7.63 mm | 7, p 27 |
| 7.65 mm Luger (Parabellum) Pistols M 1900 and M 1900/06 were used during WW I. Model 1900 was an official Swiss pistol Note: According to Smith (Ref 9, p 462) the original Luger was designed by an American, Borchardt, and was further developed by a German, Leuger. It was first manufd under the name of "Borchardt-Leuger" and later corrupted and shortened in the U S A to the name "Luger." The name "Parabellum", which literally means in Latin "for war", is used in Europe. See also 9 mm Luger (Parabellum) Pistols | Barrel length 4 1/4". Used cartridges contg 10 gr of smokeless prop and a bullet weighing 93 gr. M2 vel 1250 ft/sec | 2, p 320; 3, p 187; 7, p 27 & 10, v1, p 182 |
| 7.65 mm Luger Automatic Carbine (Parabellum Karabiner) | It consisted of a regular Luger pistol provided with a detachable wood stock and a long barrel with a checkered wooden fore-end | 10, v1, p 184 |
| 7.65 mm Dreyse Automatic Pistol M 1907 | Blowback-action pistol weighing 24 oz; capacity 8 | 10, v1, pp 233-5 & 552 & Ref 12 |
| 7.65 mm Beholla Automatic Pistol manufd by Becker & Holländer, Suhl | Blowback-action pistol weighing ca 22 oz. Was used during both WWS. Capacity 7 | 10, v1, pp 218 & 579 |
| 7.65 mm DWM Automatic Pistol, manufd by the Deutsche Waffen- u Munitionsfabriken | Blowback-action pistol weighing 20 1/2 oz. Capacity 7 | 10, v1, pp 235-6 |
| 7.65 mm Automatic Pistol invented by F. Langenham of Suhl and called F L Selbslader (F L Self-loader) | Blowback-action pistol weighing 22.9 oz, capacity 8. Was used during WW I as a substitute officer's pistol | 10, v1, pp 243-5 & 585 |
| 7.65 mm Automatic Pistol, called PB Special Model III, manufd by A. Menz, Suhl | Double-action blowback pistol which closely resembled Walther PPK | 10, v1, pp 253-4 & 588 |
| 7.65 mm Orgies Automatic Pistol (manufd by the Deutsche Werke, Erfurt) | Striker-fired blowback pistol | 10, v1, pp 254-6 |
| 7.65 mm Jäger Automatic Pistol | A blowback-operated pistol of simple and most unusual design | 10, v1, pp 248-3 & 585 & Ref 12 |
| 7.65 mm Mauser Automatic Pocket Pistol M 1910 | A straight blowback-action pistol weighing 21 1/2 oz. Capacity 8 | 10, v1, pp 246-9 & 587 |

Ger 228
WEAPONS
(PISTOLS AND REVOLVERS)




6.35 mm AUTOMATIC
ORTGIE PISTOL




6.35 mm WALTHER
PISTOL MODEL 8




7.65 mm AUTOMATIC
DREYSE PISTOL



7.65 mm AUTOMATIC
MAUSER PISTOL
(MODIFICATION 1934)




7.65 mm MAUSER PISTOL




7.65 mm AUTOMATIC
SAUEP PISTOL

7.65 mm SEMI-
AUTOMATIC JÄGER
PISTOL

7.65 mm AUTOMATIC WALTHER PISTOL



7.65 mm MAUSER PISTOL
MODEL HSc



9 mm AUTOMATIC LUGER
(PARABELLUM) PISTOL 08
MODIFIED IN 1920 (BARREL
LENGTH 4")



9 mm AUTOMATIC
LUGER (PARABELLUM)
PISTOL 08 (BARREL
LENGTH 6")




9 mm AUTOMATIC LUGER
(PARABELLUM) PISTOL 08
(BARREL LENGTH 8")



9 mm AUTOMATIC LUGER
(PARABELLUM) PISTOL 08
WITH SHOULDER STOCK
ATTACHMENT



9 mm SEMI-AUTOMATIC MAUSER PISTOL
WITH SHOULDER STOCK ATTACHMENT



11 mm SUHL
REVOLVER

26 mm RIFLED SIGNAL
PISTOL (KAMPFPISTOLE)


(Weapons) (cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|--|--|---|
| 7.65 mm Mauser Automatic Pistol, HSc (Hammer-Self-loading) | Double-action blowback pistol, length barrel 3 3/8" and overall 6 1/2". Wt 20.6 oz and capacity 8 cartridges, either 7.65 mm Browning or .32 CAP | 10, v 1, pp 246-9 & 587 & 11, pp 472-3 |
| 7.65 mm Rheinmerall Automatic Pistol | Blowback-operated pistol weighing 23.6 oz | 10, v 1, pp 254-6 |
| 7.65 mm Roth-Sauer Automatic Pistol was somewhat similar to the Austro-Hungarian Roth-Steyr pistols | Long recoil-operated weapon weighing 23 oz with capacity 7 cartridges, caliber .301 | 10, v 1, pp 208-9 & 11, p 483 |
| 7.65 mm Sauer Automatic Pistol M 1908 manufd by J.P.Sauer & Sohn, Suhl | Was replaced after WW I by M 1930 and and M 1938 | 10, v 1, p 258. |
| 7.65 mm Sauer Automatic Pistols M 1913 and Behördenmodell (Authority Model) | Blowback-operated weapons, capacity 7. The Behördenmodell was widely used by military and police officials | 260-1 & 590 11, p 485 |
| 7.65 mm Sauer Automatic Pistol M 1930 | Streamlined modification of earlier models | 10, v 1, p 259 |
| 7.65 mm Sauer Double Action Automatic Pistol M 1930 (called also Model H) was widely used during WW II by the German air and tank forces. Considered one of the world's best pocket pistols | Straight blowback-action weapon. Length of barrel 3 1/2" and overall 6 1/2". Wt 22 oz, capacity 8 cartridges either 7.65 mm Browning or .32 CAP | 10, v 1, pp 259-8 262-4 and 11, pp 474-7 |
| 7.65 mm Walther Pistols Models 3 (1909), 4 (1910), 6 and 7 (1917), manufd by K.Walther of Zella Mehlis | Blowback-action weapons using .32 CAP cartridges | 10, v 1, pp 286-7 & 594 & 11, p 478 |
| 7.65 mm Walther Pistol PP (Polizei Pistole), introduced in 1921 | Holster type pistol widely used by police forces throughout Europe | 10, v 1, pp 286-7 & 11, p 478 |
| 7.65 mm Walther Pistol PPK (Polizei Pistole Kriminal), introduced in 1929 and manufd in great numbers | Designed for detectives who carry their weapons concealed | 10, v 1, pp 286-92; 11, p 478 & Ref 12 |
| 7.9 mm (.311") Rifle M 1888 (Gewehr 88, abbreviated to Gew 88) and developed by a German Military Commission. It combined a modified Mauser (M:871) two-piece bolt system with a modified Mannlicher loading system (magazine) | Prototype of Army rifles used in both WWs. The first 300,000 rifles were made in 1888 by L.Loewe & Co, Berlin. The carbine (Karabiner) was slightly shorter and lighter than the rifle. Both of them used rimmed, necked, center-fire cartridges with round nose bullets | 10, v 2, pp 201-15; 11, pp 425-7 and Ref 10 |
| 7.92 mm (.312") Mauser Rifle M1898 (Gewehr 98), Bolt Action, was the standard German Infantry Rifle of WW I and the early form of all modern Mauser rifles. Served as prototype for military rifles of many European and South American countries Note: Originally Gew 98 used a round nosed bullet (same as in M 1888) which had a slightly smaller diam than the pointed bullet. In order to take the new bullet it was necessary to enlarge the diam of Gew 98 | Length of barrel 29.15" and overall (without bayonet) 49.25", wt 9.5 lb. Capacity 5 rimless, necked, center-fire cartridges with pointed bullet (Spitzer). Muz vel 875 m/sec (2807 ft/sec) and pressure 3500 atm (51333 psi) | 4, pp 83-90; 10, v 2, pp 171 & 215; 11, pp 427-8 and Ref 12 |
| 7.92 mm Mauser Carbine 1898 (Karabiner 98, abbr to Kar 98). Original model | Cavalry version of Gew 98. Barrel length 18" | 11, p 428 |
| 7.92 mm Mauser Carbine 1898 which was introduced in 1904 and adopted in 1908 for use by artillery and engineer (pioneer) personnel | Cut-down version of Gew 98. Length of barrel 24" and overall 43.5"; wt 8.2 lb; capacity 5 | 4, pp 83-90; 10, v 2, pp 171-5; and 11, p 428 |
| 7.92 mm Kar-98a was introduced after WW I by the Reichswehr | Slightly modified version of Kar 98. Was used in WW II | 10, v 2, pp 171 & 177 & 11, p 429 |
| 7.92 mm Kar 98b, developed after WW I by the Reichswehr for cavalry and armored forces use | It differed from Kar 98 in having a bent-down bolt handle and side sling. Was used during WW II | 10, v 2, pp 171 & 177 and 11, p 429 |
| 7.92 mm Karabiner 98 h (Kb-98h) | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 7.92 mm Semi-Automatic Rifle, Model 1915 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 7.92 mm Gewehr 98/17, developed during WW I and discarded after it | Slightly modified version of Gew 98 designed to permit speeding up manuf by reducing machine operations | 10, v 2, pp 175-6 |
| 7.92 mm Gewehr 18, developed after WW I as an experimental model | Was provided with magazines of 5, 10 and 25 round capacities | 10, v 2, pp 176-7 |
| 7.92 mm Machine Gun M 1908 (MG-08) | Short recoil-operated, water-cooled MG used during WW I. Wt 40.5 lb with feed | 8, v 1, pp 309 & 662 |
| 7.92 mm Machine Gun M 1908/15 (MG-08/15) Maxim | A lighter version of MG 08, which weighed 30 and 31 lb. Its air-cooled version, manufd at Spandau Arsenal, was called Spandau Machine Gun | 8, v 1, pp 309 & 314; 11, pp 517-20 and Ref 12 |

Ger 250

WEAPONS


(CARBINES AND RIFLES)



7.65 mm. AUTOMATIC LUGER CARBINE



7.9 mm RIFLE MODEL 1888 (GEWEHR 88)



7.92 mm RIFLE MODEL 1898/1940, (GEWEHR 98/40)


7.92 mm MAUSER CARBINE MODEL 1898K (KARABINER 98K)



LAUNCHER GRENADE (MODIFIED FOR KARABINER 98)



7.92 mm SEMI-AUTOMATIC MAUSER RIFLE MODEL 1915




7.92 mm SELF-LOADING SEMI-AUTOMATIC RIFLE




7.92 mm KRIEGHOFF AUTOMATIC ANTITANK RIFLE (PANZERBUCHSE 40K)




7.92 mm SEMI-AUTOMATIC RIFLE (GEWEHR 41)



7.92 mm PARATROOP RIFLE MODEL 1942 (FG 42)



7.92 mm PARATROOP RIFLE MODEL 1942 MODIFIED




7.92 mm SEMI-AUTOMATIC RIFLE (GEWEHR 41M)




7.92 mm SEMI-AUTOMATIC CARBINE (KARABINER 43)



7.92 mm SEMI-AUTOMATIC WALTHER RIFLE (GEWEHR 41W)



7.92 mm ANTITANK RIFLE MODEL SS-41



13 mm (13.2 mm) TUFF-MAUSER ANTITANK RIFLE (MACHINE GUN) MODEL 1918




7.92 mm PEOPLE'S RIFLE (VOLKSSTURM GEWEHR)

(Weapons) (cont'd)


| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|--|---|--|
| 7.92 mm Bergmann Machine Gun M 1910 was invented prior to 1900 and improved in 1903 and 1910 | Short recoil-operated, water-cooled MG weighing (with feed) 36 lb | 8, v 1, pp 214-16 & 658 |
| 7.92 mm Dreyse Machine Gun M 1912 was invented in 1907 by L. Schmeisser and called the Dreyse, in honor of J. von Dreyse, the inventor of the "needle gun" | Short recoil-operated, water cooled MG weighing (with feed) 37.5 lb. Was used during WW I | 8, v 1, pp 217 & 660 & Ref 12 |
| 7.92 mm Dreyse Machine Gun, called MG 13 | Air-cooled MG, secretly manufd after WW I in violation of Versailles treaty | 8, v 1, pp 367-70 and Ref 12 |
| 7.92 mm Parabellum Light Machine Gun M 1913, manufd by DWM and used during WW I | Short recoil-operated, air-cooled MG weighing (with feed) 22 lb | 2, p 314; 8, v 1, pp 310-13 & 662 and Ref 12 |
| 7.92 mm Bergmann Aircraft, Machine Guns M 1915 and M 1915 NA (New Pattern) were used during WW I | Short recoil-operated, air-cooled MGs weighing 36 lb (with feed) | 2, p 315; 8, v 1, pp 365-7 & 658 and Ref 12 |
| 7.92 mm Gast Double-Barrel Aircraft Machine Gun M 1918 | Recoil and gas actuated, air-cooled MG weighing 60 lb. It was secretly manufd after WW I | 8, v 1, p 379 |
| 7.92 mm Solothurn Machine Gun M 1929 | Short recoil-operated, air-cooled MG weighing only 17 lb | 8, v 1, pp 453 & 664 |
| 7.92 mm Solothurn Machine Gun M 1930 | Short recoil-operated, air-cooled MG weighing 18.5 lb | 8, v 1, pp 453-4 & 664 |
| 7.92 mm Aircraft Machine Gun, adopted in 1932 under the name of Maschinengewehr 15 (MG-15) | Short recoil-operated, air-cooled MG weighing 27½ lb | 8, v 1, pp 445 & 662 |
| 7.92 mm Aircraft Machine Gun, adopted before WW II under the name of Maschinengewehr 17 (MG-17) | An improved version of MG-15. Wt (with feed) 27¼ lb | 8, v 1, pp 455-6 & 662 |
| 7.92 mm Mauser Carbine M 1898, Short (Karabiner 98 Kurz, abbr to Kar-98K or Kb-98K), mass produced beginning 1935. Was the principal military small arm used during WW II. Its essential difference from Gew 98 was in the improved bolt sleeve, sights and shorter barrel | Length of barrel 23.4" and overall (without bayonet) 43.5"; wt 9 lb. Type of action: turnbolt-rotating head; type of bolt: one piece rotating head; type of magazine: box-staggered column; capacity: 5 rimless, necked, center-fire cartridges as in Kur 98. Muz vel 2800 ft/sec | 10, v 2, pp 176, 174 & 179; 11, pp 422, 429-30, and Ref 12 |
| 7.92 mm Grenade Rifle (Launcher Grenade) (Modification of Karabiner 98 K) | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 7.92 mm Knorr-Bremse Machine Guns M 1933 and M 1935/36 were developed by H. Lauf of the Knorr-Bremse Manufg Co, Lichtenberg | Gas-operated air-cooled MGs. The latest model weighed 18½ lb (with feed) | 8, v 1, pp 469-71 & 660 |
| 7.92 mm Mauser Light Machine Gun, called MG-34, was developed about 1934 at the Mauser Plant and became the standard MG of the German Army | Short recoil-operated, air-cooled MG weighing 24½ lb (with feed). Barrel length 23¼", muz vel ca 2750 ft/sec, rate of fire 750-800 rpm and range 5000 yd | 8, v 1, pp 472-4 & 662; 11, pp 503-8 and Ref 12 |
| 7.92 mm Light Machine Guns MG-34 (Modified MG-34s and MG-34/41) | Slightly modified versions of MG-34 | 8, v 1, pp 475-7 and Ref 12 |
| 7.92 mm Light Machine Gun MG-81, developed in 1938 at the Mauser plant (Aircraft Model) | Recoil-operated and air-cooled. Wt (with feed) 13¼ lb, rate of fire 1200-1300 rpm and muz vel 2750 ft/sec. It was a modification of the MG-34, designed for flexible mounting | 8, v 1, pp 478-9 & 662 |
| 7.92 mm Light Machine Gun MG-81, ground use | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 7.92 mm Aircraft Machine Gun, Model 39 (Krieghoff) | Same as above | 12 |
| 7.92 mm Antitank Rifle PzB-38, PzB-39 and PzB-40 (Krieghoff) | Same as above | 12 |
| 7.92 mm Gewehr 98/40 (Modification of the Hungarian Service Rifle M 1935) | Essentially the Mannlicher-Schönauer turnbolt rifle equipped with a Mauser type magazine. Overall length 43.5", barrel 24", wt 9 lb | 11, p 430 and Ref 12 |

WEAPONS


(SUBMACHINE GUNS AND MACHINE GUNS)




7 mm BERGMANN
MACHINE GUN
MODEL 1915



7.5 mm FÜRER MACHINE GUN
MODEL 1925




7.5 mm DARNE
AIRCRAFT MACHINE GUN
MODEL 1916 (DUAL FLEXIBLE
MOUNT)



7.5 mm DARNE MACHINE
GUN MODEL 1929




7.92 mm MAXIM
MACHINE GUN
MODEL 08/15
WATER COOLED



7.63 mm
MAUSER
SUBMACHINE
GUN
(MASCHINEN-
PISTOLE) MODEL 1932




7.92 mm
MAXIM MACHINE
GUN MODEL 08
WITH SLED MOUNT




7.92 mm
BERGMANN
MACHINE
GUN MODEL
1910, WATER
COOLED

7.92 mm MAXIM AIRCRAFT MACHINE
GUN MODEL 08/15, CALLED
"SPANDAU MG"



7.92 mm
DREYSE
MACHINE
GUN
MODEL 1912
(MG-12)
WATER
COOLED




7.92 mm PARABELLUM
AIRCRAFT MACHINE GUN MODEL
1913, WITH MODIFIED BARREL
JACKET


7.92 mm GAST AIRCRAFT MACHINE GUN
MODEL 1916-1917 (WITH FEED DRUMS
REMOVED)



7.92 mm DREYSE
MACHINE GUN
MODEL 1913 (MG-13),
AIR COOLED



7.92 mm MAUSER
AIRCRAFT MACHINE
GUN MODEL 81,
DUAL MOUNT




7.92 mm
LIGHT AIRCRAFT
MACHINE GUN MG-81,
MODIFIED FOR
GROUND USE

(Weapons) (cont'd)


| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|---|---|
| 7.92 mm Gewehr 33/40 (Modification of Czech Model 33) | Short weapon (barrel 18") used by mountain and ski troops | 11, p 430 and Ref 12 |
| 7.92 mm Gewehr 98/40 and 29/40 Mauser | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 7.92 mm Antitank Rifle, Model SS-41 | Same as above | 12 |
| 7.92 mm Semi-Automatic Rifle Model 41-M (Halbautomatisches Gewehr 41-M) developed at Mauser plant | Gas-operated weapon which did not prove to be successful in field use | 10, v 2, pp 187-8 & 11, pp 432 & 438 and Ref 12 |
| 7.92 mm Semi-Automatic Rifles Gew-41 (G-41) and its improved version G-41W were designed by Walther | Experimental gas-operating weapons incorporating some features found in pre-WW II Russian Degtiarev, Simonov and Tokarev weapons | 4, pp 111-13; 10, v 2, pp 188-9; 11, pp 432-7 & Ref 12 |
| 7.92 mm Semi-Automatic Rifle M 1943 (Gew-43) and Carbine M 1943 (Kar-43) were developed during WW II in order to do away with some defects of G-41 and G-41W weapons | These weapons were gas operated and the action was of the straight-line (non-rotating) bolt type. Characteristics of Gew 43: overall length 44.5", barrel 22", wt 8.9 and magazine capacity 10 cartridges from two Mauser 5-round clips | 10, v 2, pp 189-197 & 11, pp 432-43 |
| 7.92 mm Automatic Rifle, M 1942 (Light Machine Gun), called Fallschirmjäger Gewehr 42 (Paratrooper's Rifle 42), abbr to FG-42. It was fitted with a folding bipod mount | Gas-operated, air-cooled weapon of revolutionary design. Overall length (without bayonet) ca 42", barrel ca 19" and wt 9 ¹ / ₂ lb (without magazine). Magazine: straight box inserted on the left side | 4, pp 176-79; 8, v 1, p 489-91; 11, p 444 and Ref 12 |
| Note: This weapon was manufd by the H.Krieghoff Waffenfabrik, Suhl. It was also made in the U S A under the designation of T-44 | | |
| 7.92 mm Automatic Rifle, M 1942, Modified | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 7.92 mm Light Machine Gun, MG-42 was the latest German machine weapon of WW II and the most remarkable gun of its type ever produced in any country of the world. MG-42 incorporated the best features of previous Russian and German MGs | Short recoil-operated, air-cooled MG weighing 24 lb (with feed). Rate of fire 1200-1350 rpm and muz vel 2570 ft/sec. Used 7.92 mm German Service ammunition | 4, pp 176-9; 8, v 1, pp 484-8 & 662; 11, pp 509-16 & Ref 12 |
| 7.92 mm Machine Carbine (Maschinen-Karabiner, abbr to MKb-42) | Was used on the Russian front. Its improved version appeared in 1943 on the Western front under the designation MP-43. It was practically identical with MP-44 described below | 11, pp 500 and 502 |
| 7.92 mm Machine Carbines MKb-42 (H) and MKb-42(W). Called also Submachine Guns | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 7.92 mm Carbine 1943, Kb-43 | Same as above | 12 |
| 7.92 mm Machine Pistol M 1944 (Maschinenpistole 44), was originally developed in 1942 and then improved in 1943. On Hitler's order it was called Sturmgewehr 44 (StuG-44) | Gas-operated, air-cooled weapon of remarkable design and manuf. It was practically identical with Maschinenpistole 43 (MP-43) and Karabiner 44 (K-44). Overall length 36 ¹ / ₂ ", barrel ca 16", wt (not given), capacity 30 cartridges of special design | 11, pp 499-501 and Ref 12 |
| Note: The cartridge used in the latest 7.92 mm weapons, such as machine carbines and machine pistols, was a cut-down version of the standard bottle-neck rifle cartridge using a 125 grain pointed bullet. Muzzle velocity was ca 2250 ft/sec ca 650 yd (Ref 11, p 502) | | |
| 7.92 mm People's Rifle 1 (Volksturm Gewehr 1, abbr to VG-1), manufd by K. Walther, Suhl | Short, turnbolt action rifle, manufd with the intention of issuing it to civilians for home defense. Overall length 43", barrel 23.2", wt 8.3 lb and magazine capacity 10 | 10, v 2, pp 181-3; 11, p 431 and Ref 12 |
| 7.92 mm People's Rifle Special (Short) was developed in 1942 by H. P. al of Suhl and introduced in 1945 | Weapon of very original design and of great simplicity. Overall length 34.9", barrel 14.9", wt 9.4 lb and magazine capacity 30 | 10, v 2, pp 198-9 & 11, pp 445-7 |
| 8 mm (.315") Schwarzlose Machine Gun M 1907/12, invented by A. W. Schwarzlose of Germany and first manufd by the Steyr Arms Works in Austria | Operated by retarded blow-back and cooled by water. Wt 46 ¹ / ₂ lb, muz vel 1875 ft/sec and rate of fire 400-450 rpm | 8, v 1, pp 228-31 |

Ger 234
WEAPONS


(SUBMACHINE GUNS AND MACHINE GUNS)



UPPER PHOTO-7.92 mm MAUSER MACHINE GUN MODEL 4 (MG-34) MOUNTED ON A TRIPOD FOR USE AS A HEAVY MACHINE GUN
LOWER PHOTO-7.92 mm MAUSER MACHINE GUN (MG-34) (USED AS A LIGHT MACHINE GUN WITH A 50-SHOT DRUM MAGAZINE)




7.92 mm MAUSER MACHINE GUN MODEL 1934S




7.92 mm KNORR-BREMSE MACHINE GUN MODEL 35/36




7.92 mm SUBMACHINE GUN [MASCHINENKARABINER 42(H)]




7.92 mm KRIEGHOFF AIRCRAFT MACHINE GUN MODEL 1939 (MG-39)




7.92 mm LIGHT MACHINE GUN MODEL 1942 (MG-42)




7.92 mm WALTHER SUBMACHINE GUN MASCHINENKARABINER 42(W)




7.92 mm SUBMACHINE GUN (MASCHINENPISTOLE MP-43)



7.92 mm SUBMACHINE GUN (MP-43/I)



7.92 mm MACHINE GUN MODEL 42, MOUNTED ON A TRIPOD



7.92 mm SUBMACHINE GUN [MP-44 OR STUG (STURMGEGWEHR) 44]


(Weapons) (cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|--|--|
| 9 mm (.354") Luger (Parabellum) Automatic Pistols Models 1902, 1902/06, 1904 and 1904/06 (M 02, M 02/06, M 04 and M 04/06) | Barrel lengths: 4" for M 02 & M 02/06 and 6" for M 04 and M 04/06. The last two models were issued with a leather holster attached to a wooden stock. The M 04 was an official German Navy weapon used during WW I | 4, pp 271-3; 10, v 1, pp 182 & 417-18 and Ref 12 |
| [See also Note given under 7.65 mm Luger (Parabellum) Pistols M 1900 and 1900 and 1900/06] | | |
| 9 mm Luger (Parabellum) Automatic Pistol Model 1908 (Official German Army Weapon of both WWs). It was slightly modified in 1920 | Recoil-operated. Lengths: barrel 4" and overall 8 1/2"; wt 30 oz; magazine capacity 8 cartridges with round or flat point bullets weighing 110 and 125 grains. Muz vel 1040 to 1500 ft/sec | 10, v 1, pp 182 & 418-19; 11, pp 456-63 and Ref 12 |
| Note: Special 6", 8" and 10" barrels were provided for this pistol. The model using an 8" barrel and called 9 mm Parabellum M 08 Lang (long) was issued to artillery and "Z" boat personnel | | |
| 9 mm Mauser Automatic Pistol, Military Model, also called Maschinenpistole. Used in WW I and to a limited extent in WW II | Same design as 7.63 mm Mauser. Magazine capacity 10 Luger cartridges. Could be fired with shoulder stock holster attached to magazine | 4, pp 275-8; 10, v 1, p 420 and Ref 12 |
| 9 mm Bergmann Automatic Pistol M 1910 was manufd for the Greek Army. There was also a Model 18-1 | Similar in size and design to the Belgian 9 mm Bergmann-Bayard except that it was lighter (32 oz) | 10, v 1, pp 439-41; 11, p 491 and Ref 12 |
| 9 mm Bergmann Automatic Pistol (Maschinenpistole) M 1934, called also Submachine Gun | Modification of Model 18-1 | 11, pp 491-2 and Ref 12 |
| Note: This weapon was officially adopted by Sweden in 1937 and for this reason is briefly described in the Swedish section. | | |
| 9 mm Steyr Automatic Pistol, invented prior to WW I | Recoil-operated; magazine capacity 8 rounds | 2, p 322 |
| 9 mm Steyr-Solothurn Automatic Pistol (Maschinenpistole) (MP), called in the U S A Submachine Gun and in Gt Britain Machine Carbine. Also designated as S1-100 | Operated by recoil on the blowback principle. Overall length 32 1/2"; wt 9 1/2 lbs; magazine capacity 30 Parabellum cartridges. Muz vel 1100 to 1600 ft/sec | 4, pp 246-8; 11, pp 496-7 and Ref 12 |
| 9 mm Walther Automatic Pistol, invented before WW I | Blowback-operated. Served as the prototype for later models. Capacity 8 | 2, p 322 |
| 9 mm Walther Automatic Pistol, originally introduced as Model HP, was officially designated as P-38. This model was called "Walther Armeepistole" | Operated by short recoil. Length barrel 4 1/2" and overall 8 1/2"; wt 34 oz; magazine capacity 8 Parabellum cartridges | 2, p 322; 4, pp 278-80; 10, v 1, pp 425-82; 11, pp 450-55 and Ref 12 |
| Note: Several factories manufd it during WW II | and it was extensively used by the Armed Forces | |
| 9 mm Schmeisser Machine Pistol, MP-28 II | Blowback-operated. Length barrel 7.8" and overall 31.6"; wt 9 lb; capacity 32 Parabellum cartridges | 11, p 495 and Ref 12 |
| 9 mm Schmeisser Maschinen Pistole 38 (MP-38), called in the U S A Sub-machine Gun, Parachute Model | Operated by blowback. Overall length (with stock extended) 35"; wt (without magazine) 9 lb. Magazine capacity 32 Parabellum cartridges | 11, pp 486-7 and Ref 12 |
| 9 mm Submachine Gun, MP-34/1, Bergmann | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 9 mm Machine Carbine, M-35/1 | Same as above | 12 |
| 9 mm Schmeisser Maschinen Pistole (MP-40) called in the U S A Submachine Gun and Burp Gun | Slight modification of MP-38; same dimensions. Cyclic rate of fire 500 rpm | 4, pp 248-50; 7, p 37; 11, p 490 and Ref 1 |
| 9 mm Automatic Browning Pistol, M 1935, designed 10 years earlier by J.M. Browning. Was used during WW II by SS troops | Recoil-operated; length: barrel 4" and overall 7 1/2"; wt 35 oz; capacity 13 | 10, v 1, pp 404-8 |
| 9 mm Dreyse Automatic Pistol, Military Model | One of the earliest blowback operated pistols, manufd in the closing years of WW I | 10, v 1, pp 408-10 |
| 9 mm Erma Machine Pistol, sometimes called the Schmeisser Machine Pistol or Carbine | Overall length 33 1/2"; wt 9 lb and cyclic rate of fire 520 rpm | 11, p 493 |
| 9 mm Neuhausen Machine Pistol | Capacity 40 cartridges; wt of pistol 9 lb 2oz | 11, p 494 |
| 9 mm Submachine Gun, EMP-40 and EMP-41 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 10.15 mm (.40") Norwegian Rifle | Used Norwegian ball ammo, type 522 | 3a, p 8 |

Ger 236

WEAPONS


(SUBMACHINE GUNS AND MACHINE GUNS)



9 mm SCHMEISSER SUBMACHINE GUN
(MASCHINENPISTOLE 28 II)



9 mm BERGMANN SUBMACHINE GUN
(MASCHINENPISTOLE 34 / I)



9 mm SUBMACHINE GUN
(MASCHINENKARABINER 35 / I)




9 mm SUBMACHINE GUN
(MASCHINENPISTOLE 36)



9 mm SUBMACHINE GUN
(MASCHINENPISTOLE EMP-40)



9 mm SUBMACHINE GUN
(EMP - 44)



13 mm RHEINMETALL AIRCRAFT
MACHINE GUN MODEL 131, FIXED



13 mm RHEINMETALL AIRCRAFT
MACHINE GUN MODEL 131, FLEXIBLE




15 mm
MACHINE GUN
MG-151 / 15
(TRIPLE ANTI-AIRCRAFT
GUN ON PEDESTAL
MOUNT)

(Weapons) (cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|--|------------------------------------|
| 11 mm (.433") Single Shot Rifle Mauser M 1871 (Gewehr 71) | Tumbolt action; the first metallic cartridge breechloader officially adopted in Germany Wt without bayonet 10.3 lb. It used black powder | 10, v 2, pp 200 & 204 |
| Note: Previous to the Mauser M 1871, the Prussian Army (Germany did not exist as such until 1871) used the so-called Needle Gun (Zündnadelgewehr) invented in 1836 by a gunsmith Nicolas von Dreyse (1787-1867) and officially adopted successfully in the wars of 1866 (against the Austrians) and in 1870-71 (against the French). It fired a conical bullet (caliber 15.43 mm) encased in a papier-mâché cartridge together with a charge of black powder. | | |
| References: a) W.W.Greenier, The Gun, Cassell, Letter & Galpin, London (1881), pp 199-200 b) Encyclopedia Britannica, London, vol 16 (1952), p 190 | | |
| 11 mm Rifle Model 1884 (Gewehr 84) was developed by Mauser and a German Army Commission | A slightly shorter and lighter Model 1871 altered to take a tubular magazine with a capacity of 8 rounds. It used black powder | 10, v 2, p 204 |
| 11 mm Revolver, German Service M 1880. Although obsolescent it was used by the Armed Forces as late as WW II | It used a cartridge contg ca 20 grains of black powder and a lead bullet weighing 210 gr | 10, v 1, pp 467-8 and Ref 12 |
| 11 mm French Parabellum Pistol | Used French ball ammo | 5a, p 8 |
| 11 mm French Rifle 1879/83 | Used French ball ammo | 5a, p 8 |
| 12.7 mm (.50") Maxim Machine Gun T u F (Tank und Flieger) for use in tanks and aircraft. One of the secret weapons of WW I. About 6000 were produced in 1918 but none was used in combat | Short recoil-operated and cooled by air or water. Wt (with feed) 84 lb, rate of fire 400-450 rpm and muz vel 2750 ft/sec. Used British, German, Italian and Russian ammo | 5a, p 8 and 8, v 1 pp 515-16 & 664 |
| 13 mm (.512") Tuff-Mauser A/T Machine Gun, Mod 1918 | Can be seen at the Aberdeen Proving Ground (Listed as a 13.2 mm weapon) | 3, p 211 and Ref 12 |
| 13 mm AC Machine Gun, MG-131, developed in 1938 by the Rheinmetall-Borsig | Short recoil operated and air-cooled. Wt (with feed) 40 lb, rate of fire 850-960 rpm and muz vel 2560 ft/sec | 8, v 1, pp 557-60 & 662 |
| 13 mm Solothurn Machine Gun | Used HE, HEI-T, AP-T and T ammo | 9, p 543 |
| 13.2 mm (.52") French Machine Gun [13.2 mm MG 271 (f)] | Used French, Belgian and Polish ammo | 5a, p 9 |
| 13.9 mm (.55") British Machine Gun | Used British AP ammo [13.9 mm Patr Smk 895 (e)] | 5a, p 8 |
| 14.5 mm (.571") Russian A/T Rifle, Panzerabwehrbüchse 784 (r) | Used AP-Inc and SAP Russian ammo | 5a, p 13 |
| 15 mm (.590") Machine Gun MG-151/15, Antiaircraft, Triple Pedestal Mount | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 15 mm Mauser Machine Gun (15 mm MG-151, Mauser) | Used HE-T, HEI-T(SD), HEI-T(SD), AP-T, AP Tungsten core and T ammo | 5a, p 9, 9, p 543 & Ref 12 |
| 15.43 mm (.607") Needle Gun M 1862 (See Note under 11 mm Single Shot Rifle) | Can be seen in the Museum of Aberdeen Proving Ground, Md | 12 |
| 20 mm (.787") Czakats Automatic AC Cannon, Models CZA-1, CZA-2, CZB CZC. Developed during WW I by a Polish engineer, G.Sczakata but never used in combat | Blowback-operated and air-cooled. Wt (with feed) 91 lb, rate of fire 400-450 rpm and muz vel 1500 ft/sec | 8, v 1, pp 523-5 & 668 |
| 20 mm (.787") Becker Automatic AC Cannon, developed in 1918 | Blowback-operated and air-cooled. Wt (with feed) 66 lb, rate of fire 300-350 rpm and muz vel 1570 ft/sec | 8, v 1, pp 512 & 666 and Ref 12 |
| 20 mm Ehrhardt Automatic AC Cannon, developed at the end of WW I | Short recoil-operated and air-cooled. Wt (with feed) 160 lb, rate of fire 250-300 rpm and muz vel 2200 ft/sec | 8, v 1, pp 550 & 666 |
| 20 mm Lübbe AC Cannon, invented in 1929 by H.Lübbe but not accepted by the German Govt | Operated by gas-actuated piston and cooled by air. Wt (with feed) 107 lb, rate of fire 360 and muz vel 2650 ft/sec | 8, v 1, pp 548-9 & 666 |
| 20 mm Rheinmetall-Solothurn Automatic Cannon, MK-ST-3, a Naval Mount, developed before WW II | No characteristics given | 8, v 1, pp 551-2 |
| 20 mm Rheinmetall Automatic AC Cannon, MK-ST-11, developed before WW II | Short recoil-operated and air-cooled. Wt (with feed) 118 lb, rate of fire 350-380 and muz vel 2250 ft/sec | 8, v 1, pp 553 & 668 |
| 20 mm Rheinmetall-Solothurn Semi- Automatic A/T Cannon, developed before WW II | No characteristics given | 8, v 1, p 553 |

Ger 238
WEAPONS

CALIBERS 20 mm AND 28/20 mm




20 mm BECKER AUTOMATIC AIRCRAFT CANNON MODEL 1918 (FLEXIBLE)

20 mm RHEINMETALL AUTOMATIC AIRCRAFT CANNON MODEL ST-11



20 mm SEMI-AUTOMATIC ANTITANK CANNON RHEINMETALL-SOLOTHURN, DEVELOPED BEFORE WWII





20 mm FLEXIBLE AIRCRAFT CANNON, SHORT CASE (2 cm OERLIKON MG-FF)




20 mm RECOILLESS NINE BARREL GUN


20 mm QUADRUPLE ANTI-AIRCRAFT GUN (2 cm FLAK-38) ON TANK CHASSIS




20 mm RHEINMETALL-SOLOTHURN AUTOMATIC CANNON MODEL ST-5 ON A NAVAL MOUNT




20 mm OERLIKON ANTI-AIRCRAFT MACHINE CANNON (2 cm FLAK 29)



20 mm MAUSER AUTOMATIC AIRCRAFT CANNON MODEL 151, MOUNTED FOR ANTITANK DUTY



20 mm AUTOMATIC INFANTRY CANNON "SEMAG"



28/20 mm GERLICH TAPERED BORE ANTITANK GUN (2.8/2.0 cm PAK 41)



(Weapons) (cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|--|---|--|
| 20 mm Rheinmetall Automatic AA Cannon, Flak 30, developed before WW II | Short recoil-operated and air-cooled. Wt (with feed) 141 lb, rate of fire 200-280 and muz vel 2950 ft/sec. Used HE-T projectiles | 5b, table 1 and 8, v 1, p 666 |
| 20 mm Oerlikon Short Case AC cannon (2 cm Oerlikon MG-FF) | Used projectiles: HE, HE (self-destroying), HEI-T, AP, APHE and API | 5a, pp 41-5 |
| 20 mm Oerlikon Automatic AC Cannon, Models F and S, developed by the Oerlikon Co., Zürich and adopted by the Germans before WW II | Blowback-operated and air-cooled. Wt (with feed) 136 lb, rate of fire 280 and muz vel 2610 ft/sec | 5a, p 44; 8, v 1, pp 516 & 618 and Ref 12 |
| 20 mm Oerlikon AA Cannon (2 cm Flak 28) | Used AP, AP-T, HE, HE-T, HEI-T and HE-T self-destroying projectiles | 5a, p 43 |
| 20 mm Oerlikon AA Cannon (2 cm Flak 29) | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 20 mm Mauser Automatic AC Cannon, Model 151 (MG-151), developed before WW II by the Waffenfabrik Mauser A-G | Short recoil-operated and air-cooled. Wt (with feed) 9 3/4 lb, rate 700-750 and muz vel 2590 ft/sec. Called by Smith (Ref 9) one of the most remarkable AC MGs in existence | 5a, p 45; 8, v 1, pp 602-4 & 666; 11, p 501 and Ref 12 |
| 20 mm Mauser Automatic AA Cannon, Flak 38 | Short recoil-operated and air-cooled. Wt (with feed) 123 lb, rate of fire 420-480 and muz vel 2950 ft/sec | 8, v 1, pp 605-6 & 666 and Ref 12 |
| 20 mm Dutch A/T Rifle [2 cm PzB 785 (h)] | Used Dutch AP and HE ammo | 5a, p 13 |
| 20 mm French Machine Gun [2 cm MG 39 (i)] | Used French HE shell, type 39 | 5a, p 13 |
| 20 mm Solothurn Cannons: 2 cm KwK 30, 2 cm KwK 38 2 cm Flak 30, 2 cm Flak 38 2 cm Flak Vierling 38, 2 cm GebFlak 38 and Italian 2 cm M 35 (i) | Used ammunition: HE, HEI, HEI-T HE-T, HE-T (self-destroying, HE (Italian), AP, AP-T, API-T, AP-T (self-destroying), AP-T (irritant) and AP (Italian) | 5a, pp 43-4 |
| 20 mm Mauser Machine Gun, MG-213, developed during WW II | Not described here because the reference is confidential | 8, v 3, pp 44-51 |
| 20 mm Recoilless Cannon (9 barrels) | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 20 mm and 25 mm Semag Automatic Cannon for Infantry (Mounted on a wheeled carriage) | Developed in 1921 and 1923 but not adopted in Germany because it was considered to be too heavy. A number of Semags were sold before 1930 to China and to Spain | 8, v 1, pp 514-15 |
| 25 mm (.984") French AA Gun [2.5 cm Flak Hotchkiss (f)] | Used French HE and HE-T shells | 5a, p 14 and Ref 12 |
| 25 mm French A/T Guns: 2.5 cm Pak 112 & 113 (f) and 2.5 cm KwK 121 (f) | Used French AP type 114 shell | 5a, p 14 |
| 27 mm (1.063") Signal Pistol (Kampfpistole), Modified | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 28/20 mm (1.102/0.787") Tapered Bore A/T Rifle (sPzBü 41), called also Squeeze Bore or Gerlich Gun | Used ammo: HE (2.8 cm Sprgr Patr 41) and AP (Pzgr Patr 41) | 5a, p 14; 9, p 371 and Ref 12 |
| 30 mm (1.181") Mauser Machine Gun, MK-213C, developed during WW II | Not described here because Ref 8, v 3 is confidential | 8, v 3, p 44 |
| 30 mm Rheinmetall Automatic AC Cannon, MK-101, developed in 1942 | Short recoil-operated and air-cooled. Wt (with feed) 335 lb, rate of fire 230-260 and muz vel 2950 ft/sec | 8, v 1, pp 555-61 & 666-8 |
| 30 mm Rheinmetall Automatic AC Cannon MK-103, developed in 1943 | Operated by gas-actuated piston and air-cooled. Wt (with feed) 308 lb, rate of fire 420 and muz vel 2820 ft/sec | 8, v 1, pp 555-61 666-8 & Ref 12 |
| 30 cm Rheinmetall Automatic AC Cannon MK-108, developed in 1944 | Blowback-operated and gas-cooled. Wt (with feed) 135 lb, rate of fire 400-450 and muz vel 1640 ft/sec | Same as above |
| 30 mm Automatic Recoilless Cannons, SG-110, SG-117 and SG-118, developed during WW II by the H.Görsing Werke | Not described here because the reference is confidential | 8, v 3, pp 630-31 |
| 30 mm Solothurn AC Cannon (3 cm Flak K) | Used HE and AP ammo: 3 cm Sprgr and 3 cm Page 40 | 9, p 379 |
| 30 mm Aircraft Machine Cannon, MK-303 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |

Ger 210


WEAPONS

(CALIBERS 30 mm TO 47 mm INCLUSIVE)



37 mm AUTOMATIC ANTI-AIRCRAFT CANNON RHEINMETALL FLAK 18


30 mm AUTOMATIC AIRCRAFT CANNON RHEINMETALL MK-103




30 mm AUTOMATIC AIRCRAFT CANNON RHEINMETALL MK-101




37 mm ANTI-AIRCRAFT GUN (3.7 cm FLAK 43)




37 mm ANTI-AIRCRAFT GUN (3.7 cm FLAK 36) MOUNTED ON B TON HALF TRACK



42/28 mm ANTITANK GERLICH TAPERED BORE GUN (4.2/2.8 cm PAK-41)



47 mm ANTITANK GUN ON Pz Kw I CHASSIS






47 mm ANTITANK GUN M38 (CZECH DESIGN)

(Weapons) (cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|---|---|
| 37 mm (1.457") Rheinmetall Automatic AA Cannon, Type 18 (3 cm Flak 18), developed prior to WW II by Rheinmetall-Borsig A.-G. | Short recoil-operated and air-cooled. Wt (with feed) 595 lb, rate of fire 160-180 and muz vel 2520 ft/sec. Used projectiles: HE, HEI, HEI-T, HE (high capacity) and AP | 8, v 1, pp 554 & 666; 5a, pp 45-6 & 9, p 384 |
| 37 mm AA Cannons: 3.7 cm Flak 36, Flak 37 and Flak 43 | Used ammo: HE (3.7 cm Sprgr Patr 18), HE, high capacity (Mingr Patr 18), HEI (Br Sprgr Patr 18), HEI-T (Br Sprgr Patr 18 L'spur) and AP, without cap (Pzgr Patr 18) | 5a, pp 45-6; and 9, p 384 |
| 37 mm A. T Cannon (3.7 cm Pak) | Used: AP proj with core, arrowhead design (3.7 cm Pzgr Patr 40); AP proj without cap (Pzgr Patr) and HE proj lb modified (Sprgr Patr 18 umg) | 5a, p 15 and 9, pp 373 & 386 |
| 37 mm A. T Cannon, Fixed Defence (3.7 cm Pak K) | Used ammo: HE (3.7 cm Sprgr Patr) and AP (Pzgr Patr 18 umg) | 5a, p 15 |
| 37 mm Naval Gun: 3.7 cm SK C/30 | Used ammo: HE (3.7 cm Sprgr Patr 40) and HE-T (Sprgr Patr L'spur) | 5a, p 15 and 9, pp 382 & 388 |
| 37 mm Naval Gun: 3.7 cm SK C/36 | Used HE projectiles | 5b, table 1 |
| 37 mm Tank Gun: 3.7 cm KwK | Used ammo: HE (3.7 cm Sprgr Patr 18 umg & Sprgr Patr 40), HE-T (Sprgr Patr 18 L'spur), AP (Pzgr Patr & Pzgr Patr 40) and Stick grenade (Stielgr 41) | 5a, p 35 |
| 37 mm A/T Gun: 3.7 cm Pak 41 | Used stick (rodged) bomb: 3.7 cm Stielgr 41 | 9, p 383 |
| 37 mm Czech A/T Gun: 3.7 cm Pak 37 (t) | Used Czech ammo: HE (3.7 cm Sprgr Patr 34), AP (Pzgr Patr 34, 37, 37 umg & 40/37) and Stick Grenade (Stielgr 41) | 5a, p 16 |
| 37 mm Czech Tank Gun: 3.7 cm KwK 38 (t) | Same as above | 5a, p 36 |
| 37 mm French Tank Guns: 3.7 cm KwK 143 (f) (lang) and 144 (f) (kurz) | Used French HE and AP ammo: 3.7 cm Sprgr Patr 145, 147, 148 (f) and Pzgr Patr 145 & 146 (f) | 5a, p 35 |
| 37 mm French Light Gun: 3.7 cm LK 152 (f) | No description given | 5a, p 59 |
| 37 mm Russian Infantry Howitzers: 3.7 cm IG 145 & 146 (r) | No description given | 5a, p 59 |
| 37 mm Polish A/T Gun, called by the Germans 3.7 cm Pak (p) | Used Polish design AP proj: 3.7 cm Pzgr (p) | 9, p 382 |
| 37 mm Cannons: Flak 36, Pak 37, Flak 43, Revolver Cannon and AC Cannon (used in Stuka aircraft) | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 40 mm (1.575") AA Gun, Type 28 (4 cm Flak 28) | Used ammo: HE (4 cm Sprgr Patr Lh 28), HE-T (Sprgr Patr L'spur), HEI (Br Sprgr Patr) AP (Pzgr Patr, 18) and AP-T (Pzgr Patr L'spur) | 5a, p 46 and 9, pp 388-9 |
| 42/28 mm (1.654/1.102") Tapered Bore Gun 41 (4.2/2.8 cm IPak 41), called also Gerlich Gun or Squeeze Bore Gun | Used ammo: HE (4.2 cm Sprgr Patr IPak 41) and AP with core (Pzgr Patr) | 5a, p 46 and 9, pp 388-9 |
| 44.5 (1.75") mm Recoilless Grenade Discharger Panzerfaust 30, klein (Armored Fist, type 30, small) formerly called Faustpatrone 1, (Fist Cartridge, type 1) and a larger model Panzerfaust 30, formerly called Faustpatrone 2 | Smooth-bore tube, 1.75" diameter and 31.5" long which fired a hollow charge A/T missile, resembling in appearance a rodged hand grenade. Projectile available at Museum of Picatinny Arsenal is 19 1/2" long of which the warhead is 9 1/2" long and the finned cylindrical body is 10". Diameter of warhead is 3 1/2" and of body 1 1/2" | 9, pp 339-40 11, p 522 and Ref 13 |
| Note: Later models of weapon were called Panzerfaust 60 and Panzerfaust 100 (See description under Faustpatrone) | | |
| 45 mm (1.772) Russian A/T Guns: 4.5 cm Pak 184 u 184/1 (r) | Used Russian HE and AP ammo | 5a, p 17 |
| 45 mm Russian Tank Guns: 4.5 cm KwK 184/2, 184/3 & 184/4 (r) | Used Russian HE and AP ammo | 5a, p 17 |
| 45 mm Russian Infantry Howitzer: 4.5 cm IG 186 (r) | No description, given | 5a, p 59 |
| 45 mm Italian Mortar: 4.5 cm GrW 176 (l) | Used HE bomb, wgr (l) | 5a, p 26 |
| 46 mm (1.811") Polish Mortar: 4.6 cm G:W 31 (p) and GrW 36 (p) | No description given | 5a, p 26 |

WEAPONS


(CALIBERS 50mm TO 75mm)





| Caliber and Designation | (Weapons) (cont'd) Remarks, Uses and Some Characteristics | References |
|--|---|--------------------------------------|
| 47 mm (1.850") Austrian "Böhler" Gun 4.7 cm Böhler K(ö) or 4.7 cm Pak Böhler (ö) | Used Austrian design AP and HE ammo; 4.7 cm Pzgr Patr 35 (ö) and Sprgr Patr (ö) | 5a, p 17 and 9, pp 391-2 |
| 47 mm Belgian A/T Gun, 4.7 cm Pak 185 (b) | Used Belgian HE and AP ammo | 5a, p 17 |
| 47 mm Czech Guns: 4.7 cm K 36 (t), Pak Skoda 1936 (t) and Flak 37 (t) | Used Czech design HE and AP ammo: 4.7 cm Sprgr Patr 36 (t), Pzgr Patr 36 (t) and Flak 37 (t) | 5a, p 18, 9, pp 390-2 & Ref 12 |
| 47 mm French A/T Gun, 4.7 cm Pak 18 u 183 (f) | Used French HE and AP ammo: 4.7 cm Sprgr Patr and Pzgr Patr | 5a, p 17 |
| 47 mm French Tank Gun: 4.7 cm KwK 173 (f) | Used French HE and AP ammo: 4.7 cm Sprgr Patr 175 (f) and Pzgr Patr 176 (f) | 5a, p 36 |
| 47 mm Italian A/T Gun, 4.7 cm Pak 177 (i) | Used Italian HE and AP ammo | 5a, p 17 |
| 50 mm (1.9685") Tank Gun: 5 cm KwK | Used ammo: HE (5 cm Sprgr Patr 38), AP (Pzgr Patr 39, 40 & 40/1) and Stick grenade (Stielgr 42) | 5a, pp 36-7 and 9, pp 376 & 395-5 |
| 50 mm Tank Gun 38: 5 cm KwK 38 | Used AP ammo: 5 cm Pzgr Patr | 9, p 395 & Ref 12 |
| 50 mm Long Tank Guns: 5 cm KwK 39 (L/60), KwK 39/1 and KwK 39/2 (L/60) | Used ammo: HE (5 cm Sprgr Patr 38), AP (Pzgr Patr 39, 40 & 40/1) and Stick Grenade (Stielgr 42) | 5a, p 37 |
| 50 mm Tank Guns: 5 cm KwK 40 and KwK L/42 | Used ammo: HE (5 cm Sprgr Patr 38), AP (Pzgr Patr 39, 40 & 40/1) and Stick Grenade (Stielgr 42) | 5a, pp 36-7 |
| 50 mm A/T Gun 38 (5 cm Pak 38) | Used ammo: HE (5 cm Sprgr Patr 38) and stick grenade (Stielgr 42) | 5a, p 18 |
| Note: According to Ref 5b table 1, this gun existed in 50 and 60 caliber lengths and was designated as 5 cm Pak(L/50) | | |
| 50 mm A/T Casemate and Turret Gun, long mount [5 cm Pak KuT (LgL)] | Used ammo: HE (5 cm Sprgr Patr 38), AP (Pzgr Patr 39, 40 & 40/1) and stick grenade (Stielgr 42) | 5a, p 19 |
| 50 mm A/T Casemate and Turret Gun, short mount [5 cm Pak KuT (KzL)] | Used ammo: Short HE (Kz 5 cm Sprgr Patr 38) and Short AP [Kz 5 cm Pzgr Patr f Pak KuT (KzL)] | 5a, p 19 |
| 50 mm Light Mortars: 5 cm GrW 36 and GrW M/19 | Used HE mortar ammo such as: 5 cm Wgr Patr 36, 39 & 41 | 5a, pp 26-7 and 9, pp 530-1 |
| 50 mm AA Gun 41 (5 cm Flak 41) | Used ammo: HEI-T (5 cm Br Sprgr Patr 41 L'spur), HE-T (Sprgr Patr L'spur), AP (Pzgr Patr 39 & 42) and AP-T (Pzgr Patr 42 V) | 5a, p 46 and 9, p 395 |
| 50 mm Automatic Aircraft Cannon (5 cm BK) developed during WW II by the Rheinmetall-Borsig A - G | No description is given here because Ref 8, v 3 is confidential | 8, v 3, p 638 |
| 50 mm Automatic AC Cannon, MK-214 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 50 mm AC Cannon | Same as above | 12 |
| 50 mm A/T Automatic Cannon, Skoda | Same as above | 12 |
| 50 mm Automatic Mortar (Westwall) | Same as above | 12 |
| 50 mm Belgian Light Mortar: 5 cm GrW 201 (b) | Used various mortar ammo: Belgian, French, German and Russian | 5a, p 26 |
| 50 mm French Light Mortar: 5 cm GrW 203 (f) | Same as above | 5a, p 26 |
| 50 mm Russian Light Mortar: 5 cm GrW 205 (r) | Same as above | 5a, p 26 |
| 50.8 mm (2") British Mortar: 5 cm GrW 202 (e) | Used British HE and smoke bombs | 5a, p 27 |
| 55 mm (2.165") Aircraft Automatic Cannon, MK-112, developed near the end of WW II by the Rhein- metall-Borsig A - G | Not described here because Ref 8, v 3 is considered confidential | 8, v 3, pp 614 & 627 |
| 55 mm Automatic Cannon, MK-114, not fully developed during WW II | Same as above | 8, v 3, p 636 |
| 55 mm Automatic Recoilless Cannon, MK-115, developed by Rheinmetall-Borsig A - G but not put into production | Same as above | 8, v 3, p 637 |

Ger 244
WEAPONS
(CALIBER 75 mm)

75 mm ASSAULT GUN [7.5 cm STUK (L/48)] ON Pz Lw IV CHASSIS




75/55 mm GERLICH TAPERED BORE ANTITANK GUN (7.5/5.5 cm PAK-41)




75 mm RECOILLESS GUN (7.5 cm LG-40) ON TRIPOD




75 mm ANTITANK GUN (7.5 cm PAK 40/2) ON TANK DESTROYER Pz Jäg II CHASSIS



75 mm INFANTRY HOWITZER (7.5 cm IH-42) SMOOTH BORE




75 mm ANTITANK GUN PAK-42 (7.5 cm PAK 40 ON LFH 18/40 CARRIAGE)



75 mm RECOILLESS GUN (7.5 cm RFK-43)



75 mm ASSAULT GUN (7.5 cm STUK-42) ON Pz Jäg IV CHASSIS



75 mm ANTITANK GUN (7.5 cm PAK 50) ON PAK 38 CARRIAGE (EXPERIMENTAL)

(Weapons) (cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|---|--|
| 60 mm (2.362") French Mortar: 6 cm GrW 225 (f) | Used French HE cast steel bomb: 6 cm Stg (Stahlguss) Wgr 225 (f) | 5a, p 27 |
| 60 mm Mortar Barrage | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 65 mm (2.559") French Mountain Pack Howitzer: 6.5 cm GebK 221 (f) | Used French HE shell: 6.5 cm Gr Patr (f) | 5a, p 52 |
| 65 mm French Quick-Firing Gun: 6.5 cm SGesch (Schnellgeschütz) 02 (f) | Used French ammo: HE [6.5 cm Gr Patr AZ & Gr Patr DoppZ (f)] and AP [Pzgr Patr (f)] | 5a, p 60 |
| 65 mm Italian Mountain (Pack) Howitzer: 6.5 cm GebH 216 (i) | Used Italian ammo: HE [6.5 cm Sprgr Patr (i)] and AP [Pzgr Patr (i)] | 5a, p 52 |
| 65 mm Yugoslav Mountain (Pack) Howitzer: 6.5 cm GebK 222(j) | Used Yugoslav ammo: HE [6.5 cm Sprgr Patr 222 (j)] and Shrapnel [Schr Patr 223 (j)] | 5a, p 52 |
| 73 mm (2.874") Rocket Launcher, Föhn Gerät, capable of firing 35 rockets simultaneously | A 35-frame launcher with fast elevating and transverse gears. It fired 7.3 cm Raketen Sprenggranate or 7.3 cm Propagandasprenggranate 41 | 9, pp 234-6 |
| 75 mm Mountain Guns: 7.5 cm GebK 15 & GebK 14/15 | Used ammo: HE (7.5 cm GebGr 15, GebGr 15 Al, GebGr 15 Rot, GebGr 39), HoC (Gr 39 Hl/A), as well as some Austrian and Czech ammo | 5a, p 55 and 9, pp 399 & 403 |
| 75 mm Skoda Mountain Gun M 15: 7.5 cm GebK M 15 | Same ammo as above | 5a, p 55 |
| 75 mm Light Field Gun 16: 7.5 cm IFK 16 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 75 mm Field Gun 16/1: 7.5 cm FK 16/1 | Used HE proj (KGrRotKPS) and AP proj (KGrRotPz) | 9, pp 421 & 423 |
| 7.5 mm Field Gun 16, new pattern: 7.5 cm FK 16nA | Used same ammo as above, plus HoC proj (7.5 cm Gr 38 Hl/A) | 5a, pp 60-1 and 9, pp 409, 421 & 423 |
| 75 mm Light Field Gun 18: 7.5 cm IFK 18 | Used ammo: HE (7.5 cm Sprgr Patr 34 & KGrRotKPS), AP (KGrRotPz), APC (PzGrPatr 38), HoC (Gr 38 Hl/A & Gr Patr 38 Hl/A) and Smoke (Nbgr Patr) | 5a, pp 61-2 and 9, pp 400-3, 407, 409, 421 & 423 |
| 75 mm AA Cannon 18: 7.5 cm Flak 18 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 75 mm Light Infantry Howitzer 18: 7.5 cm IJH 18 | Used ammo: HE (7.5 cm Jgr 38 FES) and HoC (Jgr 38 Hl/A and Hl/B) | 9, pp 413, 418 & 425 and Ref 12 |
| 75 mm Light Mountain Infantry Howitzer 18: 7.5 cm IGebJH 18 | Used same projectiles as previous weapon | 9, pp 413, 418 & 425 |
| 75 mm Light Infantry Guns: 7.5 cm IJG 18, 37 & 42 | Used ammo: HE (7.5 cm Jgr 18, Jgr 18 Al), HoC (Jgr 38 Hl, Jgr 38 Hl/A, Jgr Patr Hl/A, Jgr 38 Hl/B) and Indicating shell (Jgr Deut) | 5a, p 30; 9, p 404 and Ref 12 |
| 75 mm Light Infantry Mountain Gun: 7.5 cm IGebJG 18 | Same as above | 5a, p 30 and 9, pp 404-5 |
| 75 mm Heavy Infantry Guns: 7.5 cm sJG 33, sJG 33/1 & sJG 42 | Used ammo: HE (15 cm Jgr 33, Jgr 38 & Jgr 38 Al), HoC (Jgr 39 Hl/A & Jgr Hl/B) Stick grenade (Stielgr 42), Smoke (Jgr 38 Nb) and Inc (Jgr 38 Br) | 5a, p 31 |
| 75 mm Naval Gun: 7.5 cm SK C/34 (L/33) | Used HE projectiles | 5b, table 1 |
| 75 mm Mountain Howitzer Dofors: 7.5 cm GebH 34 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 75 mm Mountain Gun 36: 7.5 cm GebG 36 | Used ammo: HE (7.5 cm Gr 34 Sprgr Patr 34, KGrRotAl & KGr 34 Al), HoC (Gr 36 Hl/A, Hl/B & Hl/C) and Smoke Indicator (KGrRot Deut blau & KGrRotBunt) | 5a, p 52 and 9, pp 398, 401, 405 & 416 |
| 75 mm Gun 37: 7.5 cm K 37 L/24 | Used ammo: HE (7.5 cm Sprgr Patr), HoC (Gr Patr 38 Hl/A, Hl/B & Hl/C), AP (Pzgr Patr), Case Shot (Kt Patr), Smoke (Nbgr Patr) and Indicating shell (KGrPatr Rot Deut) | 5a, p 38 |
| 75 mm Tank Gun: 7.5 cm KwK | Same as above | 5a, p 38 |
| 75 mm Assault Gun: 7.5 cm StuG | Same as above | 5a, p 38 |
| 75 mm Field Gun 38: 7.5 cm FK 38 | Used ammo: HE (7.5 cm KGrPatr, Sprgr L/4.8), HoC (Gr Patr 38 Hl/B & Hl/C) and Smoke Indicator (KGrPatr Rot Deut) | 5a, p 62 and 9, p 415 |

Ger 246

(Weapons) (Cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|--|---|---|
| 75 mm Tank Gun 38: 7.5 cm KwK 38 | Used HoC ammo: 7.5 cm Gr Patr 38 III/A | 9, p 409 |
| 75 mm A/T Gun 39: 7.5 cm Pak 39 L/48 | Used ammo: HE (7.5 cm Sprgr Patr 34), HoC (Gr Patr 38 III/A, III/B & III/C), AP (Pzgr Patr 39, Pzgr Patr 40 & Pzgr Patr W) and Smoke (Nbgr Patr) | 5a, p 39 |
| 75 mm Tank Guns: 7.5 cm KwK 40 L/43 and KwK 40 L/48 | Same as above | 5a, p 39 |
| 75 mm Assault Guns: 7.5 cm StuK L/43 & StuK L/46 | Same as above | 5a, p 39 |
| 75 mm A/T Guns: 7.5 cm Pak 97/38 and 97/40 | Used ammo: HE (7.5 cm Sprgr Patr), HoC (Gr Patr 15/38 III, Gr Patr 38 III, Gr Patr 38/97 III/A & III/B), AP (Pzgr Patr 39), and Star (Lt Gr Patr) and some foreign ammo | 5a, p 21 and 9, pp 415, 419-20 & 425 |
| 75/50 mm Skoda Dual Purpose Gun | Used HE ammo: 7.5 cm Sprgr Patr 75/50 | 9, p 406 |
| 75 mm A, T Gun 40: 7.5 cm Pak 40 | Used ammo: HE (7.5 cm Sprgr Patr 34 KwK, etc), HoC (Gr Patr III/A, III/B and III/C, etc), AP (Pzgr Patr 40, Weicheisen or Pzgr Patr 40, harter Kern) and Smoke (Nbgr Patr) | 5a, p 21; 9, pp 398, 401-2, 408-9, 411 & 417 & Ref 12 |
| 75 mm Self-Propelled A/T Guns: 7.5 cm Pak 40/1 (Sf), Pak 40/2 (Sf) and Pak 40/3 (Sf) | Used HoC ammo, such as 7.5 cm Gr Patr III/B | 5a, p 21; 9, p 411 and Ref 12 |
| 75 mm Tank Gun 40: 7.5 cm KwK 40 | Used ammo: HE (7.5 cm Sprgr 34 & Sprgr Patr 34) APC (Pzgr Patr), HoC (Gr Patr III/A, Gr Patr III/B, Gr Patr 38 III/B & Gr 38 III/B), Smoke (Nbgr Patr) | 9, pp 398, 400-3, 409, 411 & 417 |
| 75 mm Recoilless Gun for Airborne Troops Type 40 (7.5 cm Leichtes Geschütz 40) | Used same ammo as above, less Sprgr 34 and Gr 38 III/B | 9, pp 398, 400-3, 409 & 411 & Ref 12 |
| 75 mm Assault Gun 40 (7.5 cm StuG 40) | Used ammo: HE (7.5 cm Sprgr Patr 34), APC (Pzgr 39 FES), HoC (Gr Patr 38 III/A & III/B, Gr 38 III/B & Gr Patr III & III/B) and Smoke (Nbgr Patr) | 9, pp 398, 400-2 & 409-11 |
| 75 mm Assault Guns: 7.5 cm StuK 40 L/43 and StuK 40 L/48 | Used ammo: HE (7.5 cm Sprgr 34) and HoC (Gr 38 III/B) | 9, pp 411 & 417 and Ref 12 |
| 75/55 mm A/T Gun 41: 7.5/5.5 cm Pak 41 [Gerlich Type Gun, called also Tapered Bore Gun, Reducing Bore Gun or Squeeze Bore Gun] | Can be seen at the Museum of Aberdeen Proving Ground, Md. Used AP proj with iron core [7.5 cm Pzgr 40 (W)] and AP proj with tungsten carbide core, arrowhead design [Pzgr Patr 41 (HK)] | 5a, p 20; 9, pp 378, & 408 and Ref 12 |
| 75 mm Assault Gun 42: 7.5 cm StuK 42 | Used ammo: HE (7.5 cm Sprgr Patr 42), HoC (Gr Patr 38 III) and AP (Pzgr Patr 39/42, 40 & 40/42) | 5a, p 39 |
| 75 mm Tank Gun 42: 7.5 cm KwK 42 L/70 | Same as above | 5a, p 39 |
| 75 mm Tank Gun 42: 7.5 cm KwK 42 | Used ammo: HE (7.5 cm Sprgr 42) and AP (Pzgr 39/42) | 9, pp 411 & 423 and Ref 12 |
| 75 mm Assault Gun 42: 7.5 cm StuK 42 L/70 | Used same ammo as above | 9, pp 411 & 423 and Ref 12 |
| 75 mm Infantry Howitzer 42, Smooth Bore: 7.5 cm IH 42 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 75 mm Recoilless Gun 43: 7.5 cm RfK (Rückstossfreie Kanone) 43 | Can be seen at the Museum of Aberdeen Proving Ground, Md. Used HoC proj: 7.5 cm Gr Patr 43 III | 5a, p 21 and Ref 12 |
| 75 mm A/T Gun 50, Experimental: 7.5 cm Pak 50 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 75 mm Belgian Guns: 7.5 cm FK 234 (b) 7.5 cm FK 235 (b) 7.5 cm FK 236 (b) | Used ammo: HE: Sprgr 230/7, (f) and HoC: Gr 15/38 III/B (f) HE: Sprgr 240/2 (b) HE: Sprgr 1900/15 (f) | 5a, p 21 and 9, pp 415, 420-1 & 425 |
| 75 mm Czech AA Gun: 7.5 cm Flak (Skoda) | Used Czech HE ammo, 7.5 cm Sprgr Patr (t) | 5a, p 46 |
| 75 mm Czech Field Gun 17: 7.5 cm FK 17 (t) | Used Czech HE ammo: 7.5 cm Gr M/17 & M/19 (t) | 5a, p 66 |
| 75 mm Dutch Guns: 7.5 cm FK 243 (h) 7.5 cm FK 243 (h) L 30 | Used ammo: HoC: Gr 38 III/C (h) HE: KGr RotKPS and K Gr Rot Pa | 9, pp 413, 421 & 423 |


(Weapons) (cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|---|---|
| 75 mm French Guns: 7.5 cm FK 231 (f), Mle 97 | Used ammo HE: Sprgr 1900/15 (f) & Sprgr 231/1 (f) and HoC: Gr 15/38 Hl/B (f) | 5a, pp 21 & 41 9, pp 413-25 |
| 7.5 cm FK 232 (f), Mle 97/33 | HE: Sprgr 231/1 (f) & Sprgr 264 (j) and HoC: Gr 15/38 Hl/B (f) | |
| 7.5 cm GebK 238 (f), Mle 1928 | HE: Sprgr 231 (f) | |
| 7.5 cm KwK 251 (f), Mle 1935 | HE: Sprgr 231 (f) | |
| 7.5 cm Flak M 17/34 & Flak M 36 | HE: Sprgr 28 (f) | |
| 75 mm Field Guns: 7.5 cm FK 237 (i) & 244 (i) | Used Italian HE and Shrapnel ammo | 5a, p 64 |
| 75 mm Italian Mountain Gun: 7.5 cm GebK 259 (i) | Used same ammo as 7.5 cm GebK 15 | 5a, p 55 |
| (See also under Weapons in the Italian section) | | |
| 75 mm Norwegian Guns: 7.5 cm FK Schneider (n) | Used Norwegian ammo HE: GrKartã M/31 (n) and Shrapnel: GrSchr(u) | 5a, pp 55 & 65-66 |
| 7.5 cm FK 01 (n) | HE: GrKartã M/01, M/21 & M/36(n) and HE-Inc: BrGrKartã M/13 (n) | |
| 7.5 cm BK L/17 (n) | HE: GrKartã M/21 & M/36 (n); HE-Inc: BrGrKartã M/14 (n) | |
| 7.5 cm FK 246 & 247 (n) | No information available | |
| 75 mm Polish Gun: 7.5 cm FK 97 (j) | Used ammo HE: Sprgr 1900/15 (f) & HoC: Jgr 38 Hl/B | 5a, p 21 and 9, pp 419-20 & 423 |
| 7.5 cm FK 02/26 (p) | | |
| 75 mm Yugoslav Guns: 7.5 cm FK 249 (j) Mod 12 (Schneider) | Used ammo HE: Sprgr 264 (j) & Sprgr 1900/15 (f) and HoC: Gr 15/38 Hl/B (f) & Gr 38-97 Hl/C (f) | 5a, pp 21, 54-5 & 9, pp 415, 419-20 and 423 |
| 7.5 cm GebK 258 (j) | Same ammo as 7.5 cm GebK 15 | |
| 7.5 cm GebK 259 (j) | HE: Sprgr 249 (j) and Shrapnel (Schr 250 & 251) | |
| 7.5 cm GebK 285 (j) | HE: Sprgr 260/1 & 260/2 (j) | |
| 75 mm Yugoslav Mortar: 7.5 cm GrW 229 (j) | Used HE bomb: Wgr 229 (j) | 5a, p 27 |
| 76 mm (2.992") British AA Gun: 7.6 cm Flak (e) | Used British HE fixed round: 7.6 cm Sprgr Patr (e) | 5a, p 48 |
| 76.2 mm (3.004") Russian Guns: 7.62 cm FK 39 (r) | Used various Russian design projectiles either captured or manufactured in Germany | 5a, pp 23-4, & 40-1; 9, pp 426-32 |
| 7.62 cm KK 290/1 and 310 (r) | | |
| 7.62 cm Pak 36 (r) | | |
| 7.62 cm RFK 299 (r) | | |
| and many other models were captured and used by the Germans during WW II (See Weapons in the Russian section) | | |
| 76.5 mm (3.004") Austrian Field Guns: 7.65 cm FK 5/8/6, FK 17/8, and FK 18/6, manufactured by Skoda Works, Pilsen | Used Austrian and Czech design ammo | 5a, p 68 |
| 76.5 mm French Field Guns: 7.65 cm FK 16 (f) & FK 17 | Used French design ammo | 5a, pp 68-9 |
| 76.5 mm Yugoslav Guns: 7.65 cm FK 300 (j), 303 (j), & 304 (j), manufactured by Skoda Works | Used Yugoslav, Czech and Austrian ammo | 5, pp 68-9 |
| 77/45 mm (3.03/1.77") Recoilless Automatic Cannon, SG-113 A, developed during WW II by the H.Göring Werke but not put into production | Not described here because Ref 8, v 3 is confidential | 8, v 3, p 630 |
| 80 mm (3.15") Medium Mortar, designated 8 cm SGrW 34 | Used HE mortar ammo: 8 cm Wgr 34, Wgr 38, Wgr 39 & Wgr 38 Deut) | 9, pp 529, 531 & 533 |
| 80 mm Medium Mortar, designated as 7.5 cm MGrW 34 | Used smoke mortar ammo (7.5 cm Wgr 34 Nb) | 9, p 532 |
| 80 mm Trench Mortar, designated as 7.5 cm KzGrW 42 | Used HE Mortar ammo (7.5 cm Wgr 34) and Smoke (Wgr 34Nb) | 9, pp 532-3 and Ref 12 |
| 80 mm Automatic Mortar, "Pilsen" | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 80 mm A/T Gun (High-Low Pressure Mortar Bomb Projector) | Same as above | 12 |
| 80 mm Smooth-Bore Weapon, called Panzerwaffenkanone, developed by the Rheinmetall-Borsig Co and issued to the troops at the end of 1944 | Mounted on a carriage weighing 1370 lb, it fired a finned projectile at a muzzle velocity of 1700 ft/sec to an effective range of 700 meters. The shell weighed 6 lb, was 18" long and had a penetration of 140 mm at 60° angle of impact | 6, p 188 |

WEAPONS

(CALBERS 80 mm TO 88 mm)


80 mm
AUTOMATIC
TRENCH
MORTAR
"PII SEN"




80 mm ANTITANK GUN
(HIGH-LOW PRESSURE MORTAR
BOMB PROJECTOR)



80 mm RECOILLESS
GUN SMOOTH BORE
(EXPERIMENTAL) (REAR
WITH ARFFCH
OPEN)



80 mm SKODA FIELD
GUN (8 cm LK 3C)




88 mm ANTI-AIRCRAFT
CANNON (8.8 cm FLAK 36)



81 mm MORTAR
(EXPERIMENTAL)




80 mm TRENCH MORTAR
MOD 42 SHORT TUBE



88 mm ANTI-AIRCRAFT OR ANTI-TANK
CANNON (8.8 cm FLAK 41)



88 mm ANTITANK GUN (8.8 cm PAK 43)
[SIDE VIEW IN FIRING POSITION AT
MAXIMUM (40°) ELEVATION AND 45°
TRAVERSE]




88 mm ANTITANK GUN
(8.8 cm PAK 43)



(Weapons) (cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|--|---|
| 80 mm Multiple-Rocket Launcher, designated as 8 cm Raketenvielfachwerfer | It fired HE aircraft rockets (8 cm Raketen Sprenggranaten), similar in construction to a standard Russian aircraft rocket | 9, p 237 |
| 80 mm French Mortar, Short Tube, Mod 47 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 80 mm Recoilless Gun, Smooth Bore, Experimental | Same as above | 12 |
| 80 mm Czech Field Gun: 8 cm FK 18/17 (t) | Used Czech HE shell, 8 cm Gr M 30/17 (t) | 5a, p 69 |
| 80 mm Czech Field Gun: 8 cm FK 30 (t) | Used Czech HE and AP projectiles: Gr 30, Cr 35 and Pzgr (t) | 5, p 69 |
| 80 mm Polish Mortar: 8 cm GrW 28 (p) | Used German and foreign projectiles | 5a, pp 28-9 |
| 81 mm (3.19") Mortar, Experimental | Same as above | 12 |
| 81-82 mm Foreign Mortars used by the Germans included: 8.1 cm GrW 274 (dan), 8.1 cm GrW 279 (h), 8.1 cm GrW 286 (h), 8.14 cm GrW 278 (f), 8.14 cm GrW 286 (f), 8.2 cm GrW 274 (r) & 274/2 (r) | Used German and foreign projectiles | 5a, pp 28-9 |
| 83.5" (3.28") Czech Design AA Gun [8.35 cm Flak M/22 (t)] | Used Czech design and manuf projectiles: 8.35 cm Gr 23/30 (t) and 8.35 cm Pzgr (t) | 5a, p 48 and 9, p 436 |
| 83.8 mm (3.305") British Field Guns: 8.38 cm FK 271, 272 & 273 (e) | Used British HE and smoke shells: SprgrPatr 106 and NbrgPatr 106 (e) | 5a, p 70 |
| 83.8 mm Russian Field Gun: 8.38 cm FK 305 (r) | No information given | 5a, p 70 |
| 86 mm (3.386") Single Barrel Rocket Launcher, designated as 8.6 cm R Ag M 42 and weighing 40 kg | It fired various rockets used by the Navy, such as HE, flare, etc | 9, p 241 |
| 86 mm Rocket Launcher (No German designation is given) | Used HE rockets, designated 8.6 cm RSprgr L/4.5 and RSprgr L/5.5 | 9, pp 256-7 |
| 87.6 mm (3.45") British Field Guns 260, 281 & 282 (e) (25 pounders) | Used British ammo: HE [Gr 292 & 295 (e)] and Smoke [Rauchgr (e)] | 5a, p 70 |
| 88 mm (3.465") AA Gun 18: 8.8 cm Flak 18 | Used ammo: HE (8.8 cm Sprgr L/4.5, Sprgr L/4.5 ZtZ & SprgrPatr L/4.5 Kz), AP (Pzgr & Pzgr 39), APC (PzgrPatr BdZ) and Inc Shrapnel (Gr BrSchrFlak) | 9, pp 438, 441, 444, 446 & 448 |
| 88 mm Tank Gun 36: 8.8 cm KwK 36 | Used HE ammo: 8.8 cm Sprgr L/4.5 | 9, p 444 |
| 88 mm Naval Guns: 8.8 cm SK C/25, C/30, C/31, C/32 & C/35 | Used HE and Star projectiles | 5b, table 2 |
| 88 mm Torpedoboot Gun: 8.8 cm T'bots K L/45 | Used HE and Star projectiles | 5b, table 2 |
| 88 mm Tank Gun 36 (56 calibers long): 8.8 cm KwK 36 L/56 | Used ammo: HE (8.8 cm SprgrPatr L/4.5), HoC (GrPatr 39 III), AP (PzgrPatr 36, 39, 39/1 & 40), Shrapnel-Incendiary (BrSchrGrPatr), and Star Shell (LtGesch L/4.5) | 5a, p 41 and 9, pp 444-5 & 448 |
| 88 mm AA Gun 36: 8.8 cm Flak 36 | Used ammo: HE (8.8 cm Sprgr L/4.5, SprgrPatr L/4.5 Kz & Sprgr L/4.5 ZtZ), AP (Pzgr 39) and Inc-Shrapnel (Gr BrSchrFlak) | 9, pp 438, 444, 446 & 448 and Ref 12 |
| 88 mm AA Gun 37: 8.8 cm Flak 37 | Same as above | 9, pp 438, 444 446 & 448 |
| 88 mm AA Gun 41: 8.8 cm Flak 41 | Used ammo: HE (8.8 cm SprgrPatr L/4.7 FES & SprgrFlak 41), AP with tungsten carbide core (Pzgr 40), AP (PzgrPatr 41) and APC (PzgrPatr 39) | 9, pp 437-9, 441 & 444 r d Ref 12 |
| 88 mm AA Gun 43: 8.8 cm Flak 43 | Used HE ammo: 8.8 cm SprgrPatr (L/4.7) FES | 9, p 441 |
| 88 mm Short Mortar | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 88 mm Tank Gun 43 [8.8 cm KwK 43 (L/71)] | Used ammo: AP (8.8 cm PzgrPatr 39, 39/1, 39/43, 40 & 40/43), HoC (GrPatr 39 III & 39-43 III) and HE (SprgrPatr 43, etc) | 5a, pp 24-5; 9, pp 442 & 447 and Ref 12 |

Ger 250
WEAPONS
(CALIBERS 88mm TO 105 mm)



88 mm ANTITANK GUN
(8.8 cm PAK 43) ON PzKw IV
CHASSIS ("RHINOCERUS")

88 mm ANTITANK GUN
(8.8 cm PAK 43) ON PzJgd
TIGER P CHASSIS ("ELEPHANT")

100 mm LIGHT FIELD
HOWITZER SKODA
[10 cm LFH 30 (t)]

105 mm MOUNTAIN HOWITZER
(10.5 cm GebH-10) (FIRING
POSITION AT MAXIMUM
ELEVATION)

88 mm TANK GUN (8.8 cm KwK-43)
ON PzKw V CHASSIS (TANK DESTROYER
"JAGDPANTHER")

105 mm LIGHT FIELD
HOWITZER (10.5 cm LFH-18)

105 mm LIGHT FIELD HOWITZER
(10.5 cm LFH-18 40) (CARRIAGE
PAK 40)

105 mm RECOILLESS GUN
(10.5 cm LG-40 (PREVIOUSLY
KNOWN AS LG 2Kp))

105 mm SMOOTH
BORE RECOILLESS
GUN

105 mm COMPRESSED AIR
MORTAR

(Weapons) (Cont'd)

Caliber and Designation

88 mm A/T Guns 43, 43/1,
43/2, 43/3 (8.8 cm Pak 43,
43/1, 43/2, 43/3)

88 mm Self-Propelled Assault
Gun 43 (8.8 cm Stuk 43 (L/71)]

88 mm Self-Propelled A/T Guns
[8.8 cm Pak 43 & Pak 43/41 (L/71)]

88 mm AA Gun (Converted
Russian 85 mm Gun) (8.5/8.8 cm
Flak 39 (r)]

88 mm Rocket Launcher, called
Raketenpanzerbüchse 43 (8.8 cm
RPzB 43), known also as
Raketenwerfer 43 or **Ofenrohr**
(Stovepipe)

88 mm Rocket Launcher, called
8.8 cm Raketenpanzerbüchse 54
(8.8 cm RPzB 54) or **Panzerschreck**.
It was an enlarged version of
original American Bazooka. Its
operation required two men. This laun-
cher was also called **Ofenrohr**

Note: This weapon was provided with a simple electric generator which produced the necessary spark to ignite the propelling charge in the rocket. The original American Bazooka used flashlight batteries for producing a spark. When the projectile was launched the back blast of flame reached a length of about 16 ft (See also description of Faustpatrone, called later Panzerfaust)

88 mm Rocket Launcher **Püppchen**;
designated as **8.8 cm Raketenwerfer 43**
(8.8 cm RW 43), known also as
"Wheeled Bazooka". The projectile
was the same as above except that it
was modified for percussion firing

90 mm (3.54") French AA Gun:
9 cm Flak (f)

90 mm Yugoslav Mortar: 9 cm
GrW 309 (j)

94 mm (3.7") British AA Gun:
9.4 cm Flak (e)

94 mm British Pack Howitzer:
9.4 cm GebH 301 (e) (Mountain
Howitzer)

100 mm (3.937") Guns 17 and 17/04,
new design: 10 cm K 17 & 17/04nA

100 mm Heavy Gun 18: 10 cm K 18

100 mm Light Field Howitzer 18:
10 cm IFH 18

100 mm Casemate and Turret
Guns (Medium): 10 cm KK and
KT

100 mm Long Turret Gun:
10 cm KT

100 mm Chemical Projector
(Smoke Shell Mortar): 10 cm NBW 37

100 mm Rocket Launcher: 10 cm
"Panzerschreck"

100 mm Guns 18/40 and 42:
10 cm K 18/40 & K 42

100 mm Austrian Mountain Howitzer
(Pack Howitzer): 10 cm GebHau
M/16 (d)

100 mm Light Czech Field Howitzer:
10 cm IFH 14/17 (t) and IFH 30 (t)

100 mm Italian Light Field Howitzer:
10 cm IFH 315 (l)

Remarks, Uses and Some Characteristics

Same as in 88 mm Tank Gun 43

Same as above

Same as above

Used Russian and German ammo: HE
(8.8 cm Sprgr L/4.5) and AP (8.8 cm
Pzgr and Pzgr 39)

This was an earlier version of the 8.8 cm
RPzB described below. It had no shield.
It used the same ammunition as below

Smooth-bore tube 5'4 1/2" long and weighing
20 1/2 lb, exclusive of shield. It fired a shaped
charge rocket projectile (8.8 cm RPzBGr 4322)
25 1/2" long and weighing about 7 lb, which
penetrated steel armor about 4 1/4". Its range
was 55 to 165 yd and muzzle velocity up to
3280 ft/sec. The launcher was provided with a pro-
jectile guide which wore out after firing 300 rounds

It was essentially the **Panzerschreck**
mounted on a light carriage. The total weight
of launcher was 340 lb and the effective
range 200 yd. This model was discontinued
before the end of WW II

No other information given

Used Yugoslav HE mortar bomb: 9 cm
Wgr 309 (j)

Used British HE ammo: 9.4 cm Sprgr Patr (e)

Used British HE ammo: 9.4 cm Sprgr mAZ (e)

Used ammo: HE (10 cm FHGr & Gr 15 Hb)
and AP (Pzgr)

Used ammo: HE (10 cm Gr 19), AP (Pzgr) and
Smoke (Gr 38Nb)

Used HoC ammo: 10 cm Gr Rot Hl/B and Hl/C

Used ammo: HE (10 cm GrPatr 34),
AP (PzgrPatr) and Case Shot (KtPatr)

Used ammo: HE (10 cm Gr 19), AP
(Pzgr), Smoke (Gr 38Nb) and Case Shot (Kt)
Used HE mortar ammo: 10 cm Wgr 37

An enlarged version of 88 mm Panzerschreck

No description given

Used Austrian ammo: HE (10 cm GebGr M/32
and Smoke (GebGr M/32Nb)

Used Czech HE ammo: 10 cm Gr 15, 21 & 30

Used Italian HE ammo: 10 cm Sprgr 315 (l)

References

5a, pp 24-5 and
9, pp 442 & 447

5a, pp 24-5 and
9, pp 442 & 447

5a, pp 24-5;
9, pp 442 & 447
and Ref 12

9, pp 444, 446
& 448

5b, pp 9-13;
11, p 521

5a, p 10, 6, p 188,
7, p 23, 9, pp 243-6,
11, pp 521-2 and
Ref 13

5, p 188, 6, p 199,
9, p 245 and
11, p 522

5a, p 49

5a, p 30

5a, p 50

5a, p 56

5a, p 79

5a, p 80

9, pp 450-1
and Ref 12

5a, p 79

5a, p 81

9, p 533

6, p 188

5a, p 80

5a, p 57


5a, p 78 and
9, pp 451-5

5a, p 77


(Weapons) (cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|--|---|
| 100 mm Polish Light Field Howitzer: 10 cm IFH 14/19 (p) | Used Polish HE steel shell: 10 cm Sgr (p) | 5a, p 78 and 9, pp 451-5 |
| 100 mm Yugoslav Light Field Howitzer: 10 cm IFH 315 (j), 316 (j), 317 (j), 317/1 (j) & 317/2 (j) | Used Yugoslav ammo: HE (10 cm Sprgr 310, 311 & 315) and Shrapnel (Schr 316 & 317) | 5a, pp 76-8 and 9, pp 451-5 |
| 105 mm (4.134") Light Field Howitzer 16:10.5 cm IFH 16 | Used ammo: HE (10.5 cm FHGr, FHGrStg, FHGr 38, FHGr 38 Seg FES), HE-1 (FHGrSprBr), AP (Pzgr Rot L'apur), HoC (Gr 39 Rot HI, Gr 39 Rot HI/A, Gr 39 Rot HI/B & Gr 39 Rot HI/C) and Smoke (FHGrNb, FHGr 38 Nb and FHGr 40 Deut) | 5a, p 71 and 9, pp 457, 461 & 470-6 |
| 105 mm Guns 17 and 17/04 new pattern: 10.5 cm K 17 & K 17/04nA | Used HE ammo: 10.5 cm FHGr Rot | 9, p 457 |
| 105 mm Medium Heavy Gun 18: 10.5 cm sK 18 | Used ammo: HE (10.5 cm Gr 19 & Gr 19 Kz 13) and AP (Pzgr Rot) | 9, pp 456, 468 & 481 |
| 105 mm Light Field Howitzers: 10.5 cm IFH 18, 1FH 18mM, 1FH 18/1, 1FH 18/2, 1FH 18/39 & 1FH 18/40 | Used ammo: HE (10.5 cm FHGr, FHGrStg, FHGr 35, FHGr 38, FHGr 38 Seg FES, FHGr 38Kh, FHGr 39, Sprgr 43 PG Sprgr 42 Ta, MinGr and FHGr F), HE1 (FHGrSprBr), HoC (Gr 39 Rot III, Gr 39 Rot III/A, Gr 39 Rot HI/B & Gr 39 Rot HI/C), AP (Pzgr mB4Z, Pzgr Rot & Pzgr 39TS), Smoke (FHGrNb, FHGrNb 38 FES, FHGrNb 39, FHGrNb 40 FES & FHGr 41Nb), Smoke Indicator (FHGr 40 Deut FES), incendiary (FHGrBr), Star (LuGesch) and Propaganda (Weiss Rot Geschosse) | 5a, pp 71-2, 9, pp 457, 460-1, 464-5 & 470-6, and Ref 12 |
| 105 mm Naval Guns: 105 cm SK C/28, C/32 & C/33 | Used HE and Star shells | 5b, table 3 |
| 105 mm Medium Heavy Turret Gun: 10.5 cm sKT | Used ammo: HE (10.5 cm Gr 19 Kz 13) and AP (Pzgr Rot) | 9, pp 468 & 481 |
| 105 mm AA Guns 38 and 39: 10.5 cm Flak 38 & Flak 39 | Used ammo: HE (10.5 cm Sprgr L/4.4 & Sprgr L/4.4 & Sprgr L/4.4 Kz) and AF C (Pzgr Rot) | 9, pp 467-8 & 480 & Ref 12 |
| 105 mm Mountain Howitzer 40: 10.5 cm GebH 40 | Used ammo: HE (10.5 cm FHGr Al, FHGr 38 Al) HoC (Gr 39 Rot HI/A, HI/B & HI/C) and Star Shell (LuGr) | 5a, p 56 and Ref 12 |
| 105 mm Long Turret Gun: 10.5 cm lgKT | Used HE ammo: 10.5 cm Gr 19 Kz 13 | 9, p 481 |
| 105 mm Light Guns (Recoilless Airborne Guns): 10.5 cm LG (Leichtes Geschütz) 40, 40/41 & 40/42) | Used ammo: HE (10.5 cm FHGr 41), HoC (Gr 39 HI, Gr 39 HL/A, Gr 39 HI/B & Gr 39 HI/C), Smoke (FHGr 41Nb) and Inc (FHGr Br) | 5a, p 74, 9, pp 471-6 and Ref 12 |
| 105 mm Assault Howitzers: 10.5 cm StuH 40 & StuH 42 | Used same ammo as 105 mm Light Field Howitzers: 10.5 cm IFH 18 etc | 5a, pp 71-3, 9, pp 471-2 and Ref 12 |
| 105 mm Smoke Shell Mortar 40: 10.5 cm NbW 40 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 105 mm Compressed Air Mortar | Same as above | 12 |
| 105 mm Light Gun 41 (Recoilless Airborne Gun): 10.5 cm LG 41 | No description given | 5a, p 74 |
| 105 mm Light Guns (Recoilless Airborne Guns): 10.5 cm LG 42 & 42/1 | Used ammo: HE (10.5 cm FHGr, FHGr 38 & FHGr 38 Stg), HoC (Gr 39 Rot III, Gr 39 Rot HI/A, Gr 39 Rot HI/B & Gr 39 Rot HI/C), Smoke (FHGr Nb & FHGr 38 Nb) and Inc (FHGr Br & FHGr 41 Br) | 5a, p 75 |
| Note: According to Ref 5b, table 7, the recoilless gun, designated as 10.5 cm LG 42, used same HE projectiles as the 10.5 cm IFH 18 | | |
| 105 mm Light Field Howitzer: 10.5 cm IFH 43 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 105 mm Skoda Howitzer (German designation is not given) | Used HE ammo, Models 23 and 28 | 9, pp 478-80 |
| 105 mm Belgian Gun: 10.5 cm K 333(b) | Used Belgian and French ammo | 5a, p 81 |
| 105 mm Czech Heavy Gun: 10.5 cm K 35 (c), L 138 | Used Czech HE ammo: 10.5 cm AZGr 35 and also some French and Yugoslav ammo | 5a, p 83 and 9, pp 459 & 464-7 |
| 105 mm Dutch Gun: 10.5 cm K 334(h) | No description given | 5a, p 83 |
| 105 mm Dutch Gun: 10.5 cm K 335(h) | Used Dutch HE ammo: 10.5 cm KGr 335 (h) | |


Ger 2-5
WEAPONS
 (CALIBERS 105 mm TO 128 mm)




105 mm ASSAULT HOWITZER ON Pz Kw II CHASSIS ("WASP")




105 mm RECOILLESS GUN (10.5 cm LG 42/1) (BREECH OPEN)




105 mm ASSAULT HOWITZER ON Pz Kw III CHASSIS




105 mm LIGHT FIELD HOWITZER (10.5 cm LFH-43)




105 mm MORTAR (10.5 cm NEBELWERFER 40)




128 mm GUN (12.8 cm FLAK-40) ON RAILROAD MOUNT




128 mm EXPERIMENTAL ANTI-TANK GUN (12.8 cm KANGONE B1/2 ON RUSSIAN 152 mm HOWITZER CARRIAGE)




128 mm MORTAR (12.8 cm M-42)



128 mm GUN (12.8 cm PJK-44) ON "KING TIGER" (Pz Kw VI) CHASSIS ("JAGDTIGER")



128 mm ANTI-AIRCRAFT GUN (12.8 cm FLAK-40)




128 mm KRUPP ANTI-TANK SELF-PROPELLED GUN K-44


(Weapons) (cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|--|---|
| 105 mm French Guns and Howitzers: 10.5 cm FH 322 (f), 323 (f), 324 (f), 325 (f), 331 (f) and 332 (f) | Used various French ammo | 5a, pp 57, 76, 81-4 & 9, pp 459, 461, 463-7 |
| 105 mm Italian Gun: 10.5 cm K 338 (i), 105/28 | Used Italian HE ammo: 10.5 cm Sprgr 338/11 (i) | 5a, p 83 and 9, p 462 |
| 105 mm Norwegian Field Gun: 10.5 cm FK L/28.8 Gock (n) | Used Norwegian ammo: HE (Gr M/15, M/23, M/36 & GrKartå M/04, M/15 & M/23) | 5a, p 78 |
| 105 mm Norwegian Gun: 10.5 cm K 427(n) | No description given | 5a, p 85 |
| 105 mm Polish Gun: 10.5 cm K 29 (p) | Used Polish and French ammo | 5a, p 82 and 9, pp 459 & 464-7 |
| 105 mm Russian Guns: 10.5 cm K 348 (r), K 349 (r) & K 350 (r) | No description given | 5a, p 86 |
| 105 mm Yugoslav Guns and Howitzers: 10.5 cm IFH 316 (j), IFH 317 (j), IFH 317/1 (j), IFH 317/2 (i), K 321 (j), K 356 (j) & K 358 (j) (Schneider) and IGebil 329 (j) | Used Yugoslav, French and Czech ammo | 5a, pp 57, 77-8, 81, 83-5 and 9, pp 459 & 464/7 |
| 107 mm (4.21") Russian Gun: 10.5 cm K 352 (r) | Used Russian ammo | 5a, pp 86 |
| 114.3 mm (4.5") Gun: 11.4 cm K 365 (e) | Used British ammo: HE (11.4 cm Gr 365) and Smoke (Nbgr) | 5a, p 87 |
| 120 mm (4.72") Mortar: 12 cm GrW 42 | Used mortar ammo: HE (12 cm Wgr 42) and Indicating bomb (Wgr Deut) | 5a, p 30 and Ref 12 |
| 120 mm Belgian Gun: 12 cm K 370(b) | Used Belgian HE ammo: 12 cm Gr(b) | 5a, p 88 |
| 120 mm Norwegian Field Howitzers: 12 cm FH 375 (n) & FH 376 (n) | No description given | 5a, p 91 |
| 120 mm Russian Mortar: 12 cm GrW 378 (r) | Used Russian HE mortar bomb: 12 cm Wgr 378/2 (r) | 5a, p 30 |
| 120 mm Yugoslav Field Howitzer: 12 cm IFH 377 (j) | No description given | 5a p 91 |
| 122 mm (5.04") Russian Guns and Howitzers: 12.2 cm FH 385 (r), FH 386 (r), FH 387 (r), IFH 388 (r), K 390, 390/1 & 390/2 (r) and sFH 396 (r) | Used various Russian 122 mm ammo: Sprgr 372, 374- 377, 380, 381, 384(r), Sprgr FEW(r), GR 371 Be(r), Nbgr 385(r), Schi 383(r) and Schr 383/1(r) | 5a, pp 88-90 & 9, pp 481-2 |
| 128 mm (5.90") Self-Propelled Gun 40: 12.8 cm K 40 (Pz Sfl) | Used ammo: HE (12.8 cm Sprgr L/4.5) and AP (Pzgr & Pzgr 43) | 5a, pp 91-2 |
| 128 mm AA Gun 40: 12.8 cm Flak 40 | Used AP ammo: 12 cm Pzgr FES & Pzgr KPS | 9, p 483 & Ref 12 |
| 128 mm AA Gun 40M: 12.8 cm Flak 40M | Used AP projectiles | 5b, table 8 |
| 128 mm Self-Propelled A/T Guns 44: 12.8 cm Pak 44, Krupp and Rheinmetall models | Used AP ammo: 12.8 cm Pzgr & Pzgr 43 | 5a, p 25; 9, p 485 and Ref 12 |
| 128 mm Light Infantry A/T Gun: 12.8 cm PzK 44 (Panzerjägerkanone) also called Tank Destroyer Gun | Used HE and AP projectiles Can be seen at the Museum of Aberdeen Proving Ground, Md | 5b, table 8 and Ref 12 |
| 128 mm A/T Gun: 12.8 cm K 81/2 Experimental | Same as above | 12 |
| 145 mm (5.705") French Gun: 14.5 cm K 405 (f) | Used French ammo: HE (Gr 403) and HE, cast steel (Stggr 401 & 403) | 5a, p 92 |
| 149.1 mm (5.87") Naval Guns: 15 cm SK C/25, C/28, L/40, L/45 & L/55 | Used HE and Star projectiles | 5b, table 8 |
| 149.1 mm Torpedoboat Gun: 15 cm TbtK C/36 | Used HE and Star projectiles | 5b, table 9 |
| 149.1 mm U-Boat Gun: 15 cm UtsK L/45 | Used HE and Star projectiles | 5b, table 8 |
| 150 mm (5.91") Long Howitzers 13: 15 cm sFH 13, sFH 13 (S) and sFH 13/02 | Used ammo: HE (15 cm Gr 18, 19 and Dutch Gr 406), HE cast steel (Stggr 19), HE-A/C (Gr 19 Be), HE Sahot type, HoC (Gr 39 Hl & Hl/B) and Smoke (Gr 19Nb) | 5a, pp 92-3 and 9, pp 371, 495 & 500 |
| 150 mm Gun 16: 15 cm K 16 | Used HE howitzer ammo: 15 cm Hbgr 16 & Hbgr 16 umg | 5a, p 96; 9, p 502 and Ref 12 |


Ger 255
WEAPONS
(CALIBERS 128 mm TO 300 mm)




128 mm RHEINMETALL
ANTITANK GUN
(12.8 cm K-44)




150 mm MEDIUM FIELD HOWITZER
(15 cm sFH 18) WITH
MUZZLE BRAKE



(15 cm sFH 18),
MOUNTED ON PzKw IV
CHASSIS
'BUMBLE BEE'




150 mm MEDIUM
FIELD HOWITZER WITH
MODIFIED BREECHBLOCK
(15 cm sFH 18 43)




150 mm ASSAULT HOWITZER
(15 cm STUH 43) ON PzKw IV
CHASSIS ('GRIZZLY BEAR')




150 mm MEDIUM INFANTRY
HOWITZER (15 cm sIG 33)




210 mm MORTAR (21 cm GrW 19)




150 mm SKODA MORTAR



210 mm GUN 38 (21 cm KANONE 38)



280 mm RAILROAD GUN
'LEOPOLD' OR 'ANZIO ANNIE'
[28 cm KANONE 5 (E)]



300 mm ROCKET LAUNCHER

240 mm GUN
MOD 3 (24 cm
KANONE 3)

Ger 256

(Weapons) (Cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|--|---|
| 150 mm Gun 15.1 cm K 15 | Used ammo: HE (15 cm KGr 18 & 42), HE-A/C (Gr 19 Rot Be), and AP (PzSprgr L/3.7 mHbe) | 5a, p 97 and 9, pp 486-7, 491 & 493 |
| 150 mm Heavy Field Howitzers: 15 cm sFH 15, sFH 18, 1, sFH 18 and sFH 30 | Used ammo: HE (15 cm KGr 18, Gr 19, & Gr 36 FES), HE cast steel (Stggr 19), HE-A/C (Gr 19Be), Rocket Assisted (RGr 19), HoC (Gr 39 III), HE, Sabot (Sprgr 42 TS), AP, Sabot (Pzgr 39 TS) and Smoke (Gr 18Nb, Gr 19Nb, Gr 39Nb & Gr 40Nb) | 5a, pp 93-4; 9, pp 492-5, 497-8, 506-7 & 509 and Ref 12 |
| 150 mm Field Howitzer: 15 cm sFH 18 40 | No description given | 5a, p 95 |
| 150 mm Heavy Infantry Gun (Howitzer): 15 cm sIG 33 or sIG 33 | Used ammo: HE (15 cm Gr 19 & Jgr 38), Rodded bomb (Stielgr 42) and Smoke (Jgr 38Nb) | 9, pp 486, 494-5, 497-8, & 562 and Ref 12 |
| 150 mm Gun 39: 15 cm K 39 | Used ammo: HE (15 cm KGr 18, Sprgr L/4.6 & KGr 47), A/C (Gr 19 RotBe), AP (Pzgr) and SAP (HohPzgr) | 5a, p 98 and 9, pp 487, 493, 498 & 504-5 |
| 150 mm Railway Gun: 15 cm K (E) | Used ammo: HE (15 cm KGr 18) and AC (Gr 19 Be) | 9, pp 493 & 496 |
| 150 mm Heavy Turret Howitzer: 15 cm sFH 12 | Used ammo: HE (15 cm Gr 19 & Gr 19 Stg) and A/C (Gr 19 Be) | 5a, pp 9* 9, pp 4... |
| 150 mm Heavy Field Howitzer: 15 cm sFH 12 | Used same ammo as 15 cm sFH 18 | 5a, p 95 |
| 150 mm Gun on Howitzer Carriage: 15 cm K/MrsLaf | Used ammo: HE (15 cm KGr 18, Sprgr L/4.5, Sprgr L/4.6 & Sprgr mHbe), A/C /Gr 19 Rot Be) and APC BC HE (PzSprgr L/3.8 mHbe) | 5a, pp 96-7 |
| 150 mm Heavy Field Howitzer: 15 cm sFH 18, 43) (with modified breech-lock) | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 150 mm Assault Howitzer: 15 cm Stuhl 43 (L/12) | Used ammo: HE (15 cm Jgr 38 FES) and HoC (Jgr 39 III/A) | 5a, p 99; 9, pp 486 & 491 & Ref 12 |
| 150 mm Recoilless Gun: 15 cm LG 43 | No information given | 5a, p 93 |
| 150 mm Czech Guns and Howitzers: 15 cm K 15, 16 (t), sFH 14/16(t), sFH 25 (t) and sFH 37 (t) | Used Czech ammo | 5a, pp 99-101 & 9, pp 485 & 488-90 |
| 150 mm Rocket Launcher | Used 15 cm HE, smoke and chemical rockets | 9, pp 245-7 |
| 152 mm (5.9") Rocket Launcher | Used HE rocket projectile | 9, pp 247-8 |
| 152 mm Italian Heavy Field Howitzer: 15.2 cm sFH 412 (i) | Used Italian HE ammo: 15.2 cm Sprgr 412/11(i) | 5a, p 106 |
| 152 mm Russian Guns and Howitzers: 15.2 cm sFH 404 (r), sFH 443 (r), sFH 445 (r), KH 433/1 (r), KH 433/2 (r) and KK 456 (r) | Used Russian design HE, Smoke and Shrapnel ammo | 5a, pp 104-7 & 9, pp 510-12 |
| 155 mm (6.10") Belgian Gun: 15.5 cm K 432 (b) | Used Belgian HE ammo: 15.5 cm Gr 420 & 420(b) | 5a, p 108 |
| 155 mm French Guns and Howitzers: 15.5 cm sFH 412 (f), sFH 415 (f), K 416, 417, 418, 419, 420 & 425 (f) | Used French ammo: HE and HoC | 5a, pp 101-3 & 108 |
| 155 mm Polish Heavy Field Howitzer: 15.5 cm sFH 17 (p) | Used Polish HE ammo: 15.5 cm Gr 14 & 15 (p) | 5a, p 101 |
| 155 mm Yugoslav Guns and Howitzers: 15.5 cm sFH 427/1 & 427/2 (j) and K 403 (j) | Used Yugoslav HE ammo | 5a, pp 107-8 |
| 170 mm (6.69") Gun in Mortar Mounting: 17 cm K/MrsLaf | Used ammo: HE (17 cm KGr 38 & 39), Incendiary (BrGr 39), AP (Pzgr 43) and Star Shell (Leuchtgeschoss) | 5a, p 112 and 9, pp 516-17 |
| 170 mm Gun 18: 17 cm K 18 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 170 mm Railway Gun: 17 cm K(E) | Used HE ammo: 17 cm Sprgr L/4.7 | 5a, p 112 |
| 170 mm Austrian Gun: 17 cm K(B) | Same as above | 5a, p 112 |
| 172.6 mm (6.795") Naval Gun: 17 cm SK L/40 | Used HE, AP and Star projectiles | 5b, table 11 |
| 194 mm (7.64") French Railway Gun: 19.4 cm K 486 (E)(f) | Used French HE, cast steel proj: 19.4 cm Stggr 486 (f) and 487 (f) | 5a, p 113 and 9, p 517 |

(Weapons) (cont'd)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|---|--|------------------------------|
| 200 mm (7.874") Light Spigot Mortar: 20 cm H.d.g.W (20 cm Leichter Ladungswerfer) | Used HE and Smoke mortar bombs: 20 cm Wgr 40 and Wgr 40Nb | 5a, p 34 and 9, p 334 |
| 200 mm Rocket Launcher | Used 20 cm AA Rocket | 9, p 248 |
| 203 mm (8.0") Railway Gun: 20.3 cm K(F) | Used ammo: HE (20.3 cm Sprgr L/4.7), AP (Pzgr L/4.7) and flare (LeuchtGr) | 5a, p 114 and 9, pp 520-2 |
| 203 mm Russian Heavy Howitzers: 20.3 cm H 503 (r) & H 503/2 (r) | Used Russian A/C proj: 20.3 cm Gr 503/2 Be (r) | 9, p 518 |
| 203 mm Naval Gun: 20.3 cm SK C./31a | Used HE, AP and Star projectiles | 5b, table 11 |
| 209.5 mm (8.24") Naval Gun: 21 cm SK L/45 | Used HE and AP projectiles | 5b, table 11 |
| 210 mm (8.27") Guns: 21 cm K 12 and K 12 (F) | Used HE projectile: 21 cm Gr 35 | 5a, p 116 |
| 210 mm Mortar 18: 21 cm Mrs 18 (Heavy Howitzer) | Used A/C proj: 21 cm Gr 18 Be | 5a, p 109; 9, p 522 & Ref 12 |
| 210 mm Long Mortar 18: 21 cm lg Mrs 18 | Used ammo: HE (21 cm Gr 17, 17umg 18, 18 Stg) and HE-A/C (Gr 18 Be) | 5a, p 109; and 9, p 523 |
| 210 mm Mortar 19: 21 cm Mrs 19 | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 210 mm Gun 38: 21 cm K 38 | Used HE shell: 21 cm KGr 38 | 5a, pp 114-15 and Ref 12 |
| 210 mm Guns 39, 39/40 & 39/41: 21 cm K 39, K 39/40 & K 39/41 | Used ammo: HE (21 cm Gr 39 & 40), HE-A/C (Gr 39 He) and SAP (HalbPzgr 39) | 5a, pp 110-11 |
| 210 mm Gun 42: 21 cm K 42 | No description given | 5a, p 115 |
| 210 mm Krupp Gun: 21 cm K (Krupp) | No description given | 5a, p 116 |
| 210 mm Rocket Launchers: 21 cm RAG M 42 and others | Used for launching various rockets, such as 21 cm RLg, Wgr 42 Spr and R 1000 BS | 9, pp 248-9, 255-6 & 258-60 |
| 210 mm Czech Heavy Howitzer: 21 cm Mrs Kz(t) | Used Czech ammo: HE (21 cm AZGr 35) and HE High Capacity (MinGr 35) | 5a, p 117 |
| 211 mm (8.27") Gun, designated K 12 (120 km range) | Used HE projectiles | 5b, table 12 |
| 220 mm (8.66") French Gun: 22 cm K 532 (f) | Used French HE ammo: 22 cm Gr 534 (f) & 535 (f) | 5a, p 117 |
| 220 mm Norwegian Heavy Howitzer: 22 cm Mrs M 32 (n) | No description given | 5a, p 118 |
| 220 mm Polish Howitzer: 22 cm Mrs (p) | Used Polish ammo: HE (22 cm Gr 40) and SAP (HalbPzgr) | 5a, p 119 |
| 220 mm Yugoslav Howitzer: 22 cm Mrs (j) | Used Yugoslav HE ammo: 22 cm Gr (j) | 5a, pp 119-20 |
| 234 mm (9.213") Belgian Howitzers: 234 cm H 545 (b), 545/1 (b) & 545/2 (b) | No description given | 5a, pp 119-20 |
| 238 mm (9.37") Naval Gun: 24 cm SK L/40 | Used HE and AP projectiles | 5b, table 12 |
| 238 mm Theodore Gun: 24 cm Theodor K (F) | Used HE and AP projectiles | 5b, table 12 |
| 240 mm (9.449") Howitzer 39: 24 cm H 39 | Used ammo: HE (24 cm Gr 39 & 39 umg), SAP (Gr 39 Be or HalbPzgr) and French cast steel HE shell: Stggr 558/2 (f) | 5a, p 120 |
| 240 mm Guns Modeln 3 and 18: 24 cm K 3 & K 18 | Used HE shell: 24 cm Gr 35 Mod 3 gun; can be seen at the Museum of Aberdeen Proving Ground, Md | 5a, p 120 and Ref 12 |
| 240 mm Theodor Bruno Gun (Railway): 24 cm ThBrK (E) | Used HE ammo: 24 cm Sprgr L/4.2 and L/4.3 | 5a, p 121 and 9, pp 524-5 |
| 240 mm Naval and Seacoast Gun: 24 cm SK L/50 | Used HE ammo: 24 cm Sprgr L/4.1 and L/4.2 | 5a, p 121 |
| 240 mm Thendor Gun (Railway): 24 cm ThK (E) | Same as above | 5a, p 121 |
| 240 mm Krupp Gun: 24 cm K L/46 (Krupp) | No description given | 5a, p 122 |
| 240 mm Czech Gun: 24 cm K (t) | Used Czech HE ammot 24 cm Gr 23 (t) and Gr 40 (t) | 5a, p 122 and 9, p 523 |

| Caliber and Designation | (Weapons) (cont'd) Remarks, Uses and Some Characteristics | References |
|--|---|-----------------------------------|
| 240 mm French Guns: 24 cm K(E) 557 (f) & K 558 (f) | Used French HE cast steel shell: 24 cm Stggr 557 (f) | 5a, p 123 |
| 240 mm French Guns: 24 cm K 546 (f) & K 566 (f) | No description given | 5a, pp 122-3 |
| 240 mm Russian Howitzer: 24 cm H 564 (r) | No description given | 5a, p 122 |
| 270 mm (10.6") French Coast Howitzer: 27 cm Küste Mrs 585 (f) | No information available | 5a, p 124 |
| 274 mm (10.76") French Railway Guns: 27.4 cm K (F) 591 (f) and K(E) 592 (f) | Used French HE ammo: 27.4 cm Gr 593, 594, 595 and 596 (f) | 5a, p 124 |
| 280 mm (11.024") Howitzer: 28 cm H L/12 | Used HE shell: 28 cm Sprgr L/3.5 | 5a, p 124 |
| 280 mm Coast Howitzer: 28 cm Küste H | Same as above | 5a, p 125 |
| 280 mm Short Bruno Gun (Railway): 28 cm KzBrK (E) | Used ammo: HE (28 cm Sprgr L/4.1) and HEAP (PzSprgr L/2.6) | 5a, p 125 |
| 280 mm Long Bruno Gun (Railway): 28 cm LgBrK (E) | Used HE ammo: 28 cm Sprgr L/4.4 | 5a, pp 125-6 |
| Note: According to Ref 5b, table 13, the short and the long Bruno guns were 283 mm | | |
| 280 mm Theodor Bruno Gun (Railway): 28 cm ThBrK (E) or BrNK | Used HE ammo: 28 cm Gr 39mHbgrZ | 5a, p 126 and 9, p 529 |
| 280 mm Gun, Model 5 (Railway): 28 cm K 5(E), nicknamed "Leopold" and "Anzio Annie" | Used ammo: HE (28 cm Gr 35 & Gr 42) and rocket-assisted (RGr L/4.7) | 5a, p 126; 9, pp 527-8 and Ref 12 |
| 280 mm Guns (Railway): 28 cm K 5/1 (E) and K 5/2 (E) | Used HE ammo: 28 cm Gr 39/42 & Gr 42 | 5a, p 127 |
| 280 mm Naval and Seacoast Gun: 28 cm SK L/50 | Used ammo: HE (28 cm Sprgr L/3.6) and AP (Pzgr L/3.2) | 5a, p 127 |
| 280 mm French Heavy Howitzers: 28 cm Mrs 601 (f) and 602 (f) | No description given | 5a, p 128 |
| 280 mm Russian Howitzers: 28 cm H 34/35 (r) and H 607 (r) | No description given | 5a, p 127 |
| 280 Rocket Launcher | Used HE rocket proj: 28 cm WfkSpr | 9, pp 249-51 |
| 283 mm (11.142") Naval Guns: 28 cm SK C/28, C/34 & C/40 | Used HE and AP projectile | 5b, tables 12 and 13 |
| 300 mm (11.81") Self-Propelled Trench Mortar | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 300 mm Rocket Launcher, New Type | Used HE rocket proj: 30 cm Wfk 42 Spr | 9, pp 251-3 and Ref 12 |
| 305 mm (12.00") Naval and Seacoast Gun: 30.5 cm SK L/50 | Used ammo: HE (30.5 cm Sprgr L/3.6) and AP (Pzgr L/3.4) | 5a, p 129 |
| 305 mm Czech Howitzer: 30.5 cm Mrs (t) | Used Czech ammo: HE (30.5 cm Gr 35) and HE-High Capacity (MinGr 35) | 5a, p 128 |
| 305 mm Belgian Howitzer: (30.5 cm H 632(b)), Russian Howitzers: H 622 & 623 (r)] and Yugoslav Gun [M 638(j)] | No description given | 5a, pp 129-30 |
| 310 mm (12.397") Glött Gun on Railway Mount | Can be seen at the Museum of Aberdeen Proving Ground, Md | .2 |
| 320 mm Rocket Launcher (No German designation is given) | Used HE rocket ammo designated as 32 cm Wfk | 9, pp 253-4 |
| 340 mm (13.385") French Gun: 34 cm K 673 (f) | Used French ammo: HE, cast steel (34 cm Stggr) and AP (Pzgr) | 5a, p 130 |
| 355 mm (13.975") Howitzer M-1: 35.5 cm M1, known also as M1 Gun | Used A/C ammo: 35.3 cm GrBe, Ró(Röchling) Gr 42 Be and RÜGr 44 Be | 5a, p 130; 9, p 529 & Ref 12 |
| Note: According to Ref 5b, table 14, the M1 gun was 350 mm | | |
| 365 mm (14.37") Recoiless Gun: 36.5 cm G 104, developed during WW II by the Rheinmetall-Borsig A-G | Not described here because Ref 8, v 3 is confidential | 8, v 3, pp 614 & 623 |
| 370 mm (14.567") French Gun: 37 cm K 710 (f) | No description given | 5a, p 131 |

(Weapons) (con't)

| Caliber and Designation | Remarks, Uses and Some Characteristics | References |
|--|---|--|
| 380 mm (14.96") Heavy Spigot Mortar (38 cm SLdgsW) (38 cm schwerer Ladungswerfer) | Used HE and Smoke mortar bombs: 38 cm Wgr 40 and Wgr 40Nb | 5a, p 34 and 9, p 535 |
| 380 mm Siegfried Railroad Gun: 38 cm SK (E) | Used ammo: HE (38 cm Sprgr L/4.5 & L/4.6) and AP (Pzgr L/4.4) | 5a, p 131 |
| Note: According to Ref 5b, table 14, the Siegfried gun was used as a coast defence gun | | |
| 380 mm Naval Gun: 38 cm SK C/34 | No description given | 5b, table 14 |
| 380 mm Rocket Launcher (No German designation is given) | Used HE rocket, designated 38 cm RSprgr 4581 | 9, pp 254-5 |
| 380 mm Rocket Projector (Sturmörser) mounted on tank: PzKpfw IV | Can be seen at the Museum of Aberdeen Proving Ground, Md | 12 |
| 400 mm (16") Adolf Gun: 40.6 cm SK C/34 | Used ammo: HE (40.6 cm Gr 40, Adolf Gr L/4.2, Sprgr L/4.6 & L/4.8) and HEAP (PzSprgr L/4.4) | 5a, pp 131-2 |
| 420 mm (16.54") Howitzer called by the Germans Gamma Mörser | Used heavy A/C shell: 42 cm sGrBe | 5a, p 132 |
| Note: According to W.Ley, Coast Art J, Jan-Feb 1943, p 16, the word Mörser referred to short medium and heavy howitzers with barrels from 12 to 16 calibers long, while the word Haubitze was restricted to field howitzers. The Austrian usage was not quite uniform, some heavy howitzers were called Mörser , while others were called Haubitzen | | |
| 420 mm Czech and Russian Howitzers: 42 cm Mrs (t) and 42 cm H (r) | Same as above | 5a, p 132 |
| Note: According to W.Ley, Coast Artillery Journal, Jan - Feb 1943, pp 14-15, the following heavy ordnance was developed prior or during WW I: 17 cm L/11 gun, 21 cm L/40 & L/45, 21 cm L/150 (Parisgeschütz or Ferngeschütz), 21 cm L/12 howitzer, 23.5 cm L/132 cm L/132 gun (Parisgeschütz or Ferngeschütz), 24 cm L/30 & L/40 guns, 24.4 cm howitzer (presumably called Alpha), 28 cm L/40 & L/45 guns, 28 cm L/12 & L/14 howitzers (Schwere Küstenhaubitze), 30.5 cm L/50 gun, 30.5 cm L/8 howitzer (called Beta or Schwere Küstenmörser), 30.5 cm L/12 howitzer (Schwere Küstenmörser), 30.5 cm L/16 howitzer (called Beta 09 L/16), 30.5 cm L/17 howitzer (nicknamed Kartause in honor of the German 15th century gun), 35.6 cm L/52.5 gun (built by the Krupp Co for the Greek battleship Basileos Georgios but requisitioned by the Germans before it was delivered), 38.1 cm L/45 coast defense gun (nicknamed Der lange Emil), 42 cm L/14 howitzer (called M or KMK L/14 Kurze Marine Kanone, Lange 14) and nicknamed Dicke Bertha (fat Bertha, not referring to Frau Bertha von Krupp), Dickes Luder (fat wench), Tante aus Essen (aunt from Essen), etc and 42 cm L/16 howitzer (called KMK, Gamma or Eisenbahn 42 (railroad 42)). It has to be mentioned that the shells for the Dicke Bertha were usually called Eiserne Portion (iron portion), while the shells for heavy, flat trajectory, Naval guns were nicknamed Kohlkasten (coal box) | | |
| According to the above author, the long 21 cm and 23.5 cm guns used for shelling Paris were called erroneously Big Berthas . The official name of each of these guns was Kaiser Wilhelm Geschütz but was usually referred to as Parisgeschütz or Ferngeschütz . The crews of the guns made no distinction between the two types and called them Die Pariserin (La Parisienne) | | |
| The term Big Bertha should be reserved for the 42 cm L/14 howitzer, nicknamed by the Germans the Dicke Bertha | | |
| 533.4 mm (21.14") Gun, designated as Gerät 36 | No description given | 5b, table 14 |
| 540 mm (21.26") Heavy Howitzer. 54 cm Karl Mörser or Karl Gerät, called also self-Propelled Mortar M 41 | Can be seen at the Museum of Aberdeen Proving Ground, Md (See also under Panzer) | 5a, p 133 and Ref 12 |
| Note: According to G.B. Jarrett, "Achtung Panzer," Great Oaks, RD1, Aberdeen, Maryland (1948), p 98 there were 540 mm and 610 mm weapons called Thor and Karl Mortars (See under T). According to W.Ley, Coast Art J, Jan-Feb 1943, p 20 the Thor was likely to be 610 mm but some observers claimed only 510 mm | | |
| 615 mm (24.21") Heavy Howitzer: 61.5 cm Karl Mörser | Used HE shell called: Geschloss L/41 für Karl Gerät | 5a, p 133 |
| Note: According to W.Ley, Coast Artillery Journal; Jan-Feb 1943, p 13, the Germans used at the siege of Sevastopol the following super-heavy weapons: 610 mm (appr 24") rifled mortar (short howitzer), 690 mm (appr 27") short Naval rifled gun, railroad mounted and 715 mm (appr 28") rifled mortar (short howitzer) | | |
| 800 mm (31.5") Super Heavy Gun: 80 cm Gustav Geschütz, known also as Sevastopol Gun. (See also "Sevastopol Gun" in descriptive section) | Used HE shell: 80 cm Gustav Granate, which can be seen at the Museum of Aberdeen Proving Ground, Md | 5a, p 133; Ref 12 & F.B. Porter, Field Art J, 35, 545 (1945) |
| Notes: L.E. Simon stated in his book "German Research in World War II", J. Wiley, N Y (1947), p 187 that: "Krupp undertook the development of a 1500-ton tank to mount the 90 cm Krupp gun which was used at Sevastopol. It was designed for operation in built-up areas. This development was stopped before the war ended". According to other sources of information the Sevastopol Gun was 80 cm. One of the photographs in the files of Aberdeen Proving Ground gives the caliber of Gustav Geschütz as 82 cm | | |
| References: See p 226 | | |

Abbreviations:

American and British: AA Antiaircraft; AC Aircraft; A/C Anticoncrete; AP Armor-piercing; A/P Antipersonnel; A/T Anti-tank; BC Ballistic cap (windshield); C Capped; CAP Colt automatic pistol (ammunition); W/see feet per second; HE High explosive; HoC Hollow charge; How Howitzer; l or Inc Incendiary; lb pound(s); M Model; max maximum; MG Machine gun; MP Machine Pistol; muzzle velocity; oz ounce(s); PG Proving Ground; Ref Reference; rpm rounds per minute; SAP Semi-armor-piercing; sec second(s); T Tracer; v volume (of a book); Wt Weight

German: See Abbreviations at the end of German vocabulary.

Table 64 Wetersprengstoffe
(For definition of Wetersprengstoffe see p 226)

| Designation | Composition % | | | | | | | | | | | | | Remarks | References | | | |
|--|---|---------------------|-----|---------------|--------------|-----|-----|-------------------|-----------------------|-------------|--------------------|---------------------|--------------------------------------|-----------------------------|---------------------|----------------------|---|-----|
| | Am- ni- trate | Ba- ni- trate | MNN | NG | Wood Meal | DNT | TNT | K ni- trate | Naph- tha- lene | Car- bon | K chlo- ride | Na chlo- ride | 50% soln of Ca ni- trate | | | Other Ingredients | | |
| W-Ageid A | 27.0 | - | - | 30.0 (Gel) | - | - | - | - | - | - | 38.0 | - | - | Na nitrate Mg silicate | 3.4 1.6 | Gel | 2&4 | |
| W-Albit | Mentioned in Ref 1, p 428 but no composition was given. | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 2&4 |
| W-Ammonochärit A | 64.7 | - | - | 4.0 (Gel) | 1.3 | 8.0 | - | - | - | 2.0 | - | 20.0 | - | - | - | Non-gel | 2&4 | |
| W-Ammonochärit B | 67.0 | - | - | 4.0 (Gel) | 1.5 | 6.0 | - | - | - | 1.5 | - | 20.0 | - | - | - | Non-gel | 2&4 | |
| W-Ammonochärit D } W-Ammonochärit E } | Marshall, v 3, p 121 lists them as having compositions similar to W-Ammonochärites A and B and W-Detonite | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| W-Arit A | 29.5 | - | - | 25.8 (Gel) | - | 3.7 | - | - | - | - | - | 40.0 | - | Glycerin | 1.0 | Gel | 2&4 | |
| W-Arit B | 31.0 | - | - | 25.8 (Gel) | - | 4.2 | - | - | - | - | - | 38.0 | - | Glycerin | 1.0 | Gel | 2&4 | |
| W-Astralit A | 57.0 | - | - | 12.0 (Gel) | 2.0 | 2.0 | - | - | - | - | - | 27.0 | - | - | - | Semi-gel | 2&4 | |
| W-Astralit of type WW I | 74.5 | - | - | 4.0 (Gel) | 1.0 | 7.0 | - | - | - | 1.0 | - | 10.0 | - | Vaseline or paraffin | 2.5 | Non-gel | 6 | |
| W-Balduvit A | 50.0 | - | - | 12.0 (Gel) | 2.0 | 2.0 | - | - | - | 0.5 | - | 33.5 | - | - | - | Semi-gel | 4 | |
| W-Barbarit A | 25.0 | 3.0 | - | 30.5 (Gel) | - | 0.5 | - | - | - | - | 40.0 | - | - | Talc | 1.0 | Gel | 4 | |
| W-Barbarit B | 24.0 | 2.5 | - | 30.0 (Gel) | - | - | - | - | - | - | - | 41.5 | - | Talc Glycerin | 1.0 1.0 | Gel | 4 | |
| W-Bavarit A | 55.0 | - | - | 12.0 (Gel) | 1.0 | 3.0 | - | - | - | 1.0 | - | 28.0 | - | - | - | Semi-gel | 4 | |
| W-Bavarit B | 56.0 | - | - | 12.0 (Gel) | - | 2.0 | - | - | - | - | - | 28.0 | - | - | - | Semi-gel | 4 | |
| W-Carbonit A | 26.5 | - | - | 30.0 (Gel) | 0.5 | - | - | - | - | - | - | 40.0 | 3.0 | - | - | Gel | 2&4 | |
| W-Dalmerit A | 81.0 | 8.0 | - | 4.0 (Gel) | 1.0 | 2.0 | - | - | - | 0.5 | 4.0 | - | - | - | - | Non-gel | 2&4 | |
| W-Detonit A | 82.0 | - | 1.0 | 4.0 (Gel) | 2.0 | - | - | - | - | 0.5 | 10.5 | - | - | - | - | Non-gel | 2&4 | |
| W-Detonit B | 81.0 | 8.0 | - | 4.0 (Gel) | 1.0 | 2.0 | - | - | - | 0.5 | 4.0 | - | - | - | - | Non-gel | 2&4 | |
| W-Detonit C | 64.5 | - | - | 4.0 (Gel) | 1.5 | 7.0 | - | - | - | 0.5 | 10.5 | - | - | - | - | Non-gel | 5 | |
| W-Detonit A | 82.0 | - | 1.0 | 4.0 (Gel) | 2.0 | - | - | - | - | 0.5 | 10.5 | - | - | - | - | Non-gel | 2&4 | |
| W-Dosmit B | 81.0 | 8.0 | - | 4.0 (Gel) | 1.0 | 2.0 | - | - | - | - | 4.0 | - | - | - | - | Non-gel | 2&4 | |
| W-Dosmit A (1936) | See under Commercial Explosives of WW II | - | - | 30.0 | 6.0 | - | - | - | 2.0 | - | - | - | - | Na nitrate Alum Flour | 31.0 1.0 30.0 | Non-gel | Barnett, Explosives (1918), p 194 | |
| W-Dynamit No 1 | - | - | - | - | - | - | - | - | 2.0 | - | - | - | - | - | - | Non-gel | Marshall, v 1, p 392 | |
| W-Dynamit | 94.0 | - | - | - | - | - | - | - | - | 4.0 | - | - | - | - | - | Non-gel | Marshall, v 1, p 392 | |
| W-Füdit A | 75.0 | - | - | 4.0 | 2.0 | 5.5 | - | - | - | 0.75 | 18.25 | 10.0 | - | Guncotton Paraffin } | 4.0 2.5 | Non-gel | Marshall, v 1, p 391 | |
| W-Fulmit | 76.5 | - | - | - | - | - | - | - | - | 1.5 | - | - | - | - | - | Non-gel | Marshall, v 1, p 391 | |
| W-Lignosit A | 62.0 | - | - | 4.0 (Gel) | 4.0 | 0.7 | - | - | - | - | - | 18.0 | - | - | - | Non-gel | 2&4 | |
| W-Lignosit B | 61.5 | 3.0 | - | 4.0 (Gel) | 4.0 | 5.0 | - | - | - | - | - | 22.5 | - | - | - | Non-gel | 2&4 | |
| W-Lignosit C | Marshall, v 3, p 121 lists this explosive but does not give the composition | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| W-Lignosit D | 82.0 | - | - | 4.0 | 1.0 | 1.5 | - | - | - | 0.5 | - | - | - | - | - | Non-gel | 5 | |
| W-Monakit A | 32.0 | - | - | 26.0 (Gel) | 1.0 | 2.0 | - | - | - | - | - | 11.0 | 2.5 | - | - | Gel | 2&4 | |
| W-Monakit A } W-Monakit B } | Marshall, v 3, p 121 lists both W-Monachites as non-gelatinized explosives similar to W-Ammonochärites, W-Detonites, W-Lignosites and W-Westfalites | - | - | - | - | - | - | - | - | - | - | 36.5 | - | - | - | - | - | - |

Table 64 (cont'd)

| | | | | | | | | | | | | | | | | |
|--|------|------|------------|-----|------|------|-----|---|---|---|-----|-------|-----|----------------------|----------|-------|
| W-Nobelit A | 32.0 | - | 26.0 (Gel) | 1.0 | 2.0 | - | - | - | - | - | - | 36.5 | 2.5 | - | Gel | 2,4&6 |
| W-Nobelit B | 26.5 | - | 30.0 (Gel) | 0.5 | - | - | - | - | - | - | - | 40.0 | 3.0 | - | Gel | 2,4&6 |
| W-Nobelit C | 29.3 | - | 24.7 (Gel) | 1.0 | 2.0 | - | - | - | - | - | - | 38.0 | 5.0 | - | Gel | 2&4 |
| See under Commercial Explosives of VW II | | | | | | | | | | | | | | | | |
| W-Nobelit A (1932) | 32.0 | - | - | 3.0 | 8.0 | - | - | - | - | - | - | 23.00 | - | K perchl DNN 4.0 | Non-gel | 1 |
| W-Nobelit B (1932) | 34.0 | - | - | 3.0 | 10.0 | - | - | - | - | - | - | 22.5 | - | K perchl 30.0 | Non-gel | 1 |
| W-Perchlorit I | 57.0 | - | 12.0 (Gel) | 2.0 | - | - | - | - | - | - | 1.5 | 27.5 | - | - | Semi-gel | 5 |
| W-Ferchlorit IV | 57.0 | - | 12.0 (Gel) | 2.0 | - | - | - | - | - | - | 2.0 | 27.0 | - | - | Semi-gel | 4&6 |
| W-Persalit | 81.0 | 8.0 | 4.0 (Gel) | 1.0 | - | 2.0 | - | - | - | - | - | 4.0 | - | Gelose | Non-gel | 2&4 |
| W-Salit A | 20.0 | 10.0 | 28.0 (Gel) | - | - | - | - | - | - | - | - | 40.5 | - | Talc | Gel | 2&4 |
| W-Siegrit A | 36.0 | - | 26.0 (Gel) | 0.3 | 1.35 | 1.35 | - | - | - | - | - | 35.0 | - | - | Gel | 2&4 |
| See under Commercial Explosives of VW II | | | | | | | | | | | | | | | | |
| W-Vasagit A of VW II | 84.0 | 2.4 | 4.0 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| W-Vasagit B of VW II | 82.0 | 2.0 | 4.0 | 1.5 | - | - | 1.6 | - | - | - | 1.5 | 8.0 | - | - | Non-gel | 2&4 |
| W-Wesfalit A | 80.0 | 2.0 | 4.0 | 2.0 | - | 1.5 | - | - | - | - | - | 11.0 | - | - | Non-gel | 2&4 |
| W-Wesfalit B | | | | | | | | | | | | 5.0 | - | m-MNT | Non-gel | 2&4 |
| W-Wesfalit C | | | | | | | | | | | | | | | | |
| W-Wesfalit A of VW II | | | | | | | | | | | | | | | | |
| W-Zellit A | 35.0 | - | 15.0 (Gel) | - | - | - | - | - | - | - | - | 23.0 | - | Cellulose Na nitrate | Semi-gel | 5 |

Abbreviations: Am Atmosphere; DNN Dinitronaphthalene; DNT Dinitrotoluene; Gel Gelatinous explosive; m-MNT m-Nonnitrotoluene; MN Mononitronaphthalene; NC Nitrocellulose; NG Nitroglycerin; Non-gel Non-gelatinous explosive; perchl perchlorate; Semi-gel Semi-gelatinous explosive; TNT Trinitrotoluene; W Wetter (firedamp)

Note: Most of the explosives in Table 64 were on the "Liste der Bergbau Sprengstoffe" (List of Mining Explosives) used prior to WW II.

Table 65 Properties of Some Wetter-Sprengstoffe

| Explosive | Oxygen Balance % | Density of Charge | Veloc Deton, m/sec | Trauzl Test (Lead Block Expansion) cc | Sensitive-ness to Initiation Requires at least: | Gap Test, (using 30 mm cart-ridges) | Heat of Expi-sion, kcal/kg | Tempet of Expi-sion, °C | Vol of Gases in 1. kg at 20°C & 760 mm | Specific Pres-sure (t) atm-kg | Bri-sance (R) (by Kast formula) | Bri-sance (by Pb crushing) mm | Refer-ence |
|--|-------------------------|-------------------|--------------------|---------------------------------------|---|-------------------------------------|----------------------------|-------------------------|--|-------------------------------|---------------------------------|-------------------------------|---------------|
| W-Aszalit A | +4.1 | 1.21 | 3800 | 210 | No 1 cap | 25 mm | 601.0 | 1738 | - | 5900 | 17200 | 10.0 | 2 |
| W-Dahmeit A | +16.1 | 1.06 | 3650 | 220 | No 3 cap | 40 mm | 462.0 | 1388 | 821.0 | 5900 | 17200 | 8.3 | 2 |
| W-Detonit A | +19.9 | 1.04 | 3600 | 230 | No 3 cap | 40 mm | 548 | 1520 | - | 5853 | 18600 | 8.5 | 2 |
| W-Detonit A | +10.4 | 1.06 | 3000 | 215 | No 3 cap | 40 mm | 516.0 | 1730 | 772.3 | 5853 | 18600 | 10.5 | 7 |
| Note: No composition of this second W-Detonit A could be found in any of the sources at our disposal | | | | | | | | | | | | | |
| W-Detonit B | Same as for W-Dahmeit A | | | | | | | | | | | | |
| W-Detonit C | Same as for W-Dahmeit A | | | | | | | | | | | | |
| W-Detonit B | Same as for W-Dahmeit A | | | | | | | | | | | | |
| W-Detonit B | Same as for W-Dahmeit A | | | | | | | | | | | | |
| W-Dynamit I | - | 1.16 | 3900 | - | - | - | 531.0 | 1490 | 763.0 | 4740 | 15900 | - | 5 |
| W-Linoxir D | - | 1.04 | 3000 | - | - | - | - | - | - | - | - | - | Barnett p 194 |
| W-Nobelit B | - | 1.7 | 5650 | - | - | - | 518.0 | 1480 | 911.0 | 5620 | 17500 | - | 5 |
| W-Salit A | - | 1.1 | 3300 | - | - | - | 607.0 | 1615 | 538.0 | 5300 | 35400 | - | 5 |
| W-Sonmit A | Same as for W-Detonit B | | | | | | | | | | | | |
| W-Zellit A | - | 0.6 | 3000 | - | - | - | 937.0 | 2630 | - | 6370 | 11500 | - | 5 |

Specific pressure (Speziellesches Druck), (P) is calculated according to the formula given on p 51 of Ref 5.
 Bri-sance by Kast (Bri-sanzwert nach Kast), (R) is calculated according to the formula given on p 57 of Ref 5.
 (See also in general section)

The explosives of Table 64 were divided into three groups:

A. Ammonsalpeter-Wettersprengstoffe (Ammonium Nitrate Permissible Explosives), marked in Table 64 above as Non-gel (Non-Gelatinous)

B. Nitroglycerin-Wettersprengstoffe (Nitroglycerin Permissible Explosives), marked in Table 64 above as Semi-gel (Semi-gelatinous)

C. Gelatinöse-Wettersprengstoffe (Gelatinous Permissible Explosives), marked in Table 64 above as Gel (Gelatinous).

The (A) group included powdery compositions with a NG content not higher than 5% and a density of about 1.0. Wetter Ammoncahüsit, W-Astralit, W-Dononit, W-Lignosit, W-Monachit and W-Westfalit belonged to this group. They were suitable for blasting soft coal.

The (B) group included partly gelatinous but not plastic compositions containing 1.7-15% of NG-NC gel and had a density of about 1.3. Wetter-Baldurit A, W-Bavarit A, W-Salit A and W-Siegrit A belonged to this group. They were suitable for blasting hard coal and rock seams.

The (C) group included gelatinous (plastic) explosives which contained about 30% of NG-NC gel and had a density up to 1.7. Wetter-Arit A, W-Barbarit A, W-Carbonit, W-Nobelit and W-Wasagit belonged to this group. They were suitable for blasting hard rock.

Table 65 gives the properties of some Wetter-Sprengstoffe listed in Table 64 (See previous page).

Weyl Explosives, patented in 1895, were based on a mixture of NG and coal tar (creosote), as for instance: NG 27.0, creosote 4.5, collod cotton 1.0, Na nitrate 53.0, rye flour 9.0 and Na bicarbonate 5.5%.

Reference: Daniel, Dictionnaire, Paris (1902), p 808.


Wgr 21 cm. An air-to-air, solid propellant rocket developed in 1943. Launching weight 176 lb, overall length 3.7 ft, diameter 8.3" and velocity (all burnt), 1,050 ft/sec.

Wilhelm Explosives, patented in 1894, were manufactured by Dynamit A-G. E.g.:

a) Am nitrate 90 and aniline tartrate (neutral) 10%

b) Am oxalate 94 and naphthylamine oxalate 6%.

Reference: Daniel, Dictionnaire, Paris (1902), p 809.



Note: According to Marshall, v 3, p 123, all German coal mining explosives contained a large excess of oxygen. This achieved two purposes:

- It lowered the brisance of an explosive so that the coal would not be broken into very small pieces
- It avoided the formation of carbon monoxide which is undesirable because of its high toxicity.

Too large an excess of oxygen also had to be avoided because it caused the formation of nitrogen oxides which are poisonous (although not as much as carbon monoxide).

References:

- P.Naoum, Schiess- und Sprengstoffe, Steinkopf, Dresden (1927), p 147
- P.Naoum, Nitroglycerin etc, Williams & Wilkins, Baltimore (1928), pp 389, 414-16, 428, 436-39 & 444
- A.Marshall, Explosives, Churchill, London, v 1 (1917), v 3 (1932), pp 121-3
- J.Pepin Lehalleur, Poudres, Explosifs, et Artifices, Baillière, Paris (1935), pp 411-14
- C.Byling & K.Drekopf, Sprengstoffe und Zündmittel, Springer, Berlin (1936), pp 32, 100-05
- Thorpe's Dictionary of Applied Chemistry, Longmans, Green, London, v 4 (1940), pp 554-6
- P.Naoum, S S 39, 54 (1944) (Table giving properties of W-Dononit A and W-Nobelit A)
- A.Stettbacher, Spreng- und Schiesstoffe, Rascher, Zürich (1948), p 91.

(See also Schlagwettersichere Sprengstoffe and Sicherheits-sprengstoffe).

Wind Gun, developed during WW II in Stuttgart, was designed to shoot a mass of air at an airplane in such a way as to bring it down. The energy for projecting the air was supplied by heat produced on burning a mixture of oxygen and hydrogen. It was claimed that the air shot from this gun could break a 1 inch board at a range of 200 meters, but at longer ranges it was not effective (See drawing below).

Reference: L.E.Simon German Research in WW II, Wiley, N Y (1947), p 180.

Wind Tunnel (Windkanal). Many wind tunnels were used in Germany during WW II. Of these the following were used for ballistic testing of weapons and ammunition:

a) Supersonic ballistic tunnel of AVA at Göttingen was capable of going to a Machnumber of 3.7

b) Supersonic tunnel of IWA at Kochel was capable of going to a Machnumber of 4.4. This was the mightiest supersonic wind tunnel in Germany

c) Subsonic wind tunnels for testing ballistics of ... belonged to LGZ, near Stuttgart.

... numerous wide wind tunnels for testing aircraft.

... belonged to the following organizations: AVA at Göttingen, LFA in Braunschweig, LFA at München, LGZ near Stuttgart and WVA at Kochel. One of the largest tunnels (8 m in diameter) was under construction at Otstal in the Bavarian Alps

(See also High Speed Tunnels)

Abbreviations: See under Warplants, etc.

References:

- CIOS Report (1945), pp 28-47
- L.E.Simon, German Research in World War II, J.Wiley, N Y. (1947), pp 16, 24-30, 131, 140-146 & 154-155.

Wire Command Guidance System for Missiles. See under Guidance Systems for Missiles.


Witol. The name given to synthetic toluene.

Wohl Dynamites, patented in 1891, were based on the low-freezing NG, which was prep'd by the nitration of glycerin previously heated with conc'd sulfuric acid to 130-160° and then cooled. As the result of this heating, some polyglycerines were formed which on nitration gave low-freezing nitropolyglycerins.

Reference: Daniel, Dictionnaire, Paris (1902), p 811.

WEAPONS


(CALIBERS 310 mm TO 610 mm)



310 mm GLÖTT GUN, MOUNTED ON 280 mm RAILWAY GUN [28 cm K 5 (E)] MOUNT




420 mm HOWITZER (WEIGHT OF WEAPON 35 TONS, WT OF PROJECTILE 1750 LB, RANGE 14500 YDS)




355 mm HOWITZER M1 BARREL (PLACED ON TRANSPORT CARRIER)




610 mm MORTAR "THOR" (USED AT THE SIEGE OF SEVASTOPOL)



380 mm ROCKET PROJECTOR (38 cm STURMMÖRSER), PLACED ON PzKw VI CHASSIS



540 mm SELF-PROPELLED MORTAR KARL GERÄT ON RAILROAD TRUCKS



540 mm BARREL OF SELF-PROPELLED MORTAR KARL GERÄT, PLACED ON TRANSPORT CARRIER

WP (Würfelpulver) (Cubical or Prismatic Propellant). A flaked smokeless propellant in the form of small rectangular grains. It was first manu'd under the name of **WPC-89** (Würfelpulver Construction 1889) by the Vereinigte K nig-Rottweiler Pulverfabrik in Rottweil, W rttemberg for use in the Army guns, caliber 37 mm, 53 mm and 150 mm. The composition of WPC-89 was similar to the Italian Ballistite (Ref 1).

Barnett (Ref 2) gives the composition of an early WP as follows: NG 50, NC 50% and small quantity of DPHA, added.

Brunswig (Ref 3) gives for WP used after WW I: NG 38.5, NC 60, centralite, or acardite 1.0 and moisture 0.5%.

References:

1) J. Daniel, Dictionnaire des Mat res Explosives, Dunod, Paris (1902), p 811

2) F. Barnett, Explosives, Van Nostrand, N Y (1919), p 78

3) H. Brunswig, Das rauchlose Pulver, W. de Gruyter, Berlin 1929, p 136.

WPC-89. See under WP (Würfelpulver).

W-Salz. The name given to Hexogen (RDX) prep'd by the nitration of N methylenaminc sulfonate (See under Hexogen)

W rfelpulver. See WP.

W rgebohrung Gesch tz. See Tapered bore gun.

X-4 was a fin-stabilized guided missile with a proximity fuze'd warhead developed especially for use by fighter planes against enemy bomber formations. It was propelled by a liquid fuel (Tonka 250) and an oxygen carrier (Salbei). Some experimental models were equipped with devices called "Kranich" and "Pudel" [TM 9-1985 (1953), pp 215-19].

X-Ray Equipment (R ntgeneinrichtung). A short description of the x-ray equipment manufacturing industry is given in CIOS Report 28-31 (1945).

X-Series Guided Missiles. See Ruhrstahl under Guided Missiles.

X-Stoff. See Tetan.

Zabel, in 1899, constructed a metallic cartridge consisting of two compartments divided by a thin partition. In one of the compartments was a mixture of Ca carbide and Ba peroxide, while the other contained a dilute acid solution. On breaking the partition the acid reacted with carbide and peroxide to form a mixture of acetylene and oxygen which immediately exploded.

Reference: Daniel, Dictionnaire (1902), p 814.

Zeitschnur (Time Fuse), called in the USA Safety or Blasting Fuse. See under Fuses in the general section.

Zeitschnurzeitz nder (Time Igniter With Fuse). See under Electric Igniters, or Primers and also in Beyling Drekkopf (1936) pp 175 & 266-69.

Zell-Igelit was a porous vinyl chloride polymer laminate for use as an outside armor for the air intake tube (Schn rkel) as well as for the periscope in order to prevent the detection of submarines by short waves sent from enemy planes by radar.

The pores of Zell-Igelit contained nitrogen generated within the material by a special process involving the use of a substance known as "Porofor N". For this a mixture consisting of polyvinyl chloride 95 and Porofor N 5% was heated in an autoclave at 130  and then the mass was laminated. During this process the Porofor N dissolved in the vinyl chloride and reacted with the liberation of nitrogen which formed bubbles inside the material. Each Schn rkel tube was covered with 7-8 layers of the above porous laminate each layer being separated from the other by interposing carbon black coated paper, which was slightly conductive to electricity. It was assumed that the incoming short waves from a radar generated convection currents within the carbon paper and these currents were subsequently buffered if not completely absorbed by the laminates. Reflection of the short wave was thus minimized if not completely absorbed by the insulating mass.

Reference: CIOS Report 25-18 (1945), pp 29-30.

Zellpoch. See under Raschig's White Blasting Powder.

Zinn (Tin). See general section.

Note: According to A. Stettbacher, Spreng- und Schiesstoffe, (1948), p 43, small quantities of tin, (or of its easily reducible compounds) were incorporated in some German NG smokeless propellants in order to protect the inside of gun barrels from erosion.

Z-Salz the name given to Na or Ca permanganates used as oxidizing components of rocket propellants in which T-Stoff served as a combustible component. A-Salz was used in the Feuerlilie type guided missiles called Hecht. Reference: I. Ross, Jr, Guided Missiles, Rockets and Torpedoes, Lothrop etc N Y (1951), pp 45-46.

Z-Stoff C. An aqueous soln of calcium permanganate containing 600 g MnO₄ per liter. Sp gr 1.4 at 20  and fr p -22 . Used as a catalyst, as described below (CIOS 30-115, p 10).

Z-Stoff N. An aqueous soln of sodium permanganate containing 600 g of MnO₄ per liter Sp gr 1.4 at 20  and fr p -80  Used as a liquid catalyst in liquid rocket propellants to assist the decomposition of hydrogen peroxide which served as a source of oxygen (CIOS 30-115, pp 8 & 10).

Note: Z-Stoff N was used in summer since its fr p is -8 , while Z-Stoff C was used in winter (fr p -22 ). When Z-Stoff C or N is used to decompose the T-Stoff (hydrogen peroxide) the gaseous products contain besides water vapor and oxygen some small particles of manganese dioxide. Due to the presence of these particles, the gaseous mixture thus produced is not suitable for driving a turbine but can be used for other purposes such as in assisted take-off units and in rockets. When it is necessary to obtain a gaseous mixture free of MnO₂ the decomposition of H₂O₂ is conducted by means of a solid catalyst, such as described under MP-14.

Z nder. See Fuze.

Z ndersprengkapsel-43. A separate cap and detonator assembly designed for use in some A/T mines in conjunction with a tilt type igniter, called Kippz nder 43 [TM 9-1985-2 (1953)].

Z ndkraft. See Initiatorverm gen.

Z ndpatronensatz. See Cartridge Case Percussion Primer.

Z ndsatz (Priming Composition). See Primary and Initiating Compositions.

Z ndschnuranz nder (Igniter or Lighter for Fuse). Beyling-Drekkopf (1936), pp 166-69, describes several types of igniters. Some of them are intended for use in fireamp-free mines (f r Schlagwetterfreie Gruben), while others for gaseous mines (f r Schlagwettergruben).

Z ndstoffe oder Initialexplosivstoffe (Priming, Igniting or Initiating Compounds). See Primary and Initiating Compositions.

Z ndverst rker (Ignition Intensifier). Ignition of a propellant in 50 to 240 mm weapons was accomplished by means of a primer combined with an igniter contg about 2 g black powder. For larger guns, an extension, called Z ndverst rker was fixed in front of the primer. This was filled with large grains of black powder and had a venturi at the forward end to throw the flame the full length of the charge. There were also one or two small side holes to ignite the rear of the charge as well.

Reference: CIOS 31-68 (1946), p 7 (See also under Ignition).

Zunehmender Drill. See Progressive Rifling.

Zusammengesetzte Z nder (Composite Igniters or Primers) are described in Beyling-Drekkopf (1936), p 174.

Zwischenladung, Zwischenz ndladung, oder Zwischenz nder (Intermediate Charge or Houser) is described in A. Stettbacher, Schie - und Sprengstoffe, Leipzig (1933), p 352.

Zwischenz nder. See Zwischenladung.

Zwischenz ndladung. See Zwischenladung.

VOCABULARY
OF
GERMAN ORDNANCE, AMMUNITION AND
RELATED TERMS WITH SOME
ABBREVIATIONS

(In collaboration with H. A. Tisch and J. F. Hauck of
Picatinny Arsenal, Dover, New Jersey)

A

| | | | |
|---------------------------------|--|--------------------------------------|---|
| Abbau | Mining(ors), dismantling(structure); decomposition | abschiessen | to shoot down; discharge; fire |
| Abbildung (Abb) | Illustration; figure; diagram | abschleppen | to tow |
| abblazen | to release gas | Abschleudermaschine | Centrifuge; catapult (See also Schleudermaschine) |
| abbrechen | to break off; cease | abschleudern | to throw with a sling |
| abbremsen | to brake; stop | Abschmelzdraht | Fuze wire; fusible wire |
| abbrennen | to burn off; deflagrate; finish burning | abschmierem | to grease; lubricate |
| abdampfen; abdunsten | to evaporate | Abschnitt | Sector; area |
| Abdrift | Drift | Abschrägung | Sloping; slope; bevel; taper |
| abdrücken | to pull a trigger; fire | Abschuss | Discharge |
| Abfalläure | Waste acid | Abschussrohr | Projector (CWS) |
| Abfeuern | Firing | absehen | to see; aim; take sight at |
| Abfeuerungsvorrichtung | Firing mechanism; release mechanism (Mor) | Abspaltung | Splitting off; cleavage; separation |
| Abgang | Discharge | absprengen | to blast; burst |
| Abgangsfehler | Jump; vertical jump (Arty) | Abstand | Distance |
| Abgangswinkel | Angle of departure | Abstandsladung H15 | Prepared hollow charge, 15 kg Hexogen (RDX), equipped with three legs to provide the desired stand off distance |
| Abgase | Exhaust gases | Abstandwerfen | Pattern bombing |
| abgiessen | to cast metal; pour off; decant; spray chem warfare agents | Abstandzünder; Radiogesteuertezünder | Radio proximity fuze; VT fuze |
| abknallen | to explode; go off; fire off | Abstellbahnhof | Railroad yard |
| abknistern | to decrepitate | Abteilung | Detachment; unit: |
| Abkommen | Deviation; point of aim (at time of firing) | Abwehr | Active defence; military security |
| Abkommrohr | Subcaliber tube (G) | Abwehrgeschütz | Defense gun; AA gun |
| Abkommachiessen | Subcaliber firing | Abwehrleuchtzeichen | Air flare |
| abkühlen | to cool | Abweichung (des Geschosses) | Deviation; drift (Proj) |
| Abkühlung | abkühlung | Abweiser | Cartridge case deflector protector |
| Ablage | Dump; depot | Abwerfen | to drop; jettison |
| Ablagerung | Storage; deposit | Abwurf | Release (bombing) |
| Ablenkung | Deflection; deviation | Abwurfbehälter | Aerial bomb container |
| Abnahme | Acceptance; decrease | Abwurfgerät; Abwurfvorrichtung | Bomb release mechanism |
| Abnahmeprüfung | Acceptance test | Abwurfmunition | Drop ammunition such as aerial bombs, mines, torpedoes and some pyrotechnic items. |
| Abnahmevorschrift | Specification | Abwurfzeichen | Aircraft smoke signal (lit Drop-smoke signal) |
| abnutzen | to wear out | Abwurfzeichen | Bomb rack |
| Abnutzung des Rohres | Bore erosion (G); (see Ausbrennung des Rohres) | Abwurfzeichen | Bomb sight |
| Aböl | Waste oil | Abwurfzeichen | to pull (a trigger); draw off |
| Abpraller | Ricochet | Abwurfzeichen | |
| Abprallwinkel | Angle of ricochet | Abwurfzeichen | |
| Abproduct | Waste product; by-product | Abwurfzeichen | |
| Abreisaknopf | Fuze-cord button (HdGr) | Abwurfzeichen | |
| Abreise-schleife | Fling cord loop (HdGr) | Abwurfzeichen | |
| Abreise-schnur | Fuze cord; lanyard | Abwurfzeichen | |
| Abreisenzünder | Friction igniter; rife cord igniter | Abwurfzeichen | |
| Abriistung | Disarmament | Abwurfzeichen | |
| Abtaugentfeuchter | Vacuum deaerator | Abwurfzeichen | |
| Abseider; Abseidungsvorrichtung | Separator | Abwurfzeichen | |

| | | | |
|--------------------------------|---|---|--|
| Abzug | Trigger | Annäherung | Approximation; approach |
| Abzugsgang | Trigger pull | Anpassung | Adaptation |
| Abzugssehne | Firing line; lanyard | Anrufzeichen | Call signal |
| Abzugsvorrichtung | Trigger mechanism; firing mechanism | Ansäuerung | Acidification |
| Abzweigung | Branch; junction (RR) | Ansaugung | Suction |
| Acetessigäther; Acetessigester | Ethyl acetate | Anschlag | Impact; stroke; aiming or firing position |
| Acetsäure | Acetic acid | Anschliesspatrone (See also Anwürmeschuss and Einschiessgeschoss) | Cartridge used for adjustment fire and for warming up a gun; warmer |
| Achse | Axis; axle | Anschluss | Joining; junction; connection; something annexed; liaison |
| Adamsit; DM | Adamsite; diphenylaminocoloroarsine | Anschlussbahnhof | Railroad junction |
| Adolf (Kanone) | 406 mm coast defense cannon | Anschluss | Sighting shot |
| Aether | See Äther | ansetzen (das Geschoss) | to ram |
| Apo | Name of an aircraft manufacturing company | Ansetzer | Rammer; ramrod (G) |
| Akazin | Gum arabic | ansprengen | to blow up; blast |
| Akja | Boat type runner placed under gun wheels for operation in deep snow; (also used as a swamp conveyance for wounded, etc) | Ansteckmagazin | Detachable magazine |
| Akkumulator | Storage battery; accumulator | Anstellwinkel | Angle of yaw |
| Aktiengesellschaft (A - G) | Joint Stock Company; Open Corporation | Anstoss | Collision; impulse |
| Alarmpistole | Alarm pistol; blank pistol | anstürmen | to attack; assault; charge |
| Alarmschussgerät | Trip-wire alarm flare equipment | ansvisieren | to take aim; to sight |
| Alarmschusspatrone | Trip-wire alarm flare cartridge | Anwärmeschuss | Warming - up shot |
| Alkalipatrone | Alkali cartridge (oxygen breathing apparatus) | Anwendung | Employment; use |
| alkalisch (alkal) | alkaline | Anzahl (Anz) | Number; quantity |
| Alkalität; Alkalizität | Alkalinity | Anzahl der Nuten | Number of grooves |
| Alkohol (Alk) | Alcohol; ethanol | Anzeiger | Index; indicator |
| allgemein | general; common | Anzünder | Igniter; lighter |
| Amboss | Anvil | Arabin-gummi | Gum arabic |
| Ammon | Ammonium; ammonia | Arbeit | Work; labor; job |
| Ammoniak | Ammonia | Arbeitsgeschütz | Roving gun (Arty) |
| Ammonpulver | Ammonal | Armee | Army (a tactical unit above Army Corps, distinguished from Heer, the Army) |
| Ammonsalpeter | Ammonium nitrate | Armeevolyer | Service revolver |
| Ammonsalpeter - Sprengmittel | Ammonium nitrate explosive | Arsenal; Zeughaus | Arsenal |
| Amorce (see also Zundhütchen) | Paper percussion cap (toy pistols) | Arsin | Arsine (CWS) |
| Amphibienkampfwagen | Amphibian combat vehicle | Art | Kind; sort; variety; species; pattern; type; manner |
| Am | Office; post; employment; business | Artillerie (A) | Artillery |
| Anfangsdrall | Initial twist of rifling | Artillerie, leichte (A) | Light artillery |
| Anfangsdruck | Initial pressure | Artillerie, schwere (sA) | Medium artillery (lit Heavy) |
| Anfangsgeschwindigkeit | Initial (muzzle) velocity | Artillerie, schwere (ssA) | Heavy artillery (lit Heaviest) |
| Anfangsladung | Initial charge | Artilleriewesen | Gunnery; Ballistics (See also Schiesswesen) |
| Anfeuchtung | Moistening; damping; humidifying | Arznei; Arzneimittel | Drug; medicine |
| Anfeuerung | Combustible composition in a flare cartridge; ignition | Arzt | Doctor; physician; medical officer |
| Anfeuerungssatz | Fulminating compound; booster charge; igniter train | Ast der Flugbahn | Branch of trajectory |
| Anführungszeichen | Quotation marks | Atemgerät | Oxygen apparatus (lit Breathing apparatus) |
| Angriff | Attack | Äther | Ether |
| Anhänger (Anh); Anhängewagen | Trailer | Äthylarsindichlorid | Ethyl dichloroarsine (CWS) |
| Anhydrierungsmittel | Dehydrating agent | Äthylchlorarsin | Ethyl dichloroarsine (CWS) |
| Anker | Anchor; armature; rotor | ätzender Kampstoff | Bilateral gas (CWS) |
| Ankermine | Anchored mine; moored mine | Ätznatron | Caustic soda (NaOH) |
| Anladung; Primärladung | Top (primary) charge of a blasting cap or a detonator; primer | äussere Ballistik | External Ballistics |
| Anlage | Installation; annex; plant; design | äussere Weite (aW) | External diameter (ED) |
| Anlasser | Starter | Atmosphäre (Atm) | Atmosphere |
| Anlaufgeschwindigkeit | Starting (take off) speed | Atombombe | Atomic bomb |
| Anlegepunkt | Aiming point | | |

| | | | |
|---|---|----------------------------|---|
| Aufbau | Building up; structure; super-structure, i.e. sponson and turret (Tk) synthesis | Auseinandernehmen | Taking apart, stripping |
| aufbauchen; aufhauschen | to swell up; puff up | Ausfall | Precipitation; falling out |
| Aufbauchung | Bulge; swelling | Ausführung (Ausf) | Design; model; execution |
| aufbrauchen | to consume; use up | Ausgang | Exit; departure; start |
| aufbrausen | to effervesce | Ausgleicher | Compensator; equilibrator |
| aufbrechen | to break up; burst; open up | ausgluhen | to anneal; to ignite |
| aufdunsten; aufdunsten | to evaporate | Ausguss | Lip; spout; casting |
| Auffangvorrichtung | Buffer | Ausgussmörser | Lipped mortar |
| Aufforderungssignal (AS) | Call signal | aushärten | to temper; harden |
| Aufklärungspanzer | Light armored reconnaissance vehicle (See also Panzerspähwagen.) | auslöschen | to extinguish; put out (fire) |
| Aufladung | Detonating (base) charge of a cap | Auslöseeinrichtung | Release mechanism (bombing) |
| Aufloslichkeit | Solubility | Auslösehebel | Release lever |
| Aufnahme | Photographic picture | auslösen | to uncouple; release |
| Aufplatzen | to explode; burst open; blow up | Ausnahmeladung | See Sonderladung |
| Aufsatz | Rear sight; telescope mount | Ausnutzungskoeffizient | Utilization coefficient; efficiency |
| Aufschlag | Impact; percussion; shock | Ausreisser; Fehlschuss | Stray shot |
| Aufschlaggeschoss | Impact (percussion) projectile | Ausrüstung | Equipment; armament; outfit |
| Aufschlaggranate | Impact (percussion) shell | ausschiessen (Lauf) | to wear out the gun; to score the bore |
| Aufschlagzünder (AZ) | Impact (percussion) fuze | Ausschnitt | Cut; notch |
| Aufschlagzünder mit Verzögerung (AZmV) | Impact (percussion) fuze with delay | Ausschwitzung | Exudation |
| Aufschlagzünder ohne Verzögerung (AZoV) | Impact fuze without delay | äussere Ballistik | External Ballistics |
| aufschrauben | to screw in | Ausprungwinkel | Angle of reflection |
| Aufspaltung | Splitting up; cleavage (of compounds) | Ausstossbuchse | Smoke canister ejected from projectile on burst |
| aufsprengen | to blow (blast or force) open | Ausstossen | to expel; eliminate |
| Aufsteckmunition | Semi-fixed ammunition | Ausstossladung | Expelling charge of a projectile; burster |
| aufsteigender Ast | Ascending branch (of trajectory) | Ausstossrohr | Ejecting tube; torpedo launching tube |
| Auftaupunkt | Thaw point | Austrockner | Desiccator |
| Auftreff | Impact; collision | auswiegen | to weigh out; calibrate by weight |
| Auftreffgeschwindigkeit | Terminal velocity; striking velocity | Auswahl | Choice; selection |
| Auftreffpunkt | Impact point; striking point | auswalzen | to roll out |
| Auftreffwinkel | Angle of impact; angle of incidence | auswärmen | to anneal; roast |
| Aufzug | Elevator | Auswaschflasche | Wash bottle |
| Augenblicks- | Instantaneous | Abwechselbar; austauschbar | interchangeable |
| Augenblickszünder | Instantaneous nondelay fuze; quick fuze | auswechselbares Seelenrohr | Removable (interchangeable) liner in a gun |
| Augenblickzünder mit Verzögerung | Instantaneous fuze with delay | Ausweg | Way out; outlet |
| Augenreizstoff | Lacrimator (CWS) | Ausweichung | Deviation; deflection; detour |
| Aushau | Construction; dismantling (G) | Ausweis | Proof; evidence, report |
| Ausbauchung | Expansion; swelling; enlargement | Auswerfer | Ejector (Ord) |
| Ausbrutz | Yield; crop; output | Auswertung | Valuation; value |
| Ausbläser | Deflagration without detonation | Auswitterung | Efflorescence; detection by odor |
| Ausblühung | Efflorescence | ausziehen | to extract |
| Ausbohrung | Bored hole; bore of rifle | Auszieher | Extractor (Ord) |
| Ausbrennen | to burn out rifling; erode | Autofrettage | See Kaltfrettung |
| Ausbrennung des Laufes; Rohrabnutzung | Erosion of the bore (G) (See also Abnutzung des Rohres) | Automat | Automat |
| Ausdampfung | Steaming out | automatische Mine | Automatic mine |
| Ausdehnung | Expansion | automatisches Gewehr | Automatic rifle; submachine gun |
| Ausdunstung; Ausdünstung | Evaporation; vapor | Axe; Achse | Axis |
| | | Azetylsauerstoffbrenner | Oxacetylene torch |
| | | Azot; Stickstoff(N) | Nitrogen |
| | | | B |
| | | Backbord | Port side |
| | | Bahn | Way; road; railroad; trajectory |
| | | Bahnhof | Railroad station |
| | | Bajonett | Bayonet (See also Seitengewehr) |

| | | | |
|-------------------------------|---|---------------------------|--|
| Bayonetverbindung | Bayonet joint | Berger-Mischung | Berger-type smoke agent (Zu dust 40 and hexachloroethane 60%) |
| Bake | Beacon; navigation guide | Berggeschütz(BG) | Mountain gun (See also Gebirgsgeschütz) |
| Balkenlafette | Beam gun carriage | Bergmann | Miner |
| Balkenwage | Beam balance | Bergwachs | Mineral wax; ozocerite |
| ballistischer Beiwert | Ballistic coefficient | Bergwerk | Mine(coal, ore, etc) |
| ballistischer Pendel | Ballistic pendulum | Bergwerksprengmittel | Mining explosive |
| Ballon | Balloon; carboy | Bergweiler | Damp (Mining) |
| Bandolier | Bandoleer; shoulder-belt | Bergwolle; Steinflachs | Mineral wool; asbestos |
| Bar | Bear (One of the tanks)(See under Panzer) | Asbest | |
| basisch(bas) | basic | Bericht | Report; notice; information |
| Batterie | Battery(Arty); accumulator | Bernstein | Amber |
| Bauart | Type of construction | Bernsteinsäure | Succinic acid |
| Baujahr | Year of construction | berittene Artillerie | Horse artillery |
| Baumegrad; Be | Degree Baumé; Bé | hersten | to burst; explode |
| Baumwollabfall | Cotton waste; cotton linters | Berücksichtigung | Consideration; regard |
| Baumwolle | cotton | Beruf | Calling; occupation |
| Bausoldat | Soldier in a construction unit | Besatz | Stemming; tamping(See also Verdämmen) |
| Beamter; Beamte | Official; civil servant | Besatzung | Garrison; crew |
| Beanspruchung | Strain; straining | Besatzungsheer | Army of occupation |
| Becher | Beaker | Beschädigung | Damage; injury |
| Bedienung | Gun squad; gun crew; service | Beschaffung | Procurement(A division of Heereswaffenamt in charge of procurement of amterials and finished articles) |
| Bedruckung | Printing; impression | Beschäftigung | Occupation; business |
| Befehl | Order; command | beschossen | to proof fire; to cannonade |
| Befeuchtung | Moistening; dampening | Beschissung | Hombardment |
| Begleitartillerie | Accompanying artillery | Beschuss(Bs) | Firing-shooting; proof fire |
| Begleitgeschütz | Accompanying gun | Beschusspatrone(BsPatr) | Proof round (high pressure) |
| Behälter | Container; gasoline tank | beschuss-sicher | bulletproof |
| Beharrungsvermögen | Inertia; force of inertia | beschützen | to protect |
| Beheizung | Heating | Beselcratc | Footbridge; hasty trestle (named after General H. von Beseler; 1850-1921) |
| Behelfsmine | Makeshift mine | Besetzungarmee | Army of occupation |
| Beiheft | Supplement (The word is sometimes used in titles in journals such as Kolloidchemische Beihefte) | besonders(bes) | especially; singularly |
| Beihilfe | Help; assistance | bespanntes Geschütz | Horse-drawn gun |
| Beiladung | Supplementary (increment) charge (such as in non-fixed ammunition); booster charge; ignition charge | Bessemerstahl | Bessemer steel |
| Bein | Leg | Bestand | Stock; (supplies; equipment); inventory; strength |
| Beispiel | Example | Beständigkeit; Stabilität | Stability (See also Haltbarkeit) |
| Beisszange | Nippers; pinchers | Bestätigung | Confirmation |
| Beitrag | Contribution; share | Bestimmung | Determination |
| Beiwagen(Beiw) | Side car | bestreichendes Feuer | Grazing fire(Arty)(See also Strichfeuer) |
| Beiwart | Coefficient | Bestückung | Armament(AC or Tk)(See also Bewaffnung) |
| Beize | Corrosive; corrosion | Beton(Be;Bet) | Concrete(made with cement) |
| Bekapseln(der Patronenhülsen) | Priming(of cartridge cases) | Betonbombe(BetB) | Concrete bomb |
| bekapselte Hülse | Primed cartridge case | Betonbunker | Concrete pillbox |
| bekupfern | to copper | Betongranate(Betgr) | Anticoncrete shell(See also Granate Beton) |
| Beladen; Beladung | Loading; charging; load; cargo | Betonturm | Concrete turret(Fort) |
| Belagerung | Siege | Betriebsanlage | Plant; works |
| Belagerungsgeschütz | Siege gun | Betriebsbereich | Limits of operation |
| Beleuchtung | Lighting; illumination | Bettung(Bett) | Platform(RR G); base (Fixed G); foundation |
| Belgien | Belgium | Bettungsgeschütz | Platform gun |
| Belüftung | Ventilation | Beute | Booty; captured materiel; loot |
| Benzin | Gasoline | Beutegeschütz | Captured gun |
| Benzol | Benzene | Beutel | Bag; pouch |
| Beobachtungsmine | Observation mine | | |
| Beobachtungspatrone(BPatr) | Cartridge with a smoke producing projectile used for adjustment fire | | |
| Benplattung(des Zünders) | Fuze cap | | |
| Berg | Mountain | | |
| Bergart; Bergbau(Bgb) | Mining | | |

| | | | |
|--|--|--------------------------------------|--|
| Beuteltartusche | Propellant charge in a bag | Bodenkammer der Granate | Base chamber; rear burster of a projectile |
| Bewaffnung | Armament; equipment | Bodenkammerladung | Base charge (Ammo) |
| beweglich | mobile; movable; flexible | Bodenkammerschrapnell | Shrapnel with rear burster |
| bewegliches Geschütz | Flexible gun | Bodenkanzel | Ball turret; ventral turret (Ap) |
| bewegliche Scheibe | Moving target | Bodenkappe | Base cap; bottom plate |
| bewegliches Maschinen- gewehr | Mobile (flexible) ma- chine gun | Bodenkrepierer | Dud |
| Beweglichkeit | Mobility; maneuverability | Bodenlafette (Bola) | Ventral gun mount (Ap) |
| Bewegungskrieg | Mobile warfare | Bodenplatte | Base plate (Mor) |
| Bewetterung | Ventilation (Mining) | Bodenrand | Flange; rim |
| Bezirk (Bez) | District | Bodenteisser (der Hülse) | Split base; ruptured base (of a case) |
| beziehungsweise (bzw) | respectively; or | Bodenrang (der Patronen- hülse) | Rim (of a case) |
| Bezug | Datum; reference; relation | Bodenschwanz | Tail (of a bomb); breech end; breech ring (G); butt assembly (MG) |
| bezüglich | referring to; with reference to | Bodenstütze | Outrigger support (G) |
| bild | Image; figure | Bodenziel | Ground target |
| bildsam | plastic; flexible; ductile | Bodenzünder (BdZ) | Base detonating fuze (BDFz) |
| Bildungswärme | Heat of formation | Bogen | Bow; arc; bend; curve |
| Hindemittel | Binding agent or material; adhesive | Bogenschuss | Curved fire; high-angle fire |
| Binitrotoluol | Dinitrotoluene | Bogenspitze | Ogive (Ammo) |
| Biwak | Bivouac | Bohrgeschoss | APHE projectile (HE charge exploded after the armor or concrete was pierced) |
| blank | bright; clear; smooth; blank | Bohrladung | Borehole blasting charge |
| blanke Waffen | Hand weapons; armes blanches | Bohrloch; Minenrohr | Borehole |
| Blasangriff | Cloud attack; cloud gas attack | Bohrpatrone | Blasting cartridge; prepared charge; demolition charge |
| blasenziehender Kampfstoff | Vesicant agent (CWS) | Bohrpatrone 88 (BhrPatr 88) | Demolition cartridge type 1888 (containing picric acid) |
| Blatt | Leaf; blade; sheet | Bohrpatrone 02 (BhrPatr 02) | Demolition cartridge, type 1902 (containing 75g of TNT) |
| Blättchen | Lamina; leaflet; flake; lamella | Bohrpatrone 28 (BhrPatr 28) | Demolition cartridge, type 1928 (containing 100g of TNT) |
| Blättchenpulver (BIP) | Rectangular flake propellant | Bohrung | Bore; caliber |
| Blaukreuz (Bik) | Blue cross (sternutators) (CWS) | Bolzen | Bolt; peg; striker; firing pin; crossbow bolt |
| Blaupause | Blueprint | Bolzenblech | Washer; rosette (Arty) |
| Blausäure | Hydrocyanic acid (HCN) (CWS) | Bolzenbüchse | Compressed air gun |
| Blech | Sheet metal | Bombard | Great gun; bombard |
| Blechbüchse | Sheet metal container; tin can | Bombardierung; Bombarde- ment | Bombing; bombardment |
| Blei | Lead | Bombe | Bomb |
| bleichen | to bleach; whiten | Bombe in Felder einge- teilt | Segment bomb; fragmentation bomb |
| Bleidraht | Lead wire (used for decoppering gun tube) | Bomb mit Verzugszeit | Time bomb |
| Bleigeschoss | Lead bullet | Bombenabwurf; Bombenaus- lösung | Bomb release |
| Bleimantelgeschoss | Lead-jacketed bullet | Bombenbündelträger | Bomb cluster carrier; cluster adapter |
| Blendbombe | Dazzle bomb | Bombenfallkurve; Bomben- flugbahn | Bomb trajectory |
| Blende | Gun mantlet; gun shield | Bombenkopf | Bomb nose |
| Blendkörper (BK 1) | Frangible glass smoke grenade; glass bottle grenade | Bombenlast | Bomb load |
| Blendungsschiessen | Smoke-screening fire (Arty) | Bombenschacht | Bomb rack |
| blind | blind; dull; inert | Bombensplitter | Bomb fragment |
| Blindgänger; Bodenkrepier | Dud | Bombentorpedo | Torpedo bomb |
| blindgeladen | loaded with blank ammunition | Bombenträger; Bomber tal- gen | Bomb carrier; bomb rack |
| blindgeladene Granate | Blank shell | Bombenvisier; Bombenziel- gerät | Bomb sight |
| Blinkgerät; Blinklampe | Signal lamp | | |
| Blitzkrieg | Blitz war; lightning war | | |
| Blitzlichtbombe; Blitzlicht- cylindrische Bombe (BLC) | Photoflash bomb; photographic flash bomb, cylindrical | | |
| Blitzschutz | Lightning protection | | |
| Blockverschluss | Block action; block-lock | | |
| Boden | Ground; earth; base; container for bombs (such as described in TM 9-1985-2, p 117) | | |
| Bodenabstandszünder | Base delay-action fuze | | |
| Bodenabwehr | Ground defense; AA defense | | |
| Bodenanlage | Ground installation | | |
| Bodenaufschlagzünder (BdAZ) | Base percussion fuze | | |

| | | | |
|---|---|---|--|
| Bombenzünder | Bomb fuze | Brennschluss | End of burning |
| Boat | Boat; hull(of a flying boat) | | |
| Bürdelung | Crimp; crimping | | |
| Bordkanone(BK) | Gun on ship or airplane | Note: According to W. Dornberger, V-2, Viking Press, N Y (1954), pp 9-14 the above word is used in liquid rockets to signify the moment of disappearance of the flame issuing from the tail of a rocket. The English term "all burnt" is not correct, because at Brennschluss considerable quantities of fuel may still be left in the tanks. | |
| Bordlafette(BL) | Gun mount on ship or airplane | | |
| Bordland Fackel, weiss | Beach flare, white | | |
| Bor.Ammunition | Aircraft ammunition | | |
| Bordwaffen | Aircraft armament; tank armament | | |
| Borsäure | Boric acid | Brennstoff | Fuel; gasoline; Diesel fuel; combustible |
| Böschungswinkel | Angle of slope | Brennzünder(BZ) | Powder-train fuze (Sh); time fuze(HdGr) (lit Burning fuze) |
| Bouteille, Flasche | Bottle | | Friction type igniter (4½ seconds) |
| Boxe | Submarine pen | Brennzünder 24 | Pyro- |
| Brand(Br) | Fire; incendiary; gangrene | | Pyrocatechol |
| Brandbombe(BrB) | Incendiary (Inc) bomb | | Pyrotartaric acid |
| Brandbombenbündel | Cluster of incendiary bombs | | Pressure-board land mine |
| Brandflasche(such as ½ and ¼ liter) | Frangible incendiary grenade; glass bottle incendiary grenade; "Molotov Cocktail" | Brenz- | High explosive; disruptive (brisant) explosive |
| | | Brenzcatechin | Shattering power; brisance |
| Brandgeschoss(BrG) | Incendiary bullet; incendiary projectile | Brenzweinsäure | High explosive(HE)shell |
| Brandgranate(BrGr) | Incendiary shell | Brettstückmine | HE ammunition |
| Brandgranate mit Leuchtspur (Brgr mL'spur) | Incendiary shell with tracer | brisanter Sprengstoff; | HE shrapnel |
| Brandgranate ohne Leuchtspur (Brgr ol'spur) | Incendiary shell without tracer | Brisanzsprengstoff | HE; brisant powder |
| Brandkerngeschoss | Incendiary bullet | Brisanz | |
| Brandkuchen | Incendiary composition | Brisanzgranate | |
| Brandloch | Vent; flash hole; flame passage | Brisanzmunition | |
| Brandmittel; Brandstoff | Incendiary Agent | Brisanzschrapnell | |
| Brandmunition | Incendiary ammunition | Brisanzsprengstoff; | |
| Brandpanzergranate(Brpzgr) | AP Inc projectile | Brisanzpulver | |
| Brandpfeil | Incendiary arrow | Brombenzylcyanid | Brombenzylcyanide(CWS) |
| Brandsatz-Brandzeug | Incendiary composition; incendiary filling | Bromzyan | Cyanogen bromide(CWS) |
| Brandsprenggranate(Brsprgr) | HE-Inc projectile | Bruch | Fracture; rupture; crash (of a plane) |
| Brandstab | Incendiary rod (used for destruction of documents, etc) | Bruchlandung | Crash landing |
| brandwirkend | incendiary | Bruchprobe | Breaking test |
| Braunark | Liquid used in recoil mechanism | Bruchstück; Splitter | Fragment |
| Braunkohle | Lignite; brown coal | Brücke | Bridge; platform |
| Bräunierung | Burnishing; browning | Brückenglühzünder | Electric(bridge-)wire of blasting cap (lit Incandescent bridge-wire igniter) |
| Braunstein | Manganese dioxide(lit Brown stone) | | bridge-wire igniter; electric blasting cap |
| Braunpulver | Brown powder | Brückenzünder | |
| Brause | Effervescence; shower | Brumbär | Grizzly Bear (SP weapon) (See under Panzer in descriptive part) |
| Brechung | Breaking; refraction | | |
| Breite | Width | Bruno N Kanone | 280 mm Railway Gun (See under Weapons) |
| Breitenfeuer | Sweeping fire | Brustschild | Breast shield (G); chest protector |
| Breitenstreuung | See Querstreuung | Brustwehr | Breastwork; parapet |
| Bremse | Brake; buffer(also Rohrbremse) | Bruttogewicht | Gross weight |
| Bremsrohr | Brake tube | B-Stoff | Bromaceton(CWS) |
| brennbar | combustible; burnable | Buchse(Bu) | Bushing; jack; socket(Rad) |
| Brenndauer | Duration of burning; burning time(Fz, etc) | Büchse(Bü) | Shotgun; canister; tin can; rifle |
| Brenngemisch | Liquid combustion mixture, such as gasoline | Büchsenhandgranate 42(*) | Norwegian,box type,hand-grenade 42 |
| Brenngeschwindigkeit | Burning rate(Fz, etc) | Büchsenkonserven | Canned food; canned ration |
| | | Büchsenpulver | Rifle propellant |
| | | Bug | Bow; front; nose |
| | | Bügel | Trigger guard |
| | | Buggeschütz | Bow gun; front gun |

| | | | |
|---|---|----------------------------|---|
| Diglykolnitratpulver(Dig F) | DEGDN propellant | Drilling | Three-barreled hunting gun, usually with two smooth bore and one rifled barrels |
| Diphenylchlorarsin | See Chlorarsinkampfstoff | Druck | Pressure; compression; print |
| Diphenylcyanarsin | Diphenylarsine Cyanide, called also Cyanchlorarsinkampfstoff | Druckbolzen | Buffer bolt |
| Diskushandgranate | Hand grenade in the form of a disk | Druckfestigkeit | Compressive strength |
| Dobgerät | Launcher for firing simultaneously up to 65 rockets, such as Taifun(TM 9-1985-3, p 223) | Druckknopflünder 42 | Pushbutton rocket igniter or snap igniter, pattern 42 |
| Docht | Wick | Druckkugel | Land mine operated by pressure |
| Do-Gerät 38 | Launcher for 150 mm rockets (15 cm Wurfkörper 41 Spreng and Wurfgranate 41Nb) | Druckwelle | Pressure wave |
| Dolch | Dagger | Druckzylinder 35(DZ 35) | Pressure fuze; pressure igniter; push igniter, type 35 |
| Donaritpatrone 100 g | Demolition cartridge with 100g of Donarite | D-Stoff | Dimethylsulfate(CWS) |
| Doppelbüchse | Double-barreled rifle | Dumdum Geschoss(DdG) | Dumdum bullet |
| Doppellafette | Two-barreled mount | Dunkelkammer | Darkroom |
| doppelläufig | double-barreled | dünn | thin; dilute; slender |
| Doppelzünder(Dopp Z) | Time and percussion fuze (lit Double action fuze); combination fuze | Dunst | Vapor; haze; smoke; fine shot; small shot; 'dunst shot' |
| Note: Fuze which contains a powder-train ignition element is called Pulverbrennzünder | | durchbrechen | to break through; pierce |
| Dora (Kanone) | Same as Sevastopol Gun, called also Gustav Geschütz | durchbrennen | to burn out |
| Draht(D) | Wire | Durchbruchkampfwagen | Land cruiser (lit Breaking through combat car) |
| Drahtnetz | Wire net; wire mesh | Durchdringung | Penetration |
| Drahtrohr | Wire-wound gun barrel | durchladen | to load(a magazine or belt) |
| Drahtschere | Wire cutters | Durchmesser (/) | Diameter |
| Drahtzange | Pliers(for handling wire) | Durchschiesen; Durchschuss | Perforation |
| Drall | Rifling twist (in a gun); spin (of a projectile); pitch of rifling (Uniform twist) | Durchschlag | Penetration; filter; screen; punch; carbon copy |
| (gleichbleibender Drall) | (Increasing twist; progressive rifling) | Durchschlagkraft | Force of penetration; |
| (zunehmender Drall) | Drift (due to spin of projectile) | Durchschnitt | perforating power |
| Drallabweichung; Seitenabweichung | Length of twist(rifling) | Durchschnittpanzerstärke | Average; mean; cross section |
| Dralllänge | Angle of rifling; pitch of rifling | Durchstrückung | Average thickness of armor |
| Drallwinkel | Grooves(Rifling) | Düse (Dü) | Saturation; impregnation |
| Drallzüge | Throng; pressure; impulse | Düsenjäger | Injector; jet; nozzle; vent (Rocket) |
| Drang | Rotary; rotating | Düsenrohr | Jet-fighter plane |
| Dreh- | Lathe | Düsenwaffe(DuW) | Blast pipe |
| Drehbank | Revolving copola | Dynamitgeschütz | Jet-propelled projectile, such as Panzerfaust (lit Vent weapon) |
| Drehkuppel | Gun carriage on turntable | | Pneumatic gun shooting projectiles filled with dyanmite |
| Drehscheibenlafette | Revolving turret | | |
| Drehturm | Revolving breech mechanism | | |
| Drehverschluss | Number of revolutions per minute (rpm) | E-100(Panzer) | One of the heavy tanks (See under Panzer) |
| Drehzahl | Tachometer | Ecke | Corner; angle |
| Drehzahlmesser | Triaxial mount (G) | Ei (pl Eier) | Egg |
| Dreischlafette | Tripod | eichen | to calibrate |
| Dreibein; Dreifuss | Tripod gun mount | Eichung | Calibration; adjustment |
| Dreibeinlafette | Triple mixture (gasoline 50, benzene 40 and alcohol 10%) | Eierhandgranate | Egg-shaped hand grenade; |
| Dreiergemisch | Triple-action fuze; combination fuze (superquick, delay and time) | Einabzug | single hand grenade |
| Dreifachzünder | Tripod gun mount | Einäscherung | Single trigger |
| Dreifuslafette | | Einbau | Incineration; complete combustion |
| | | Einbruchfeuer | Mounting; installation |
| | | Eindämpfung | Assault fire |
| | | | Evaporation |

E

| | | | |
|--|---|--|---|
| Eindecker | Monoplane | Eisenbahngeschütz | Railroad gun |
| Eindrehung | Slot; groove | Eisenbahnhautbitze | Railroad howitzer |
| Eindrehung der Patronenhülse | Neck of the cartridge case | Eisenbahnlafette | Railroad mounting(G) |
| eindringen | to penetrate; press in; infiltrate | Eisenbahnpanzerzug | Armored railroad train |
| Eindruck | Impression | Eisenbahnschiene | Rail |
| einfach | simple | Eisenbetonbau | Reinforced concrete construction |
| Einfallwinkel | Angle of impact | Eisenblech | Sheet iron |
| Einfeuer | Single shot fire | Eisenwalze | Iron roller (in clearing of mines) |
| Einflussrohr | Inlet pipe | Eismine(EisM; F.sMi) | A/P bottle mine (lit Ice mine) |
| einführen | to adopt; introduce | (See also Flascheneismine) | |
| Eingang | Entrance; introduction | Eiweiss | White of egg; albumin |
| Eingangszündung | Priming charge | Elektron | Electron (trade name for Al-Mg alloy) |
| Eingießung | Pouring in | Elefant | "Elephant" tank destroyer (See under Panzer in descriptive part) |
| Einheit | Unit; unity | empfindlich | sensitive |
| Einheitsgeschoss | Standard projectile; combined shell | empfindlicher Aufschlagzünder(EAZ) | Superquick impact fuze |
| Einheitsgeschütz | Universal piece; dual-purpose gun | empfindlicher Koptzünder(EKZ) | Sensitive type of PD Fz; all ways fuze |
| Einheitsgewicht | Specific gravity | empfindlicher Zünder(EZ) | Superquick fuze; high-sensitivity fuze (See also Schuellzünder) |
| Einheitsgranate | Combination HE and shrapnel shell | Empfindlichkeit | Sensitiveness; sensitivity |
| Einheitsmunition | Fixed ammunition | Enddrall | Terminal twist of rifling |
| Einheitspatrone | Standard cartridge | Enddruck | Final pressure |
| Einheitspulver(EP) | Standard propellant (See descriptive section) | Ende | End; limit; termination |
| Einheitswaffe | Dual-purpose weapon | Endgeschwindigkeit; | Terminal velocity; remaining velocity |
| Einheitszünder | Standard fuze; combination fuze | Restgeschwindigkeit | Remaining energy |
| Einlage | Insert | Endwucht | Narrowness; closeness |
| Einlagerung | Storage | Enge | Duck gun |
| Einlaufgewehr | Single barrel gun | Ententflinte | Range; distance (See also Schussweite) |
| Einlegerohr | Subcaliber tube; liner | Entfernung(E) | Range finder; range indicator |
| Einpressen des Geschosses in die Züge | Forcement of a projectile into rifling; engraving | Entfernungsgesetz; Entfernungsmesser; Entfernungsmessgerät | Desiccator |
| einrasten | to engage; ram home; lock to adjust (fire, etc) | Entfeuchter | Inflammation; flash |
| einrichten | Installation; establishment | Entflammung | Flash test |
| Einrichtung | Installation; establishment | Entflammungsprobe | Detoxication; decontamination(CWS) |
| Einsäuerung | Acidification | Entgiftung | to decopper |
| Einschiessen | Adjustment fire; trial fire; target(range) finding | entkupfern | Decoppering agent (such as Pb wire) |
| Einschiessgeschoss (See also Anschliesspatrone and Anwärmschuss) | Range finding bullet; projectile used for adjustment fire; round to locate target; "warmer" | Entkupferungsmittel | to relieve (of pressure) |
| Einschießziel | Adjustment target | entlasten | Antilifting igniter (with HE charge) |
| Einschiffung | Embarkation | Entlastungszünder(EZ) | to ventilate; to bleed recoil mechanism |
| Einschlag | Impact; strike | entlüften | Unlocking |
| Einschnitt | Notch; cut | Entriegelung | to unprime (Fz) |
| Einschuss | Hit | entschürfern(Zünder) | to disengage or release the safety device (Wp); to arm or to activate (Mi or B) |
| einsetzen | to commit; insert | entsichern | Arming vane(B) |
| Einspritzdüse | Injection nozzle | Entsicherungsflügel | to uncock; to relieve tension; to let the firing pin down to disarm |
| Einstecklauf; Einsteckrohr | Subcaliber tube; insert barrel; adapter | entspannen | to free from water; dehydrate |
| Einsteckmagazin | Detachable magazine | entwässern | Drainage ditch |
| einstellen | to adjust or set (Fz, etc); cease fire; tune in(Rad) | Entwässerungsgraben | to ignite |
| Einstellung; Stellung | Adjusting ring(Fz) | entsüden | Flammability |
| Eintauchrefraktometer | Immersion refractometer | Entzündlichkeit | Ignition (inflammation) |
| einvisieren | to sight in | Entzündungstemperatur | temperature |
| Einzellademagazin | Single-loading magazine (for repeating fire) | | |
| Einzellader | Single-loader; single shot weapon | | |
| Einzelschuss | Single shot; single round | | |
| Einzelschussfeuer | Single shot fire (in contrast to bursts) | | |
| Einzelsternpatrone | Single star cartridge | | |
| Eis | Ice | | |
| Eisenbahn(E) | Railroad(RR); railway | | |

| | | | |
|--------------------------------|--|-----------------------------------|--|
| Erdartillerie | Artillery used against ground targets (as distinguished from AA Arty) | Exsudat | Exudate; exudation |
| Erdbebenbombe | Earthquake bomb | | |
| Erde | Earth; soil; ground (electrical) | F | |
| Erdmine; Landmine | Land mine | Fabrik | Factory; works |
| Erdöl | Petroleum | Fach | Branch; department; trade; branch of knowledge |
| Erdziel | Ground target | Fackel | Flare; torch |
| Erforschung | Investigation; research | Faden | Thread; filament; string |
| Ergänzung | Completion; supplement; replacement(s); reserve(s) | Fadenpulver | String propellant |
| Ergebnis | Result; yield; score | fahrbar | passable; transportable; portable |
| Erhitzung | Heating | Fahrer | Driver (of a car) |
| Erhöhung | Quadrant elevation(Guny) | Fahrgestell(Fg; Fgst) | Chassis |
| Erkennung | Detection; recognition | Fahrrad | Bicycle |
| Erklärung | Explanation; declaration | Fahrzeug | Vehicle; craft |
| Ermüdungskampfstoff | Harassing agent(CWS) | Fallblockverschluss | Drop hammer |
| Ermüdungsschiessen | Harassing fire; gas-shell fire | Fallhöhe | Height of drop |
| Ersatz(Er)(See also | Proving ground; place for testing weapons | Fallkessel | Precipitating vessel |
| Surrogat) | Substitute; replacement; synthetic material; spare part | Fallprobe | Drop test; impact test |
| Ersatzsprengstoffe(ErS) | Substitute explosive | Fallschirm(FS) | Parachute |
| Ersatzstück(Erst) | Spare part; inert piece resembling in appearance a fuze found in front section of some projectiles | Fallschirmbombe(FB) | Parachute bomb |
| | Substitute part; spare part | Fallschirmgewehr(FGw) | Parachutist's automatic rifle |
| Ersatzteil | Concussion; shock | Fallschirmjägergewehr-42 (KFG-42) | Paratroop fully automatic rifle |
| Erschütterung | Solidification; congelation | Fallschirmleuchtkugel; | Parachute flare |
| Erstarrung | Asphixiating gas; lung irritant(CWS) | Fallschirmleuchtbombe | Parachute-flare cartridge for signal pistol |
| erstickender Kampfstoff | Warming; heating | Fallschirmleuchtpatrone | Cartridge with parachute for measuring wind velocity |
| Erwärmung | Softening | Fallschirmrakete | Parachute rocket signal |
| Erweichung | to reply; return | Fallschirmrauchpatrone | Smoke signal cartridge with parachute |
| erwidern | Retaliation fire; counterfire | Fallschirmrauchzeichen | Parachute smoke signal |
| Erwiderungsfeuer | Ore; metal especially bronze | Fallwinkel | Angle of fall |
| Erz | Producer; generator; manufacturer | Fällung | Precipitation |
| Erzeuger | Nickname for 1000 kg. AP bomb, called in Ger "1000 kg SD" | Fallzündler | Percussion fuze (lit drop fuze) |
| Esau | Ash; ash tree | Fangnetz | Antisubmarine net |
| Esche | Forge; hearth; chimney; stack | fangen | to catch; capture |
| Esse | Vinegar | Farbe | Color; dye; pigment |
| Essig | Ethyl acetate | Faschine(Fasch) | Fascine (bundle of sticks for the strengthening of field fortifications) |
| Essigäther | Acetone | | |
| Essiggeist | Acetic acid | Faser | Fiber; filament |
| Essigsäure | Drill(practice)bomb; dummy bomb | Fassnebelzerstäuber | Smoke sprayer (barrel) |
| Exerzierbombe(ExB) | Drill(dummy)projectile | Faust | Fist; grasp |
| Exerziergeschoss(ExG) | Training hike | Faustfeuerwaffe | Hand gun |
| Exerziermarsch | Drill(dummy)ammunition | Faustpatrone | Fist Cartridge; HoC rocket (See description) |
| Exerziermunition(ExMun) | Drill(dummy)cartridge | | |
| Exerzierpatrone(ExPatr) | Expanding bullet; hollow point bullet | F-Boot | Tank landing craft |
| Expansionsgeschoss | explosive; explodable | Feder | Feather; pen; spring |
| explodierbar; explosibel | to explode | Federantrieb | Spring action (clockwork fuze) |
| explodieren | Explosibility | Federkapsel | Cap over a spring |
| Explosibilität | Explosion pressure | Federkraft | Elasticity |
| Explosionsdruck | Explosibility | Fehler | Error; defect; miss |
| Explosionsfähigkeit | HE projectile | feinkörniges Pulver | Fine-grained propellant |
| Explosionsgeschoss | Explosive force or power | Feld | Field; land(rifling); ground |
| Explosionskraft; Explosivkraft | Explosive impact | Feldbahn(Feba) | Field railroad(narrow-gage) |
| Explosionsstoss | Explosion temperature | Feldgeschütz(FGesch) | Field piece; field gun |
| Explosionstemperatur | Heat of explosion | Felder | Lands(Ord) |
| Explosionswärme | Explosion wave; shock wave | Felder und Züge | Lands and grooves(Ord) |
| Explosionswelle | Explosive bullet | Feldhaubitze(FH) | Field howitzer |
| Explosivgeschoss | Explosive; explosive substance | Feldkanone(FK) | Field cannon |
| Explosivstoff | | | |

| | | | |
|---|--|-------------------------------|---|
| Feldpatrone(FPatr) | Field gun cartridge(Fix Ammo) | Feuerwerkskörper | Pyrotechnic composition |
| Feldpolizei(Fepo) | Field police | Filterbüchse | Gas mask |
| Feldscher | Army medic | Filz | Felt |
| Feldweibel(Fldw) | Staff sergeant (except in Arty & Cav) | Filzpropfen | Felt wad |
| Feldneuglager | Ordnance depot | Fia(Flugabwehr) | Antiaircraft |
| Ferdinand | SP mount(See under Panzer) | Flachbahn | Flat trajectory |
| fern | far; distant | Fläche | Surface; flatness |
| Ferngeschoss(FGesch) | Long-range projectile | Flachfeuer | Flat trajectory fire |
| Ferngeschütz; Fernkampfgeschütz(FKG) | Long-range gun | Flachfeuergeschütz | Flat trajectory gun |
| Ferngesteuertes Geschoss | Guided missile | Flachkopfgeschoss | Flat-nosed bullet |
| Fernladung | Long-range propellant charge | flackern | to flare; flicker |
| Fernrohr | Telescope | Fladdermine | Contact land mine |
| Fernsehen(Fesh) | Television | Flaggschiff | Flagship |
| Fernsprecher(Fsp) | Telephone | Flak(Flugabwehrkanone) | AA cannon |
| Fernsteuer Gerät | Remote control guidance for winged missiles, such as V-1 | Flakmaschinen-gewehr | AA machine gun |
| Feinststeuerung | Remote control; guidance | Flakpanzer | Special armored vehicle with full armor cover; used as AA weapon(See also under Panzer) |
| Fertigung | Making ready; manufacture | Flakvierling | Four-barreled AA gun |
| Fertigungsjahr | Year of manufacture | Flammendämpfer | See Feuerdämpfer |
| Fertig; nder | Ready-fixed fuze | Flammenstrahl | See Feuerstrahl |
| Fesselballon(FessB) | Captive balloon; sausage balloon | Flammenwerfer(FmW) | Flame-thrower(See also Nahwerfer and Weitwerfer) |
| fest eingebautes Maschinengewehr | Fixed machine gun | Flammenwerferpanzerwagen | Flame-throwing tank |
| Festigkeit | Strength; resistance; solidity | Flansch | Flange |
| Festlegungspunkt | Reference point | Flanschgeschoss | Flange projectile(See description) |
| feststellen | to establish; ascertain; fix | Flaschensmine(FIEsMi) | Bottle-shaped mine placed under ice |
| Festung(Fest) | Fortress; fort | Flats(Flammenwerfertank) | Flame-thrower tank |
| Festungsartillerie | Fortress artillery | Flattermine | Tumbling mine |
| Festungsflak(FF) | Fortress AA gun | Fla-Waffe | AA weapon |
| Festungsgeschütz | Fortress gun | Flieger | Pilot in Air Corps personnel |
| Festungsgraben | Moat | Fliegerabwehr | AA defense |
| Festungskrieg | Siege warfare | Fliegerbombe | Airplane bomb |
| fett | fatty; oily | Fliegerdiebstütze(FIDSt) | Meaning unknown to us |
| feucht | moist; humid | Fliegerleitpanzer | Armored observation car used with front line support aircraft(See also under Panzer) |
| Feuchter | Humidifier | Fliegerleuchtpistole | Aircraft signal pistol |
| Feuchtigkeitgehalt | Moisture content | Fliehbacke | Centrifugal arming device(Fz) |
| Feuer | Fire | Fliehbackenfeder | Spring of centrifugal arming device(Fz) |
| Feuerbereich | Fire zone; range | Fliehbolzen | Centrifugal safety pin(Fz); disappearing firing pin |
| feuerbeständig | fireproof | Fliehkraft | Centrifugal force |
| Feuerdämpfer; Flamme-dämpfer; Mündungsfuehdämpfer | Flash hider; flash damper | Fliegsdeckel(Dichtungsdeckel) | A cardboard disk impregnated with ozokerite, placed between propellant and shell to prevent the escape of gases (obturation) and to lubricate the gun barrel. The device was used during WW I by the Austrians. |
| feuerfest; feuersicher | fireproof | Flinte | Shotgun |
| feuergefährlich | inflammable, liable to catch fire | Flotte | Fleet; Navy; dye liquor |
| Feuergewicht | Weight of gun in action | Flug | Flight; flying |
| Feuerhöhe | Height of muzzle | Flugabwehr(Fla) | AA defense |
| Feueriger Schwaden | Firedamp(coal mine) | Flugabwehrkanone(Flak) | AA gun |
| Feuerkraft | Firepower | Flugbahn | Trajectory |
| Feuerkunst; Feuerwerk; Feuerwerkerei; Pyrotechnik | Pyrotechnics, fireworks; pyrotechny | Flugblatt | Propaganda leaflet |
| Feuerleitgerät | Fire control instrument | Flügel(Fl) | Stabilizing vane or fin; wing |
| Feuerleitung | Fire control | Flügeldüse(FIDü) | Jet motor mounted on a wing |
| Feuerlöcher | Fire extinguisher | Flügelgranate | Fin-stabilized shell |
| Feuerlöschmittel | Fire extinguishing substance | Flügelmine | Fin-stabilized mortar shell |
| Feuerrohr | Firearm; fire tube; flue | | |
| Feuerschiff | Lightship | | |
| feuersicher | See feuerfest | | |
| Feuerstoss | Burst | | |
| Feuerstrahl; Flammenstrahl | Jet of liquid fire | | |
| Feuerverteilung(Fvtg) | Fire distribution(Arty) | | |
| Feuerwaffe | Firearm; gun | | |
| Feuerwehr | Fire department | | |
| Feuerwerk; Feuerwerkerei | See Feuerkunst | | |
| Feuerwerker | Ordnance noncommissioned officer; pyrotechnist | | |

| | | | |
|---------------------------------|---|--------------------------------|---|
| flügelstabilisiertes Geschoss | Fin-stabilized projectile | Funkturm(FuTu) | Radio tower |
| Flugzeit | Time of flight | Funktionsprobe | Functioning test |
| Flugzeitmesser | Chronograph(Le Boulengé, etc) | Funkwelle | Radio wave |
| Flugzeug(Flzg); Luftfahrzeug | Airplane; aircraft | Furier | Quartermaster sergeant |
| Flugzeugabwehrkanone | See Flugabwehrkanone(Flak) | Füsillier | Rifleman; infantry private |
| Flugzeuggeschütz; | Aircraft (AC)gun | Fussmörser | Plate-base mortar |
| Flugzeugkanone | | Fussplate | Foot plate; float(AA G) |
| Fluss | River | Futter | Forage; fodder; lining |
| flüssige Luft | Liquid air | Futteral | Case; scabbard; sheath |
| Flüssigkeitsbremse | Hydraulic brake | Futterlauf | Liner(of a gun) |
| Flüssigkeitsrücklaufbremse | Hydraulic recoil brake | Futterrohr | Lining tube; inner liner(G) |
| Flüssigkeitszünder | Liquid escape fuze; hydraulic fuze | Futterstück | Bushing(breechblock) |
| Flüssigluft Sprengstoff | Liquid air explosive | | |
| Flusskabel | Marine cable; underwater cable | | |
| Flussstreibmine(FITrMi) | Drifting mine | | |
| Föhn Gerät | 73 mm Rocket Launcher(See under Weapons) | Gabel | Bracket; fork |
| | Deformation | Gabellafette | Gun carriage with shafts |
| Formänderung | Plasticity | Gabelstütze | Bipod |
| Formbarkeit | Propulsion; movement | Gallert | Jelly; gelatin; glue |
| Fortbewegung | Velocity of propagation; - of transmission; or - of detonation | Gamma(Mürser) | 420 mm Howitzer(See under Weapons) |
| Fortpflanzungsgeschwindigkeit | Freight | | Motion; action; passage(Mining) |
| Fracht | Milling; cutter; reamer | Gang | Capstan |
| Fräser | See Guerillakämpfer | Gangspill | Cone of dispersion(Guny) |
| Freischarler, Partisane | Hooping; shrinkage | Garbe | Gas defence |
| Frettage | Freezing point | Gasabwehr | Gas bomb |
| Frierpunkt | Apparatus for measuring friction | Gasbombe | Gas bomb |
| Friktionsmesser | Friction igniter; friction priming screw | Gasbrisanzgeschoss; | High explosive chemical shell |
| Friktionszündschraube | Fritting; sintering | Gasbrisanzgranate | Gas pressure; blowback |
| | Nickname for 1400 kg AP Bomb, called in Ger "1400 kg SD" (TM9-1985-2, p 25) | Gasdruck | Pressure bomb |
| Frittung | Premature burst(Arty) | Gasdruckbombe | Pressure gage; crusher gage |
| Fritz | Premature ignition; pre-ignition(MG) | Gasdruckgerät; Gasdruckmesser | (See also Messei) |
| | Titanium tetrachloride(smoke agent) (CWS) | Gasdruckhülse(GDrH) | High-pressure cartridge |
| Frühzerspringer | Fougasse(See general section) | Gasdruckklader; Gaskolbenlader | Blowback-operated(automatic) weapon; gas operated gun |
| Frühzündung | Rotating band; driving band | Gas-Erdmine | Chemical land mine |
| F-Stoff | Bourellet(See also Zentrierwulst) | Gasgeschoss | Chemical projectile; gas shell |
| | Filling hole(Ref 6, p 57) | Gasgewehrgranate | Chemical rifle grenade |
| Fugasse | Filling material; loading material | Gasgranate(Ggr) | Chemical shell |
| Führungsband; Führungsring | Charging hole (Arty) | Gashandwerfer | Chemical hand grenade |
| Führungs wulst | HE filler(lit Filling powder) | Gaskampf; Gaskrieg | Chemical warfare |
| Füllloch | Installation for filling projectiles | Gasmörser | Chemical mortar |
| Füllmaterial; Füllmittel | See Füllmaterial | Gasmunition | Chemical munitions |
| Füllöffnung | Filling funnel | Gasteer | Gas-tar |
| Füllpulver(Fp) | Filling; filler | Gaswerfer | Chemical(gas)projector |
| Füllstelle | Base-plate; foundation-plate | geballte Ladung(GebLdg) | Concentrated charge(consisting of several explosive blocks tied together) |
| Füllstoff | Radio | geballte Ladung 3 kg | Demolition block containing 3 kg TNT |
| Fülltrichter | Spark; sparkle | geballte Ladung 10 kg | Demolition block containing 10 kg HE |
| Füllung | Spark chronograph | Gebirgsartillerie(GebA) | Mountain artillery |
| Fundamentplatte | High-tension priming; spark priming | Gebirgsgeschütz(GebG) | Mountain piece; pack gun |
| Funk(Fu); Funkgerät | Radio operator | Gebirgsgranate | Shell for mountain guns |
| Funke; Funken | Radio controlled light tank for special purposes(See also under Panzer) | Gebirgshaubitze(GebH) | Mountain howitzer |
| Funkenchronograph | Radar | Gebirgsinfanteriegeschütz | Mountain infantry howitzer |
| Funkenzündung | Armored vehicle for troop communication(See also under Panzer) | Gebirgsjäger | Mountain infantryman(See also Jäger) |
| Funker | Radio transmission | | Mountain infantry battalion (shock troops) |
| Funklenkpanzer | Radio station | Gebirgsjäger-Bataillon | Use; custom |
| | Signal corps detachment | Gebrauch | Normal charge; service charge(Ammo) |
| Funkmessgerät(FuMG) | | Gebrauchsladung | |
| Funkpanzer | | | |
| Funksendung | | | |
| Funkstelle(FuSt) | | | |
| Funktrupp(FuTr) | | | |

| | | | |
|---------------------------------|---|---|---|
| Gefäss | Vessel; receptacle | Geschütz | Artillery piece; gun; cannon |
| Gefecht | Fight; fighting; battle (See also Kampf and Krieg) | Geschütz auf Selbstfahrlafette | Self-propelled gun |
| Gefechtskopf | Warhead(Td) | Geschützladung | Gun propelling charge |
| Gefreiter | Private first class | Geschützpulver | Gun propellant |
| Gefrierpunkt | Freezing point | Geschützrohr | Gun barrel(See also Rohr) |
| Gefüge | Structure; texture | Geschützverschluss | Breech mechanism; breechblock |
| Gehalt | Content; concentration(CWS) | Geschwindigkeit | Velocity; speed |
| gehärteter Stahl | Hardened steel | Gesellschaft | Society; company |
| gehärtet('h, 'H) | hardened | Gestalt | Form; shape; figure |
| Gehäuse | Case; casing; housing | Gestapo | See under German Abbreviations |
| Geheime Staatspolizei (Gestapo) | Secret State Police | Gestein | Rock; stone |
| gekrümmte Flugbahn | Curved trajectory | Gesteinssprengmittel; Gesteinssprengstoff | Rock blasting explosive; blasting explosive |
| geladen(gel) | loaded; armed; charged | gesteuert | controlled; steered; synchronized |
| Gelände | Terrain; ground; country | gesteuertes Geschoss | Guided missile |
| Gelatinedynamit | Gelatin dynamite | gesteuertes Maschinengewehr | Synchronized MG |
| Gelbkreuz | Yellow cross (Ger marking for vesicants) (CWS) | gestreckte Flugbahn | Flat trajectory |
| Gelbkreuzgeschoss | Chemical projectile with vesicant filler | gestreckte Ladung | Bangalore torpedo (See also Rohrladung) |
| Gelbkreuzgas | Mustard gas | gestrecktes Eisen | Wrought iron (See also strecken) |
| Gelenk | Joint; knuckle; flexible coupling | Getreidemehl | Cereal meal; grain flour |
| Gelenklafette | Nonrigid gun carriage | getrennte Munition | Separate-loaded ammunition |
| geliefert(gel) | manufactured; provided | Getriebe | See Wechselgetriebe |
| Gemeinde Polizei | Local police; township police | Gewalt | Power; force; violence |
| Gemenge; Gemisch | Mixture | gewalzter Stahl | Rolled steel |
| Gendarm | Rural policeman | Gewebe | Fabric; tissue |
| Generalstab des Heeres (GenStH) | General Staff of the Army | Gewehr(Gew) | Rifle |
| Gepäck | Baggage; luggage | Gewehrblindgranate 42 | See Gewehrnebelgranate 42 |
| gepanzert | armored | Gewehrgeschoss(GewG) | Rifle bullet |
| gepanzerte Kampffahrzeuge | Armored fighting vehicles | Gewehrgranate(GewGr) | Rifle grenade |
| Gerät | Nonexpendable supplies; materiel; ordnance; apparatus; instrument | Gewehrkartusche | Propelling cartridge for rifle grenade |
| Gerblohe | Tanbark; tan liquor | Gewehrmunition | Rifle ammunition |
| Gerbstoff | Tannin | Gewehrnebelgranate 42 | Smoke grenade for rifle 42 |
| gerieft; gerillt | grooved(rifling) | Gewehrpanzergranate(GewPzgr) | Armor-piercing rifle grenade |
| gerilltes Geschoss | Cannelured bullet | Gewehrpatrone(GewPatr) | Rifle cartridge |
| gesamt | total, entire | Gewehrpulver(GewP) | Rifle propellant |
| Gesamtlänge | Over-all length | Gewehrschuss | Rifle shot |
| Geschoss(Gesch; Gs) | Projectile; missile | Gewehrschütze | Rifleman |
| Geschossbahn | Trajectory; ballistic curve | Gewehrsprenggranate(GewSprgr) | HE rifle grenade |
| Geschossboden | Base of projectile | gewerbliche Sprengstoffe | Industrial(commercial) explosives |
| Geschossdrill; Geschossdrehung | Spin of projectile | Gewicht | Weight; gravity |
| Geschossdurchmesser | Diameter of projectile | Gewichtladung(Gldg) | Weight of live projectile |
| Geschossfabrik(Gf) | Projectile factory; shell factory | Gewinde | Thread (of a screw); winding |
| Geschossführung | Seating(forcing)of projectile | gewölbt | convex; arched; vaulted |
| Geschossgewicht(Gg) | Weight of projectile | gezogen(gez) | rifled(barrel); drawn; towed |
| Geschossgeschwindigkeit | Velocity of projectile | gezogener Teil des Laues | Rifled part of barrel |
| Geschosshöhlung | Shell cavity | gezogenes Geschütz | Rifled gun |
| Geschosshülse | Body of projectile; shell | gezogenes Ziel | Towed target |
| Geschosshülse | Cartridge case | Gichtstaub | Blast furnace dust; flue dust |
| Geschosskappe | Cap of projectile | gieren | to yaw (See also Seitwärtsbewegung) |
| Geschosskern | Core of bullet | giessen | Toxic smoke; irritant smoke(CWS) |
| Geschosskopf | Head(point)of projectile | Giftnebel; Giftrauch | Poisonous matter; toxic agent(CWS) |
| Geschossmantel | Jacket of bullet | Giftstoff | |
| Geschossmine(GMi) | Improvised A, T mine made of a HE shell | | |
| Geschoss-spitze; Bogenspitze | Ogive(Proj) | | |
| Geschoss-sprengstoff | Burating charge of projectile | | |
| Geschoss-teile | Projectile components; bullet components | | |
| Geschosszapfen | Rear part of a shell | | |
| geschrumpftes Rohr | Built-up barrel (lit Shrank barrel) | | |

| | | | |
|---|---|------------------------------------|---|
| Gipfelhöhe | Maximum ordinate(Traj) | Granatzünder(GrZ) | Fuze for HE shell |
| Gipfelpunkt | Summit(Traj) | Granulierung | Granulation |
| Gitter | Grating; screen; grid; lattice | graphische Schuss- tafel | Trajectory chart (not to be confused with US graphical firing table) |
| Glasmine | Glass land mine | graphitieren | to graphite; coat with graphite |
| Glätten(des Pulvers) | Glazing(of powders or propellants) | Grat | Edge; ridge; burr; seam; (in bore of a gun) |
| glattes Geschütz(glG) | Smooth-bore gun | Grauguss(Gg) | Cast iron; gray iron casting |
| glattes(poliertes) Pulver | Glazed(polished) powder or propellant | Grauspiessglanz | Antimony trisulfide(Sb ₂ S ₃) |
| glattes Rohr | Smooth-barrel | gravimetrisches Gewicht | Gravimetric density |
| glattwandig | Smooth-bore | Grenadier | Infantry rifleman, private(See also Panzergrenadier) |
| Gleichgewicht | Balance; equilibrium | Grenze(Gr) | Frontier; border; boundary |
| Gleis | Rail; track(RR) | Griff | Grip; handle |
| Gleitbombe | Rail bomb | grobes Blättchen- pulver(grBlP) | Propellant in large flakes |
| Glimmer | Mica | Grobgewicht | Gross weight |
| Glimmsur(Gl's; r) | Tracer with glowing composition; dim tracer | Groß(grosser) Flammen- werfer | Heavy flame thrower(on two- wheel carrier) |
| glühen | to glow | Grossadmiral | Admiral of the Fleet |
| Glühdraht; Glühfaden | Filament | Grosse | Quantity; magnitude; size |
| Glühkathodenrohre | Vacuum tube(kad) | grosse Ladung(grLdg) | Large charge |
| Glühköpfchen | Hot-wire bridge-head (in an electric igniting device) | grosse Zündladung(grZldg) | Large igniter or primer charge |
| Glühlampe | Incandescent lamp | Grossfertigung | Mass production |
| Glühzündapparat (See also Zündmaschine) | Low tension blasting machine; exploder(Engr); electrical ignition apparatus | grosskalibrig | large caliber; big bore |
| Glühzünder(Gluhz) | Low tension electric igniter or detonator | grösste Vo | Muzzle velocity |
| Glühzündkette | Electric detonator chain with delays | Grube | Mine; quarry; hole; pit; ditch |
| Glühzündstück | Low tension electric igniter or detonator | Grubengas; Grubenwetter | Firedamp(explosive mixture of methane and air); mine damp |
| Goliath S. 302 (Goliath Sprengdienst Kraftzug 302) | "Goliath" Demolition Vehicle 302 | Grundgeschütz | Base piece; directing gun |
| Gondel | Gondola; nacelle | Grundladung(Grundldg) | Base charge; main charge(See also Sekundärladung) |
| Goudron | Soft asphalt or mixture of hard asphalt with high-boiling mineral oil | Grundmine | Fixed ground mine; controlled mine(Nav) |
| Graben | Trench; ditch | Grünkreuz(Grkz) | Green cross (Ger marking for lung irritants)(CWS) |
| Grabengeschütz | Trench piece(Arty); trench gun | Gruppenfeuer | Group fire; volley fire |
| Grabenhaubitze | Trench howitzer | Gudulpulver(GuP) | Double-base propellant contg nitroguanidine(NGu) |
| Grabenkrieg | Trench warfare | Guerillakämpfer; | Guerilla (See also Partisane) |
| Grabenmine; Grabenmörser- granate | Trench mortar shell | Freischarfer | Field kitchen (slang) |
| Grabenmörser | Trench mortar | Gulaschkanone | Rubber; gum |
| Grad | Degree; grade; rank | Gummi | Belt; strap; girdle; ammunition belt; feed belt |
| Granatbüchse(GrB) | Grenade launching rifle | Gurt | Belt; strap; band; girdle; zone to load an ammunition belt |
| Granate | Shell; projectile; grenade | Gürtel | Casting |
| Granate Beton(GrBe) | Anticoncrete shell | gurten | Cast iron |
| Granatfüllung(Grf) | Shell filler | Guss | Cast steel; furnace steel |
| Granatfüllung 02 (Grf 02) | Shell filler type 1902(TNT) | Gusseisen | 800 mm Gun(Sevastopol)Sec under Weapons) |
| Granatfüllung 88 (Grf 88) | Shell filler type 1888(Picric acid) | Gussstahl | Freight station(RR) |
| Granathülse | Shell case | Gustav Geschütz; Dora | Freight car(RR) |
| Granatkartätsche | Canister shell | Güterbahnhof | Freight train(RR) |
| Granatloch | Shell hole | Güterwagen | |
| Granatsignal | Projector signal; rocket signal; star shell | Güterzug | |
| Granatsplitter | Shell splinter | | |
| Granattrichter | Shell crater | | |
| Granatwerfer(GrW)(See also Mörser) | Grenade thrower or projector; trench mortar; A/T grenade rifle | | |
| Granatwerfer Fünf- ling(GrW 5ling) | Five-barreled automatic mortar (launcher) | | |
| Granatwerfergeschoss (GrWG) | Mortar shell | | |
| | | haarartig | Hairlike, capillary |
| | | Haften | Port; harbor |

| | | | |
|-------------------------------|--|--|----------------------------|
| Haft | Custody; arrest; bolt; loop; confinement | Hauptkartusche(Hptkart) | Main propelling charge |
| Haft Hohlladung(HaftHll) | Magnetic antitank hollow charge(HoC) (lit Adhering hollow charge) | (See also Kartusche and Teilkartusche) | in non-fixed ammo |
| Haft Hohlladung 500g | Magnetic HoC of 500g RDX | Hauptladung | Main charge of propellant; |
| Haft Hohlladung 3kg | Magnetic HoC of 3kg RDX | | base charge of blasting |
| Hahn | Hammer; cock; stopcock (lit rooster) | Hauptmann(Hpt) | cap or detonator |
| Hahnflinte | Hammer shotgun | Hauptwache | Captain |
| Hahngewehr | Hammer rifle | Hauptzündung | Main ignition |
| hahnlos | hammerless | hautätzend | lead-in(BI) |
| hahnloses Gewehr | hammerless rifle | Hautgift | vesicant(CWS) |
| Haken | Hook; clasp; clamp; catch | Hebel | Blister agent; |
| Hakenbüchse | Arquebus | Hebelzünder | vesicant(CWS) |
| Halbautomat | Semi-automatic weapon | Heer(H) | Lever |
| Halbdurchmesser | Radius; semidiameter | | Lever type igniter |
| Halbkugel | Hemisphere | | (for Glass mine) |
| Halbpanzergrenate(Halbpzgr) | SAP projectile | Heeresanstalt | Army (the Army, as |
| Hals | Neck; throat; stem(of a thermometer) | Heeresartillerie | distinguished from Armee, |
| haltbar | stable; durable; lasting | Heeresfahrzeug(Hf) | a tactical unit) |
| Haltbarkeit; Beständig | Stability(See also Lagerbeständigkeit) | Heeresflak(HFlak) | Army establishment |
| Haltering(HRg) | Retaining ring | Heeresfunkstelle(HFu) | Army artillery |
| Halteschraube | Retaining screw(Fz) | Heereshauptquartier | Army vehicle |
| Haltestift | Retaining pin | | Army AA Army |
| Haltezeichen | Stop signal | | Army radio station |
| hammerbar | malleable | | Army general |
| Hammer Eisen | Wrought iron | | headquarters(GHQ) |
| Handbremse | Hand brake; emergency brake | Heereslazarett | Army general hospital |
| Handfeuerwaffen | Small arms; shoulder arms(lit | Heeresmunitionslager(HML) | Army ammunition depot |
| | Hand firearms) | Heereswaffenamt(HWA) | |
| Handgranate(Hgr) | Hand grenade(HdGr) | | Army Ordnance Office |
| Handgriff; Handhabe | Handle; grip | | (See under Warplants, etc) |
| Handhabung | Handling; manipulation | Heereszeugamt | Army ordnance supply |
| Handhabungssichere | Explosives safe to handle | | depot; quartermaster |
| Sprengstoffe | | | depot |
| Handleuchtzeichen | Hand signal flare(ground) | Heizkraft | Heating power; |
| Handrauchzeichen | Hand smoke signal(ground) | Heizplatte | calorific power |
| handtätig | hand-operated; manual | Heizung | Hot plate |
| Handwaffe | Hand weapon; hand arm | Helm | Heating; firing |
| Handwerfer(See also | Mortar; trench mortar | Hemd | Helmet |
| Granatwerfer) | (lit Hand projector) | Hemmung | Shirt; shell of a |
| Handwerkzeug | Hand tools | Hermann | blast furnace |
| Hang | Slope; bent | | Jamming; stoppage |
| Hangemine | Hanging mine | Hersteller | Nickname for 1000 kg |
| Harnstoff | Urea | Herstellung | GP-HE bomb, called in |
| Härte | Hardness; temper(of a metal) | Hetzer | Ger "1000 kg SC" |
| Hartgummi | Ebonite | | Manufacturer; fabricant |
| Hartkem | Hard core (such as of tungsten carbide) | Hilfslafette | Production; manufacture |
| Harz | Resin; rosin | Hilfstafel | Baiter. Tank destroyer |
| Haube(Hb) | Ballistic cap(BC)on some larger | Hilfswaffe | of Skodawerke (See under |
| | caliber shells; false cap; | Hinterlader | Panzer) |
| | windshield | Hitze | Improvised mount |
| Haubengranate(Hbgr) | Shell with BC (ballistic cap) | H-Ladung; Hohl- | Auxiliary table (Ball) |
| Haubengranatenzünder(HbgrZ) | PD fuze for use under BC | ladung(HI;HL) | Auxiliary arm |
| Haubenschrapnell(HbSchr) | Shrapnel with false cap | hochbrisanter Sprengstoff; | Breech loader |
| Haubitze(H) (See also Mörser) | Howitzer (light and medium) | Brisanzsprengstoff | Heat; hotness; passion |
| | (See also Seilfeuergeschütz) | | Hollow charge(HoC); |
| Haubitze in Turm(HT) | Turret howitzer | | shaped charge |
| Haubitze granate(HGr;Hgr) | Howitzer shell | | High explosive(HE) |
| Haubitze ringpulver(HRgP) | Propellant in rings for field | | (lit Highly brisant |
| | howitzer | | explosive) |
| Haubitzezünder(HZ) | Howitzer shell fuze | hochempfindlich | supersensitive |
| Hauptgetriebe | Main transmission; main gear | | |

| | | | |
|---|---|----------------------------|-------------------------------|
| hochempfindlicher Aufschlag-zünder | Supersensitive percussion fuze | Infanterigranate(Igr; Jgr) | Shell for infantry gun |
| Höchstgasdruck | Maximum gas pressure | Influenzdetonation | Sympathetic detonation |
| Höchstschussweite | Maximum range | Ingenieur; Ingeniör | Engineer |
| Höcker | Maximum range | Inhaltsverzeichnis | Table of contents |
| Höckerhindernisse | Bump | Inhaltszettel | Content label |
| hohl | Dragon Teeth (A/T obstacle) | Initialexplosivstoff; | Initiating explosive (such as |
| Höhle | hollow; concave | Initialsprengstoff | M F , L A , L St , etc) |
| Hohlgeschoss; Hohlkopf-geschoss | Cave; cavern; hole; cavity | initialimpuls | See Zündreiz |
| Hohlladung(III, III.) | Hollow head projectile | Initialladung | Initiating explosive charge |
| | Hollow charge(III C); | Initialzünder | Initiator |
| | shaped charge | Innenzünder | Internal fuze |
| Note: During WWII the Germans used at least four types of hollow charges: III, III A, III B and III C | | Innere Ballistik | Interior Ballistics |
| Hohlladung 300g | 300g Hollow demolition charge | im Rohr gefüllte | Bangalore torpedo |
| Hohlladung 400g | 400g Hollow demolition charge | Reihenladung | |
| Hohlladung 12.5 kg | 12.5 kg Hollow demolition charge | Interessengemein- | Association for Furtherance |
| Hohlladung 13.5 kg | 13.5 kg Hollow demolition charge | schaft(IG) | of Mutual Interest; Trust |
| Hohlladung 50 kg | 50 kg Hollow demolition charge | Invarol | Gold resisting grease |
| Hohlringladung | Hollow, ring demolition charge | Irdenware | Earthenware |
| Hohlringladung 1.2 kg | 1.2 kg Hollow, ring charge | Irrtum | Error; mistake |
| Hohlringladung 3.2 kg | 3.2 kg Hollow, ring charge | Isolator | Insulator |
| holländisch(h) | Dutch | | |
| Holzgeist; Holzspiritus | Wood alcohol, methanol | Jabo(Jagdbomber) | Fighter bomber |
| Holzkasten | Wooden box | Jagd | Hunt; chase |
| Holzkohle | Charcoal | Jagdpanther | Tank destroyer Jagdpanzer V |
| Holzmehl | Wood meal; wood flour | | (See under Panzer in |
| Holzmine | Wooden box mine | Jagdpanzer(JagdPz); | descriptive part) |
| Holzpech | Wood pitch | Panzerjäger(PzJäg) | Tank destroyer or hunter |
| Holzruss | Wood snot | Jagdpulver | (See under Panzer) |
| Holzsteinkohle | Lignite | Jagdtiger | Hunting (sporting) propellant |
| Holzstoff | Wood pulp; cellulose(from wood) | Tiger Jäger | Tank destroyer (See under |
| Holzstoffmasse | Wood pulp | Jäger(J) | Panzer in descriptive part) |
| Holztee | Wood tar | | Hunter; chasseur; ranger; |
| Holzteepech | Wood-tar-pitch | Jägerbataillon | rifleman in Jägerdivision; |
| Holzzellstoff | Lignocellulose | | private in Gebirgsjäger- |
| Horchapparat; Horchgerät | Sound locator or detector | | Bataillon; fighter airplane; |
| Hornisse | Hornet; Self-propelled A/T gun | | pursuit plane |
| | (See under Panzer) | Jägerdivision | Light infantry battalion; |
| Hubschrauber | Helicopter | Jägergeschütz(JG) | ranger battalion; (See also |
| Hülle | Cover; covering; case; sheath | | Gebirgsjäger-Bataillon) |
| Hülse | Hull; husk; cartridge case | Jägergranate(JGr) | Light infantry division |
| Hülseauszieher | Cartridge case extractor | Jod | Light infantry piece |
| Hülsebezeichnung | Cartridge case identification | Jodazid | (G or How) |
| | (number) | Jodessigester | Light infantry gun projectile |
| Hülseboden | Base of cartridge case | Jodtinktur | Iodine |
| Hülsehnals | Neck of cartridge case | Jodzahl | Iodine azide |
| Hülsekartusche(HülKart) | Cartridge case of rapid-fire non-fixed | justieren | Ethylidoacetate(CWS) |
| | ammunition (as opposed to bag) | | Tincture of iodine |
| Hülse(patrone) | Cartridge case | | Iodine number |
| Hülsetrand | Cartridge case rim | | to adjust; collimate |
| Hummel | Bumblebee SP Howitzer(See under | | (bore-sight alignment) |
| | Panzer in descriptive part) | | |
| Hut | Hat; cap; cover; lid; top | | |
| Hütchen | Blasting cap; cup (cartridge) | | |
| Hütte | Hut; cottage; iron works; rolling mill; | Kabel | Cable; wire |
| | glass works | Kabine | Compartment; cockpit |
| Hydrocyansäure; Hydro- | Hydrocyanic acid | Kahn | (See also Kajüte) |
| zyansäure | | Kai | Boat |
| hydropneumatische Lafette | Hydropneumatic gun; carriage | Kajüte; Koje | Quay |
| | | Kaliber(Kal) | Cabin (ship) |
| | | Kalilauge | Caliber; gauge |
| | | Kalium(K), Kali | Caustic potash(KOH) |
| | | Kalk | Potassium(K) |
| | | | Lime |
| Infanterie(I; J) | Infantry | | |
| Infanteriegeschütz (IGesch) | Infantry piece(G or How); | | |
| | close support gun | | |

| | | | |
|------------------------------------|---|--|---|
| Kalkmilch | Lime solution; milk of lime | Kavaleriegeschütz | Cavalry gun |
| Kaliumsalpeter | Calcium nitrate | Kegel | Cone |
| Kalklebkitt(Kat) | Cold adhesive putty used for attaching demolition charges | Kennbuchstabe | Identification mark |
| Kaltspritzen | Cold extrusion (lit Cold-squirting) | Kennzeichen | Mark; sign; indication |
| Kaltrecken; Kaltreckung; | Autofrettage (a process used in manuf of gun barrels)(See in the general section) | Kennzeichnung | Code; designation |
| Selbstschumpfung | Crest; ridge; comb; cam | Kern | Core; nucleus |
| Kamm | Chamber; room | Kerngeschoss | Bullet with core |
| Kammer | Central tube; flash tube(Shr) | Kernladung | Base section(SL Ammo) |
| Kammerhülse(Kh) | Flash tube charge(Shr) | Kerzenstärke | Candle power |
| Kammerhülsenladung | Burster tube | Kettenkugel | Chain shot |
| Kammerhülsenrohr | Batt' :; combat; fight (See also Gefecht and Krieg) | Kiesel | Flint; silica; silex, gravel |
| Kampf | War gas; poison gas(CWS) | Kiff | Tan; tanbark |
| Kampfgas; Kampfstoff | Rifled bore signal pistol; Very pistol (See also Leucht-pistole) | Kippzünder(KiZ) | Tilt type igniter |
| Kampfpistole(KP) | Chemical bomb | Kissen | Cushion; pad; pillow |
| Kampfstoffbombe | Combat vehicle; tank; armored vehicle | Kiste | Case; chest, crate; box |
| Kampfwagen(KpW; Kw) | Tank trap | Kitt | Cement; putty |
| Kampfwagenfalle(KwF) | Tank gun | Klammer | Clamp; clasp; put swivel(Rf); clip; parenthesis |
| Kampfwagenkanone(KwK; KpW) | Cannon; gun; piece of ordnance | Klappe | Flap; trap; lid; damper |
| Kanone(K) | Gunboat | Kleif(kleiner Flammenwerfer) | Portable flame thrower |
| Kanonboot | Cannon shell | kleine Ladung | Reduced charge |
| Kanonengranate(KGr) | Gun barrel | Kleinkaliberlauf | Small bore barrel(Rf); subcaliber tube(G) |
| Kanonrohr | Smoke-puff charge (simulated fire) | Kleinkalibermunition | Subcaliber ammunition |
| Kanonenschlag mit Raucherscheinung | Gun shot | Kleinluftschiff | Blimp |
| Kanonenschuss | Fuze for a cannon shell | Kleister | Adhesive paste; thin paste |
| Kanonenzünder | Private(Arty); cannoneer | Klemme | Clip; clamp; terminal(Elec); binding post |
| Kanonier | Lieutenant-Commander(Nav) | klopfest | antiknock |
| Kapitänleutnant | Captain(Nav) | Knall | Bang; crack; detonation; report |
| Kapitän zur See | AP cap (See also Haube) | Knalldämpfer | Silencer(Ri or Pist); muffler |
| Kappe(Kp) | Capped projectile | Knallgas | Oxyhydrogen gas |
| Kappengeschoss | Capsule; priming cap; blasting cap; detonator | Knallglyzerin | Fulminating glycerin; nitroglycerin(NG) |
| Kapsel | Carbine | Knallquecksilber | Mercuric fulminate(M F) |
| Karabiner(Kb; Kar) | Heavy SP Mortars (See Thor and Karl Mortars) | Knallsäure | Fulminic acid |
| Karl Gerät | Canister(SL Ammo); case shot | Knallsilber | Silver fulminate(AgF) |
| Kartätsche | Schrapnel(Shr) | Knallwelle | Shock wave |
| Kartätschengranate; | Propellant bag | Knallzucker | Nitroglucose; nitrosaccharose |
| Schrapnell | Cover for Kartusche | Knallzündschnur; Detonierende Zündschnur | Primacord; detonating fuse |
| Kartuschbeutel(Kartb) | Cartouche; container of propellant charge not used in fired ammo | Knetmaschine | Kneading machine; malaxator |
| Kartuschdeckel(Kartd) | Bag container of propellant charge placed in Kartuschenhülse | Knick | Break (in curves); sharp bend |
| Kartusche(Kart) | Cartridge case for Kartuschen(q v) | Knickzünder(KnZ) | Snap type igniter |
| Kartusche,einfach | Ammunition using Kartuschen (Compare with Patronenmunition) | Knopf | Button |
| Kartuschenhülse(Karth) | Muzzle-flash reducing wad | Kochsalz | Kitchen salt; common salt |
| Kartuschenmunition(KartMu) | Casemate | Kohle | Coal; carbon |
| Kartuschenvorlage | Casemate cannon | Koje | See Kajüte |
| Kasematte | Casemate gun mount | Kohlengrube | Coal mine |
| Kasemattenkanone(KK) | Permanent barracks | Kohlensäure | Carbonic acid; carbon dioxide |
| Kasemattenlafette(KL) | Officer's mess or club | Koks | Coke(coal) |
| Kaserne | Target indicating flare (TM-9-1985-2, pp 71-2) | Kolben | Flask; butt(Rf, Pist, MG, etc); piston |
| Kasino | Chest; box; case | Kolbenpistole | Machine pistol |
| Kask(such as Mk 50 Kask) | Box, trail gun carriage | Kollodiumwolle | Colodion cotton; soluble NC |
| Kasten | Catapult | Königstiger | King Tiger(Tank)(See under Panzer) |
| Kastenlafette | Caoutchouc; rubber, before vulcanization | konisches Rohr; | Tapered-bore barrel(G); squeeze bore barrel |
| Katapult; Schleuder | | Würgebohrung | Contact sea mine |
| Kautschuk | | Kontaktseemine | Head; nose(B); point(Sh) |
| | | Kopf(Kpf) | Front ring(Proj) |
| | | Kopfring | Shock wave(at the tip of projectile) |
| | | Kopfwelle(an der Spitze des fliegenden Geschoss) | |

| | | | |
|---|--|-----------------------------------|--|
| Lafette(L) | Gun carriage; gun mount | Leistung | Output, performance; capacity; work |
| Lafettentisch | Gun carriage bed | Leiter | Conductor; leader; guide |
| Lage | Situation; position; layer | Leitfähigkeit; Leitungsfähigkeit | Conductivity |
| Laget | Camp; depot; dump; bed; layer; bearing; seat | Leitfeuer | Ranging rounds (used to establish the accuracy of the estimated distance from firing position to target) |
| Lagerbeständigkeit | Stability in storage (See also Beständigkeit, Haltbarkeit and Stabilität) | Leitung | Electric cable; conduit |
| Lagerungsprobe | Storing test | Lenkballon; Lenkluftschiff | Dirigible |
| laktiert | lacquered; varnished | Leopard | One of the tanks (See under Panzer) |
| Lakmus; Lackmus | Litmus | Leopold | 280 mm Railway Gun Model 5. called also Anzio Annie |
| Landflucht | Ground flare for aircraft landing | Letten | Potter's clay; clay used for tamping |
| Landpanzer | Armored amphibious troop carrier (See also under Panzer) | Leuchtbombe | Illuminating bomb; flare bomb |
| Landmeile | Statute mile(1.609 km) | Leuchte | Light; lamp; illumination |
| Landmine | Land mine | Leuchtfallschirm | Parachute flare |
| Landsturm | Territorial trained reserves | Leuchtfallschirmgranate | Parachute flare shell |
| Note: According to H. A. Tisch of Picatinny Arsenal, the Imperial German Army had approximately the following classification: Active (ages 18--22), Reserve (22--28), Ersatz Reserve (28--32), Landwehr I (32--35), Landwehr II (35--38), Landsturm I (38--42) and Landsturm II (over 42). All classes were trained. If the men had not served 2 years in the active army, they had to go through 6 months of basic training. | | Leuchtfallschirmrakete | Parachute flare rocket |
| Landswerke 60(L-60) | One of the tanks(See under Panzer) | Leuchtgeschoss; | Star shell; illuminating shell |
| Landungsrauchzeichen | Smoke generator for aircraft landing | Leuchtgranate | |
| Landwehr | See Note under Landsturm | Leuchtgeschoss-Zünder(LgZ) | Fuze for star shell |
| Landwirtschaftlicher Schlepper(LWS) | Agricultural tractor of pre-WW II which was converted to a tank (See under Panzer) | Leuchtgranatwerfer | Pyrotechnic mortar (projector) |
| Länge | Length; longitude | Leuchtsignal | Ground signal; Véry signal light |
| Länge der Waffe | Length of weapon | Leuchtmittel | Pyrotechnic device |
| Langgeschoss; Langgranate | Elongated projectile | Leuchtmunition (LMun) | Pyrotechnic ammunition; flare ammunition |
| Langnebelkerze 42(NbKzL42) | Long smoke generator 42 | Leuchtpatrone(LPatr) | Signal cartridge; flare cartridge; (single star) |
| Langrohrgeschütz | Long gun; long-barreled gun | Leuchtpistole(LPist) | Smooth-bore pyrotechnic pistol; signal pistol (See also Kampfpistole) |
| langsam verbrennendes Pulver | Slow-burning propellant | Leuchtrakete | Signal rocket; flare rocket |
| Langwellen | Long waves(Rad) | Leuchtröhre | Fluorescent tube |
| Langzeitzünder | Long time fuze; delay fuze | Leuchtsatz | Luminous composition; flare composition; pyrotechnic composition |
| Last; | Load; burden; weight | Leuchtspur(L'spur); Lichtspur | Tracer trajectory; light trail of tracer projectile |
| Lastkraftwagen | Truck | Leuchtspurgeschoss (L'spurG) | Projectile with tracer |
| Lauf | Barrel(SA); course; path (See also Rohr) | Leuchtspurgranate (L'spurGr) | Tracer shell |
| Laufbohrung | Bore(G) | Leuchtspurnmunition (L'spurMun) | Tracer ammunition |
| Lauffinieren; Laufseele | Bore(of a small arm) | Leuchtspursatz | Tracer composition; tracer column |
| Laufweite | Caliber(SA); (See also Kaliber) | Leuchtturm | Signal(illuminating signal) |
| Laufzeit | Running time(Fz) | Leucht- u Signal-Munition(LuSMun) | Signal pistol ammunition |
| Lauge | Lye; leach, (Sodium or Potassium Hydroxide) | Leuchtvisier | Luminous sight |
| Lautsprecher | Loud speaker | Leuchtzeichen | Ground signal light |
| Lazarett; Krankenhaus; Spital | Hospital | Leuchtzifferblatt | Luminous dial |
| Lazarettzug | Hospital train | Leutnant | Second lieutenant |
| Lebensdauer(des Geschützes) | Life (of a gun) | Licht | Light; candle |
| Lebhaftigkeit | Vivacity | Lichtmessung(LMssg) | Flash ranging |
| Leere | Vacuum; emptiness; gage | Lichtspur(L.Sp) | See Leuchtspur |
| Leergewicht | Weight empty | Lichtspurnmunition (L'spurMun) | See Leuchtspurnmunition |
| leicht(l; le; L) | light | Leuchtspursatz | Tracer composition; tracer column |
| Leichtgeschütz(LG; leG) | Light weapon(such as recoilless gun) | Leuchtturm | Signal(illuminating signal) |
| leichtes Geschütz | Light metal(Aluminum) | Leucht- u Signal-Munition(LuSMun) | Signal pistol ammunition |
| Leichtmetall(Lm; LM) | Glue | Leuchtvisier | Luminous sight |
| Leim | Glue | Leuchtzeichen | Ground signal light |
| Leinöl | Linseed oil | Leuchtzifferblatt | Luminous dial |

| | | | |
|--|---|--|--|
| lidern | to pack; seal; obturate | Lunte | Slow match; fuse lighter |
| Liderung | Obturator(G); gas check | Luntengewehr | Matchlock gun |
| Lieferung | Supply; delivery; lot | | |
| Lieferungsnummer | Delivery number | | |
| Linie, ballistische | Ballistic line; trajectory (See also Flugbahn) | | |
| links | to the left; levo | | |
| linksdrehend | levorotatory; counterclockwise | | |
| Linse | Lens | | |
| Lippe | Lip; edge; rim | | |
| Livens-Handwerfer | Livens projector(CWS) | | |
| Loch | Hole; opening | | |
| Lochgeschoss | Hollow point bullet (See also Hohlladung) | | |
| Lokomotivbahnhof | Engine yard(RR) | | |
| Lokomotivschuppen | Roundhouse(RR) | | |
| Losantin | Decontaminating agent (Ca hypochlorite preparation in powder or in tablet form) (CWS) | | |
| Losantinbrei | Ca hypochlorite slurry(CWS) | | |
| löschen | to extinguish; quench; slake(lime); discharge; unload(a ship) | | |
| Löschgerät | Fire extinguisher | | |
| Lösemittel; Lösungsmittel | Solvent | | |
| lösemittelfrei | solventless | | |
| Löslichkeit | Solubility | | |
| Lösung | Solution | | |
| Losungswort(Lsg) | Password | | |
| Lot | Sounding lead; plummet; solder | | |
| Lotmetall; Lotzinn | Solder | | |
| Lorsee | Pilot(Nav) | | |
| Loupe | Magnifying glass | | |
| Luchs | Lynx; reconnaissance tank (See under Panzer) | | |
| Luftbüchse; Luftgewehr | Air gun; air rifle | | |
| luftdicht verschlossen | airtight; hermetically sealed | | |
| Luftdichte; Luftgewicht | Air density | | |
| Luftdruck | Air pressure(Mech); atmospheric pressure(Met); blast effect; effect of explosion | | |
| Luftdruckbremse | Air brake | | |
| Luftdruckmesser | Barometer | | |
| Luftdruckwirkung; Luftstoss | Blast effect | | |
| Luftfahrt | Aeronautics; aviation | | |
| Luftfahrzeug; Flugzeug | Aircraft | | |
| Luftflasche | Compressed air cylinder; oxygen flask air-cooled | | |
| luftgekühlt | Volatile chemical agent(CWS) | | |
| Luftkampfstoff | Light armored vehicle used with | | |
| Luftlandepanzer | Airborne(See also under Panzer) | | |
| Luftmine(LM) | Aerial mine | | |
| Luftpistole | Air pistol | | |
| Luftschutz(LS) | Air raid defense | | |
| Luftschutzraum(LSR) | Air raid shelter | | |
| Luftsog | Vacuum, resulting from an explosion | | |
| Luftstoss; Blasen(See also Luftdruckwirkung) | Concussion of air caused by an explosion; blast effect | | |
| Luftstosswelle | Blast wave | | |
| Lufttorpedo(LT) | Aerial torpedo | | |
| Luftwaffe | German Air Forces | | |
| Luger(Parabellum)Pistole | See under Weapons | | |
| Lungenreizstoff | Lung irritant(CWS) | | |
| | | M | |
| | | M1(Kanone) | 353 mm Howitzer(See under Weapons) |
| | | Macht | Might; power; force |
| | | Magazingewehr | Magazine rifle |
| | | Manöver(Man) | Maneuver |
| | | Manöverkartusche(ManKart) | Maneuver(blank)cartridge |
| | | Manöverpulver(ManP) | Maneuver(blank)propellant |
| | | Mantel | Mantle; envelope; overcoat; jacket(bullet, projectile, etc); sheath |
| | | Mantelgeschoss; Verbundgeschoss | Jacketed projectile(such as nickel-cased or steel coated); compound bullet |
| | | Mantelkanone | Jacketed gun |
| | | Mantelpatrone | Sheathed cartridge(coal mining) |
| | | Mantelringrohr; | Built-up barrel(G); jacketed barrel(MG) |
| | | Mantelrohr | (See also geschrumpftes Rohr and Ringrohr) |
| | | Mantelsprengstoff | Sheathed explosive |
| | | Marder(38 and II) | Marten. Nickname for some SP A/T guns (See under Panzer in descriptive part) |
| | | Marienbad | Water bath (laboratory); watering place |
| | | Marine | Navy(See also Kriegsmarine) |
| | | Marineflak | Naval AA gun |
| | | Marinelager(Marlag) | Prisoner-of-war camp for sailors |
| | | Marineministerium | Admiralty of the German Navy |
| | | Marinewaffenamt(MWA) | Bureau of Naval Ordnance |
| | | Marinewaffenamt | (Branch of Oberkommando der Kriegsmarine) |
| | | Mark | See Reichsmark(RM) |
| | | Marke | Mark; index mark; label; brand |
| | | Marlag | See Marinelager |
| | | Marmor | Marble |
| | | Maschinenflak | AA automatic weapon |
| | | Maschinengewehr(MG); MGew); Kugelspritze | Machine gun(MG) |
| | | Maschinenkanone(MK) | Automatic cannon |
| | | Maschinenkarabiner(MKb) | Automatic rifle or carbine |
| | | Maschinenpistole(MP) | Machine pistol; submachine gun |
| | | Maschinenpistole 44(MP 44) | Submachine gun(called later Sturmgewehr 44) |
| | | Maschinenschlosser; | Mechanic |
| | | Mechaniker | |
| | | Maschinenschreiber | Typist |
| | | Maschinenwaffe | Automatic weapon |
| | | Maskensicherung | Meaning unknown to us |
| | | massanalytisch | volumetric |
| | | Massenherstellung | Fabrication in series; mass production |
| | | Matrose | Sailor; apprentice seaman |
| | | Maus | Mous-; heavy tank developed by Porsche (See under Panzer) |

| | | | |
|---|--|---------------------------------------|--|
| Max(Bombe) | Nickname for 2500 kg GP-HE bomb, called in Ger "SC 2500 Max" (TM9-1985-2, p 13) | Mischung tp 60/40 mit Verzögerung(mV) | Amatol 40/60 with delay |
| Maximalgasdruck | Maximum gas pressure | Mitte; Mittel | Middle; mean |
| mechanischer Zünder | Mechanical fuze | Mitteilung | Communication; information |
| Meerküste | Seacoast | Mittelkammerschrapnell | Central-burster shrapnel |
| Mehl | Meal; flour; dust; powder | mittlere Flugbahn | Mean trajectory |
| Mehlpulver | Finely ground black powder; meal powder | mittlerer Fehler | Average (mean) error |
| Mehrfachzünder | Combination fuze | mittlerer Gasdruck | Mean pressure |
| Mehrlader; Mehrladegewehr | Magazine-fed rifle; repeating rifle | Mockstahl | German steel made by direct refining of cast iron |
| Meissel | Chisel | Mollit | Centrallite (See in descriptive part) |
| Meisselapparat; Gasdruckmesser | Crusher gage; pressure gage (See also Messei) | Montage | Mounting assembly |
| Meldebüchse | Message container(carrier) | Montan- | Mountain; mining; montan; montanic |
| Meldebüchse, Land | Land message container (with yellow smoke generator) | Montanwachs | Montan wax |
| Meldebüchse, See | Sea message container (with yellow smoke generator) | Mörser(Mrs) | Short, large caliber howitzer; (translated also as mortar) |
| Meldepatrone; M-Patrone | Ground signal cartridge | Mörtel | Mortar (building material) |
| Meldung(See also Nachricht) | Message; report; dispatch | MOTO | See under German Abbreviations |
| Messei | Pressure gage(Arty) (lit Measuring egg) | Motor | Engine |
| messen | to measure; survey | Motorrad | Motorcycle |
| Messing | Brass | Motorschnellboot | Motor speedboat; |
| Messpatrone | Bore gage | Motortorpedoboot | PT boat |
| MG-Zwilling | Twin machine gun | mPak | Motor torpedo boat; |
| Milag | See Militärlager | M-Patrone(MPatr) | PT boat |
| Milchglas | Frosted glass | Muffe | See under abbreviations |
| militärische Besetzung | Military occupation | Mühle | See Meldepatrone |
| Militärlager(Milag) | Army camp | Mund | Socket; coupling box; |
| Mine | Mine; lead for pencil | Mundloch | bushing; muff |
| Minenbombe | Aerial mine | Mundloch(des Zünders) | Mill |
| Minenfeld; Minensperre | Mine-field | Mundlochbüchse | Mouth; opening; muzzle |
| Minengang | See Minenstollen | | Adapter opening |
| Minengechoss(M) | Mortar shell; high capacity, HE missile | | Fuze hole |
| Minenhund | Remote-controlled explosive-laden miniature tank | Mundlochfutter | Gaine-type fuze-booster container; bushing to hold detonator in fuze |
| Minenleger | Mine layer | | Gaine (See general section) (lit Fuze hole casing) |
| Minenpulver | Blasting powder | Mundlochgewinde | Adapter opening thread |
| Minenräumer; Minenräumboot | Mine sweeper(Nav) (See also Räumboot) | Mundlochschaube | Adapter plug |
| Minerohr; Bohrloch | Borehole | Mundstück | Mouth piece |
| Minenschacht | Mining shaft | Mündung | Muzzle(G); outlet; mouth(river) |
| Minensperre | Mine field; mine obstacle | Mündungsbremse | Muzzle brake |
| Minenstollen; Minengang | Mining gallery | Mündungsenergie; | Kinetic energy at the muzzle |
| Minensuchboot; Minensucher | Mine sweeper(Nav) | Mündungswucht | Muzzle flash |
| Minensuchgerät | Mine detector | Mündungsfeuer | Flash damper; flash hider (See also Feuertämpfer) |
| Minentrichter | Mine crater | Mündungsfeuertämpfer | flashless(propellant) |
| minenverseuchtes Gebiet | Mine-infested area | mündungsfeuerfrei | Muzzle velocity; initial velocity |
| Minenwerfer(MiW)(See also Granatwerfer) | Trench mortar(lit Mine projector) | Mündungsgeschwindigkeit | Muzzle cover; tampon |
| Minenwirkung | Mining effect | | Muzzle report; muzzle blast |
| Minenzünder | Mine igniter | Mündungskappe | Ammunition(Ammo) |
| Ministerium Speer | Ministry of Armaments and War Production named after its chief, Speer | Mündungsknall | Ammunition box; caisson |
| Mischmetall | Mixed metal; alloy; an alloy of cerium and lanthanum with some other rare earth metals | Munition(Mu; Mun) | Ammunition truck |
| Mischsäure | Mixed acid(such as mixed nitric-sulfuric acid) | Munitionskasten | Ammunition dump; |
| Mischung | Mixture; mixing; blend | Munitionskraftwagen(MKw) | ammunition depot |
| | | Munitionslager | ammunition pit |
| | | Munitionslach | ammunition carrier |
| | | Munitionsträger(Mun; Muntr) | ammunition packaging |
| | | Munitionsverpackung | |

| | | | |
|--------------------------------------|--|--|---|
| Munitionswagen | Ammunition wagon; ammunition car; caisson; ammunition carrier | Nebelwerfer(NbW)(See also Raketenwerfer und Wurfgerät) | Rocket launcher (lit chemical smoke projector) |
| M-u R-Patr | See under Ger Abbreviations | Nebelwerfer 41 | A six-tube rocket launcher (See descriptive section) |
| Muster | Model; type; pattern; sample | Nebelwurfgranate(NbWgr) | Mortar smoke-shell |
| Mutter | Mother; matrix; nut; female screw | Nebelzerstauber | Smoke sprayer |
| Mutterrohr | Gun tube designed to receive a liner | Nebenprodukt | By-product |
| Mutterschlüssel | Socket wrench | Nebenschluss | Shunt |
| Mütze | Cap; hat | Nest | Nest; pocket(in ore); position consisting of a group of foxholes with shallow connecting trenches |
| N | | | |
| Nab | Hub; nave | netto | net |
| Nachbildung | Dummy; mock up; model; copy | Nettogewicht | Net weight |
| Nachbrenner | Hangfire | Netz | Net; netting; gauze; grid; wiring system |
| Nachfolger(Nachf) | Successor | Neuseelen | Relining; retubing(G) |
| Nachforschung | Research; investigation | Neusilber | German silver; nickel silver |
| Nachleuchten | Afterglow; phosphorescence | nichtbrisanter Sprengstoff | Low explosive (lit Nonbrisant explosive) |
| Nachricht(See also Meldung) | News; information; notice; message | nichtrostender Stahl | Stainless steel (lit Rustless steel) |
| nachrichten | to repaint; ream; correct the range | Niederdruck | Low pressure |
| Nachrichtenmittel | Means of intercommunication | niederländisch | See holländisch |
| Nachrosten | Corrosion; after-rusting | Niederschlag | Precipitate; sediment |
| Nachzündung | Retarded ignition | Niet; Niete | Rivet; pin |
| Nadel | Needle; firing pin(Fz) | Nitratpulver | Nitrate powder |
| Ni gel | Nail | Nitrierbaumwolle | Nitrating cotton |
| Nahkampfgeschütz | Close-range gun | Nitriergemisch | Nitrating mixture |
| Nahkampfmittel | Close combat material(weapon) | Nitrierung; Nitration | Nitration; nitrating |
| Nahpatrone | Low velocity cartridge used for close combat; close-range round; silencer cartridge (SA) | Nitrocellulose; Nitrozellulose | Nitrocellulose(NC) |
| Nahwerfer | Short range flame thrower (See also Flammenwerfer) | Nitroglycerin(Ngl); Nitroglyzerin | Nitroglycerin(NG) |
| Näpfchen | Cup; small dish or bowl; blank (for blasting caps) | Nitroglykol | Nitroglycol(NGc) |
| Nase | Nose; cap; stud; lug | Nitroguanidin(Nigu) | Nitroguanidine(NGu) |
| Nasenrachenreizstoff | Sternutator; nose and throat irritant(CWS) | Nitropenta(Np); Pentrit | Pentaerythritol tetranitrate(PETN) |
| Nashorn | Rhinoceros; SP A/T Gun (See under Panzer in descriptive part) | Nitropentapulver | Propellant containing PETN |
| nass | wet; moist | Nitrostärke | Nitrostarch |
| Nassbrandpulver | Black powder contg 72-75% of K nitrate (See also Schwarzpulver) | Nitroverbindung | Nitro compound |
| Nassgehalt; Nassgehalt | Moisture content | Norm | Standard |
| Natrium | Sodium | normieren | to standardize; gage; regulate |
| Natriumnitrat; Natronsalpeter | Sodium nitrate; chile saltpeter | norwegisch(n) | Norwegian |
| Nebel(Nb) | Smoke(CWS); fog; mist | Notbremse | Emergency brake |
| Nebelbombe(NbB) | Smoke bomb | Notfeuer | See Sperrfeuer |
| Nebeldecke; Nebelwand | Smoke screen; smoke blanket | Notlandung | Emergency landing |
| Nebelgeräte | Smoke producing equipment | Notsignal | Distress signal; SOS |
| Nebelgeschoss(NbG) | Smoke projectile | Notsignalfakel | Distress signal flare(torch) |
| Nebelgranate(NbGr) | Smoke shell | Nudelpulver (NdP; NP) | Chopped cord propellant; nodular(noodle)propellant |
| Nebelhandgranate(NbHgr) | Smoke hand grenade | Nummer(Nr) | Number |
| Nebelkasten | Smoke generator | Nuss | Nut; tumbler |
| Nebelkerze(NbK) | Smoke candle; thermal smoke generator | Nut; Nute | Groove; slot |
| Nebelkerzen Wurf-ladung (NbKerzWldg) | Propelling charge for thermal smoke grenade | Nutsche | Nutsch; auction filter |
| Nebelpatrone(NbPatr) | Smoke cartridge | Nutzarbeit | Useful work |
| Nebelstoff | Smoke agent; screening agent(CWS) | Nutzeffekt; Nutzwirkung | Efficiency; useful effect |
| Nebeltopf | Smoke pot(CWS) | Nutzfahrzeug | Commercial vehicle |
| Nebeltrommel | Drum-type smoke container | Nutzkraftwagen | Commercial motor vehicle |
| | | Nutzlast | Useful load; payload |
| | | Nutzleistung | Net horsepower |

| O and Ö | | Ostwind | Eastwind; SP AA gun (See under Panzer in descriptive part) |
|--|---|---|---|
| Ober- | Upper; chief; supreme; superior | Otter | Paravane |
| Oberbefehlshaber; Oberster Befehlshaber | Commander-in-Chief | | |
| Oberdecke | Housing cap | | |
| Oberfeldkommandatur | High Field Command | | |
| Oberfeldwebel (See also Oberwachtmeister) | Master sergeant (except in Arty & Cavy) | Pack; Paket Packhaus; Packhof | Pack; bale; bundle; parcel Warehouse; shipping department |
| Oberfeuerwerker | Master sergeant (Ord) | Packstoff | Packing material; packing |
| Oberfläche | Surface; area | Pak | See Panzerabwehrkanone |
| Obergefreiter | Corporal | Pak-Flak | A/T-AA gun; dual-purpose gun |
| Obergrenadier | Private 1st Class(Infy) | | A/T gun |
| Oberjäger | Private 1st Class(Mountain Infy) | Pakgeschütz | Self-propelled A/T gun; |
| Oberkanonier | Private 1st Class (Arty) | Pakgeschütz auf Selbstfahrlafette | tank destroyer |
| Oberkommando des Heeres(OKH) | Army High Command | Panther | Same as Panzerkampfwagen V (See under Panzer in de- scriptive part) |
| Oberkommando der Kriegsmarine(OKM) | High Command of the Navy | | Tiger II or King Tiger(See under Panzer) |
| Oberkommando der Luftwaffe(OKL) | High Command of the Air Forces | Pantiger | Armor; cuirasse; tank (See descriptive section) |
| Oberkommando der Wehrmacht(OKW) | High Command of the Armed Forces | Panzer (Pz) | Tank detachment |
| Oberleutnant | First lieutenant | Panzerabteilung | A/T defense |
| Oberpanzergrenadier | Private 1st class in armored infantry | Panzerabwehr | A/T rifle |
| Oberpionier | Private 1st class in engineers | Panzerabwehrgewehr, later called Panzerbüchse | |
| Oberquartiermeister | Deputy Chief of the General Staff | Panzerabwehrgeschütz | A/T gun |
| Oberreiter | Private 1st class(Cavy) | Panzerabwehrkanone (Pak), later called Panzerjägerkanone | A/T gun |
| Oberschütze | Private 1st class(Infy rifleman) | Panzerabwehrmine | A/T mine |
| Oberst(O) | Colonel | Panzerabwehrrakete | A/T rocket |
| Oberster Befehlshaber der Wehrmacht | Commander-in-Chief of the Armed Forces | Panzerartillerie | Armored artillery |
| Oberstleutnant | Lieutenant colonel | Panzerbefehlswagen (PzBefWg) | Tank with a minimum of armor and arms; equipped with radio for command use (See also under Panzer) |
| Oberwachtmeister (See also Oberfeldwebel) | Master sergeant (Arty and Cavy) | | Armored car used for artillery spotting(See also under Panzer) |
| Oel | See Öl | Panzerbeobachtungswagen | Armor plate |
| Ofenrohr | Stovepipe (slang term for 88 mm Rocket Launcher described under Weapons) | | A/T bomb; AP bomb; heavy-case bomb armor-piercing |
| Offizier | Officer | Panzerblech; Panzerplatte | |
| Öfnung | Opening; orifice | Panzerbombe | |
| ohne Verzögerung(oV) | without delay (Fz) | | |
| Öl; Oel | Oil | panzerbrechend; panzerdurchschlagend | |
| Ölbombe | Oil bomb | Panzerbüchse, formerly called Panzerabwehrgewehr | A/T rifle |
| Öldruckbremse | Hydraulic brake | Panzerdurchschlageistung | Penetration; armor- piercing capacity |
| Oppanol | Polyisobutylene(synthetic substance resistant to mustard gas and Lewisite) (CWS) | | Armored vehicle; tank |
| O-Punkt; Nullpunkt | Aiming point (Guns) | Panzerfahrzeug | Tank trap |
| Order | Order; medal; decoration | Panzerfahrzeugfalle; Panzerfalle | |
| Orgelgeschütz | Organ gun; multiple barrel gun | Panzerfahrzeuggraben | A/T ditch |
| Ort | Locality; place(See also Standort) | Panzerfaust (PzF) | Armor Fiat (See under 44.5 mm Weapons and under Faustpatrone) |
| ortsfest | fixed; permanent; in fixed emplacement | | Formerly Faustpatrone 2 |
| ortsfeste Flak | Fixed AAG; fixed AA Arty | Panzerfaust 30 | Formerly Faustpatrone 1 |
| ortsfeste Lafette | Stationary gun mount | Panzergeschoss (PzG) | AP projectile |
| Ortungsluchtzeichen | Ground position signal; signal bomb illuminating ground | panzergeschützt | armor-protected |
| | | Panzerglas | Multiple laminated glass, resisting bullet penetration |

| | | | |
|--|---|---|---|
| Panzergraben | A/T ditch | Panzerschütze | Tank gunner |
| Panzergranate (PzGr; Pzgr) | A/T (AP) projectile | Panzerselbstfahrlafette (PzSfe) | Armored SP gun mount |
| Panzergranate 39 (Pzgr 39) | APBCHE (armor-piercing capped, ballistic cap, high-explosive) projectile, type 39 | Panzerspähwagen (PzSpW) | Rapid, lightly armored vehicle for reconnaissance (See also Aufklärungspanzer and under Panzer) |
| Panzergranate 40 (Pzgr 40) | AP projectile with a tungsten carbide core, type 40 | Panzersprenggeschoss (PzsprG) | HEAT projectile; HE A/T projectile |
| Panzergranate 41 (Pzgr 41) | AP projectile with a tungsten carbide core for tapered bore gun (type 41) | Panzersprenggranate (PzsprGr) | HEAT shell; HE A/T shell |
| Panzergranate-Patrone | AP fixed round of ammunition | Panzerstahl | Armor steel |
| Panzergrenadier | Private in armored infantry brigade | Panzerstärke | Thickness of armor |
| Panzergrenadier-Division | Motorized division (See also SS-Panzer-grenadier-Division) | Panzerturm | Turret of a tank (lit Armored turret) |
| Panzerhandmine 3kg (PHM 3) | Magnetic A/T hollow charge 3 kg hand mine | Panzerung | Armor; armor plating |
| Panzerjäger | Tank destroyer (See also Jagdpanzer) | Panzerwaffe | Armored weapon |
| Panzerjägerabteilung | Tank destroyer detachment | Panzerwagen | Armored combat vehicle |
| Panzerjägerschütz; | A/T gun (See also Panzerabwehrkanone) | Panzerwagenmine | A/T mine |
| Panzerjägerkanone | Full-track tank with tactical armor and weapons, used in organized front line units; armored combat vehicle | Panzerwurfmine | A/T trench mortar shell or bomb; A/T hand grenade |
| Panzerkampfwagen (PzKpfw) (See also under Panzer in the descriptive section) | | Panzerzug | Armored train (RR); tank platoon |
| Panzerkampfwagen I (PzKpfw I) | | Papiermasse | Paper pulp; papier-mâché |
| Panzerkampfwagen II (PzKpfw II) | | Pappe; Pappdeckel | Cardboard; paperboard |
| Panzerkampfwagen III (PzKpfw III) | See under Panzer in descriptive part | Papphülse (für Wurfgranate) | Cardboard cartridge for mortar shell |
| Panzerkampfwagen IV (PzKpfw IV) | | Pappmine | Cardboard mine |
| Panzerkampfwagen V (PzKpfw V) | | Pappminenzünder | Igniter for cardboard mine |
| Panzerkampfwagen VI (PzKpfw VI) | | Parabellum (Luger) Pistole | See under Weapons |
| Panzerkanone (PzK); | | Parade Marsch | Goose step |
| Kampfwagenkanone (KwK) | | Parole | Password |
| Panzerkopf (Pzk) | | Partisane | See Guerillakämpfer |
| Panzerkorps | | Patrone (Patr) (Compare with Kartusche) | Cartridge (SA); round of QF fixed ammo (Arty) |
| Panzerkraftfahrzeug; | | Patrone 318 (Patr 318) | Fixed AP ammo used in A/T rifle 39 (PzB 39); (the bullet usually contained a small charge of lacrymatory gas) |
| Panzerkraftwagen | | Patronenauswerfer | Cartridge ejector |
| Panzerlafette | | Patronenauszieher | Cartridge extractor |
| Panzerleuchtspurgeschoss (PzL'spurG) | | Patronenbeutel | Pouch; cartridge belt |
| Panzermine; Panzerwagenmine | | Patronenfabrik | Cartridge factory; ammunition plant |
| Panzermine 43 (PzMi 43) | | Patronenfüllmaschine | Cartridge loading machine |
| Panzermunition | | Patronengurt; Patronengürtel | Cartridge belt |
| Panzerpatrone | | Patronenhaken | Shell extractor |
| Panzerplatte | | Patronenhals | Collar of the cartridge |
| Panzerschild | | Patronenhülse (PatrH) | Cartridge case of fixed ammo |
| Panzerschreck | | Patronenkasten (PatrKast) | Cartridge box; ammunition box |
| | | Patronenlager; | Cartridge chamber |
| | | Patronenkammer | |
| | | Patronenmunition (PatrMu) | Fixed ammunition (Compare with the Kartuschenmunition) |
| | | Patronenrahmen | Clip (Rf and AA gun) |
| | | Patronenrand | Rim of a cartridge case |
| | | Patronenraum | Propelling charge chamber in mortar shell |
| | | Patronenstreifen | Cartridge clip |
| | | Patronentrommel | Cartridge drum |
| | | Patronenzuführung | Cartridge feed mechanism (SA) |

| | | | |
|-------------------------------------|---|--|---|
| Pausepapier | Tracing paper | Plättchenpulver (PeP) | Disk propellant |
| Peck | Pitch; asphalt; cobbler's wax | Plattenpulver | Rolled propellant; sheet propellant |
| Peilung | Direction finding; bearing | Platz | Place; square (in a city or town); space; airfield; landing field |
| Pendelapparat | Pendulum apparatus | Platzpatrone (PlPatr) | Blank cartridge |
| Pendeln des Geschosses | Oscillation (precession) of a projectile | Platzpatronengerät | Weapon for firing blank cartridges |
| Pendelung | Oscillating motion (See also Seitwärtsbewegung) | Plombe | Lead seal |
| Pentrit | See Nitropenta | Plongierschuss | Plunging fire; mortar fire |
| Perkussionszünder | Percussion igniter | Plotz | Explosion |
| Perkussionszündhütchen | Percussion cap | pneumatisches Geschütz | Pneumatic gun |
| Perkussionszündung | Percussion priming or igniting | Polizist; Schutzmann | Policeman |
| Perlitgus (PG) | Cast steel in pearlite condition | Polklemme | Battery terminal binding post (Elec) |
| Perstoff | Diplosgene; superpalite (C1CO ₂ CC1 ₃) | Potenz | Power (Math) |
| Petarde | Closed metallic box filled with black powder (used formerly as a demolition charge) | Prahm | Barge; lighter (Nav) |
| Petrol; Petroleum | Kerosene; petroleum | Prallschuss; Prellschuss | Ricochet |
| Pfahl | Picket; stake; post; pile | Pressling (Pr) | Pressed article; molding; briquet |
| Pfeife | Whistle; pipe | Pressluft | Compressed air |
| Pfeifpatrone | Whistling pyrotechnic signal cartridge used as gas alarm | Press-stoff (PrS) | Thermosetting plastic; (lit Pressed material) |
| Pfeifsignal | Whistle signal | Presswerkzeug | Forged tool |
| Pfeil | Arrow | Pr-Geschoss | See Phosphorgeschoß |
| Pfeilgeschoss | Arrow-type, fin stabilized, discarding sabot artillery projectile | Primärladung; Aufladung | Primary charge of a cap or of a detonator |
| Pfeinig | 1/100 Reichsmark or Deutschmark | prismatisches Pulver | Prismatic propellant |
| Pferdestärke (PS); | Metric horsepower (1 PS = | Probe | Test; trial; essay; sample |
| Pferdekraft (PK) | 0.986 HP) | Probeschiessen | (See also Prufung) |
| Pferdezug | Horse draught; horse team | Profil | Test firing |
| Pfiffikus; Phenyldichlorarsin | Phenyldichlorarsine (CWS) | profiliert | Profile; cross section; |
| Pfropfen | Wad; wadding; plug; stopper | Progressivdrill; zunehmender (wachsener) Drall | tread of a tire |
| Phosgen | Phosgene; carbonylchloride (CWS) | Progressivpulver | streamlined |
| Phosphor | Phosphorus | Propagandageschoß 41 | Increasing twist of rifling; progressive rifling |
| Phosphorbombe; Phosphorfliegerbombe | Phosphorus bomb | Propagandawerfer | Progressive burning propellant; progressive propellant |
| Phosphorgeschoß (PrGesch) | Phosphorus (incendiary) bullet | Protze (Pr) | Leaflet projectile 41 |
| Phosphorgeschoß mit Stahlkern | AP-Inc steel core bullet with phosphorus | Prozentsatz | Jaucher for leaflet projectile |
| Phosphormunition | Phosphorus ammunition | Prüfgerät | Limber (Arty) |
| Pi-Kampfmittel | Engineer combat equipment | Prüfung | Percentage |
| Pikrinsäure | Picric acid | Prüfungsschiessen | Testing apparatus |
| Pille | Pill; pellet; primer | Puffer | Proof; test; testing; assay; trial; verification; examination |
| Pillenbolzen | Detonator pellet | Pulk | Test firing proof firing |
| Pilz | Mushroom; mushroom head of obturator; small pill-box | Pulver (P) | Buffer; shock absorber |
| Pilzmine | Mushroom land mine | Pulverbrennzünder | Formation (Avn slang); boat-type runner placed under gun wheels for operations in deep snow |
| Pioniertruppe | Corps of Engineers | Pulverbrennzündung | Propellant; powder |
| Pirschbüchse | Stalking rifle; hunting rifle | Pulverbündel | Powder-train ignition fuze (See also Doppelzünder) |
| Pistole (Pist) | Pistol | Pulverfabrik | Powder-train ignition (Fz) |
| Pistolpulver | Pistol propellant | Pulverfüllmaschine | Propellant bag |
| Platte | Plate (Tech); phonograph record | | Explosive plant; powder works |
| | | | Apparatus for charging cartridges with powder |

| | | | |
|-----------------------------|--|--------------------------------|--|
| Riefe | Groove; channel | Rotes Kreuz | Red Cross |
| Riefelung | Channel, groove; cannellure | Rotkreuz | Red cross, (ocr marking on time fuzes of some artillery shells not contg poison gases) |
| Riegel | Bolt; rail; bar | R-Patrone | Smoke-puff cartridge; flash and sound cartridge |
| Riegelblock | Breechblock | Rückdruck | Thrust reaction pressure (Rock) |
| Riegelmine | See R-Mine | Rücklauf; Rückstoss | Recoil |
| Riemen | Strap; sling; belt | Rücklaufbremse | Recoil brake (G) |
| Riffeltrichter | Ribbed funnel | Rücklaufeinrichtung | Recoil mechanism |
| Rille | Cannellure; groove; furrow | Rücklauflos (Rf) | Recoilless |
| Rillenmunition; R-Munition | Rimless cartridge case for ball SA Ammo | Rücklaufloses Geschütz (RfG) | Recoilless gun |
| Ring | Ring; link; band; loop | Rückschlag | Blowback (Ord); back pressure |
| Ringanlage | Ring layer | Rückstoss; Rücklauf | Recoil; kick (Ord) |
| Ringgranate | Ring shell; shell with pre-arranged fragmentation | Rückstossfrei (Rf) | Recoilless |
| Ringkanone | Built-up gun; jacketed gun | Rückstossfreikanone (RFK; RfK) | Recoilless gun |
| Ringpulver (RgP) | Annular or ring propellant | Rückstossfreierwerfer (RfW) | Recoilless launcher |
| Ringrohr | Built up barrel (G) | Rückstossmotor | Recoil-operated automatic weapon |
| Ringstütze | Ring on tripod support | Rührer; Rührapparat | Jet-propulsion engine |
| Rinne | Channel; groove; furrow; gutter | Rumpf | Stirrer; agitator |
| Rippe | Rib; cooling fin of an air-cooled engine | Rundblickfernrohr (RbLF) | Trunk; torso; fuselage (AC) |
| Rittmeister | Captain (Cavy) | Runde | Panoramic telescope |
| R-Mine; Riegelmine | Cross bar land mine | Rundfunktender | Tour; round; circle; curve |
| R-Munition | See in descriptive part. under R | Rundgeschoss | Radio broadcasting station |
| Röchlinggranate (RöGr) | Rye | Rundkopfgeschoss | Round bullet |
| Roggen | Pig iron | Russ | Round nose bullet |
| Roh Eisen | Crude oil | Rüstung | Soot; lampblack |
| Rohöl | Tube; pipe; gun barrel | Rüstungswerk | Armament; equipment |
| Rohr (R; Ro) | (See also Lauf and Geschützrohr) | rütteln | Armament plant; war-plant to shake; jolt |
| Rohrabnutzung | Erosion of the bore | S | |
| Rohrbreite | (See also Ausbrennung des Rohres) | Säbel | Saber; sword |
| Rohrbremse; Rücklaufbremse | Caliber (See also Kaliber) | Sachindex; Sachregister | Subject index |
| Röhre (R; Ro) | Tube brake; recoil brake (G) | Sack | Bag; sack; pouch |
| Röhrenlafette | Tube (radio); nozzle; spout; duct | Saft | Juice; electric current |
| Röhrenpulver (RP) | Tubular mount (G) | Sägemehl | Sawdust |
| Rohrfrei (Rf; R frei) | Tubular (perforated) propellant | Salmiak | Sal ammoniak; Am chloride |
| Rohrriener; Rohrseele | Empty gun barrel | Salpeter | Saltpeter; K nitrate; niter |
| Rohrkarre | Bore of a gun | Salpetergrube | Saltpeter mine |
| Rohrladung Stahl, 3kg | Tube carriage | Salpeterhütte | Niter works |
| Rohrmantel | Bangalore torpedo, 3 kg in steel pipe (See also in Rohr gefüllte Reihenladung and gestreckte Ladung) | Salpetersäure | Nitric acid |
| Rohrmündung | Gun tube jacket | Salpeterschwefelsäure | Mixture of nitric and sulfuric acids; mixed acid |
| Rohrrücklauf | Muzzle of a gun | Salpetrige Schwefelsäure | Nitrosylsulfuric acid |
| rohrsicherer Zünder | Barrel recoil (G) | Salvenfeuer | Salvo (or volley) fire |
| Rohrsicherheit des Zünders | Bore-safe fuze | Salvengeschütz | Automatic gun |
| Rohrweite; Kaliber | Bore-safety of fuze | Salz | Salt |
| Rohrzange | Caliber | Salzkartusche | Flash-reducing wad (lit Salt cartridge) |
| Rohrzerspringer | Pipe wrench; | Salzsäure | Hydrochloric acid; |
| Rohstoff | Stillson wrench | Salzvorladung; Salzvorlage | muriatic acid |
| Rolle | Premature in a gun barrel | Sammler (batterie) | Flash-reducing wad contg some salts |
| Rollenbombe | Raw material | Sandbad | Storage battery |
| Röntgenstrahlen; X-Strahlen | Roller; roll | | Sand bath |
| Rost | Rolling mine | | |
| rostfrei | X-rays | | |
| | Rust; grate; grill | | |
| | noncorrosive; stainless | | |

| | | | |
|------------------------|---|---------------------------------------|---|
| Sandpapier | Sand paper | Schiessen | Gunnery |
| Sandprobe | Sand test; dust test | schiessen (schooss, geschossen) | to shoot; fire |
| Satan (Bombe) | Nickname for 1800 kg GP-HE Bomb, called in Ger SC 1800 Satan (TM 1985-2, p 12) | Schiessplatz; Waffenprüfungsstelle | Proving ground; artillery range |
| Sättigung | Saturation; satisfaction | Schiesspulver | Gunpowder |
| Satz | Set; composition; unit; deposit; sediment; pellet | Schiess-stock (am Granatwerfer) | Rifle grenade rod |
| Satzpille | Pellet primer | Schiess-stoffwesen | Powder business; all that concerns propellants and explosives |
| Satzring | Time train ring (TiFz) | Schiesswesen; Schiesslehre | Gunnery; Ballistics (See also Artilleriewesen) |
| Satzstück | Black powder pellet (TiFz); fuze composition disk | Schiesswollpulver | Guncotton propellant |
| sauer | acidic; sour | Schiff | Ship; vessel |
| Sauerstoff | Oxygen (lit Sour substance) | Schiffbauwerft; Schiffwerft | Shipyards |
| Sauerstoffträger | Oxidizer (lit Oxygen carrier) | Schiffskanone (SK) | Naval gun |
| Säule | Column; pile; pillar | Schild | Shield; label; signboard |
| Säure | Acid; sourness; acidity | Schirm | Screen; umbrella; parachute; cover (See also Fallschirm) |
| Säuremesser | Acidimeter | Schirm Lafette | Gun mount protected with a shield |
| S-Boot | See Schnellboot | Schlacht | Battle |
| Schabe | Scraper; grater | Schlachtfliegerbombe | Fragmentation bomb carried by a fight plane |
| Schablone | Stencil; template; model; pattern | Schlachtflotte | Battle fleet |
| Schacht | Shaft (mining); bomb rack | Schlacke | Slag; cinder; clinker (in coal) |
| Schachtel | Box; case | Schlag | Shock; stroke; blow |
| Schaft | Shaft; stock; handle | Schlagbolzen | Firing pin; inertia striker pellet (Fz) |
| Schale | Dish; basin; bowl; husk; bark | Schlagempfindlichkeit | Sensitivity to shock (to blow or to impact) |
| Schall | Sound; ring; resonance | Schlagfeder | Striker spring (Fz) |
| Schalldrücker | Silencer (Ord); muffler | Schlagladung | Booster charge; magazine charge (Fz) |
| Schallwellen | Sound wave | Schlaglot | Hard solder |
| schalten | to insert; shift; switch | Schlagrohre | Percussion tube; friction tube (primer) |
| scharf | sharp; pointed; acute; armed; primed; live (Ammo) | Schlagstift | Striker (Fz) |
| scharfe Munition | Live ammunition; service ammunition | Schlagversuch; Schlagprobe | Impact test; percussion test |
| scharfe Panzermine | Activated A/T mine | Schlagwetter | Firedamp |
| scharfe Patrone | Live cartridge; ball cartridge | schlagwettertaucher | Safe against firedamp |
| scharfgeladene Granate | Live shell | Schlagwetterversuchsstrecke | Testing gallery |
| scharfmachen; | to arm (Ammo); to activate | schlagwetterzündfähig | ignitable by firedamp |
| scharfstellen | a mine; to fuze a shell | Schlagzünder | Impact fuze; percussion fuze |
| Scharfschütze | Sharpshooter; sniper | Schlagzündschraube | Threaded percussion primer |
| Scharfschützengewehr | Sharpshooter's rifle | Schlamm | Mud; sludge; slime; slurry |
| Scharnier | Hinge; joint | Schlange | Snake; coil; hose (flexible tube); spiral |
| Schaufel | Shovel; scoop; paddle; blade | Schlauch | Tube; tubing; pipe (flexible); hose |
| Schaum | Foam; froth; scum; lather | Schlauchboot | Pneumatic raft |
| Scheibe (Schb) | Disk; plate; practice target; pane (of glass) | Schlauchklemme | Tube clamp |
| Scheibenpulver | Disk propellant | Schleifmittel | Abrasive |
| Scheibenwischer | Windshield wiper | schleppen | to tow; drag |
| Scheide | Scabbard; sheath | Schlepper | Tractor; tug |
| Scheinmine | Dummy mine | Schlepptorpedo | Towed torpedo |
| Scheinwerfer | Searchlight; projector; spotlight; headlight | Schleuder | Centrifuge; sling; catapult |
| Scherdraht | Shear wire | Schleuderguss | Centrifugal casting (foundry) |
| Schere | Shears; scissors | Schleudermachine; | Centrifugal machine; |
| Scherfestigkeit | Shearing strength | Abachleuder-machine | catapult |
| Scherplatte | Shear plate | Schleudermine | Sling mine; sliding mine |
| Scherstift | Shear pin | Schleuderstart | Catapult take-off (Avn) |
| Schiedsrichter | Umpire (maneuvers) | | |
| Schiefer | Slate; schist; shale | | |
| Schiene | Rail; strip; surgical splint | | |
| Schiensbaumwolle; | Guncotton | | |
| Schiesswolle | | | |
| Schiessbecher | Rifle grenade launcher (discharger) | | |

| | | | |
|---|---|--|---|
| Schlieren (pl) | Streaks; striae; schlieren (regions of varying refraction, as in liquids and gases) | Schreck Schreckladung; Schreckmine | Fright; terror Booby trap; booby mine (See also Sprengfalle) |
| Schliff | Grinding; sharpening | Schrot | Shot (for shotgun); pellet; cut; piece |
| Schlitten | Sled, sleigh; sleigh mount; sliding carriage (G) | Schrotgewehr Schrotpatrone Schuh | Shotgun Shotgun shell Shoe; SA scabbard or holster |
| Schlitz | Slit; slot; fissure | Schulbombe | Training bomb; dummy bomb |
| Schloss | Lock; bolt mechanism; castle | Schuld | Debt; fault; blame |
| Schlot; Schlotte | Smoke stack | Schü-Mine | Same as Schützenmine |
| Schlüssel | Key; wrench; cipher code | Schuppe | Scale; flake |
| Schlüsselgraben | Main trench | Schuss | Shot (discharge of a fire- arm); round of ammunition; blast |
| Schlüsselmine | Antivehicle mine laid as road block (lit Key mine) | Schussbeobachtung | Observation of fire (Arty); spotting |
| Schmalspurbahn | Narrow-gage rail ad | Schussbereich | Range of gun; danger zone |
| Schmelzpunkt | Melting point | Schussfolge | Rate of fire |
| Schmier | Fat; grease; suet | Schusstafel | Range table; firing table |
| Schmiergel | Emery | Schussversager | Dud; miss |
| Schmetterling | Butterfly (nickname of a guided missile) | Schusswaffe | Firearm |
| schmiedbar | malleable | Schussweite | Range (See also Entfernung) |
| Schmiede | Forge; smithy | (grösste Schussweite) | (Maximum range) |
| Schmiedeeisen; geschmie- detes Eisen | Wrought iron; forged iron; | Schusswinkel | Firing angle |
| Schmiermittel; Schmierstoff | malleable iron | Schütteltrichter | Separator funnel |
| Schmieröl | Lubricant | Schüttkasten | Container with a number of small bombs; "Molotov Breadbasket"; bomb maga- zine |
| Schmierung | Lubricating oil | Schütz | Relay (Elec) |
| Schmirgel | Lubrication | Schütze | Private (infy); rifleman; sharpshooter |
| Schnabel | Emery | Schützengrabenkanone | Trench gun; trench mortar |
| Schnalle | Beak; bill; nozzle; nose | Schützenhöhle | Dugout; foxhole |
| Schnalle | Buckle; clasp; gungling hook | Schützenmine (SchüMi; S-Mi) | Antipersonnel mine (See descriptive part) |
| Schnauze | Snout; mouth; nose; nozzle; spout | Schützenpanzerwagen (SPW; SPzWg) | Multipurpose armored car (used for carrying troops or equipment) (See also under Panzer) |
| Schnecke | Worm (Mech); endless screw; spiral | Schutzfeder (SF) | Protective spring; safety spring |
| Schneckentrieb; Schneckenrad | Worm gear | Schutzglas | Bulletproof glass |
| Schnecke | Snow chain; skid chain | Schutzschild | Protective shield |
| Schneekette | Boat-type runner placed under gun carriage wheels for opera- tions in deep snow | Schutzstaffeln (SS) | Elite guard of the Nazi party |
| Schneewanne | Edge (of a knife, bayonet, etc) | Schutzwall | Protective wall (system of land defenses, such as Westwall) |
| Schneide | Cutter; Tailor | Schwaden | Suffocating vapor or ex- halation; gas cloud; noxious gases; detonation products |
| Schneider | Motor torpedo boat; PT-Boat; | Schwadron | Troop (Cavy) |
| Schnellboot; S-Boot | E-Boat | schwängern | to impregnate; saturate; inseminate |
| Schnellfeuergeschütz | Rapid-fire gun; quick-firing gun | Schwankung | Fluctuation; variation; oscillation |
| Schnellfeuerkanone | Rapid-fire cannon; quick- firing cannon | Schwarz | Tail; trail (G) |
| Schnell Ladekanone | Rapid loading gun | Schwarzkreuz | Black cross (Ger marking for diphenylcyanarsine) (CWS) |
| Schnell Ladverschluss | Rapid loading breechblock | Schwarzpulver | Black powder |
| Schnell Ladung | Emergency demolition charge | Schwebe | Suspension; sling |
| Schnell Lot | Soft solder | schwedisch | Swedish |
| Schnellzünder | Instantaneous fuze; nondelay fuze (See also empfindlicher Zünder) | | |
| Schneppe | Spout; snout; nozzle; lip | | |
| Schnitt | Cut; slice; section; intersection | | |
| Schnur (See also Züandschnur) | Rope; cord; twine; string | | |
| schrag | oblique; sloping; inclined | | |
| Schräglinie | Diagonal | | |
| Schrank | Cabinet; case; closet; cupboard | | |
| Schrapnell (S; Schr) | Shrapnel | | |
| Schrapnellmine (S-Mi; SchrMi) | Antipersonnel mine (lit Shrapnel mine) (See also Schützenmine) | | |
| Schraube | Screw; propeller | | |
| Schraubenflugzeug | Helicopter | | |
| Schraubenmutter | Nut (Tech) | | |
| Schraubenschlüssel | Wrench | | |
| Schraubenzieher | Screw driver | | |
| Schraubkappe | Screw cap | | |
| Schraubstock | Vise (Tech) | | |

| | | | |
|----------------------------------|--|----------------------------------|---|
| schwedisches Hölzchen | Safety match (lit Swedish match) | Selbstfahrlafette (Sf; Sfl) | Self-propelled (SP) mount; gun motor carriage (See also under Panzer) |
| Schwefel | Sulfur | (Geschütz auf Selbstfahrlafette) | (Self-propelled gun) |
| Schwefelantimon | Antimony sulfide (Sb ₂ S ₃) | Selbstladeeinstecklauf | Subcaliber barrel for semi-automatic weapon |
| Schwefelsäure | Sulfuric acid | Selbstladegewehr | Semiautomatic rifle; self-loading rifle |
| Schwefeltrioxide | Sulfur trioxide (CWS) | Selbstladepistole | Semiautomatic pistol; self-loading pistol |
| Schwefelwasserstoff | Hydrogen sulfide | Selbstlader; Selbstladewaffe | Semiautomatic weapon; self-loading weapon |
| Schwefligsaure; schweflige Säure | Sulfurous acid | Selbstschrimpung | Self-shrinkage |
| schweißen | to weld; sweat | Selbstverbrennung | Self-destroying type of fuze |
| schwelen | to burn slowly; smolder | Selbstzersetzung | Spontaneous decomposition |
| Schwelkerze | Smoke candle (CWS) | Selbstzündung | See Selbstentzündung |
| schwellen | to swell; distend | Sender; Sendegerät | Radio transmitter |
| Schwemmstein | Pumice stone | Sendung | Shipment; transmission (Rad) |
| schwer | heavy | Senfgas; Yperit | Mustard gas (CWS) |
| schwere Artillerie (sA) | Medium artillery (lit Heavy artillery) | senkrecht | vertical; perpendicular |
| schwere Haubitze (sH) | Medium howitzer (lit Heavy howitzer) | Senkung | Sinking; lowering; hollow; depression |
| schwere Kanone (sK) | Medium gun (lit Heavy gun) | Sensibilität | Sensitivity; sensitiveness |
| schwere Panzerbüchse | Heavy antitank gun | Serienfabrikation | Production in series |
| Schwerkraft | Force of gravity | Sesshafter Kampfstoff | Persistent chemical warfare agent |
| schweres Maschinengewehr | Heavy MG | S-Geschoss | See Spitzgeschoss |
| schwerste Artillerie (sSA) | Heavy artillery (lit Heaviest artillery) | sicher | safe; secure |
| Schwert | Sword | Sicherheitsbottich | Safety tank; drowning tank |
| Schwimmweste | Mac West; life vest | Sicherheitsdraht | Safety wire (Ord) |
| Schwingung; Schwung | Vibration; oscillation | Sicherheitsglas | Safety glass; shatterproof glass |
| schwirren | to whizz; buzz; centrifuge | Sicherheitsminenpulver | Safety blasting powder |
| Schwunggewicht | Pendulum | Sicherheits Sprengstoff | Safety explosive |
| Schwungkraft | Vibrating power; centrifugal force | sichern | to make safe; lock (Ord and Ammo); cover; protect; make secure |
| Schwungmaschine | Centrifuge | Sicherungskappe | Safety device (Fz); safety cap (HdGr) |
| Schwungrad | Flywheel | Sicherungsklappe | Safety valve; safety hatch |
| See-fliegerei; Seeflugwesen | Naval aviation | Sicherungsmutter | Lock nut |
| Seeflugzeug | Seaplane; hydroplane | Sicherungsstift | Safety pin (Fz) |
| Seele | Bore (of a gun) | Sicherungsvorstecker | Arming pin (Fz); safety pin (B) |
| Seelenachse | Axis of the bore | Sicherungszünder | Safety fuse |
| Seelendurchmesser; Seelenweite | Diameter (caliber) of the bore (See also Kaliber) | Sicht | Sight; visibility |
| Seelenlänge | Gun barrel length | Sichtfeld | Field of view |
| Seelenrohr | Tube; liner (of a gun) | Sieb | Screen; sifter; filter |
| Seemeile | Nautical mile (1.853 km) | Siedepunkt | Boiling point |
| Seemine | Sea mine; underwater mine; submarine mine | Siegfried Kanone | 380 mm Railway Gun (See under Weapons) |
| Seeminensperr | Submarine mine field | Signal bombe | Signal flare |
| Seezünder | Hydrostatic bomb fuze (in depth charges) | Signalpatrone | Signal cartridge |
| Segelflugzeug | Glider; sailplane | Signalrakete | Signal rocket |
| Segler | Sailboat; glider | Signalwerfer | Ground signal projector |
| Segmentgranate | Segmented shell | Siliziumtetrachlorür | Silicon tetrachloride |
| Schrohr | Periscope; telescope (lit Seeing tube) | Sinkstoff | Deposited matter; sediment |
| seigern | to exude | Sipo (Sicherheitspolizei) | Security police |
| Seite | Side; face; direction (Guns) | SM; S-Mine; SchüMi | See Schrapnellmine and Schützenmine |
| Seitenfeuer | Enfilade fire | S-Mine Verbindungstück, Drilling | Three-way adapter for S-Mine |
| Seitengewehr | Bayonet (lit Side arm) | Sockellafette (Sk) | Pedestal mount (G) |
| Seitenverschiebung | Drift correction | Sog | Suction |
| Seitenwagen | Sidercar | | |
| Seitwärtsbewegung | Yawing (See also Pendeln des Geschosses) | | |
| Sekundärladung | Secondary charge; base charge (of a detonator) | | |
| Selbstentzündung; Selbstzündung | Spontaneous ignition | | |

| | | | |
|---|--|---|---|
| soggen | to crystallize out; precipitate | Spitzgeschoss mit Stahlkern (gehärtet) [SmK (H)] | Pointed bullet with hardened steel core; super AP bullet |
| Sohle | Sole; bottom of a trench | Spitzgeschoss mit Stahlkern und Glimmspur (SmK-GI'spur) | Pointed bullet with steel core and tracer |
| Soldat | Soldier | Spitzgeschoss mit Stahlkern und Leuchtspur (SmKL'spur) | Pointed bullet ammunition |
| Solvens (pl. Solvenzien) | Solvent | Spitzmunition (S'fu) | Splice |
| Sonder | Separate; special; exclusive | Spleissung; Splissung | Splint |
| Sonderartillerie | Heavy artillery (lit Special artillery) | Splint | Splint; cotter pin; split pin |
| Sondergerät (SGer) | Device serving a special purpose | Splitter; Sprengstück | Splinter; fragment (Proj) |
| Sonderkartusche (SKart) | Special propelling charge in non-fixed ammunition; super-charge cartridge | Splitterbetonbombe (SplBeß) | Concrete fragmentation bomb |
| Sonderkraftfahrzeug (SdKfz) | Specialized vehicle, such as tank, tank destroyer, etc (See also under Panzer) | Splitterbombe (SplB) | Fragmentation bomb; A/P (antipersonnel) bomb |
| Sonderladung; Ausnahme-ladung | Super-charge | Splitterdichte | Density of fragments (number of shell fragments per unit area) |
| Sondermunition (Smu; SdMu) | Non-fixed ammunition, special purpose ammunition | Splittergranate (SplGr) | Fragmentation shell; grenade |
| Sonderwaffe (SdW) | Special purpose weapon | Splitterring | Fragmentation sleeve fitting over casing of the Stielhandgranate (lit Splitting ring) |
| Spähwagen (SpWg) | Scout car; reconnaissance vehicle | Splitterschutzbrille | Protective goggles |
| Spak | See under Ger Abbreviations | splintersicher | splinterproof |
| Spalt; Spalte | Crack; split; slit; fissure | Spom | Trail spade (G); spike (MG tripod) |
| Spaltanlage | Cracking installation; splitting device | Sprachrohr | Megaphone |
| Spaltanlage zur Gewinnung von Oleum aus Rücksaure | Installation for recovering oleum from spent acid by splitting process | Spreizlafette | Split trail spade carriage |
| Spaltfunkzünder | Jump-spark electric igniter | Sprengarbeit | Blasting job |
| Spaltglühzünder | High-tension electric igniter | Sprengbombe (SB; SprB) | HE bomb; demolition bomb |
| Spaltring | Split ring (breachblock) | Sprengbombe, dickwandige | HE bomb, thick-walled |
| Spaltzünder | High-tension detonator | Sprengbrandbombe (SprBrB) | HE-Inc bomb |
| Spaltzündermaschine | Exploder for high-tension detonator | Sprengbüchse | Demolition charge in a container; petard |
| Spannvorrichtung | Cocking mechanism | Sprengbüchse 02/24 | Demolition charge consisting of a box containing 1 kg TNT |
| Sparstoff | Scarce material; high priority material | Sprengdienst (Sd) | Demolition service to blast |
| Spartgras | Esparto grass | sprengen | to blast |
| Spätzerspringer | Retarded burst; delayed action projectile | Sprengfalle | Booby trap (See also Schreckladung) |
| Spätzünder; Verzögerungs-zünder | delay fuze | Sprengfüllung | Filler; HE filling charge |
| Spätzündung | Retarded ignition | Sprengflüssigkeit | Explosive liquid |
| Speer | Spear | Sprenggelatine; Sprenggummi | Blasting gelatin |
| Sperrballon | Barrage balloon | Sprenggranate (Sprgr) | HE shell |
| Sperrre | Block; obstacle; barrier | Sprenggranate 41 (Sprgr 41) | HE shell pattern 41, for a tapered bore gun |
| Sperrfeuer; Notfeuer | Barrage fire; barrage | Sprenggranate-Patrone (SprgrPat.) | HE shell in a cartridge; (complete round of fixed ammunition) |
| Sperrholz | Plywood | Sprenggummi | See Sprenggelatine |
| Sperrrohr | Outer steam tube of MG | Sprengkammer | Mine chamber (blasting) |
| Sperrversuchsanstalt (VA) | Naval establishment working on development and testing of sea mines | Sprengkapsel | Detonator; blasting cap; initiator |
| spezifisches Gewicht | Specific weight | Sprengkapsel Nr 8 (A1) | Detonator No. 8 (Alum. am) |
| Spiegel | Mirror; periscope; stern (of a ship) | Sprengkapselzünder (7.5, 10, 25 Sekunden) | Detonating cord unit with blasting cap and fuse lighter; prepared demolition set |
| Spiegeltelegraph | Heliograph | Sprengkapselzünder 28 (kurz) | Prepd demolition set with delay 100 sec |
| Spiegelvisier | Mirror sight | Sprengkapselzünder 28 (lang) | Prepd demolition set with delay 200 sec |
| Spindel | Spiral; pinion; gear shaft | Sprengkörper | Demolition block; prepared charge |
| Spiralbohrer | Twist drill; spiral drill | Sprengkörper 28 | Demolition slab, 200 g |
| Spiralfeder | Spiral spring; helical spring | Sprengkörper 88 | Demolition charge consisting of a box containing 200 g picric acid |
| Spitze (S) | Point; tip | | |
| Spitzgeschoss (S; SGesch) | Pointed bullet | | |
| Spitzgeschoss mit Eisenkern (SmE) | Pointed bullet with iron core; SAP bullet | | |
| Spitzgeschoss mit Stahlkern (SmK) | Pointed bullet with steel core; AP bullet | | |

| | | | |
|-------------------------------|--|---------------------------------|---|
| Sprengkörper, Tp | Demolition slab, 200 g in bake- lite container (for tropical climates) | Stahlblechpanzer | Steel plate; sheet steel armor |
| Sprengkraft | Explosive force | Stahlgeschoss; Stahlgranate | Light case shell of cast steel |
| Sprengladung (Sprgldg) | Bursting charge; demolition charge; blasting charge | Stahlguss | Cast steel |
| Sprengladungstohre | Burster tube (Proj) | Stahlhelm | Steel helmet |
| Sprengloch | Blast hole | Stahlhütte; Stahlwerk | Steel works |
| Sprengluft | Liquid-air explosive; oxyliquit | Stahlkerngeschoss | Steel-core bullet; armor- piercing bullet |
| Sprengmittel | Explosive in prepared form, as distinguished from generic term | Stahlmantelgeschoss | Steel-jacketed bullet |
| Sprengmittelkasten Satz | Sprengstoff; HE demolition charge | Stahlmörser | Steel mortar |
| Sprengmunition | HE charges and accessories | Stahlpanzer | Steel armor |
| Sprengmunition 02 | Explosive ammunition | Stahlseele | Steel liner (G) |
| Sprengmunition 88 | Trinitrotoluene (TNT) charge | Stahlspitzengeschoss | Steel pointed bullet |
| Sprengniete | Picric acid (PA) charge | Stahlweike | Steel foundry |
| Sprengöl | Explosive rivet | Stalag (Stammlager) | Prisoner of war camp for NCO's, privates and labor detachment |
| Sprengölpulver | Nitroglycerin (NG); detonating oil | Stammkörper; Stammsubstanz | Parent substance |
| Sprengpatrone | NG propellant; double base (NG-NC) propellant | Standort | Post; garrison; station; position |
| Sprengpatrone Zerstörer | Blasting cartridge (demolitions); explosive bullet | Stange | Pole; post; pillar; bar; rod |
| Sprengpulver | Gun destructor charge | Stangenkugel | Crossbar shot; double- headed shot |
| Sprengsalpeter | Blasting powder; black powder | Stangenladung | Pole charge (See general section) |
| Sprengsatz | Nitrate explosive | Stangenladung | Pole-charge antipersonnel mine |
| Sprengschlag | Bursting charge; explosive filler | Stapel | Staple; warehouse; pile; launching cradle |
| Sprengschnur | Explosion | Stärke | Starch; strength; thickness |
| Sprengstoff | Fuse (lit Explosive cord) | Startkatapult | Catapult |
| Sprengstoffart | Explosive; HE (See also Spreng- mittel) | Startvorrichtung | Launching device |
| Sprengstofffüllung | Type of explosive | Stativ | Stand; support; tripod |
| Sprengstoff, Lose | HE filler (Ammo) | Staub | Dust |
| Sprengstoffwesen | HE bulk | Staubpulver (StbP) | Finely granulated powder to compress (by blow); knock |
| Sprengstück | Subject of explosives; all that con- cerns explosives | stauchen | to compress (by blow); knock |
| Sprengtechnik | See Splitter | Stauchlafette | Retractable (telescopic) gun carriage |
| Sprengtrichter | Technics of manufacture of explo- sives; technics of demolitions | Stauchprobe | Compression test; crusher test |
| Sprengung | Mine crater | Stauchzylinder | Crusher cylinder |
| Sprengwirkung | Demolition; blasting | Stearinsäure | Stearic acid |
| Sprengzünder | Explosive effect; bursting effect | stechen | to stick; prick; pierce; puncture |
| springen | Detonating fuse; primacord | stecken | to stick; stay; remain |
| Spritzdüse | to burst; break; crack | Stecker | Plug (Elec) |
| Spritzform | Injection nozzle; steam injector | Steckzünder 40 | Inserted rocket igniter, pattern 40 |
| Spritzguss | Injection mold; jet mold | steil | steep |
| Spritzgussmasse | Injection molding; die casting | Steilbahn | High-angle trajectory |
| Spritzweire | Injection molding composition | Steilfeuer | High-angle fire; curved fire |
| Spule | Range (of flamethrower) | Steilfeuergegeschütz (Haubitze) | Howitzer (lit High-angle fire gun) |
| Spülung | Spool; electric coil | Stein | Stone; rock |
| Spur | Rinsing; washing; flushing | Steinbruch | Quarry |
| Spur (S); Leuchtspur (L'spur) | Trace; track; trail | Steinflachs | Asbestos |
| Spurgeschoss | Tracer | Steinkohle | Mineral coal; anthracite |
| SS | Tracer projectile | Steinkohlenpech | Coal tar |
| SS-Panzerkorps | See Schutzstaffeln | Steinschlossgewehr | Flintlock gun |
| Stab | SS armored corps | Stellmutter | Lock-nut; regulating (adjust- ing) nut |
| Stabbrandbombe | Staff; rod; bar | Stellring | Adjusting ring (Fz); time- setting ring |
| Stäbchenpulver (StbP) | Stick-type incendiary bomb | Stellachlüssel | See Stellstift |
| Stabilität | Chopped tube propellant | Stellschraube | Set screw; adjusting screw |
| Stabmine | Stability (See also Beständigkeit and Haltbarkeit) | | |
| Stachelbombe (Stabo) | Stick mine | | |
| Stacheldraht | Bomb with long nose spike (See description) | | |
| Staffelfeuer | Barbed wire | | |
| | Echelon fire | | |

| | | | |
|--|--|---------------------------------------|---|
| Stellstift; Stell- schlüssel (St) | Fuze setter | Streichholz; Streich- zündhölzchen | (Friction) match |
| Sternbündelpatrone | Star cluster cartridge (signal); multiple star cartridge | Streifen | Band, strip; stripe; belt; sector |
| Sternpulver (StP) | Star-shaped propellant | Streifenlader | Magazine clip (Rf) |
| Sternsignal | Signal flare; star signal | Streifenpulver (StrP) | Strip (band or lamellar) propellant |
| Steuer | Control; steering wheel; tax | Streit | Contest; combat; strife; dispute |
| Steuerflügel | Stabilizing fin (B) | Srenglot | Hard solder |
| Steuerung | Steering | Streubrandbombe | Scatterfire bomb |
| Stich | Thrust; stab; sting | streuen | to scatter; strew; cover with zone fire (Arty) |
| Stichprobe | Sample taken at random | Streufeuer; Streungsfeuer | Zone fire (Arty); sweeping fire |
| Stichwaffe | Thrusting weapon | Streugarbe | Cone of dispersion |
| Stickstoff (N) | Nitrogen | Streukegel | Sheaf of fire; cone of fire; cone of dispersion; cone of spread |
| Stickstoffsäure; Stickstoff- wasserstoffsäure; Stick- stoffwasserstoff | Hydrazoic acid; hydronitric acid; hydrogen trinitride (HN ₃) | Streu mine | Uncontrolled mine; stray mine (not laid to regular pattern) |
| Stiefel | Boot; case; barrel | Streuung | Dispersion (Ball); scattering; deviation |
| Stiel | Handle; shaft; stem; stalk | Strichfeuer; bestreichendes Feuer | Grazing fire |
| Stielgranate (Stgr) | Stick grenade; rodged bomb | Strohzellstoff | Straw pulp |
| Stielgranate 41 | 37 mm Rodged bomb for A/T gun, Pak 41 | Strom | Stream; current; flow; elec- tric current |
| Stielhandgranate (Sthgr) | Hand grenade with handle; potato-masher hand grenade | Stromerzeuger | Generator (Elec) |
| Stift | Pin; peg; tack; stag | Stromliniengeschoss | Streamlined bullet; boat- tailed bullet |
| Stimпанzer | Front armor | Strommesser | Ammeter; current meter |
| Stock | Stick; cleaning rod (Rf); picket; pole | Stromstärke | Amperage |
| Stockmine (StoMi) | A/P picket-type mine; stake mine (of concrete) | Stromung | Current; flowing; flood; magnetic flux |
| Stoff | Substance; stuff; fabric; material | Stück; Geschütz | Piece (Arty); gun; cannon |
| Stofflehre | Seme as Chemie | Stufe | Step; stage; degree; rank |
| Stollen | Gallery; tunnel | Stuka (Sturzkampfflugzeug) | Dive fighter bomber |
| Stolperdraht | Trip wire | Stukafliieger | Dive fighter bomber pilot |
| Stolperdrahtfeld | Field of trip wire obstacles | Stumpf | Stump |
| Stolperdrahtmine | Trip wire mine | stumpfer Winkel | Obtuse angle |
| Stopfbüchse | Gland; stuffing box | Sturm (Stu) | Assault; storm |
| Stör | Liaison airplane | Sturmartillerie (StuA) | Assault artillery |
| stören | disturb; trouble; harass | Sturmgeschütz (StuG) | Assault gun (SP G) |
| Störungsfeuer | Harassing fire (Arty) | Sturmgewehr 44 (StuG 44) | Stormtrooper's rifle (previously called Maschinenpistole 44) |
| Stoss | Impulse; thrust; shock; blow; push | Sturmkanone (StuK) | Assault cannon (SP) |
| Stossdämpfer | Bumper | Sturm mortar (StuMrs) | SP Assault rocket projector (See under Panzer) |
| Stössel | Pestle; rammer; tapper (Fz) | Sturmpanzer (StuPz) | Assault tank; front line support armored vehicle supplying over- head fire power (See also under Panzer) |
| Stossempfindlichkeit | Sensitivity to shock (Exp!) | Sturmwind | Storm wind |
| Stossempfindlichkeitsprobe | Test for sensitiveness to shock | Sturz | Plunge; dive; fall |
| stossen | to push; thrust; strike | Sturzangriff | Diving attack |
| Stosskappenmine; Stossmine | Contact mine (Nav) | Sturzbomben | Dive-bombing |
| Stosskraft | Percussive power, impact | Stürze | Lid; cover |
| stossreizbar; stossempfindlich | sensitive to shock | Sturzflamme | Reverberatory flame |
| stoss-sicher | insensitive to shock | Sturzflug | Dive |
| Stossversuch | Shock test (Expl) | Sturzkampfflugzeug (Stuka) | Dive bomber |
| Stosswaage | Ballistic pendulum | Stütze | Support; stay; prop |
| Stosswelle | Shock wave; percussion wave | Stützschraube (StzSe) | Support screw |
| Stosszylinder | Percussion fuze | Stuvi (Sturzvisier) | Dive Bombing sight |
| Strahl | Ray; jet (of liquid or gas); flash (of lightning) | | |
| Strahlung | Radiation; radiance | | |
| Strandmine (SdMi) | Beach mine; shore mine | | |
| Strecke | Distance; space; stretch; drift (Mining) | | |
| strecken | to stretch; extend; flatten; roll (metal, glass) | | |
| Streckstahl | Rolled steel | | |
| streichen | to cross out; strike out; eliminate | | |

| | | | |
|---------------------------------|---|--------------------------------|---|
| Treibmine | Floating mine; an anchored automatic contact mine | Übertrommel | Rauge drum (sight mount) |
| Treibmittel | Propulsive agent | Überwachung | Surveillance; observation; policing |
| Treibpulver | Propellant; propellent powder | Überwasserstreitkräfte | Surface forces (Nav) |
| Treibspiegel | Sabot disc | U-Boot (Unterseeboot) | U-boat; submarine |
| Treibspiegelgeschoss | Sabot projectile (lit Disc projectile) | U-Boot-Bunker | Submarine pen |
| Treibsprengstoff | Propellant | U-Boot-Jäger | Submarine chaser |
| Treibstoff | Eagine fuel | U-Bootkrieg | Submarine warfare |
| Trennungverfahren | Separation process | U-Boot-Mutterschiff | Submarine tender |
| Trennungvorgang | | U-Bootnetz | Submarine net |
| treten | to step; tread; pass; enter | U-Boot-Werft | Submarine construction yard |
| Tretmine | Tread mine; pressure-ignited A/P mine | Übung | Practice; exercise; training; drill |
| Trichter | Funnel; crater; cone | Übungsbombe | Practice bomb; dummy bomb |
| Trichterfeld; Trichtergelände | Terrain pitted with shell craters | Übungsgeschoss | Training projectile; target-practice projectile; drill projectile |
| Trichterladung | Crater charge | Übungsgranate | Practice shell |
| Trichtermine | Funnel mine | Übungshandgranate | Practice hand grenade |
| Trichterwirkung | Mine effect | Übungsladung | Practice charge (Ammo) |
| Triebkraft | Motive power | Übungsmine | Practice mine |
| Treibwerk | Power plant | Übungsmunition | Practice ammunition |
| Trilit | Trinitrotoluene (TNT) | Übungspatrone | Practice cartridge |
| Tripelerde; Trippelerde trocken | Tripoli dry | Übungsschiessen | Practice firing |
| Trockner | Drier | Uhr | Watch; clock; timepiece |
| Trog | Trough; vat | Uhrwerkantrieb | Clockwork action (Fz) |
| Trommel | Drum; cylinder of a revolver | Uhrwerkzünder | Clockwork fuze |
| Trommelfeuer | Drum fire; heavy barrage (Arty) | Uhrzeiger | Clockhand; indicator (instruments) |
| Trommelmagazin | Drum (cylinder) magazine | (im Gegengsinn zum Uhrzeiger) | (Counterclockwise) |
| Trommelmagazinzuführung | Drum feed | Uhrzeit | (Clockwise) |
| Tropen (Tp) | Tropics | (im Sinne des Uhrzeigers) | Clocktime (such as 13 45 as distinguished from Zeit, which means "time length") |
| Tropfenflasche; Tropfflasche | Dropping bottle | Ultrageschoss | High-speed bullet |
| Tropftrichter | Dropping funnel | Ultrakurz welle | Ultrashort wave; ultra-high frequency wave (30 mc to 300 mc) |
| Trotyl | Trinitrotoluene (TNT) | Umänderung | Conversion; change |
| Trübungsgad | Degree of turbidity | Umdrehungszahl | Number of revolutions; rpm |
| T-Stoff | See Tränenstoff; highly concentrated (80-85%) hydrogen peroxide | Umfang | Circumference, perimeter; scope |
| U and Ü | | | |
| üben | to practice; exercise; train | umfassen | to embrace; comprise; envelop |
| Überborsäure | Perboric acid | Umformer | Converter (Elec) |
| Überchlorsäure | Perchloric acid | umgeändert; umgearbeitet (umg) | Modified; converted; reworked |
| Überchromsäure | Perchromic acid | Umkreis | Perimeter; radius; circumference |
| Überdruck | Excess pressure; pressure above 1 atm | umkristallisiert | recrystallized |
| Überführungszahl | Transport (transference) number | umlaboriert | equipped; outfitted |
| überhitzen | to superheat (steam); overheat (engine) | Umlauf | Rotation; revolution; circulation |
| Überhitzer | Superheater | Ummantelung | Jacket; envelope; sheath |
| Übersalpetersäure | Pernitric acid | Umrandenmaschine | Crimping machine |
| übersättigen | to supersaturate | Umrandung | Edge; border |
| Überschiessen (eigener Truppen) | Overhead firing | umrühren | to stir; stir up |
| überschweres Maschinen-gewehr | Superheavy machine gun | Umschalter | Switch board; reverser; commutator |
| Überschwefelsäure | Persulfuric acid | Umschlagspunkt | Transition point |
| Überstrahlung | Overradiation; overexposure (to radiation) | unbcwaffnet | unarmed |
| übertragen | to transfer; transport; transmit; propagate waves | Unbrennbarmachung | Fireproofing |
| Übertragung | Transmission | undicht | not waterproof or gasproof; permeable; leaky; not tight |
| Übertragungskörper | Induced-detonation charge | | |
| Übertragungsladung | Intermediate charge; booster; communication charge | | |

| | | | |
|-------------------------------|--|---|--|
| undurchdringlich | impermeable; impenetrable | Verbesserung | Correction (Gunny); improvement |
| unendlich | infinite; endless | Verbindung | Compound; ur ² joining; assembly; ali aetal); liaison |
| unentbehrlich | indispensable | Verbindungsstück | Adapter |
| unentzündbar | inert (Ammo) | Verbot | Prohibition; off-limits declaration |
| unerlaubte Entfernung | Absence without leave (AWOL) | Verbrauchssatz | Consumption per 100 kilometers (gas and lubricants) |
| ungefähr | about; approximate | verbleibbar | combustible |
| ungelöschter Kalk | Quick lime | Verbrennung | Combustion; burning; deflagration |
| unscharf | unarmed (Fz); out of focus (Optics) | Verbrennungsanalyse | Analysis by combustion |
| unscharf machen | to disarm (Ammo) | Verbrennungskraftmaschine | Internal combustion engine |
| Unterarzt | Interne; young physician | Verbrennungsraum | Combustion chamber; propellant chamber; powder chamber |
| Unterbrecher | Interruptor | Verbrennungsrückstände | Residues of ignition (or combustion) |
| Unterchlorigsäure | Hypochlorous acid | Verbrennungswärme | Heat of combustion |
| Unterchlorsäure | Hypochloric acid | Verbrennungswert | Calorific power; combustion value |
| Unterdruck | Diminished pressure; vacuum; below atmosphere pressure | Verbundgeschoss (V) | Compound projectile (See Mantelgeschoss) |
| Unterfeldwebel | Staff sergeant | verchloren | to chlorinate |
| Unterführung | Underpass (RR) | verchromt | Chromium plated |
| Unterkalibergeschoss | Sub-caliber projectile | Verdämmen; Verdämmung (See also Besatz) | Tamping; mud capping (Dem); damming up (a stream) |
| Unterkühlung | Supercooling | verdampfen | to evaporate; vaporize |
| Unteroffizier | NCO; corporal | Verdampfungswärme | Heat of vaporization (or evaporative) |
| Unterschied | Difference | verdeckte Zündung | Covered priming |
| Unterseeboot | See U-Boot | Verdichtungsapparat | Condenser |
| unterstützen | to support | Verdichtungsstossquelle; | Compression wave; burst wave; |
| Untersuchung | Investigation; examination; inspection | Verdichtungswelle | detonation wave |
| Untertauchung | Submersion; immersion | Verdickungsmittel | Thickening agent; thickener |
| Unterwachmeister | Staff sergeant (Cavy and Arty) | verdünnen | to thin; dilute (liquids); rarefy (gasses) |
| Unterwasserbombe | Depth charge; depth bomb | verdunsten | to evaporate |
| Unterwasserbrückenzünder | Underwater bridge primer | Verein; Vereinigung | Union; association; society |
| Unterwasserhorchgerät | Hydrophone (Nav) | Vereinheitlichung | Standardization |
| Unterwassernebenschlusszünder | Underwater shunt primer | Vereisung | Formation of ice; icing (Avn) |
| Unterwasserspaltzünder | Underwater split primer | Veresterung | Esterification |
| Unterwassersprengung | Underwater blasting (Dem) | Verfahren | Method; procedure; process |
| Unterwasserzünder | Underwater primer or fuze | Verfall | Decay; deterioration; decline |
| Urbaumuster | Original model; prototype | Verfälschung | Adulteration; falsification; forgery |
| Ursstoff | Primary matter | verfeinern | to refine; improve |
| Urwaldkrieg | Jungle warfare | verfertigen | to make; prepare; manufacture |
| | | verfeuern | to fire; launch; burn up |
| | | verflüchtigen | to vaporize; evaporate |
| | | Verflüchtigungsfähigkeit | Volatility |
| | | verflüssigen | to liquify; dilute |
| | | verfrüht | premature |
| | | Verfügung | Disposal; disposition; availability |
| | | Verfügung des Oberkommandos des Heeres | Army Regulation |
| | | Vergälung | Denaturing |
| | | vergären | to ferment |
| | | Vergaser | Gasifier; carburator |
| V-1, V-2, and V-3 | See Vergeltungswaffe | | |
| V ₂ A | Eins, etc | | |
| Vakuumröhre | Brand of stainless steel | | |
| V-Boot; Verkehrsboot | used in German explosives plants | | |
| Velocitas-Null (Vo) | Vacuum tube | | |
| Ventil | Launch | | |
| Ventildichtung | Initial velocity; muzzle velocity | | |
| ventiloser Motor | Vent; valve | | |
| veraltet | Valve gasket | | |
| veränderlich | Sleeve-type engine | | |
| verankerte Mine | obsolete; antiquated | | |
| Veraschung | variable; changeable; unstable | | |
| Verausgabung | Moored mine | | |
| Verband | Ashing; incineration | | |
| Verbandsabwurf; | Issue | | |
| Verbandswurf | Binding; bandage; dressing; | | |
| verbessert (v) | band; combined arms unit | | |
| | Formation release (bombing) | | |
| | improved | | |

| | | | |
|-----------------------------|---|--------------------------------|--|
| Vergeltung | Retaliation; reprisal; revenge | vernickeln | to nickel-plate |
| Vergeltungswaffe (V) | Retaliation (revenge) weapon such as V-1, V-2 and V-3) | vernieten | to rivet |
| vergessbar | castable; ready to cast | Verordnung | Order; decree; regulation |
| vergiften | to poison; contaminate (CWS) | Verpackung | Packing; casing |
| Vergiftungsschiessen | Gas shell fire (Arty) | Verpackungsgeschoss | Dummy projectile for vehicle-loading practice |
| Verglasung | Vitrification; glazing | verplatinieren | to platinize |
| Vergleichsschiessen | Calibration fire (Arty); test shooting | verpuffen | to puff off; deflagrate; explode |
| Vergrößerung | Enlargement | Verpuffungsprobe | Deflagration test |
| vergüten | to improve; temper (metals); compensate | Verrichtung | Performance; execution; action |
| Vergütungsstahl | Heat-treated steel | verrostet | rusty |
| Verhältnis | Proportion; ratio; rate | Versager | Misfire; failure |
| Verhärtung | Hardening | Versäuerung | Acidification |
| Verharzen; Verharzung | Resinification | verschießen | to expand; fade; discharge |
| Verholzung | Lignification | verschleiern | to mask; screen; veil; camouflage |
| Verhüttung | Smelting; working off (metals) | Verschleierungsfeuer | Diversion fire; smoke-shell fire |
| Verjüngung | Taper; reduction (of scale) | Verschluss | Closing; closure; breechblock; breech mechanism |
| verkanten | to cant; tilt; incline | Verschlussblock | Screw-type breechblock |
| Verkehrsboot | See V-Boot | Verschlusskeil | Wedge-type breechblock |
| verkehrt | reverse; inverse | Verschlossring | Breech ring; closing ring |
| Verkettung | Linking; linkage | Verschlossschieber | Breech locking slide; shutter slide |
| Verkittung | Fastening (sealing) with putty or other adhesive; cementing | Verschluss-schraube | Breech screw; threaded closing cap in fuze |
| Verkleidung | Facing; casing; lining; disguise; camouflage | Verschraubung | Screw joint; screw cap |
| Verkleinerung | Diminution; reduction | Verschreibung | Prescription; order; note |
| verkleistern | to make into paste; to cover with glue; to stick together | Verschwindlafette | Disappearing gun mounting |
| verklemmen | to jam; wedge | versehen | to provide; supply; furnish |
| verknallen | to detonate | versilbern | to silver-plate |
| verknistern | to decrepitate | verspannen | to brace; tighten; stretch |
| Verknisterung | Decrepitation | versprühen | to spray (CWS) |
| verkobalten | to plate with cobalt | Verstählung | Acieration; case hardening |
| verkochen | to boil down; concentrate | Verstärkung | Reinforcement |
| verkohlen | to char; carbonize | Versuch; Versuchung | Experiment; assay; trial; test |
| verkoken | to coke | Versuchladung | Test charge (Arty) |
| verkreiden | to calcify | versuchs | experimental |
| verkühlen | to cool down | Versuchsschiessen | Test firing (Ord) |
| verkupfern | to copper | Versuchswesen | Research |
| verkuppeln | to couple; to connect | verteidigen | to defend; maintain |
| verkürzte Leuchtspur | Shortened tracer trail | Verteidigungswaffe | Defense weapon |
| (vk L' spur) | | verteilen | to distribute; divide |
| verkürztes Röhrenpulver | Tubular propellant cut into short lengths | Verteilungsstelle | Distributing point |
| Verlag; Verlagsbuchhandlung | Publishing house | Vertiefung | Deepening; depression; cavity |
| verlasten | to pack or load on vehicles or horses | vertrocknen | to dry up |
| verlastete Artillerie | Pack artillery | verunreinigen | to render impure; contaminate |
| verlastetes Geschütz | Pack piece (of ordnance) | vervielfachen; vervielfältigen | to multiply |
| verlöschen | to go out; be extinguished | Verwendung | Application; use; utilization |
| verlöten | to solder | Verwitterung | Efflorescence; weathering |
| vermengen; vermischen | to mix; blend | Verzahnung | Gear; gearing |
| vermessen | to measure; survey | Verzeichnis | List; register; index |
| Vermessungsbatterie | Ranging battery | verzinken | to coat with zinc; galvanize |
| verminderte Ladung | Reduced charge | verzinnen | to tin; coat with tin |
| verminen | to mine; lay mines | verzögern | to delay; postpone |
| Vermögen | Ability; power; property | Verzögerung (V) | Retardation; delay; lag |
| Vernebelung | Smoke screening | | |
| Vernichtung | Destruction; annihilation | | |

| | | | |
|--|--|--|---|
| Wärmeprobe | Heat test | Werkstatt | Workshop |
| Wärmeregler | Thermoregulator | Werkstoff | Material (industrial) |
| Wärmeübertragung (W) | Heat transfer | Werkzeug | Tool; instrument |
| Wärmermögen | Heat capacity | Werkzeugpatrone (WZgPatr) | Steel precision round used by armorers for testing the function of weapons (lit instrument cartridge) |
| Warze | Lug; stud; nipple; knob | | Tool steel |
| waschen | to wash; scrub | | Being; nature; character |
| Wascherde | Fuller's earth (See also Walkerde) | | Wasp; SP Howitzer (See under Panzer in descriptive part) |
| Wasser | Water | Werkzeugstahl | West Wall (Fortifications along Germany's western frontier) |
| Wasserbombe (Wabo) | Depth bomb; depth charge | Wesen | Weather; storm; firedamp (Mining) |
| Wasserdampfbad | Steam bath | Wespe | Permissible dynamite; dynamite safe to use with firedamp |
| wasserdicht; wasserfest | waterproof; water-tight | | Meteorology (Met) |
| wassergierig | hygroscopic | Westwall | safe in the presence of firedamp |
| Wasserhahn | Water tap; water cock | | Permissible explosives; safety mining explosives; explosives safe to use in fiery coal mines |
| Wasserkunst | Water-work; draining engine (Mining); hydraulics | | Whetstone; hone |
| Wasserlinie | Waterline | Wetter | Unit of weight; specific gravity |
| Wassermantel | Waterjacket | Wetterdynamit | against; contrary to |
| Wassermörtel | Hydraulic mortar | | Resistance |
| Wasserprüfung | Water testing; water analysis | | Ohmmeter |
| Wasserschussprova | Underwater firing test | | Center of resistance; center of drag |
| Wasserstoff | Hydrogen (H) | Wetterkunde | Countershock |
| Wasserstoff-hyperoxyd | Hydrogen peroxide (See also T-Stoff) | wettersicher | again; new |
| Wasserstoff-peroxyd | | | Cradle (G) |
| Wasserstoffzahl | Hydrogen ion concentration (pH) | Wettersprengmittel; Wettersprengstoffe | to weigh; rock |
| Watte | Absorbent cotton; wadding | | Pennant |
| Wechsel | Change; displacement (Arty); exchange; currency | | downwind |
| Wechselgetriebe; Getriebe | Transmission (motor vehicles) (See also Kraftübertragung) | | Windlass; winch; worm (screw) |
| wegsaugen | to suck away; remove by suction | Wetzstein | Arming vane (B) |
| wegwerfen | to throw away; reject | Wichte | Arming vane stop |
| Wehr; Wehre | Defense; parapet | wider | Wind gauge; anemometer |
| Wehrdienst | Military service | Widerstand | Windshield |
| Wehrmacht | Armed Forces | Widerstandsmesser | Storm matches for lighting a fuse (lit Wind strike matches) |
| Wehrmacht-Heer (WH) | Armed Forces, Army | Widerstandszentrum | Blast current; air current |
| Wehrmacht-Luftwaffe (WL) | Armed Forces, Air Corps | | Twist (Ord) |
| Wehrmacht-Marine (WM) | Armed Forces, Navy | Widerstoss; Wiederstoss | windward; upwind |
| Weicheisen | Soft iron | wieder | Angle; V-formation corner |
| Weichlot; Weisslot | Soft solder | Wiege | Firing angles |
| Weichstahl | Soft (mild) steel | wiegen | Goniometer; gunner's quadrant; protractor |
| Weinessig | Wine vinegar | wiegen | Periscope; periscopescope (Tk) |
| Weingeist | Spirits of wine; ethyl alcohol | Wimpel | Flagman; signaler using a signal disk; signal arm or light indicating direction of turn |
| Weinsäure; Weinstein | Tartaric acid | windabwärts; leewarts | Winter warfare |
| Weinstein | Tartar | Winde | 50/50 mixture of Lewisite and mustard gas (CWS) |
| Weissglühbirne; Weissglut | White heat; incandescence | Windflügel | |
| Weisskreuz | White cross (Ger marking for lacrimator) | Windflügelsicherung | |
| Weisslot | See Weichlot | Windmesser | |
| Weitschusspatrone | Long-range cartridge | Windschutzschleibe | |
| Weitwerfer | Long-range flame thrower (See also Flammenwerfer) | Windstreichholzer | |
| Wellblech | Corrugated sheet iron | | |
| Welle | Wave; shaft; axle; frequency (Rad) | Windstrom | |
| Wellenband | Wave band; frequency band (Rad) | Windung | |
| Weltkrieg | World War I (WWI) | windwärts | |
| Wendepunkt | Turning point; critical point | Winkel | |
| werfen | to throw; fling | Winkelgruppe | |
| Werfer (W) | Launcher for rocket or signal projectile; mortar (lit Thrower) | Winkelmesser | |
| Werfergranate (Wfg) (See also Wurfgranate) | Mortar shell; rocket | Winkelspiegel | |
| Verfahren | Frame-type rocket projector | Winker | |
| Verft | Shipyard; wharf; dock | | |
| Werg | Tow; oakum | Winterkrieg | |
| Werk | Work; works; plant; factory | Winterlost | |

| | | | |
|---|---|---|---|
| Wirbel | Vortex; eddy; spigot; drum roll | | |
| Wirbelstrom | Eddy current; whirlpool | | |
| Wirbelsturm | Cyclone; tornado | | |
| Wirbelwind | Whirlwind (20 mm SF four-barreled AA gun) (See also under Panzer in descriptive part) | Yperit | Mustard gas; yperite |
| | | Y-Rohr; Y-Röhre | Y-tube |
| | | | Z |
| wirksame Schussweite | Effective range | Zacke; Zacken | Pro.ig; tooth; notch |
| Wirkung | Action; effect; efficiency | Zähe; Zähigkeit | Toughness; tenacity; |
| Wirkungsbereich | Field of fire; sphere of action; effective range | | viscosity |
| Wirkungsgrad; Nutzeffekt | Efficiency | Zahl | Number; numeral |
| Wischer | Wiper; sponge; windshield wiper | Zahnarzt | Dentist |
| Wischstock | Cleaning rod (G) | Zahnrad | Gear wheel; pinion; |
| Wismut; Wismuth; Wismut | Bismuth (Bi) | | toothed wheel |
| Wolfram | Tungsten; wolfram (W) | Zahnradpumpe | Gear pump |
| Wolfram-Nickel-Stahl | Tungsten-nickel-steel | Zange | Pliers; tongs |
| Wolframstahl | Tungsten steel | Zapfen | Peg; pin; plug; stud; |
| Wolke | Cloud; wave of gas (CWS) | | pivot |
| Wolle | Wool | Zapfhahn | Drain cock; tap |
| Wolokusche | Boat-type runner placed under gun wheels for operation in deep snow | Zäsium; Cäsium | Cesium |
| | | Zehnlng (Zehnlng) | Ten-tuber |
| Wucht | Kinetic energy; striking power; force of impact | Zeichen | Sign; mark; signal |
| Wulst | Pad; padding; roll; enlargement | Zeichnung | Drawing; blueprint; |
| Wulst (am Geschoss) | Shoulder; swell (on projectile) | Zeiger | drawing |
| Wurf | Throw; cast; bomb release | | Pointer; indicator; |
| Wurfbahn; Wurfparabel | Bomb trajectory | Zeit | hand; needle |
| Würfel | Cube; pellet; die; capsule | Zeitbombe | Time (length); period |
| Würfelpulver (WP) | Cubical (or prismatic) powder or propellant; dice-shaped propellant | Zeitmesser | (See also Uhrzeit) |
| | | Zeitschnur; Zeitzündschnur | Time bomb |
| Wurfgerät (schweres Wurfgerät) (See also Nebelwerfer) | Heavy projector for rockets, signals, etc (Chemical rocket projector) | | Chronometer |
| Wurfgeschoss | Missile; projectile | Zeitschrift | Time fuse; safety fuse; |
| Wurfgranate (Wgr) (See also Werfergranate) | Mortar shell; rocket projectile | | Bickford fuse; blasting fuse |
| Wurfgranatzünder (WZ) | Mortar-shell fuze | Zeitung | Periodical; journal; |
| Wurfkörper | Special projectile for signal pistols; rocket projectile | Zeitzünd (ZzZ); (ZZdr) | magazine |
| Wurfladung (Wurfdg) | Reduced propelling charge | Zeitzündung | Newspaper; paper; news |
| Wurfmine | Trench-mortar shell or bomb | Zelle | Time fuze (Ammo) |
| Wurfpfeil | Dart; arrow | Zelle | Delayed ignition |
| Wurfrahmen | Framework-type projector for HE or incendiary rockets | Zellon | Cell; cellule |
| Wurfweite | Mortar range; throwng range for hand grenades; bombing range | Zellstoff | See under Warplants in descriptive part |
| Würgebohrung | Tapered bore; choke barrel (Ord); (See also konisches Rohr) | Zelluloid | Cellulose acetate |
| Würgelpumpe | Rotary pump | Zellulose | Paper pulp; cellulose |
| Würgezange | Crimping pliers (for caps) | Zellwolle | Celluloid |
| Würgung | Crimp (Ammo) | Zementcylindrische Bombe (ZCB) | Cellulose |
| | | Zementieren | Cellulose fiber |
| | | Zement-Kalk | Concrete cylindrical bomb |
| | | Zementstahl | |
| | | Zentner | Cementation |
| | | Zentralblatt | Hydraulic lime |
| | | Zentrierwulst (Compare with Führungsband) | Cementation steel |
| | | Zentrifugalsicherung | Hundredweight; 50 kg |
| | | Zer; Zerium | Central journal or paper |
| | | zerbrechen | Bourrelet (lit Centering band) |
| | | | Centrifugal safety (Fz) |
| | | | Cerium |
| | | | to break in pieces; |
| | | | shatter; crack |
| | | | to crush; crumple |
| | | | to disintegrate |
| | | | to deliquesce; melt |
| X-Strahlen | X-Rays (See also Röntgenstrahlen) | zerdrücken | |
| Xylol | Xylene | zerfallen | |
| | | zerfließen | |

| | | | |
|-----------------------------------|--|---|--|
| zerkleinern | to reduce to small pieces | Zonenzeit | Standard time |
| Zerkleinerungsmaschine | Crusher; pulverizer | Zubehör | Accessories; fittings |
| Zerknallstoss | Blast; concussion | Zucker | Sugar |
| zerknistern | to decrepitate | Zuckerin | Saccharin |
| zerlegen | to decompose; disassemble; dismantle | Zufluss | Flow; flux; resources |
| Zerteigerzunder; Zerlegungszunder | Self-destroying fuze (AA Ammo) | Zufuhrer | Feeder; feed mechanism (automatic weapons); belt feed (MG) |
| Zerlegung | Dispersal; self-destruction; stripping | Zug (pl Züge) | Train; rifling groove; pulling; draft platoon |
| zermahlen; zerreiben | to crush; grind fine; triturate; pulverize | Zugabe | Supplement; addition |
| zerreißen | to tear; lacerate; break | Zugbrücke | Drawbridge |
| Zerschneidezunder | See Zug- und Zerschneidezunder | Zugdruckzunder | Pull-pressure igniter (LdMi) |
| Zersetzung | Decomposition; disintegration | Zugfeder | Draw spring |
| zerspalten | to split up; cleave | Zugfestigkeit; Zugspannung | Tensile strength |
| zersplittern | to split up; shatter; dissipate (forces etc.) | Zugkraft; Zugleistung | Tractive force; traction |
| zersprengen | to crack; burst into pieces; blow up | Zugmaschine | Prime mover; tractor |
| zerspringen | to explode; burst | Zugtau | Tow rope |
| zerstäuben | to reduce to dust; atomize; spray | Zug- und Druckzunder 29 (ZDZ 2R) | Pull and bush igniter 29; (lit Pull and pressure igniter) (LdMi) |
| Zerstäuberdüse | Spray nozzle; Diesel fuel injector | Zug- und Zerschneidezunder 35 (ZuZZ 35) | Pull and tension wire igniter 35; (lit Pull and cut up igniter) (LdMi) |
| Zerstäubegerät | Chemical spray apparatus | Zugverkehr | Railroad traffic |
| Zerstörer | Destroyer (Nav); long-range fighter (Avn) | Zugversuch | Tensile test |
| Zerstörpatrone | Gun destruction charge | Zugwagen | Tractor |
| Zerstörung | Destruction; demolition | Zugzunder | Pull igniter |
| Zerstörungsarbeiten | Demolitions | Zugzunder 35 (ZZ 35) | Pull igniter 35 (LdMi) |
| Zerstörungsbombe | Demolition bomb | zumachen | To shut; close |
| Zerstörungsgafeuer | Destruction fire | Zumischpulver | Admixed powder; dope (in dynamites) |
| Zerstreuung | Dispersion; diffusion; scattering | Zumischstoff | Admixed material; admixture |
| Zerteilung | Division; separation | Zündanlage | Ignition system |
| Zerrennung | Separation | Zündapparat | Ignition apparatus; priming apparatus; magneto; exploder; blasting machine |
| Zettel | Card; ticket; tag | zündbar | inflammable |
| Zug | Ordnance supplies; gear; equipment; stuff; material; fireworks composition | Zündbolzen | Percussion plunger (TiFz) |
| Zugamt | Ordnance Department | Zünddraht | Priming wire |
| Note: Zugamt was in charge of | weapons, ammunition, military vehicles and clothing | zünden | to ignite; detonate; fire a demolition charge; take fire |
| Zughaus | Arsenal; armory | Zunder | Tinder; forge scale |
| Zugnis | Certificate; transcript of grades (School) | Zunder (Zd) | Igniter (LdMi); fuze (Sh) (to set the fuze) |
| ziehbar | ductile | Zunder (elektrische) | Electrical igniter |
| ziehen | to draw; pull | Zunderdeckel | False ogive (Proj) |
| Ziehen; Zichung | Drawing | ZunderEinstellung | Fuze setting |
| Ziebzunder | Pull firing device (LdMi) | Zunderfüllmasse; Zündsatz | Fuze filling; fuze composition |
| Ziel | Goal; target; objective; aim | Zundergehäuse | Fuze body (Sh); fuze cover (B); fuze housing |
| Zieleinrichtung | Sighting mechanism | Zundergerät, tragbar | Portable demolition equipment |
| zielen | to aim; sight | Zunder, gesicherter | Fuze set at safety (See also Zunder, scharfer) |
| Zielfernrohr | Telescopic sight mechanism (Rf) | Zunderhalter | Detonator holder |
| Zielgerät; Zielvorrichtung | Sighting mechanism; bomb sight | Zunderhülse | Hood of a fuze; fuze cover |
| Zielmunition | Subcaliber ammunition; target practice ammunition | Zunderkappe | Closing cap (TiFz); head (PD Fz); upper cap (Clock-work Fz) |
| Zielpunkt | Target point; aiming point | Zunderkörper | Body of a fuze |
| Zielpuppe | Target dummy | Zunderlaufzeit | Time of functioning of a fuze |
| Zielscheibe | Practice target | | |
| Zielschwarze | Bull's-eye | | |
| Ziffer | Figure; number; cipher | | |
| Zifferblatt | Dial (on instruments) | | |
| Zink | Zinc | | |
| Zinknebel | HC smoke mixture (Zn dust 40 and hexachloroethane 60%); Berger mixture | | |
| Zinn | Tin | | |
| Zipfel | Tip; point; end; lobe; ear | | |
| Zoll | Inch (2.54 cm); duty; tariff; toll | | |

| | | | |
|---|---|----------------------|--|
| Zünder, scharfer | Armed fuze | Zündschnurzeitzünder | Time fuze igniter |
| Zünderschutzkappe | Fuze cap, protective | Zündschraube | Threaded percussion primer (for propellant) |
| Zündersprengkapsel 43 | Cap and detonator assembly 43 | Zündschrauben Futter | Bushing of a threaded percussion primer |
| Zünderstellmaschine | Automatic fuze setter (in AA gun) | Zündschrauben Hülse | Case of a threaded percussion primer |
| Zünderstellung | Fuze setting | Zündstift | Firing pin |
| Zünderteller | Body of a powder-train time fuze | Zündstoff | Flammable material; igniting agent |
| Zündervorrichtung | Austrian name for a fuze (lit Fuze device) | Zündstrahl | Flas. in an igniter or primer |
| Zünderzwischenstück | Fuze extension cap | Zündübertragung | Induced detonation (Dem) |
| zündfertig | fuzed; armed; ready for firing (Fz) | Zündung (Zdg) | Firing; detonation (Ammo and Dem); ignition |
| Zündgerät | Demolition equipment | Zündungstemperatur | Temperature of ignition |
| Zündgerät 40, tragbar | Portable demolition kit pattern 40 | Zündverstärker | Reinforcing igniter (See in descriptive section) |
| Zündholz; Zündhölzchen | Match | Zündverbindung (Zdv) | Relay (Fz) |
| (Schwedisches Zündhölzchen) | (Safety match; Swedish match) | Zündverteiler | Distributor (Mor) |
| Zündhülse 502 | Primer tube 502 (French design) | Zündvorrichtung | Priming arrangement; igniting mechanism |
| Zündhütchen (Zdh) | Primer (SA Ammo); percussion primer (Fz); percussion cap (Ammo); propellant primer (Ammo) | Zündwaren | Flammable goods |
| Zündhütchenhülse | Casing of a primer; primer cup | Zündwärme | Heat of ignition |
| Zündhütchensatz | Priming composition | zunehmender Drall | increasing twist; progressive rifling |
| Zündhütchenzange | Primer pliers | Zuneigung | Inclination; attachment |
| Zündkanal | Primer vent (Cart); axial flash hole (Fz); cap hole (BI Cart); vent hole (obturator) | Zunge | Tongue; pointer; needle (of a balance) |
| Zündkapsel | Detonator | Zurrbolzen | Locking pin (G) |
| Zündkegel | Anvil (in primer cap) | Zurrung | Locking mechanism (G or MG); seizing; anchorage |
| Zündkerze | Spark plug | Zurückgleiten | Recoil |
| Zündkirsche | Ignition pellet | Zurückstossung | Repulsion; pushing back |
| Zündladung (Zldg; Zdlg) | Booster charge; gain; ignition tube | Zusammenfassung | Summary; resumé; concentration (Arty) |
| Zündladung A, B, C/98, | See under Booster in descriptive part | Zusammensetzung | Concentrated fire (Arty); collective fire (SA) |
| C/98Np, 36 and 40 | Ignition tube used in smoke generators and smoke grenades | Zusammenstoß | Composition; synthesis; chemical compound |
| Zündladung No 4 | Detonator casing (Fz); primer container; primer charge housing | Zusammenwirken | Collision; encounter; clash |
| Zündladungskapsel | Detonator charge (Fz); primer composition | Zusammenziehung | Synchronization; coordination; working together |
| Zündladungskörper | Touch hole; vent hole; flash hole | Zusatz (Zus) | Contraction; shrinking |
| Zündloch | Ignition magneto | Zusatzgetriebe | Addition; admixture; appendix; extension |
| Zündmagnet | Blasting machine; exploder (Engr) | Zusatzkartusche | Auxiliary transmission; auxiliary drive |
| Zündmaschine (See also Glühzündapparat) | Ignition mixture; igniting composition | Zusatzladung | Additional (secondary) propellant charge |
| Zündmasse | Flammable metal (such as Mg, Al or Zr) | Zusatzladung | Additional charge; augmenting charge (Mor); increment (in SL Ammo) |
| Zündmetall | Igniter and fuze materials | Zusatzmittel | Addition agent; reagent |
| Zündmittel | Fuses and accessories, types A, B, C | Zusatzstoff | Admixed material; material for admixing |
| Zündmittelkasten Satz A, B, C | Percussion needle; firing pin (Fz) | Zuschlag | Addition; increase; extra charge; admixture |
| Zündnadel | Needle gun (invented in 1836 by N. von Dreyse) | Zustand | State; condition; situation |
| Zündnadelgewehr | Ignition paper | Zutritt | Delivery |
| Zündpapier | Ignition cartridge; percussion tube | Zuwachs | Access; admittance; admission |
| Zündpatrone | Pellet of a detonating composition in a cap | | Increase; increment; growth |
| Zündpille | Priming powder | | |
| Zündpulver | Flash point | | |
| Zündpunkt | Initial impulse | | |
| Zündreiz; Initialimpuls | Vent; channel to transmit fire | | |
| Zündröhren | Powder train (Ammo or Dem); igniter train (Pyro); fuze composition | | |
| Zündsatz | Safety fuze; lanyard; match cord | | |
| Zündschnur (Zdschn) (See also Zeitzchnur) | Safety fuze lighter or igniter, type 29A, 29B, 29C | | |
| Zündschnuranzünder 29A, 29B, 29C | Detonating fuze; primacord; | | |
| Zündschnur, detonierend | | | |

| | | | |
|------------------------------------|----------------------------------|-----------------------|--|
| zweiachsig | biaxial | Zwillings-MG-Drehturm | Revolving turret with twin-barreled MG |
| zweiäugig | binocular | Zwillingsessig | Double salt |
| Zweibein | Bipod (MG) | Zwillingswaffe | Twin-barreled weapon |
| Zweidecker | Biplane | Zwinge | Cramp; clamp; vise |
| Zweielektrodenröhre | Diode tube (Rad) | Zwinger | Wedge |
| Zweigleitung; Zweigleitung | Branch line (RR); junction line | Zwirn | Thread (linen) |
| Zweimetall | Bimetal | Zwirnband | Tape |
| zweimotorig | twin-engine | Zwirnfadenbund | Binding thread |
| Zwei-Ohr-Verfahren | Binaural method (sound location) | zwischen | between; among |
| zweiphasig | two-phase; biphasic | Zwischenbodengeschoss | Large caliber shell provided inside with a solid partition |
| Zweipolröhre | See Zweielektrodenröhre | Zwischenlage | Intermediate layer |
| Zweirad | Bicycle | Zwischenprodukt | Intermediate product |
| Zweitaktmotor | Two-cycle engine | Zwischenstück | Adapter |
| zweiwertig | bivalent; divalent | Zwischenstufe | Intermediate stage |
| Zwickzange | Cutting pliers; pincers | Zwischenzeit | Time interval |
| Zwilling (Zw) | Twin; two-tuber | Zwischenzustand | Intermediate state |
| Zwillingsgestell; Zwillingslafette | Twin mount (Ord) | Zyanwasserstoffsäure | Hydrocyanic acid; prussic acid (CWS) |
| Zwillingsläufe | Twin barrels (such as in MG) | Zylinderpulver (Zyfp) | Cylindrical propellant |
| Zwillingsmaschinengewehr | Twin-barreled MG | Zylinderverschluss | Bolt mechanism (Rf) |

Abbreviations (American and British)

Used in the Preceding Vocabulary and in the List of German Abbreviations which Follows

AA Antiaircraft; AAG Antiaircraft gun; AC Aircraft
A/C Anticoncrete; A/D Antidisturbance; Am Ammonium;
Ammo Ammunition; Ap Airplane; AP Armor-piercing; A/P Anti-personnel; A/T Antitank; Avn Aviation; B Bomb; Ball Ballistics; BC Ballistic cap; BD Fz Base detonating fuze;
Bl Blasting; C Cap or capped; Cort Cartridge; Coy Cavalry; contg containing; CP Concrete-piercing; Cryst Crystal or crystalline; CWA Chemical Warfare Agent; CWS Chemical Warfare Service; DA Direct action; DEGDN Diethyleneglycol dinitrate; Dem Demolition; E-Boat Enemy boat (British designation for German PT-Boat); Elec Electrical; Engr Engineers; Expl Explosive(s); Fix Ammo Fixed ammunition; Fix G Fixed gun; Fort Fortification; Fz Fuze; G Gun; Ger German; Govt Government; GP General purpose; GP-HE General purpose-high explosive; Gr Grenade; Guny Gunnery; H or How Howitzer; HdGr Hand grenade; HE High explosive; HEAT High-explosive, antitank; HoC Hollow charge; shaped charge; Imp Impact; Inc Incendiary; Inc B Incendiary bomb; Inc-T Incendiary-Tracer; Infy Infantry; kc kilocycle; kg kilogram; km kilometer; L A Lead Azide; LD Long delay; LdMI Land mine; lit literally; L St Lead styphnate; Moth Mathematical; Mc Megacycle; Mech Mechanical; Met Meteorological; M F Mercuric fulminate; MG Machine gun; Mi Mine (land or underwater); Mk Mazk; Mor Mortar; Mot Motor; Mount Mounting; N Nose; Nav Naval; NC Nitrocellulose; NCO Noncommissioned officer; NG Nitroglycerin; NGc Nitroglycol; NGu Nitroguanidine; Ord Ordnance; PD Fz Point-detonating fuze; PETN Pentaerythritol Tetranitrate; Pist Pistol; pl plural; Proj Projectile; Pyro Pyrotechnical; QF Quick firing; Rad Radio; Rf Rifle; Rock Rocket; RR Railroad; Railway; SA Small arms; SA Ammo Small arms ammunition; SAP Semi-armor-piercing; Sgt Sergeant; Sh Shell; Shr Shrapnel; S L Ammo Separate-loaded ammunition; SP Self-propelled; SP G Self-propelled gun; SP How Self-propelled howitzer; T or Tk Tank; Td Torpedo; Tech Technical; Telag Telegraph; TIFz Time fuze; Tr or T Tracer; Traj Trajectory; Wp Weapon; Wt Weight

References:

- 1) Krupp-Wörterbuch (Deutsch-Französisch-Englisch), Fr. Krupp, Essen (1938-1942)
I Teil: Feld-, Gebirgs- und Flugabwehrgeschütze;
II Teil: Eisenbahnartillerie, Maschinenwaffe, Panzerkampfwagen, Ballistic, Sondergerät, etc
- 2) Anon, Gerätlste vom 1.7.43, Reichsdruckerei, Berlin (1943)
- 3) Anon, Deutsche Abwurfmunition, Berlin (1943)
- 4) L. I. Dance, Foreign Ammunition, The Ordnance Sergeant, August 1943, pp 86-94
- 5) Anon, German Military Dictionary, War Dept Tech Manual, TM 30-506, Washington, D C (1944)
- 6) H. Strom et al, Dictionary of Ordnance Terms, F. Unger Pub Co, N Y (1944)
- 7) Anon, Recognition Handbook for German Ammunition, Supreme Headquarters Allied Expeditionary Force (1945)
- 8) Otto Wolf, "Glossary of German Ordnance Terms", The Ordnance Sergeant, March 1945, pp 181-3
- 9) Anon, Enemy War Materials Inventory List, Office of Supreme Headquarters Allied Expeditionary Force, (1945)
- 10) A. M. Patterson, A German-English Dictionary for Chemists, J. Wiley, N Y (1950)
- 11) P. Naslin, Three-Language Technical Vocabulary, Edit Revue d'Optique, Paris (1951), p 209-227
- 12) Anon, German Explosive Ordnance, TM 9-1985-2 and TM 9-1985-3 (1953)
- 13) G. B. Jarrett, K. F. Kemp and H. M. Reed, Museum of Aberdeen Proving Ground, Maryland; private communications
- 14) J. E. Capell, A. B. Schilling, E. W. Blasczyk, J. F. Hauck, H. A. Tisch, H. H. Bullock, G. Coghlan and Drs H. W. Adam and R. Weil of Picatinny Arsenal; private communications
- 15) K. H. Eitzen, The Military Eitzen, Verlag WEU/Offene Worte, Bonn (1957)

**LIST OF
GERMAN ABBREVIATIONS (Abkürzungen)
OF ORDNANCE AND RELATED TERMS**

(In collaboration with K. F. Kempf of Aberdeen Proving Ground, Maryland)

A

| | | |
|---|---|---|
| A; Abw | Abwehr | Defense |
| A; Art | Artillerie | Artillery |
| A (when following projectile designation; white stencilling) | Ausstossladung | Expelling charge of a shrapnel or smoke projectile |
| A (such as in: H1/A, H1/B, H1, C) | Hohlladung A, B, and C | Types of hollow charges |
| A-1 | Aggregat Eins | Aggregate No 1 |
| Note: A-1 was the first successful liquid-propellant rocket developed | | at the Rocket Development Center at Kummersdorf West |
| A-4 | Aggregat Vier | Aggregate No 4 |
| Note: A-4, commonly known as V-2, was one of the most successful liquid-propellant rockets (See V-2 in the description section) | | |
| aA; AA | alte Art | of old type or pattern (See also nA and nF) |
| AB | Abwurfbehälter | Aerial bomb container |
| Examples: AB 23 SD2, AB 24 SD 2, AB 36, AB 42, AB 500-1B, AB 500-3A, etc [TM 9-1985-2(1953), pp 95-108 and 11-119] | | |
| AB (black stencilling on a projectile, such as KGr rot AB) | Ausstossbüchse (Kanonengranate rot AB) | Smoke canister ejected from projectile on burst (Gun shell with red smoke canister) |
| Abk | Abkürzung | Abbreviation |
| Abpr; Abr | Abpraller | Ricochet; ricochet burst |
| Abr | Abrüstung | Demobilization; disarmament |
| Abs | Absender | Sender |
| absol | absolut | absolute |
| Absch Ger | Abschussgerät | Grenade launcher |
| ABSt | Artillerie-Beobachtungsstelle | Artillery Observation post |
| Abt; Abtlg | Abteilung | Section; detachment; department |
| Abw | Abwehr | Defence |
| Abz | Abzug | Trigger; retreat |
| ac | anni currentis | of the current year |
| ACB (such as in WGR AT ACB) | (Wurfgranatenzünder Trolitul ACB) | Marking on a plastic PDFz in 80 mm smoke mortar shell [TM 9-1985-3(1953), p 591] |
| a/d | an der | on the; at the |
| aD | ausser Dienst | retired |
| adD | auf dem Dienstwege | Through official sources; through channels |
| AD | Armeedolch | Army dagger |
| Adj | Adjutant | Adjutant |
| Adm | Admiral | Admiral |
| ADO | Allgemeine Dienstordnung | General Service Regulations |
| Adr | Adresse | Address |
| Ae; Ä | Aether; Äther | Ether |
| AEG | See under Warplants (descriptive section) | |
| acW; äW | äussere (äussere) Weite | Outside diameter |
| Afl | Artillerieflieger | Artillery air observer; Artillery spotting flier |
| A G | Atomgewicht | Atomic weight |
| A - G | Aktiengesellschaft | Joint Stock Company; Open Corporation |
| AGFA; Agfa | A - G für Anilinfarbenfabrikation | Aniline Dye Manufacturing Corporation |
| AGs | Anschliessgeschoss | Sighting projectile |
| AHA | Allgemeines Heeresamt | General Army Office |
| AHQ | Armeehauptquartier | Army Headquarters |
| AK | Armeekorps | Army Corps |
| akt | aktiv | active; on duty |
| Al | Aluminium | Aluminum |
| Al (black stencilling following the designation of shell 7.5 cm GebGr 15 Al) | Aluminiumgrüss | Designation of an HE shell containing some granular Al flash producer |

| | | |
|--------------|--|--|
| Al.F | See under Warplants, etc (descriptive section) | |
| Alk | Alkohol | Alcohol; ethyl alcohol; ethanol |
| Am | America; amerikanisch | America; American (See also VStA) |
| Am | Ammonsalpeter | Ammonium nitrate |
| AmmonStrl | Ammonstreifenpulver | Am nitrate strip propellant |
| a M | an Main | on the Main (river) |
| am | an dem | at; by; to; on; near to |
| AML | Armee-Munitionslager | Army Ammunition Depot |
| AmptSt | Ampere-stunde | Ampere-hour |
| amrl | amtlich | official |
| An | Anisol | Trinitroanisole (TNAns) |
| An 60/40 | Anisol 60/40 | TNAns 60 and Am nitrate 40% |
| Anf | Anfang | Beginning |
| Anfgeschw | Anfangsgeschwindigkeit | Initial velocity; muzzle velocity |
| Angew Chem | Angewandte Chemie (formerly Zeitschrift für Angewandte Chemie) | Applied Chemistry (Journal) |
| Anh | Anhang | Appendix; supplement |
| Anh | Anhänger | Trailer; supporter; follower |
| AnhW | Anhängewagen | Trailer |
| Anl | Anlage | Plant; establishment |
| Anm; Anmerk | Anmerkung | Remark; footnote |
| Ann | Annahme | Acceptance; receipt |
| Ann | Annalen der Chemie | Annals of Chemistry (Journal) |
| Anp | Anpassung | Adaptation |
| ANR | Armee Nachrichten Regiment | Army Signal Regiment |
| ansch | anschiessen | to hit by shooting |
| Ansch Patr | Anschliesspatrone | Ammo used for adjustment fire |
| Anst | Anstalt | Establishment; institution |
| Anz | Anzahl | Number |
| Anz | Anzeiger | Indicator; informer |
| ANZ | Anzünder | Igniter |
| ANZ-29 | Anzünder 29 | Friction pull type igniter used to ignite a safety fuse or to set off a smoke candle (TM 9-1985-2, pp 286-7) |
| AO | Artillerieoffizier | Artillery officer |
| Ao | Ago | Designation of airplanes manufd by Ago Co |
| AP | Artilleriepunkt | Artillery reference point (Gunnery) |
| App | Apparat | Apparatus; device; equipment |
| AR | Artillerieregiment | Artillery regiment |
| Ar; AR | Arado | Designation of airplanes manufd by Arado Co |
| ARDR | Meaning unknown to us | Designation of a smoke signal flare (TM 9-1985-2, p 80, Fig 84) |
| A/R | am Rhein | on the Rhine (river) |
| Ark | Arktikmunition | Ammo for use in Arctic climate |
| Arm | Armee | Army (formation above Army Corps) |
| arm | armiert | Armed |
| Ars; As | Arsenal | Arsenal |
| Ars | Arsenik | Arsenic (As) |
| Art; Artl; A | Artillerie | Artillery |
| Art SchPl | Artillerieschießplatz | Artillery firing range; Proving ground |
| AS | Anforderungssigna! | Call signal |
| ASt | Auswertestelle | Computing station (sound and flash ranging gunnery) |
| At; Atm | Atmosphäre | Atmosphere |
| Att | Attaché | Attaché |
| Attr | Attrape | Dummy |
| Atll | Atmosphärenüberdruck | Gage pressure; pressure above atmospheric |
| Aubo | Aussenbordmotor | Outboard motor |
| Aufb | Aufbau | Building up; construction; organisation |
| * ufl | Auflage | Edition |
| ufa | Aufnahme | Photographic picture |
| Auftr | Auftreff | Impact (gunnery) |
| Ausb | Ausbeute | Yield |
| Ausb | Ausbildung | Training |
| Ausbr | Ausbrennung | Erosion (of a barrel) |
| Ausf | Ausführung | Execution; completion; model; design |
| Ausg | Ausgabe | Issue; issuance |
| Ausr | Ausrüstung | Arms and equipment |

| | | |
|---------------------------------|--|---|
| autom Gew | automatisches Gewehr | Automatic rifle |
| AVA | See under Warplants, etc (descriptive section) | |
| AW | Abwehrwerfer | Defense smoke shell mortar |
| aZ | auf Zeit | Temporary |
| AZ | Azerylzahl | Acetyl number |
| AZ; Az | Aufschlagzünder | Percussion fuze; PDFz |
| AZf Hbgr | AZ für Haubengranate | PDFz for shells with ballistic cap |
| AZfLWM | AZ für leichte Wurfmine | PDFz for light mortar shell |
| AZfmExMR | AZ für mittlere Exerziermine, Rauch | PDFz for medium practice mine, with smoke |
| AZ 39K | Aufschlagzünder 39, Klappensicherung | PD fuze, pattern 39 with centrifugal safety device |
| AZmK | AZ mit Kappe | Capped percussion fuze |
| AZmV | AZ mit Verzögerung | Delay action percussion fuze |
| AZmVfKGrmP | AZ mit Verzögerung für Kanonengranate mit Panzerkopf | Delay PDFz for cannon shell with armored head |
| AZoV | AZ ohne Verzögerung | Nondelay percussion fuze |
| AZ 269 oV mStö(f) | Aufschlagzünder ohne Verzögerung mit Stössel (französisch) | French impact fuze without delay with tappet (hammer) |
| AZ 38 St | Aufschlagzünder 38, Stahl | Steel PD fuze, pattern 38 |
| AZmRZ | Aufschlagzünder und Brennzünder | Time and percussion fuze (TPFz) (lit Impact and burning fuze) |
| AZ 23 umg | AZ 23 umgeändert mit zwei Verzögerungen | PDFz 23, modified, with two delays |
| AZ 23v (0.15) | AZ 23 vereinfacht mit 0.15 Sekunden Verzögerung | PDFz 23, simplified, with 0.15 seconds delay |
| AZ 23 Zn | Aufschlagzünder 23, Zink | Zinc PD fuze, pattern 23 |
| B | | |
| B; Bat; Batts | Batterie | Battery |
| B | Bau | Construction |
| (b) | belgisch | Belgian (Marking on equipment) |
| B | Beutel | Bag; pouch |
| B | Bombe | Bomb |
| B; Bu | Buchse | Jack; bushing; socket (Rad) |
| B; Bü | Büchse | Rifle; canister; shot gun; tin can |
| B1E, B1EZA and B1EZB | Bombe 1E, etc | Types of 1 kg Inc bombs (TM 9-1985-2, p 48) |
| B1.3E, B1.3EZA and B1.3EZB | Bombe 1.3E, etc | Types of 1.3 kg Inc bombs (TM 9-1985-2, p 49) |
| B2EZ and B2.2EZ | Bombe 2EZ, etc | Types of 2 kg and 2.2 kg Inc bombs (TM 9-1985-2, p 49) |
| BA | Bauamt | Building and construction office |
| Baj | Bajonett | Bayonet |
| BAK; Ball AK | Ballon Abwehr Kanone | AA gun (lit Balloon defense gun) |
| Ball | Ballistik | Ballistics |
| Ball | Ballon | Balloon |
| Baon; Batl | Bataillon | Battalion |
| bas | basisch | basic |
| BASF | See under Warplants (Descriptive section) | |
| B-B (such as SC 250-B) | B-Bombe (Sprengcylindrische 250) | HE cylindrical bomb of three-piece construction; nose-cast steel, body-tube steel and base-arched case steel (TM 9-1985-2, p 8) |
| Bb; Beob | Beobachtungsbatterie | Observation battery |
| BD | Bleidraht | Lead wire; decoupling wire or foil |
| Bd | Boden | Base; bottom |
| Bd | Brand | Fire; incendiary |
| BDC | | Designation of a cluster-bomb container (TM9-1985-2, pp 93-5) |
| BdG; Bd Gesch | Brandgeschoss | Incendiary projectile |
| BdGr | Brandgranate | Incendiary shell |
| BdZ | Bodenzünder | Base detonating fuze (BDFz) |
| BdZd 3.7 cm Pzgr | Bodenzünder der 3.7 cm Panzergranate | PDFz of 37 mm AP shell |
| BE | Besondere Einflüsse | Special factors (Ball) |
| Be; Bet | Beton | Concrete |
| Fefh | Befehlshaber | Commanding officer |
| BeGr; Betgr | Betongranate | Concrete-piercing shell (See also GrBe) |
| beh; behelfsm | behelfsmässig | emergency; hasty; improvised; makeshift |
| BdStz (such as in DOV BdStz 15) | Bodenstütze (DOV Bodenstütze 15) | Base support Meaning of DOV is unknown to us. |

| | | |
|---|--|--|
| Beil | Beilage | Annex; enclosure; appendix |
| Beildg | Beiladung | Increment charge; booster charge |
| beim | bei dem | at; near; about; with |
| Beiw | Beiwagen | Side car |
| Bel | Belagerung | Siege |
| Bel | Belastung | Load; charge; burden |
| Ber | Berichte (der Deutschen Chemischen Gesellschaft) | Reports of the German Chemical Society (Title of a journal). Called now "Chemische Berichte" |
| | beritten | Mounted |
| ber; beritt | Berlin | Berlin |
| Berl | Besatzung | Garrison; crew |
| Bes | Beschiessung | Firing; shelling; bombardment |
| Besch | bespannt | horse-driven |
| besp | See Be | |
| Bei | Betriebs | operational |
| Bei; Betr | See BeGr and GrBe | |
| BeiGr; Betgr | Bettung | Base (fixed gun); foundation (gun emplacement); platform (RR gun) |
| Bett; Bet | Bettungsgeschütz | Outrigger base gun (AA); gun on platform mounting |
| | Beutelkartusche | Propellant charge in a bag |
| Bett Gesch | | |
| Beutelkart (such as in French 10.5 cm shell) | | |
| Bew | Bewaffnung | Arms |
| Bez; Bz | Berzirk | District |
| bezw; bzw | beziehungsweise | respectively; or; and/or |
| Bf; Bhf | Bahnhof | RR station |
| Bfh | Befehlshaber | Commanding officer (CO) |
| BGesch | Beobachtungsgeschoss | Projectile used for adjustment fire |
| Bgw | Bergwerk | Mine |
| BhrGesch | See Bo; BoGesch | |
| BhrPatr; BohrPatr | Bohrpatrone | Demolition cartridge; blasting cartridge |
| BhrPatr 88 | Bohrpatrone 88 | Demolition cartridge 1888 (containing picric acid) |
| BhrPatr 02 | Bohrpatrone 02 | Demolition cartridge 1902 (contg 75 g of TNT) |
| BhrPatr 28 | Bohrpatrone 28 | Demolition cartridge 1928 (contg 100 g of TNT) |
| BhSkL | Behelfssockellafette | Auxiliary pedestal mount |
| Bi (such as SC 50 Bi) | (Sprengcylindrische 50 Bi)(Bombe) | HE cylindrical bomb having a one piece cast steel body machined down (TM 9-1985-2, p6) |
| BK 1 | Blendkörper 1 | Frangible smoke grenade; glass smoke grenade, pattern 1 |
| BK | Bordkanone | Aircraft or shipboard cannon |
| BK (such as Mk 250 BK) | (Mark 25 BK) | Marking on a container with 25 modified red flares and three SD 2 bombs (TM 9-1985-2, p 108) |
| BL | Bordlafette | Gun mount on ship or airplane |
| Bl (black or white stencilling) | Blau | used in conjunction with Deut to indicate blue color of smoke |
| Bl; BIK | Blaukreuz | Blue cross (Ger marking on sternutators)(CWS) |
| Bl | Bleiplombe | Lead seal of protective cap (fuze) |
| Bl (white stencilling) | Blindgeladen; Blindgeschoss | Ammo with inert charge |
| BLC (such as 50 kg BLC) | Blitzlichtcylindrische (Bombe) | Photoflash cylindrical bomb, 50 kg (TM 9-1985-2, p 81) |
| blf | blätterförmig | in leaflets or flakes |
| BLM | See under Warplants (descriptive section) | |
| BIP | Blättchenpulver | Propellant in the form of square flakes (Used in some howitzers) |
| BlWaff | blanke Waffen | Armes blanches (bayonet and other cutting weapons) |
| BMW | See under Warplants (descriptive section) | |
| Bn-Stoff | Brommethyläthylketon | Bromomethylethyl ketone (tear gas) (stable) |
| Bo; BoGesch | Bohrgeschoss | APHE projectile (HE charge exploded after the armor or concrete was pierced) |
| Bo; BoPr (black stencilling) | Bohrgeschoss, Press-stahlform (ausgebohrte Press-stahlgranate) | Forged steel shell with cavity filled with HE |
| Bo (1 inch lettering midway between the rotating band and shoulder) | | Indicates a rotating band of the bimetal type, iron covered with copper (TM 9-1985-3, p 349) |
| Bola | Bodenlafette | Ventral gun mount |
| Bo Stg (black stencilling) | Bohrgeschoss, Stahlgranate | Light case shell of cast steel (TM 9-1985-3, p 349) |
| B Patr | Beobachtungsgeschoss Patrone | Fixed round with a smoke producing projectile used for adjustment fire |
| Br; Bd | Brand | Fire; incendiary |

| | | |
|---|---|--|
| Br (such as Br C 250 A) | Branabombe | Incendiary bomb (TM 9-1985-2, p 35) |
| Br (white stencilling) | Brandgranate | Incendiary shell |
| BK | See Buntr | Incendiary bullet |
| BrG; BrGesch | Brandgeschoss | Incendiary shell |
| Brg; BrGr | Brandgranate | Incendiary shell with tracer |
| Brg m L'spur | Brandgranate mit Leuchtspur | Incendiary shell without tracer |
| Brg o L'spur | Brandgranate ohne Leuchtspur | Railroad gun |
| BrK | Bruno Kanone | Incendiary charge (in a projectile or a bomb) |
| Brdg | Brandladung | Bronze mortar |
| BrMrs | Bronze Mörser | Bruno railroad gun |
| BrNK | Bruno N Kanone | Armor-piercing-incendiary projectile |
| Brpzgr | Brandpanzergranate | Incendiary composition in a projectile or bomb |
| BrSatz | Brandsatz | Incendiary shrapnel shell |
| BrSchrGrPatr | Brandschrapnell Granate Patrone | High-explosive-incendiary projectile |
| BrSpgr; Brspgr | Brandsprenggranate | HE-incendiary-tracer, self-destructing fixed round of ammo |
| BrSprgrPatr L'spur m Zerl (such in 15 mm MG-151) | Brand Sprenggranate Patrone mit Zerlegung | Time fuze (lit Burning fuze) |
| BrZ; BZ; Bz | Brennzünder | Firing; shooting |
| Bs | Beschuss | Proof round (high pressure round) |
| BsPatr | Beschusspatrone | Various types of incendiary bomb containers [See in TM 9-1985-2 (1953), pp 110-11] |
| BSB (such as BSB-360, BSB- 700 and BSB-1000) | _____ | Rectangular, aluminum bomb container [See in TM 9-1985-2 p 98] |
| BSK (such as BSK-36) | _____ | Observation post |
| BSt | Beobachtungsstelle | Concealed stick mine (TM 9-1985-2, p 276) |
| BStbMi | B-Stabmine | Bromacetone (tear gas) (unstable) (CWS) |
| B-Stoff | Bromazeton | Torpedo bomb |
| BSW | See under Warplants (descriptive section) | Boat assault gun |
| BT | Bombentorpedo | Colored smoke |
| BtsK | Bootskanone | Designation of airplanes manufd by Bücker Co |
| Bu | See B; Bu | Bulletin of the Belgian Chemical Society (Journal) |
| Bu | Buntrauch | Bulletin of the French Chemical Society (Journal) |
| Bü | Bücker | Filling in a projectile giving on burst a cloud of vari- colored smoke (See also Buntkreuzmunition) |
| Bu | See B; Bu | Association of manufacturers of benzene |
| Bull (Belg) | Bulletin de la Societé Chimique de Belgique | Time fuze (lit Burning fuze) |
| Bull (Fr) | Bulletin de la Societé Chimique de France | Friction, pull type igniters used in hand grenades (TM 9-1985-2, pp 283-4) |
| Buntr; BR (black stencilling) | Buntrauchsprengladung | Benzene |
| BV | Benzolverband | Bomb sight |
| BZ; Bz; BzZ | Brennzünder | Friction, pull type igniter used in "egg" type grenade (TM 9-1985-2, p 284) |
| BZ-24; BZ-39 | Brennzünder 24; Brennzünder 39 | Bomb sight referring to; in reference to |
| Bz | Benzol | Gasoline |
| BZA | Bombenzielapparat | |
| BZE | Brennzünder E | |
| BZG | Bombenzielgerät | |
| bzg! | bezüglich | |
| Bzn | Benzin | |
| bzw | See bezw | |
| C (such as C/1, C/2 . . . C/12 etc) | Konstruktion (obsolete spelling of Konstruktion) | Model; type; make (when placed after designation of a gun, shell, fuze, etc) |
| C (such as SC 1000-C "Hermann") | (Sprengcylindrische 1000 C) | Marking on a 1000 kg HE cylindrical bomb (See in TM 9-1985-2, pp 9-10) |
| C; CZ; ChZtr Ca | See ChZtr circa (zirca) | about; approximately |
| C-Gesch | C-Geschoss | Streamlined projectile |
| Chl | Chloroform | Chloroform |
| Chm | Chemie | Chemistry |
| Ch-mZ; cMZ | Chemisch-mechanischer Zünder | Chemical-mechanical igniter |
| ChZtr; CZ; C | Chemisches Zentralblatt | German journal similar to Chemical Abstracts |
| CMZ 41 | Chemisch-mechanischer Zünder 41 | Chemical-mechanical type igniter, pattern 41 |

C

| | | |
|---|--|--|
| CMZ-41W | Chemisch-mechanischer Zünder 41W | Chemical-mechanical igniter for delayed action demolition (TM 9-1985-2, p 313) |
| CPVA | See under Warplants, etc (descriptive section) | |
| Cu (white stencilling) | Kupfer | Copper driving band |
| C-Zug | Zugmaschine für schwerste Artillerie | Prime mover for heavy artillery |
| D | | |
| D; Dpf | Dampfer | Steamer |
| D | Dauerfeuer | Continuous fire |
| (d) | deutsch | German (marking on equipment) |
| D | Dichte | Specific gravity; density |
| D | See Digi | |
| D; Dm | Durchmesser | Diameter |
| D (in fuze designation Hbgr Z 35D) | (Haubengranatenzünder 35D) | Rocket nose fuze under BC, (See in TM 9-1985-3, p 585) |
| D (in igniter designation, DZ 35) | Druck (Druckzünder 35) | Pressure type igniter (TM 9-1985-2, pp 295-6) |
| DA (in fuze designations, such as DAAZ) | Direkte Aktion (Direkte Aktion Aufschlagzünder) | Designates a direct action fuze, such as DA Impact Fuze (TM 9-1985-3, pp 552, 555, 556, 561) |
| D A -G | Dynamit Aktiengesellschaft | Dynamite Joint Stock Co |
| (dän) | dänisch | Danish (marking on equipment) |
| Dap | Dapolin | Trademark of motor fuel |
| DB; DF | Dreibein; Dreifuss | Tripod |
| DD-Gesch; DdGesch | Dumdumgeschoss | Dumdum bullet |
| Dep | Depesche | Telegram |
| Deut (Gesch); Dt | Deutgeschoss | Projectile giving on burst a cloud of colored smoke serving as indicator |
| Deut (Patr) | Deutpatrone | Indicator cartridge, such as for grenade pistol |
| Df | See DB | |
| DFS | See under Warplants (descriptive section) | |
| Di | Dinitrobenzol | Dinitrobenzene (DNB) |
| Digi | Diglykolnitrat | Diethyleneglycoldinitrate (DEGDN) |
| Digi; DigIP; D | Diglykolpulver | Double-base propellant DEGDN-NC, stabilized with centralite, with K sulfate added to reduce flash DEGDN-NC (double base) square flake propellant |
| Digi BIP | Diglykol Blättchenpulver | DEGDN-NC, improved propellant |
| DigiP | See Digi | DEGDN-NC (double-base) propellant (a circular disc with a central hole) |
| DigiPV | Diglykolpulver, verbessert | DEGDN-NC (double base) tubular propellant |
| Digi RGP | Diglykol Ringpulver | DEGDN-NC (double base) strip propellant |
| Digi RP | Diglykol Röhrenpulver | German industrial standards |
| Digi StrP | Diglykol Streifenpulver | Two-barreled mount |
| DIN | Deutsche Industrie Normen | Designation of a German commercial air line |
| DL | Doppellafette | Adamsite (CWS) |
| DLH | Deutsche Lufthansa | Designation of airplanes manufd by Dornier Co |
| DM ; Adamsit | Diphenylaminchlorarsin | Marking on 150 mm smoke shell mortar 38 |
| Do | Dornier | Marking on a DEGDN propellant used in mortar ammo (Recognition Handbook for German Ammunition Sup Hqs AEF, April 1945, p 201) |
| DO (such as in 15 cm DO Ger 38) | 15 cm DO Gerät 38 | Combination fuze; time and percussion fuze (TPFz) |
| DOP [such as in DOP 15 Wu (Digi)] | | TPFz with folding safety device |
| DoppZ; DoppZ; DZ | Doppelzünder | TPFz, new construction |
| DoppZ mK | Doppelzünder mit Klappen siehe.u.r.f. | TPFz, 60 seconds burning time |
| DoppZ nF | Doppelzünder neue Fertigung | TPFz, 60 seconds burning time, centrifugally operated |
| DoppZ S/60 | Doppelzünder, Sekunden 60 | |
| DoppZ S/60 Fl | Doppelzünder Sekunden 60, Fliedkratt- antrieb | |
| DoppZ S/60 Geb | Doppelzünder, Sekunden 60, Gebirgs- geschütz | TPFz 60 seconds for mountain gun |
| DoppZ S/60s | Doppelzünder, Sekunden 60, schwer | TPFz, 60 seconds, heavy |
| DOV (in fuze designation such as BJZ DOV) | (Bodenzünder DOV) | Marking on a base-detonating fuze used in 150 mm rocket projectile (TM 9-1985-3, p 622) |
| DOV (in booster designation DOV Zdlg C/98Np) | DOV Zündladung, Konstruktion 98, Nipolit) | Marking on the PETN booster, pattern 98 used in 150 mm smoke rocket 41 (15 cm Wurfgranate 41Nb) |

| | | |
|--------------------------------|---|--|
| DPG | See under Warplants (descriptive section) | |
| Dr | Doctor | |
| DR | Deutsches Reich | German State |
| DR | See Dig! RP | |
| DRP | Deutsches Reichspatent | German State Patent |
| DRP angem | Deutsches Reichspatent angemeldet | German State Patent applied for |
| D/See (such as in NC 50 D/See) | (50 kg Nebelcylindrische Bombe D/See) | Marking on 50 kg Cylindrical Smoke Bomb, Floating (TM 9-1985-2, p59) |
| DST; DSt | See Dig! StP | |
| Si (Gesch) | See Deut (Gesch) | |
| Du | Duplex | Duplex |
| Du | Düse | Nozzle; jet; injector; vent (rocket) |
| DuW | Düsenwaffe | Jet weapon such as Panzerfaust (lit Vent weapon) |
| DV | See Dig!PV | |
| DVA | See under Warplants (descriptive section) | |
| DVA | See under Warplants (descriptive section) | |
| DWM | See under Warplants (descriptive section) | |
| Dyn | Dynamit | Dynamite |
| DZ | See DoppZ | |
| DZ | Druckzünder | Pressure type igniter |
| DZ 35(A) | Druckzünder 35(A) | Pressure igniter used in heavy A/T mine and some prepared charges (TM 9-1985-2, p 295) |
| DZ 35 (B) | Druckzünder 35(B) | Pressure igniter used in bobby traps and some prepared charges (TM 9-1985-2, p 296) |
| DZG | Deckungszünder | Protected (sheltered) optical aiming device |

E

| | | |
|---|--------------------------------|--|
| E | Einfeuer | Single shot fire |
| (E) (when marked on projectiles or weapons) | Eisenbahn | Railway; railroad |
| E; El | Elektrisch | electric |
| E | Elektron | Electron |
| E | Elektron | An alloy of Mg and Al used as an incendiary (See also ET) |
| E; e | empfindlich | sensitive |
| (e) | englisch | English (marking on equipment) |
| E | Entfernung | Range; distance |
| E (such as in BZE) | (BrennzünderE) | Marking on a friction, pull-type igniter (TM 9-1985-2, p 284) |
| E-4 | Enzian-4 | Air-to-air weapon called "Great Enzian" (TM 9-1985-2, p 229) |
| EAZ | Empfindlicher Aufschlagzünder | Superquick impact fuze |
| Ec | | With rear driving band only |
| E-Flak | Eisenbahn-Flugzeugabwehrkanone | RR antiaircraft gun |
| FHZ | Empfindlicher Haubitzzünder | Sensitive howitzer fuze; graze fuze |
| Ei (black stenciling) | Einschiessgeschoss | Projectile used for adjustment fire; sea ranging shell |
| Eibgr | Eierhandgranate | Egg shaped hand grenade |
| EinL; El | Einlegelauf | Sub-caliber barrel |
| EinLR | Einlegerohr | Sub-caliber barrel; liner |
| EisMi | See FIEsMi | |
| EKZ; EKz; EKzdr | Eisenbahkopfzünder | PDFz of shell with ballistic caps used in RR guns |
| EKZ | empfindlicher Kanonenzünder | Sensitive cannon fuze; graze gun fuze |
| EKz; EKZ; EKZdr | empfindlicher Kopfzünder | Sensitive type of PDFz |
| El; E | elektrisch | electric |
| EL | Erdkampflafette | Ground mount |
| EL | Ersatz Lafette | Replacement gun mount |
| E-Latte | Entfernungslatte | Aiming post |
| EIAZ; eIAZ | Elektrischer Aufschlagzünder | Electric impact fuze |
| eIRDZ | See ERZ; ERDZ | |
| EIZ; eIZ | Elektrischer Zünder | Electric fuze |
| EIZZ; eIZZ | elektrischer Zeitzünder | Electric time fuze |
| Em; EMG | Entfernungsmessgerät | Range finder |
| EMK | Elektromotorische kraft | Electromotive force (EMF) |
| EMP | Erma-Maschinenpistole | Erma automatic pistol |
| ENZ; enz (in fuze designation Mk 35 ENZ 3/40) | (Mark 35 ENZ 3/40) | Marking on a Czech PD fuze used in German 47 mm shell (TM 9-1985-3, p 368) |

| | | |
|----------------------|---|--|
| EP | Einheitspulver | Standard propellant (See descriptive part) |
| EP | See EPED | |
| EPGL'sp | Exerzierrone Granate mit Leuchtspur | Drill cartridge with tracer projectile |
| EPS | Effektive Pferdestärke | Actual horsepower |
| Er; Erstp | Erstarrungspunkt | Solidification point |
| ERDZ | See ERZ; ERDZ | |
| Ers | Ersatz | Substitute; replacement; spare part |
| ErsRP; EP | Ersatzröhrenpulver | Substitute, tubular propellant |
| Ersst; ESr | Ersatzstück | Substitute piece; inert item resembling in appearance a fuze, found in front section of some projectiles |
| ERZ; ERDZ | Elektrischer Randdüsenzünder | Electric rimvent fuze (Ammo) |
| ERZ 39 | Elektrischer Raketenzünder 39 | Electric igniter for rocket propellant, pattern 39 (TM 9-1985-3, p 623) |
| Es | Einschiessgeschoss | Registering projectile; adjustment fire projectile |
| ESMi | See FIEsMi | |
| ESMiZ-40 | Elektrischer S-Mineazünder | Electric pressure igniter used in S-Mine |
| ESN | Einzelsternpatrone | Single star cartridge |
| ESr | See Ersst | |
| EI | Elektron-Thermit | Incendiary missile made of Elektron (Mg-Al alloy) and filled with thermite (Al-Fe oxide) |
| EV | Eingetragener Verein | Chartered Society; Registered Company |
| Ex (red stencilling) | Exerziergeschoss | Drill ammunition; practice ammunition |
| ExB | Exerzierbombe | Practice bomb |
| ExMu | Exerziemunition | Drill ammunition |
| ExPatr | Exerzierrone | Drill cartridge |
| EXRZ f IWM | Exerzierrrauchzünder für leichte Wurfmine | Practice smoke fuze for mortar mine |
| EZ | empfindlicher Zünder | Instantaneous fuze; superquick fuze (lit Sensitive fuze) |
| EZ | Entlastungszünder | Antilifting igniter (with HE charge) |
| EZ | Esterzahl | Ester number |
| EZ-44 | Empfindlicher Zünder, patr. 44 | Antilifting and antiremoval device (release or pressure type) placed beneath land mines (TM 9-1985-3, p 318) |

F

| | | |
|--|--|--|
| F; Fahr | Fahrenheit | Fahrenheit |
| F; FS | Fallschirm | Parachute |
| F; Fd | Feld | Field (of battle) |
| F (black stencilling) | Fernladung | Indicated a shell to be fired only with super charge of propellant |
| F (in projectile designation such as FHGr F) | Ferngeschoss (Feldhaubitze granate Ferngeschoss) | Long range shell or propellant (for a field howitzer) |
| F (such as in DoppZ nF) | Fertigung (Doppelzünder neue Fertigung) | Construction (Time-percussion fuze, new construction) |
| F | Fliehbolzen | Centrifugal safety pin |
| F; Fl | See Fl; F and also Fg | |
| F; Flzg | See Flzg | |
| F (in FZ) | See FZ | |
| (f) | französisch | Franch (marking on equipment) |
| f | für | for |
| F-25 } | Feuerlilie 25 } | Fire lilly 25 and 55, rocket-propelled guided missiles (TM 9-1985-2, pp 223-6) |
| F-55 } | Feuerlilie 55 } | |
| FA; FdA; Fda; Felda | Feldartillerie | Field artillery |
| FA (such as in flare MkC 50 FA) | Fallschirmleuchtbombe (Mark C 50 FA) | Part of designation of single candle parachute flare described in TM 9-1985-2 p 71 |
| Fab; Fabr; Fbr | Fabrik | Factory; plant |
| F & L | Franken und Lunenschloss | Makers of Dreyse carbine |
| FAZ | Fernladung Aufschlagzünder | Long distance impact fuze |
| FB | Führungsband | Driving band (in shell) |
| FB (such as in flare: FB 50) | Fallschirmleuchtbombe (FB 50) | Mark on a single candle parachute flare described in TM 9-1985-2, p 67 |
| Fb; Flieb | Fliehbolzen | Centrifugal bolt (fuze safety device) |
| Fd | See F; Fd | |
| FdA | See FA | |
| FDO | Felddienstordnung | Field Service Regulation |
| Fdw | See Fldw | |
| Fe; Fernspr | Fernsprecher | Telephone |
| Feba; FE | Feldeisenbahn | Light narrow gage RR |

| | | |
|---|--|---|
| Felda | Feldkampfatillerie | Long-range artillery |
| Feldat | See FA | |
| Feldg; Feldgend | Feldartilleriegerät | Field artillery equipment |
| Feldw | Feldgendarm; Feldgendarmarie | Military policeman; military police |
| FEP | See under Warplants, etc in descriptive part | |
| Fepo | Feldpolizei | Field police |
| Fernf | Fernfeuer | Long-range fire |
| Fesh | Fernsehen | Television |
| FES (white stencilling, such as in 10.5 cm FHGr 38 FES) | Führungsring, Sintereisen (10.5 cm Feldhaubitzzgranate 38 FES) | Sintered iron rotating band (such as in 105 mm field howitzer shell 38 FES) |
| FessB | Fesselballon | Captive balloon; sausage balloon |
| Fest | Festung | Fortification; fortress; fort |
| Festkr | Festungskrieg | Siege warfare |
| Feu | Feuer | Fire |
| Feuerw | Feuerwaffen | Firearms |
| Feuerw | Feuerwerker | Ordnance sergeant |
| FEW (white stencilling such as in 15.2 cm Sprgr FEW) | Führungsring, Weicheisen (15.2 cm Sprenggranate FEW) | Soft iron rotating band (in 152 mm HE shell) |
| FF | Festungsflak | Fortress AA gun; stationary AA gun |
| FF | Flugzeugflügel | Wing of an airplane |
| FF (MK) | (Maschinenkanone) im Flügel eines Flugzeug | Rapid fire cannon in the wing of an airplane |
| FFA | See under Warplants, etc (descriptive section) | |
| FFM (such as 2 cm MG FFM) | (2 cm Maschinengewehr FFM) | Marking on a 20 mm AC machine gun |
| Fg, Fgst | Fahrgestell | Chassis |
| FG; FGesch | Feldgeschütz | Field piece; field gun |
| FG; FGew; FSJG-42 | Fallschirmjäger Gewehr-42 | Paratroop fully automatic rifle |
| Fg; Fl; Flg (AZ Zerl Fg) | Fliehgewichtsantrieb (Aufschlagzünder, Zerleger, Fliehgewichtsantrieb) | Operated by centrifugal force (Fz) |
| (ZtZ S/30 Fg) | Zeitzünder, Sekunden 30. Fliehgewichtsantrieb | PD fuze, self-destroying, centrifugal (TM 9-1985-3, p 546) |
| FGesch | Ferngeschoss | Mechanical time PD fuze in which the motive power was derived from centrifugal force; 30 seconds delay (TM 9-1985-3, p 597) |
| FgW-43 | Festungswerfer 43 | Long range projectile |
| FGZ | See under Warplants, etc (descriptive section) | Fortress mortar; fixed mortar |
| FH | Feldhaubitze | Field howitzer |
| FHG; Nb | Feldhaubitzzgranate Nebel | Field howitzer smoke shell |
| FHG; Stg | Feldhaubitzzgranate, Stahlring | Field howitzer shell, steel ring |
| FHSchr | Feldhaubitzzschrapnell | Field howitzer shrapnel |
| Fhz | Fahrzeug | Vehicle |
| Fi | Fieseler | Designation of airplanes manufactured by Fieseler Co |
| FK | Federkapsel | Cap over a spring |
| FK | Feldkanone | Field cannon |
| Fk | Funk | Radio |
| FKFS | See under Warplants (descriptive section) | |
| Fl; Flg | Flagge | Flag |
| Fl; F (such as in DoppZ S/60 Fl) | Fliehkraftzünder, Fliehgewichtsantrieb (Doppelzünder, Sekunden 60, Fliehgewichtsantrieb) | Centrifugally operated fuze (Time-percussion fuze, 60 seconds burning time, centrifugal) |
| Fla | Flugzeugabwehr | AA defense |
| Flachf | Flachfeuer | Flat trajectory fire |
| FlaDrMG | Fliegerabwehr-Dreifachmaschinengewehr | AA triple machine gun |
| Flak | Flugzeugabwehrkanone | AA cannon; AA gun |
| Flakvierling 38 (2 cm) | 2 cm Flugabwehr-Vierling | 20 mm Four-barreled AA gun |
| Flam | Flugabwehrmaschinenwaffen | Automatic AA weapons |
| Flam (B) (such as: C-250) | Flammenöl Bombe | Incendiary bomb filled with flammable oil |
| FIDü | Flügeldüse | Jet motor mounted on a wing |
| FIDrSt | Fliegerdrehstütze | Meaning unknown to us |
| Fldw; Feldw; Fdw; Fw | Feldwebel | Master Sergeant |
| FIEisMi; FIEsMi; EoMi (FIEisMi 42) | FlaScheneismine; Eismine (FlaScheneismine 42) | Glass bottle antipersonnel land mine (Glass bottle A/P mine 42) |

FIEsMi
FIEsMiz

Fleucht
FM; FIMi
FIMW
FITMi 41; FITrMi 41
Flugb
Flüggz; Flzg; Flz
FIW; FmW
FM
FMG
FMG
FmW
FoFü
Fp
Fp02
Fp 5
Fp 88
Fp 60/40
Fp C/02
FPatr
Frw
FS; Fschm
FSchr
Fsp
Fst; Fs
FSt; FuSt; FS
F-Stoff
FSTR
Fu
FuMG
FuSt
FuTr
FuTu
Fvtg; Fvtl; Fvt
Fw
FW; Fw
FZ (such as
FZ 60)

See FIEis Mi
Flascheneisminen Zünder
Fallschirmleuchtpatrone
Flügelmine
Flügelminenwerfer
Flussstreibmine 41
Flugboot
Flugzeug
Flammenwerfer
Feldmarschall
Fernmessgerät
Flugzeugabwehrmaschinengewehr
See FIW
See under Warplants (descriptive section)
Füllpulver
Füllpulver 02
Füllpulver 5
Füllpulver 88
Füllpulver 60/40
Füllpulver C/02
Feldpatrone
Feuerwerker
Fallschirm
Feld-Schrapnell
Fernsprecher
Festung
Funkstelle; Funkenstation
Titantrichlorid
Fallschirmtruppen
Funk; Funker
Funkmessgerät
See FSt
Funktrupp
Funkturn
Feuerverteilung
See Fldw
Focke-Wulf
(F Zünder 60)

Pressure igniter for A/P glass bottle mine (TM 9-1985-2, p 307)
Parachute-flare signal cartridge
Fin-stabilized mortar projectile
Trench mortar firing finned projectiles
River drifting (floating) mine, pattern 41
Flying boat
Airplane
Flame thrower
Field marshal
Range finder
Rapid-fire AA machine gun
Filler; filling explosive; bursting charge
1902 pattern filling (TNT)
TNT contg 5% wax
1888 pattern filling (Cast P A)
60/40 filling (TNT 60 and Am nitrate 40%)
Same as Fp 02
Field gun cartridge (fixed ammunition)
Artificer; ordnance sergeant
Parachute
Field gun shrapnel
Telephone
Fortress; fort; fortification
Radio station
Titanium tetrachloride (smoke producing agent)
Parachute troops
Radio; radio operator
Radar
Signal Corps detachment
Radio sending tower
Fire distribution
Designation of airplanes built by Focke-Wulf Co
Marking on a clockwork aerial burst fuze (See in TM 9-1985-2, p 186)

G

G
G; Ger
G; Gesch
G; Gesch
G; Gew
G; g
G; Gr
G (propelling charge stencil)
G 98; Gew 98
Gamma-Mrs
Gbd; Geb
Gbh
GB; GBomb
GDH
Geb; Gb
Geb (in fuze designation
AZ 23 Geb)
GebG; GebGesch
GebGr
GebH; GebHauh
GebIG; GebJG
GebK

Gas
Gerät
See Gs
Geschütz
Gewehr
Gramm
Granate
Pulvermasse G (Gallwitz)
Gewehr 1898
Gamma Mörser
Gebäude
Güterbahnhof
Gasbombe
Gasdruckhülse
Gebirg
Gebirgs-
(Aufschlagzünder 23, Gebirggeschütz)
Gebirggeschütz
Gebirgsgranate
Gebirgsaubitze
Gebirgsinfanteriegeschütz; Gebirgs-
jägersgeschütz
Gebirgskanone

Gas
Equipment; apparatus; device
Gun; cannon
Rifle
Gram
Shell; grenade
Propellant with a standard heat of explosion (690 kcal/kg)
Rifle, model 1898
420 mm Heavy mortar
Building
Freight yard
Chemical bomb
High-pressure cartridge
Mountain
Mountain-
(PD fuze 23 for mountain ordnance)
Mountain gun
Shell for mountain gun
Mountain howitzer; pack howitzer
Mountain infantry gun; or howitzer
Mountain cannon

| | | |
|-------------------------------|---------------------------------------|--|
| Gef | Gefreiter | Acting corporal; private first class |
| GebLdg | Geballteladung | Concentrated charge consisting of several explosive blocks tied together; prepared charge |
| GebLdg Abg | Geballteladung | Prepared TNT charge, 3kg |
| geh. | geheim | secret |
| gel; Gel | geladen | loaded |
| Gel; GelK | Gelbkreuz | Yellow cross (Ger marking on vesicants)(CWS) |
| gel | geliefert | delivered |
| GemPol | Gemeindepolizei | Township police; local police |
| Gen | General | General |
| GenStbH | Generalstab des Heeres | Army General Staff |
| GP; GP | gepanzert | armored |
| Ger; G | Gerät | Equipment |
| Gesch; G | Geschoss | Projectile; missile |
| Gesch; G | Geschütz | Piece; gun; cannon |
| GeschGiess | Geschützgiesserei | Gun foundry |
| Gestapo | Geheime Staatspolizei | Secret state police |
| Gew; Gwr; G | Gewehr | Rifle |
| GewGr; Gg | Gewehrgranate | Rifle grenade |
| GewGrGew | Gewehrgranatengewehr | Grenade rifle |
| GewSprgt | Gewehrsprenggranate | HE rifle grenade |
| gez | gezogen | rifled |
| Gf | Geschosfabrik | Shell factory |
| Gf; GeschFabr | Geschützfabrik | Gun factory |
| GFM | Generalfeldmarschal | Field marshal |
| Gg | Geschossgewicht | Weight of projectile |
| Gg | See GewGr | |
| Gg; Gr | Grauguss | Cast Iron |
| GgP; GewGrPz | Gewehrgranate Panzer | A/T rifle grenade |
| GGr; Ggr | Gasgranate | Gas grenade |
| GH | See GebH | |
| GK | See GebK | |
| GKart | Gewehrkartusche | Cartridge case |
| GKF | gepanzerte Kampffahrzeuge | Armored combat vehicle |
| GKw | Geschützkraftwagen | Self-propelled gun mount |
| GL | Gauleiter | District leader |
| gl | glatt | smooth; even |
| Gl; Glat | Gleichstrom | Direct current |
| GlDg | Gewichtladung | Weight of live projectile |
| Gleisk | Gleiskettenfahrzeug | Full-track vehicle |
| GleiskPr | Gleisketten-Panzerfahrzeug | Full-track armored vehicle |
| glGesch | Glattes Geschütz | Smooth-bore gun |
| GL'spur; Gl'spur | Glimmleuchtpur; Glimmspur | Tracer with glowing composition dim tracer |
| Glühz | Gliühziinder | Low tension electrical igniter |
| glWM | glatte Wurfmine | Smooth bore mine-thrower shell |
| Gm | Gasmaste | Gas mask |
| GM | Generalmajor | Major General |
| GmbH | Gesellschaft mit beschränkter Haftung | Company with limited liability; limited company |
| Gmi | Geschossmine | Mine made from a shell |
| Go | Gotha | Designation of airplanes built by Gothaer Waggonfabrik |
| GP | gepanzert | armored |
| GP; G Pulver | Gallwitz Pulver | DEGDN propellant developed in 1930's by General Uto Gallwitz (See "G" Pulver in descriptive section) |
| Gr; G | Granate (See also Sprgr) | Grenade; shell; projectile |
| gr | grau | gray |
| Gr | Grenze | Frontier |
| gr; Gr | Gross | large |
| gr | grün | green |
| GrB (such as GrB 39 & GrB 43) | Granatbüchse | Antitank grenade rifle |
| GrBe | Granate Beton | Anticoncrete shell |
| grBlP | grobes Blättchenpulver | Propellant in large flakes |
| GReisGr | Gewehr Reichsweite Granate | Long-range rifle grenade |
| Grf | Granatfüllung | Shell filling; bursting charge of a projectile |
| Grf 88 | Granatfüllung 88 | Shell filler, pattern 1888 (picric acid) |
| Grf 02 | Granatfüllung 02 | Shell filler pattern 1902 (TNT) |
| Grkz | Grünkreuz | Green cross (CWS) |

| | | |
|------------------------------|---------------------------------|---|
| grLdg | grosse Ladung | Large charge |
| Grof | grosser Flammenwerfer | Heavy flame-thrower (on two-wheel carrier) |
| GrPatr (See also Sprgr Patr) | Granate Patrone | Fixed ammunition HE shell |
| Grundldg | Grundladung | Main charge; base charge |
| GrW | Granatwerfer | A/T grenade rifle; grenade projector; mortar |
| GrW 5ling | Granatwerferfüßling | Five-barreled automatic mortar |
| GrZ | Granatzünder | Fuze for HE shell |
| grZldg | grosse Zündladung | Large igniting charge; large primer |
| Gs; G; Geschl | Geschoss | Projectile |
| Gu; Gup | Gudolpulver | Double base DEGDN-NC, low calorific value, propellant containing about 30% Gudol (nitroguanidine) |
| GuBlp | Gudolblättchenpulver | Gu propellant in the form of square flakes |
| GuRP | Gudolröhrenpulver | Gu tubular propellant |
| GwFSLtGr | Gewehr Fallschirm Leuchtgranate | Illuminating parachute rifle grenade (TM 9-1985-2, p 339) |
| GwGrGer | Gewehrgranategerät | Rifle grenade equipment |
| Gwr | See Gew | |
| GwrGr | See GewGr | |
| GwrSprgr | See GewSprgr | |

H

| | | |
|---------------------------------|------------------------------|--|
| H; Hb; Hbe | See Hb | |
| H; Haub | Haubitze | Howitzer |
| H; Hptm | Hauptmann | Captain |
| H | Heer | Army |
| 'h, 'H | gehärtet | hardened |
| H | Hexogen | RDX |
| (h) | holländisch | Dutch (mark on equipment) |
| H5; H10; H15 etc | Hexogen 5, etc | RDX 1 5, etc per cent wax |
| H 15; Hldg 15 (H 50 + Fp02 50%) | Hohlladung 15 | Hollow charge containing 15 kg 50/50-RDX/TNT mixture |
| HA | Hexogen-Aluminium | RDX-Al explosive |
| HA-41 | Hexogen-Aluminium 41 | RDX-Al explosive pattern 41 |
| Ha | Hamburg | Designation of airplanes built by Blohm & Voss Co, Hamburg |
| Haf; Hfa | Hafen | Port; harbor |
| Haft; HaftHldg | Haft Hohlladung | Magnetic antitank hollow charge |
| Haft H3 | Haft Hohlladung, Hexogen 3kg | Magnetic HoC, 3kg RDX |
| Halbpzgr | Halbpanzergranate | SAP projectile (literally Half armor-piercing) |
| Haube | See Hb; Hbe | |
| Hauptkart; HptKart | Hauptkartusche | Main propelling charge in non-fixed ammunition |
| Hb; Hbe; Haube | Haube | Ballistic cap (false cap or windshield) on some larger caliber shells (TM 9-1985-3, p 491) |
| Hbf; Hbhf | Hauptbahnhof | Main depot; main RR station |
| Hbgr; HbGr | Haubengranate | Shell with ballistic cap (BC) |
| HbgrZ | Haubengranatenzünder | PDFz for use under BC |
| HbSchr | Haubenschrapnell | Schrapnel with BC |
| Hdb | Handbuch | Handbook; manual |
| Hdfw | Handfeuerwaffe | Small fire arms |
| HdGr | See Hgr | |
| Hdgr | Handgriff | Handle |
| HDP or V-3 | Hochdruckpumpe | See in descriptive section |
| He | Heinkel | Designation of airplanes built by Heinkel Co |
| HF | Hochfrequenz | High frequency (Rad) |
| Hf | Heeresfahrzeug | Army vehicle |
| HFlak | Heeresflugabwehrkanone | Army AA gun |
| HFu | Heeres-Funkstelle | Army radio station |
| Hgr; HdGr | Handgranate | Hand grenade |
| HGr | Haubitzegranate | Howitzer shell |
| HGrZ; HbgrZ | Haubitzegranatenzünder | Fuze for howitzer shells |
| HGs | Holzgeschoss | Wooden shell (dummy) |
| HK (black stencilling) | Hartkern | Tungsten core (lit Hard core) |
| HK; HKart; HülsKart | Hülsenkartusche | Cartridge (in non-fixed ammo) as opposed to bag |
| HL | Hügelafette | Suspended gun mount |
| HL (black stencilling); HL; | Hohlladung | Hollow charge (HoC) such as A/T projectiles; shaped charge |
| Hldg | | Types of hollow charges (See TM 9-1985-3, pp 407, 411, and 313) |
| HL/A; HL/B & HL/C | Hohlladungen A, B and C | |

| | | |
|-------------------------------------|---|---|
| HLB | Hohlladungsbombe | HoC bomb |
| Hldg 12.5 kg | Hohlladung 12.5 kg | Prepared HoC, 12.5 kg TNT |
| Hldg 50 kg | Hohlladung 50 kg | Prepared HoC, 50 kg, in two parts |
| HA | Heeresmunitionsanstalt | Office of Army Ammunition |
| HMi | Holzmine | Wooden mine |
| HML | Heeresmunitionslager | Army Ammunition Depot |
| HP | Horchposten | Listening post |
| Hpt | Haupt | Chief, principal |
| Hpt; Hptst | Hauptstadt | Capital |
| HptKart; HauptKart | Hauptkartusche | Main propellant charge in ammunition other than fixed |
| Hpt Ldg | Hauptladung | Base charge of blasting cup of detonator (lit main charge) |
| hptm | Hauptmann | Captain |
| Hptwm | Hauptwachtmeister | First sergeant (Arty or Cavy) |
| HPzgr | Halbpanzergranate | SAP projectile |
| HRg | Haltering | Retaining ring |
| HRgP | Haubitze-Ringpulver | Propellant in rings for light field howitzer |
| Hs | Henschel | Designation of airplanes and guided missiles built by Henschel Co |
| Hschr | Haubitze-Schrapnell | Howitzer shrapnel |
| HT | Haubitze-in-Turm | Turret howitzer (See also teHT) |
| HTA | Hexogen-Trotyl-Aluminium | RDX-TNT-Al explosive mixture |
| HülsEnt | See HK; HKart, etc | |
| Huc (such as in AZC (Hut)*3) | (Aufschlagzünder C(Hut)* 3) | Marking on a mechanical impact bomb fuze type 3 |
| HWA; HWaA | Heereswa.fenamnt | Army Ordnance Office (Branch of the OKH) |
| HWZ | See under Warplants (descriptive section) | |
| HZgA | Heereszeugamt | Army, Ordnance and quartermaster department |
| I | | |
| i | im; in; ins | in; in the |
| I; Inf | Infanterie | infantry |
| I; Ing | Ingenieur | Engineer |
| (i) | italienisch | Italian (marking on equipment) |
| IdA | Inspekteur der Artillerie | Inspector of Artillery |
| iG; IGesch | Infanteriegeschütz | Infantry piece; infantry howitzer |
| IG | Interessengemeinschaft | Association for Furtherance of Mutual Interest; Trust |
| IGFarben | Interessengemeinschaft Farbenindustrie | Dye Industry Trust |
| IGesch | See IG; IGesch | |
| IGK | Infanteriegeschütz Kompanie | Infantry howitzer company |
| Igr | Infanteriegranate | Shell for infantry piece |
| IgrZ | Infanteriegranate-Zünder | Infantry shell fuze |
| iHL | in Haubitze-Lafette | or howitzer mount; on howitzer carriage |
| ij | im Jahre | in the year |
| iKL; iKasLaf | in Kasematten-Lafette | in casemate mount |
| iKatLaf | in Küsten-Lafette | in coast defense mount |
| iL | in Ladestreifen | in clips |
| iMraLaf | in Mörser-Lafette | in mortar mount |
| iPL; iPzLaf | in Panzer-Lafette | in shielded mount |
| iRL; iRLaf | in Rad-Lafette | on wheeled carriage |
| iSL; iSLaf | in Schirm-Lafette | On carriage with overhead shield |
| IZ; Iz | Innenzünder | Internal fuze |
| J | | |
| J; Jäg; Jgr | Jäger | Ranger; rifleman in light infantry; pursuit plane |
| J | Jagdflugzeug | Pursuit plane |
| J | Jahr | Year |
| j | jährlich | yearly |
| j | jüdisch | Jewish |
| (j) | jugoslawisch | Yugoslavian (marking on equipment) |
| J (in bomb designation SC 50 J) | (Sprengcylindrische Bombe 50 J) | Marking on a 50 kg HE cylindrical bomb having one-piece nose and body (TM 9-1985-2, p 8) |
| J/2 (in bomb designation SC 50 J/2) | (Sprengcylindrische Bombe 50 J/2) | Marking on a 50 kg HE cylindrical bomb having drawn steel body and pressed steel nose (TM 9-1985-2, p8) |

Ja (in bomb designation
Sc 50 Ja)

Jabo
Jäg
(Jap)
JB (in bomb designation
Sc 50 JB)
JC (in bomb designation
Sc 50 JC)
JF (such as
JF-04)
JG; JGesch
JadPz (PzJäg)

Jgr
Jgr; JGr
Jgr?
ju

K
K; Kan
K; Kar; Kb
K; Kt
K (such as
3.7 cm Pak K)
K
K
K
K (in fuze designation
Dopp Z. 28K)
K; Kast
K (in fuze designation
mVuK)
K (in bomb designation
Sc 250-K)
K3
K5
K12
K18
K 18/40
K; kl
KA
Kal
Kar 98k
Kart
Kart (Compare with Patr)

Karb
Kartd
Kart ein

Karth; Karth
KertMu

Kartvorl
Kat
Kb
KBett
KC (Bombe)
KC Flam (Bombe)
KDF

(Sprengcylindrische Bombe 50 Ja)

Jagdbomber
See J; Jäg; Jgr
japanisch

(Sprengcylindrische Bombe 50 JB)

(Sprengcylindrische Bombe 50 JC)

(J-Feder 504)
Jägergeschütz
Jagdpanzer (Panzerjäger)

See J; Jäg
Jägergranate
Jägergranatzünder
Junkers

Marking on a 50 kg HE cylindrical bomb having one piece drawn steel body (TM 9-1985-2, p 6)
Pursuit bomber

Japanese (marking on equipment)
Marking on a 50 kg HE cylindrical bomb, an improved version of J (TM 9-1985-2, p 8)
Marking on a HE cylindrical bomb having drawn steel body and pressed steel nose (TM 9-1985-2, p 8)
Marking on a clockwork long-delay igniter (TM 9-1985-2, p 309)
Light infantry piece (gun or howitzer)
(Tank destroyer; tank hunter (See under Panzer in the descriptive part)

Light infantry gun projectile
Percussion fuze for use with light infantry gun projectiles
Designation of airplanes built by Junkers Co

K

Kalium
Kanone
Karabiner
Kartätsche
Kasematte
(3.7 cm Panzerabwehrkanone-Kasematte)
Kasten
Kern
Krieg
Kanone
(Doppel Zünder 28 Kanone)
Kasten
Klappensicherung
(mit Verzögerung und Klappensicherung)

(Sprengcylindrische 250-K)
Kanone 3
Kanone 5
Kanone 12
Kanonen 18
Kanone 18/40
klein
Küstenartillerie
Kaliber
Karabiner 98 kurz
Kartätsche
Kartusche

Kartuschbeutel
Kartuschdeckel
Kartusche,einfach

Kartuschenhülse
Kartuschenmunition

Kartuschenvorlage
Kaltklebekitt
See K; Kar
Kanone in Bettung
Kampfstoffcylindrische (Bombe)
Kampfcylindrische Flammenbl Bombe
Kraft durch Freude

Potassium
Cannon
Carbine
Case shot; canister
Casemate
(37 mm A/T Cannon, Fixed Defense)
Box; case; magazine
Cere
War
Time and percussion fuze, pattern 28 for use with high velocity gun (TM 9-1985-3, p 603)
Box
Folding safety device (Fuze equipped with delay action and folding safety device) (TM 9-1985-3, p 580)
Marking on a HE cylindrical bomb of three piece construction (TM 9-1985-2, p 8)
240 mm Gun with range up to 30 km
280 mm Gun with range up to 50 km
211 mm Gun with range up to 120 km
105 mm and 150 mm Guns, pattern 1918
105 mm Gun pattern 1918/1940
small
Coast artillery
Caliber
Carbine pattern 1898, short (length of barrel 600 mm)
Case shot; canister shot
Cartouche; container of propellant charge not used in fixed ammunition
Propellant bag
Cover for Kartusche (q v)
Ba, container of propelling charge placed in Kartuschenhülse (q v)
Cartridge case for Kartuschen
Ammunition using Kartuschen (Compare with Patronenmunition)
Muzzle-flash reducing wad
Cold adhesive putty used for attaching demolition charges

Platform mounted cannon
Chemical cylindrical, thin-walled bomb; gas bomb
Chemical cylindrical incendiary bomb (TM 9-1985-2, pp 32-3)
Association for welfare of workers (lit strength through joy).It financed the construction of Volkswagen and some ships

| | | |
|---|---|---|
| K(L) | Kanone (Eisenbahn) | Railroad gun |
| Kfw; Kpfw | Kampfwagen | Tank; armored vehicle |
| Kfz | Kraftfahrzeug | Motor vehicle |
| KG | Kavalleriegeschütz | Cavalry gun |
| KG | Abbreviation for some manufacturing company | |
| Kg; kg | Kilogramm | Kilogram |
| kg | Kugel | Ball; sphere; bullet |
| kg mB | Kilogramm mit Beutel | Kilogram including weight of bag |
| KGr | Kanonengranate | Cannon shell |
| XGr(BoPr) | Kanonengranate (Bohrgeschoss, Pressstahlform) | Shell prepared by drilling pressed steel block |
| KGrPatrPz | Kanonengranate PatronenPanzer | AP shell, fixed round |
| XGr:RotAl | Kanonengranate, rote Sprengwolke, Aluminium | HE shell containing aluminum and giving on bursting a cloud of red smoke |
| KH | Kanonenhaubitze | Gun-howitzer |
| Kh; KH | Kammerhülse | Central burster tube in projectile |
| KhLdg | Kammerhülseladung | Central burster tube charge |
| KiHL | Kanone in Haubitzenlafette | Gun on howitzer carriage |
| K;MrsL | Kanone in Mörserlafette | Gun in mortar mount |
| KiRL | Kanone in Radlafette | Cannon on wheeled mount |
| KiZ | Kippzünder | Tilt-type igniter |
| K-K | Kaiserlich-Königlich | Imperial-Royal (Austrian Empire) |
| KK | Kanone-Kasemate | Casemate gun |
| kl | klein | small |
| klK; KK | Kleinkaliber | Small caliber |
| K L/ | Kanone, Lauflänge | Cannon of so many calibers long |
| (K L/50) | (Kanone, Lauflänge 50) | Cannon 50 calibers long |
| Kl | Klemm | Designation of airplanes built by Klemm Co |
| klAZ | kleiner Aufschlagzünder | Percussion fuze to fit a shell with small opening |
| klLdg | kleine Ladung | Small charge; reduced propelling charge |
| klV; Kv | kleine Verzögerung | Small delay |
| klZdlg (such as klZdlg 34Np) | kleine Zündladung 34 | Small booster; any intermediate charge with detonator between fuze and HE filling |
| Kn | Knaulkörper | Firecracker (simulated fire) |
| KN (Pulver) | Krumbach Nitrat (Pulver) | DEGDN-NC propellant containing small amount of K nitrate (CIOS 31-62, p5) |
| KnZ | Knickzünder | Snap-type igniter |
| KnZdSchn | See KZS | |
| KOD (Pulver) | Krumbach(Pulver)ohne Nitrate aber mit Dinitrotoluol | Same as KN(Pulver) except that K nitrate was replaced by DNT (CIOS 31-62, p5) |
| kon | konisch | conical |
| KP; KfPist | Kanospistole | Rifled Véry pistol |
| Kp | Kappe | Cap of projectile or fuze |
| Kp; Kr | See under Warplants, etc in descriptive part | |
| Kpf | Kampf | Combat; battle |
| Kpf | Kopf | Head; nose (of a bomb); point (of a shell) |
| Kpfw; Kfw; Kw | Kampfwagen | Tank (lit Battle car) |
| KpfwAbw; KwAbw; XfwAbw | Kampfwagenabwehr | Antitank defense |
| KpfwAbwGesch; KwAbwG; KfwAbwG | Kampfwagenabwehrgeschütz | Antitank gun |
| KpfwF; KwF; KfwF | Kampfwagenfalle | Tank trap |
| KpfwK-Stand; KwK-Stand; KfwK-Stand | Kampfwagenkanone-Stand | Fixed emplacement made of tank gun turret |
| KpfZ | See Kz; KZ; KpfZ; Kzdr | |
| KpfZ Zerl | See KzZerl; KpfZ Zerl | |
| KPS (white or red stem-cilling above rotating band) | Kupfer Pressstahlführungsring | Rotating band of the bimetallic type |
| Kr | See Krw | |
| Kr | Kreuz | Cross; crosspiece (of a universal joint) |
| Kr; KrP | Kreuzpulver | Tubular propellant with a crosspiece inside of tube |
| Krabus | Kraftomnibus | Motor bus |
| Krad | Kraftrad | Motor cycle |
| Krad mB | Kraftrad mit Beiwagen | Motorcycle with side car |
| KrG | See KrwGesch | |
| Kripo | Kriminalpolizei | Criminal investigation police |

| | | |
|--|--|---|
| KrR | Kreuz Rohr | Central tube made of colloided propellant; it served to retain propellant charge in base of cartridge case (lit Cross tube) |
| Krw; Kr; Kw | Kraftwagen | Motor car |
| KrwAnh; KwAnh | Kraftwagenanhänger | Trailer truck |
| KrwFlak | Kraftwagen-Flugzeugabwehrkanone | Motorized AA gun |
| KrwG; KrGesch | Kraftwagenschütz | Tractor drawn gun or gun mounted on a truck |
| KrzFlak | See KzFlak | |
| Ks; KS | Kaskade | Cascade (cartridge similar to canister) |
| Kst; Küst | Küste | Coast; shore |
| KstA | Küstenartillerie | Coast defense artillery |
| KstBtrr | Küstenbatterie | Coastal battery |
| KstG | Küstengeschütz | Coast defense gun |
| KstH | Küstenhaubitze | Coast defense howitzer (such as 280 mm) |
| KstK | Küstenkanone | Coast defense cannon |
| KstL | Küstenlafette | Coast defense mounting |
| KstMi | Küstenmine | Coastal mine |
| KstMrs | Küstenmörser | Coast defense mortar |
| Kt; KT KtPatr | Kartätsche; Kartätschenpatrone | Case shot; canister ammunition |
| Kt | Kanone-Turm | Turret gun |
| KTM (in fuze designation | | Captured Russian projectile |
| KTM:.) | | used by the Germans in 76.2 mm |
| KTrMi 41 | Kugeltreibmine 41 | Spherical Drifting Mine, Type GL |
| KuTK | Kasemate- und Turmkanone | Casemate and turret gun |
| KV | See kIV | |
| KVK | Kriegsverdienstkreuz | War service cross (decoration) |
| KVP | Kasernierte Volkspolizei | Garrisoned People's Police (Armed Forces of East Germany) |
| kW | Kilowatt | kilowatt |
| Kw | See Kpf; Kw; Kfw | |
| Kw | See Krw; Kr | |
| KWI | Kaiser Wilhelm Institut (Göttingen) | Emperor William Institute (Educational and research establishment) |
| KwF | See KpFwF | |
| KwK | See KpFwK | |
| KZ | Kanonenzünder | Gun percussion fuze; cannon shell fuze |
| Kz; KZ; KpZ; Kzdr (in designation of ammo, such as 8.8 cm SprGr L/4.5 (Kz) | Kopfzünder (8.8 cm Sprenggranate Länge 4.5, Kopfzünder) which means 88 mm HE shell, 4.5 calibers long with PDFz kurz | Point detonating fuze (PDFz) under a ballistic cap, except in the case of the KZ-38, an ordinary PDFz (TM 9-1985-3, p 545) |
| kz; Kz | kurzer Aufschlagzünder | short |
| kzAzl | kurzer Bodenzünder | Short percussion (impact) fuze |
| kzBd | kurze 28 cm Bruno Kanone (Eisenbahn) | Short base detonating fuze |
| kz 28 cm Brk(E) | | Short 280 mm Bruno Railroad Gun |
| KZ Boden (such as in AB 250 KZ Boden) | | Markings on a container with 19 parachutes and three SD2 bombs (TM 9-1985-2, p 108) |
| KzFlak | Kraftzug-Flugzeugabwehrkanone | Motorized AA gun |
| Kzg (such as in sPzB 41(Kzg)) | Kraftz. [schwere Panzerbüchse 41(Kraftzug)] | Power-driven (Heavy A/T power-driven rifle) |
| KZGrGeb | Kanonenzünder Granate für Gebirgskanone | Gun percussion fuze for mountain gun |
| kzGrW | kurzer Granatenwerfer | Short barreled mortar |
| kzL | kurze Länge | Short length |
| KzL | kurze Lafette | Short gun carriage |
| KzLaf | Kreuzlafette | Outrigger-gun platform for AA gun (lit Cross gun mounting) |
| kzLK | kurze Länge-Kanone | Short-barreled gun |
| kzMk | kurze Marinekanone | Short Naval gun |
| KZS; KzZdSchn | Knallzündschaur | Detonating cord; primacord |
| KzZerl; | Kopfzünder mit Zerleger | Self-destroying nose fuze |
| Kz 2Zerl P | Kopfzünder mit 2 Zerleger Pulver | Nose fuze with 2 self-destroying black powder units |
| KZ Zl Pv vf | Kopfzünder, Zerleger, Pulversatz, vereinfacht | Simplified self-destroying PD fuze with powder train |
| L | Ladestreifen | Ammunition clip; cartridge charge (SA) |
| L; Ld; Ldg | Ladung | Charge; load; propelling charge |

L

| | | |
|--|--|---|
| L; Laf; Lf (such as MG 1. 08/15) | Lafette (Maschinengewehr Lafette 08/15) | Gun mount; gun carriage (Machine gun mount, pattern 1908/15) |
| L (such as in 17 cm Mörsl.) | Lafette (17 cm Mörser Lafette) | Markings on a 170 mm mortar |
| L (such as in PzWfMi 1 (i.)) | Luftwaffe [Panzerwurfmine I (Luftwaffe)] | Air Force (A/T hand grenade 1, introduced by Air Force) |
| L/ (in designation of gun 8.8 cm StuK 43 L/71) | Lauf (Kaliberlänge) (8.8 cm Sturmkanone 43, Lauf 71) | Length of a gun barrel in calibers (80 mm Ansult Gun pattern 43, barrel 71 calibers long) |
| L/ (in designation of shell 10.5 cm Sprgr L/4.4) | Kaliberlänge (Granate) (10.5 cm Sprenggranate, Länge 4.4) | Length of a shell in calibers (105 mm HE Shell, 4.4 calibers long (TM 9-1985-3, p 468) |
| L | See Leuchtg and Lg | Delivery, lot; shipment |
| L; Lfg | Lieferung | Marking on the 250 kg Cylindrical HE Bomb of two-piece construction; nose forged steel, body tube steel (TM 9-1985-2, pp 8-9) |
| L | See le; l; L | Camp; dump; denot Designations for hydrazine hydrate |
| L2 (in bomb designation SC 250-L2, "Hermann") | (Sprengcylindrische 250-L2, "Hermann") | Cylindrical flare; candle flare Single candle parachute flare (TM 9-1985-2, p 65) Four candle parachute flare design C (TM 9-1985-2 p 67) Flare bomb airtight |
| Laf | See L; Laf; Lf | |
| Lag | Lager | |
| LB-St | | |
| LC | Lichtcylindrisch; Leuchtzylindrisch | |
| LC-10 | Lichtcylindrisch 10 | |
| LC-50 F AusfC | Lichtcylindrisch 50 F Ausführung C | |
| LC Bombe | lichtcylindrische Bombe | |
| ld | luftdicht | |
| Ld; Ldg | See L; Ld Ldg | |
| LdgW | See LWrf | |
| LdKpf | Ladekopf | Charging head; a device for charging some electric bomb fuzes (TM 9-1985-2, p 132) |
| LdW | See LWrf; LdgW | |
| le; l; L | leicht | light |
| leFH; IFH | leichte Feldhaubitze | Light field howitzer |
| leG; IG; LGS | Leichtesgeschütz | Gun for airborne operations; recoilless gun |
| leGebIG; lGebIG | leichtes Gebirgsinfanteriegeschütz | Light gun for mountain infantry |
| leGeb Jg; lGebJG | leichtes Gebirgsjägersgeschütz | Light gun for mountain rangers |
| leGrW; lGrW | leichter Granatwerfer | Light mortar |
| leHT; lHT | leichte Haubitze-in-Turm | Light turret howitzer |
| (10 cm leHT) | (10 cm leichte Haubitze-in-Turm) | 100 mm Fixed Mortar (breech loading) |
| leIG; lIGs; leJG; lJGs | leichtes Infanterie Geschütz | Light, very low velocity gun for use by infantry |
| leJgrZ | leichter Infanteriegranatzünder | Light infantry shell fuze |
| leLdgW; lLdgW | leichter Ladungswerfer | Light spigot mortar |
| leMiW; lMW | leichter Minenwerfer | Light mortar |
| LE-Mun | Lichteinschiess Munition | Tracer ammunition used in range adjustment fire |
| lePzMi; lPzMi; LPZMi | leichte Panzermine | Light AP mine; A/T mine (TM 9-1985-2, p274) |
| leS; lS | leichtes Spitzgeschoss | Pointed, light weight bullet |
| leSPur; lSLS | leichtes Spitzgeschoss mit Leuchtspur | Pointed light weight bullet with tracer |
| Leuchtg (black stenciling); L; Lg | Leuchtgeschoss | Star shell; flare shell |
| LeuchtgZ; LgZdr | Leuchtgeschosszünder | Time fuze for use with star shell |
| Leut; Lt | Leutnant | Second lieutenant (See also ObLeut) |
| leWM; lWMi; LWM | leichte Wurfmine | Light mortar shell |
| leWMZ | leichter Wurfminenzünder | Fuze for light mortar shell |
| lExM | leichte Exerziermine | Light training mine |
| lExMmR | leichte Exerziermine mit Rauchladung | Light training mine with smoke element |
| LF | Lafettenfahrzeug | Gun carriage |
| LFA | See under Warplants, etc in descriptive part | |
| ld | luftdicht | airtight |
| Lfg | See L; Lfg | |
| IFH | See leFH | |
| IFK | See leFK | |
| LFM | See under Warplants (descriptive part) | |
| Lfw; Lw | Luftwaffe | Air force Aeronautics; aviation |
| Lfw | Luftfahrzeug | long |
| lg | lang | |
| IG | See leG | |
| LG (such as 7.5 cm LG 40) | leichtgeschütz (7.5 cm Leichtgeschütz 40) | Recoilless gun (lit Light gun) (75 mm Recoilless gun, pattern 40) |
| Lg; Leuchtg; L | Leuchtgeschoss | Flare shell; star shell |

| | | |
|---|--|---|
| IgBdZ | langer Bodenzünder | Long base percussion fuze |
| IgBrIG; IB | lange Brennlänge | Long burning length (fuze) |
| IGebIG | See IGebIG | |
| IGebJG | See IGebJG | |
| IgFHGr(Nb) | lange Feldhaubitzzgranate (Nebel) | Long field howitzer shell (smoke) |
| Lgg; IgGr | Lunggranate | Long shell |
| IgKZ | langer Kanonenzünder | Long gun fuze |
| Igl | lange Lafette | Long gun carriage |
| IgM (black stencilling) | lange Mundlochbüchse | Shell with lengthened gaine-type booster |
| IgMB | lange Mundlochbüchse | Long gaine-type booster |
| LgP 40 | Leuchtgeschosspulver 40 | TEGDN propellant of calorific value 650 kcal/kg used with Naval starshell charges |
| LgP 40N | Leuchtgeschosspulver 40 (Nitronaphthalin) | TEGDN propellant of calorific value 670 kcal/kg and contg α -nitronaphthalene used with Naval starshell charges |
| IGrW | See IGGrW | |
| IGs | See IGs | |
| Ig sFH | lange, schwere Feldhaubitze | Long and heavy field howitzer |
| LGZ | See under Warplants (descriptive section) | |
| LkZ; LgZdr; I.cuchgZ (such as LgZ S/33) | Leuchtgeschosszünder | Fuze for star shell |
| Lh (such as 4 cm SprgrPatr Lh 28) | Leuchtpurhülse (4 cm Sprenggranate Patrone Leuchtpurhülse 28) | Tracer container (cartridge) (40 mm HE Fixed Round with tracer cartridge type 28) |
| IHT | See IeHT | |
| IjgrZ 23 | Leichter Infanteriegranatzünder 23 | Fuze for light infantry shell pattern 23 |
| IIGs | See IeIGs | |
| IjGs | See IeJGs | |
| LK (such as Mk 250 LK) | | Marking on a container with 41 single candle parachute flares (TM 9-1985-2, p 108) |
| LKZ | See IgKZ | |
| ILdgW | See IeIdgW | |
| Lm; LM | Leichtmetall | Light metal (Aluminum) |
| Lm; LM [black stencilling such as in KZ C/27 (LM)] | Leichtmetall [Kopfzünder, Konstruktion 27 (Leichtmetall)] | Marking on a shell fuze with combined cap and gaine in aluminum [Aluminum body PD fuze, Naval, pattern 1927 (TM 9-1985-3, p 565)] |
| LM | Luftmine | Aerial Mine |
| LMssg | Lichtmessing | Flash ranging |
| LMsSt | Lichtmess-Stelle | Flash ranging station |
| IMW | See IeMiW | |
| Lo (black stencilling) | losen Sprengstoffkörpern | HE filling consisting of separate explosive bodies, carton-loaded but not cemented |
| LP; LtPist | Leuchtpistole | Smooth bore pyrotechnic pistol such as Véry pistol; flare pistol; signal pistol |
| LPatr | Leuchtpatrone | Illuminating cartridge |
| LPist | See LP | |
| LPzMi; LPZMi | See IePzMi | |
| LrS [such as in 7.5 cm Pak 40/1 (Sf LrS) (f)] | Lorraine Schlepper [7.5 cm Pak 40/1, Selbstfahrlaette, Lorraine Schlepper (französisch)] | Lorraine tank chassis [75 mm A/T Self-Propelled Gun on Lorraine Tank Chassis (French)] |
| Ls (white stencilling) | Leuchtsatzsprengladung | Illuminating filler (in a shell) |
| Ls | Luftschutz | Air raid defense |
| LS | See L'spur | |
| LS | See IeS | |
| Lsg | Losungswort | Password |
| LSGesch | See L'spurGesch | |
| ISLS | See IeSL'spur | |
| LS Mun | See L'spur Mun | |
| LSpH | Leuchtpurhülse | Tracer element container |
| L'spur; L'Spur; LS; LSp | Leuchtspur; Lichtspur | Tracer projectile trajectory; trace |
| L'spurGesch; LSGesch | Leuchtspurgeschoss; Lichtspurgeschoss | Projectile with tracer |
| L'spurMun; LSMun | Leuchtspurmunition; Lichtspurmuniton | Tracer ammunition |
| LSR | Luftschutzraum | Air raid shelter |
| LT | Leuchtturm | Lighthouse |
| LT | Lufttorpedo | Aerial torpedo (bomb) |
| LuS Mun | Leucht- und Signalmunition | Flare pistol ammunition |
| Lux EZ 50 SC | | Designation of a sea marker (TM 9-2985-2, p 86) |

LUX N and LUXS

L.v
L.w
L.wg
LwMi
LwMiZ
L.Wrf; L.dgW; L.dw
L.7e7.

Ladungsverhältnis
See Lftw
Lastwagen
See leWM
See leWMZ
Ladungswerfer
Langzeitzunder

Designations of flame floats (TM 9-1985-2, p 92),
Ratio of charge to weight of projectile

Truck

Spigot mortar
Long time delay fuze

M

M
M; Man
M
M; Mk; MK
M
M; m
M; Mi
M
in
M; Md; MB (such as in
8.1 cm GrWM 35 (n))

(1e FH18M; 1FH18mM)

Main
See Man; Manöv
Marine
Marke (Kennzeichen)
Maske
Meter
Mine
Minengeschoss
mit
Mündungsbremse
[8.1 cm Granatwerfer mit Mündungs-
bremse type 35 (Norwegian)]
(leichte Feldhaubitze mit Mündungs-
bremse)
Muster

River Main

Navy Naval
Mark (identification)
Gas mask
Metre (m)
Mine
Mortar shell; high capacity, HE missile
with
Muzzle brake of the Norwegian Launcher 35

M
M-1 (Kanone)
MA; Ma

Munitionsanstalt

Light field howitzer, pattern 18 provided with muzzle brake

Pattern; model; sample
Designation of a gun, cal 305 mm
Ammunition depot; ammunition loading factory (such as at
Cassel, Hannover, Ingolstadt, Jüterbog, Königsberg,
Stettin and Zeithain)

MAA
Mag Gew
Man; Manöv;
MAN
Man Kart; MKart
Marlag
MB; M; Md
MB; MB
M-Boot
M-Boot
Mdg
Mdlch
Mdlchb; MB; Mb
Mdlchf
Mdlchsch
Me
mE
ME
Mebu

Marineartillerieabteilung
Magazingewehr
Manöver
See under Warplants (descriptive section)
Manöverkartusche
Marinelager
Mündungsbremse
See Mdlchb
Minensucherboot
Motor boat
Mündung
Mundloch
Mundlochbüchse
Mundlochfutter
Mundlochschaube
Messerschmid:
mit Eisenkern
mit Entkupferungsband
Maschinengewehr-Eisenbeton Unter-
stand

Naval coast artillery battalion
Magazine rifle
Maneuver

Blank cartridge
Prisoner-of-war camp for sailors
Muzzle brake

Mine sweeper
Motorboat
Muzzle
Fuze hole; adapter opening
Gaine type, fuze booster container
Gaine (lit Fuze hole casing)
Adapter plug (Ammo)
Designation of airplanes built by Messerschmidt Co
With iron core (bullet)
With a decoppering strip
Machine gun in reinforced concrete pillbox

MEB (in rocket designation,
such as 30 cm Wfk 42 Spr
MEB)

mit eingebauten Brennzünder
(30 cm Wurfkörper 42 Spr MEB)

Markings on a 300 mm HE rocket, spin stabilized
and provided with a time fuze (TM 9-1985-2, p 251)

MF
Mf
M-Flak
mFmV
MFS
MG; MGew
mg
MG08

Marineform
Motorfahrzeug
Flugzeugabwehrmaschinenkanone
mittlerer Flammenwerfer
Marinefunkstelle
Maschinengewehr
Milligramm
(schweres) Maschinengewehr
Konstruktion von 1908 (Maxim)
(leichtes) Maschinengewehr, Kon-
struktion von 1908 mit Änderungen
von 1915

Naval design
Motor vehicle
Automatic AA gun, such as 3.7 cm M-Flak
Medium-weight flame thrower
Naval radio station
Machine gun
Milligram
(Heavy) machine gun (Maxim) 1908 construction

MG08/15

(Light) machine gun, 1908 construction with changes of
1915

| | | |
|---|---|---|
| MGBA | See under Warplants (descriptive section) | |
| M-Gerät | Mörser (auf Kraftzug) | Mortar (on motor tractor) |
| mit geringer Spreldg | mit geringerer Sprengladung | With reduced bursting charge |
| MGeach (auch als MGeach Patr oZerl) | Minengeschoß (Minengeschoß Patrone ohne Zerlegen) | HE, high capacity projectile (HEHC fixed round without self-destruction) |
| MGFF (2 cm) | 2 cm Maschinengewehr in den Flügeln eines Flugzeug | 20 mm Machine gun in the wings of an airplane |
| MG FFM (2 cm) | 2 cm Maschinengewehr FFM | 20 mm Machine gun FFM |
| MGr; Mgr (such as 3.7 cm Mgr Patr 18) | Minengranate (3.7 cm Minengranatepatrone 18) | High capacity HE shell; mine shell (3.7 mm HEHC fixed round pattern 18) |
| MGrW | Minengranatwerfer | Trench mortar |
| MGrW; mGrW | Mittlerer Granatwerfer | Medium mortar (81 mm) |
| mgV | mit grün Vorsignal | With green signal |
| mHb; mHbe | mit Haube | With ballistic cap; with windshield |
| MHbr | Mörserlaubengranate | HE heavy howitzer shell with ballistic cap (windshield) |
| Mi; Min | Mine | Mine |
| Mi A200 | Mine A200 | A/P land mine filled with 13 oz picric acid |
| MiAG | See under Warplants (descriptive section) | |
| Milag | Militärlager | Army camp |
| Min-Su | Minensucher | Minesweeper |
| MinWf; MiW | Minenwerfer | Trench mortar |
| Mipo | See MP; Mipo | |
| Mi S 150 | Mine S 150 | A/P land mine containing 5½ oz picric acid |
| mit Ldg; mitrl.dg | mittlere Ladung | Medium size charge |
| MiW | See MinWf | |
| MiWPr | See MWPr | |
| MiZ | Minenzünder | Mine igniter |
| MiZ 530(e), Mk 3 | Minenzünder 530 (englisch), Mk3 | Pressure type igniter for use in captured British A/T mines Mark 3 (TM 9-1985-2, p 305) |
| Mk | Mark | Mark; pattern |
| Mk | Maschinenkanone | Automatic cannon |
| Mk; MKb | Maschinenkarabiner | Machine carbine; submachine gun |
| mK | mit Kappe | With cap; capped |
| mK | mit Kern | With core |
| mK; MK (in fuze designation such as AZ 5075 MK) | mit Klappensicherung (Aufschlagzünder 5075 mit Klappensicherung | With a shutter safety device (Percussion fuze 5075 with a shutter safety device) |
| Mk 50 Kask | Mark 50 Kaskade | Designation of a cascade target indicating flare (TM 9-1985-2, pp 71-3) |
| MKA | Marine-Küstenartillerie | Naval coast artillery |
| MKb | See MK; MKb | |
| MkS | | Designation of a two-candle sea flare (TM 9-1985-2, p 77) |
| Mkw | Munitionskraftwagen | Ammunition truck |
| mL | mit Luftvorholer | with pneumatic recuperator |
| MLB; Mlb; M | Mundlochblüchse | Gaine-type fuze-booster container |
| mM; mMb | mit Mündungsbremse | With muzzle brake |
| MNH | See under Warplants (descriptive section) | |
| mO | mit Oberzündung | With overhead ignition |
| Mod | Modell | Model; pattern |
| Mörs; Mrs | Mörser | Large caliber, short barrel howitzer; mortar |
| mot | motorisiert | motorized |
| MOTO | Monat-Tonne | Metric tons per month |
| MP-44 | Maschinenpistole-44 | Machine pistol; automatic pistol (Called later StuG-44) |
| mP | mit Panzerkopf | With armor-piercing cap |
| MP; Mipo | Militärpolizei | Military police |
| mPak | mittlere Panzerabwehrkanone | Medium A/T gun |
| MPatr | Meldepatrone | Ground illuminating, single star, signal cartridge (long range) |
| mPz; mP | mit Panzerkopf | With AP head |
| mR (black stencil) | mit Rauchentwickler | With smoke generator |
| mR8 | mit Rauchentwickler Nr 8 | With smoke generator, type 8 |
| mRr | mit Rohrrücklauf | With recoil |
| Mrs | See Mörs | |
| MrsL (such as in 17 cm MrsL) | Mörser L (17 cm Mörser L) | Markings on a 170 mm howitzer |
| MS | Mannschaftsäbel | Enlisted personnel's sword |
| Ms | Messing | Brass |
| MSGer | Minensuchgerät | Mine detector |

| | | |
|--------------|--|---|
| Mstb | Muss-stab | Scale; standard; rule |
| Mstr | Muster | Pattern; model |
| MtK | Mantelkanone | Jacketed gun |
| Mun | Munition | Ammunition |
| Mun; Muntrug | Munitionsträger | Ammunition carrier |
| MunF | Munitionsfabrik | Ammunition factory |
| MunWg | Munitionswagen | Ammunition wagon; caisson |
| M-u R-Patr | Niede- und Rauchpatronen | Ground signal and smoke cartridges |
| mV; MV | mit Verzögerung | With delay action (Fz) |
| m verst F | mit verstärkt Flichbolzen | With reinforced centrifugal safety bolt |
| mv F | mit vorderem Führungsring | With forward rotating band |
| mVorl | mit Vorlage | With flash reducer |
| MvU (21 cm) | 21 cm Mörser vereinfachte Unterlafette | Simplified lower carriage for 210 mm howitzer |
| mVuk | mit Verzögerung und Klappensicherung | Fuze equipped with delayed action and folding safety device |
| MW | Minenwerfer | Trench mortar |
| MWA | See Marine Waffenanstalt in the vocabulary | |
| MWMZ; mWMZ | Mittlerer Wurfminen Zünder | Fuze for medium size mortar, such as 80 mm |
| MWP; MiWPr | Minenwerfer-Protze | Mortar ammunition wagon; limber; caisson |
| mwV | mit weissem Vorsignal | With white signal |

N

| | | |
|--------------------------|--------------------------------------|--|
| N | See Nb | |
| (a) | See (h) | |
| (n) | norwegisch | Norwegian (mark on equipment) |
| N; NJa | Norden | North |
| nA; NA | neuer Art | Of new type or pattern (See also aA and nF) |
| Nachf | Nachfolger | Successor |
| Nachf | Nachforschung | Investigation; search |
| NAG | Nationale Automobil Gesellschaft | National Automobile Corporation |
| Nb; N; NeL | Nebel | Smoke; fog; gas |
| Nb; N(white stencilling) | Nebelgeschoss | Smoke shell |
| NbB Z-38 | Nebelbrennzünder 38 | Friction igniter, pull type, type 38, used in smoke grenade (TM 9-1985-2, p 233) |
| NbC | See NC | |
| NbGr; NbGr | Nebelgranate | Smoke shell |
| NbGr(Pe) | Nebelgranate (Press-stoff) | Smoke shell with plastic fuze body (TM 9-1985-3, p 607) |
| NbHgr | Nebelhandgranate | Smoke hand grenade |
| NbK; NbKz | Nebelkerze | Smoke candle; thermal smoke generator |
| NbKz L42 | Nebelkerze, lang 42 | Long thermal smoke generator 42 |
| NbKzS | Schnellnebelkerze | Rapid thermal smoke generator |
| NbKzWfldg | Nebelkerzen Wurfladung | Propelling charge for thermal smoke generator |
| NbMun | Nebelmunition | Smoke ammunition |
| NbS; NS | Nebelsignal | Smoke signal |
| NbSt | Nebelstoff | Smoke producing material |
| NbSt | Nebelwurfgranate aus Stahl | Steel mortar shell |
| NbW | Nebelwerfer | Rocket launcher (lit Chemical smoke projector) |
| (15 cm NbW41) | (15 cm Nebelwerfer 41) | (150 mm Rocket launcher 41) (Six tubes) |
| (28/32 cm NbW41) | (28/32 cm Nebelwerfer 41) | (280/320 mm Rocket launcher 41) |
| (21 cm NbW 42) | (21 cm Nebelwerfer 42) | (210 mm Rocket launcher 42) |
| (30 cm NbW 42) | (21 cm Nebelwerfer 42) | (210 mm Rocket launcher 42) |
| (15 cm NbW 10 ling 42) | (15 cm Nebelwerfer-Zeholing 42) | (150 mm Ten tube rocket launcher) |
| (15 cm NbW 30 ling 43) | (15 cm Nebelwerfer Dreissig ling 43) | (150 mm Thirty tube rocket launcher 43) |
| NbZst | Nebelzerstäuber | Smoke disperser |
| NC; NbC(Bombe) | Nebelcylindrische (Bombe) | Smoke cylindrical (bomb) |
| nC | neuere Konstruktion | Of new type construction (See nK) |
| NC 250s | Nebelcylindrische 250s | Cylindrical smoke bomb filled with mixture of sulfur trioxide 60 and chlorosulfonic acid 40% (TM 9-1985-2, p 59) |
| NC 50 WC | Nebelcylindrische 50 WC | Floating cylindrical smoke marker bomb (TM 9-1985-2, p 59) |
| NC D/SEE | Nebelcylindrische D/SEE | Floating cylindrical smoke marker (TM 9-1985-2m p 59) |
| NdP; NP | Nudelpulver | Chopped cord propellant; nodular propellant |
| Neb | See Nb; N | |
| neb | neben | besides; next to |
| Neb-Ma | Nebenmunitionsanstalt | Branch ammunition depot |
| nF | neue Fertigung | New model |
| nF; NF | neuer Form | of new shape |
| Ng; Ngl | Nitroglycerin | Nitroglycerin |

| | | |
|---|---|---|
| NGewP 71 Ngl; NgHP | neues Gewehrpulver 71 Nitroglycerinpulver | New rifle powder 71 (used now only in igniters) Double-base NG-NC propellant stabilized with centralite, acardite or diphenylamine NG-NC flake propellant |
| NgBlP NgHP NgHP NGRP Niga Nitroz nK (formerly nC) | Nitroglycerin-Blättchenpulver See Ngl Nitroglycerin-Flattenpulver Nitroglycerin-Röhrenpulver Nitroguanidin See Nz neuere Konstruktion (neuere Konstruktion) | NG-NC propellant in the form of flat discs NG-NC tubular propellant Nitroguanidine (NGu) of new-type construction |
| NK [in designation Bruno NK (E)] Nkz NMun Np NP NP Np5, Np 10, etc NPatr NpGewP | [Bruno N Kanone (Eisenbahn)] See Nbk See Nbmun Nitropenta See NdP Nullpunkt Nitropenta 5; Nitropenta 10, etc Nahpatrone Nitropentagewehrpulver | Markings on a 280 mm Bruno railroad gun (TM 9-1985-3, p 529) PETN (pentaerythritol tetranitrate) Zero point; zero PETN + 5, PETN + 10, etc percent wax Low velocity ball round for close range Small arms double base propellant of PETN and NC stabilized with diphenylamine and including ethyl centralite and K sulfate Propellant containing PETN Number |
| NpP Nr NS NSP; NzSP | Nitropentapulver Nummer See Nbs Nitrozellulose-Schwarzpulver | Igniter powder consisting of black powder bound by colloided NC (See also under Ignition in descriptive part) Useful load; pay load |
| Ntzl NVA Nz; Nitroz NZ Nz; NzP | Nutzlast See under Warplaus, etc in descriptive part Nitrozellulose Normalzeit Nitrozellulosepulver | Nitrocellulose (NC) Standard time Single base NC propellant stabilized with diphenylamine and with Na oxalate and K sulfate added to reduce flash NC flake propellant for rifle ammunition Small arms NC propellant stabilized with diphenylamine and including ethyl centralite and K sulfate Porous quick burning NC, chopped cord propellant used in drill ammunition and in igniters (See also under Ignition in descriptive part) NC chopped cord propellant |
| NzGewBlP NzGewP | Nitrozellulose Gewehblättchenpulver Nitrozellulose Gewehrpulver | |
| NzManMP | Nitrozellulose Manöver Nudelpulver | |
| NzNP NzP NzRP NzStbP NzStF | Nitrozellulose Nudelpulver See Nz; NzP Nitrozellulose Röhrenpulver Nitrozellulose Stäbchenpulver Nitrozellulose Staubpulver | NC tubular propellant NC strip propellant (for pistols) NC propellant, finely granulated |
| 0 | | |
| O; Ob; Obst o o; O O (ö) O (black stencilling) oAl (white stencilling) oAz Ob OB Obbfb oBD Oberlt; ObLt Oberwld Oberstlt Obfdw Obfw ObKerGer | Oberat ohne ortfest Osten österreichisch ohne Füllung ohne Aluminium ohne Aufschlagzündung See O; Ob Ortbatterie Oberbefehlshaber ohne Bleidraht Oberleutnant Oberachlesien Oberstleutnant Oberfeldwebel Oberfeuerwerker Oberkriegsgericht | Colonel without fixed; permanent; static Eaat Austrian (marking on equipment) Without filling (marking on some inert shells) Without aluminium (in HE shell filling) Fuze without percussion element Local battery Commander in chief Without lead wire serving as decoupling agent First lieutenant Upper Silesia Lieutenant colonel Master sergeant (except Army) Ordnance sergeant; artificer General Court-martial |

Oblt
ObQu; ObQuMstr
Obst
Obus; Omn
Obw
ObZm
oB
Oerl

Oerl Flak
Off; Offz
Offz (W)

OFK
oFlak; O-Flak
oH
OKH
OKL
OKM
OKW
oL
oM (black stencilling)
oM
oR
oR (black stencilling)
OS
oV
Oz

See Oberst
Oberquartiermeister
See O; Obst
Omnibus
Oberwachtmeister
Oberzahlmeister
ohne Datum
Oerlikon

Oerlikon Flugzeugabwehrkanone
Offizier
Offizier des Waffenwesens (Waffen-
offizier)
Oberfeldkommandatur
Oberst Flugabwehrkanone
ohne Hülse
Oberkommando des Heeres
Oberkommando der Luftwaffe
Oberkommando der Kriegsmarine
Oberkommando der Wehrmacht
ohne Ladestreifen
ohne Mündlochbüchse
ohne Mündungsbremse
ohne Rauch
ohne Rauchenwickler
Offiziersäbel
ohne Verzögerung
Ozean

Army quartermaster

Motor bus
Master sergeant (Army)
Chief paymaster
undated
Designation of ammunition or weapons manufd by the
Oerlikon Co.
Oerlikon AA gun
Officer
Ordnance officer

High Field Command
Stationary or fixed AA gun
Without a cartridge case
High Command of the Army
High Command of the Air Forces
High Command of the Navy
High Command of the Armed Forces
Without cartridge clip
Shell without gaine container
Without muzzle brake
Smokeless
Shell without smoke generator
Officer's sword
Without delay (Fz)
Ocean

P

P; Patr

P; PG

P

(p)

P; Pol; Polte

P; Pv; Pulv

P

PA

Note: Superseded in compound words by PzJag (Panzerjäger), which means tank destroyer

PAe; PA

Pak; PAK

Note: Superseded in compound words by PzJagK (Panzerjägerkanone), which means tank destroyer gun

Pak-Flak

Patr; P

Note: When the word "Patr" is included in a designation, such as 7.5 cm SprgrPatr, it indicates a complete round of fixed ammunition (Compare with "Kart")

Patr 318

Patr B; Patr Br

PatrH

PatrKast

Patr leS; Patr IS

Patr leS L'apur; Patr IS-
L'apur

Patr Pmk

PatrS; PatrStr

PatrS*

Patr SmE

Patr SmFK

Patr SmE (lg)

See Patr; P

See PG; P

Phosphor

Pistole

polnisch

See under Warplants (descriptive section)

Pulver

Punkt

Panzerabwehr

Petroläther

Panzerabwehrkanone

Panzerabwehr- und Flugabwehrkanone

Patrone

Patrone 318

Patrone, Brand

Patronenhülse

Patronenkasten

Patronen leichtes Spitzgeschoss

Patronen leichtes Spitzgeschoss mit
Leuchtspur

Patronen, Phosphor, mit Stahlkern

Patronenstreifen

Patrone S*

Patronen Spitzgeschoss, mit Eisenkern

Patronen Spitzgeschoss mit Eisenkern
für Scharfschützengeneignet

Patronen Spitzgeschoss mit Eisenkern
(lang)

See Ph

See Pist

Polish (marking on equipment)

Powder; propellant

Point

Antitank defense

means tank destroyer

Petroleum ether

Antitank gun

Antitank-antiaircraft artillery

Cartridge; round of fixed ammunition

AP fixed round of ammo used in A/T rifle 39

HE-Inc round of fixed ammo

Cartridge case (of fixed ammo)

Cartridge box; ammunition container

Light, pointed ball ammunition (filled with aluminum)

used for practice

Light, pointed ball ammunition with tracer; used for
practice

Ball ammunition, Phosphorus, with steel core

Cartridge clip

Signified that cartridge was made of brass consisting of
Cu 72 and Zn 28%

Pointed ball ammunition with iron core. SAP bullet

Pointed ball ammunition (SAP) for 7.92 mm sniper's rifle

Long, pointed ball ammunition with iron core; SAP round

| | | |
|--|--|--|
| Patr SmK | Patronen Spitzgeschoss, mit Stahlkern | Pointed ball ammunition with steel core; AP shot |
| Patr SmK(H) | Patronen Spitzgeschoss mit Stahlkern (gehärtet) | Pointed ball ammunition with hardened steel core; AP shot |
| Patr SmK1'apur | Patronen Spitzgeschoss mit Stahlkern und Leuchtpapir | Pointed ball ammunition with steel core and tracer; AP-T round |
| Patr sS | Patronen schweres Spitzgeschoss | Heavy, pointed ball ammunition (streamlined) |
| Patr sS IL | Patronen, schweres Spitzgeschoss, in Ladestreifen | Heavy, pointed ball ammunition (hard lead core), in clip |
| Patr St | Patrone, Stahl | Steel cartridge case |
| Patr St | Patrone, Stahl | Steel cartridge case |
| Patr Tr | Patronentrommel | Cartridge drum |
| PC Bombe | Panzerdurchschlagzylindrische Bombe | Armor-piercing cylindrical bomb (Loading factor 15-20% HE) |
| [Examples: PC 1000 kg, known as "Esaü" and PC 1400 kg, known as "Fritz" (TM 9-1985-2, pp 24-25)] | | |
| PC-RS Bomben (such as 500 kg and 1000 kg) | Panzerdurchschlagzylindrischen Raketenstart Bomben | Rocket-assisted cylindrical armor-piercing bombs, 500 kg and 1000 kg (TM 9-1985-2, pp 26-28) |
| PD Bombe (PD 500 B) | Panzerdickenwand Bombe (Panzerdickenwand Bombe 500 kg) | Armor-piercing thick-walled bomb (Loading factor 10% HE) (500 kg AP thick-walled bomb) |
| Per-Stoff | Grünkresol | "Green cross" choking gas (CWS) |
| Pf | Pfund | Pound |
| Pfd Zg | (mit) Pferdzeug | Horse-drawn |
| Pfg; Pf | Pfennig | Pfennig (1/100 of mark) |
| PG (black steeling) | Perlitguß-stahl | Shell of cast steel in the pearlite condition |
| PGr | See Pzgr | |
| Pb (black steeling); P | Phosphor | Phosphorus incendiary filling |
| PH | Panzerhaubitze | Armored howitzer (self-propelled mount) |
| (IPH or lePH) | (leichte Panzerhaubitze) | (Light armored howitzer) |
| (sPH) | (schwere Panzerhaubitze) | (Medium heavy armored howitzer) |
| PHM 3; PzHdMi3 | Panzerhandmine, 3kg | 3 kg Magnetic mine A/T hollow charge |
| Pict; P | Pistole | Pistol |
| Pist Nahpatr | Pistolen Nahpatrone | Pistol cartridge, close range; low velocity pistol round |
| Pist Nahpatr 08 S | Pistolen Nahpatrone 08, Stahl | 9 mm Low velocity pistol round, pattern 1908, with steel bullet |
| Pist Patr 08; PPatr 08 | Pistolenpatrone 08 | 9 mm ball ammunition for pistol |
| PistPatr 08 mE | Pistolenpatrone 08 mit Eisenkern | 9 mm pistol round with iron core bullet; SAP pistol ammunition |
| PistPatr 08 mSE | Pistolenpatrone 08 mit Sinterkern | 9 mm pistol round with sintered iron bullet |
| PistPatr 08, St | Pistolenpatrone 08, Stahl | 9 mm pistol round, steel case |
| PivL | Pivotlafette | Pivot mounting; rotating mount (Arty) |
| PJ; PJäg | See PzJäg and Jgd Pz | |
| PJK; PJägK | See PzJägK | |
| PK; PKast | Pulverkasten | Ammunition box |
| PKpfw | See PzKpfw | |
| Pkw | See PzKw | |
| PL [such as in PLW 42 (Sf)] | [PL Werfer 42 (Selbstfahrlafette)] | Marking on a self-propelled rocket launcher |
| PIP | Plättchenpulver | Multiperforated disc propellant |
| PIP | Plattenpulver | Propellant in the form of circular discs without a central hole (used in mortars); rolled propellant; sheet propellant |
| PIPatr | Platzpatrone | Blank cartridge |
| PIPatrGer | Platzpatronengerät | See Vocabulary |
| PM; PulvMag | Pulvermagazin | Powder magazine; ammunition magazine |
| PmK; Ph mK | Phosphorgeschoß mit Stahlkern | AP-Inc bullet with phosphorus and a steel core |
| P-Mun; Pl-Mun | Platzpatronenmunition | Blank ammunition |
| Pol; Pol; POL | Pulver ohne Lösungsmittel | Solventless propellant (propellant produced without the use of a solvent) |
| Pom | Pommern | Pomerania |
| PP | Polizeipistole | Police pistol (such as Walther) |
| PPatr 08 | See PistPatr 08 | |
| PPK | Polizeipistole, Kriminal | Criminal detectives pistol (such as Walther) |
| Pr | Pressling | Pressed article; molding |
| Pr | Press-stahl | Pressed steel |
| Pr; PrS | Press-stoff | Thermosetting plastic; (lit Pressed material) |
| Pr | Protze | Limber (Arty), caisson |
| (Pr f 12 cm GrW 42) | (Protze für 12 cm Granatwerfer 42) | (Limber for 120 mm mortar pattern 42) |
| Prf; Prüf | Prüfung | Test examination; check |
| PrGesch | Phosphorgeschoß | Phosphorus projectile |
| PrGr; PrG | See PropGr | |

| | | |
|--|--|--|
| PtM | preussische Meile | Prussian mile (7.542 km) |
| Pz Mun | Phosphormunition | Phosphorus ammunition |
| Pto j | Projektile | Projectile |
| PropGr; Propgr; PzGr | Propagandagränate | Propaganda shell; leaflet rocket |
| Proz | Prozent | Per cent (%) |
| Prü | Presslingsumhüllung | Casing or jacket made of pressed material |
| Prüf | See Prüf; Prüf | |
| PzW | Propagandawerfer | Launcher for propaganda projectile |
| PS | Pferdestärke | Horsepower |
| PSGr; PzGr | See PzSGr | |
| PStz (such as in 21 cm PStz DO) | Pulverstütze (21 cm Pulverstütze DO) | Propellant support (Propellant support DO in 210 mm ammunition) |
| PSW | See PzSpW | |
| PT | Pulvertemperatur | Ammunition temperature |
| Pulv | See P; Pulv | |
| PulvFabr | Pulverfabrik | Powder factory |
| Pv | Pulver | Designation of slow-burning powder used in time-delay Fz |
| PvSt (such as in KZ. ZerPv St) | Pulver, Stahl (Konfzunder, Zerleger-Pulver, Stahl) | Powder (black), steel (Nose fuze self-destroying black powder unit, steel body) |
| Pwg | See PzWg | |
| PWM | See PzWuMi | |
| Pz-32 | | |
| <hr/> | | |
| Pyr | Pyrotechniker | Artificer (Military). See Feuerwerker |
| Pz | Panzer | Tank; armor; armored vehicle |
| PzAbt(F) | Panzerabteilung (Flammenwerfer) | Armored flame-thrower detachment |
| PzAbwAbt | Panzerabwehrabteilung | Antitank battalion |
| PzB | Panzerbüchse; Panzerabwehrbüchse | Antitank rifle |
| PzBefWg; gpBefWg | Panzerbefehlswagen; gepanzerter Befehlswagen | Commander's armored vehicle |
| PzBeoWg | Panzerbeobachtungswagen | Armored vehicle used for artillery spotting |
| PzF | Panzerfaust | A/T shaped charge missile |
| PzF 60 | Panzerfaust 60 | Hand operated grenade launcher A/T, 60 (weight 93 lb) |
| PzF (kl) | Panzerfaust (klein) | Small hand operated grenade launcher, A/T (weight 51 lb) |
| PzFuWg | Panzerfunkwagen | Armored radio car |
| Pzgr; PzGr | Panzergranate | Solid AP projectile |
| Pzgr 39 | Panzergranate 39 | APC BC HE (armor-piercing capped, ballistic cap, high explosive) shell, type 39 |
| Pzgr 40 | Panzergranate 40 | AP shell with a tungsten carbide core, type 40 |
| Pzgr 41 | Panzergranate 41 | AP shell with a tungsten carbide core for tapered bore gun, type 41 |
| Pzgr Patr (2.8 cm Pzgr Patr 41) | Panzergranate Patrone (2.8 cm Panzergranate Patrone 41) | Antitank projectile in fixed ammunition (28 mm AP shell for 28/20 mm Tapered Bore Gun called SPBu 41) |
| Pzgr Patr L'spur (Ra) | Panzergranate Patrone Leuchtspur (Reizstoff) | AP-T fixed round containing a charge of irritant |
| PzGr(W) | Panzergranate (Weicheisen) | Antitank shell, soft iron |
| PzJäg; PzJg; PJ; Pjäg | Panzerjäger | Tank destroyer (lit Tank hunter) (See also jgdPz) |
| PzJgK; PJK; PzJK | Panzerjägerkanone | A/T gun (lit Tank hunter's gun) |
| PzK (such as in KG 15 PzK) | Panzerkopf (Kanone-Granate 15 mit Panzerkopf) | Armor-piercing cap (Cannon shell 15 with AP cap) |
| PzKpfw; Pz; PzKpfWg (See also Panzer in the descriptive part) | Panzerkampfwagen | See Vocabulary |
| PzKw; Pkw | Panzerkraftwagen | Armored motor car |
| PzMi 43 | Panzermine 43 | Magnetic A/T mine 43 |
| PzSf; PzSfl | Panzer-Selbstfahrlafette | Armored self-propelled gun mount |
| PzSGr; PSGr; PzGr | Panzerstahlgranate | Steel armor-piercing shell (with small HE content) |
| PzSprGr; PzSprgr | Panzer sprenggranate | Antitank-high explosive shell |
| PzSpWg; PSW; PSpW; PSPW | Panzer spähwagen | Armored reconnaissance car; armored scout vehicle |
| PzT | Panzerturn | Turret of a tank |
| PzWg; PwG | Panzerwagen | Armored combat vehicle |
| PzWff | Panzerwaffe | Armored troops; tank troops |
| PzWK; PzWkpr | Panzerwurfskörper | Hollow charge A/T projectile fired from signal pistol |
| PzWK 42 LP | Panzerwurfskörper 42 für Leuchtpistole | Hollow charge A/T projectile pattern 42 fired from 23 mm signal pistol |
| PzWuMi; PWM; PzWM | Panzerwurfmine | Hollow charge A/T grenade or mine |

Q: QuBel
qcm
Qmstr; QuM
Qu

Querschnittsbelastung
Quadratzenimeter
Quartiermeister
Querschnitt

Q

R

R, Rak
R
R; Ro
R; Ro
R; RP
R
r; rd
R
(r); russ
R8; R11, etc (black sten-
cilling)

Rakete
Rauchentwickler
Rohr
Röhre
Röhrenpulver
Rückstosslander
rund
Rundkopfgeschoss
russisch
Rauchentwickler Nr 8, Nr 11, etc

R-3
Rad
RadfAbt; RdfAbt
RAG (in rocket launcher
designation 21 cm RAz M42)
Raup; Rp
RaupFzg; RpFzg
RaupSchl; RpSchl
RAZ 51

Rheintochter 3
Radio
Radfahrabteilung
Raketen Ag
(21 cm Raketen Ag M42)
Raupe
Raupenfahrzeug
Raupenschlepper
Raketenaufschlagzünder 51

rBattr
RbIF
R-Boot
R BS (such as
R 100 BS

reitende Batterie
Rundblickfernrohr
Räumboot; Minenräumer

(Rakete 100 BS)

RbZdh
Rcklf
Rd
Rd
Rdf
RDg; RDG (such as
8.6 cm RDg 1000)

See RZdh
Rücklauf
See Radf
Reinsdorf
See Radf
Raketendrahtgerät
(8.6 cm Raketendrahtgerät 1000)

Rdr
Rdr
RDZ
Rev
RevK
REW
Rf; R-frei
RF

Rechtsdrill
Reichdruckerei
Randdüsenzünder
Revolver
Revolverkanone
Rauchentwickler
Rohrfrei
Rundfunk
Rückstossfrei; Rücklauflos
(7.5 cm Rückstossfrei Kanone 43)

Rf (such as
7.5 cm RfK 43)

Rückstossfreiekanone
See under Warplants (descriptive section)

RfK; RfK
RFR
RfW
Rg
RgK
RgP

Rückstossfreier Werfer
Ring
See RK
Ringpulver

RGr
RGr
RgStz (such as
DOV RgStz 15)
Rh

Raketengranate
Rauchgranate
Ringstütze

Rhein

Querschnittsbelastung
Quadratzenimeter
Quartiermeister
Querschnitt

Rakete
Smoke generator
Barrel (Gun pipe; tube)
Radio tube; nozzle
Tubular propellant
Recoil-operated gun
round
Round-headed projectile
Russian (marking on equipment)
Shell containing smoke generator No 8, No 11, etc

Daughter of the Rhein 3 (radio controlled AA rocket)
Radio (See also RF)

Bicycle detachment
Designation of a single-barreled launcher for 21 cm
RLg Rocket (TM 9-1985-2, p 259)

Caterpillar track
Full-track vehicle
Caterpillar tractor
Rocket percussion fuze, screwed directly into the
nose of the warhead (TM 9-1985-2, p 235)

Mounted battery
Panoramic telescope
Mine sweeper
Marking on an air-to-air incendiary rocket equipped with
"Oberon Geräte" (TM 9-1985-2, p 255)

Recoil (of weapons)

Reinsdorf Plant (See under Warplants in descriptive section)

Rocket wire barrage (86 mm rocket contg a parachute suspended
spool of wire with no explosive attached (TM 9-1985-2, p 240)

Clockwise rifling (Weapons)
Government Printing Office
Rimvent fuze (Ammo) (See cIRDZ)

Revolver
Revolver gun
Smoke generator
Empty gun barrel
Radio; broadcasting
Recoilless (75 mm Recoilless cannon, pattern 43)

Recoilless gun (See also DüW)

Recoilless launcher
Ring

Flat ring (washer) type propellant (used in some howitzers
and mortars)

Rocket-assisted projectile
Smoke shell

Ring on tripod support

Rhein (river)

| | | |
|---|---|--|
| Rh; Rhm | See under Warplants in descriptive part | Marking on the PD fuze 150 manuf'd by the Rheinmetall Co (TM 9-1985-3, p 564) |
| RhS (in fuze designation such as AZ 150 RhS) | Rheinmetall S (Aufschlagzünder 150 Rheinmetall S) | Department of the Interior |
| Ri | Reichs Innen Ministerium | Captain (cavalry) |
| Rit | Rittmeister | Smoke filler (Ammo); smoke-puff charge (simulated fire) |
| RK | Rauchkörper | Built-up gun barrel; jacketed gun |
| RK. . . K | Ringkanone | Tubular gun carriage |
| RK | Rohrkarte | Smoke puff charge for observation purposes (such as in maneuvers) |
| RKfB | Rauchkörper für Beobachtungszwecke | See in Vocabulary |
| RKfS | Rauchkörper für Schiedsrichter | Wheeled gun carriage |
| Rl | Radlafette | Tubular gun carriage |
| Rl. . . Pl. . . | Röhrenlafette | Rocket flare device |
| RLG; RLg | Raketen Leuchtgerät | [210 mm Rocket containing a parachute suspended flare (TM 9-1985-2, pp 258-9)] |
| (21 cm RLg) | (21 cm Raketen Leuchtgerät) | Rocket illuminant simulating device |
| RLGS | Raketen Leuchtgerät Scheingeschoss | Air Force Ministry |
| RLM | Reichsluftfahrtministerium | See in Vocabulary |
| RM | Reichsmark | Rumanian (marking on equipment) |
| Rm | Rumänisch | Cross bar mine |
| RM | Riegelmine | A/T mine 43 described in TM 9-1985-2, p 272) |
| Rm. . . | (Riegelmine 43) | Rimless cartridge case of SA ball ammo |
| R-Mun | Rillenmunition | Name of metallurgical plant in Saar |
| R. . . such in | Röchling | (210 mm Röchling Anticoncrete Projectile) |
| (21 cm Röchling) | (1 cm Röchlingsgranate, Beton) | Recoil brake (Arty) |
| Rohbr | Rohrbremse | HE shell giving red smoke burst |
| Kof (black stencil) g) | Rohr | |
| Rp | Rohrpulver | Propellant in the form of long tubes (Usual form of German cannon propellant) |
| RP 12 | Rohrpulver 12 | Tubular NG propellant of calorific value 950 kcal/kg used in Naval guns since about 1912 |
| RP 32 | Rohrpulver 32 | Tubular NG propellant of cal value 820 kcal/kg which replaced RP 12 in Naval guns |
| RP | Rohrpulver 38 | Tubular DEGDN propellant of calorific value 820 kcal/kg which replaced RP 32 |
| RP 39 | Rohrpulver 39 Nitronaphthalin | Same as above but it contained α -nitronaphthalene |
| RP 40 | Rohrpulver 40 | Tubular DEGDN-NC propellant which superseded RP 38 in Naval guns. Its calorific value varied between 690 and 730 kcal/kg |
| RP 40 N | Rohrpulver 40 Nitronaphthalin | Same as above but containing α -nitronaphthalene |
| Note: None of the RP 40 propellants contained potassium salts | | |
| R-Patr | Rauchpatrone | Smoke signal cartridge |
| RPC 12 | Rohrpulver Konstruktion 12 | Tubular propellant used in Naval guns type 1912 |
| RPC 32 | See Rohrpulver C7 (descriptive section) | |
| RPE (P) | Rohrpulver (Einheit) pulver | Standard tubular propellant (See also RP) |
| RZb | Raketenpanzerbüchse | A/T rocket launcher |
| (8.6 cm RZb 434) | (8.6 cm Raketenpanzerbüchse 4) | 98 mm A/T rocket launcher type 34, called Panzerbrech |
| RZBGr | Raketen Panzerbuchse Granate | hollow charge rocket fired from A/T rifle |
| (8.6 cm RZBGr 432) | (8.6 cm Raketen Panzerbüchse Granate 432) | [88 mm HE HoC rocket, fin stabilized (TM 9-1985-2, pp 24-5)] |
| RZ | Raketenzünder | Rocket-assisted takeoff |
| RZ (black stencilling) | Reizstoff | Shell containing irritant filling, such as tear gas or lacrimator |
| Rst | Raketenstartbohrer | Rocket-assisted bomb |
| RSch-Schule | Reichs-See-Flugzeug-Schule | Reich Glider Construction School |
| RSpr | Raketensprenggranate | HE rocket shell |
| (8.6 cm RSpr L. 4.5 und L. 5.5) | (8.6 cm Raketensprenggranate L. 4.5 und L. 5.5) | [80 mm HE rocket propellant rockets 4.5 and 5.5 calibers long (TM 9-1985-2, pp 258-9)] |
| (8.6 cm RSpr 40 wsm) | (8.6 cm Raketensprenggranate Weismann) | 80 mm Naval HE rocket fin stabilized, Weismann (TM 9-1985-2, p 340) |
| RSSG | Raketen Scheinrauchgerät | See signal simulating device |
| RtBattr | Rittmeister Batterie | See in Vocabulary |
| Rtm | See Rittm | |

| | | |
|--|---|---|
| Rü; Rüst | Rüstung | Armament; Equipment |
| Rüchl | Rücklauf | Recoil (of a gun) |
| (zum) | rumänisch | Romanian (marking on equipment) |
| (russ); (r) | russisch | Russian (marking on equipment) |
| RVfW | Raketen Vielfachwerfer | Multiple rocket launcher |
| RW | Raketenwerfer | Rocket launcher |
| (8.8 cm RW 43) | (8.8 cm Raketenwerfer 43) | (88 mm wheeled rocket launcher, called Püppchen) |
| R-Wagen | Rungenwagen | Heavy freight car (15 tons) |
| RWg | Rohrwagen | Barrel carriage |
| RZ | Raketenzünder | Rocket igniter (See also ERZ) |
| Rz | Kohrzerspringer | Barrel burster (Arty) |
| RZdh | Reibensündhütchen | Friction type cap |
| RZP | Roheisenzündpulver | Raw iron igniter powder (used in prepn of sintered iron items) |
| S | | |
| S | Säure | Acid |
| S; s | scharf | Live (Ammo) |
| S | Schrapnell | Shrapnel |
| s | schwehr | heavy |
| s (marked on a fuze) | schwer | Heavy fuze (for use in guns with high shell acceleration) |
| S; SL | Seelenlänge | Gun barrel length; tube length |
| S | Sekunde | Second (sec) |
| ..S/30 (in fuze designation) | Sekunden 30 | Time fuze with maximum running time of 30 sec |
| ..S/90/45 | Sekunden 90/45 | Time fuze with maximum running time of 45 sec modified to 90 sec |
| ..S/45-125 | Sekunden 45-125 | Time fuze with no setting possible below 45 sec, and with max running time of 125 sec. |
| S* | See Patr S* | |
| s; S | sicher | safe |
| (s) | spanisch | Spanish (marking on equipment) |
| S; S-Gesch | Spitzgeschoss | Pointed bullet with a flat base |
| S; SG; SGew | Seitengewehr | Bayonet (lit Side arm) |
| S-42 | Seitengewehr 42 | Bayonet, pattern 42 |
| S; St (such as Patr S) | Stahl (Patronenhülse Stahl) | Steel (such as steel cartridge) |
| S | Sud | South |
| SA; sA | schwere Artillerie | Heavy artillery, called in the U S A "medium artillery" |
| SA | schwere Abwurfbombe | High capacity bomb (Grossladungsbombe) (Loading factor up to 80%) |
| (SA 4000) | schwere Abwurfbombe 4000 | Designation of a 4000 kg high capacity bomb (TM 9-1985-2, pp 43-4) |
| Säb | Säbel | Saber; sword |
| SB | Splitterbombe | Fragmentation (A/P) bomb |
| SB | Sprengbombe | Thinwalled high explosive bomb; demolition bomb (Loading factor up to 75%) |
| SB 400 (Kugel K) | Sprengbombe (Kugel B) | Spherical, hydrostatically operated, aircraft-laid, skip bomb, known in the U S A as Kurt Apparatus (TM 9-1985-2, p 14) |
| S Be (B) | Splitter Beton (Bombe) | Concrete fragmentation bomb |
| SBC (B); SBrc (B) | Sprengbrandcylindrische (Bombe) | HE-incendiary cylindrical bomb, contg either phosphorus or thermit (TM 9-1985-2, p 51) |
| SBe (B); SplBe (B) | Splitterbeton (Bombe) | Concrete fragmentation bomb (Loading factor about 30% HE) |
| Note: This bomb is one of the versions of SD | | |
| SC (B) | Sprengcylindrische (Bombe) | Thin walled HE-GP bomb; loading factor about 50% |
| (SC 1800 B) | (Sprengcylindrische 1800 kg Bombe) | [HE cylindrical bomb, known as "Satan" (TM 9-1985-2, p 12)] |
| Note: This type of bomb was also called "Minenbombe" | | |
| (SC 2500 B) | (Sprengcylindrische 2500 kg Bombe) | [HE cylindrical bomb, known as "Mex" (TM 9-1985-2, p 13)] |
| SCD (B) | Sprengcylindrisch-dickwandige Bombe | HE cylindrical, thick-walled bomb (Semi-armor-piercing bomb) |
| (SCD 1700 B) | (Sprengcylindrisch-dickwandige 1700 kg Bombe) | (1700 kg SAP bomb) |
| Sch | Schanze | Fieldwork; entrenchment |
| Sch | Scheinwerfer | Searchlight; highlight |
| Schlld | Schalldämpfer | Silencer; muffler |
| Schb | Scheibe | Target |
| Schbw | Schiessbaumwolle | Guncotton |

| | | |
|---|--|--|
| SchGrabK | Schützengrabkanone | Trench gun |
| Schiessb | Schiessbecher | Rifle grenade discharger (launcher) |
| Schiessb HlGr, 6.6 cm | 6.6 cm Schiessbecher Hohlladung Granate | 66 mm Hollow charge grenade launched from Schiessbecher |
| Schiessw | Schiesswesen | Ballistics; gunnery |
| Schles | Schlesien | Silesia |
| Schlgzdschr; sehlZ.Schr | Schlagzündschraube | Threaded percussion primer |
| SchW | Schleppwagen | Tow car (motor vehicle) |
| SchMi | See SchüM | |
| SchPIJ | Schiessplatz Jüterbog | Jüterbog Firing Range |
| SchPIK | Schiessplatz Kummersdorf | Kummersdorf Firing Range |
| Schr | Schrapnell | Shrapnel |
| Schr Mi | See S-Mi | |
| SchrPatr [such as: 6.5 cm | Schrapnellpatrone [6.5 cm Schrapnell | Shrapnel, fixed round (65 mm Yugoslav Shrapnel Fixed |
| SchrPatr 223 (j)] | Patrone (jugoslawisch)] | Round 223) |
| SchüMi; SchMi; Schümine; | Schützenmine | A/P land mine (See also SchrMi) |
| S-Mi | | |
| Schwpv | Schwarzpulver | Black powder |
| SD (B) | Spreng, dickwandige Bombe | HE thick-walled bomb (Loading factor 20-30%) |
| Note: This bomb was also called "Splitterbombe" (fragmentation bomb). | | It was SAP (semi-armor-piercing) |
| SDHL-B | Spreng, dickwandige (Hohlladung) Bombe | HE-HoC thick-walled bomb; SAP-HoC-A/T bomb |
| SD (k)-B | Spreng, dickwandige (klein) Bombe | Small HE thick-walled fragmentation bomb |
| SdKart | Sonderkartusche | Special propellant charge |
| SdKz | Sonderkraftfahrzeug | See in Vocabulary and under Panzer |
| SdKfz | Sprengdienst Kraftfahrzeug | Demolition service motor vehicle |
| (Goliath Sdkfz 302) | (Goliath Sprengdienst Kraftfahrzeug 302) | (Demolition service vehicle, carrying prepared charges of 50/50-RDX/TNT) (remote controlled) |
| SdrGesch | Sondergeschoss | Special projectile |
| SeeFlgz | Seeflugzeug | Seaplane; hydroplane |
| Sehr | Sehrohr | Periscope (submarine, tank); telescope |
| Sek; S | Sekunde | Second |
| SEL | See SELf | |
| SelbstLaf | See Sf; Sfl | |
| SELf; SEL | Selbstlade-Einstecklauf | Subcaliber barrel for automatic weapon |
| Sf; Sfl; SelbstLaf | Selbstfahrlafette | Self-propelled (SP) gun (lit Self propelled gun mount) |
| SF | Schutzfeder | See in vocabulary |
| sFH | schwere Feldhaubitze | Medium field howitzer |
| SFK | Schnellfeuerkanone | Rapid-fire cannon |
| SG | See S; SG; S-Gew | |
| SG 39 | Schmidting Gerät 39 | Schmidting device 39 (see descriptive part) |
| S-Ger | Sondergerät | Special purpose device |
| S-Gesch | See S; S-Gesch | |
| S-Gew | See S; Sg; S-Gew | |
| SgFl | Sgflieger | Glider |
| sGrW | schweres Granatwerfer | Heavy mortar |
| sHT | schwere Haubitze-in-Turm | Heavy howitzer for fortifications (lit Heavy howitzer in tower) |
| Si | Siebel | Designation of airplanes built by Siebel Co |
| sIG; SIG; sJG | schweres Infanteriegeschütz | Heavy infantry gun |
| SigP | Signalpistole | Signal pistol |
| SigR | Signalrakete | Signal rocket; flare |
| SigW | Signalwerfer | Signal flare projector |
| SiK (E) | Siefried Kanone (Eisenbahn) | Siegfried railroad cannon |
| sJG | See sIG | |
| sJgZ | schwerer Jägergranatzünder | Heavy fuze for light infantry shell |
| SK | Schiffskanone | Ship cannon |
| SK C/12 | Schiffskanone - Konstruktion 12 | Ship cannon type 1912 |
| SK L/45 | Schiffskanone - uflänge 45 | Ship cannon with barrel (tube) 45 calibers long |
| SK; SLK | Schnellfeuerkanone; Schnelladekanone | Rapid-fire gun; rapid-loading gun |
| Sk | Socket | Pedestal; swivel |
| S-Ker | Sonderkartusche | Special propelling charge (S-L Ammo) |
| SkL; SockLaf | Sockellafette | Pedestal mount |
| SL | See- und Landflugzeug | Amphibious plane |
| sLdgW | schwerer Ladungswerfer | Heavy spigot mortar |
| SLK | See SK; SLK | |

| | | |
|---|---|--|
| S-M | Seemile | Nautical mile; knot (1855 meters; 6080 feet) |
| sMg | schweres Maschinengewehr | Heavy machine gun |
| S-Mi; S-Mine | Schrapnellmine; Spreng- und Schrapnell Mine | Shrapnel mine; A/P mine filled with shrapnel balls; (nicknamed "silent soldier") |
| Note: Abbreviation S-Mi, was also used to designate a Schützenmine, | | usually abbreviated as SchüMi (q v) |
| SmE | Spitzgeschoss mit Eisenkern | Pointed bullet with iron core |
| S-MiZ-35 | Schützenminen Zünder 35 | Pressure type igniter used in A/P land mine 35 or in bounding mine (TM 9-1985-2, p 299) |
| S-MiZ-44 | Schützminen Zünder 44 | Push-pull type igniter used in A/P land mine 44 or in some improvised mines (TM 9-1985-2, p 294) |
| SmK | Spitzgeschoss mit Stahlkern | Pointed bullet with steel core (AP bullet) |
| SmKG1'spur | Spitzgeschoss mit Stahlkern und Glimmspur | Pointed bullet with steel core and dim tracer (AP-T bullet) |
| SmK(H) | Spitzgeschoss mit Stahlkern (gehartet) | Pointed bullet with hardened steel core (super AP bullet) |
| SmKL'spur | Spitzgeschoss mit Stahlkern und Leuchtspur | Pointed bullet with steel core and tracer (super AP-T bullet) |
| S-Mun | scharfe Munition | Live ammunition |
| S-Mun | Spitzmunition | Pointed ball ammunition |
| sMw | schwerer Minenwerfer | Heavy mortar |
| SO | Südosten | Southeast |
| SockLaf | See SkL | |
| sond; S | sonder | Special; separate |
| SondKart | Sonderkartusche | Special propellant charge |
| Sp; Spr | Spreng | Explosive |
| sPak | schwere Panzerabwehrkanone | Heavy A/T gun |
| SP (B); Spl (B) | Splitter (bombe) | Fragmentation bomb; antipersonnel (A/P) bomb |
| SF Be (B); Spl Be (B) | Splitterbeton (bombe) | Concrete fragmentation bomb |
| sPBu-41 | schwere Panzerbüchse 41 | Heavy tapered-bore gun |
| SpBr | See SpBr | |
| SpBü | See SpBü | |
| SP-Gesch | Spitzgeschoss | Pointed bullet |
| Sprgr; SprGr; SpGr | Sprgranate | A shell with tracer |
| SprgrZmK | Sprenggranatenzünder mit Klappensicherung | HE shell fuze with folding safety device |
| SPh | Spitzgeschoss, Phosphor | Pointed bullet with phosphorus |
| SpKps; SprK; SprKps | Sprengkapsel | Detonating cap |
| SplBo | Splitterbombe | Fragmentation bomb; splinter bomb |
| SplGr | Splittergranate | Fragmentation shell |
| SPr | See SP-Gesch | |
| Spr; Sp (such as in 28 cm Wfk Spr) | Spreng | High explosive |
| SprB; SprBo | (28 cm Wurfkörper Spreng) | (280 mm HE Rocket) |
| SprBr; SprBd | Sprengbombe | (High explosive bomb) |
| SprBü; SprB | Sprengbrand | HE-Inc filling |
| (SprBü 02/24) | Sprengbüchse | Demolition slab |
| Sprldg; SprLdg | (Sprengbüchse 02/24) | (Demolition slab, 1 kg TNT) |
| Sprgr; Sprgr Gr | Sprengladung | HF charge; demolition charge |
| Sprgr-41 | Sprenggranate; Granate | High explosive shell |
| Sprgr L (such as in 15 cm Sprgrl) | Sprenggranate 41 | HE shell for tapered bore gun |
| Sprgr mK | Sprenggranateladung | HE filling for shell |
| Sprgr Patr | (15 cm Sprenggranateladung) | (150 mm HE shell) |
| SprgrPatr KP | Sprenggranate mit Klappensicherung | HE shell with folding safety device |
| SprK | Sprenggranate Patrone | HE round of fixed ammunition |
| SprKab | Sprenggranate Patrone für Kampfpistole | HE grenade for rifled bore signal pistol, caliber 27 mm |
| SprKpr; SprK | See SpKps and SpKpr | |
| (SprK 68) | Sprengkabel | Blasting ignition cable |
| SprKps | Sprengkörper | Blasting charge; demolition charge |
| SprLdg | (Sprengkörper 68) | Prepared demolition charge, 200 g picric acid |
| SprPatr 28 | See SpKps | |
| SprSchwp | Sprengpatrone 28 | Demolition cartridge, 100 g TNT |
| SprSt | Sprengschwarzpulver | Blasting black powder |
| Sprzlaf | Sprengstoff | Explosive |
| S Pulver | Spreizlafette | Split-trail carriage |
| SPW; SPzWg | Pulver für scharfe Munition | Powder for live ammunition |
| sPzB; SPBu | Schützenpanzerwagen | See in Vocabulary |
| | schwere Panzerbüchse | Heavy A/T rifle |

| | | |
|----------------------------------|---|---|
| (2.8/2.0 cm SPzBü 41) | (2.8; 2.0 cm schwere Panzerbüchse 41) | (28/20 mm Tapered bore A/T rifle 41) |
| sPzKp/Wg | schwerer Panzerkampfwagen | Heavy tank |
| sPzSpWg | schwerer Panzerspähwagen | Heavy armored scouting (reconnaissance) car |
| SR | Schrohr | Periscope; telescope |
| Srk | Schraubkappe | Screw cap |
| sS | schweres Spitzgeschoss | Heavy pointed bullet with metal jacket; streamlined (boat tail) bullet |
| S S | Zeitschrift für das gesamte Schiess- und Sprengstoffwesen | Journal of Propellants and Explosives, now called Explosivstoffe |
| ss | schwerste; überschwere | heaviest; superheavy |
| ssa | schwerste Artillerie | Heaviest Artillery (corresponds to American Heavy Artillery) |
| sSmK | schweres Spitzgeschoss mit Kern | Heavy pointed bullet with core |
| St | Stahl | Steel |
| St | Stellstift; Stellschlüssel | Fuze setter; Fuze adjuster wrench |
| Stabo-B (such as in Sc 50 Stabo) | Stachelbombe (Sprengzylinderis: he Bombe 50 Stabo) | Nose spike (fuze extension rod) [HE cylindrical bomb having a one piece body with a threaded lug forged to the nose of the bomb and a spike (TM 9-1985-2, p 6)] |
| Stahlw | Stahlwerks | Steel works |
| Stb | Stab | Staff |
| StbP | Stäbchenpulver | Chopped tube propellant |
| StbP | Staubpulver | Finely granulated black powder |
| StB (B) | Stabbrandbombe | Stick type incendiary bomb |
| StMi | Strandmine | Beach mine; shore mine |
| Stg (black stencilling) | Stahlguss (granate) | Cast steel shell |
| Stg; Stggr | Stahlgeschoss; Stahlgussgranate | Light case shell of cast steel (TM 9-1985-3, p 349) |
| StHg; StHg; StGr | Steilhandgranate; Stielgranate | Stick hand grenade; rodded or potato masher hand grenade |
| StiGr | See Stbg | |
| StK | Stahlkern | Steel core |
| Stö | Stößel | Tappet; hammer (Fz) |
| Sto-Mi | Stockmine | A/P concrete picket type mine |
| Sto-Mi | Stolperdrahtmine | Trip-wire mine |
| StP | Sternpulver | Star propellant (flat 6 pointed stars) |
| StP | Streifenpulver | Strip propellant |
| StuA | Sturmartillerie | Assault artillery |
| StuG; StuGesch | Sturmgeschütz | Assault gun (self-propelled) |
| StuG -44 | Sturmgeschütz -44 | Stormtrooper's rifle (previously called MP-44) |
| StuH | Sturmhaubitze | Assault howitzer (self-propelled) |
| StuK | Sturmkanone | Assault cannon (self-propelled) |
| Stuka | Sturmkampfflugzeug | Dive fighter-bomber |
| St u StSr | Stößel und Stösselschraube | Tappet and tappet screw (Fz) |
| StZ | Stechzündler | Inserted igniter |
| Stzb | Sturzbomber | Dive bomber |
| StzSr | Stützschraube | Support screw |
| Sulfitri | Sulfitttrinitrotoluol | TNT purified by Na sulfite |
| SVA | See under Warplants, etc in descriptive part | |
| SW | Scheinwerfer | Searchlight |
| SW | Südwest | Southwest |
| sW | schwerer Werfer | Heavy smoke shell mortar |
| SwB [such as in SwB K5(E)] | Schwenkbahnbettung [Schwenkbahnbettung für Kanone 5 (Eisenbahn)] | Turntable platform [Turntable platform for railroad cannon 5] |
| sWG | schweres Wurfgerät (Werfergerät) | Heavy smoke mortar equipment |
| sWuR | schwere Wurfrahmen | Heavy framework-type rocket launcher |
| SZ; SZerl | Selbstzerleger | Self destruction charge (Proj) |

T

| | | |
|----------------------|--|---|
| T; Tk | Tank | Tank |
| T | Temperatur | Temperature |
| t; To | Tonne | Metric ton (1000 kg = 2205 lb) |
| T; Torp; Tp | Torpedo | Torpedo |
| T (marked on a fuze) | Trolitul | Fuze body, such as "WgrZ T" made of plastic material "Trolitul" |
| (t) | tatschecho-slowakisch | Czechoslovakian (marking on equipment) |
| T; Tu | Turm | Turret; tower |
| TAL | See under Warplants, etc in descriptive part | |

| | | |
|---------------------------------|---|--|
| FaschMin | Faschenmunition | Small arms ammunition in pouches |
| FATO | Tag-Tonne | Metric Tons per day |
| Fbt-K | Torpedoboots' Kanone | Torpedo boat's heavy gun |
| Teilkart | Teilkartusche | Partial propellant charge; increment charge |
| F-Falle | Tankfalle | Tank trap |
| TG | Turmgeschütz | Turret piece (gun) |
| TH | Turmhaubitze | Turret howitzer |
| ThBrK (E) | Theodor Bruno Kanone (Eisenbahn) | Theodor Bruno railroad cannon |
| ThK | Theodorkanone | Theodor cannon |
| Thür | Thüringen | Thuringia |
| Tk | See T; Tk | |
| TK | Turmkanone | Turret cannon |
| Tkst | Tankstelle | Filling station; gas station |
| T-Mi; TMI | Tellermine | Disk-type A/T mine (TM 9-1985-2, p 270) |
| TMIZ | Tellerminenzünder | Igniter for disc-type A/T mine |
| T Mun | T-Mun | Tank ammunition |
| TMZ-35, 42 and 43 | Tellerminenzünder, 35, 42 und 43 | Types of pressure igniters for use in various T-Minen and Pilz-Minen (TM 9-1985-2, pp 501-5) |
| To | See T; To | |
| ToMi | Topfmine | Pot-shaped land mine |
| Torp | See T; Torp | |
| TorpMotB | Torpedomotorboot | Torpedo motor boat |
| Tp | Transport | Transport |
| Tp (red or black stencilling) | Tropenmunition | Ammunition suitable for use in tropical climate |
| Tr; Trblgd | Treibladung | Propellant charge |
| TrMi (such as: KgTrMi 42) | Treibmine (Kugeltreibmine 42) | Floating (unanchored) automatic contact mine (spherical floating mine 42) |
| TS | Treibspiegel | See in Vocabulary |
| TS | Treibspiegelgeschoss | See in Vocabulary |
| TStz (such as 21 cm TStz DO-Wu) | | Meaning unknown to us |
| Tu; T | Turm | Turret; tower |
| TuMg; TMG | Turmmaschinengewehr | Turret or tower machine gun |
| TVA | See under Warplants (Descriptive section) | |
| U | | |
| u | und | and |
| (u) | ungarisch | Hungarian (marking on equipment) |
| U | Unterlafette | Bottom gun carriage |
| U (black stencilling) | Unterrichtsgeschoss | Instruction (practice or drill) projectile |
| U; U-Boot | Unterseeboot | U-boat; submarine |
| UA | Unterseebootsabwehr | Defense against submarines |
| Üb | Übung | Practice |
| Üb (white stencilling) | Übungsgeschoss | Practice projectile; shell containing black powder |
| ÜbAl | Übungsgeschoss mit Aluminium | Practice shell giving on burst a bright flash (due to the presence of Al) |
| ÜbB (white stencilling) | Übungsgeschoss B | Practice shell giving on burst a cloud of smoke (due to the presence of sulfur trioxide) |
| Übg; ÜbGr | Übungsgrenate | Practice shell; drill shell |
| ÜbMi | Übungsmine | Practice mine |
| ÜbR (white stencilling) | Übungsgeschoss, Rot | Practice shell giving red smoke burst |
| ÜbS | Übungsgeschoss, Schwarz | Practice shell giving black smoke on burst |
| ÜbSprK | Übungssprengkörper | Dummy blasting charge |
| ÜbW | Übungsgeschoss, Weiss | Practice shell giving white smoke on burst |
| Uffz | Unteroffizier | Noncommissioned officer, corporal |
| U ₆ /M; Umdr/M | Umdrehungen pro Minute | Revolutions per minute (rpm) |
| UKr | Übertragungs Körper | Induced detonation charge |
| UKW | Ultrakurzwellen | Ultrashort wave (Rad) |
| ÜLdg | Übertragungsladung | Propagation charge; primer charge |
| umg | umgearbeitet; umgeändert | reworked; converted; modified |
| (92 umg) | (92 umgeändert) | (1892 pattern converted) |
| uml | umlaboriert | equipped; outfitted |
| UtvK | | U-boat cannon (such as 149 mm) |
| UW | Uhrwerk | Clockwork mechanism (Fz) |

UW; UWZ

Uhrwerkzünder; Uhrzünder

Clockwork fuze

V

V
v
v; verb
V (such as
5 cm PzgrPatr 42 V)

Veränderung
verbessert
verboten
Verbundgeschoss
(5 cm Panzergranate Patrone Verbund-
geschoss)

Change; alteration; modification
improved
forbidden; prohibited
Compound (jacketed) projectile
(50 mm AP-T fixed round ammo, pattern 42 with
jacketed projectile)

v
V; Verg
V-1
V-2
V-3 or HDP
V (in fuze designation)
(1/V)
(2/N)
(0.05 Sek V)
VA, V₂A, etc

vereinfacht
Vergeltung
Vergeltungswaffe Eins
Vergeltungswaffe Zwei
Vergeltungswaffe Drei
Verzögerung
(Erste Verzögerung)
(Zweite Verzögerung)
(0.05 Sekunden Verzögerung)

simplified
Retaliation; reprisal; revenge
Retaliation weapon 1 (V-1) (See Descriptive part)
Retaliation weapon 2 (V-2) (See descriptive part)
Retaliation weapon 3 (V-3)
Delay
[First delay (short delay)]
[Second delay (long delay)]
(1/20th second delay)
Types of stainless steel, generally contg Ni, Cr, Mo
and used in German acid and explosives plants

VDM
Verf OKH

See under *Werplants* (descriptive section)
Verfügung des Oberkommandos des
Heeres

Army Regulations

Verg
Verh
verl A
Verrgl
Vers
Vers Anst
Vers Anst Hdfw
VersBt
VerschwLaf
verst; Vernt
VerzZ
vf
VG 1
Vierlg
vk; Vk (black stencilling)
Vkkh
vkl'spur
VLdg
VM-stoff
vnull; Vo; V-Null
Vorh
Vorkart

See V; Verg
Verhältnis
verlastete Artillerie
Verriegelung
Versager
Versuchsanstalt
Versuchsanstalt für Handfeuerwaffen
Versuchsboot
Verschwindlafette
verstärkt
Verzögerungszünder
vereinfacht
Volkssturmgewehr Eins
Vierling
verkürzt
Verkürztekammerhülse
verkürzte Leuchtspur
Verbessertladung
Victor Meyer Stoff
Velocitas-Null
Vorholer
Vorkartusche

Relation
Pack artillery
Locking mechanism (weapons); barricade
Misfire; dud
Experimental station; research laboratory
Experimental station for small arms
Experimental boat
Retractable gun mount
reinforced
Delay-action fuze
simplified
See in Vocabulary and under Weapons
See in Vocabulary
shortened
Shortened central tube (shrapnel)
Shortened tracer trail
Adjusted charge (lit Improved charge)
A camouflaged name for Mustard gas
Initial velocity; muzzle velocity (Proj)
Counterrecoil mechanism
Front increment charge in separate-loaded ammunition
(See also Teilkart)
Counterrecoil
Flash-reducing wad
formerly
Front; anterior (charge, etc)
Dummy round for vehicle loading practice
Tubular propellant cut into short lengths
Safety pin (bomb, mine, grenade); lug (fuze)
United States of America
Safety fuzing
Safety time (in fuzing)
Model designation (Czech fuzes)
Delay-action fuze
Safety fuze
"All-ways action" fuze described in TM 9-1985-2,
p 189; used in V-1 bomb

Vorl
Vorl
vorm
Vorn-; vorne
Vp; VpGesch
VRP
Vrst
VStA
VrzZ; Vz
VrzZt; VZt
Vz
VZ
VZ
VZ. 80

Vorlauf
Vorlage
vormals
Verpackungsgeschoss
verkürztes Röhrenpulver
Vorstecker
Vereinigte Staten von Amerika
Verzugszündung
Verzugszeit
Verzögerungszünder
Vorzugszünder
Verzögerungszünder 80

W

| | | |
|--|---|--|
| W | Wache | Guard; watch; sentinel |
| W; Wa | Waffen | Arms; weapons; ordnance |
| W | Offizier des Waffenwesens | Ordnance officer |
| W | Wagen | Wagon; vehicle |
| W (such as 2 cm SprgrPatr L'spur W) | Wärmeübertragung (2 cm Sprenggranate Patrone Leuchtspur Wärmeübertragung) | Heat transfer (20 mm HE-T fixed round self-destroying by heat generated by tracer) |
| W; Wehr.; Wm | Wehrmacht | Armed Forces |
| W (white stencilling) | Weicheisenkern | Soft iron core projectile |
| w | weiss | white |
| W; Werf; Wrf | Werfer | Shell mortar; launcher (rocket, signal) |
| W | West | West |
| W (in shell designation) | Wolfram | AP subcaliber shell with tungsten carbide core |
| Wa | See W, Wa | |
| WaA | Heeres-Waffenamt | Army Ordnance Office |
| Wab | Wasserbombe | Depth charge or bomb (lit Water bomb) |
| Waf | Forschungsabteilung des Heeres- waffenamts | Research Section of Army Ordnance Office (See also under Warplants, etc) |
| Wag | Wagen | Wagon; vehicle |
| WaPrüf | See under Warplants (descriptive section) | |
| WASAG | Westfälisch-Anhaltische Aktiengesell- schaft | Westphalian-Anhalt Stock Company |
| WC (such as in NC 50 WC) | (50 kg Nebelcylindrische Bombe WC) | Marking on a 50 kg cylindrical smoke bomb (TN 9-1985-2, pp 58-9) |
| WEM | Waffenentgiftungsmittel | Liquid preparation for decontamination of weapons |
| Werf | See W; Werf | |
| Wfgr | Werfergranate | Mortar shell; rocket |
| Wfk; WK; WrfK | Wurfkörper | Special projectile for signal pistol such as Véry pistol |
| Example: WK 361 LP (Wurfkörper 361 für Leuchtpistole) | | HE grenade (egg shape with stem) used for 26 mm signal pistol |
| Note: Abbreviation Wfk was used also to designate some rockets, such as 32 cm Wfk MF150, 28 cm WfkSpr and 30 cm WkSpr 42 (TM 9-1985-2, pp 251-254) | | |
| Wgr; WGr | Wurfgranate | Mortar shell; rocket |
| Wgr Grün | Wurfgranate, Grünring | Chemical rocket, such as 150 mm pattern 41, with green ring |
| Wgr Nb | Wurfgranate Nebel | Mortar smoke shell; smoke rocket, such as 150 mm |
| WgrPatr LP | Wurfgranate Patrone für Leuchtpistole | HE mortar round for signal pistol |
| Examples: 2.6 cm WgrPatr 326LP (26 mm HE round with percussion fuze, for signal pistol) and 2.6 cm WgrPatr LPmZZ (26 mm HE round with time fuze, for signal pistol) | | |
| WgrSpr | Wurfgranate Sprenggranate | HE mortar shell or HE rocket |
| Example: 15 cm Wgr 41 Spr (150 mm HE rocket, spin stabilized and 21 cm Wgr 42 Spr (210 mm HE spin stabilized rocket) (TM 9-1985-2, pp 245 and 249) | | |
| WgrZ; WZ | Wurfgranatenzünder | Mortar shell fuze |
| Note: According to TM 9-1985-3 (1953), p 545 the WgrZ is a fuze for infantry gun or howitzer | | |
| WgrZT | Wurfgranatenzünder, Trolitul | Mortar shell fuze with body made of polystyrene plastic material |
| WH | Wehrmacht-Heer | Armed Forces Army (marking on vehicles) |
| WIFO | See under Warplants (descriptive section) | |
| Wimp | Wimpel | Pennant; streamer |
| WiSp | Winkelspiegel | Periscoposcope (Tk); periscope |
| WK | See Wfk; WK; WrfK | |
| wKh (white stencilling) | weite Kammerhülse | Wide central flash tube (burst) |
| wKhNb | weite Kammerhülse, Nebel | Mortar smoke shell with solid filling and wide central flash tube |
| WL | Wehrmacht-Luftwaffe | Armed Force, Air Corps marking on vehicles |
| WL | See Wurfldg | |
| Wm | See W; Wehrm | |
| WM | Wehrmacht-Marine | Armed Forces, Navy (marking on vehicles) |
| WMZ | Wurfminezünder | Mortar shell fuze |
| Wn | Wiener-Neustadt | Designation of airplanes built by Wiener Neustädter Flugzeugwerke, Austria |
| WO | Waffenoffizier | Ordnance officer |
| WP | Wachposten | Sentry post |
| WP | Würfelpulver | Flaked propellant (in small rectangular tablets); dice shaped propellant |

| | | |
|-----------------------------|---|--|
| ZerlP; ZerlPv | Zerleger, Pulver | Black powder burning self-destruction element in fuze |
| ZerlPS; ZIPS | Zerleger, Pulversatz | Same as above |
| ZerlZ | Zerlegungszünder | Self-destroying fuze |
| zerspr | zersprengt | dispersed; scattered; blown up |
| Zerst | Zerstäuber | Spraying apparatus (CWS); sprayer; diffuser |
| Zers | See Z; Zerst | |
| Zerst | Zerstörung | Demolition; destruction |
| Zentr | Zertrümmerung | Demolition; destruction |
| ZF | Zielfernrohr | Telescopic sight (arms) |
| Zf | Ziffer | Cipher; numeral |
| zF | zu Fuss | afloat; on foot |
| AF-4 | Zielfernrohr 4-fach | Rifle sighting telescope, 4-power |
| ZF | Zwischenfrequenz | intermediate frequency (Rad) |
| Zf; ZF (such as in Zf Hbgr) | Zünder für Haubegränate | Marking on a point detonating fuze located under ballistic cap |
| Zg | See Z; Zg | |
| ZgA | See ZA; Za | |
| Zglls | Zeughaus | Arsenal; armory |
| ZielF | Zielferrohr | Telescopic sight |
| Zielgew | Zielgewehr | Subcaliber rifle (lit Target rifle) |
| Zielmun | Zielmunition | Subcaliber ammunition (lit Target ammunition) |
| Zit | Zitadelle | Citadel |
| Zk | Zündkerze | Spark plug |
| Zkw | Zugkraftwagen | Prime mover truck, tractor |
| Zl | Zinklegierung | Zinc alloy |
| ZL; ZdL | Zündlunte | Slow match; igniting cord; fuze igniter |
| ZL | Zwischenladung | Intermediate blasting charge (combat engineers) |
| ZLdg | See Zldg; ZLdg | |
| ZIPS | See ZerlPS | |
| ZM | Zugmaschine | Prime mover, tractor |
| ZmZ | Zünder mit Verzögerung | Delay-action fuze |
| Zn (marking on equipment) | Zink | Made of zinc |
| Zldg | See ZusLdg | |
| ZSnZ | See ZdschnANZ | |
| ZSprLdg | See ZusSprLdg | |
| ZSr | See Zdschr | |
| ZSrF H leHT | Zündschraubenfutter für die Hülse der leichten Haubitze-in-Turm | Bushing for threaded percussion primer for cartridge of light tower howitzer |
| ZStM | Zünderstellmaschine | Automatic fuze setter (AA Arty) |
| Zt | Zeit | Time; period |
| Ztschr | Zeitschrift | Periodical publication |
| ZtZ; ZZdr; ZZ | Zeitzündler | Time fuze (TiFz) |
| ZtZöscin | Zeitzündschau | Time safety fuze |
| ZuDZ; ZDz | See ZDZ | |
| Zus; Zu; Z | Zusatz | Addition; extension |
| ZusKart | Zusatzkartusche | Secondary propellant charge (in separate loaded ammo) |
| ZusLdg | Zusatzladung | Supplementary charge increment |
| ZusSprLdg | Zusatzsprengladung | Supplementary charge of HE |
| ZusZ 40 | Zusatzzünder 40 | Mechanical antiwithdrawal type fuze, pattern 40 (TM 9-1985-2, pp 177-8) |
| ZUW | Zünderuhrwerk | Clock mechanism fuze |
| ZuZZ-35 | Zug- und Zerschneidezünder-35 | Pull and tension wire release igniter used with S-Mine, some prepared charges and booby traps (TM 9-1985-2, p 290) |
| ZV | Zündervorrichtung | Austrian name for fuze |
| ZVer | Zeugverwaltung | Ordnance department administration |
| Zw; Zwill | Zwilling | See in Vocabulary |
| ZWB | See under Warplants (descriptive section) | |
| ZwL | Zwillingalafette | See Zwillingsgestell in Vocabulary |
| ZwMG; ZwillMG | Zwillingmaschinen-gewehr | See in Vocabulary |
| ZwSk 42; ZwillSk 42 | Zwillingsocket 42 | Twin gun swivel (pedestal) pattern 42 |
| ZwittFz | Zwitterfahrzeug | Half-track vehicle |
| Zyl | Zylinder | Cylinder |
| ZyIP | Zylinderpulver | Propellant in cylindrical grains |
| ZylVerschl | Zylinderverschluss | Cylinder locking; bolt action |
| ZZ | See ZtZ; ZZdr | |
| ZZ (such as ZZ 1505) | Zerlegungszünder 1505 | Self-destroying fuze, pattern 1505 |

DISTRIBUTION LIST

P. A. Technical Report Nr. 2510

| | <u>Copy Number</u> |
|--|--------------------|
| Commanding Officer Picatinny Arsenal Dover, New Jersey ATTN: Technical Information Section | 1 - 50 |
| Chief of Ordnance Dept of the Army Washington 25, D. C. ATTN: ORDGX-PNB | 51 |
| ORDGX-OTL | 52 |
| ORDGU-SE | 53 |
| ORDGU-IN | 54 |
| ORDIM | 55 - 56 |
| ORDIT | 57 - 58 |
| ORDTB | 59 - 60 |
| Armed Services Technical Information Agency Arlington Hall Station Arlington 12, Virginia | 61 - 71 |
| Commanding General Aberdeen Proving Ground Maryland | 72 - 76 |
| Commanding General Redstone Arsenal Huntsville, Alabama | 77 - 81 |
| Commanding Officer Detroit Arsenal Centerline, Michigan | 82 - 83 |
| Commanding Officer Diamond Ordnance Fuze Laboratory Connecticut Ave & Van Ness Street Washington 25, D. C. ATTN: ORDFL 06.33 | 84 - 85 |
| Commanding General Frankford Arsenal Bridge & Tacony Streets Philadelphia 37, Pennsylvania | 86 - 87 |
| Commanding Officer Holston Ordnance Works Kingsport, Tennessee | 88 - 89 |

Distribution List (cont'd)

| | <u>Copy Number</u> |
|---|--------------------|
| Commanding Officer Jefferson Proving Ground Madison, Indiana | 90 - 91 |
| Commanding Officer Office of Ordnance Research Box CM, Duke Station Durham, North Carolina | 92 - 93 |
| Commanding Officer Army Chemical Center Edgewood, Maryland | 94 - 98 |
| Commanding General Ordnance Ammunition Command Joliet, Illinois | 99 - 101 |
| Commanding General Ordnance Weapons Command Rock Island, Illinois | 102 - 104 |
| Commanding Officer Rock Island Arsenal Rock Island, Illinois | 105 - 106 |
| Commanding Officer Springfield Armory Springfield 1, Massachusetts | 107 - 108 |
| Commanding Officer Watertown Arsenal Watertown 72, Massachusetts | 109 - 110 |
| U. S. Military Academy West Point New York | 111 - 113 |
| Department of the Navy Office of Naval Research Washington 25, D. C. | 114 - 116 |
| Commander Naval Ordnance Laboratory White Oak Silver Spring, Maryland | 117 - 119 |

Distribution List (cont'd)

| | <u>Copy Number</u> |
|--|--------------------|
| Commander Naval Ordnance Test Station Inyokern China Lake, California | 120 - 122 |
| Commanding Officer U. S. Naval Powder Factory Indian Head, Maryland | 123 - 125 |
| Commander U.S. Naval Academy Annapolis, Maryland | 126 - 128 |
| Engineer Research & Development Laboratories Fort Belvoir Virginia | 129 - 133 |
| Solid Propellant Information Agency Johns Hopkins University Silver Spring, Maryland | 134 - 138 |
| Library of Congress Washington, D. C. | 139 - 140 |
| Commanding General Continental Army Command Headquarters Fort Monroe Virginia | 141 - 143 |
| Chief of the Bureau of Ordnance Dept of the Navy Washington 25, D. C. ATTN: ReU3a | 144 |
| Commander Naval Research Laboratory Washington, D. C. | 145 |
| U. S. Bureau of Mines Bruceton Pennsylvania | 146 - 147 |
| Asst Secretary of Defense (R&E) Director/Ordnance Washington 25, D. C. | 148 |

Distribution List (cont'd)

Copy Number

Office of Technical Services
Department of Commerce
Washington 25, D. C.

149

Ordnance Technical Intelligence Agency
Arlington Hall Station
Arlington 12, Virginia

*150 - 165

*To be issued to U. S. Military Attaches in NATO
Countries as per recommendation by the Office of
the Chief of Ordnance - REF: 3rd Ind, dated 7 May 1950.
OO/7-639 $\frac{1}{2}$, OO to PA.

NATO COUNTRIES

| | |
|---------------|--------------|
| Canada | Luxemburg |
| Iceland | Portugal |
| Norway | France |
| Great Britain | Italy |
| Netherlands | Greece |
| Denmark | Turkey |
| Belgium | West Germany |

| | | |
|---------|---|--------------------------------------|
| ZZ | Zugzünder | |
| Example | ZZ-35 (pull type igniter used with trip mines, booby traps and stock mines) (TM 3-40) | (pull or pressure type igniter used) |
| zZ | zur Zeit | at present, at this time |
| ZZS; Zz | Zünderzylinder | igniter extension cap |
| ZylP | Zylinderpulver | cylindrical powder |
| (Z) | Durchmesser | diameter |

Abbreviations } See at the end of previous section "Vocabulary of German Ordnance, Ammunition and Related Terms"

References }